

Application settings

From a monolithic to a modular architecture

S.Ducasse, L. Fabresse, G. Polito, and P. Tesone




Goals

- Think about **customizable** elements
- Think about modularity
- Study one real case: Preference in Squeak and Pharo



The case of Preferences



Challenges

- How to make sure that we can have
 - One application with **only its** preferences and its dependencies?
 - A **modular** definition of preferences?
- How do we make sure that
 - **domain** objects do **not** refer to preference objects and
 - still can offer preferences to the user?



Looking into the problem

Back in time in Squeak 3.8

- Preferences **was** a Facade (bad Design Pattern) managing preferences
- Preferences **class** was referenced 617 times
- Preferences **was** a huge dependency attractor
 - referring to many other subsystems (reading 3D files, RTF, PNG, Compiler....)



UI, Tools,... all referenced Preferences

```
MenuMorph >> initialize  
  super initialize.  
  bounds := 0@0 corner: 40@10.  
  self setDefaultParameters.  
  self listDirection: #topToBottom.  
  self hResizing: #shrinkWrap.  
  self vResizing: #shrinkWrap.  
  defaultTarget := nil.  
  selectedItem := nil.  
  stayUp := false.  
  popUpOwner := nil.  
  Preferences roundedMenuCorners ifTrue: [ self useRoundedCorners ]
```

UI, Tools,... all referenced Preferences

```
BasicButton >> label: aString font: aFontOrNil
```

```
| oldLabel m aFont |  
(oldLabel := self findA: StringMorph)  
  ifNotNil: [ oldLabel delete ].  
aFont := aFontOrNil ifNil: [ Preferences standardButtonFont ].  
m := StringMorph contents: aString font: aFont.  
self extent: (m width + 6) @ (m height + 6).  
m position: self center - (m extent // 2).  
self addMorph: m.  
m lock
```

Even core parts of the system

```
Class class >> templateForSubclassOf: priorClassName category: systemCategoryName
```

```
Preferences printAlternateSyntax
```

```
  ifTrue: [^ priorClassName asString, ' subclass (#NameOfSubclass)
instanceVariableNames (""')
classVariableNames (""')
poolDictionaries (""')
category ('', systemCategoryName asString, '')']
  ifFalse: [^ priorClassName asString, ' subclass: #NameOfSubclass
instanceVariableNames: ''
classVariableNames: ''
poolDictionaries: ''
category: '' , systemCategoryName asString, ''']
```



Even core parts of the system 2


```
InputSensor >> duplicateControlAndAltKeysChanged
```

```
(Preferences  
  valueOfFlag: #swapControlAndAltKeys  
  ifAbsent: [false]) ifTrue: [  
    self inform: 'Resetting swapControlAndAltKeys preference'.  
    (Preferences preferenceAt: #swapControlAndAltKeys) rawValue: false.  
  ].  
self installKeyDecodeTable.
```




Externalized and centralized flow of components

The octopus AntiPattern :(



Referencing an attractor: monolithic system



Analysis

- **Everybody** depends on Preferences
- Preferences is **not optional**
- Each time the Preferences class depends on a new item, all its **dependents are impacted**
- A clear **lost-lost**
- **Monolithic**



Facade and Singleton are against modularity

- A Facade should **rarely** be used
 - Propose a single entry point to a subsystem
 - Compiler is probably the only working example
- A Facade is often a disguised **global variable**!
- Singleton is most of the time not understood and correctly used (see Lectures on Singleton)





A new architecture

- A class **defines state / methods** that implement **its** customization points
- The class **declares** its settings via description
- The settings browser collects the **setting declaration** and builds a UI for the user
- The settings browser **configures** objects **using settings description**



Supporting Internal control flow

- Limiting external dependencies
- Reinforcing locality



Sound obvious but so true

- An object should **be designed to be customizable** without referring to external global objects
- Think about encapsulation
- The state of customization should be internal to the object



In Action: A class implements its customization points

```
JobProgressBarMorph >> isInterruptible  
  ^ self class isInterruptible
```

```
JobProgressBarMorph class >> isInterruptible  
  ^ IsInterruptible ifNil: [ IsInterruptible := true ]
```

```
JobProgressBarMorph >> addInterruptionButton  
  self isInterruptible ifFalse: [ ^ self ].  
  self addMorphBack: (self iconNamed: #stop) asMorph
```

- `IsInterruptible` is a state local to `JobProgressBarMorph`
- `JobProgressBarMorph` uses its own internal state to configure itself




In Action: Settings declaration using a Builder

```
JobProgressBarMorph class >> interruptionSetting: aBuilder
  <systemsettings>
  (aBuilder setting: #isInterruptable)
    label: 'Make progress bar interruptable';
    default: true;
    description: 'When enabled, add a button to progress bars to
    interrupt the action when clicked.';
    parent: #progress;
    target: self;
    order: 1
```


- Using a builder as parameter we avoid direct references to Settings classes
- Can be optionally packaged in another package if needed



In Action: Settings Browser



A layered and modular architecture



Analysis

Layered

- the domain does not depend on the setting framework
- Settings do not depend on Browser

Modular

- The domain can be loaded alone
- We don't have dependencies to unnecessary stuff



About customization

- An object should be **designed to be customisable**
- The logic flow should be **internal**
- The object logic should **not be tight to a preference object**
- The object customisation can be set from an external object (like the Setting browser)



Conclusion

- A good architecture should not promote global variable usage
- Avoid Singleton/Facade, these are anti-patterns
- Our theory is that Facade is only "useful" for Compiler :)
- Customization should first be internal



Produced as part of the course on <http://www.fun-mooc.fr>

Advanced Object-Oriented Design and Development with Pharo

A course by

S.Ducasse, L. Fabresse, G. Polito, and P. Tesone



Except where otherwise noted, this work is licensed under CC BY-NC-ND 3.0 France
<https://creativecommons.org/licenses/by-nc-nd/3.0/fr/>