

Decorator Design Pattern

A composable alternative to subclassing

S.Ducasse, L. Fabresse, G. Polito, and P. Tesone



Goals

- Present the Decorator Design Pattern
- Think about API




Decorator

From the book:


- **Dynamically** attach additional responsibilities to an object
- Decorators provide a flexible alternative to subclassing for extending functionality



Decorator core



Often mixed with inheritance



Decorator

A decorator wraps a decoree


- It is placed between the client and the decoree
- It propagates or not messages to the decoree

Easier to understand when the `Decorator` is a subclass of `Decoree` but not necessary (think duck typing)



Decorator nesting

A decorator wraps an instance or decorated instance of the component



Transparent to the client

- A client manipulates **transparently** decorated and undecorated elements
- A client talks to the decorator which **delegates** to the decoree (a leaf object or a another decorator)
- **Strong Implication:** decoree and decorator **must** expose the same API



Example of Stream

ZnStreams are decorators of Streams

ZnNewLineWriterStream

on: (ZnCharacterWriteStream on: Stdio stdout encoding: 'utf8').

- ZnNewLineWriterStream **decorates** ZnCharacterWriteStream



Another use

```
AbstractFileReference >> readStreamEncoded: anEncoding
```

```
  ^ ZnCharacterReadStream  
    on: self binaryReadStream  
    encoding: anEncoding
```

- ZnCharacterReadStream is decorating another stream with an encoding



Implementation

```
WriteStream << #ZnNewLineWriterStream  
  slots: { #stream . #cr . #lf . #previous . #lineEnding};  
  package: 'Zinc-Character-Encoding-Core'
```

```
ZnNewLineWriterStream class >> on: aStream  
  ^ self basicNew  
    initialize;  
    stream: aStream;  
    yourself
```

```
ZnNewLineWriterStream >> close  
  stream close
```

```
ZnNewLineWriterStream >> flush  
  ^ stream flush
```

Example of Stream (I)

testNextPutEnsureLineEndsAreWrittenCorrectly

```
| expectedString stream crStream |  
expectedString := 'a', OSPlatform current lineEnding, 'b'.  
{ String cr . String lf . String crlf } do: [ :lineEnd |  
    stream := String new writeStream.  
    crStream := ZnNewLineWriterStream on: stream.  
    crStream  
        << 'a';  
        << lineEnd;  
        << 'b'.  
    self assert: stream contents equals: expectedString ]
```



Example of Stream (II)

```
ZnNewLineWriterStream >> nextPut: aCharacter
```

```
"Write aCharacter to the receivers stream.
```

```
Convert all line end combinations, i.e cr, lf, crlf, to the platform convention"
```

```
(previous == cr and: [ aCharacter == lf ]) ifFalse: [
```

```
  (aCharacter == cr or: [ aCharacter == lf ])
```

```
    ifTrue: [ self newLine ]
```

```
    ifFalse: [ stream nextPut: aCharacter ] ].
```

```
previous := aCharacter.
```



Analysis

- All decorators should have the same API
- close, flush, nextPut:, contents, next, atEnd, on:
- Stream decorator individual behavior can be reused and composed



About dynamic behavior

Decorators attach additional responsibilities to an object

- The decorator is based on delegation
- We should control the creation of the decoration chain (the client reference)
- **Strong Implication:** decorated objects **do not know** if they are decorated
 - Changing the decoration chain at runtime is not simple



When not to use decorator

- When decorations have different APIs
- When the decorations should change dynamically
- Think twice when the APIs are HUGE



Conclusion

- Decorators can represent composable facets of an object
- Pay attention all the decorators should implement the same API
- Decorator is modular but within a common API



Produced as part of the course on <http://www.fun-mooc.fr>

Advanced Object-Oriented Design and Development with Pharo

A course by

S.Ducasse, L. Fabresse, G. Polito, and P. Tesone



Except where otherwise noted, this work is licensed under CC BY-NC-ND 3.0 France
<https://creativecommons.org/licenses/by-nc-nd/3.0/fr/>