Verify Form Data | Export Form Data | Import Form Data

EMVCo	***Level 2 – EMV® KERNEL Implementation Conformance Statement Version 4.4c***

ICS Reference Number and Validity Period (for EMVCo administrative use only)	
ICS Reference Number:	
Valid from:	
Valid to:	

Notice: ***This ICS form shall be completed for products submitted to receive EMVCo Level 2 testing and approval. The form shall be completed in its entirety.***

Part I - Administrative		
Product Provider Identification		
	Company Legal Name: (As listed on the Letter of Registration)	
	EMVCo Registration Number:	
Laboratory Identification		
	Company Legal Name:	
	EMVCo Registration Number:	
ICS Submission Type		
	Select submission type	<Select>
	For any submission except Initial, please provide the approval number of the Baseline configuration (cf Config '1C' on the letter of approval, if already approved)	
	Is this ICS a replacement of a previously accepted ICS?	☐ Yes ☐ No
	If Yes, please provide the reference number of the previously accepted ICS	
	If Yes, please provide the reason for replacing the ICS	<Select>
	If Yes, please provide details of ICS replacement	

Copyright ©2025 EMVCo, LLC. All rights reserved.

If EMVCo approval is issued, the EMV Kernel identification information provided in Part II is utilized on the EMVCo approval notification and posted on the EMVCo website. This identification information must agree with the information provided on the approval request letter and test results submitted for EMVCo evaluation. Inconsistent identification information in these three documents may delay the approval process or may result in a decline for the approval request.

If submitting a Configurable Kernel for type approval, then all ***configurable options*** must be defined in Parts II through V. These ***configurable options*** must show all values supported. Part VI is required to specify the vendor defined configurations of these options.

If submitting multiple PIN pads for approval under the PIN Pad Change process, section IIb must be completed for each PIN Pad. Any PIN pad identified in section IIa will serve as the baseline for this process.

Copyright ©2025 EMVCo, LLC. All rights reserved.

PART IIa – Product Identification

EMV Kernel Name This is the name of the overall EMV Kernel whether the Kernel is split in several submodules or in a single module. In case the Kernel is in a single physical location, the EMV Kernel Name maybe the same as Kernel Name below (first line of 'as tested in')	
EMV Kernel Version:	
EMV Kernel Java runtime machine Name (only in Case that the Kernel run on a JVM):	
EMV Kernel Java runtime machine Version (only in Case that the Kernel run on a JVM):	

Device/Terminal(s) Name within which the EMV Kernel will be tested (referred to 'As tested in' Name):

The EMV Kernel may be contained within a single physical location, module, or library in which case the entries above must be complete. However, when the EMV Kernel is split across several physical component devices (e.g.: server, mobile etc.), All hardware components must be fully described below (Only first line if a single location, multiple lines if multiple locations):

Note: If PIN Pad contains Kernel functions (such as PIN management), it shall be described below and in section 'Part IIb - PIN Pad Identification'

Device / Terminal HW Name	Type of Device	Kernel Name (or sub-kernel if multiple location)	Kernel Version (or sub-kernel if multiple location)	Kernel Checksum (or sub-kernel if multiple location)	OS Name (or sub-OS if multiple location)	OS version (or sub-OS if multiple location)
	<Select>					
	<Select>					
	<Select>					
	<Select>					
	<Select>					
	<Select>					

IFM (Level 1) Approval Reference[1]	

Please identify the Device / Terminal within which the EMV Kernel will be tested, for information purposes only (multiple tick possible):

Standard POS	
Standard POS with PIN Pad	
ATM	
Cash Register based Solution	
PC based Solution	
mPOS / Phablet	

[1] When supporting the PIN Change Process the IFM Approval Reference may vary for some PIN pads, if so these references must be identified in section IIb.

Copyright ©2025 EMVCo, LLC. All rights reserved.

Tablet	
Merchant Server Solution (closed environment)	
Cloud based Solution (open environment)	
Others	
If the answer to the above question is Yes for "others", please describe the device/terminal with in which kernel is tested	
Is Device / Terminal within which the EMV Kernel will be tested PCI-PTS approved (For information purpose only)?	
If the answer to the previous question is yes, please provide the PCI-PTS Certificate reference	
Are Device / Terminal(s) within which the EMV Kernel is tested present in the Laboratory (Devices maybe not present ONLY for ATM or Petrol Station or Cloud or Server based Solutions)	
If the answer to the above question is "No", are the Device / Terminal(s) following the Solution 1 (as per Administrative Process section 4.2.4)? **(If the answer is 'No' the Laboratory shall request the EMVCo Acceptance before starting any test)**	
If the answer to the two above question is "No", please describe why the ATM or Petrol Station or Cloud or Server based Solutions cannot be located in the Laboratory premises	
If the Device / Terminal within which the EMV Kernel is tested is NOT present in the Laboratory, Product Provider understand he has to comply with the Sample retention described in the Administrative Process Section 4.2.4.	

Copyright ©2025 EMVCo, LLC. All rights reserved.

PART IIb – PIN Pad Identification	
If the PIN is supported, is the PIN Pad transparent?	☐ Yes ☐ No
If the PIN Pad is transparent, please confirm you provided the requested transparency information as per Administrative Process section 2.7.7	☐ Yes

The tables below shall be used to describe all PIN pads, including those defined in part IIa.
- If a single PIN Pad is supported it must be described in the first Table below. Section VII, first line must also be filled.
- In case the PIN Pad is the same device as the Device/terminal within which the Application Kernel will be tested (a single box), it must be described in the first Table below (copy from section IIa the 'Device/terminal Name' into the section IIb ' PIN Pad “Marketing name”).

- For PIN Pad Change Process; the minimum number of PIN pads that must be supported is 1, there is no maximum number of PIN pads that may be submitted for the PIN Pad Change Process. If more PIN pads are submitted than space allows, an additional ICS Part IIb must be provided.
- If PIN Pad is supported the question ‘is the Terminal equipped with a PIN Pad’ of section V and VII shall be answered with ‘yes’ (even if the PIN Pad is the same device as the Device/terminal within which the Application Kernel will be tested).
- If this ICS is a subsequent submission with additional PIN Pad(s), make sure to assign to each new PIN Pad a number that has not been used for another PIN Pad during the previous session(s).

Copyright ©2025 EMVCo, LLC. All rights reserved.

PIN Pad	<Select the PIN Pad unique nb.>
PIN Pad "Marketing name" which will be submitted with the application kernel.	
PIN Pad software name and version:	
If the PIN Pad is Non Transparent, are the EMV functionality limited to PIN processing? Please note: in order for the PIN Pad to be eligible for this process the only EMV functions that may reside on the PIN pad are those related to PIN processing.	
List all EMV PIN processing functions residing on the PIN pad (only for Non Transparent PIN pad):	
PIN Pad combined with an IFM?	
IFM (Level 1) approval reference, if combined with PIN pad:	
PIN Pad Checksum:	

PIN Pad	<Select the PIN Pad unique nb.>
PIN Pad "Marketing name" which will be submitted with the application kernel.	
PIN Pad software name and version:	
If the PIN Pad is Non Transparent, are the EMV functionality limited to PIN processing? Please note: in order for the PIN Pad to be eligible for this process the only EMV functions that may reside on the PIN pad are those related to PIN processing.	
List all EMV PIN processing functions residing on the PIN pad (only for Non Transparent PIN pad):	
PIN Pad combined with an IFM?	
IFM (Level 1) approval reference, if combined with PIN pad:	
PIN Pad Checksum:	

Copyright ©2025 EMVCo, LLC. All rights reserved.

EMV PIN Pad Identification	<Select the PIN Pad unique nb.>
PIN Pad "Marketing name" which will be submitted with the application kernel.	
PIN Pad software name and version:	
If the PIN Pad is Non Transparent, are the EMV functionality limited to PIN processing? Please note: in order for the PIN Pad to be eligible for this process the only EMV functions that may reside on the PIN pad are those related to PIN processing.	
List all EMV PIN processing functions residing on the PIN pad (only for Non Transparent PIN pad):	
PIN Pad combined with an IFM?	
IFM (Level 1) approval reference, if combined with PIN pad:	
PIN Pad Checksum:	

EMV PIN Pad Identification	<Select the PIN Pad unique nb.>
PIN Pad "Marketing name" which will be submitted with the application kernel.	
PIN Pad software name and version:	
If the PIN Pad is Non Transparent, are the EMV functionality limited to PIN processing? Please note: in order for the PIN Pad to be eligible for this process the only EMV functions that may reside on the PIN pad are those related to PIN processing.	
List all EMV PIN processing functions residing on the PIN pad (only for Non Transparent PIN pad):	
PIN Pad combined with an IFM?	
IFM (Level 1) approval reference, if combined with PIN pad:	
PIN Pad Checksum:	

Copyright ©2025 EMVCo, LLC. All rights reserved.

EMV PIN Pad Identification	<Select the PIN Pad unique nb.>
PIN Pad "Marketing name" which will be submitted with the application kernel.	
PIN Pad software name and version:	
If the PIN Pad is Non Transparent, are the EMV functionality limited to PIN processing? Please note: in order for the PIN Pad to be eligible for this process the only EMV functions that may reside on the PIN pad are those related to PIN processing.	
List all EMV PIN processing functions residing on the PIN pad (only for Non Transparent PIN pad):	
PIN Pad combined with an IFM?	
IFM (Level 1) approval reference, if combined with PIN pad:	
PIN Pad Checksum:	

EMV PIN Pad Identification	<Select the PIN Pad unique nb.>
PIN Pad "Marketing name" which will be submitted with the application kernel.	
PIN Pad software name and version:	
If the PIN Pad is Non Transparent, are the EMV functionality limited to PIN processing? Please note: in order for the PIN Pad to be eligible for this process the only EMV functions that may reside on the PIN pad are those related to PIN processing.	
List all EMV PIN processing functions residing on the PIN pad (only for Non Transparent PIN pad):	
PIN Pad combined with an IFM?	
IFM (Level 1) approval reference, if combined with PIN pad:	
PIN Pad Checksum:	

Copyright ©2025 EMVCo, LLC. All rights reserved.

PART IIc – Additional Operating System Identification

This section applies to the Multi OS process only

The tables below shall be used to describe the additional Operating Systems for the Multi OS process. When supporting the Multiple OS process indicate all EMV kernel operating systems and versions submitted for type approval at this time, in addition to the operating system defined in part IIa.

Additional Operating System Identification	
EMV Kernel Operating System Name:	
EMV Kernel Operating System Version:	
I confirm that for this additional operating system to apply, no recompilation or linkage for the kernel code is needed and the kernel checksum and/or PIN pad checksum does not change	

Additional Operating System Identification	
EMV Kernel Operating System Name:	
EMV Kernel Operating System Version:	
I confirm that for this additional operating system to apply, no recompilation or linkage for the kernel code is needed and the kernel checksum and/or PIN pad checksum does not change	

Additional Operating System Identification	
EMV Kernel Operating System Name:	
EMV Kernel Operating System Version:	
I confirm that for this additional operating system to apply, no recompilation or linkage for the kernel code is needed and the kernel checksum and/or PIN pad checksum does not change	

Additional Operating System Identification	
EMV Kernel Operating System Name:	
EMV Kernel Operating System Version:	
I confirm that for this additional operating system to apply, no recompilation or linkage for the kernel code is needed and the kernel checksum and/or PIN pad checksum does not change	

Copyright ©2025 EMVCo, LLC. All rights reserved.

PART III – Terminal Resident Data Objects		
	Value	**Configurable?**
Terminal Type: **(if configurable, list all supported values separated by a comma)** **Warning: All Terminal Type value supported for additional configuration shall be listed**	11 12 13 14 15 16 21 22 23 24 25 26 34 35 36	

PART IV – EMV Specifications	
EMV Specification Date & Version:	EMV Integrated Circuit Card Specifications for Payment Systems version 4.4, October 2022

Copyright ©2025 EMVCo, LLC. All rights reserved.

PART V – Terminal Details

	Terminal Capabilities	Value Supported
	Card Data Input Capability	
	Manual Key Entry	
	Magnetic Stripe	
	IC with Contacts	Yes
	CVM Capability	
	Plaintext PIN for ICC Verification	
	Enciphered PIN for online Verification	
	Signature	
	Enciphered PIN for offline Verification (RSA ODE)	
	No CVM Required	
	Enciphered PIN for offline Verification (ECC ODE)	No
	Does the Kernel support Biometric? If Yes: - The values in range 000110-001111 of the Book3, Table 39 - CVM Codes are considered as recognized values for unsupported Biometric CVM Codes - the Kernel implements the Biometric flow 'T' of the Book3, figure 9 - Biometric Data Objects as per Book3, Annex A1 are recognized by the Kernel, If no the kernel shall not support any Biometric requirements (the values in range 000110-001111 of the Book3, Table 39 - CVM Codes are considered as RFU)	
	If Biometric supported, does the Kernel support Finger biometric verified offline (by ICC)?	
	If Biometric supported, does the Kernel support Finger biometric verified online (by ICC)?	
	If Biometric supported, does the Kernel support Facial biometric verified offline (by ICC)? Note: This Biometric CVM is not supported for approval and testing in this version. In case your Product support it, please contact EMVCo	No
	If Biometric supported, does the Kernel support Facial biometric verified online (by ICC)? Note: This Biometric CVM is not supported for approval and testing in this version. In case your Product support it, please contact EMVCo	No
	If Biometric supported, does the Kernel support Palm biometric verified offline (by ICC)? Note: This Biometric CVM is not supported for approval and testing in this version. In case your Product support it, please contact EMVCo	No
	If Biometric supported, does the Kernel support Palm biometric verified online (by ICC)? Note: This Biometric CVM is not supported for approval and testing in this version. In case your Product support it, please contact EMVCo	No
	If Biometric supported, does the Kernel support Iris biometric verified offline (by ICC)? Note: This Biometric CVM is not supported for approval and testing in this version. In case your Product support it, please contact EMVCo	No

Copyright ©2025 EMVCo, LLC. All rights reserved.

	If Biometric supported, does the Kernel support Iris biometric verified online (by ICC)? Note: This Biometric CVM is not supported for approval and testing in this version. In case your Product support it, please contact EMVCo	No
	If Biometric supported, does the Kernel support Voice biometric verified offline (by ICC)? Note: This Biometric CVM is not supported for approval and testing in this version. In case your Product support it, please contact EMVCo	No
	If Biometric supported, does the Kernel support Voice biometric verified online (by ICC)? Note: This Biometric CVM is not supported for approval and testing in this version. In case your Product support it, please contact EMVCo	No
	If One of the Biometric CVM is supported, what is the Biometric Data Block Maximum Length supported?	
	Security Capability	
	Static **D**ata **A**uthentication **and** **D**ynamic **D**ata **A**uthentication (**Mandatory** for offline capable terminals)	
	Card Capture	
	Combined Dynamic Data Authentication / Application Cryptogram Generation (if CDA is supported it shall support one of the 4 modes described in EMV Book2)	
	Extended Data Authentication (XDA)	No

Copyright ©2025 EMVCo, LLC. All rights reserved.

	Additional Terminal Capabilities	Value Supported
	Transaction Type Capability At least one of the following transaction types must be supported:	
	Cash	
	Goods	
	Services	
	Cash Back	
	Inquiry	
	Transfer	
	Payment	
	Administrative	
	Cash Deposit	
	Terminal Data Input Capability	
	Does terminal have a keypad (If keypad is supported the terminal **shall** support one or more of the following key types:)	
	Numeric Keys	
	Alphabetic and Special Character Keys	
	Command Keys	
	Function Keys	
	Terminal Data Output Capability	
	Print, Attendant and/or Cardholder	
	Display, Attendant and/or Cardholder	
	Code Table 10	
	Code Table 9	
	Code Table 8	
	Code Table 7	
	Code Table 6	
	Code Table 5	
	Code Table 4	
	Code Table 3	
	Code Table 2	
	Code Table 1	

	Application Selection	Value Supported
	How Many AIDs with the associated set of data (such as TAC,…) can be supported by the Application Kernel? (if unlimited number please enter 99)	
	Support PSE selection Method	
	Support Cardholder Selection & Confirmation	
	Does the terminal have a preferred order of displaying applications	
	Does the terminal perform partial AID selection	Yes
	Does the terminal have multi language support	
	Does the terminal support the EMV Language Selection method	
	Does the terminal support the Common Character Set as defined in Annex B Table 20 Book 4	Yes

Copyright ©2025 EMVCo, LLC. All rights reserved.

	Selectable Kernel Configurations (MCK only)	Value Supported
	Is your Multi-Configuration Kernel capable of dynamically selecting a configuration at the time of transaction	

	Data Authentication	Value Supported
	During data authentication does the terminal check validity for revocation of Issuer Public Key Certificate	
	When supporting certificate revocation, what is the Certificate Revocation List format? (CRL format must include: RID, CA Public Key Index, Certificate Serial Number, and optional additional data)	
	Does the terminal contain a default DDOL (**Mandatory** for terminals supporting DDA)	

	Cardholder Verification Method	Value Supported
	Terminal supports bypass PIN Entry	
	If the terminal supports bypass PIN Entry: When selecting to bypass a PIN method, all other PIN entry methods are also considered bypassed.	
	Terminal supports Get Data for PIN Try Counter	
	Terminal supports Fail CVM	Yes
	Are amounts known before CVM processing	

Copyright ©2025 EMVCo, LLC. All rights reserved.

	Terminal Risk Management	Value Supported
	Floor limit checking (**Mandatory** for offline only terminals and offline terminals with online capability)	
	Random Transaction Selection (**Mandatory** for offline terminals with online capability, except when cardholder controlled)	
	Velocity Checking (**Mandatory** for offline only terminals and offline terminals with online capability)	
	Transaction Log	
	Exception File	
	Terminal Risk Management performed irrespective of AIP setting (expected behavior)	Yes

	Terminal Action Analysis	Value Supported
	Does the terminal support the Terminal Action Codes (If the answer is no, please contact EMVCo)	
	Can the Terminal Action Codes be deleted or disabled? If yes, the default TAC values of the TAC-Online, TAC-default and TAC-denial shall be set to zeroes	
	If Offline Only is supported, which option of the Offline Only Terminal processing is implemented? (according to Book3, section 10.7)	
	If Online Only is supported, how does online only terminal process TAC/IAC-Default when unable to go online?	

Copyright ©2025 EMVCo, LLC. All rights reserved.

	Completion Processing	Value Supported
	Transaction Forced Online Capability	
	Transaction Forced Acceptance Capability	
	Does the terminal support Issuer initiated Voice Referrals	
	Does the terminal support a Default TDOL	
	If a Default TDOL is supported, can this default TDOL be not configured (or not loaded) in the terminal	
	Is the Default TDOL TVR bit set before or after the 1st Generate AC Terminal Action Analysis? (Note: When applicable, the setting/unsetting of the Default TDOL TVR bit according to the Default TDOL usage is always performed prior to the 1st Generate AC. However this TVR bit only impacts the 1st Generate AC TAA if it is set before the 1st Generate AC TAA is performed)	

	Exception Handling	Value Supported
	What is the POS Entry Mode value when IC cannot be read and the transaction falls back using Magstripe	Configurable:

	Miscellaneous	Value Supported
	Is the terminal equipped with a PIN Pad (shall be answered 'yes' if Offline or online PIN is supported)	Yes
	Is the amount and PIN entered at the same keypad	
	Is the ICC/Magstripe Reader combined	
	Does the terminal support account type selection	
	Does the terminal support 'on fly' script processing (not recommended behavior)	
	Is the Issuer Script device limit greater than 128 bytes	
	If the Issuer Script device limit is greater than 128 bytes, what is the value supported *(If unlimited please enter 0)* ***Note**: if the kernel supports unlimited script length, a value of 400 bytes shall be used for testing purpose*	Configurable:
	Does the terminal support Internal Date Management *(If the terminal is capable of managing the increment of dates internally without synchronization or instruction from the host, 'Yes' should be selected for this option)*	
	Is the Level 2 Contact Kernel Random Generator using the algorithm described in Book2, section 11.3	
	If the Level 2 Contact Kernel Random Generator is not using the algorithm described in Book2, section 11.3, is this function PCI approved?	
	If the Level 2 Contact Kernel Random Generator is not using the algorithm described in Book2, section 11.3, describe the function (such as algorithm used, etc)	
	Is the Random Generator function of the Level 2 Contact Kernel Software dependent on the Terminal Hardware?	
	If answer to previous question is Yes, describe the Hardware (a clear description of the chipset is required)	
	Are the Cryptographic functions (RSA, Hash, etc.) of the Level 2 Contact Kernel Software dependent on the Terminal Hardware?	
	If answer to previous question is Yes, describe the Hardware (a clear description of the chipset is required)	
	Is any other functions of the Level 2 Contact Kernel Software dependent on the Terminal Hardware?	
	If answer to previous question is Yes, describe the functions and the Hardware (a clear description of the chipset is required)	

Copyright ©2025 EMVCo, LLC. All rights reserved.

	If the answer to at least one of the 6 previous questions is Yes, do you plan to port the Kernel to other Terminals having the same Hardware component supporting these above functions (Family of Terminal)?	
	Does the terminal support Receipt (by printing or any electronic means)?	
	List the Currency Code(s) supported as for ISO 4217: (one currency shall be declared at a minimum, and up to 10 if multiple currencies are supported with at least one per currency exponent supported) Note: Changing from one currency supported to multiple is considered as a major change	
	Does the terminal support the Application Selection Registered Proprietary Data (ASRPD)?	
	List the Language(s) supported as for ISO 639 (minimum one shall be declared, and up to 10 if Multiple Languages are supported)	
	Can the Kernel be configured so the data object 'Terminal Risk Management Data' '9F1D' is absent or configured with no value (00 is a value)?	
	Can the Transaction Sequence Counter (TSC) be personalized to any value?	
	If answer to previous question is Yes, what is the Maximun Value of the Transaction Sequence Counter?	

	Checksum	**Value Supported**
	Does the product comply with the Checksum rules as defined in Contact Terminal Level 2 administrative process	
	If answer to previous question is No, the following question must be checked Yes: - This is an Initial submission or Subsequent submission or renewal of the original approved product prior to the effective date of checksum rules (cf Terminal Type Approval Bulletin No. 134)	
	Configuration Checksum (Static Kernel only)	

Copyright ©2025 EMVCo, LLC. All rights reserved.

PART VI – Terminal Configurations

When supporting a configurable kernel, each type approval session is applied to a number of vendor defined configurations. The table below shall be used to describe these configurations. The minimum number of configurations that must be supported is 1, there is no maximum number of configurations that may be submitted for type approval. If more than 10 configurations are submitted for type approval an additional ICS must be provided, detailing the additional configurations in Part VI.

About Configuration unique numbers:
- The unique number of the Baseline configuration (Baseline is always the column 1) is 01.
- The Baseline configuration settings are always required in the ICS, whatever the submission (initial or subsequent submission). In case of Subsequent Submission, please copy the Baseline settings values submitted in the Initial Submission of this product.
- Baseline configuration shall be the configuration, submitted during initial configuration, with the highest weight.
- Please assign a unique number (02, 03, etc.) to each additional configuration listed in the table below.
- If this ICS concerns a Static Kernel, the table below is left empty. The unique number of the configuration is 01 by default;
- If this ICS is a subsequent submission with additional configuration(s), make sure to assign to each new configuration a number that has not been used for another configuration during the previous session(s).

Configuration unique nb.	01									
Identification										
Terminal Type										
Manual Key Entry										
Magnetic Stripe										
IC with Contacts	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Plaintext PIN										
Online Enciphered PIN										
Signature										
Offline Enciphered PIN (RSA)										
No CVM										
Offline Enciphered PIN (ECC)	No	No	No	No	No	No	No	No	No	No
Biometric										

Copyright ©2025 EMVCo, LLC. All rights reserved.

Configuration unique nb.	01									
Offline Finger										
Online Finger										
Offline Facial	No	No	No	No	No	No	No	No	No	No
Online Facial	No	No	No	No	No	No	No	No	No	No
Offline Palm	No	No	No	No	No	No	No	No	No	No
Online Palm	No	No	No	No	No	No	No	No	No	No
Offline Iris	No	No	No	No	No	No	No	No	No	No
Online Iris	No	No	No	No	No	No	No	No	No	No
Offline Voice	No	No	No	No	No	No	No	No	No	No
Online Voice	No	No	No	No	No	No	No	No	No	No
SDA and DDA										
Card Capture										
CDA										
XDA	No	No	No	No	No	No	No	No	No	No
Tran Type – Cash										
Tran Type – Goods										
Tran Type – Services										
Tran Type – Cash Back										
Tran Type - Inquiry										
Tran Type – Transfer										
Tran Type – Payment										
Tran Type – Administrative										
Tran Type – Cash Deposit										
Keypad										
Numeric Keys										

Copyright ©2025 EMVCo, LLC. All rights reserved.

Configuration unique nb.	01									
Alphabetic and Special Character Keys										
Command Keys										
Function Keys										
Print										
Display										
Code Table 10										
Code Table 9										
Code Table 8										
Code Table 7										
Code Table 6										
Code Table 5										
Code Table 4										
Code Table 3										
Code Table 2										
Code Table 1										
PSE										
Cardholder Confirmation										
Preferred display order?										
Partial AID Selection	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Multi language?										
EMV Language Selection method?										
Common Character Set	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Revocation of Issuer Public Key Certificate										
Certificate Revocation List Format										

Copyright ©2025 EMVCo, LLC. All rights reserved.

Configuration unique nb.	01									
Default DDOL										
Bypass PIN Entry										
Subsequent Bypass PIN Entry										
Get Data for PIN Try Counter										
Fail CVM	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Amount known before CVM processing										
Floor limit checking										
Random Transaction Selection										
Velocity Checking										
Transaction Log										
Exception File										
Terminal Risk Management irrespective of AIP setting	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Terminal Action Codes supported										
Terminal Action Codes can be deleted/or disabled										
Offline Only Terminal processing										

Copyright ©2025 EMVCo, LLC. All rights reserved.

Configuration unique nb.	01									
TAC/IAC-Default process when unable to go online										
Forced Online										
Forced Acceptance										
Voice Referrals initiated by Issuer										
Default TDOL										
Default TDOL not loaded										
POS Entry Mode										
Amount and PIN entered on the same keypad										
Is the ICC/Magstripe Reader combined?										
Does the terminal support account type selection?										
‘on fly’ script processing										
Is Issuer Script device limit > 128 bytes?										
If the Issuer Script device limit > 128 bytes, what is the value supported?										

Copyright ©2025 EMVCo, LLC. All rights reserved.

Configuration unique nb.	01									
Internal Date Management										
Does the terminal support Receipt?										
Configuration Checksum										
Total weight										

Copyright ©2025 EMVCo, LLC. All rights reserved.

PART VII – Supported Combination(s) of PIN Pads / Configurations

The table below shall be used to identify uniquely the supported Combinations of PIN Pads / Configurations.
- The PIN Pad Unique numbers refer to those assigned in Part IIb of the present ICS but also to Part IIb of ICS used for previous submission(s) of the same product (if any).
- The Configuration Unique numbers refer to those assigned in Part VI of the present ICS but also to Part VI of ICS used for previous submission(s) of the same product (if any).
- Information provided in this table shall be exhaustive and consistent with the information of the section VII in ICS of the previous submission(s) (if any), so if a previous submission was made the table below contain also the information of these combinations.

Supported combinations		Unique Configuration number (as per section VI)																																									
		01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
Unique PIN Pad number (as per section IIb)	01	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
	02	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
	03	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
	04	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
	05	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
	06	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
	07	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
	08	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
	09	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
	10	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐

Copyright ©2025 EMVCo, LLC. All rights reserved.

Part VIII - Digital Signatures	
Product Provider	
I hereby declare that the above referenced product currently is and will remain in compliance with the above referenced EMV specification for all mandatory and supported optional requirements.	
Comments	
Signature	

Laboratory	
I hereby declare that this ICS document has been reviewed, and that all product information is consistent throughout the ICS.	
Comments	
Signature	

EMVCo Approval Secretariat	
Signature	

Copyright ©2025 EMVCo, LLC. All rights reserved.