1.2.2 Access Point Specification

Danish Business Authority

Nemhandel eDelivery Access Point Specification version 1.2.2

Certificate validation

Requests made to a CRL, OCSP server or equivalent MAY be cached up to 24 hours.

Availability

The Access Point MUST maintain a timeout window (the period during which the service, once initiated, MUST NOT terminate due to lack of activity from the counterparty) of no less than 120 seconds.

The Access Point MUST maintain no less than 99.65 % uptime, on average over any 30 calendar day period. The service is deemed unavailable if it is not reachable for 10 continuous seconds, or for other reasons is not able to handle incoming messages or requests in a secure manner.

Logging

In order to comply with legislation concerning keeping of business records, all access points SHOULD keep logs of all messages transferred for at least 5 years, containing as a minimum:

- identity of sending party
- identity of receiving party
- identity of sending access point
- identity of receiving access point
- unique identifier of message
- business identifier of message, if known
- format of message (e.g. OIOUBL 2.1)
- type of message (e.g. OIOUBL Invoice 2.1)
- timestamp

Capabilities

The Access Point MUST be able to handle payloads up to 100 MB.

Notifications

The Access Point MUST publish a technical contact e-mail for incident reporting purposes. (Nemhandelsregisteret provides this for the Access Points). Incidents reported by other Nemhandel users MUST be acknowledged within 1 working day. Incidents that cannot be resolved within 5 working days MUST be reported to the Danish Business Authority's Nemhandel team (nemhandel@nemhandel.dk).