

Initialization

Identify yourself

bzr whoami "Name <e-mail>"

New project

bzr init-repo <REPO_URL>

New branch

cd myproject/mybranch

bzr init

bzr add

bzr acommit

bzr push <BNCH URL>

New branch, copy of an existing branch

bzr branch <BNCH1 URL> <BNCH2 URL>

Branch checkout

bzr checkout <BNCH_URL>

Merging

Update a checkout

bzr update

List conflicts

bzr conflicts

Resolve conflicts

bzr resolve <FILE>

bzr resolve –all

Merge current and another branch

bzr merge <BNCH URL>

bzr qcommit

File Manipulation

Add/"version" files

bzr gadd

Remove/"unversion" a file

bzr remove <FILE>

Move or rename a file

bzr move <FILE>

Version Control

Commit

bzr qcommit

Revert changes

bzr grevert

Undo last commit => NEVER USE IT

bzr uncommit

Variables

REPO URL: protocol://SERVER:PORT/REPOSITORY NAME/

protocol://SERVER:PORT/REPOSITORY NAME/BRANCH NAME/ BNCH_URL:

FILE: Windows or Linux file path **REV ID:** specific revision no => 1, 2, 3, 4, ...

relative revision no => last:1, last:2, last:3, ...

Concepts

Branch: line of development for a project Working tree: version controlled directory Repository: store for Bazaar revisions

Revision: version of the source code committed to the repository

Tag:

Related branches: branches having a common ancestor

Merge: the operation of applying to a branch all the changes introduced by another one

Access using the standard filesystem (default)

Supported URL Prefixes

aftp:// Access using active FTP

bzr:// Fast access using the Bazaar smart server bzr+ssh:// Fast access using the Bazaar smart server over SSH file://

ftp:// Access using passive FTP

http:// Read-only access of branches exported on the web https:// Read-only access of branches exported on the web using SSL

Access using SFTP (most SSH servers provide SFTP) sftp://

More information

bzr help / bzr help commands http://bazaar-vcs.org

Information

Working tree status

bzr status

Revision log

bzr qlog

bzr glog <FILE>

Working tree changes

bzr diff

bzr diff <FILE>

Missing revisions

bzr missing <BRANCH URL>

Contents of file at a specific revision

bzr qcat -r <REV ID> <FILE>

Publishing and Binding

Push revisions remotely (or publish vour local branch as a new remote branch)

bzr push <BNCH URL>

Unbind local branch

bzr unbind

Bind local branch to remote branch

bzr bind <BNCH URL>