



Appendix 13B

Authentication Multiplexor

Structures and Definitions

Constant Definitions	2
Authenticaton Service IDs	2
Structure Definitions	2
AUTH_SVC_API_SET_TYPE	2
AUTH_SVC_DESC_BLOCK	3
Return Codes	4

Constant Definitions

Authenticaton Service IDs

```
#define BINDERY_AUTHEN_ID    0x00000001
#define NDS_AUTHEN_ID       0x00000002
#define PNW_AUTHEN_ID       0x00000003
```

Structure Definitions

AUTH_SVC_API_SET_TYPE

Describes routines that an authentication service module must register with AuthMux.

```
typedef struct {
    UINT32    (*CreateAuthenticationHandle)
                (UINT32        processGroupID,
                 UINT32        processID,
                 SPECT_DATA    *username,
                 SPECT_DATA    *password,
                 SPECT_DATA    *domainName,
                 VOID          *authenSpecInfo,
                 AUTH_HANDLE   *authenHandle );

    UINT32    (*AuthenticateWithHandle)
                (AUTH_HANDLE   authenHandle,
                 CONN_HANDLE   connHandle);

    UINT32    (*Authenticate)
                (UINT32        processGroupID,
                 UINT32        processID,
                 CONN_HANDLE   connHandle,
                 SPECT_DATA    *username,
                 SPECT_DATA    *password,
                 SPECT_DATA    *domainName,
                 VOID          *authenSpecInfo);

    UINT32    (*Unauthenticate)
                (CONN_HANDLE   connHandle);

    UINT32    (*CloseAuthenticationHandle)
                (AUTHHANDLE    authenHandle );

    UINT32    (*GetAuthenInfo)
                (AUTH_HANDLE   authenHandle,
```

```
        SPECT_DATA    *username,  
        SPECT_DATA    *domainName,  
        VOID          *authenSpecInfo)  
} AUTH_SVC_API_SET_TYPE;
```

AUTH_SVC_DESC_BLOCK

The data structure that an authentication provider registers with AuthMux that further describes the authentication service module being registered. This information can be obtained by other NLMs by calling **ConnEnumerateAuthenticationSVC**.

```
typedef struct {
    UINT8    majorVersion;
    UINT8    minorVersion;
    UINT8    revision;
    UINT8    name[13];
    UINT8    description[80];
    UINT32    authenSvcID;
} AUTH_SVC_DESC_BLOCK;
```

Fields:

<i>majorVersion</i>	Major version of this authentication service module.
<i>minorVersion</i>	Minor version of this authentication service module.
<i>revision</i>	Revision of this authentication service module.
<i>name</i>	ASCIIZ name of this authentication service module.
<i>description</i>	ASCIIZ description of this authentication service module.
<i>authenSvcID</i>	Unique authentication service ID assigned to this authentication service module.

Return Codes

<code>AUTHEN_FAILED</code>	Returned by authentication service module if it cannot authenticate the supplied connection with given authentication information.
<code>AUTHEN_SVC_ALREADY_REGISTERED</code>	Specified authentication service module is already registered with AuthMux.
<code>AUTHEN_SVC_NOT_REGISTERED</code>	Specified authentication service module is not registered with AuthMux.
<code>INVALID_AUTHEN_HANDLE</code>	Returned by AuthMux if supplied authentication handle is not valid.