

### Create Unlimited Runs of Continuous Solid Lines of Light.

Complete lighting solution that offers a low profile and easily bends against it's line of light (opposite bend to Super Neon Edge). Ultra flexible, bends easily, free from any form of shape memory. Create endless contours, forms, lines, curves and shapes of powerful solid light. Transparent ends allows for unlimited run lengths, combined with integral "No Tool" connectors and simple leader/jumper cables. UV protected IP67 Wet Location Rated.




## OUTPUT

Delivered Lumens	132.72
CCT & SDMC	3000K - 2 Step MacAdam Ellipse
Chromaticity Coordinates	x: 0.4414 y: 0.4303 u: 0.2425 v: 0.5319
Color Bin Tolerance	+ 3% / -3%
Efficacy (lm/w)	28.35
CRI	88
Lumen Maintenance	70,000 Hours L70 @ 25°C 90,000 Hours L50 @ 25°C 50,000 Hours L70 @ 50°C 70,000 Hours L50 @ 50°C
Testing Data	Light Data LM-79-08 & LM-80-08

## ELECTRICAL

Input Voltage	24V DC
Power Consumption	4.68W (0.04A)
Power Factor	≤ 1
Control	100 - 277V 0-10 & Magnetic Low Voltage

## CIE 1931 CHROMATICITY DIAGRAM




## LUMINANCE DATA (cd/sq.m)

Angle in Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	5177	3841	3740
55	4848	3617	3637
65	4453	3503	3586
75	3903	3480	3601
85	3361	3598	3700

## PHYSICAL


Applications	Accent Linear / Curved Surfaces, Architectural Highlights
Dimensions	Length 11 7/8" (300mm) Width 7/16" (11mm) Height 7/8" (21mm)
Weight	4.8 oz (136g)
Construction	UV Resistant Tough White Flexible PVC
Thermal Management	Cool to Touch, Free Air Convection
Optics	N/A
Fixture Connections	Male and Female Barrel Connectors
Operating Temperature	-4°F ~ 113°F (-20°C ~ 45°C)
Storage Temperature	-4°F ~ 122°F (-20°C ~ 50°C)
Humidity	0-95% Non Condensing

## DIMENSIONS




## CONNECTOR DIMENSIONS

### Bottom Feed



### Side Feed




Project Name:

Notes:


## STANDARDS & CERTIFICATIONS



ILLUMINANCE AT A DISTANCE



POLAR CANDELA DISTRIBUTION



ZONAL LUMEN SUMMARY


Zone	Lumens	% Lamp	% Fixt
0-30	19.90	N.A.	15.00%
0-40	33.31	N.A.	25.10%
0-60	63.17	N.A.	47.60%
60-90	26.94	N.A.	20.30%
0-90	100.86	N.A.	76.00%
90-180	30.65	N.A.	24.00%
0-180	132.72	N.A.	100.00%

LUMENS PER ZONE

Zone	Lumens	% Lamp	% Fixt
0-10	2.40	N.A.	1.81%
10-20	6.91	N.A.	5.21%
20-30	10.65	N.A.	8.03%
30-40	13.29	N.A.	10.02%
40-50	14.79	N.A.	11.15%
50-60	15.09	N.A.	11.37%
60-70	14.29	N.A.	10.77%
70-80	12.68	N.A.	9.56%
80-90	10.72	N.A.	8.08%
90-100	8.87	N.A.	6.69%

WIRING

UL / cUL Non-Dimming



UL / cUL 0-10V Dimming



WIRING LEGEND

Power (100-277V AC)	24V Driver	0-10V Dimmer
Power Positive	Power Positive	Power In
Power Negative	Power Negative	Power Out
Ground		Ground
		Data Positive
		Data Negative

MAX CONTINUOUS RUN

150W Driver      30ft

## ACCESSORIES



**SN-LDR-CBL-5FT**  
**5' Leader Cable**

Connects SUPER NEON to Power Supply

Cable Dimension	Connector Dimension
5' (3m)	L: 1 3/8" (30mm)
	W: 5/8" (17mm)
	H: 1/2" (14mm)



**SN-LDR-CBL-10FT**  
**10' Leader Cable**

Connects SUPER NEON to Power Supply

Cable Dimension	Connector Dimension
10' (3m)	L: 1 3/8" (30mm)
	W: 5/8" (17mm)
	H: 1/2" (14mm)



**SN-LDR-CBL-20FT**  
**20' Leader Cable**

Connects SUPER NEON to Power Supply

Cable Dimension	Connector Dimension
20' (3m)	L: 1 3/8" (30mm)
	W: 5/8" (17mm)
	H: 1/2" (14mm)



**SN-JMP-CBL-1FT**  
**1' Jumper Cable**

Connects Two SUPER NEON Together

Connector Dimension
L: 1 3/8" (30mm)
W: 5/8" (17mm)
H: 1/2" (14mm)



**SN-T**  
**Terminator**

Terminates SUPER NEON Fixture

L: 1" (25mm)  
W: 11/16" (18mm)  
H: 1/4" (7mm)



**SNX-CLP-S2**  
**Aluminum Mounting Clip**

Aluminum Mounting Clip for SUPER NEON X

L: 2" (50mm)  
W: 5/8" (17mm)  
H: 15/16" (24mm)



**SNX-XTR-1F**  
**1' Aluminum Xtrusion®**

1' Aluminum Xtrusion for SUPER NEON X

L: 1' (305mm)  
W: 5/8" (17mm)  
H: 15/16" (24mm)



**SNX-XTR-4F**  
**4' Aluminum Xtrusion®**

4' Aluminum Xtrusion for SUPER NEON X

L: 4' (1.22m)  
W: 5/8" (17mm)  
H: 15/16" (24mm)

## 24V 0-10V Dimming Driver



**MP89**  
**100 - 277V**

150W - IP66

L: 9 1/2" (241mm)  
W: 2 5/8" (67mm)  
H: 1 5/8" (40.5mm)

## 24V Non Dimming Driver



**MP17**  
**100-277V AC**

150W - IP67

L: 8 11/16" (222mm)  
W: 2 11/16" (68mm)  
H: 1 1/2" (39mm)

## STANDARDS & CERTIFICATIONS

Certification	Tested to UL & CSA by ETL For Use in USA & CANADA, Complies with California Title 24 Requirements, Lighting Facts. Exceeds ANSI C78.377A, CE & RoHS Compliant.
Class	3
Environment	Wet Location - IP67
Warranty	3 Year Limited Warranty

## ORDERING

Bottom Feed	<b>SNX-F-BF-3000K-1FT</b>
Side Feed	<b>SNX-F-SF-3000K-1FT</b>