


**Create Unlimited Runs of Continuous Solid Lines of Light.**

Complete lighting solution that offers a low profile and easily bends along it's line of light (opposite bend to Super Neon X Dome & Flat). Ultra flexible, bends easily, free from any form of shape memory. Create endless contours, forms, lines, curves and shapes of powerful solid light. Transparent ends allows for unlimited run lengths, combined with integral "No Tool" connectors and simple leader/jumper cables. UV protected IP67 Wet Location Rated.




**OUTPUT**

Delivered Lumens	5953.45
CCT & SDMC	3500K - 2 Step MacAdam Ellipse
Chromaticity Coordinates	x: 0.4414 y: 0.4303 u: 0.2425 v: 0.5319
Color Bin Tolerance	+ 3% / -3%
Efficacy (lm/w)	58.71
CRI	88
Lumen Maintenance	70,000 Hours L70 @ 25°C 90,000 Hours L50 @ 25°C 50,000 Hours L70 @ 50°C 70,000 Hours L50 @ 50°C
Testing Data	Light Data LM-79-08 & LM-80-08

**ELECTRICAL**

Input Voltage	24V DC
Power Consumption	101.40W (0.85A)
Power Factor	≤ 1
Dimming	100 - 277V 0-10V & Magnetic Low Voltage
Emergency	N/A

**CIE 1931 CHROMATICITY DIAGRAM**




**LUMINANCE DATA**  
(cd/sq.m)

Angle in Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	5177	3814	3740
55	4848	3617	3637
65	4453	3503	3586
75	3903	3480	3601
85	3361	3598	3160

**PHYSICAL**


Applications	Accent Linear / Curved Surfaces, Architectural Highlights
Dimensions	Length 30' 15/16" (9.17m) Width 5/8" (16mm) Height 9/16" (15mm)
Weight	144 oz (4,082g)
Construction	UV Resistant Tough White Flexible PVC
Thermal Management	Cool to Touch, Free Air Convection
Optics	N/A
Fixture Connections	Male and Female Barrel Connectors
Operating Temperature	-4°F ~ 113°F (-20°C ~ 45°C)
Storage Temperature	-4°F ~ 122°F (-20°C ~ 50°C)
Humidity	0-95% Non Condensing

**DIMENSIONS**



**CONNECTOR DIMENSIONS**

**Bottom Feed**



**STANDARDS & CERTIFICATIONS**



Project Name:


Notes:

## ILLUMINANCE AT A DISTANCE

	Center Beam FC	Beam Width
2.0 ft	551.24 fc	6.3 ft 5.9 ft
4.0 ft	137.81 fc	12.6 ft 11.8 ft
6.0 ft	68.90 fc	18.9 ft 17.7 ft
8.0 ft	34.45 fc	25.2 ft 23.6 ft
10.0 ft	17.22 fc	31.6 ft 29.4 ft
12.0 ft	13.78 fc	37.9 ft 35.3 ft

Vert. Spread: 115.3°  
Horiz. Spread: 114.9°

## POLAR CANDELA DISTRIBUTION



## ACCESSORIES



**SN-LDR-CBL-5FT**  
5' Leader Cable

Connects SUPER NEON to Power Supply

Cable Dimension	Connector Dimension
5' (3m)	L: 1 3/8" (30mm)
	W: 5/8" (17mm)
	H: 1/2" (14mm)



**SN-LDR-CBL-10FT**  
10' Leader Cable

Connects SUPER NEON to Power Supply

Cable Dimension	Connector Dimension
10' (3m)	L: 1 3/8" (30mm)
	W: 5/8" (17mm)
	H: 1/2" (14mm)



**SN-LDR-CBL-20FT**  
20' Leader Cable

Connects SUPER NEON to Power Supply

Cable Dimension	Connector Dimension
20' (3m)	L: 1 3/8" (30mm)
	W: 5/8" (17mm)
	H: 1/2" (14mm)



**SNE-CLP-S2**  
Aluminum Mounting Clip

Aluminum Mounting Clip for SUPER NEON EDGE

L: 2" (50mm)
W: 5/8" (17mm)
H: 15/16" (24mm)



**SNE-XTR-1F**  
1' Aluminum Xtrusion®

1' Aluminum Xtrusion for SUPER NEON EDGE

L: 1' (305mm)
W: 5/8" (17mm)
H: 15/16" (24mm)



**SNE-XTR-4F**  
4' Aluminum Xtrusion®

4' Aluminum Xtrusion for SUPER NEON EDGE

L: 4' (1.22m)
W: 5/8" (17mm)
H: 15/16" (24mm)

## 24V 0-10V Dimming Driver



**MP89**  
100 - 277V

150W - IP66

L: 9 1/2" (241mm)
W: 2 5/8" (67mm)
H: 1 5/8" (40.5mm)

## 24V Non-Dimming Driver



**MP17**  
100 - 277V AC

150W - IP67

L: 8 11/16" (222mm)
W: 2 11/16" (68mm)
H: 1 1/2" (39mm)

## STANDARDS & CERTIFICATIONS

Certification	Tested to UL & CSA by ETL For Use in USA & CANADA, Complies with California Title 24 Requirements, Lighting Facts. Exceeds ANSI C78.377A, CE & RoHS Compliant.
Class	3
Environment	Wet Location - IP67
Warranty	3 Year Limited Warranty

## ORDERING

Bottom Feed

**SNE-BF-2700K-30FT**