


Project Name: \_\_\_\_\_ SKU: \_\_\_\_\_

MODA Contact: \_\_\_\_\_ E-Mail: \_\_\_\_\_

Type: \_\_\_\_\_ PO#: \_\_\_\_\_ Quantity: \_\_\_\_\_

Notes: \_\_\_\_\_



## PHYSICAL

<b>Dimensions</b>	L: 1ft 1/4in (308mm) W: 1 3/16in(29mm) L: 4ft 5/32in(1.22m) H: 1 1/2in(38mm)
<b>Weight</b>	1ft: 0.38 lbs (0.17kg) 4ft: 1.22 lbs (0.55 kg)
<b>Applications</b>	Cove, Accent, & Indirect General Illumination
<b>Construction</b>	6063 Aluminum Body, Polycarbonate Self-Locking Mounting Bracket and Polycarbonate Optical Lens
<b>Ingress Protection</b>	Dry/Damp Location IP52
<b>Thermal Management</b>	Moda Aluminum Heat Sink
<b>Fixture Connections</b>	Integral Male & Female Connectors
<b>Operating Temperature</b>	-4°F ~ 149°F (-20°C ~ 65°C)
<b>Storage Temperature</b>	-13°F ~ 158°F (-25°C ~ 70°C)
<b>Humidity</b>	20-70% Non Condensing

## SPECIFICATIONS

	<b>Lumens</b>	<b>Efficacy</b>
RGB 1FT	120.47	30.88
RGB 4FT	481.88	35.43

## POWER CONSUMPTION

	<b>120V AC</b>	<b>240V AC</b>	<b>277V AC</b>
1 Foot	3.9W	4W	4.7W
4 Foot	13.6W	14W	14W

## OUTPUT

<b>Colors</b>	RGB
<b>Beam Angle</b>	200°
<b>Color Bin Tolerance</b>	Zero Bin
<b>Lumen Maintenance</b>	90,000 Hours L70 @ 25°C 70,000 Hours L70 @ 50°C
<b>Testing Data</b>	Light Data LM-79-08 & LM-80-08

## ELECTRICAL

<b>Input Voltage</b>	100-277V AC 50Hz/60Hz
<b>Control</b>	DMX 512
<b>Power Factor</b>	≥ 0.98

## MAX CONTINUOUS RUN

	<b>120V AC</b>	<b>240V AC</b>	<b>277V AC</b>
SO	120 ft	240 ft	240 ft

## STANDARDS & CERTIFICATIONS



<b>Certification</b>	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, CCC, C-Tick, RoHS, & WEEE Compliant.
<b>Class</b>	1
<b>Warranty</b>	5 Year Limited Warranty

FIXTURE	SKU
<b>1 FT</b> Moda Mini Cove Interior Standard Output Silver DMX 512 RGB 1FT	105-1000
<b>4 FT</b> Moda Mini Cove Interior Standard Output Silver DMX 512 RGB 4FT	105-3000

ACCESSORIES	DESCRIPTION	SKU
Leader Cable US 5 Pin 10ft	Power to first fixture of run	299-0100
Leader Cable US 5 Pin 25ft	Power to first fixture of run	299-0102
Jumper Cable US 5 Pin 1ft	Connection between fixtures	299-1100
Jumper Cable US 5 Pin 4ft	Connection between fixtures	299-1102
Leader Cable EU 5 Pin 3m	Power to first fixture of run	299-0101
Leader Cable EU 5 Pin 7.62m	Power to first fixture of run	299-0103
Jumper Cable EU 5 Pin 300mm	Connection between fixtures	299-1101
Jumper Cable EU 5 Pin 1m	Connection between fixtures	299-1103
Terminator 5 Pin	Must be fixed to last fixture for safety	299-2100
Mounting Track	Allows user to install fixtures in a continuous linear position. Packaged in 5 4ft sections in total of 20ft.	299-3200

CONTROLS	DESCRIPTION	SKU
Kandi Touch	DMX 512 Controller Available in black and white	KND-TCH-B KND-TCH-W

CONTROL ACCESSORIES	DESCRIPTION	SKU
Moda DMX Wiring Hub 2.0	Simplifies wiring and strengthens DMX signal.	250-0100
Belden Shielded Cable 500ft	RS-458 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	BDL-9841-500FT
Belden Shielded Cable 1000ft	RS-458 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	BDL-9841-1000FT