

modaLIGHT[®]

SPECIFICATION


MODA MINI COVE[®] INTERIOR DYNAMIC WARM

Project Name: _____ SKU: _____

MODA Contact: _____ E-Mail: _____

Type: _____ PO#: _____ Quantity: _____

Notes: _____



PHYSICAL

Dimensions	L: 1ft 1/4in (308mm) W: 1 3/16in(29mm) L: 4ft 5/32in(1.22m) H: 1 1/2in(38mm)
Weight	1ft: 0.38 lbs (0.17kg) 4ft: 1.22 lbs (0.55 kg)
Applications	Cove, Accent, & Indirect General Illumination
Construction	6063 Aluminum Body, Polycarbonate Self-Locking Mounting Bracket and Polycarbonate Optical Lens
Ingress Protection	Dry/Damp Location IP52
Thermal Management	Moda Aluminum Heat Sink
Fixture Connections	Integral Male & Female Connectors
Operating Temperature	-4°F ~ 149°F (-20°C ~ 65°C)
Storage Temperature	-13°F ~ 158°F (-25°C ~ 70°C)
Humidity	20-70% Non Condensing

SPECIFICATIONS

	Lumens	Efficacy
DYNAMIC WARM 1FT	353.60	60.96
DYNAMIC WARM 4FT	1414.40	65.48

POWER CONSUMPTION

	120V AC	240V AC	277V AC
1 Foot	5.8W	6.2W	6.2W
4 Foot	21.6W	21.6W	21.8W

OUTPUT

Colors	Dynamic Warm (1800K - 3000K)
Beam Angle	200°
CRI	95-97
SDCM	2-Step MacAdam Ellipse
Color Bin Tolerance	Zero Bin
Lumen Maintenance	90,000 Hours L70 @ 25°C 70,000 Hours L70 @ 50°C
Testing Data	Light Data LM-79-08 & LM-80-08

ELECTRICAL

Input Voltage	100-277V AC 50Hz/60Hz
Control	DMX 512
Power Factor	≥ 0.98

MAX CONTINUOUS RUN

120V AC	240V AC	277V AC
120 ft	240 ft	240 ft

STANDARDS & CERTIFICATIONS



Certification	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, CCC, C-Tick, RoHS, & WEEE Compliant.
Class	1
Warranty	5 Year Limited Warranty

FIXTURE	SKU
1 FT Moda Mini Cove Interior Standard Output Silver DMX 512 Dynamic Warm HCRI 1FT	106-1201
4 FT Moda Mini Cove Interior Standard Output Silver DMX 512 Dynamic Warm HCRI 4FT	106-3201

ACCESSORIES	DESCRIPTION	SKU
Leader Cable US 5 Pin 10ft	Power to first fixture of run	299-0100
Leader Cable US 5 Pin 25ft	Power to first fixture of run	299-0102
Jumper Cable US 5 Pin 1ft	Connection between fixtures	299-1100
Jumper Cable US 5 Pin 4ft	Connection between fixtures	299-1102
Leader Cable EU 5 Pin 3m	Power to first fixture of run	299-0101
Leader Cable EU 5 Pin 7.62m	Power to first fixture of run	299-0103
Jumper Cable EU 5 Pin 300mm	Connection between fixtures	299-1101
Jumper Cable EU 5 Pin 1m	Connection between fixtures	299-1103
Terminator 5 Pin	Must be fixed to last fixture for safety	299-2100
Mounting Track	Allows user to install fixtures in a continuous linear position. Packaged in 5 4ft sections in total of 20ft.	299-3200

CONTROLS	DESCRIPTION	SKU
Kandi Touch	DMX 512 Controller Available in black and white	KND-TCH-B KND-TCH-W

CONTROL ACCESSORIES	DESCRIPTION	SKU
Moda DMX Wiring Hub 2.0	Simplifies wiring and strengthens DMX signal.	250-0100
Belden Shielded Cable 500ft	RS-458 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	BDL-9841-500FT
Belden Shielded Cable 1000ft	RS-458 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	BDL-9841-1000FT