


Client: _____ Project Name: _____

MODA Contact: _____ E-Mail: _____

Type: _____ PO#: _____ Quantity: _____

Notes: _____



Specification Grade Premium Interior Cove Fixture.

MODA COVE Interior is a new patent pending cove lighting system designed for interior applications. Utilizing MODA's latest DMX software, our onboard Microprocessor is uniquely programmed in-house with a firmware to receive DMX 512 signals for full independent control of every 1ft section. Change the color temperature ranging from 1800K to 3000K and create a variety of moods. With MODA's methods of precision and high standards of work, MODA achieves perfect illumination. Color Rendering Index is at a MODA standard of 90-98. R1 - R15 values are in excess of 90. No striations, no color over angle, and no dark spots. 100-277V, 50/60Hz power input allows these fixtures to be installed anywhere in the world. New patent pending locking bracket rotates 180 degrees for a multitude of light directions. Rugged aluminum design. Fast installation is achieved with MODA KWIK CONNECT plugs and install-integral thumb latch connectors. Available in 1ft & 4ft sections. Series is designed for driver or light engine to be factory replaced at its end of life or recycled.

Designed and developed in Las Vegas, USA by MODA.

PAGE	
3	FEATURES
4	1 FOOT
5	4 FOOT
6	DMX WIRING
7	ACCESSORIES: LEADER CABLES
8	ACCESSORIES: JUMPER CABLES
9	ACCESSORIES: SUMMARY
10	ITEM NUMBER

PHYSICAL

Lengths	1ft & 4ft sections available
Applications	Cove, Accent & Indirect General Illumination
Construction	Pure Aluminum Body, Polycarbonate Mounting Bracket and Lens
Ingress Protection	Dry/Damp Location IP44
Thermal Management	MODA Aluminum Heat Sink
Beam Angle	120°
Fixture Connections	Integral Male & Female Connectors
Operating Temperature	-40°F ~ 122°F (-40°C ~ 50°C)
Storage Temperature	-40°F ~ 176°F (-40°C ~ 80°C)
Humidity	0-95% Non Condensing

OUTPUT

CCT & SDCM	1800K - 3000K - SO, HO+ only 2200K - 3000K - HO only 2 Step MacAdam Ellipse
Color Bin Tolerance	Single Bin
CRI	95-98
Lumen Maintenance	90,000 Hours L50 @ 25°C 70,000 Hours L50 @ 50°C
Testing Data	Light Data LM-79-08 & LM-80-08

ELECTRICAL

Input Voltage	100-277V AC 50Hz/60Hz
Dimming	DMX 512 Controlled
Power Factor	≥ 0.96
Emergency	N/A

MODA TECHNOLOGY

moda**SOFT**™

moda**DIM**™

moda**DMX**™

moda**DYNAMIC WARM**

moda**DRIVER**™

moda**PHOSPHOR**™

moda**BIN**™

moda**HIGH CRI**™

moda**KWIK CONNECT**™

moda**THERMAL MANAGEMENT**™

moda**COMMUNICATE**™




RoHS ✓



Certification Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, C-Tick, RoHS, & WEEE Compliant.

Class 1

Warranty 3 Year Limited Warranty




DMX


	Lumens	CRI	Efficacy
SO	629.62 - 730.00	95	62.96 - 73.00
HO	1001.40 - 1139.09	97	100.14 - 113.90
HO+	1141.68 - 1298.66	98	114.16 - 129.86


	Power Consumption 100-277V AC	Max Run Length	
		120V AC	277V AC
SO	10W	80ft	80ft
HO	10W	80ft	80ft
HO+	10W	80ft	80ft

Illuminance at a Distance



Polar Candela Distribution






DMX


	Lumens	CRI	Efficacy	
SO	2537.36 - 2941.90	95	63.43 - 73.54	
HO	4035.64 - 4590.53	97	100.89 - 114.76	
HO+	4600.97 - 5233.59	98	115.02 - 130.83	


	Power Consumption 100-277V AC	Max Run Length	
		120V AC	277V AC
SO	40W	80ft	80ft
HO	40W	80ft	80ft
HO+	40W	80ft	80ft

Illuminance at a Distance



Polar Candela Distribution





Wiring Legend

1	Power 100-277V
2	DMX Controller
3	8 Pin Leader Cable
4	Junction Box
5	Wiring Nuts


8 Pin Leader Cable

	UL/cUL	CE/CCC*
A Live 100-277V	Black	Brown
B Neutral	White	Blue
C Ground	Green/Yellow	Yellow/Green
D Data Positive	Orange	Orange
E Data Negative	Yellow	Yellow


*not illustrated

DMX Connectors


Male Output



Female Output




Angle Adjustment




DMX

Moda Cove Interior 8 Pin Leader Cables


	UL/cUL	EU/CCC
Lengths	10ft and 25ft	3m and 7.62m
Color	Gray	Gray



Female Connector



Pin Assignment




		UL/cUL	EU/CCC
1	Live 100-277V	Black	Brown
2	Neutral	White	Blue
3	DMX Positive	Orange	Orange
4	DMX Negative	Yellow	Yellow


DMX

Moda Cove Interior 8 Pin Jumper Cables


	UL/cUL	EU/CCC
Lengths	1ft and 4ft	300mm and 1m
Color	Gray	Gray




Connectors



Pin Assignment



		UL/cUL	EU/CCC
1	Live 100-277V	Black	Brown
2	Neutral	White	Blue
3	DMX Positive	Orange	Orange
4	DMX Negative	Yellow	Yellow



		UL/cUL	EU/CCC
1	Live 100-277V	Black	Brown
2	Neutral	White	Blue
3	DMX Positive	Orange	Orange
4	DMX Negative	Yellow	Yellow

NAME	SKU	DESCRIPTION
Leader Cable US 8 Pin 10ft	MLCI-US-8PIN-G-10FT	Power to first fixture of run
Leader Cable US 8 Pin 25ft	MLCI-US-8PIN-G-25FT	Power to first fixture of run
Jumper Cable US 8 Pin 1ft	MJCI-US-8PIN-G-1FT	Connection between fixtures
Jumper Cable US 8 Pin 4ft	MJCI-US-8PIN-G-4FT	Connection between fixtures
Leader Cable EU 8 Pin 3m	MLCI-EU-8PIN-G-3M	Power to first fixture of run
Leader Cable EU 8 Pin 7.62m	MLCI-EU-8PIN-G-7.62M	Power to first fixture of run
Jumper Cable EU 8 Pin 300mm	MJCI-EU-8PIN-G-300MM	Connection between fixtures
Jumper Cable EU 8 Pin 1m	MJCI-EU-8PIN-G-1M	Connection between fixtures
Terminator 8 Pin	MTI-8PIN-G	Must be fixed to last fixture for safety
Interior Bracket Lock	MCGI-BL-G	Holds fixture in place for vertical installations
Belden Shielded Cable 500 FT	BDL-9841-500FT	RS-458 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation
Belden Shielded Cable 1000 FT	BDL-9841-1000FT	RS-458 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation
Kandi Touch	KANDI-TOUCH-BLACK KANDI-TOUCH-WHITE	DMX 512 Controller
Moda DMX Wiring Hub	250-0100-01	Simplifies wiring and strengthens signal



COMPLETE SKU SAMPLE: MCI-HOP-S1-S-DWW-1

A - FIXTURE & LOCATION

MCI	—	Moda Cove Interior
-----	---	--------------------

D - PRODUCT FINISH

S	—	Silver
---	---	--------

B - LIGHT OUTPUT

SO	—	Standard Output
HO	—	High Output
HOP	—	High Output Plus

E - LED COLOR

DWW	—	1800K - 3000K (Dynamic Warm)
DW	—	2200K - 6500K (Dynamic White)
DC	—	3500K - 6500K (Dynamic Cool)

C - SERIES NUMBER

S1	—	Series 1
----	---	----------

F - LENGTH

1	—	1FT
4	—	4FT