


Project Name: _____ SKU: _____

MODA Contact: _____ E-Mail: _____

Type: _____ PO#: _____ Quantity: _____

Notes: _____



PHYSICAL

Dimensions	L: 1ft 1/8in (307.5mm)	W: 1 1/4in (32mm)
	L: 4ft (1.22m)	H: 1 3/8in (34.5mm)
Weight	1ft: 0.38 lbs (0.17kg)	
	4ft: 1.22 lbs (0.55 kg)	
Applications	Cove, Accent, & Indirect General Illumination	
Construction	6063 Aluminum Body, Polycarbonate Self-Locking Mounting Bracket and Polycarbonate Optical Lens	
Ingress Protection	Dry/Damp Location IP52	
Thermal Management	Moda Aluminum Heat Sink	
Fixture Connections	Integral Male & Female Connectors	
Operating Temperature	-4°F ~ 149°F (-20°C ~ 65°C)	
Storage Temperature	-13°F ~ 158°F (-25°C ~ 70°C)	
Humidity	20-70% Non Condensing	

SPECIFICATIONS

	Lumens	Efficacy
DYNAMIC COOL 1FT	480.60	82.86
DYNAMIC COOL 4FT	1922.40	89.00

POWER CONSUMPTION

	120V AC	240V AC	277V AC
1 Foot	5.8W	6.2W	6.2W
4 Foot	21.6W	21.6W	21.8W

OUTPUT

Colors	Dynamic Cool (3500K - 6500K)
Beam Angle	200°
CRI	95-98
SDCM	2-Step MacAdam Ellipse
Color Bin Tolerance	Zero Bin
Lumen Maintenance	90,000 Hours L70 @ 25°C
	70,000 Hours L70 @ 50°C
Testing Data	Light Data LM-79-08 & LM-80-08

ELECTRICAL

Input Voltage	100-277V AC 50Hz/60Hz
Control	DMX 512
Power Factor	≥ 0.98

MAX CONTINUOUS RUN

120V AC	240V AC	277V AC
120FT	240FT	240FT

STANDARDS & CERTIFICATIONS



Certification	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, CCC, C-Tick, RoHS, & WEEE Compliant.
Class	1
Warranty	5 Year Limited Warranty

FIXTURE		ORDERING NUMBER	SKU
1FT	Moda Mini Cove Interior Standard Output Silver DMX 512 Dynamic Cool HCRI 1FT	MMCI-S-S-DC-1	106-1401
4FT	Moda Mini Cove Interior Standard Output Silver DMX 512 Dynamic Cool HCRI 4FT	MMCI-S-S-DC-4	106-3401

ACCESSORIES	DESCRIPTION	ORDERING NUMBER	SKU
Leader Cable US 5 Pin 10FT	Power to first fixture of run	MLCI-US-5PIN-W-10FT	299-0100
Leader Cable US 5 Pin 25FT	Power to first fixture of run	MLCI-US-5PIN-W-25FT	299-0102
Jumper Cable US 5 Pin 1FT	Connection between fixtures	MJCI-US-5PIN-W-1FT	299-1100
Jumper Cable US 5 Pin 4FT	Connection between fixtures	MJCI-US-5PIN-W-4FT	299-1102
Leader Cable EU 5 Pin 3M	Power to first fixture of run	MLCI-EU-5PIN-W-3M	299-0101
Leader Cable EU 5 Pin 10M	Power to first fixture of run	MLCI-EU-5PIN-W-10M	299-0103
Jumper Cable EU 5 Pin 300MM	Connection between fixtures	MJCI-EU-5PIN-W-300MM	299-1101
Jumper Cable EU 5 Pin 1M	Connection between fixtures	MJCI-EU-5PIN-W-1M	299-1103
Terminator 5 Pin	Must be fixed to last fixture for safety	MTI-5PIN-W	299-2100
Mounting Track	Allows user to install fixtures in a continuous linear position. Packaged in 5 4FT sections in total of 20FT.	MMC-20-TRACK-1-S1-G	299-3200
Symmetric Louvre	1FT Symmetric louvre for light control	N/A	299-4230
Asymmetric Louvre	1FT Asymmetric louvre for light control	N/A	299-4231
Honeycomb Louvre	1FT Honeycomb louvre for light control	N/A	299-4232
Blade Louvre	1FT Blade louvre for light control	N/A	299-4233

CONTROLS	DESCRIPTION	ORDERING NUMBER	SKU
Kandi Touch	DMX 512 Controller	KND-TCH-B	250-0040
		KND-TCH-W	250-0041

CONTROL ACCESSORIES	DESCRIPTION	ORDERING NUMBER	SKU
Moda DMX Wiring Hub 2.0	Simplifies wiring and strengthens DMX signal.	N/A	250-0100
Shielded Cable 500FT	RS-458 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	BDL-9841-500FT	250-0251
Shielded Cable 1000FT	RS-458 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	BDL-9841-1000FT	250-0252