

# modaLIGHT<sup>®</sup>

## SPECIFICATION



## MODA MINI COVE<sup>®</sup> INTERIOR DYNAMIC WHITE

Project Name: \_\_\_\_\_ SKU: \_\_\_\_\_

MODA Contact: \_\_\_\_\_ E-Mail: \_\_\_\_\_

Type: \_\_\_\_\_ PO#: \_\_\_\_\_ Quantity: \_\_\_\_\_

Notes: \_\_\_\_\_



### PHYSICAL

<b>Dimensions</b>	L: 1' 3/32in (307.46mm) W: 1 1/4in (32mm) L: 4' 1/8in (1.22m) H: 1 11/32in (34.5mm)
<b>Weight</b>	1ft: 0.38 lbs (0.17kg) 4ft: 1.22 lbs (0.55 kg)
<b>Applications</b>	Cove, Accent, & Indirect General Illumination
<b>Construction</b>	6063 Aluminum Body, Polycarbonate Self-Locking Mounting Bracket and Polycarbonate Optical Lens
<b>Ingress Protection</b>	Dry/Damp Location IP52
<b>Thermal Management</b>	Moda Aluminum Heat Sink
<b>Fixture Connections</b>	Integral Male & Female Connectors
<b>Operating Temperature</b>	-4°F ~ 149°F (-20°C ~ 65°C)
<b>Storage Temperature</b>	-13°F ~ 158°F (-25°C ~ 70°C)
<b>Humidity</b>	20-70% Non Condensing

### SPECIFICATIONS

	Lumens	Efficacy
DYNAMIC WHITE 1FT	418.60	72.17
DYNAMIC WHITE 4FT	1674.40	77.51

### POWER CONSUMPTION

	120V AC	240V AC	277V AC
<b>1 Foot</b>	5.8W	6.2W	6.2W
<b>4 Foot</b>	21.6W	21.6W	21.8W

### OUTPUT

<b>Colors</b>	Dynamic White (2200K - 6500K)
<b>Beam Angle</b>	200°
<b>CRI</b>	97-98
<b>SDCM</b>	2-Step MacAdam Ellipse
<b>Color Bin Tolerance</b>	Zero Bin
<b>Lumen Maintenance</b>	90,000 Hours L70 @ 25°C 70,000 Hours L70 @ 50°C
<b>Testing Data</b>	Light Data LM-79-08 & LM-80-08

### ELECTRICAL

<b>Input Voltage</b>	100-277V AC 50Hz/60Hz
<b>Control</b>	DMX 512
<b>Power Factor</b>	≥ 0.98

### MAX CONTINUOUS RUN

120V AC	240V AC	277V AC
120 ft	240 ft	240 ft

### STANDARDS & CERTIFICATIONS



<b>Certification</b>	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, CCC, C-Tick, RoHS, & WEEE Compliant.
<b>Class</b>	1
<b>Warranty</b>	5 Year Limited Warranty

FIXTURE		ORDERING NUMBER	PART NUMBER
1 FT	Moda Mini Cove Interior Standard Output Silver DMX 512 Dynamic White HCRI 1FT	MMCI-S-S-DWH-1	106-1003
4 FT	Moda Mini Cove Interior Standard Output Silver DMX 512 Dynamic White HCRI 4FT	MMCI-S-S-DWH-4	106-3003

ACCESSORIES	DESCRIPTION	ORDERING NUMBER	PART NUMBER
Leader Cable US 5 Pin 10ft	Power to first fixture of run	MLCI-US-5PIN-W-10FT	299-0100
Leader Cable US 5 Pin 25ft	Power to first fixture of run	MLCI-US-5PIN-W-25FT	299-0102
Jumper Cable US 5 Pin 1ft	Connection between fixtures	MJCI-US-5PIN-W-1FT	299-1100
Jumper Cable US 5 Pin 4ft	Connection between fixtures	MJCI-US-5PIN-W-4FT	299-1102
Leader Cable EU 5 Pin 3m	Power to first fixture of run	MLCI-EU-5PIN-W-3M	299-0101
Leader Cable EU 5 Pin 7.62m	Power to first fixture of run	MLCI-EU-5PIN-W-7.62M	299-0103
Jumper Cable EU 5 Pin 300mm	Connection between fixtures	MJCI-EU-5PIN-W-300MM	299-1101
Jumper Cable EU 5 Pin 1m	Connection between fixtures	MJCI-EU-5PIN-W-1M	299-1103
Terminator 5 Pin	Must be fixed to last fixture for safety	MTI-5PIN-W	299-2100
Mounting Track	Allows user to install fixtures in a continuous linear position. Packaged in 5 4ft sections in total of 20ft.	MMC-20-TRACK-1-S1-G	299-3200

CONTROLS	DESCRIPTION	ORDERING NUMBER	PART NUMBER
Kandi Touch	DMX 512 Controller	KND-TCH-B	250-0040
		KND-TCH-W	250-0041

CONTROL ACCESSORIES	DESCRIPTION	ORDERING NUMBER	PART NUMBER
Moda DMX Wiring Hub 2.0	Simplifies wiring and strengthens DMX signal.	N/A	250-0100
Belden Shielded Cable 500ft	RS-458 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	BDL-9841-500FT	250-0251
Belden Shielded Cable 1000ft	RS-458 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	BDL-9841-1000FT	250-0252