

Project Name: _____ SKU: _____

MODA Contact: _____ E-Mail: _____

Type: _____ PO#: _____ Quantity: _____

Notes: _____

MODA Touch[®] is a wall-mounted DMX 512 controller for architectural lighting applications. The glass faceplate features 6 touch-sensitive scene buttons allowing simple control of up to 36 dynamic or static scenes for one zone. Use the touch-sensitive color wheel to select specific colors. This controller is programmable via a computer or mobile app. MODA Touch[®] is an economical solution for hospitality, commercial, residential, and civic projects.



SPECIFICATIONS

Dimensions	W: 4 3/16in (106mm) H: 5 3/4in (146mm) L: 7/16in (11mm)
Weight	7.05 oz (200g)
Mobile Apps	DMX Lightpad 3 ARCOLIS on iPhone / iPad / Android
Temperature	14°F ~ 113°F (-10°C ~ 45°C)
Software	ESA + ESA PRO on PC/Windows ESA2 on PC/MAC
Components	Interface, SD Card, Wall Plate, CD-Rom, USB Cable, Power Supply

ACCESSORIES

RJ2BLOCK	RJ45 to connector block converter for POWER+DMX socket
POWER4M	5-10v ACDC power supply

OPTIONS

SKU	MTCH-S1-B MTCH-S1-W
COLOR	Black frame with either White/Black glass faceplate


TECHNICAL DATA

Input Power	5-15V DC 0.6A
Output Protocol	DMX512 (x2)
Programmability	PC/MAC
Connections	USB, 8 dry contact ports, open drain output (for relay)
Memory	Built-in flash
Battery	LIR1220
Mounting	Single/Double-gang wall socket
User-Interface	12 touch-sensitive buttons. No mechanical parts
SD Card	Micro SD Card for Stand-Alone Memory Use (Supplied)
Ports 1 - 8	8 Contact Closure Inputs Connects to Ground for Operating
Ethernet	Advanced Networking Features

STANDARDS & CERTIFICATIONS




POWER + DMX WITH THE CONNECTOR BLOCK



1	DMX1 +
2	DMX1 -
3	DMX GROUND
4	POWER GROUND
5	POWER DC +

POWER + DMX WITH RJ45 CABLE



1	DMX1 +
2	DMX1 -
3	DMX2 +
4 & 5	POWER DC +
6	DMX2 -
7 & 8	POWER GROUND