


Client:P	roject Name:		
MODA Contact:	E-Mail:		
SKU:	Туре:	PO#:	Quantity:



# 111/32" (34.5mm) 1 1/4" (32mm) 1 1/2" (38mm) 1 3/32"(307.46mm) / 4' 1/8"(1.22m)

# PHYSICAL

Notes:

PHYSICAL		
Dimensions	L: 1ft 3/32in (307.46mm) W: 1 1/4in (32mm) L: 4ft 1/8in (1.22m) H: 1 11/32in (34.5mm)	
Weight	1ft: 0.38 lbs (0.17kg) 4ft: 1.22 lbs (0.55 kg)	
Applications	Cove, Accent, & Indirect General Illumination	
Construction	6063 Aluminum Body, Polycarbonate Self-Locking Mounting Bracket and Polycarbonate Optical Lens	
Ingress Protection Dry/Damp Location IP52		
Thermal Management	Moda Aluminum Heat Sink	
Fixture Connections Integral Male & Female Connectors		
Operating Temperature	e -4°F ~ 149°F (-20°C ~ 65°C)	
Storage Temperature	-13°F ~ 158°F (-25°C ~ 70°C)	
Humidity	20-70% Non Condensing	

# POWER CONSUMPTION

	120V AC	240V AC	277V AC
	(SO/HO)	(SO/HO)	(SO/HO)
1 Foot	4.7W / 9.4W	5.5W / 9.9W	5.8W / 10W
4 Foot	17.7W / 37W	19.3W / 38W	19.5W / 39W

# ELECTRICAL

nput Voltage 100-277V AC 50Hz/60Hz	
Control	0-10V
Power Factor	≥ 0.98

### MAX CONTINUOUS RUN

	120V AC	240V AC	277V AC
so	120 ft	240 ft	240 ft
НО	50 ft	100 ft	100 ft

### OUTPUT

OUIFUI		
Colors	Red, Green, Blue, Amber, Yellow, Golden	
	Yellow, Ice Blue, Cyan, Light Green, Pink, Violet,	
	Turquoise, Dark Blue, Dark Orange	
Beam Angle	200°	
Color Bin Tolerance	Zero Bin	
	90,000 Hours L70 @ 25°C/70,000 Hours L70 @	
Lumen Maintenance	50°C	
Testina Data	Light Data LM-79-08 & LM-80-08	

# **SPECIFICATIONS**

	Lumens	Efficacy per ft (120V)	Efficacy per ft (240V)	Efficacy per ft (277V)
RED SO/HO	168 - 336	34	26	26
GREEN SO/HO	196 - 395	40	30	30
BLUE SO/HO	140 - 286	29	22	22
AMBER SO/HO	234 - 464	47	36	36
YELLOW SO/HO	215 - 430	43	33	33
GOLDEN YELLOW SO/HO	509 - 1015	102	78	78
ICE BLUE SO/HO	429 - 858	86	66	66
CYAN SO/HO	169 - 338	34	26	26
LIGHT GREEN SO/HO	490 - 980	98	75	75
PINK SO/HO	200 - 402	40	31	31
VIOLET SO/HO	194 - 388	39	30	30
TURQUOISE SO/HO	168 - 341	34	26	26
DARK BLUE SO/HO	84 - 168	17	13	13
DARK ORANGE SO/HO	420 - 840	84	65	65

# STANDARDS & CERTIFICATIONS



Certification

Tested to UL & CSA by Intertek For Use in USA
& CANADA. Exceeds ANSI C78.377-2015, CE,
CCC, C-Tick, RoHS, & WEEE Compliant.

 Class
 1

 Warranty
 5 Year Limited Warranty



	FIXTURE	ORDERING NUMBER	PART NUMBER
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Red 1FT	MMCI-S-S-0-R-1	096-1000
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Green 1FT	MMCI-S-S-0-G-1	096-1001
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Blue 1FT	MMCI-S-S-0-B-1	096-1002
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Amber 1FT	MMCI-S-S-0-A-1	096-1003
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Yellow 1FT	MMCI-S-S-0-Y-1	096-1004
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Pink 1FT	MMCI-S-S-0-P-1	096-1005
0-10V	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Cyan 1FT	MMCI-S-S-0-C-1	096-1006
SO 1FT	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Violet 1FT	MMCI-S-S-0-V-1	096-1007
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Turquoise 1FT	MMCI-S-S-0-TQ-1	096-1008
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Ice Blue 1FT	MMCI-S-S-0-IB-1	096-1009
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Light Green 1FT	MMCI-S-S-0-LG-1	096-1010
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Golden Yellow 1FT	MMCI-S-S-0-GY-1	096-1011
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Dark Blue 1FT	MMCI-S-S-0-DB-1	096-1012
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Dark Orange 1FT	MMCI-S-S-0-DO-1	096-1013
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Red 1FT	MMCI-H-S-0-R-1	096-1200
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Green 1FT	MMCI-H-S-0-G-1	096-1201
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Blue 1FT	MMCI-H-S-0-B-1	096-1202
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Amber 1FT	MMCI-H-S-0-A-1	096-1203
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Yellow 1FT	MMCI-H-S-0-Y-1	096-1204
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Pink 1FT	MMCI-H-S-0-P-1	096-1205
0-10V	Moda Mini Cove Interior High Output Silver 0-10V Dimming Cyan 1FT	MMCI-H-S-0-C-1	096-1206
HO 1FT	Moda Mini Cove Interior High Output Silver 0-10V Dimming Violet 1FT	MMCI-H-S-0-V-1	096-1207
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Turquoise 1FT	MMCI-H-S-0-TQ-1	096-1208
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Ice Blue 1FT	MMCI-H-S-0-IB-1	096-1209
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Light Green 1FT	MMCI-H-S-0-LG-1	096-1210
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Golden Yellow 1FT	MMCI-H-S-0-GY-1	096-1211
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Dark Blue 1FT	MMCI-H-S-0-DB-1	096-1212
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Dark Orange 1FT	MMCI-H-S-0-DO-1	096-1213
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Red 4FT	MMCI-S-S-0-R-4	096-3000
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Green 4FT	MMCI-S-S-0-G-4	096-3001
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Blue 4FT	MMCI-S-S-0-B-4	096-3002
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Amber 4FT	MMCI-S-S-0-A-4	096-3003
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Yellow 4FT	MMCI-S-S-0-Y-4	096-3004
0 101/	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Pink 4FT	MMCI-S-S-0-P-4	096-3005
0-10V SO	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Cyan 4FT	MMCI-S-S-0-C-4	096-3006
4FT	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Violet 4FT	MMCI-S-S-0-V-4	096-3007
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Turquoise 4FT	MMCI-S-S-0-TQ-4	096-3008
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Ice Blue 4FT	MMCI-S-S-0-IB-4	096-3009
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Light Green 4FT	MMCI-S-S-0-LG-4	096-3010
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Golden Yellow 4FT	MMCI-S-S-0-GY-4	096-3011
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Dark Blue 4FT	MMCI-S-S-0-DB-4	096-3012
	Moda Mini Cove Interior Standard Output Silver 0-10V Dimming Dark Orange 4FT	MMCI-S-S-0-DO-4	096-3013





	FIXTURE	ORDERING NUMBER	PART NUMBER
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Red 4FT	MMCI-H-S-0-R-4	096-3200
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Green 4FT	MMCI-H-S-0-G-4	096-3201
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Blue 4FT	MMCI-H-S-0-B-4	096-3202
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Amber 4FT	MMCI-H-S-0-A-4	096-3203
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Yellow 4FT	MMCI-H-S-0-Y-4	096-3204
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Pink 4FT	MMCI-H-S-0-P-4	096-3205
0-10V	Moda Mini Cove Interior High Output Silver 0-10V Dimming Cyan 4FT	MMCI-H-S-0-C-4	096-3206
HO 4FT	Moda Mini Cove Interior High Output Silver 0-10V Dimming Violet 4FT	MMCI-H-S-0-V-4	096-3207
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Turquoise 4FT	MMCI-H-S-0-TQ-4	096-3208
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Ice Blue 4FT	MMCI-H-S-0-IB-4	096-3209
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Light Green 4FT	MMCI-H-S-0-LG-4	096-3210
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Golden Yellow 4FT	MMCI-H-S-0-GY-4	096-3211
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Dark Blue 4FT	MMCI-H-S-0-DB-4	096-3212
	Moda Mini Cove Interior High Output Silver 0-10V Dimming Dark Orange 4FT	MMCI-H-S-0-DO-4	096-3213

ACCESSORIES	DESCRIPTION	ORDERING NUMBER	PART NUMBER
Leader Cable US 5 Pin 10ft	Power to first fixture of run	MLCI-US-5PIN-W-10FT	299-0100
Leader Cable US 5 Pin 25ft	Power to first fixture of run	MLCI-US-5PIN-W-25FT	299-0102
Jumper Cable US 5 Pin 1ft	Connection between fixtures	MJCI-US-5PIN-W-1FT	299-1100
Jumper Cable US 5 Pin 4ft	Connection between fixtures	MJCI-US-5PIN-W-4FT	299-1102
Leader Cable EU 5 Pin 3m	Power to first fixture of run	MLCI-EU-5PIN-W-3M	299-0101
Leader Cable EU 5 Pin 7.62m	Power to first fixture of run	MLCI-EU-5PIN-W-7.62M	299-0103
Jumper Cable EU 5 Pin 300mm	Connection between fixtures	MJCI-EU-5PIN-W-300MM	299-1101
Jumper Cable EU 5 Pin 1m	Connection between fixtures	MJCI-EU-5PIN-W-1M	299-1103
Terminator 5 Pin	Must be fixed to last fixture for safety	MTI-5PIN-W	299-2100
Mounting Track	Allows user to install fixtures in a continuous linear position.  Packaged in 5 4ft sections in total of 20ft.	MMC-20-TRACK-1-\$1-G	299-3200