


Client: _____ Project Name: _____
MODA Contact: _____ E-Mail: _____
SKU: _____ Type: _____ PO#: _____ Quantity: _____
Notes: _____



PHYSICAL

Dimensions	L: 7in (178mm)	W: 1 13/16in (46mm)
	L: 12 11/16in (322mm)	H: 1 3/16in (30mm)
	L: 48 23/32in (1237mm)	
Weight	6in: 0.21 lbs (0.10 kg) / 1ft: 0.38 lbs (0.17kg)/ 4ft: 1.22 lbs (0.55 kg)	
Applications	Cove, Accent, & Indirect General Illumination	
Construction	6063 Aluminum Body, Polycarbonate Self-Locking Mounting Bracket and Polycarbonate Optical Lens	
Ingress Protection	Dry/Damp Location IP52	
Thermal Management	Moda Aluminum Heat Sink	
Fixture Connections	Integral Male & Female Connectors	
Operating Temperature	-4°F ~ 149°F (-20°C ~ 65°C)	
Storage Temperature	-13°F ~ 158°F (-25°C ~ 70°C)	
Humidity	20-70% Non Condensing	

POWER CONSUMPTION

	120V AC (SO/HO)	240V AC (SO/HO)	277V AC (SO/HO)
6 Inch	2.8W / N/A	3.8W / N/A	4.2W / N/A
1 Foot	5W / 9.7W	5.9W / 10.1W	6.5W / 10.3W
4 Foot	18.3W / 36W	18.8W / 37.1W	19.2W / 38.2W

ELECTRICAL

Input Voltage	100-277V AC 50Hz/60Hz
Control	Electronic Low Voltage Reverse Phase Trailing Edge
Power Factor	≥ 0.98

OUTPUT

CCTs	1800K, 2200K, 2700K, 3000K, 3500K, 4000K, 6500K
Beam Angle	200°
CRI	95 - 98
SDCM	2-Step MacAdam Ellipse
Color Bin Tolerance	Zero Bin
Lumen Maintenance	90,000 Hours L70 @ 25°C 70,000 Hours L70 @ 50°C
Testing Data	Light Data LM-79-08 & LM-80-08

SPECIFICATIONS

	Lumens	Efficacy (120V)	Efficacy (240V)	Efficacy (277V)
6IN SO ELV	147 - 350	53 - 125	38 - 92	35 - 83
1FT SO ELV	294 - 728	58 - 145	49 - 123	45 - 112
1FT HO ELV	588 - 1400	60 - 144	58 - 138	57 - 135
4FT SO ELV	1176 - 2801	64 - 153	62 - 148	61 - 145
4FT HO ELV	2352 - 3915	65 - 155	63 - 150	61 - 146

MAX CONTINUOUS RUN

	120V AC	240V AC	277V AC
SO	120FT	240FT	240FT
HO	50FT	100FT	100FT

STANDARDS & CERTIFICATIONS



Certification	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, CCC, C-Tick, RoHS, & WEEE Compliant.
Class	1
Warranty	5 Year Limited Warranty

	FIXTURE	ORDERING NUMBER	QS*	PART NUMBER
ELV SO 6IN	Moda Mini Cove Interior Standard Output Silver ELV Dimming 1800K HCRI 6IN	MMCI-S-S-E-18H-6		090-0001
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 2200K HCRI 6IN	MMCI-S-S-E-22H-6		090-0003
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 2700K HCRI 6IN	MMCI-S-S-E-27H-6		090-0005
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 3000K HCRI 6IN	MMCI-S-S-E-30H-6		090-0006
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 3500K HCRI 6IN	MMCI-S-S-E-35H-6		090-0008
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 4000K HCRI 6IN	MMCI-S-S-E-40H-6		090-0009
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 6500K HCRI 6IN	MMCI-S-S-E-65H-6		090-0014
ELV SO 1FT	Moda Mini Cove Interior Standard Output Silver ELV Dimming 1800K HCRI 1FT	MMCI-S-S-E-18H-1		090-1001
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 2200K HCRI 1FT	MMCI-S-S-E-22H-1		090-1003
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 2700K HCRI 1FT	MMCI-S-S-E-27H-1	- - -	090-1005
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 3000K HCRI 1FT	MMCI-S-S-E-30H-1	- - -	090-1006
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 3500K HCRI 1FT	MMCI-S-S-E-35H-1	- - -	090-1008
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 4000K HCRI 1FT	MMCI-S-S-E-40H-1	- - -	090-1009
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 6500K HCRI 1FT	MMCI-S-S-E-65H-1		090-1014
ELV HO 1FT	Moda Mini Cove Interior High Output Silver ELV Dimming 1800K HCRI 1FT	MMCI-H-S-E-18H-1		090-1201
	Moda Mini Cove Interior High Output Silver ELV Dimming 2200K HCRI 1FT	MMCI-H-S-E-22H-1		090-1203
	Moda Mini Cove Interior High Output Silver ELV Dimming 2700K HCRI 1FT	MMCI-H-S-E-27H-1	- - -	090-1205
	Moda Mini Cove Interior High Output Silver ELV Dimming 3000K HCRI 1FT	MMCI-H-S-E-30H-1	- - -	090-1206
	Moda Mini Cove Interior High Output Silver ELV Dimming 3500K HCRI 1FT	MMCI-H-S-E-35H-1	- - -	090-1208
	Moda Mini Cove Interior High Output Silver ELV Dimming 4000K HCRI 1FT	MMCI-H-S-E-40H-1	- - -	090-1209
	Moda Mini Cove Interior High Output Silver ELV Dimming 6500K HCRI 1FT	MMCI-H-S-E-65H-1		090-1214
ELV SO 4FT	Moda Mini Cove Interior Standard Output Silver ELV Dimming 1800K HCRI 4FT	MMCI-S-S-E-18H-4		090-3001
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 2200K HCRI 4FT	MMCI-S-S-E-22H-4		090-3003
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 2700K HCRI 4FT	MMCI-S-S-E-27H-4	- - -	090-3005
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 3000K HCRI 4FT	MMCI-S-S-E-30H-4	- - -	090-3006
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 3500K HCRI 4FT	MMCI-S-S-E-35H-4	- - -	090-3008
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 4000K HCRI 4FT	MMCI-S-S-E-40H-4	- - -	090-3009
	Moda Mini Cove Interior Standard Output Silver ELV Dimming 6500K HCRI 4FT	MMCI-S-S-E-65H-4		090-3014
ELV HO 4FT	Moda Mini Cove Interior High Output Silver ELV Dimming 1800K HCRI 4FT	MMCI-H-S-E-18H-4		090-3201
	Moda Mini Cove Interior High Output Silver ELV Dimming 2200K HCRI 4FT	MMCI-H-S-E-22H-4		090-3203
	Moda Mini Cove Interior High Output Silver ELV Dimming 2700K HCRI 4FT	MMCI-H-S-E-27H-4	- - -	090-3205
	Moda Mini Cove Interior High Output Silver ELV Dimming 3000K HCRI 4FT	MMCI-H-S-E-30H-4	- - -	090-3206
	Moda Mini Cove Interior High Output Silver ELV Dimming 3500K HCRI 4FT	MMCI-H-S-E-35H-4	- - -	090-3208
	Moda Mini Cove Interior High Output Silver ELV Dimming 4000K HCRI 4FT	MMCI-H-S-E-40H-4	- - -	090-3209
	Moda Mini Cove Interior High Output Silver ELV Dimming 6500K HCRI 4FT	MMCI-H-S-E-65H-4		090-3214

*QuickShip

ACCESSORIES	DESCRIPTION	ORDERING NUMBER	QS*	PART NUMBER
Leader Cable US 3 Pin 10FT	Power to first fixture of run	MLCI-US-3PIN-W-10FT	— — —	299-0000
Leader Cable US 3 Pin 25FT	Power to first fixture of run	MLCI-US-3PIN-W-25FT	— — —	299-0002
Jumper Cable US 3 Pin 1FT	Connection between fixtures	MJCI-US-3PIN-W-1FT	— — —	299-1000
Jumper Cable US 3 Pin 4FT	Connection between fixtures	MJCI-US-3PIN-W-4FT	— — —	299-1002
Leader Cable EU 3 Pin 3M	Power to first fixture of run	MLCI-EU-3PIN-W-3M		299-0001
Leader Cable EU 3 Pin 10M	Power to first fixture of run	MLCI-EU-3PIN-W-10M		299-0003
Jumper Cable EU 3 Pin 300MM	Connection between fixtures	MJCI-EU-3PIN-W-300MM		299-1001
Jumper Cable EU 3 Pin 1M	Connection between fixtures	MJCI-EU-3PIN-W-1M		299-1003
Terminator 3 Pin	Must be fixed to last fixture for safety	MTI-3PIN-W	— — —	299-2000
Mounting Track	Allows user to install fixtures in a continuous linear position. Packaged in 5 4FT sections in total of 20FT.	MMC-20-TRACK-1-S1-G	— — —	299-3200
Mounting Track Connector	Joins two pieces of track together.	N/A	— — —	299-3202
Symmetric Louver 6IN	6IN Symmetric louver for light control	N/A		299-4220
Asymmetric Louver 6IN	6IN Asymmetric louver for light control	N/A		299-4221
Honeycomb Louver 6IN	6IN Honeycomb louver for light control	N/A		299-4222
Blade Louver 6IN	6IN Blade louver for light control	N/A		299-4223
Symmetric Louver 1FT	1FT Symmetric louver for light control	N/A	— — —	299-4230
Asymmetric Louver 1FT	1FT Asymmetric louver for light control	N/A	— — —	299-4231
Honeycomb Louver 1FT	1FT Honeycomb louver for light control	N/A	— — —	299-4232
Blade Louver 1FT	1FT Blade louver for light control	N/A	— — —	299-4233

CONTROLS	DESCRIPTION	ORDERING NUMBER	QS*	PART NUMBER
Bridge ¹ 2.0 US	Allows user to convert a 0-10V dimming signal to an ELV dimming signal. North American Model.	N/A	— — —	250-0000

*QuickShip