

Database structure

Mus Art Module

Version 1.0

Mus Art Booking Module

Revision History

V#	Date of Revision	Description of Change	Reason for Change	Affected Sections	By
1.0	10 Sep 2019				

Approval History

Version (x.y)	Prepared By	Reviewed By/Date	Approved By/Date
1.0			

Signed Off By

	Person	Date/Time	Signature
1			
2			
3			

TblUser

This is a data object used to hold information of users who are the administrators of this system

Data field name	Data type	Required	Note
Id	uniqueidentifier	Primary key	
UserName	Varchar(255)	Not null (default(""))	
FirstName	Varchar(100)	Not null (default(""))	
LastName	Varchar(100)	Not null (default(""))	
Email	Varchar(100)	Not null (default(""))	
Password	Varchar(250)	Not null (default(""))	
Birthday	Datetime	Not null (default(getdate()))	
Address	ntext	Not null (default(""))	
Phone	Varchar(20)	Not null (default(""))	
IsActivated	bit	Not null (default(0))	Active / Lock the account
IsDeleted	bit	Not null (default(0))	True to marked as soft delete
Avatar	Varchar(255)	Not null (default(""))	
CreatedUser	Varchar(30)	Not null (default(""))	Used to save the account of the person who created the data object
CreatedDate	Datetime	Not null (default(getdate()))	Used to save the date, time that an administrator account has created a data object
UpdatedUser	varchar(30)	Not null (default(""))	Used to save the account of the person who updated the data object
UpdatedDate	Datetime	Not null (default(getdate()))	Used to save the date, time that an administrator account has update a data object
LoginFailedNumber	int	Not null (default(0))	
PasswordChangeDate	Datetime	Not null default(getdate())	

IsChangePassword	bit	Not null default(0)	
ResetPasswordId	uniqueidentifier	Not null default(newid())	
ResetPasswordExpired	datetime	Not null default(getdate())	

TblUserGroup

This is a data object used to store information of the administrative user group. A user can belong to different groups, with access permissions being an integral part of the permissions of the groups to which the account belongs.

Data field name	Data type	Required	Description
Id	Uniqueidentifier	Primary key	
GroupName	Varchar(255)	Not null (default(''))	
Description	ntext	Not null (default(''))	
IsActivated	bit	Not null (default(0))	In case of inactivated, the accounts of the users belonging to the group will lose the corresponding rights.
IsDeleted	bit	Not null (default('0'))	
CreatedUser	Varchar(30)	Not null (default(''))	
CreatedDate	Datetime	Not null (default(getdate()))	
UpdatedUser	Varchar(30)	Not null (default(''))	
UpdatedDate	Datetime	Not null (default(getdate()))	

TblUserGroupLinked

This is the data object associated with the user data object and the user group data object.

Data field name	Data type	Required	Description
Id	Uniqueidentifier	Primary key	
UserId	Uniqueidentifier	Foreign key	
UserGroupId	Uniqueidentifier	Foreign key	

TblFunctionPage

This is a data object used to store information of functions corresponding to pages in the admin area that can be accessed by URL users.

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
FunctionCode	Varchar(255)	Not null (default(""))	
ParentCode	Varchar(255)	Not null (default(""))	Because the structure of administrative functions supports hierarchies of many levels, it is necessary to save the Code of the parent function. By default, without a parent, the highest level would be = 0
FunctionName	Varchar(255)	Not null (default(""))	
Description	ntext	Not null (default(""))	
DisplayOrder	int	Not null (default(-1))	Because the function pages need to be in order to display on the admin area menu, this information field should be sorted in ascending order. By default, the order will be -1 meaning that the data object will not have sort priority.
Url	Varchar(100)	Not null (default(""))	

Icon	Varchar(50)	Not null (default(""))	Icon to be displayed on the menu
IsActivated	bit	Not null (default(0))	
IsDeleted	bit	Not null (default(0))	

TblPermissions

This is the data object used to store user rights.

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
FunctionPageId	Varchar(50)	Foreign key	
PermissionsName	Varchar(100)	Not null (default(""))	
Action	byte	Not null (default(0))	1: view 2: edit & create 3: delete

TblPermissionsGroup

This is the data object used to link the user rights data object to the user group data object.

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
UserGroupId	varchar(50)		
PermissionsId	varchar(50)		

TblSpaceInformation

This is a data object used to store information of a space.

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
LockId	Uniqueidentifier	Not null default(newid())	
FloorId	uniqueidentifier	Not null default(newid())	
SpaceName	varchar(255)	Not null (default(""))	
Summary	varchar(1000)	Not null default("")	
Description	ntext	Not null default("")	
SlugUrl	varchar(255)	Not null default("")	
AllowForBooking	bit	Not null default(0)	
DisplayOrder	int	Not null default(0)	
ImageUrl	varchar(255)	Not null default("")	
Coords	ntext	Not null default("")	
Size	varchar(50)	Not null default("")	
Capacity	varchar(50)	Not null default("")	
UnitPrice	decimal(18,2)	Not null default(0)	
SeoTitle	nvarchar(500)	Not null default("")	
SeoKeyword	nvarchar(500)	Not null default("")	
SeoDescription	nvarchar(2000)	Not null default("")	
IsActivated	bit	Not null (default(0))	Activated/ InActive
IsDeleted	bit	Not null (default(0))	
CreatedUser	varchar(30)	Not null (default (""))	
CreatedDate	Datetime	Not null (default getdate())	

UpdatedUser	varchar(30)	Not null (default (""))	
UpdatedDate	Datetime	Not null (default getdate())	

TblSpaceType

Space type tags

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
Name	varchar(250)	Not null (default(""))	
IsActivated	bit	Not null default(1)	
IsDeleted	bit	Not null default(0)	
CreatedUser	varchar(30)	Not null default("")	
CreatedDate	datetime	Not null default(getdate())	
UpdatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null (default(""))	

TblSpaceTypeLinked

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key default(newid())	
SpaceId	uniqueidentifier	Not null default(newid())	
SpaceTypeId	uniqueidentifier	Not null default(newid())	

TblSpaceImage

Data field name	Data type	Required	Description
-----------------	-----------	----------	-------------

Id	uniqueidentifier	Primary key	
SpaceId	uniqueidentifier	Not null default(newid())	
ImageUrl	varchar(250)	Not null default("")	
Alt	varchar(250)	Not null default("")	
DisplayOrder	int	Not null default(0)	
CreatedUser	varchar(30)	Not null default("")	
CreatedDate	Datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null (default (""))	
UpdatedDate	Datetime	Not null (default getdate())	

TblSpacePricing

Prices per space are by member type and pricing category type

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
SpaceId	uniqueidentifier	Not null default(newid())	
UnitPrice	decimal(18,2)	Not null default(0)	
PricingTimeSlotId	uniqueidentifier	Not null default(newid())	
IsActivated	bit	Not null default(0)	Activated/ InActive
IsDeleted	bit	Not null default(0)	
CreatedDate	datetime	Not null default(getdate())	
CreatedUser	varchar(30)	Not null default("")	
UpdatedDate	datetime	Not null default getdate()	

UpdatedUser	varchar(30)	Not null default("")	
-------------	-------------	----------------------	--

TblAddOnsInformation

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
AddOnsName	nvarchar(250)	Not null default("")	
Summary	nvarchar(1000)	Not null default("")	
Description	ntext	Not null default("")	
ImageUrl	varchar(250)	Not null default("")	
AllowForBooking	bit	Not null default(0)	
DisplayOrder	int	Not null default(0)	
Quantity	int	Not null default(0)	
Spacelds	varchar(4000)	Not null default("")	
UnitPrice	decimal(18,2)	Not null default(0)	
PriceType	varchar(30)	Not null default("")	
IsActivated	bit	Not null default(0)	
IsDeleted	bit	Not null default(0)	
CreatedUser	varchar(30)	Not null default("")	
CreatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null default("")	
UpdatedDate	datetime	Not null default(getdate())	

TblAddOnsImage

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	

AddOnsId	uniqueidentifier	Not null default(newid())	
ImageUrl	varchar(250)	Not null default("")	
Alt	varchar(250)	Not null default("")	
DisplayOrder	int	Not null default(0)	
CreatedUser	varchar(30)	Not null default("")	
CreatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null default("")	
UpdatedDate	datetime	Not null default(getdate())	

TblAddOnsPricing

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
AddOnsId	uniqueidentifier	Not null default(newid())	
UnitPrice	decimal(18,2)	Not null default(0)	
PricingTimeSlotId	uniqueidentifier	Not null default(newid())	
IsActivated	bit	Not null default(0)	
IsDeleted	bit	Not null default(0)	
CreatedUser	varchar(30)	Not null default("")	
CreatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null default("")	
UpdatedDate	datetime	Not null default(getdate())	

TblAddonArchive

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key not null default(newid())	
BookingId	uniqueidentifier	Not null default(newid())	
UsageDate	datetime	Not null default(getdate())	
AddonId	uniqueidentifier	Not null default(newid())	
FromHour	time(7)	Not null default(00:00:000)	
ToHour	time(7)	Not null default(00:00:000)	
Quantity	int	Not null default(0)	
IsSuccess	bit	Not null default(0)	
BookingAdditionalId	uniqueidentifier	Not null default(newid())	

TblBooking

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
SpaceId	uniqueidentifier	Not null default(newid())	
BookingCode	varchar(100)	Not null default("")	
BookingDate	datetime	Not null default(getdate())	
UsageDate	datetime	Not null default(getdate())	
CustomerId	uniqueidentifier	Not null newid()	

MemberTypeName	varchar(250)	Not null default("")	
Discount	decimal(18, 2)	Not null default(0)	
TotalPrice	decimal(18,2)	Not null default(0)	
PaymentPrice	decimal(18,2)	Not null default(0)	
PaidPrice	decimal(18,2)	Not null default(0)	
Status	varchar(20)	Not null default("")	
ProcessorNote	ntext	Not null default("")	
Note	ntext	Not null default("")	
IsDeleted	bit	Not null default(0)	
UpdatedDate	datetime	Not null default getdate()	
UpdatedUser	varchar(30)	Not null default("")	

TblBookingDetail

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
BookingId	uniqueidentifier	Not null default(newid())	
PricingCategoryName	varchar(250)	Not null default("")	
FromHour	time(7)	Not null default(00:00:000)	
ToHour	time(7)	Not null default(00:00:000)	
UnitPrice	decimal(18,2)	Not null default(0)	

TblBookingAdditional

Data field name	Data type	Required	Description
-----------------	-----------	----------	-------------

Id	uniqueidentifier	Primary key	
BookingId	uniqueidentifier	Not null default(newid())	
Quantity	int	Not null default(0)	
AddOnsId	uniqueidentifier	Not null default(newid())	
FromHour	time(7)	Not null default(00:00:000)	
ToHour	time(7)	Not null default(00:00:000)	
UnitPrice	decimal(18,2)	Not null default(0)	
PricingCategoryName	varchar(250)	Not null default("")	

TblBookingArchive

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key not null default(newid())	
BookingId	uniqueidentifier	Not null default(newid())	
UsageDate	datetime	Not null default(getdate())	
SpaceId	uniqueidentifier	Not null default(newid())	
FromHour	time(7)	Not null default(00:00:000)	
ToHour	time(7)	Not null default(00:00:000)	
IsSuccess	bit	Not null default(0)	
BookingDetailId	uniqueidentifier	Not null default(newid())	

TblPaymentHistory

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key not null default(newid())	
LinkId	uniqueidentifier	Not null default(newid())	
TransactionDate	datetime	Not null default(getdate())	
TransactionId	varchar(50)	Not null default("")	
PaymentStatus	varchar(20)	Not null default("")	
PaymentType	varchar(20)	Not null default("")	
PaymentPrice	decimal(18,2)	Not null default(0)	
ResponseCode	varchar(50)	Not null default("")	
ResponseLog	ntext	Not null default("")	
IsDeleted	bit	Not null default(0)	
UpdatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null default("")	
SystemTraceAuditNumber	varchar(30)	Not null default("")	
ReceiptNumber	varchar(30)	Not null default("")	
PaymentReference	varchar(50)	Not null default("")	
MerchantId	varchar(50)	Not null default("")	
TerminalId	varchar(50)	Not null default("")	
PaymentPlatform	varchar(50)	Not null default("")	
PaymentDescription	ntext	Not null default("")	
PaymentPriceRequest	decimal(18,2)	Not null default(0)	

SessionId	varchar(150)	Not null default("")	
LinkType	varchar(36)	Not null default("")	
ReferenceId	uniqueidentifier	Not null default(newid())	

TblPaymentHistoryQuery

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
PaymentHistoryId	uniqueidentifier	Not null default(newid())	
CreatedDate	datetime	Not null default(getdate())	
ResponseCode	varchar(15)	Not null default("")	
ResponseLog	ntext	Not null default("")	

TblCustomer

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
Type	varchar(20)	Not null default("")	Guest/ Member
CreatedDate	datetime	Not null default(getdate())	

TblGuestDetail

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	

CustomerId	uniqueidentifier	Not null default(newid())	
FullName	nvarchar(100)	Not null default("")	
Email	varchar(100)	Not null default("")	
Phone	varchar(30)	Not null default("")	
CustomerRoleId	uniqueidentifier	Not null default(newid())	

TblMemberShipDetail

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
CustomerId	uniqueidentifier	Not null default(newid())	
MemberTypeId	uniqueidentifier	Not null default(newid())	
AvatarUrl	varchar(250)	Not null default("")	
Username	varchar(100)	Not null default("")	Username can be your name or email at registration
Password	varchar(250)	Not null default("")	
FullName	nvarchar(100)	Not null default("")	
Email	varchar(100)	Not null default("")	
Phone	varchar(30)	Not null default("")	
FacebookId	varchar(50)	Not null default("")	
GoogleId	varchar(50)	Not null default("")	
DepositRemaining	decimal(18,2)	Not null default(0)	
TopUpWhenRemaining	decimal(18,2)	Not null default(0)	
CustomerRoleId	uniqueidentifier	Not null default(newid())	
ChangeId	uniqueidentifier	Not null default(newid())	

DateChange	datetime	Not null default(getdate())	
IsActivated	bit	Not null (default(0))	Activated/ Inactive
IsDeleted	bit	Not null (default(0))	
UpdatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null default("")	

TblCustomerRole

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
Name	nvarchar(250)	Not null default("")	
IsActivated	bit	Not null default(0)	
IsDeleted	bit	Not null default(0)	
CreatedUser	varchar(30)	Not null default("")	
CreatedDate	datetime	Not null default(getdate())	
UpdatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null (default(""))	

TblLockUser

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
Username	varchar(30)	Not null (default(""))	

Password	varchar(50)	Not null (default(""))	
ClientId	varchar(50)	Not null default("")	
IsDeleted	bit	Not null default(0)	
CreatedDate	datetime	Not null default(getdate())	
UpdatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null (default(""))	

TblLock

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
LockUser	uniqueidentifier	Not null (default(newid()))	
LockId	int	Not null (default(0))	
LockName	nvarchar(250)	Not null default("")	
NoKeyPassword	varchar(20)	Not null (default(""))	
LockSound	int	Not null default(0)	
ElectricQuantity	int	Not null default(0)	
ClientId	varchar(50)	Not null default("")	
LockUpdateDate	datetime	Not null default(getdate())	
LockLog	ntext	Not null default("")	
SyncedDate	datetime	Not null default(getdate())	
AutoLockTime	int	Not null default(0)	
KeyBoardPasswordVersion	int	Not null default(0)	
LockState	int	Not null default(0)	

IsDeleted	bit	Not null default(0)	
-----------	-----	---------------------	--

TblLockRecord

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
ServerDate	datetime	Not null (default(getdate()))	
RecordType	int	Not null (default(0))	
Success	int	Not null default(0)	
KeyboardPwd	varchar(20)	Not null (default(""))	
UserName	varchar(30)	Not null default("")	
LockDate	datetime	Not null default(getdate())	
LockId	uniqueidentifier	Not null default(newid())	
LogData	ntext	Not null default("")	

TblPasscode

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
LockId	uniqueidentifier	Not null (default newid())	
BookingId	uniqueidentifier	Not null default(newid())	
PasscodeName	nvarchar(250)	Not null default("")	
PasscodeType	int	Not null (default(0))	
StartDate	datetime	Not null default(getdate())	

EndDate	datetime	Not null default(getdate())	
KeyBoardPasscodeId	int	Not null default(0)	
KeyBoardPassword	varchar(20)	Not null default("")	
CreatedDate	datetime	Not null default(getdate())	
CreatedUser	varchar(30)	Not null default("")	
UpdatedDate	datetime	Not null default getdate())	
UpdatedUser	varchar(30)	Not null default("")	

TblTestimonial / OurTeams

Testimonial or Our teams on website

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
Name	nvarchar(250)	Not null (default(""))	
ImageUrl	varchar(250)	Not null default("")	
Body	ntext	Not null default("")	
DisplayOrder	int	Not null (default(0))	
Type	varchar(20)	Not null default("")	Testimonials/ OurTeams
IsActivated	bit	Not null default(0)	
IsDeleted	bit	Not null default(0)	
CreatedUser	varchar(30)	Not null default("")	
CreatedDate	datetime	Not null default(getdate())	
UpdatedDate	datetime	Not null default getdate())	
UpdatedUser	varchar(30)	Not null default("")	

TblCategory

Article category

Data field name	Data type	Required	Description
Id	uniqueidentifier	Default(newid()) Primary key	
Title	nvarchar(250)	Not null default("")	
ImageUrl	varchar(250)	Not null default("")	
SlugUrl	varchar(250)	Not null default("")	
CategoryType	varchar(20)	Not null default("")	
SeoTitle	nvarchar(500)	Not null default("")	
SeoKeyword	nvarchar(500)	Not null default("")	
SeoDescription	nvarchar(2000)	Not null default("")	
ParentId	uniqueidentifier	Not null default(newid())	
DisplayOrder	Int	Not null default(0)	
IsHighlight	bit	Not null default(0)	
IsActivated	bit	Not null default(0)	
IsDeteled	bit	Not null default(0)	
CreatedUser	varchar(30)	Not null default("")	
CreatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null (default (""))	
UpdatedDate	Datetime	Not null (default getdate())	

TblArticle

Article

Data field name	Data type	Required	Description
Id	uniqueidentifier	default(newid()) Primary key	
Title	nvarchar(250)	Not null default("")	
Summary	nvarchar(1000)	Not null default("")	
Content	ntext	Not null default("")	
ImageUrl	varchar(250)	Not null default("")	
SlugUrl	varchar(250)	Not null default("")	
Tags	nvarchar(1000)	Not null default("")	
IsHighlight	bit	Not null default(0)	
SeoTitle	Nvarchar(500)	Not null default("")	
SeoKeyword	Nvarchar(500)	Not null default("")	
SeoDescription	Nvarchar(2000)	Not null default("")	
IsActivated	bit	Not null default(0)	
IsDeleted	Bit	Not null default(0)	
CreatedDate	datetime	Not null default(getdate())	
CreatedUser	varchar(30)	Not null default("")	
UpdatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null default("")	

TblArticleMapping

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key default(newid())	
CategoryId	uniqueidentifier	Not null default(newid())	
ArticleId	uniqueidentifier	Not null default(newid())	
DisplayOrder	int	Not null default(0)	

TblEvent

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
Title	nvarchar(250)	Not null default("")	
Summary	nvarchar(1000)	Not null default("")	
Content	ntext	Not null default("")	
ImageUrl	varchar(250)	Not null default("")	
SlugUrl	varchar(250)	Not null default("")	
Tags	nvarchar(1000)	Not null default("")	
IsHighlight	bit	Not null default(0)	
EventFromDate	datetime	Not null default(getdate())	
EventToDate	datetime	Not null default(getdate())	

SeoTitle	Nvarchar(500)	Not null default("")	
SeoKeyword	Nvarchar(500)	Not null default("")	
SeoDescription	Nvarchar(2000)	Not null default("")	
IsActivated	bit	Not null default(0)	
IsDeleted	Bit	Not null default(0)	
CreatedDate	datetime	Not null default(getdate())	
CreatedUser	varchar(30)	Not null default("")	
UpdatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null default("")	

TblTags

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key default(newid())	
TagsName	nvarchar(255)	Not null default("")	
SlugUrl	varchar(250)	Not null default("")	
IsActivated	bit	Not null default(0)	
IsDeleted	bit	Not null default(0)	

TblSlide

Slide home page

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key default(newid())	

ImageUrl	varchar(255)	Not null default('')	
Title	nvarchar(250)	Not null default('')	
Description	nvarchar(500)	Not null default('')	
LinkUrl	varchar(250)	Not null default('')	
DisplayOrder	int	Not null default(0)	
LinkType	varchar(20)	Not null default('')	
IsActivated	bit	Not null default(0)	
IsDeleted	bit	Not null default(0)	
CreatedDate	datetime	Not null default(getdate())	
CreatedUser	varchar(30)	Not null default('')	
UpdatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null default('')	

TblPartner

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
Name	nvarchar(250)	Not null (default(''))	
Logo	varchar(250)	Not null default('')	
Link	varchar(250)	Not null default('')	
DisplayOrder	int	Not null (default(0))	
IsActivated	bit	Not null default(0)	
IsDeleted	bit	Not null default(0)	

CreatedUser	varchar(30)	Not null default('')	
CreatedDate	datetime	Not null default(getdate())	
UpdatedDate	datetime	Not null default getdate())	
UpdatedUser	varchar(30)	Not null default('')	

TblPricingTimeSlot

Set up price lists for time periods. 7am - 9am -> Normal hours, 9h - 24h -> Peak hours

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
FromHour	time	Not null default(00:00:000)	
ToHour	time	Not null default(00:00:000)	
IsActivated	bit	Not null default(1)	
IsDeleted	bit	Not null default(0)	
CreatedUser	varchar(30)	Not null default('')	
CreatedDate	datetime	Not null default(getdate())	
UpdatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null (default(''))	

TblContact

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	

Title	nvarchar(250)	Not null default("")	
FullName	nvarchar(100)	Not null (default(""))	
Email	varchar(100)	Not null default("")	
Phone	varchar(20)	Not null default("")	
Content	ntext	Not null default("")	
Status	varchar(20)	Not null default("")	
ContactDate	datetime	Not null default(getdate())	
Handler	varchar(30)	Not null default("")	
UpdatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null (default(""))	

TblMemberType

Thiết lập loại thành viên Basic Member, Premium member

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
Name	varchar(250)	Not null (default(""))	
Deposit	decimal(18,2)	Not null default(0)	
Discount	decimal(18,2)	Not null default(0)	
TopUpWhenRemaining	decimal(18,2)	Not null default(0)	
Description	ntext	Not null default("")	
IsActivated	bit	Not null default(1)	
IsDeleted	bit	Not null default(0)	
CreatedDate	datetime	Not null default(getdate())	
CreatedUser	varchar(30)	Not null (default(""))	

UpdatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null (default(""))	

TblFloor

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
Name	varchar(250)	Not null (default(""))	
DisplayOrder	int	Not null default(0)	
FloorImageUrl	varchar(250)	Not null default("")	
IsActivated	bit	Not null default(1)	
IsDeleted	bit	Not null default(0)	
CreatedDate	datetime	Not null default(getdate())	
CreatedUser	varchar(30)	Not null (default(""))	
UpdatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null (default(""))	

TblEmailTemplate

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key not null default(newid())	
TemplateName	varchar(250)	Not null default("")	
Subject	ntext	Not null default("")	
Body	ntext	Not null default("")	
CCEmail	varchar(250)	Not null default("")	

BCCEmail	varchar(250)	Not null default("")	
IsActivated	varchar(30)	Not null default("")	
IsDeleted	datetime	Not null default(getdate())	
CreatedDate	datetime	Not null default(getdate())	
CreatedUser	varchar(30)	Not null (default(""))	
UpdatedDate	datetime	Not null default(getdate())	
UpdatedUser	varchar(30)	Not null (default(""))	

TblEmailSending

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key not null default(newid())	
GuestId	uniqueidentifier	Not null default(newid())	
Email	varchar(100)	Not null default("")	
SubjectEmail	ntext	Not null default("")	
Body	ntext	Not null default("")	
SentUser	varchar(30)	Not null default("")	
SentDate	datetime	Not null default(getdate())	
IsSeen	bit	Not null default(0)	
SeenDate	Datetime	Not null default(getdate())	

TblEmailConfiguration

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key not null default(newid())	
EmailTemplateId	uniqueidentifier	Not null default(newid())	
ReferentId	varchar(50)	Not null default("")	
TemplateType	varchar(50)	Not null default("")	
TemplateKey	varchar(50)	Not null default("")	
UpdatedUser	varchar(30)	Not null default("")	
UpdatedDate	datetime	Not null default(getdate())	

TblStaticPage

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
Title	varchar(250)	Not null default("")	
Type	varchar(30)	Not null default("")	
Content	ntext	Not null default("")	
SeoTitle	nvarchar(500)	Not null default("")	
SeoKeyword	nvarchar(500)	Not null default("")	
SeoDescription	nvarchar(2000)	Not null default("")	
ImageShare	varchar(250)	Not null default("")	
IsDeleted	bit	Not null default(0)	
UpdatedUser	varchar(30)	Not null default("")	
UpdatedDate	datetime	Not null default(getdate())	

TblToken

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key not null default(newid())	
UserId	uniqueidentifier	Not null default(newid())	
CreateDate	datetime	Not null default(getdate())	
token	varchar(500)	Not null default("")	
Password	varchar(255)	Not null default("")	
refreshToken	varchar(250)	Not null default("")	
AccountType	varchar(20)	Not null default("")	
TokenExpired	datetime	Not null default(getdate())	
RefreshExpired	datetime	Not null default(getdate())	

TblSystemConfiguration

This is a data object used to store wide system configurations.

Data field name	Data type	Required	Description
Id	uniqueidentifier	Primary key	
SettingName	varchar(255)	Not null default("")	
SettingValue	ntext	Not null default("")	
Description	ntext	Not null default("")	
UpdatedUser	varchar(30)	Not null default("")	
UpdatedDate	datetime	Not null default(getdate())	

