

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/224506226>

Stability Analysis of Positive Systems With Bounded Time-Varying Delays

Article in *Circuits and Systems II: Express Briefs, IEEE Transactions on* · August 2009

DOI: 10.1109/TCSII.2009.2023305 · Source: IEEE Xplore

CITATIONS

143

READS

184

3 authors:



Xingwen Liu

Southwest University for Nationalities

77 PUBLICATIONS 1,789 CITATIONS

[SEE PROFILE](#)



Wensheng Yu

Chinese Academy of Sciences

99 PUBLICATIONS 1,254 CITATIONS

[SEE PROFILE](#)



Long Wang

Peking University

524 PUBLICATIONS 18,502 CITATIONS

[SEE PROFILE](#)

Some of the authors of this publication are also working on these related projects:



Evolutionary games on interdependent networks [View project](#)



HCV NS5A [View project](#)

Stability Analysis of Positive Systems With Bounded Time-Varying Delays

Xingwen Liu, Wensheng Yu, and Long Wang

Abstract—This brief addresses stability of the discrete-time positive systems with bounded time-varying delays and establishes some necessary and sufficient conditions for asymptotic stability of such systems. It turns out that, for any bounded time-varying delays, the magnitude of the delays does not affect the stability of these systems. In other words, system stability is completely determined by the system matrices.

Index Terms—Linear copositive Lyapunov function (functional), positive linear system, stability, time-varying delays.

I. INTRODUCTION

MANY physical systems in the real world involve variables that have nonnegative sign, e.g., population levels, absolute temperature, and concentration of substances. Such systems are referred to as positive systems [1]–[3], which means that their states and outputs are nonnegative whenever the initial conditions and inputs are nonnegative. The states of positive systems are confined within a “cone” located in the positive orthant rather than in the whole space \mathbb{R}^n . This feature makes analysis and synthesis of positive systems a challenging and interesting job [4]–[8].

Stability is one of the most important properties of dynamic systems, and a massive literature has been concentrated on this topic for positive systems. Reference [9] employed a characteristic equation to present some sufficient stability conditions for a class of delayed positive systems. Reference [10] established some necessary and sufficient stability criteria by using a quadratic diagonal Lyapunov function, and [11] proposed some necessary and sufficient stability conditions for

positive systems by means of a linear copositive Lyapunov function. The approach of the linear copositive Lyapunov function captures the nature of positivity; thus, it is widely used in research on positive systems [12]–[16]. References [12] and [15] established necessary and sufficient stability criteria for positive systems without delays. Reference [16] obtained a necessary and sufficient stability condition for continuous-time positive systems with delays. This result was then improved to design positive observers for delayed continuous-time positive systems in [17].

All the aforementioned references are concerned with positive systems without delays or with constant delays. In fact, many positive systems have time-varying delays. One example is the nonnegative and compartmental systems (a kind of positive systems playing a key role in biological and medical sciences) discussed in [16], where τ denotes the time it takes for the mass to flow from one subsystem to another. In usual case, τ is a function of time, i.e., it is time varying. Generally speaking, time-varying delays are more important and universal in real engineering processes and have more complex impacts on system dynamics than constant delays. For general dynamic systems with time-varying delays, the stability problem has extensively been studied (see, for example, [18]–[21]). To our knowledge, however, little attention has been paid to the same problem of positive systems with time-varying delays. Recently, it has been shown that the stability of continuous- or discrete-time positive systems with constant delays has nothing to do with the magnitude of the delays [16], [17], [22], [23]. Thus, a question immediately arises: Does a similar conclusion hold for positive systems with time-varying delays? As the first step to seek the answer, this brief investigates the stability of the discrete-time positive system with bounded time-varying delays and provides a positive answer.

The idea of this brief is original. We do not directly treat the original systems with time-varying delays, but the corresponding systems with constant delays. Hence, appropriate relations between the two types of systems must be found out, which should bridge the gap between their stability. As shown in Section III, such important relations do exist. This enables us to establish some necessary and sufficient conditions for positive systems with time-varying delays.

The remainder of this brief is organized as follows: In Section II, necessary preliminaries are presented, and some lemmas are provided. Section III proposes the necessary and sufficient stability criteria for discrete-time positive systems with time-varying delays. Section IV provides an example, and Section V concludes this brief.

Manuscript received September 24, 2008; revised February 10, 2009. First published June 16, 2009; current version published July 17, 2009. This work was supported in part by the Key Youth Projects of Southwest University for Nationalities of China and the Chinese Ministry of Education mobility program supporting doctoral students from domestic universities to visit the Chinese Academy of Sciences, by the National Natural Science Foundation of China under Grants 60674050, 60736022, 60874010, 60621001, and 60528007, by the Overseas Outstanding Young Researcher Foundation of the Chinese Academy of Sciences, by the National 863 Program under Grant 2006AA04Z258, and by the 11-5 Project under Grant A2120061303. This paper was recommended by Associate Editor B. Jean-Pierre.

X. Liu is with the Institute of Electrical and Information Engineering, Southwest University for Nationalities, Chengdu 610041, China (e-mail: xingwenliu@gmail.com).

W. Yu is with the Key Laboratory of Complex Systems and Intelligence Science, Institute of Automation, Chinese Academy of Sciences, Beijing 100080, China, and also with Shanghai Key Laboratory of Trustworthy Computing, East China Normal University, Shanghai 200062, China.

L. Wang is with the Center for Systems and Control, College of Engineering, and Key Laboratory of Machine Perception (Ministry of Education), Peking University, Beijing 100871, China.

Digital Object Identifier 10.1109/TCSII.2009.2023305

II. PROBLEM STATEMENTS AND PRELIMINARIES

Nomenclature

$A \succeq 0$ ($\preceq 0$)	All elements of matrix A are nonnegative (nonpositive).
$A \succ 0$ ($\prec 0$)	All elements of matrix A are positive (negative).
$A > 0$ (< 0)	Matrix A is a symmetric positive (negative) definite matrix.
A^T (A^{-1})	Transpose (inverse) of matrix A .
\mathbb{R} ($\mathbb{R}_{0,+}$, \mathbb{R}_+)	Set of all real (nonnegative, positive) numbers.
$\ \mathbf{x}\ $	Norm of vector \mathbf{x} .
\mathbb{R}^n ($\mathbb{R}_{0,+}^n$, \mathbb{R}_+^n)	n -dimensional real (nonnegative, positive) vector space.
$\mathbb{R}^{n \times m}$ ($\mathbb{R}_{0,+}^{n \times m}$)	Set of all real (nonnegative) matrices of $(n \times m)$ -dimension.
\mathbb{N}	$\{1, 2, 3, \dots\}$.
\mathbb{N}_0	$\{0\} \cup \mathbb{N}$.

The following notation of matrices will be used throughout this brief: $A_i = [a_{jl}^{(i)}]$. The dimensions of matrices and vectors will not explicitly be mentioned if clear from context. For simplicity, let $\underline{\mathbf{p}} = \{1, 2, \dots, p\}$ and $\underline{\mathbf{p}}_0 = \{0\} \cup \underline{\mathbf{p}}$, where p is an arbitrary positive integer.

Consider the system

$$\mathbf{x}(t+1) = A\mathbf{x}(t), \quad t \in \mathbb{N}_0 \quad (1)$$

where $\mathbf{x}(t) \in \mathbb{R}^n$ is the state vector, and $A \in \mathbb{R}^{n \times n}$ is the system matrix.

Definition 1 [10]: System (1) is said to be positive if and only if for any initial condition $\mathbf{x}(0) \succeq 0$, the corresponding trajectory $\mathbf{x}(t) \succeq 0$ holds for all $t \in \mathbb{N}$.

Definition 2: A square matrix A is called a Schur matrix if and only if system (1) is asymptotically stable. Equivalently, all the eigenvalues of A lie inside the unit circle on the complex plane.

Lemma 1 [12], [15]: A matrix $A \succeq 0$ is a Schur matrix if and only if there exists $\boldsymbol{\lambda} \in \mathbb{R}_+^n$ such that $(A - I)\boldsymbol{\lambda} \prec 0$.

Lemma 2 [10]: A matrix $A \succeq 0$ is a Schur matrix if and only if there exists a diagonal matrix $P > 0$ such that $A^T P A - P < 0$.

Consider the following delayed system:

$$\begin{aligned} \mathbf{x}(t+1) &= A_0 \mathbf{x}(t) + \sum_{i=1}^p A_i \mathbf{x}(t - \tau_i(t)), \quad t \in \mathbb{N}_0 \\ \mathbf{x}(t) &= \boldsymbol{\varphi}(t) \succeq 0, \quad t = -\tau, \dots, 0 \end{aligned} \quad (2)$$

where $A_i \in \mathbb{R}^{n \times n}$ for $i \in \underline{\mathbf{p}}_0$, $\tau = \max_{i \in \underline{\mathbf{p}}} \{\sup_{t \geq 0} \tau_i(t)\}$, $\tau_i(t) \in \mathbb{N}_0$, and $\boldsymbol{\varphi}: \{-\tau, \dots, 0\} \rightarrow \mathbb{R}_{0,+}^n$ is the vector-valued initial function.

Definition 3: System (2) is said to be positive if and only if for any initial condition $\boldsymbol{\varphi}(\cdot) \succeq 0$, the corresponding trajectory $\mathbf{x}(t) \succeq 0$ holds for all $t \in \mathbb{N}$.

Lemma 3: System (2) is positive if and only if $A_i \succeq 0$, $i \in \underline{\mathbf{p}}_0$.

Proof: Represent (2) componentwise, i.e.,

$$x_l(t+1) = \sum_{j=1}^n a_{lj}^{(0)} x_j(t) + \sum_{i=1}^p \sum_{j=1}^n a_{lj}^{(i)} x_j(t - \tau_i(t)) \quad (3)$$

where $x_l(\cdot)$ is the l th component of vector $\mathbf{x}(\cdot)$.

Sufficiency: Assume that $A_i \succeq 0$ for $i \in \underline{\mathbf{p}}_0$ and that the initial condition $\boldsymbol{\varphi}(\cdot) \succeq 0$. Then, we have $x_l(1) \geq 0$ by (3), and therefore, $x_l(t) \geq 0$ for $-\tau \leq t \leq 1$.

Assume for induction that $x_l(t) \geq 0$ for $-\tau \leq t \leq k$ with $k \in \mathbb{N}$. Then, (3) implies that $x_l(k+1) \geq 0$; thus, $x_l(t) \geq 0$ for $-\tau \leq t \leq k+1$.

By induction, $x_l(t) \geq 0$ for all $t \in \mathbb{N}$. Hence, system (2) is positive.

Necessity: Suppose that system (2) is positive. By Definition 3, $\mathbf{x}(t) \succeq 0$ for all $t \in \mathbb{N}$ if $\boldsymbol{\varphi}(\cdot) \succeq 0$.

Assume for contradiction that there exists $q \in \underline{\mathbf{p}}_0$ such that $A_q \not\succeq 0$ does not hold. Thus, there exists an element $a_{kg}^{(q)} < 0$. Denote $\boldsymbol{\varphi}(-\tau_i(0)) = [\varphi_{i1}, \varphi_{i2}, \dots, \varphi_{in}]^T$ and $\mathbf{x}(0) = [\varphi_{01}, \varphi_{02}, \dots, \varphi_{0n}]^T$. Choose φ_{ij} ($i \in \underline{\mathbf{p}}_0, j \in \underline{\mathbf{n}}$) such that $\varphi_{qg} > 0$ and $\varphi_{ij} = 0$ for all $i \neq q$ or $j \neq g$. It follows from (3) that

$$x_l(1) = \sum_{i=0}^p \sum_{j=1}^n a_{lj}^{(i)} \varphi_{ij} = a_{kg}^{(q)} \varphi_{qg} < 0$$

which contradicts the assumption that $\mathbf{x}(t) \succeq 0$ for all $t \in \mathbb{N}$. Therefore, $A_i \succeq 0$ for all $i \in \underline{\mathbf{p}}_0$. ■

Lemma 4: Assume that system (2) is positive. Let $\mathbf{x}_a(t)$ and $\mathbf{x}_b(t)$ be the trajectories solution of (2) under the initial conditions $\boldsymbol{\varphi}_a(\cdot)$ and $\boldsymbol{\varphi}_b(\cdot)$, respectively. Then, $\boldsymbol{\varphi}_a(\cdot) \preceq \boldsymbol{\varphi}_b(\cdot)$ implies that $\mathbf{x}_a(t) \preceq \mathbf{x}_b(t)$ for all $t \in \mathbb{N}$.

Proof: It is not difficult to see that $\mathbf{x}(t) = \mathbf{x}_b(t) - \mathbf{x}_a(t)$ is the solution to system (2) under the initial condition $\boldsymbol{\varphi}(\cdot) = \boldsymbol{\varphi}_b(\cdot) - \boldsymbol{\varphi}_a(\cdot) \succeq 0$. Since (2) is positive, $\mathbf{x}(t) \succeq 0$ for all $t \in \mathbb{N}$. ■

III. MAIN RESULTS

The purpose of this section is to establish asymptotic stability criteria for discrete-time positive systems with bounded time-varying delays. Consider the following system:

$$\begin{aligned} \mathbf{x}(t+1) &= A_0 \mathbf{x}(t) + \sum_{i=1}^p A_i \mathbf{x}(t - \tau_i(t)), \quad t \in \mathbb{N}_0 \\ \mathbf{x}(t) &= \boldsymbol{\varphi}(t) \succeq 0, \quad t = -\tau, \dots, 0 \end{aligned} \quad (4)$$

where $A_i \in \mathbb{R}_{0,+}^{n \times n}$ for $i \in \underline{\mathbf{p}}_0$, and the delays $\tau_i(t) \in \mathbb{N}_0$ satisfy

$$0 \leq \alpha_i \leq \tau_i(t) \leq \tau_i, \quad t \in \mathbb{N}_0 \quad (5)$$

with constants $\alpha_i \in \mathbb{N}_0$ and $\tau_i \in \mathbb{N}$, and

$$\tau = \max\{\tau_i \mid i = 1, 2, \dots, p\} \quad (6)$$

$\boldsymbol{\varphi}: \{-\tau, \dots, 0\} \rightarrow \mathbb{R}_{0,+}^n$ is the vector-valued initial function. By Lemma 3, system (4) is positive.

Now, we consider the following system closely related to (4):

$$\begin{aligned} \mathbf{y}(t+1) &= A_0 \mathbf{y}(t) + \sum_{i=1}^p A_i \mathbf{y}(t - \tau_i), \quad t \in \mathbb{N}_0 \\ \mathbf{y}(t) &= \phi(t) \succeq 0, \quad t = -\tau, \dots, 0 \end{aligned} \quad (7)$$

where all the system matrices are as in (4), and τ_i in (7) is the supremum of $\tau_i(t)$ in (4), as shown in (5). τ is defined by (6), and $\phi : \{-\tau, \dots, 0\} \rightarrow \mathbb{R}_{0,+}^n$ is an arbitrary initial condition. Note that the delays in (7) are constant.

Lemma 5: Consider system (7). Suppose that there exists a vector $\lambda \in \mathbb{R}_+^n$ satisfying

$$\left(\sum_{i=0}^p A_i - I \right) \lambda \prec 0 \quad (8)$$

and that the initial condition is $\phi(\cdot) \equiv \lambda$. Then, for any $t \in \{-\tau, \dots, 0\} \cup \mathbb{N}$, the solution to system (7) satisfies

$$\mathbf{y}(t+1) \preceq \mathbf{y}(t). \quad (9)$$

Proof: Note that the initial condition $\phi(\cdot) \equiv \lambda$. By (7), it yields that

$$\mathbf{y}(1) = A_0 \mathbf{y}(0) + \sum_{i=1}^p A_i \mathbf{y}(-\tau_i) = \sum_{i=0}^p A_i \lambda. \quad (10)$$

Since (8) holds and $\lambda \in \mathbb{R}_+^n$, (10) implies $\mathbf{y}(1) \prec \lambda$. Therefore

$$\mathbf{y}(1) \prec \mathbf{y}(0) = \mathbf{y}(-1) = \dots = \mathbf{y}(-\tau). \quad (11)$$

This means that (9) holds for any $t \in \{-\tau, \dots, 0\}$.

Now, suppose that (9) holds for any $t \in \{-\tau, \dots, k\}$ with $k \in \mathbb{N}_0$, then

$$\begin{aligned} \mathbf{y}(k+2) &= A_0 \mathbf{y}(k+1) + \sum_{i=1}^p A_i \mathbf{y}(k+1 - \tau_i) \\ &\preceq A_0 \mathbf{y}(k) + \sum_{i=1}^p A_i \mathbf{y}(k - \tau_i) \\ &= \mathbf{y}(k+1) \end{aligned}$$

which means that (9) holds for any $t \in \{-\tau, \dots, k+1\}$. By induction, (9) holds for any $t \in \{-\tau, \dots, 0\} \cup \mathbb{N}$. ■

The next lemma will show that, under certain conditions, the solution to system (4) is not greater than that to system (7), as stated in the following discussion.

Lemma 6: Suppose that there exists a vector $\lambda \in \mathbb{R}_+^n$ satisfying (8) and that the initial conditions for systems (4) and (7) are the same, i.e., $\varphi(\cdot) \equiv \phi(\cdot) \equiv \lambda$. Then

$$\mathbf{x}(t) \preceq \mathbf{y}(t) \quad (12)$$

holds for all $t \in \mathbb{N}$, where $\mathbf{x}(t)$ and $\mathbf{y}(t)$ are solutions to (4) and (7), respectively.

Proof: By (4) and (7), it follows that

$$\begin{aligned} \mathbf{x}(1) &= A_0 \mathbf{x}(0) + \sum_{i=1}^p A_i \mathbf{x}(-\tau_i(0)) = \sum_{i=0}^p A_i \lambda \\ \mathbf{y}(1) &= A_0 \mathbf{y}(0) + \sum_{i=1}^p A_i \mathbf{y}(-\tau_i) = \sum_{i=0}^p A_i \lambda. \end{aligned}$$

Due to (8)

$$\mathbf{y}(1) = \mathbf{x}(1) \prec \lambda. \quad (13)$$

Moreover

$$\begin{aligned} \mathbf{x}(2) &= A_0 \mathbf{x}(1) + \sum_{i=1}^p A_i \mathbf{x}(1 - \tau_i(1)) \\ &\preceq A_0 \mathbf{x}(1) + \sum_{i=1}^p A_i \mathbf{x}(1 - \tau_i) \\ &= A_0 \mathbf{y}(1) + \sum_{i=1}^p A_i \mathbf{y}(1 - \tau_i) \\ &= \mathbf{y}(2) \end{aligned}$$

that is, $\mathbf{x}(2) \preceq \mathbf{y}(2)$. This, together with (13), shows that for $t \in \{1, 2\}$, (12) holds.

Suppose that (12) holds for any $t \in \{1, 2, \dots, k\}$, where $k \in \mathbb{N}$ is not smaller than 2. Then, we have

$$\begin{aligned} \mathbf{x}(k+1) &= A_0 \mathbf{x}(k) + \sum_{i=1}^p A_i \mathbf{x}(k - \tau_i(k)) \\ &\preceq A_0 \mathbf{y}(k) + \sum_{i=1}^p A_i \mathbf{y}(k - \tau_i(k)). \end{aligned}$$

Since $\tau_i(k) \leq \tau_i$, Lemma 5 implies that $\mathbf{y}(k - \tau_i) \succeq \mathbf{y}(k - \tau_i(k))$. Therefore

$$\mathbf{x}(k+1) \preceq A_0 \mathbf{y}(k) + \sum_{i=1}^p A_i \mathbf{y}(k - \tau_i) = \mathbf{y}(k+1)$$

i.e., if (12) holds for any $t \in \{1, 2, \dots, k\}$, then it holds for any $t \in \{1, 2, \dots, k+1\}$. By induction, (12) holds for all $t \in \mathbb{N}$. ■

Lemma 7 [24]: The positive system (7) is asymptotically stable if and only if there exists a vector $\lambda \in \mathbb{R}_+^n$ such that

$$\left(\sum_{i=0}^p A_i - I \right) \lambda \prec 0.$$

We are now ready to provide the main results.

Theorem 1: The positive system (4) is asymptotically stable if and only if there exists a vector $\lambda \in \mathbb{R}_+^n$ such that

$$\left(\sum_{i=0}^p A_i - I \right) \lambda \prec 0. \quad (14)$$

Proof: Sufficiency. Assume that there exists a vector $\lambda \in \mathbb{R}_+^n$ such that (14) holds. By Lemma 7, system (7) is asymptotically stable.

Define $\|\phi\| = \sup_{t \in \{-\tau, \dots, 0\}} \|\phi(t)\|$. Since system (7) is asymptotically stable, for any given $\varepsilon > 0$, there exists a scalar $\delta > 0$, such that if $\|\phi\| < \delta$, then the corresponding solution $\mathbf{y}_\phi(t)$ to (7) satisfies that $\|\mathbf{y}_\phi(t)\| < \varepsilon$ for all $t \in \mathbb{N}$, and $\lim_{t \rightarrow +\infty} \|\mathbf{y}_\phi(t)\| = 0$.

In particular, choose the initial condition $\phi(\cdot) = \alpha\lambda$, where $\alpha > 0$, such that $\|\alpha\lambda\| < \delta$. Then, the corresponding solution $\mathbf{y}_{\alpha\lambda}(t)$ must satisfy that $\|\mathbf{y}_{\alpha\lambda}(t)\| < \varepsilon$ for all $t \in \mathbb{N}$, and $\lim_{t \rightarrow +\infty} \|\mathbf{y}_{\alpha\lambda}(t)\| = 0$.

For system (4), let the initial condition be $\varphi(\cdot) = \alpha\lambda$. By Lemma 6, the corresponding solution $\mathbf{x}_{\alpha\lambda}(t)$ satisfies that $\mathbf{x}_{\alpha\lambda}(t) \preceq \mathbf{y}_{\alpha\lambda}(t)$ for all $t \in \mathbb{N}$. In addition, by Lemma 4, for any initial condition $\varphi(\cdot) \prec \alpha\lambda$, the corresponding solution satisfies $\mathbf{x}_\varphi(t) \preceq \mathbf{x}_{\alpha\lambda}(t)$ for all $t \in \mathbb{N}$.

Therefore, for system (4), arbitrarily given $\varepsilon > 0$, there exists $\delta_1 = \|\alpha\lambda\| > 0$ such that $\|\varphi\| < \delta_1$ implies $\|\mathbf{x}_\varphi(t)\| \leq \|\mathbf{x}_{\alpha\lambda}(t)\| \leq \|\mathbf{y}_{\alpha\lambda}(t)\| < \varepsilon$ for all $t \in \mathbb{N}$.

Furthermore, since $\|\mathbf{x}_\varphi(t)\| \leq \|\mathbf{y}_{\alpha\lambda}(t)\|$ for all $t \in \mathbb{N}$, $\lim_{t \rightarrow +\infty} \|\mathbf{y}_{\alpha\lambda}(t)\| = 0$ implies

$$\lim_{t \rightarrow +\infty} \|\mathbf{x}_\varphi(t)\| = 0$$

and therefore, system (4) is asymptotically stable.

Necessity. Suppose that system (4) is asymptotically stable for any delays satisfying (5). Particularly, let $\tau_i(t) = \tau_i$; then system (7) is necessarily asymptotically stable. By Lemma 7, (14) must hold. ■

Remark 1: For the continuous-time positive systems with constant delays, [16] have established some necessary and sufficient stability criteria. Theorem 1 can be viewed as an extension to the discrete time-varying delayed case.

Corollary 1: For the positive system (4), the following statements are equivalent.

- (i) System (4) is asymptotically stable.
- (ii) Matrix $\sum_{i=0}^p A_i$ is a Schur matrix.
- (iii) All the eigenvalues of $\sum_{i=0}^p A_i$ lie inside the unit circle on the complex plane.
- (iv) There exists a diagonal matrix $P > 0$ such that $(\sum_{i=0}^p A_i)^T P (\sum_{i=0}^p A_i) - P < 0$.
- (v) System $\mathbf{x}(t+1) = \sum_{i=0}^p A_i \mathbf{x}(t)$, $t \in \mathbb{N}_0$, $\mathbf{x}(0) \succeq 0$, is asymptotically stable.

Proof: (i) \Leftrightarrow (ii). By Theorem 1, system (4) is asymptotically stable if and only if there exists a vector $\lambda \in \mathbb{R}_+^n$ such that (14) holds. Note that (14) is equivalent to $\sum_{i=0}^p A_i$, which is a Schur matrix due to Lemma 1. The equivalence holds.

(ii) \Leftrightarrow (iii). This obviously holds.

(ii) \Leftrightarrow (iv). Note that $\sum_{i=0}^p A_i \succeq 0$, and the equivalence between (ii) and (iv) holds due to Lemma 2.

(ii) \Leftrightarrow (v). This holds due to Definition 2. ■

Remark 2: As shown in Theorem 1 and Corollary 1, the magnitude of the delays does not affect the stability of system (4).

IV. EXAMPLE

To illustrate the theoretical results, we study the following example.




Fig. 1. Evolution of system (15), $a = 0.4999$, $\tau(t) \in \{0, 1, \dots, 10\}$.




Fig. 2. Evolution of system (15), $a = 0.5001$.

Example: Consider

$$\begin{aligned} \mathbf{x}(t+1) &= A_0 \mathbf{x}(t) + A_1 \mathbf{x}(t - \tau(t)), \quad t \in \mathbb{N}_0 \\ \varphi(t) &\succeq 0, \quad t = -\tau, \dots, 0 \end{aligned} \quad (15)$$

where $\mathbf{x}(t) = [x_1(t), x_2(t)]^T \in \mathbb{R}^2$, $\tau = \sup_{t \geq 0} \{\tau(t)\}$, and

$$A_0 = \begin{bmatrix} a & 0.1 \\ 0.2 & 0.3 \end{bmatrix}, \quad A_1 = \begin{bmatrix} 0.1 & 0.1 \\ 0.2 & 0.5 \end{bmatrix}.$$

where a is a nonnegative parameter, and therefore, system (15) is positive. One can check that the two eigenvalues of $A_0 + A_1$ are 0.4 and 1 if $a = 0.5$, and both of them lie inside the unit circle if $0 \leq a < 0.5$, and at least one of them lies outside if $a > 0.5$. By Corollary 1, system (15) is asymptotically stable for any bounded delay $\tau(t)$ if $0 \leq a < 0.5$, unstable if $a > 0.5$, and critically stable if $a = 0.5$, as shown in Figs. 1–3, respectively.

In Figs. 1–3, all the initial conditions randomly take values on the interval $[0, 1]$, and all the delays $\tau(t)$ randomly take values in the set $\{0, 1, \dots, 10\}$, whereas in Fig. 4, the delay $\tau(t)$ randomly takes values in the set $\{0, 1, \dots, 15\}$. From these figures, one can conclude that for bounded delays, the system's




Fig. 3. Evolution of system (15), $a = 0.5$.




Fig. 4. Evolution of system (15), $a = 0.4999$, $\tau(t) \in \{0, 1, \dots, 15\}$.

stability has nothing to do with the system delays, but it is completely determined by the system matrices.

V. CONCLUSION

Based on a novel approach, some necessary and sufficient stability conditions have been established for discrete-time positive systems with bounded time-varying delays. An illustrative example shows the correctness of the obtained theoretical results. These results are computationally efficient. In the field of positive systems, to our knowledge, no results on stability of systems with time-varying delays have been reported. This brief reveals that stability of a discrete-time positive system with time-varying delays is completely determined by its system matrices and is not affected by the delays.

Based on the results obtained in this brief, many other important topics, such as bounded control, constrained control, and observer design, can further be investigated. Furthermore, the method used in this brief, as well as the obtained results, is helpful in addressing the stability of continuous-time positive systems with time-varying delays, which is another open problem in this area.

ACKNOWLEDGMENT

The authors would like to thank Associate Editor Prof. J.-P. Barbot and the anonymous reviewers for their detailed comments and suggestions.

REFERENCES

- [1] A. Berman, M. Neumann, and R. J. Stern, *Nonnegative Matrices in Dynamic Systems*. New York: Wiley, 1989.
- [2] T. Kaczorek, *Positive 1D and 2D Systems*. London, U.K.: Springer-Verlag, 2002.
- [3] T. Kaczorek, *Polynomial and Rational Matrices, Applications in Dynamical Systems Theory*. London, U.K.: Springer-Verlag, 2007.
- [4] *Positive Systems*, vol. 294, L. Benvenuti, A. D. Santis, and L. Farina, Eds. Berlin, Germany: Springer-Verlag, 2003.
- [5] D. Hinrichsen, N. K. Son, and P. H. A. Ngoc, "Stability radii of higher order positive difference systems," *Syst. Control Lett.*, vol. 49, no. 5, pp. 377–388, Aug. 2003.
- [6] B. Nagy and M. Matolcsi, "A lowerbound on the dimension of positive realizations," *IEEE Trans. Circuits Syst. I, Fundam. Theory Appl.*, vol. 50, no. 6, pp. 782–784, Jun. 2003.
- [7] L. Benvenuti and L. Farina, "Positive and compartmental systems," *IEEE Trans. Autom. Control*, vol. 47, no. 2, pp. 370–373, Feb. 2002.
- [8] X. Liu, L. Wang, W. Yu, and S. Zhong, "Constrained control of positive discrete-time systems with delays," *IEEE Trans. Circuits Syst. II, Exp. Briefs*, vol. 55, no. 2, pp. 193–197, Feb. 2008.
- [9] M. Buslowicz, "Robust stability of positive discrete-time linear systems with multiple delays with linear unity rank uncertainty structure or non-negative perturbation matrices," *Bull. Pol. Acad. Sci., Tech. Sci.*, vol. 55, no. 1, pp. 1–5, 2007.
- [10] L. Farina and S. Rinaldi, *Positive Linear Systems: Theory and Applications*. New York: Wiley, 2000.
- [11] M. A. Rami and F. Tadeo, "Controller synthesis for positive linear systems with bounded controls," *IEEE Trans. Circuits Syst. II, Exp. Briefs*, vol. 54, no. 2, pp. 151–155, Feb. 2007.
- [12] M. A. Rami, F. Tadeo, and A. Benzaouia, "Control of constrained positive discrete systems," in *Proc. Amer. Control Conf.*, New York, 2007, pp. 5851–5856.
- [13] O. Mason and R. Shorten, "The geometry of convex cones associated with the Lyapunov inequality and the common Lyapunov function problem," *Electron. J. Linear Algebra*, vol. 12, pp. 42–63, 2005.
- [14] O. Mason and R. Shorten, "On linear copositive Lyapunov functions and the stability of switched positive linear systems," *IEEE Trans. Autom. Control*, vol. 52, no. 7, pp. 1346–1349, Jul. 2007.
- [15] M. A. Rami and F. Tadeo, "Positive observation problem for linear discrete positive systems," in *Proc. 45th IEEE Conf. Decision Control*, San Diego, CA, 2006, pp. 4729–4733.
- [16] W. M. Haddad and V. Chellaboina, "Stability theory for nonnegative and compartmental dynamical systems with time delay," *Syst. Control Lett.*, vol. 51, no. 5, pp. 355–361, Apr. 2004.
- [17] M. A. Rami, U. Helmke, and F. Tadeo, "Positive observation problem for time-delays linear positive systems," in *Proc. 15th Mediterranean Conf. Control Autom.*, Athens, Greece, 2007, pp. 1–6.
- [18] X. Liu, "Delay-dependent H_∞ control for uncertain fuzzy systems with time-varying delays," *Nonlinear Anal.*, vol. 68, no. 5, pp. 1352–1361, 2008.
- [19] Y. Sun, L. Wang, and G. Xie, "Average consensus in networks of dynamic agents with switching topologies and multiple time-varying delays," *Syst. Control Lett.*, vol. 57, no. 2, pp. 175–183, Feb. 2008.
- [20] Y. He, Q.-G. Wang, C. Lin, and M. Wu, "Delay-range-dependent stability for systems with time-varying delay," *Automatica*, vol. 43, no. 2, pp. 371–376, Feb. 2007.
- [21] E. Fridman and U. Shaked, "An improved stabilization method for linear time-delay systems," *IEEE Trans. Autom. Control*, vol. 47, no. 11, pp. 1931–1937, Nov. 2002.
- [22] A. Hmammed, A. Benzaouia, M. A. Rami, and F. Tadeo, "Positive stabilization of discrete-time systems with unknown delay and bounded controls," in *Proc. Eur. Control Conf.*, Kos, Greece, 2007.
- [23] M. A. Rami, U. Helmke, and F. Tadeo, "Positive observation problem for linear time-lag positive systems," in *Proc. 3rd IFAC Symp. Syst., Struct. Control*, Foz do Iguaçu, Brazil, 2007.
- [24] M. Buslowicz, "Simple stability conditions for linear positive discrete-time systems with delays," *Bull. Pol. Acad. Sci., Tech. Sci.*, vol. 56, no. 4, pp. 325–328, 2008.