

IMPROVED STABILITY CRITERIA FOR LINEAR NEUTRAL TIME-DELAY SYSTEMS

Hongwei Xia, Pingping Zhao, Li Li, Yanmin Wang, and Aiguo Wu

ABSTRACT

This paper is concerned with the problem of stability analysis of linear neutral time delay systems. First, a new simple Lyapunov-Krasovskii functional is constructed based on delay partitioning approach, then, a novel improved delay-dependent stability criterion is established to guarantee the asymptotic stability of the neutral system. The obtained stability criterion is expressed in terms of linear matrix inequalities, which can be verified easily by means of standard software. Numerical examples are given to illustrate the effectiveness of the proposed method and the advantage over some existing results.

Key Words: Neutral systems, stability criterion, delay partitioning approach, LMI.

I. INTRODUCTION

Since time delays can degrade system performance, and even result in instability, stability analysis and stabilization synthesis have been at the forefront of research on time delay systems in the recent decades [1–4]. In practice, time delays always appear in various engineering, biological, and economical systems [3–6]. Stability analysis and stabilization synthesis of neutral time-delay systems are more complex because the delays appear both in its states and in its derivatives of states. Many remarkable research results have been achieved in the literature [7–10].

It should be noted that all these stability criteria can be generally classified as delay-independent and delay-dependent types [11–13]. It is well known that the delay-dependent stability criteria, which utilize information of the upper and lower bounds of delays, are less conservative than delay-independent ones [10–15]. Obviously, there is an expectation to establish delay-dependent stability criteria with less conservatism. The Lyapunov functional approach is the main method employed to derive delay-dependent criteria [14–17]. It should be pointed out that the choices of specific Lyapunov functionals and bounding techniques are the main origin of reducing conservatism. Therefore, how to construct Lyapunov functionals, augmented vectors, new bounding techniques and derivation of the stability condition from the time-derivative of such a functional play key roles

in the field of analysis of delay systems [16–20]. Towards this objective, the new cross-term bounding technique [21], parameterized neutral model transformation method [22,23], free weighting matrices technique [24] had contributed greatly to reduce the conservatism of stability criteria for time-delay systems, as discussed by Kwon *et al.* in [20]. To mention a few, He *et al.* employed free-weighting matrices to express the relationships between the terms in the Leibniz-Newton formula [25–26]. Kwon *et al.* established some delay-dependent stability criteria by using new augmented Lyapunov functional and delay-partitioning approaches [20]. More results can be found in [27–29] and references therein. Recently, Luis *et al.* [30] and Fridman *et al.* [23] have proposed less conservative criteria for time-delay systems by the introduction of new Lyapunov-Krasovskii functionals. A similar idea can be extended to deal with stability analysis and synthesis of neutral time-delay systems.

Inspired by the works of [30], in this paper we study the delay-dependent stability for a class of neutral time-delay systems based on the delay partitioning technique. The remainder of the paper is organized as follows. Section II gives problem formulation and some preliminary lemmas. In Section III, by dividing the delay interval into multiple segments, a Lyapunov functional is first constructed for the considered system, and then a new delay-dependent stability criterion is proposed by using some matrix inequality techniques. Numerical examples are provided in Section IV, followed by the concluding remarks, which are presented in Section V.

Notation. Throughout this paper, “ T ” stands for matrix transposition. “ I ” denotes the identity matrix of appropriate dimensions. “ $P > 0$ ” means that P is positive definite. “ $*$ ” represents the elements below the main diagonal of a symmetric matrix.

II. PROBLEM FORMULATION

Consider the following linear time-varying discrete neutral system described by

Received March 18, 2013; Revised October 8, 2013; Accepted January 1, 2014.
Hongwei Xia and Yanmin Wang are with the Space Control and Inertial Technology Research Center, Harbin Institute of Technology, Harbin 150001, China.

Pingping Zhao and Aiguo Wu are with the Shenzhen Graduate School, Harbin Institute of Technology, Shenzhen 518055, China.

Li Li is with the School of Information Science and Engineering, Harbin Institute of Technology at Weihai, Weihai 264200, China.

hw_xia, qyb198622, lilihit, agwu, ymswang@163.com.

Hongwei Xia is the corresponding author (e-mail: simonxhw@163.com).

The work is supported by National Natural Science Foundation of China (No.61304108, No.61273094, No.51307035) and the Project for Distinguished Young Scholars of the Basic Research Plan in Shenzhen City under Contract No. JCY201110001. The authors are very thankful to the reviewers for their valuable suggestions and comments.

$$\begin{cases} \dot{x}(t) - C_d \dot{x}(t - \tau) = Ax(t) + A_d x(t - d(t)), & t > 0 \\ x(t) = \varphi(t), & t \in [-r, 0] \end{cases} \quad (1)$$

where $x(t)$ is the state vector; the matrices A , A_d , C_d are known constant matrices of appropriate dimensions, and the eigenvalue of the matrix C_d , $\rho(C_d)$ satisfies $\rho(C_d) < 1$. $\varphi(t) (t \in [-r, 0])$ is the initial function which is continuous differentiable on $[-r, 0]$. The scalar τ is a positive constant time-delay. Time delay $d(t)$ is a continuously differentiable function satisfying the following conditions

$$0 \leq h_{\min} \leq d(t) \leq h_{\max} \quad (2)$$

$$\mu_{\min} \leq \dot{d}(t) \leq \mu_{\max} \quad (3)$$

where h_{\min} , h_{\max} , μ_{\min} , μ_{\max} are known positive real constants. In addition, we denote $r = \max\{h_{\max}, \tau\}$.

To facilitate further developments, we introduce the following lemma that will be frequently used in deriving the main results [30].

Lemma 1. Given scalars r_1 , r_2 such that $(r_2 - r_1) \geq 0$, matrix $M = M^T > 0$, and any vectorial function $x : [r_1, r_2] \rightarrow \mathbb{R}^m$, we have:

$$(r_2 - r_1) \int_{r_1}^{r_2} x^T(\beta) M x(\beta) d\beta \geq \left(\int_{r_1}^{r_2} x(\beta) d\beta \right)^T M \left(\int_{r_1}^{r_2} x(\beta) d\beta \right)$$

III. MAIN RESULTS

This section discusses the problem of stable analysis of the system (1). Similarly to [23, 30], the time-varying delay interval $[h_{\min}, h_{\max}]$ is divided into two segments: $[h_1, h_2]$ and $[h_2, h_3]$, where $h_1 = h_{\min}$, $h_3 = h_{\max}$, $h_2 = \frac{h_1 + h_3}{2}$. With such an idea, a novel delay-dependent stability criterion for neutral systems is derived.

Theorem 1. Given positive scalars $0 \leq h_m \leq h_M$, the neutral system (1) with delay restrictions (2) and (3) is asymptotically stable if there exist matrices $P_i > 0 (i = 1, 2, 3)$, $R_1 > 0$, $R_3 > 0$, $(R_2 + R_3) > 0$, $Q_j > 0 (j = 1, 2, 3)$, $Z_k > 0 (k = 1, \dots, 4)$, $S_1 > 0$, $S_2 > 0$, $\begin{bmatrix} T_{11} & T_{12} \\ * & T_{22} \end{bmatrix} \geq 0$, $\begin{bmatrix} Q_{11} & Q_{12} \\ * & Q_{22} \end{bmatrix} \geq 0$, and

$$\begin{aligned} R_1 + (1 - \mu_{\min}) R_2 + R_3 &> 0 \\ R_1 + (1 - \mu_{\max}) R_2 + R_3 &> 0 \end{aligned} \quad (4)$$

and free-weighting matrices N_{1a} , N_{2a} , M_{1a} , M_{2a} , $a = (1, \dots, 9)$, F_{11} , F_{12} , F_{21} , F_{22} with appropriate dimensions, such that the following LMIs (5) hold:

$$\begin{aligned} \Omega_1 \Big|_{\dot{d}(t) \rightarrow \mu_{\min}} &< 0; & \Omega_1 \Big|_{\dot{d}(t) \rightarrow \mu_{\max}} &< 0; \\ \Omega_2 \Big|_{\dot{d}(t) \rightarrow \mu_{\min}} &< 0; & \Omega_2 \Big|_{\dot{d}(t) \rightarrow \mu_{\max}} &< 0; \\ \Omega_3 \Big|_{\dot{d}(t) \rightarrow \mu_{\min}} &< 0; & \Omega_3 \Big|_{\dot{d}(t) \rightarrow \mu_{\max}} &< 0; \\ \Omega_4 \Big|_{\dot{d}(t) \rightarrow \mu_{\min}} &< 0; & \Omega_4 \Big|_{\dot{d}(t) \rightarrow \mu_{\max}} &< 0; \end{aligned} \quad (5)$$

where

$$\Omega_1 = \Gamma_{11} + \Phi_{11} + \Phi_{11}^T; \Omega_2 = \Gamma_{12} + \Phi_{12} + \Phi_{12}^T$$

$$\Omega_3 = \Gamma_{21} + \Phi_{21} + \Phi_{21}^T; \Omega_4 = \Gamma_{22} + \Phi_{22} + \Phi_{22}^T$$

$$\Phi_{11}^T = \begin{bmatrix} 0 & \Theta_{11}^T & 0 & 0 & 0 & 0 & -N_1^T & M_1^T & 0 & \Theta_{12}^T \end{bmatrix}$$

$$\Phi_{12}^T = \begin{bmatrix} 0 & \Theta_{11}^T & 0 & 0 & 0 & 0 & -N_1^T & M_1^T & 0 & \Theta_{13}^T \end{bmatrix}$$

$$\Phi_{21}^T = \begin{bmatrix} 0 & \Theta_{21}^T & 0 & 0 & 0 & 0 & -N_2^T & M_2^T & \Theta_{22}^T \end{bmatrix}$$

$$\Phi_{22}^T = \begin{bmatrix} 0 & \Theta_{21}^T & 0 & 0 & 0 & 0 & -N_2^T & M_2^T & \Theta_{23}^T \end{bmatrix}$$

$$\Gamma_{11} = \begin{bmatrix} \Omega_{11}^1 & F_{11}^T A_d & \Pi_{11}^1 & \frac{1}{\tau} S_2 & F_{11}^T C_d & \Omega_{16} & U_1 & 0 & 0 & 0 \\ * & \Omega_{22} & A_d^T F_{12} & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & \Omega_{33}^1 & 0 & F_{12}^T C_d & 0 & 0 & 0 & 0 & 0 \\ * & * & * & \Omega_{44} & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & * & * & -S_1 & 0 & 0 & 0 & 0 & 0 \\ * & * & * & * & * & \Omega_{66} & \Omega_{67} & 0 & 0 & 0 \\ * & * & * & * & * & * & \Omega_{77}^1 & Q_{12} & 0 & 0 \\ * & * & * & * & * & * & * & \Omega_{88}^1 & \Omega_{89}^1 & 0 \\ * & * & * & * & * & * & * & * & \Omega_{99}^1 & 0 \\ * & * & * & * & * & * & * & * & * & \Pi_{b1}^1 \end{bmatrix}$$

$$\Gamma_{12} = \begin{bmatrix} \Omega_{11}^1 & F_{11}^T A_d & \Pi_{12}^1 & \frac{1}{\tau} S_2 & F_{11}^T C_d & \Omega_{16} & U_1 & 0 & 0 & 0 \\ * & \Omega_{22} & A_d^T F_{12} & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & \Omega_{33}^1 & 0 & F_{12}^T C_d & 0 & 0 & 0 & 0 & 0 \\ * & * & * & \Omega_{44} & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & * & * & -S_1 & 0 & 0 & 0 & 0 & 0 \\ * & * & * & * & * & \Omega_{66} & \Omega_{67} & 0 & 0 & 0 \\ * & * & * & * & * & * & \Omega_{77}^1 & Q_{12} & 0 & 0 \\ * & * & * & * & * & * & * & \Omega_{88}^1 & \Omega_{89}^1 & 0 \\ * & * & * & * & * & * & * & * & \Omega_{99}^1 & 0 \\ * & * & * & * & * & * & * & * & * & \Pi_{a1}^1 \end{bmatrix}$$

$$\Gamma_{21} = \begin{bmatrix} \Omega_{11}^2 & F_{21}^T A_d & \Pi_{21}^2 & \frac{1}{\tau} S_2 & F_{21}^T C_d & \Omega_{16} & U_2 & 0 & 0 & 0 \\ * & \Omega_{22} & A_d^T F_{22} & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & \Omega_{33}^2 & 0 & F_{22}^T C_d & 0 & 0 & 0 & 0 & 0 \\ * & * & * & \Omega_{44} & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & * & * & -S_1 & 0 & 0 & 0 & 0 & 0 \\ * & * & * & * & * & \Omega_{66} & \Omega_{67} & 0 & 0 & 0 \\ * & * & * & * & * & * & \Omega_{77}^2 & \Omega_{78}^2 & 0 & 0 \\ * & * & * & * & * & * & * & \Omega_{88}^2 & -Q_{12} & 0 \\ * & * & * & * & * & * & * & * & -Q_{22} & 0 \\ * & * & * & * & * & * & * & * & * & \Pi_{b1}^2 \end{bmatrix}$$

$$\Gamma_{22} = \begin{bmatrix} \Omega_{11}^2 & F_{21}^T A_d & \Pi_{22}^2 & \frac{1}{\tau} S_2 & F_{21}^T C_d & \Omega_{16} & U_2 & 0 & 0 & 0 \\ * & \Omega_{22} & A_d^T F_{22} & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & \Omega_{33}^2 & 0 & F_{22}^T C_d & 0 & 0 & 0 & 0 & 0 \\ * & * & * & \Omega_{44} & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & * & * & -S_1 & 0 & 0 & 0 & 0 & 0 \\ * & * & * & * & * & \Omega_{66} & \Omega_{67} & 0 & 0 & 0 \\ * & * & * & * & * & * & \Omega_{77}^2 & \Omega_{78}^2 & 0 & 0 \\ * & * & * & * & * & * & * & \Omega_{88}^2 & -Q_{12} & 0 \\ * & * & * & * & * & * & * & * & -Q_{22} & 0 \\ * & * & * & * & * & * & * & * & * & \Pi_{a1}^2 \end{bmatrix}$$

and, for $\alpha \in \{1, 2\}$,

$$N_\alpha = [N_{\alpha 1} \ N_{\alpha 2} \ N_{\alpha 3} \ N_{\alpha 4} \ N_{\alpha 5} \ N_{\alpha 6} \ N_{\alpha 7} \ N_{\alpha 8} \ N_{\alpha 9} \ 0]$$

$$M_\alpha = [M_{\alpha 1} \ M_{\alpha 2} \ M_{\alpha 3} \ M_{\alpha 4} \ M_{\alpha 5} \ M_{\alpha 6} \ M_{\alpha 7} \ M_{\alpha 8} \ M_{\alpha 9} \ 0]$$

$$\Theta_{\alpha 1} = N_\alpha - M_\alpha; \quad \Theta_{\alpha 2} = (h_{\alpha+1} - h_\alpha) M_\alpha; \quad \Theta_{\alpha 3} = (h_{\alpha+1} - h_\alpha) N_\alpha;$$

$$U_1 = \frac{1}{h_1} [R_1 + (1 - \dot{d}(t)) R_2 + R_3]; U_2 = \frac{1}{h_1} [(1 - \dot{d}(t)) R_1 + R_2 + R_3];$$

$$\begin{aligned} \Omega_{11}^1 &= \frac{\dot{d}(t)}{h_2 - h_1} (P_1 - P_2) + Q_1 + Q_3 + T_{11} \\ &\quad - Z_1 - U_1 - \frac{1}{\tau} S_2 + F_{11}^T A + A^T F_{11} \end{aligned}$$

$$\Pi_{11}^1 = P_2 + A^T F_{12} - F_{11}^T; \Pi_{12}^1 = P_1 + A^T F_{12} - F_{11}^T$$

$$\Omega_{16} = Z_1 + T_{12}; \Omega_{22} = -(1 - \dot{d}(t)) Q_2; \Omega_{44} = -Q_3 - \frac{1}{\tau} S_2$$

$$\begin{aligned} \Omega_{33}^1 &= \left(\frac{h_1}{2}\right)^2 (Z_1 + Z_2) + (h_2 - h_1) Z_3 + (h_3 - h_2) Z_4 \\ &\quad + h_2 (R_1 + R_2 + R_3) + S_1 + \tau S_2 - F_{12} - F_{12}^T \end{aligned}$$

$$\Omega_{66} = T_{22} - T_{11} - Z_1 - Z_2; \Omega_{67} = Z_2 - T_{12};$$

$$\Omega_{77}^1 = -Q_1 + Q_2 - T_{22} + Q_{11} - Z_2 - U_1$$

$$\Omega_{88}^1 = Q_{22} - Q_{11} - \frac{1}{h_3 - h_2} Z_4; \Omega_{89}^1 = -Q_{12} + \frac{1}{h_3 - h_2} Z_4;$$

$$\Omega_{99}^1 = -Q_{22} - \frac{1}{h_3 - h_2} Z_4$$

$$\Pi_{a1}^1 = -(h_2 - h_1) (Z_3 + R_1 + (1 - \dot{d}(t)) R_2 + R_3);$$

$$\Pi_{b1}^1 = -(h_2 - h_1) (Z_3 + R_1 + R_3)$$

$$\begin{aligned} \Omega_{11}^2 &= \frac{\dot{d}(t)}{h_3 - h_2} (P_3 - P_1) + Q_1 + Q_3 \\ &\quad + T_{11} - Z_1 - U_2 - \frac{1}{\tau} S_2 + F_{21}^T A + A^T F_{21} \end{aligned}$$

$$\Pi_{21}^2 = P_1 + A^T F_{22} - F_{21}^T; \Pi_{22}^2 = P_3 + A^T F_{22} - F_{21}^T$$

$$\begin{aligned} \Omega_{33}^2 &= \left(\frac{h_1}{2}\right)^2 (Z_1 + Z_2) + (h_2 - h_1) Z_3 + (h_3 - h_2) Z_4 + h_2 (R_2 + R_3) \\ &\quad + h_3 R_1 + S_1 + \tau S_2 - F_{22} - F_{22}^T \end{aligned}$$

$$\begin{aligned} \Omega_{77}^2 &= -Q_1 + Q_2 - T_{22} + Q_{11} - Z_2 - U_2 \\ &\quad - \frac{1}{h_2 - h_1} (Z_3 + (1 - \dot{d}(t)) R_1 + R_2 + R_3) \end{aligned}$$

$$\Omega_{78}^2 = Q_{12} + \frac{1}{h_2 - h_1} [Z_3 + (1 - \dot{d}(t)) R_1 + R_2 + R_3]$$

$$\Omega_{88}^2 = Q_{22} - Q_{11} - \frac{1}{h_2 - h_1} [Z_3 + (1 - \dot{d}(t)) R_1 + R_2 + R_3]$$

$$\Pi_{a1}^2 = -(h_3 - h_2) (Z_4 + (1 - \dot{d}(t)) R_1); \Pi_{b1}^2 = -(h_3 - h_2) Z_4.$$

Proof. Let us choose a Lyapunov-Krasovskii functional candidate as follows:

$$V(t) = \sum_{i=1}^7 V_i(t) \quad (6)$$

where

$$V_1(t)|_{d(t) < h_2} = x^T(t) \left(\frac{d(t) - h_1}{h_2 - h_1} P_1 + \frac{h_2 - d(t)}{h_2 - h_1} P_2 \right) x(t)$$

$$V_1(t)|_{d(t) > h_2} = x^T(t) \left(\frac{d(t) - h_2}{h_3 - h_2} P_3 + \frac{h_3 - d(t)}{h_3 - h_2} P_1 \right) x(t)$$

$$\begin{aligned} V_2(t) &= \int_{t-h_1}^t x^T(s) Q_1 x(s) ds + \int_{t-d(t)}^{t-h_1} x^T(s) Q_2 x(s) ds \\ &\quad + \int_{t-\tau}^t x^T(s) Q_3 x(s) ds \end{aligned}$$

$$V_3(t) = \int_{t-\frac{h_1}{2}}^t \begin{bmatrix} x(s) \\ x\left(s - \frac{h_1}{2}\right) \end{bmatrix}^T \begin{bmatrix} T_{11} & T_{12} \\ * & T_{22} \end{bmatrix} \begin{bmatrix} x(s) \\ x\left(s - \frac{h_1}{2}\right) \end{bmatrix} ds$$

$$V_4(t) = \int_{t-h_3}^{t-h_2} \begin{bmatrix} x(s) \\ x(s - h_2 + h_1) \end{bmatrix}^T \begin{bmatrix} Q_{11} & Q_{12} \\ * & Q_{22} \end{bmatrix} \begin{bmatrix} x(s) \\ x(s - h_2 + h_1) \end{bmatrix} ds$$

$$V_5(t) = \frac{h_1}{2} \int_{-\frac{h_1}{2}}^0 \int_{t+\theta}^t \dot{x}^T(s) Z_1 \dot{x}(s) ds d\theta + \frac{h_1}{2} \int_{-\frac{h_1}{2}}^0 \int_{t+\theta}^t \dot{x}^T(s) Z_2 \dot{x}(s) ds d\theta \\ + \int_{-h_2}^{-h_1} \int_{t+\theta}^t \dot{x}^T(s) Z_3 \dot{x}(s) ds d\theta + \int_{-h_3}^{-h_2} \int_{t+\theta}^t \dot{x}^T(s) Z_4 \dot{x}(s) ds d\theta$$

$$V_6(t)|_{d(t) < h_2} = \int_{-h_2}^0 \int_{t+\theta}^t \dot{x}^T(s) R_1 \dot{x}(s) ds d\theta \\ + \int_{-h_2}^{-d(t)} \int_{t+\theta}^t \dot{x}^T(s) R_3 \dot{x}(s) ds d\theta \\ + \int_{-d(t)}^0 \int_{t+\theta}^t \dot{x}^T(s) (R_2 + R_3) \dot{x}(s) ds d\theta$$

$$V_6(t)|_{d(t) > h_2} = \int_{-d(t)}^0 \int_{t+\theta}^t \dot{x}^T(s) R_1 \dot{x}(s) ds d\theta \\ + \int_{-h_2}^0 \int_{t+\theta}^t \dot{x}^T(s) (R_2 + R_3) \dot{x}(s) ds d\theta$$

$$V_7(t) = \int_{t-\tau}^t \dot{x}^T(s) S_1 \dot{x}(s) ds + \int_{-\tau}^0 \int_{t+\theta}^t \dot{x}^T(s) S_2 \dot{x}(s) ds d\theta$$

V_1 – V_6 in (6) are chosen as (5) in [30]. V_7 in (6) is specially constructed for neutral time-delay systems.

First, consider $d(t) \neq h_2$. Taking the time derivative of the LKF (6) with $h_1 \leq d(t) < h_2$, we have

$$\dot{V}_1(t)|_{d(t) < h_2} = 2x^T(t) \left(\frac{d(t) - h_1}{h_2 - h_1} P_1 + \frac{h_2 - d(t)}{h_2 - h_1} P_2 \right) \dot{x}(t) \\ + x^T(t) \frac{\dot{d}(t)}{h_2 - h_1} (P_1 - P_2) x(t)$$

$$\dot{V}_2(t) = x^T(t) (Q_1 + Q_3) x(t) - x^T(t - h_1) Q_1 x(t - h_1) \\ + x^T(t - h_1) Q_2 x(t - h_1) - (1 - \dot{d}(t)) x^T(t - d(t)) \\ Q_2 x(t - d(t)) - x^T(t - \tau) Q_3 x(t - \tau)$$

$$\dot{V}_3(t) = \begin{bmatrix} x(t) \\ x(t - \frac{h_1}{2}) \end{bmatrix}^T \begin{bmatrix} T_{11} & T_{12} \\ * & T_{22} \end{bmatrix} \begin{bmatrix} x(t) \\ x(t - \frac{h_1}{2}) \end{bmatrix} \\ - \begin{bmatrix} x(t - \frac{h_1}{2}) \\ x(t - h_1) \end{bmatrix}^T \begin{bmatrix} T_{11} & T_{12} \\ * & T_{22} \end{bmatrix} \begin{bmatrix} x(t - \frac{h_1}{2}) \\ x(t - h_1) \end{bmatrix}$$

$$\dot{V}_4(t) = \begin{bmatrix} x(t - h_1) \\ x(t - h_2) \end{bmatrix}^T \begin{bmatrix} Q_{11} & Q_{12} \\ * & Q_{22} \end{bmatrix} \begin{bmatrix} x(t - h_1) \\ x(t - h_2) \end{bmatrix} \\ - \begin{bmatrix} x(t - h_2) \\ x(t - h_3) \end{bmatrix}^T \begin{bmatrix} Q_{11} & Q_{12} \\ * & Q_{22} \end{bmatrix} \begin{bmatrix} x(t - h_2) \\ x(t - h_3) \end{bmatrix}$$

$$\dot{V}_5(t) = \dot{x}^T(t) \left[\left(\frac{h_1}{2} \right)^2 (Z_1 + Z_2) + (h_2 - h_1) Z_3 + (h_3 - h_2) Z_4 \right] \dot{x}(t) \\ - \frac{h_1}{2} \int_{t-\frac{h_1}{2}}^t \dot{x}^T(s) Z_1 \dot{x}(s) ds - \frac{h_1}{2} \int_{t-h_1}^{t-\frac{h_1}{2}} \dot{x}^T(s) Z_2 \dot{x}(s) ds \\ - \int_{t-h_2}^{t-h_1} \dot{x}^T(s) Z_3 \dot{x}(s) ds - \int_{t-h_3}^{t-h_2} \dot{x}^T(s) Z_4 \dot{x}(s) ds$$

$$\dot{V}_6(t)|_{d(t) < h_2} = \dot{x}^T(t) [h_2 R_1 + d(t)(R_2 + R_3) + (h_2 - d(t)) R_3] \dot{x}(t) \\ - \int_{t-h_2}^t \dot{x}^T(s) R_1 \dot{x}(s) ds - (1 - \dot{d}(t)) \int_{t-d(t)}^t \dot{x}^T(s) (R_2 + R_3) \dot{x}(s) ds \\ - \dot{d}(t) \int_{t-d(t)}^t \dot{x}^T(s) R_3 \dot{x}(s) ds - \int_{t-h_2}^{t-d(t)} \dot{x}^T(s) R_3 \dot{x}(s) ds$$

$$\dot{V}_7(t) = \dot{x}^T(t) (S_1 + \tau S_2) \dot{x}(t) - \dot{x}^T(t - \tau) S_1 \dot{x}(t - \tau) - \int_{t-\tau}^t \dot{x}^T(s) S_2 \dot{x}(s) ds$$

For $h_1 \leq d(t) < h_2$, one has

$$\int_{t-h_3}^t f(s) ds = \int_{t-h_1}^t f(s) ds + \int_{t-d(t)}^{t-h_1} f(s) ds \\ + \int_{t-h_2}^{t-d(t)} f(s) ds + \int_{t-h_3}^{t-h_2} f(s) ds \quad (7)$$

According to (7), we lead to

$$\dot{V}_5(t) + \dot{V}_6(t)|_{d(t) < h_2} \\ \leq -\frac{h_1}{2} \int_{t-\frac{h_1}{2}}^t \dot{x}^T(s) Z_1 \dot{x}(s) ds - \frac{h_1}{2} \int_{t-h_1}^{t-\frac{h_1}{2}} \dot{x}^T(s) Z_2 \dot{x}(s) ds \\ - \int_{t-h_1}^t \dot{x}^T(s) (R_1 + (1 - \dot{d}(t)) R_2 + R_3) \dot{x}(s) ds \\ - \int_{t-d(t)}^{t-h_1} \dot{x}^T(s) (Z_3 + R_1 + (1 - \dot{d}(t)) R_2 + R_3) \dot{x}(s) ds \\ - \int_{t-h_2}^{t-d(t)} \dot{x}^T(s) (Z_3 + R_1 + R_3) \dot{x}(s) ds \\ - \int_{t-h_3}^{t-h_2} \dot{x}^T(s) Z_4 \dot{x}(s) ds + \dot{x}^T(t) \left[\left(\frac{h_1}{2} \right)^2 (Z_1 + Z_2) \right. \\ \left. + (h_2 - h_1) Z_3 + (h_3 - h_2) Z_4 + h_2 (R_1 + R_2 + R_3) \right] \dot{x}(t) \quad (8)$$

By Jensen's inequality (Lemma 1), it can be seen that:

$$\dot{V}_5(t) + \dot{V}_6(t)|_{d(t) < h_2} \\ \leq - \left[x(t) - x\left(t - \frac{h_1}{2}\right) \right]^T Z_1 \left[x(t) - x\left(t - \frac{h_1}{2}\right) \right] \\ - \left[x\left(t - \frac{h_1}{2}\right) - x(t - h_1) \right]^T Z_2 \left[x\left(t - \frac{h_1}{2}\right) - x(t - h_1) \right] \\ - \frac{1}{h_1} [x(t) - x(t - h_1)]^T (R_1 + (1 - \dot{d}(t)) R_2 + R_3) [x(t) - x(t - h_1)] \\ - \frac{1}{h_3 - h_2} [x(t - h_2) - x(t - h_3)]^T Z_4 [x(t - h_2) - x(t - h_3)] \\ - \gamma_{1d}^T (d(t) - h_1) (Z_3 + R_1 + (1 - \dot{d}(t)) R_2 + R_3) \gamma_{1d} \\ - \gamma_{d2}^T (h_2 - d(t)) (Z_3 + R_1 + R_3) \gamma_{d2} + \dot{x}^T(t) \left[\left(\frac{h_1}{2} \right)^2 (Z_1 + Z_2) \right. \\ \left. + (h_2 - h_1) Z_3 + (h_3 - h_2) Z_4 + h_2 (R_1 + R_2 + R_3) \right] \dot{x}(t) \quad (9)$$

$$\text{where } \gamma_{1d} = \frac{1}{d(t) - h_1} \int_{t-d(t)}^{t-h_1} \dot{x}(s) ds, \gamma_{d2} = \frac{1}{h_2 - d(t)} \int_{t-h_2}^{t-d(t)} \dot{x}(s) ds.$$

Note that $\lim_{d(t) \rightarrow h_1} \gamma_{1d} = \dot{x}(t - h_1)$, $\lim_{d(t) \rightarrow h_2} \gamma_{d2} = \dot{x}(t - h_2)$.

By using the Leibniz-Newton formula, and denoting

$$\begin{aligned} \eta_1^T(t) = & \begin{bmatrix} x^T(t) & x^T(t-d(t)) & \dot{x}^T(t) & x^T(t-\tau) & \dot{x}^T(t-\tau) \\ x^T\left(t-\frac{h_1}{2}\right) & x^T(t-h_1) & x^T(t-h_2) & x^T(t-h_3) & \gamma_{1d}^T & \gamma_{d2}^T \end{bmatrix} \quad (10) \end{aligned}$$

the following equations hold for any free-weighting matrices N_i and M_i

$$\begin{aligned} 2\eta_1^T(t)N_1^T[-x(t-h_1)+x(t-d(t))+(d(t)-h_1)\gamma_{1d}] &= 0 \\ 2\eta_1^T(t)M_1^T[-x(t-d(t))+x(t-h_2)+(h_2-d(t))\gamma_{d2}] &= 0 \end{aligned} \quad (11)$$

where $N_i \in \mathbb{R}^{n \times n}$, $M_i \in \mathbb{R}^{n \times n}$, $i \in \{1, \dots, 9\}$.

Corresponding to (1), for any matrices $F_{ij} \in (j=1, 2)$ with appropriate dimensions, one has

$$\begin{aligned} & 2[x^T(t)F_{11}^T + \dot{x}^T(t)F_{12}^T] \\ & \times [Ax(t) + A_d x(t-d(t)) - \dot{x}(t) + C_d \dot{x}(t-\tau)] = 0 \end{aligned} \quad (12)$$

From $\dot{V}_k(t)$ ($k=1, \dots, 7$), the combination of (10) and (11), one can obtain

$$\dot{V}|_{d(t)<h_2} \leq \eta_1^T(t)(\Omega|_{d(t)<h_2})\eta_1(t) \quad (13)$$

where

$$\Omega|_{d(t)<h_2} = \Gamma_1 + \Phi_1 + \Phi_1^T \quad (14)$$

$$\begin{aligned} \Phi_1^T = & \begin{bmatrix} 0 & N_1^T - M_1^T & 0 & 0 & 0 & 0 & -N_1^T \\ M_1^T & 0 & (d(t)-h_1)N_1^T & (h_2-d(t))M_1^T \end{bmatrix} \end{aligned}$$

$$\Pi_1^1 = \frac{d(t)-h_1}{h_2-h_1}P_1 + \frac{h_2-d(t)}{h_2-h_1}P_2 + A^T F_{12} - F_{11}^T$$

$$\Pi_a^1 = -(d(t)-h_1)(Z_3 + R_1 + (1-\dot{d}(t))R_2 + R_3)$$

$$\Pi_b^1 = -(h_2-d(t))(Z_3 + R_1 + R_3)$$

$$\Gamma_1 = \begin{bmatrix} \Omega_{11}^1 & F_{11}^T A_d & \Pi_1^1 & \frac{1}{\tau} S_2 & F_{11}^T C_d & \Omega_{16} & U_1 & 0 & 0 & 0 & 0 \\ * & \Omega_{22} & A_d^T F_{12} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & \Omega_{33}^1 & 0 & F_{12}^T C_d & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & * & \Omega_{44} & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & * & * & -S_1 & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & * & * & * & \Omega_{66} & \Omega_{67} & 0 & 0 & 0 & 0 \\ * & * & * & * & * & * & \Omega_{77}^1 & Q_{12} & 0 & 0 & 0 \\ * & * & * & * & * & * & * & \Omega_{88}^1 & \Omega_{89}^1 & 0 & 0 \\ * & * & * & * & * & * & * & * & \Omega_{99}^1 & 0 & 0 \\ * & * & * & * & * & * & * & * & * & \Pi_a^1 & 0 \\ * & * & * & * & * & * & * & * & * & * & \Pi_b^1 \end{bmatrix}$$

By combining those results above, now it is interesting to note that

$$\begin{aligned} \eta_1^T(t)(\Omega|_{d(t)<h_2})\eta_1(t) &= \frac{d(t)-h_1}{h_2-h_1}\eta_{11}^T(t)\Omega_1\eta_{11}(t) \\ &+ \frac{h_2-d(t)}{h_2-h_1}\eta_{12}^T(t)\Omega_2\eta_{12}(t) \end{aligned}$$

where Ω_1 and Ω_2 results from $\Omega|_{d(t)<h_2}$ for $d(t) \rightarrow h_1$ and $d(t) \rightarrow h_2$, respectively, and

$$\begin{aligned} \eta_{11}^T(t) = & \begin{bmatrix} x^T(t) & x^T(t-d(t)) & \dot{x}^T(t) & x^T(t-\tau) & \dot{x}^T(t-\tau) \\ x^T\left(t-\frac{h_1}{2}\right) & x^T(t-h_1) & x^T(t-h_2) & x^T(t-h_3) & \gamma_{d2}^T \end{bmatrix} \end{aligned}$$

$$\begin{aligned} \eta_{12}^T(t) = & \begin{bmatrix} x^T(t) & x^T(t-d(t)) & \dot{x}^T(t) & x^T(t-\tau) & \dot{x}^T(t-\tau) \\ x^T\left(t-\frac{h_1}{2}\right) & x^T(t-h_1) & x^T(t-h_2) & x^T(t-h_3) & \gamma_{1d}^T \end{bmatrix} \end{aligned}$$

What's more, considering (3), one has

$$\Omega_1 = \frac{\mu_{\max} - \dot{d}(t)}{\mu_{\max} - \mu_{\min}} \Omega_1|_{\dot{d}(t) \rightarrow \mu_{\min}} + \frac{\dot{d}(t) - \mu_{\min}}{\mu_{\max} - \mu_{\min}} \Omega_1|_{\dot{d}(t) \rightarrow \mu_{\max}}$$

$$\Omega_2 = \frac{\mu_{\max} - \dot{d}(t)}{\mu_{\max} - \mu_{\min}} \Omega_2|_{\dot{d}(t) \rightarrow \mu_{\min}} + \frac{\dot{d}(t) - \mu_{\min}}{\mu_{\max} - \mu_{\min}} \Omega_2|_{\dot{d}(t) \rightarrow \mu_{\max}}$$

Hence, for $h_2 < d(t) < h_3$, the following expressions hold

$$\begin{aligned} \dot{V}_1(t)|_{d(t)>h_2} &= x^T(t) \left(\frac{\dot{d}(t)}{h_3-h_2} (P_3 - P_1) \right) x(t) \\ &+ 2x^T(t) \left(\frac{d(t)-h_2}{h_3-h_2} P_3 - \frac{h_3-d(t)}{h_3-h_2} P_1 \right) \dot{x}(t) \end{aligned}$$

$$\begin{aligned} \dot{V}_6(t)|_{d(t)>h_2} &= \dot{x}^T(t)(d(t)R_1 + h_2(R_2 + R_3))\dot{x}(t) \\ &- (1-\dot{d}(t)) \int_{t-d(t)}^t \dot{x}^T(s)R_1\dot{x}(s)ds - \int_{t-d_2}^t \dot{x}^T(s)(R_2 + R_3)\dot{x}(s)ds \end{aligned}$$

For $h_2 < d(t) < h_3$, one can obtain

$$\begin{aligned} \int_{t-h_3}^t f(s)ds &= \int_{t-h_1}^t f(s)ds + \int_{t-h_2}^{t-h_1} f(s)ds \\ &+ \int_{t-d(t)}^{t-h_2} f(s)ds + \int_{t-h_3}^{t-d(t)} f(s)ds \end{aligned} \quad (15)$$

By Jensen's inequality (Lemma 1) and combining (15), it can be seen that:

$$\begin{aligned}
\dot{V}_5(t) + \dot{V}_6(t)|_{d(t)>h_2} \leq & - \left[x(t) - x\left(t - \frac{h_1}{2}\right) \right]^T Z_1 \left[x(t) - x\left(t - \frac{h_1}{2}\right) \right] \\
& - \left[x\left(t - \frac{h_1}{2}\right) - x(t - h_1) \right]^T Z_2 \left[x\left(t - \frac{h_1}{2}\right) - x(t - h_1) \right] \\
& - \frac{1}{h_1} [x(t) - x(t - h_1)]^T ((1 - \dot{d}(t))R_1 + R_2 + R_3) [x(t) - x(t - h_1)] \\
& - \frac{1}{h_2 - h_1} \Gamma_a^T (Z_3 + ((1 - \dot{d}(t))R_1 + R_2 + R_3)) \Gamma_a \\
& - \gamma_{2d}^T (d(t) - h_2) (Z_4 + (1 - \dot{d}(t))R_1) \gamma_{2d} - \gamma_{d3}^T (h_2 - d(t)) Z_4 \gamma_{d3} \\
& + \dot{x}^T(t) \left[\left(\frac{h_1}{2} \right)^2 (Z_1 + Z_2) \right. \\
& \left. + (h_2 - h_1)Z_3 + (h_3 - h_2)Z_4 + h_2(R_2 + R_3) + h_3R_1 \right] \dot{x}(t)
\end{aligned} \quad (16)$$

where $\Gamma_a = x(t) - x(t - h_1)$, $\gamma_{2d} = \frac{1}{d(t) - h_2} \int_{t-d(t)}^{t-h_2} \dot{x}(s) ds$,

$$\gamma_{d3} = \frac{1}{h_3 - d(t)} \int_{t-h_3}^{t-d(t)} \dot{x}(s) ds.$$

Note that $\lim_{d(t) \rightarrow h_2} \gamma_{2d} = \dot{x}(t - h_2)$, and $\lim_{d(t) \rightarrow h_3} \gamma_{d3} = \dot{x}(t - h_3)$.

By using the Leibniz-Newton formula, and denoting

$$\begin{aligned}
\eta_2^T(t) = & [x^T(t) \quad x^T(t - d(t)) \quad \dot{x}^T(t) \quad x^T(t - \tau) \quad \dot{x}^T(t - \tau) \\
& x^T\left(t - \frac{h_1}{2}\right) \quad x^T(t - h_1) \quad x^T(t - h_2) \quad x^T(t - h_3) \quad \gamma_{2d}^T \quad \gamma_{d3}^T] \quad (17)
\end{aligned}$$

the following equations hold for any free-weighting matrices N_2 and M_2 :

$$\begin{aligned}
2\eta_2^T(t) N_2^T [-x(t - h_2) + x(t - d(t)) + (d(t) - h_2)\gamma_{2d}] &= 0 \\
2\eta_2^T(t) M_2^T [-x(t - d(t)) + x(t - h_3) + (h_3 - d(t))\gamma_{d3}] &= 0 \quad (18)
\end{aligned}$$

where $N_{2i} \in \mathbb{R}^{n \times n}$, $M_{2i} \in \mathbb{R}^{n \times n}$, $i \in \{1, \dots, 9\}$.

Corresponding to (1), for any matrices F_{2j} ($j = 1, 2$) with appropriate dimensions, one has

$$\begin{aligned}
2[x^T(t) F_{21}^T + \dot{x}^T(t) F_{22}^T] \\
\times [Ax(t) + A_d x(t - d(t)) - \dot{x}(t) + C_d \dot{x}(t - \tau)] = 0 \quad (19)
\end{aligned}$$

Combining (17)–(19) and $\dot{V}_k(t)$ ($k = 1, \dots, 7$), one can obtain

$$\dot{V}|_{d(t)>h_2} \leq \eta_2^T(t) (\Omega|_{d(t)>h_2}) \eta_2(t) \quad (20)$$

where

$$\Omega|_{d(t)>h_2} = \Gamma_2 + \Phi_2 + \Phi_2^T \quad (21)$$

$$\Gamma_2 = \begin{bmatrix} \Omega_{11}^2 & F_{21}^T A_d & \Pi_2^2 & \frac{1}{\tau} S_2 & F_{21}^T C_d & \Omega_{16} & U_2 & 0 & 0 & 0 & 0 \\ * & \Omega_{22} & A_d^T F_{22} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & \Omega_{33}^2 & 0 & F_{22}^T C_d & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & * & \Omega_{44} & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & * & * & -S_1 & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & * & * & * & \Omega_{66} & \Omega_{67} & 0 & 0 & 0 & 0 \\ * & * & * & * & * & * & \Omega_{77}^2 & \Omega_{78}^2 & 0 & 0 & 0 \\ * & * & * & * & * & * & * & \Omega_{88}^2 & -Q_{12} & 0 & 0 \\ * & * & * & * & * & * & * & * & -Q_{22} & 0 & 0 \\ * & * & * & * & * & * & * & * & * & \Pi_a^2 & 0 \\ * & * & * & * & * & * & * & * & * & * & \Pi_b^2 \end{bmatrix}$$

$$\begin{aligned}
\Phi_2^T = & [0 \quad N_2^T - M_2^T \quad 0 \quad 0 \quad 0 \quad 0 \quad 0 \quad 0 \quad -N_2^T \\
& M_2^T \quad (d(t) - h_2)N_2^T \quad (h_3 - d(t))M_2^T]
\end{aligned}$$

$$\Pi_2^2 = \frac{d(t) - h_2}{h_3 - h_2} P_3 + \frac{h_3 - d(t)}{h_3 - h_2} P_1 + A^T F_{22} - F_{21}^T$$

$$\Pi_a^2 = -(d(t) - h_2)(Z_4 + (1 - \dot{d}(t))R_1), \Pi_b^2 = -(h_3 - d(t))Z_4$$

By the results above-mentioned, we can conclude that

$$\begin{aligned}
\eta_2^T(t) (\Omega|_{d(t)>h_2}) \eta_2(t) = & \frac{d(t) - h_2}{h_3 - h_2} \eta_{21}^T(t) \Omega_3 \eta_{21}(t) \\
& + \frac{h_3 - d(t)}{h_3 - h_2} \eta_{22}^T(t) \Omega_4 \eta_{22}(t) \quad (22)
\end{aligned}$$

where Ω_3 and Ω_4 results from $\Omega|_{d(t)>h_2}$ for $d(t) \rightarrow h_2$ and $d(t) \rightarrow h_3$, respectively, and

$$\begin{aligned}
\eta_{21}^T(t) = & [x^T(t) \quad x^T(t - d(t)) \quad \dot{x}^T(t) \quad x^T(t - \tau) \quad \dot{x}^T(t - \tau) \\
& x^T\left(t - \frac{h_1}{2}\right) \quad x^T(t - h_1) \quad x^T(t - h_2) \quad x^T(t - h_3) \quad \gamma_{2d}^T]
\end{aligned}$$

$$\begin{aligned}
\eta_{22}^T(t) = & [x^T(t) \quad x^T(t - d(t)) \quad \dot{x}^T(t) \quad x^T(t - \tau) \quad \dot{x}^T(t - \tau) \\
& x^T\left(t - \frac{h_1}{2}\right) \quad x^T(t - h_1) \quad x^T(t - h_2) \quad x^T(t - h_3) \quad \gamma_{2d}^T]
\end{aligned}$$

Moreover, using (3), one can obtain

$$\Omega_3 = \frac{\mu_{\max} - \dot{d}(t)}{\mu_{\max} - \mu_{\min}} \Omega_3|_{\dot{d}(t) \rightarrow \mu_{\min}} + \frac{\dot{d}(t) - \mu_{\min}}{\mu_{\max} - \mu_{\min}} \Omega_3|_{\dot{d}(t) \rightarrow \mu_{\max}}$$

$$\Omega_4 = \frac{\mu_{\max} - \dot{d}(t)}{\mu_{\max} - \mu_{\min}} \Omega_4|_{\dot{d}(t) \rightarrow \mu_{\min}} + \frac{\dot{d}(t) - \mu_{\min}}{\mu_{\max} - \mu_{\min}} \Omega_4|_{\dot{d}(t) \rightarrow \mu_{\max}}$$

According to [15] and [21], for $d(t) = h_2$, the following expression holds:

$$\dot{V}(t)|_{d(t)=h_2} = \max\{\eta_1^T(\Omega|_{d(t)<h_2})\eta_1, \eta_2^T(\Omega|_{d(t)>h_2})\eta_2\} \quad (23)$$

The proof is thus completed.

Table I. Allowable upper bound of h_{\max} for various μ_{\max} .

μ_{\max}	0	0.5	0.9	1
Fridman <i>et al.</i> [31]	1.59	1.26	0.97	—
He <i>et al.</i> [32]	1.96	1.51	1.07	—
Xiao <i>et al.</i> [33]	2.05	1.82	1.74	1.72
Bai <i>et al.</i> [34]	2.05	1.89	1.85	1.85
Theorem 1	3.37	3.27	3.16	3.15

Remark 1. It should be pointed out that Theorem 1 presents an improved delay-dependent stability criterion for linear neutral systems with time-varying delay by constructing a novel LKF, which is much less conservative than most results in the literature, such as the results in [31–36]. The reduced conservatism of Theorem 1 benefits from the construction of the new LKF in (6) based on the idea of delay partitioning.

Remark 2. It is interesting to consider the case when μ_{\min} is unknown. In this case, from Theorem 1, by fulfilling the restrictions:

$$P_1 > P_2, P_3 > P_1, R_2 > 0 \quad (24)$$

the neutral system (1) with delay restrictions (2) and (3) is asymptotically stable.

Remark 3. Another important case to consider is the case when no restrictions are cast upon the time-varying delay derivative's characteristics. In this case, as we have no information about $\dot{d}(t)$, from Theorem 1, we must consider the following restrictions (25) such that the neutral system (1) with delay restrictions (2) and (3) is asymptotically stable.

$$P_1 = P_2 = P_3, Q_1 = 0, R_1 = 0, R_2 = 0 \quad (25)$$

Remark 4. Because of the terms U_1 and U_2 , Theorem 1 is valid only for minimum delay strictly greater than zero. However, it is straightforward to extend these results to the case where $h_{\min} = 0$ by considering $U_1 = 0$ and $U_2 = 0$.

IV. NUMERICAL EXAMPLES

This section presents some examples to illustrate the effectiveness of the methods derived above.

Example 1. Consider the neutral system (1) with [33]

$$A = \begin{bmatrix} -2 & 1 \\ 1 & -0.9 \end{bmatrix}, \quad A_d = \begin{bmatrix} 0 & 0 \\ 0 & -1 \end{bmatrix}, \quad C_d = \begin{bmatrix} 0.1 & 0 \\ 0 & 0.1 \end{bmatrix}$$

For $h_{\min} = 0$, $S_2 = 0$, and unknown μ_{\min} , and various values of μ_{\max} , the admissible upper bound value of h_{\max} to make the system (1) asymptotically stable are shown in Table I. It can be

Table II. Allowable upper bound of h_{\max} for various τ .

τ	0.1	0.2	0.3	0.4	0.5	0.6
Liu <i>et al.</i> [35]	1.772	1.764	1.755	1.746	1.737	1.729
Qian <i>et al.</i> [36]	1.820	1.807	1.793	1.779	1.766	1.752
Theorem 1	2.706	2.706	2.706	2.706	2.706	2.706

τ	0.7	0.8	0.9	1.0	1.1	10000
Liu <i>et al.</i> [35]	1.722	1.715	1.711	1.708	1.707	1.707
Qian <i>et al.</i> [36]	1.739	1.727	1.718	1.712	1.712	1.710
Theorem 1	2.706	2.706	2.706	2.706	2.706	2.703

Table III. Allowable upper bound of h_{\max} for various h_{\min}

h_{\min}	0	1	2	3	4	5
h_{\max}	2.732	2.041	2.108	3.094	4.094	5.094

seen that Theorem 1 can give less conservative results than those from [31–34]. This fact implies that the proposed method in this paper is effective and feasible.

Example 2. Consider the neutral system (1) with [36]

$$A = \begin{bmatrix} -0.9 & 0.2 \\ 0.1 & -0.9 \end{bmatrix}, \quad A_d = \begin{bmatrix} -1.1 & -0.2 \\ -0.1 & -1.1 \end{bmatrix}, \quad C_d = \begin{bmatrix} -0.2 & 0 \\ 0.2 & -0.1 \end{bmatrix}.$$

For $h_{\min} = 0$, $\mu_{\max} = 0.01$, and unknown μ_{\min} , and various τ , the results obtained by various methods in the literature for the admissible upper bound value of h_{\max} for which the system (1) remains stable, are shown in Table II, which implies that the proposed method is much less conservative than the existing results.

Example 3. Consider the neutral system (1) with the same system matrices as Example 2. For $\mu_{\min} = -0.1$, $\mu_{\max} = 0.1$, and various h_{\min} , the results obtained by the proposed method for the admissible upper bound value of h_{\max} for which the system (1) remains stable are shown in Table III.

V. CONCLUSION

In this paper, the stability analysis for linear neutral systems with time-varying delay are discussed. The main contribution of this paper is the construction of a new LKF based on the idea of delay partitioning. Introducing appropriate free-weighting matrices, those delay partitioning LKFs lead to a novel stability condition that dependent on both the upper and lower bounds on the delay derivative, which is established in terms of LMIs and can be solved readily by using existing LMI optimization techniques. Numerical examples demonstrate that the stability criteria are less conservative than existing results in the literature. In addition, how to achieve a more appropriate trade-

off between constructing the Lyapunov functional and decreasing the unnecessary decision variables in the results is the aim of our future work.

REFERENCES

- Han, S., G. Tang, Y. Chen, X. Yang, and X. Yang, "Optimal vibration control for vehicle active suspension discrete-time systems with actuator time delay," *Asian J. Control*, Vol. 15, No. 6, pp. 1579–1588 (2013).
- Weng, F., Y. Ding, G. Yang, L. Liang, and Z. Yu, "Less conservative stability criteria for discrete-time nonlinear stochastic singular systems with mixed time-delay," *Asian J. Control*, Vol. 15, No. 6, pp. 1871–1876 (2013).
- Wu, A., Q. Lin, Y. Fu, and G. Duan, "A less conservative stability condition of time-delay systems with polytopic uncertainty," *Asian J. Control*, Vol. 15, No. 5, pp. 1543–1547 (2013).
- Zhang, L., H. Gao, and O. Kaynak, "Network-induced constraints in networked control system—a survey," *IEEE Trans. Ind. Inform.*, Vol. 9, No. 1, pp. 403–416 (2013).
- Jiang, S. and H. Fang, "Fault estimation for nonlinear networked systems with time-varying delay and random packet dropout," *Asian J. Control*, Vol. 16, No. 1, pp. 126–137 (2014).
- Zhang, L., E.-K. Boukas, and A. Haidar, "Delay-range-dependent control synthesis for time-delay systems with actuator saturation," *Automatica*, Vol. 44, No. 10, pp. 2691–2695 (2008).
- Alpaslan, M. N., "Robust delay-dependent guaranteed cost controller design for uncertain neutral systems," *Appl. Math. Comput.*, Vol. 215, No. 8, pp. 2936–2949 (2009).
- Quan, Q. and K. Cai, "Stability analysis of a class of neutral type systems in a critical case without restriction on the principal neutral term," *Asian J. Control*, Vol. 15, No. 6, pp. 1858–1861 (2013).
- Han, Q. L., "Improved stability criteria and controller design for linear neutral systems," *Automatica*, Vol. 45, No. 8, pp. 1948–1952 (2009).
- Park, J. H., "A new delay-dependent criterion for neutral systems with multiple delays," *J. Comput. Appl. Math.*, Vol. 136, No. 1–2, pp. 177–184 (2001).
- Sun, T., H. Su, and Z. Wu, "State feedback control for discrete-time Markovian jump systems with random communication time delay," *Asian J. Control*, Vol. 16, No. 1, pp. 296–302 (2013).
- Li, Y., X. Zhang, and M. Yuan, "Robust exponential stability and stabilization of a class of nonlinear stochastic time-delay systems," *Asian J. Control*, Vol. 15, No. 4, pp. 1168–1177 (2013).
- Li, P., Z. Bao, Q. Yang, and W. Yan, " H_∞ control synthesis for lurie networked control systems with multiple delays based on the non-uniform characteristic," *Asian J. Control*, Vol. 15, No. 4, pp. 1112–1123 (2013).
- Long, S., S. Zhong, and Z. Liu, "Robust stochastic stability for a class of singular systems with uncertain markovian jump and time-varying delay," *Asian J. Control*, Vol. 15, No. 4, pp. 1102–1111 (2013).
- Zhang, L. and P. Shi, "Stability, l_2 -gain and asynchronous h_8 control of discrete-time switched systems with average dwell time," *IEEE Trans. Autom. Control*, Vol. 54, No. 9, pp. 2193–2200 (2009).
- Stojanovic, S. B., D. Debeljkovic, and D. S. Antic, "Robust finite-time stability and stabilization of linear uncertain time-delay systems," *Asian J. Control*, Vol. 15, No. 5, pp. 1548–1554 (2013).
- Xi, J., Z. Shi, G. Liu, and Y. Zhong, "Dynamic output feedback consensualization of uncertain swarm systems with time delays," *Asian J. Control*, Vol. 15, No. 4, pp. 1228–1237 (2013).
- Zhang, L., P. Shi, E. Boukas, and C. Wang, "H8 model reduction for uncertain switched linear discrete-time systems," *Automatica*, Vol. 44, No. 11, pp. 2944–2949 (2008).
- Wu, L. and Z. Wang, "Guaranteed cost control of switched systems with neutral delay via dynamic output feedback," *Int. J. Syst. Sci.*, Vol. 40, No. 7, pp. 717–728 (2009).
- Kwon, O., M. Park, J. Park, S. Lee, and E. Cha, "New delay-partitioning approaches to stability criteria for uncertain neutral systems with time-varying delays," *J. Frankl. Inst. – Eng. Appl. Math.*, Vol. 349, No. 9, pp. 2799–2823 (2012).
- Park, P. G., "A delay-dependent stability criterion for systems with uncertain linear state-delayed systems," *IEEE Trans. Autom. Control*, Vol. 44, No. 4, pp. 876–877 (1999).
- Wu, M., Y. He, and J. She, "New delay-dependent stability criteria and stabilizing method for neutral systems," *IEEE Trans. Autom. Control*, Vol. 49, No. 12, pp. 2266–2271 (2004).
- Fridman, E., U. Shaked, and K. Liu, "New conditions for delay-derivative-dependent stability," *Automatica*, Vol. 45, No. 11, pp. 2723–2727 (2009).
- Gouaisbaut, F. and D. Peaucelle, "Delay-dependent stability analysis of linear time delay systems," in *Proc. IFAC Workshop Time Delay System*, L'Aquila, Italy, pp. 1–11 (2006).
- Wu, M., Y. He, and J. H. She, "New delay-dependent stability criteria and stabilizing method for neutral systems," *IEEE Trans. Autom. Control*, Vol. 49, No. 12, pp. 2266–2271 (2004).
- He, Y., Q.G. Wang, L.H. Xie, and C. Lin, "Further improvement of free-weighting matrices technique for systems with time-varying delay," *IEEE Trans. Autom. Control*, Vol. 52, No. 2, pp. 293–300 (2007).
- Wu, L., X. Su, P. Shi, and J. Qiu, "A new approach to stability analysis and stabilization of discrete-time T-S fuzzy time-varying delay systems," *IEEE Trans. Syst. Man Cybern. B Cybern.*, Vol. 41, No. 1, pp. 273–286 (2011).
- Wu, L., X. Su, P. Shi, and J. Qiu, "Model approximation for discrete-time state-delay systems in the T-S fuzzy

- framework,” *IEEE Trans. Fuzzy Syst.*, Vol. 19, No. 2, pp. 366–378 (2011).
29. Duan, W., B. Du, J. You, and Y. Zou, “Synchronization criteria for neutral complex dynamic networks with interal time-varying coupling delays,” *Asian J. Control*, Vol. 15, No. 5, pp. 1385–1396 (2013).
 30. Luis, F., J. Y. Ishihara, G. A. Borges, and A. Bauchspiess, “New delay-and-delay-derivative- dependent stability criteria for systems with time-varying delay,” *Proc. 49th IEEE Conf. Decis. Control*, Atlanta, GA, USA, pp. 1004–1009 (2010).
 31. Fridman, E. and U. Shaked, “Delay-dependent stability and h_s control: constant and time-varying delays,” *Int. J. Control*, Vol. 76, No. 1, pp. 48–60 (2003).
 32. He, Y., M. Wu, and J. She, “Delay-dependent robust stability and stabilization of uncertain neutral systems,” *Asian J. Control*, Vol. 10, No. 3, pp. 376–378 (2008).
 33. Xiao, S. and H. Zeng, “On delay-dependent stability of neutral systems with time-varying delay,” *J. Hunan Univ. Technol.*, Vol. 23, No. 4, pp. 58–61 (2009).
 34. Bai, L., S. Xiao, and H. Zeng, “Delay-dependent stability for neutral systems with time-varying delay,” *IEEE Chinese Control Decis. Conf.*, Mianyang, China, pp. 540–543 (2011).
 35. Liu, X., M. Wu, R. Martin, and M. Tang, “Stability analysis for neutral systems with mixed delays,” *J. Comput. Appl. Math.*, Vol. 202, No. 2, pp. 478–497 (2007).
 36. Qian, W., S. Wang, and J. Liu, “Improved stability criteria for uncertain neutral systems with time-varying delay,” *IEEE Chinese Control Conf.*, Beijing, China, pp. 863–867 (2010).