ARTICLE IN PRESS

Automatica ▮ (▮▮▮) ▮▮▮-▮▮



Contents lists available at ScienceDirect

Automatica

journal homepage: www.elsevier.com/locate/automatica



Technical communique

Stability of positive coupled differential-difference equations with unbounded time-varying delays*

Pubudu N. Pathirana ^a, Phan T. Nam ^b, Hieu M. Trinh ^{a,*}

- ^a School of Engineering, Deakin University, Geelong, VIC 3217, Australia
- ^b Department of Mathematics, Quy Nhon University, Binh Dinh, Viet Nam

ARTICLE INFO

Article history: Received 22 April 2017 Received in revised form 7 February 2018 Accepted 27 February 2018 Available online xxxx

Keywords: Coupled differential-difference equations Positive systems Unbounded time-varying delays

ABSTRACT

This paper considers the stability problem of a class of positive coupled differential-difference equations with unbounded time-varying delays. A new method, which is based on upper bounding of the state vector by a decreasing function, is presented to analyze the stability of the system. Different from the existing methods, our method does not use the usual Lyapunov–Krasovskii functional method or the comparison method based on positive systems with constant delays. A new criterion is derived which ensures asymptotic stability of the system with unbounded time-varying delays. A numerical example with simulation results is given to illustrate the stability criterion.

© 2018 Elsevier Ltd. All rights reserved.

1. Introduction

Many systems in engineering are described by a differential equation coupled with a difference equation (see Gu, 2010; Mazenc, Ito, & Pepe, 2013; Pepe, Jiang, & Fridman, 2008 and the references therein). Such equations are called coupled differentialdifference equations (CDDEs). They cover many important classes of dynamical systems, such as neutral systems, systems with multiple commensurate delays, some singular systems as special cases (Gu & Liu, 2009; Gu & Niculescu, 2006). Many partial differential equations with nonstandard derivative boundary conditions, for example, lossless propagation systems described by a partial differential equation of hyperbolic type, can also be reformulated into CDDEs with finite delay (Niculescu, 2001; Răsvan, 2006). The most widely used approach to analyze stability of CDDEs is based on the discretized Lyapunov-Krasovskii functional method combined with linear matrix inequalities (LMIs) (see Gu, 2010; Gu & Liu, 2009; Gu, Zhang, & Xu, 2011; Karafyllis, Pepe, & Jiang, 2009; Li & Gu, 2010; Mazenc et al., 2013; Pepe et al., 2008; Zhang, Peet, & Gu, 2011 and the references therein).

Positive systems, whose states are never negative whenever the initial conditions are non-negative, appear naturally in many fields such as biology, industrial engineering and economics (see Kaczorek, 2002). The stability problem of positive systems with time

E-mail addresses: pubudu.pathirana@deakin.edu.au (P.N. Pathirana), phanthanhnam@qnu.edu.vn (P.T. Nam), hieu.trinh@deakin.edu.au (H.M. Trinh).

 $https://doi.org/10.1016/j.automatica.2018.03.055\\0005-1098/© 2018 Elsevier Ltd. All rights reserved.$

delays has also attracted significant research attention in recent years (see Ait Rami, 2009; Liu & Dang, 2011; Liu, Yu, & Wang, 2010; Nam, Phat, Pathirana, & Trinh, 2016; Nam, Trinh, & Pathirana, 2016; Ngoc, 2013; Ngoc & Trinh, 2016; Phat & Sau, 2014; Shen & Lam, 2014; Zhu, Li, & Zhang, 2012). Recently, an overview on the recent developments of stability of linear positive time-delay systems has been given in Briat (2017). Shen and Zheng (2015) considered the stability problem of a class of positive CDDEs with bounded time-varying delay. Their method is based on a comparison between the solution of CDDEs with a time-varying delay and the solution of CDDEs with a constant delay, which is an upper bound of the time-varying delay. Hence, it is not possible to extend this method to CDDEs with infinity time-varying delays.

Normally, time delays which appear in engineering systems, are bounded (see Fridman, 2014; Gu, Chen, & Kharitonov, 2003; Shafai & Sadaka, 2012; Shafai, Sadaka, & Ghadami, 2012; Sipahi, Vyhlidal, & Niculescu, 2012). However, it also appears that there are many dynamical systems whose time delays are unbounded. In dynamical systems that have a spacial nature, such as neural networks, time delay is often unbounded. Therefore, in recent years there has been a growing interest in the stability problem of dynamical systems with unbounded time-delay (see Chen & Liu, 2017; Feyzmahdavian, Charalambous, & Johansson, 2014; Li & Cao, 2017; Liu & Dang, 2011; Liu, Lu, & Chen, 2010; Shen & Lam, 2015; Zhou, 2013, 2014).

So far, most of the existing results reported only on the stability of CDDEs with constant time delays or bounded time-varying delays. No papers have reported on the stability of CDDEs with unbounded time-varying delays. In this paper, inspired by the work of Liu and Dang (2011), we study the stability problem of

in this paper was not presented at any conference. This paper was recommended for publication in revised form by Associate Editor Rifat Sipahi under the direction of Editor André L. Tits.

^{*} Corresponding author.

2

a class of positive CDDEs with unbounded time-varying delays. Instead of using the comparison method (Shen & Zheng, 2015), we construct estimates of the solution of the considered CDDEs on non-equal time sub-intervals. As a result, we can analyze the stability of CDDEs with unbounded time-varying delays. A new stability condition for the system is obtained. The obtained result is illustrated by a numerical example.

2. Notations and a problem statement

Notations. $\mathbb{R}^n(\mathbb{R}^n_{0,+}, \mathbb{R}^n_+)$ is the n-dimensional (nonnegative, positive) vector space; $\overline{1,n}=\{1,2,\ldots,n\}$; given two vectors $x=[x_1\,x_2\,\cdots\,x_n]^T\in\mathbb{R}^n$, $y=[y_1\,y_2\,\cdots\,y_n]^T\in\mathbb{R}^n$, two $n\times n$ matrices $A=[a_{ij}]$ and $B=[b_{ij}]$, the following notations will be used in our development: $x\prec y(\leq y)$ means that $x_i\leq y_i(\leq y_i)$, $\forall i\in\overline{1,n}$; $A\prec B(\leq B)$ means that $a_{ij}< b_{ij}(\leq b_{ij})$, $\forall i,j\in\overline{1,n}$; A is nonnegative if $0\leq A$; A is a Metzler matrix if $a_{ij}\geq 0$, $\forall i,j\in\overline{1,n}$, $i\neq j$; $\|x\|_\infty=\max_{i=1}^n|x_i|$; $s(A)=\max\{Re(\lambda):\lambda\in\sigma(A)\}$ stands for the spectral abscissa of a matrix A; $\rho(A)=\max\{|\lambda|:\lambda\in\sigma(A)\}$ stands for the spectral radius of a matrix A. A is a Schur matrix if $\rho(A)<1$; The limitation of a vector-valued function is understood in the component-wise sense.

Consider the following linear CDDEs with time-varying delays

$$\dot{x}(t) = Ax(t) + By(t - \tau(t)), \ t \ge 0, \tag{1}$$

$$y(t) = Cx(t) + Dy(t - h(t)), \tag{2}$$

where $x(.) \in \mathbb{R}^n$, $y(.) \in \mathbb{R}^m$ are the state vectors. $A \in \mathbb{R}^{n \times n}$, $B \in \mathbb{R}^{n \times m}$, $C \in \mathbb{R}^{m \times n}$ and $D \in \mathbb{R}^{m \times m}$ are known constant matrices. D is assumed to be a Schur matrix. Here, the delays $\tau(.) \in \mathbb{R}_{0,+}$ and $h(.) \in \mathbb{R}_{0,+}$ are unknown time-varying delays. Similar to Liu and Dang (2011), the delays can be unbounded and assumed to satisfy the following growth condition:

Assumption 1. There exist a positive scalar T>0 and a scalar $\theta\in(0,1)$ such that

$$\max \left\{ \sup_{t \ge T} \frac{\tau(t)}{t}, \sup_{t \ge T} \frac{h(t)}{t} \right\} \le \theta. \tag{3}$$

It is easy to see that all the bounded delays satisfy condition (3). Furthermore, condition (3) implies that $t - \tau(t) \ge (1 - \theta)t > 0$ and $t - h(t) \ge (1 - \theta)t > 0$ for all $t \ge T$. Hence, the initial condition of system (1)–(2) is given by $x(0) = \psi(0)$, $y(s) = \phi(s)$, $s \in [-\max_{t \in [0,T]} \max h(t), \tau(t), 0)$. Let us denote by $x(t, \psi, \phi)$ and $y(t, \psi, \phi)$ the state trajectories with the initial condition (ψ, ϕ) of system (1)–(2).

The main objective of this paper is to derive a sufficient condition for the asymptotic stability of system (1)–(2).

3. Main result

The following lemmas are needed for our development.

Lemma 1 (Berman & Plemmons, 1994). (i) Let $M \in \mathbb{R}_+^{n \times n}$ be a nonnegative matrix. Then, the following statements are equivalent: (i₁) M is Schur stable; (i₂) (M-I)q < 0 for some $q \in \mathbb{R}_+^n$; (i₃) $(I-M)^{-1} > 0$.

(ii) Let $M \in \mathbb{R}^{n \times n}$ be a Metzler matrix. Then, the following statements are equivalent: (ii₁) M is Hurwitz stable; (ii₂) Mq < 0 for some $q \in \mathbb{R}^n_+$; (ii₃) $M^{-1} \leq 0$.

Definition 2 (*Kaczorek*, 2002). System (1)–(2) is said to be positive if for any non-negative initial values, $\psi(0) \succeq 0$, $\phi(s) \succeq 0$, $s \in [-T, 0)$, the state trajectories of system (1)–(2) satisfy that $x(t, \psi, \phi) \succeq 0$, $\forall t \geq 0$ and $y(t, \psi, \phi) \succeq 0$, $\forall t \geq 0$.

Lemma 3 (Ngoc & Trinh, 2016; Shen & Zheng, 2015). Assume that A is a Metzler matrix, B, C, D are nonnegative, D is a Schur matrix. Then, (i) For all piecewise continuous functions $\omega(t) \succeq 0$, $u(t) \succeq 0$, the following system is positive

$$\dot{x}(t) = Ax(t) + By(t - \tau(t)) + \omega(t), \tag{4}$$

$$y(t) = Cx(t) + Dy(t - h(t)) + u(t).$$
 (5)

(ii) For $\psi_1(0) \prec \psi_2(0)$ and $\phi_1(s) \prec \phi_2(s)$, $s \in [-T, 0)$, we have

$$x(t, \psi_1, \phi_1) \le x(t, \psi_2, \phi_2), \ \forall t \ge 0,$$
 (6)

$$y(t, \psi_1, \phi_1) \le y(t, \psi_2, \phi_2), \ \forall t \ge 0.$$
 (7)

(iii) Assume that $s(A + B(I - D)^{-1}C) < 0$. Then, there exist $p \in \mathbb{R}^n_+$, $q \in \mathbb{R}^m_+$ and $\mu \in (0, 1)$ such that

$$Ap + Bq < 0, \tag{8}$$

$$Cp + Dq < (1 - \mu)q, \tag{9}$$

$$(I-D)^{-1}Cp < (1-\mu)q.$$
 (10)

Proof. The proof of (i) is similar to Shen and Zheng (2015). Therefore, we omit it here. We now use (i) to prove (ii). Since system (1)–(2) is linear, we have

$$x(t, \psi_2, \phi_2) - x(t, \psi_1, \phi_1) = x(t, \psi_2 - \psi_1, \phi_2 - \phi_1). \tag{11}$$

By the positivity of system (1)–(2), we have

$$x(t, \psi_2 - \psi_1, \phi_2 - \phi_1) \ge 0, \forall t \ge 0.$$
 (12)

From (11) and (12), we obtain (6). Similarly, we also obtain (7). (iii) By Ngoc and Trinh (2016), there exist two vectors $p \in \mathbb{R}^n_+$ and $q \in \mathbb{R}^m_+$ such that

$$Ap + Bq < 0, \tag{13}$$

$$Cp + (D - I)q < 0. (14)$$

Since *D* is Schur stable and nonnegative, $(I - D)^{-1}$ is nonnegative by Lemma 1. Left multiplying $(I - D)^{-1}$ on (14), we obtain

$$(I-D)^{-1}Cp - q < 0.$$
 (15)

Since (14) and (15) are strict inequalities, there is a scalar $\mu \in (0, 1)$ such that inequalities (9) and (10) hold. The proof of Lemma 3 is completed. \square

We are now in a position to introduce the main result in the form of the following theorem.

Theorem 4. Assume that A is a Metzler matrix, B, C, D are nonnegative, D is a Schur matrix and $s(A + B(I - D)^{-1}C) < 0$. Then, for all time-varying delays satisfying condition (3), system (1)–(2) is asymptotically stable.

Proof. *Step 1:* In this step, we prove that there exist a scalar $\mu^* \in (0, \mu)$ and a time $t_1 > 0$ such that

$$x(t, p, q) \le (1 - \mu^*)p, \ \forall t \ge t_1,$$
 (16)

$$y(t, p, q) \le (1 - \mu^*)q, \ \forall t \ge t_1,$$
 (17)

where p, q μ are defined in Lemma 3. Firstly, similar to Shen and Zheng (2015), we define $e_x(t) = p - x(t, p, q)$, $e_y(t) = q - y(t, p, q)$. Then, $e_x(t)$ and $e_y(t)$ satisfy the following system:

$$\dot{e}_x(t) = Ae_x(t) + Be_y(t - \tau(t)) - (Ap + Bq),$$
 (18)

$$e_{\nu}(t) = Ce_{x}(t) + De_{\nu}(t - h(t)) - (Cp + (D - I)q).$$
(19)

By parts (i) and (iii) of Lemma 3, we have $e_x(t) \succeq 0$, $\forall t \geq 0$, and $e_v(t) \succeq 0$, $\forall t \geq 0$ which imply that

$$x(t, p, q) \le p, \forall t \ge 0, \tag{20}$$

$$y(t, p, q) \le q, \forall t \ge 0. \tag{21}$$

On the other hand, from (2), we have

$$y(t) = \begin{cases} Cx(t) + Dy(t - h(t)) & \text{if } h(t) > 0\\ (I - D)^{-1}Cx(t) & \text{if } h(t) = 0. \end{cases}$$
 (22)

Combining (9) and (10) and (20)-(22), we obtain

$$y(t, p, q) < (1 - \mu)q, \ \forall t \ge 0.$$
 (23)

Further, by Lemma II.2 in Ngoc and Trinh (2016), we have s(A) < 0 which implies that $A^{-1} \le 0$. Left multiplying A^{-1} on (8), we obtain

$$p > -A^{-1}Bq. \tag{24}$$

We will prove that x(t, p, q) is decreasing and

$$\lim_{t \to \infty} x(t, p, q) \le -A^{-1}Bq. \tag{25}$$

By (1), (8), (20) and (21), we have $\dot{x}(t, p, q) < 0$, $\forall t \geq 0$. This follows that x(t, p, q) is a decreasing function on $[0, \infty)$. To prove (25), we consider the following positive comparison system

$$\dot{z}(t) = Az(t) + Bq, \ t \ge 0. \tag{26}$$

By using (21) and the solution comparison method, we obtain

$$x(t, p, q) \le z(t, p), \ \forall t \ge 0. \tag{27}$$

Putting $u(t) = z(t) + A^{-1}Bq$. Then, u(t) satisfies the system $\dot{u}(t) = Au(t)$. Since A is a Metzler matrix and s(A) < 0, system $\dot{u}(t) = Au(t)$ is positive and asymptotically stable. Also note that (24) is equivalent to $p + A^{-1}Bq > 0$. Hence, we have $u(t, p + A^{-1}Bq) \ge 0$, $\forall t \ge 0$ and $\lim_{t \to \infty} u(t, p + A^{-1}Bq) = 0$, which imply that $z(t, p) \ge -A^{-1}Bq$, $\forall t \ge 0$ and $\lim_{t \to \infty} z(t, p) = -A^{-1}Bq$. Combining this with (27), we obtain (25).

On the other hand, since (24) is a strict inequality, there exists a scalar $\mu^* \in (0, \mu)$ such that

$$-A^{-1}Bq < (1-\mu^*)p < p.$$
 (28)

Inequalities (25) and (28) imply that there exists a time $t_1 > 0$ such that (16) holds. Combining $\mu^* < \mu$ with (23), we obtain (17).

Step 2: In this step, we prove that there is a sequence of increasing numbers $0 = T_0 < T_1 < T_2 < \cdots < T_s < \cdots < \infty$ such that the following estimations hold

$$x(t, p, q) \leq (1 - \mu^*)^s p, \ \forall t \in [T_s, T_{s+1}],$$
 (29)

$$y(t, p, q) \le (1 - \mu^*)^s q, \ \forall t \in [T_s, T_{s+1}].$$
 (30)

Firstly, from Assumption 1, let us denote $Q_0 = 0$, $Q_1 = T$, $Q_{k+1} = \left\lceil \frac{Q_k}{1-\theta} \right\rceil$, $k = 1, 2, \ldots$, then: (i) (Q_k) is a strict increasing sequence and tends to infinity; and (ii) for every k > 0, we have $t - \tau(t) \ge Q_k$, and $t - h(t) \ge Q_k$ for all $t \ge Q_{k+1}$.

For s=0, denote $k_1=\min\{k\in\mathbb{N}:t_1\leq Q_k\}$ and choose $T_1=Q_{k_1}$. Then, inequalities (20) and (21) imply that the estimations (29) and (30) hold for s=0.

For s = 1, let us consider the following system

$$\dot{x}_1(t) = Ax_1(t) + By_1(t - \tau(t)), \ t \ge Q_{k_1 + 1}, \tag{31}$$

$$y_1(t) = Cx_1(t) + Dy_1(t - h(t)).$$
 (32)

Similar to part (ii) of Lemma 3, we also prove that, for $\psi_1(Q_{k_1+1}) \leq \psi_2(Q_{k_1+1})$ and $\phi_1(s) \leq \phi_2(s)$, $s \in [Q_{k_1}, Q_{k_1+1})$, then

$$x_1(t, \psi_1, \phi_1) \le x_1(t, \psi_2, \phi_2), \ \forall t \ge Q_{k_1+1},$$
 (33)

$$y_1(t, \psi_1, \phi_1) \le y_1(t, \psi_2, \phi_2), \ \forall t \ge Q_{k_1+1}.$$
 (34)

Let us set

$$p_1 = (1 - \mu^*)p, q_1 = (1 - \mu^*)q. \tag{35}$$

By combining (16), (17), (33) and (34), we obtain

$$x(t, p, q) \le x_1(t, p_1, q_1), \ \forall t \ge Q_{k_1+1},$$
 (36)

$$y(t, p, q) \le y_1(t, p_1, q_1), \ \forall t \ge Q_{k_1+1}.$$
 (37)

Note that, by linearity, we can verify that inequalities (8)–(10) also hold for $p=p_1$ and $q=q_1$. Therefore, by doing the same lines as in Step 1 for system (31) and (32), we also obtain a time $t_2>Q_{k_1+1}$ such that

$$x_1(t, p_1, q_1) \le (1 - \mu^*)p_1, \ \forall t \ge t_2,$$
 (38)

$$y_1(t, p_1, q_1) \le (1 - \mu^*)q_1, \ \forall t \ge t_2.$$
 (39)

By combining (35)–(39), we obtain

$$x(t, p, q) \le (1 - \mu^*)^2 p, \ \forall t \ge t_2,$$
 (40)

$$y(t, p, q) < (1 - \mu^*)^2 q, \ \forall t > t_2.$$
 (41)

Denote $k_2 = \min\{k \in \mathbb{N} : t_2 \le Q_k\}$ and choose $T_2 = Q_{k_2}$. Then, from (40) and (41) we obtain the estimations (29) and (30) for the case s = 1. Similarly, we also find $T_2 < T_3 < \cdots$ such that the estimations (29) and (30) hold for $s = 2, 3, \ldots$

Step 3: In this step, we prove that system (1)–(2) is asymptotically stable. Since all norms in \mathbb{R}^n are equivalent, we will use the infinite norm instead of the Euclidean norm. For any $\epsilon>0$, let us denote $N=\max\{\|p\|_\infty,\|q\|_\infty\}$ and choose $\delta=\frac{\epsilon}{N^2}$. Then, for any initial condition ψ , ϕ satisfying $\|\psi(0)\|_\infty \leq \delta$ and $\max_{s\in [-\max_{t\in[0,T]}\max\{h(t),\tau(t)\},0)}\|\phi(s)\|_\infty \leq \delta$, we have $\psi(0)\leq \frac{\epsilon}{N}p$ and $\max_{s\in [-\max_{t\in[0,T]}\max\{h(t),\tau(t)\},0)}\phi(s)\leq \frac{\epsilon}{N}q$. By linearity of system (1)–(2) and (20)–(21), we have

$$x(t, \psi, \phi) \le \frac{\epsilon}{N} x(t, p, q) \le \frac{\epsilon}{N} p, \ \forall t \ge 0,$$
 (42)

$$y(t, \psi, \phi) \le \frac{\epsilon}{N} y(t, p, q) \le \frac{\epsilon}{N} q, \ \forall t \ge 0,$$
 (43)

which follow that $\|x(t,\psi,\phi)\|_{\infty} \le \epsilon$, $\|y(t,\psi,\phi)\|_{\infty} \le \epsilon$. On the other hand, inequalities (29)–(30) imply that $\lim_{t\to\infty} x(t,p,q)=0$ and $\lim_{t\to\infty} y(t,p,q)=0$. Combining this with (42) and (43), we have $\lim_{t\to\infty} x(t,\psi,\phi)=0$, $\lim_{t\to\infty} y(t,\psi,\phi)=0$. From all the above, we can now conclude that system (1)–(2) is asymptotically stable. The proof of Theorem 4 is completed.

Remark 5. Our method presented in this paper adopts neither the usual Lyapunov–Krasovskii functional method nor the comparison method based on positive systems with constant time delays. The Shen and Zheng (2015) method is for coupled differential-difference equations (CDDEs) with large-but-bounded time-varying delays, whose upper bound may be large and may not be known. Note that for the case where the time-delay is unbounded, and for the case where one would not know whether or not the time varying delay is upper bounded, the Shen and Zheng (2015) method cannot be applied. Our method is for CD-DEs with growth time-varying delays which include large-but-bounded time-varying delays as special cases. Hence, our result is a generalization of the result presented in Shen and Zheng (2015).




Fig. 1. Trajectories of x(t).




Fig. 2. Trajectories of y(t).

4. Numerical example

Example 6. Consider the following positive CDDEs, whose matrices are the same as given in Shen and Zheng (2015) and the two unbounded time-varying delays satisfying condition (3) are given as below

$$\tau(t) = \begin{cases} 1 & t \in [0, 1] \\ 0.3t & t > 1 \end{cases} \text{ and } h(t) = \begin{cases} 1 & t \in [0, 1] \\ 0.1t & t > 1. \end{cases}$$

With some simple computations, we can verify that all the conditions given in Theorem 4 are satisfied. Therefore, the system is asymptotically stable. For simulation purpose, we choose the initial condition $\psi(0) = \begin{bmatrix} 3 & 2 & 1 \end{bmatrix}^T$, $\phi(s) = \begin{bmatrix} 1 & 1.5 \end{bmatrix}^T$, $s \in [-1, 0)$. The state trajectories are depicted in Figs. 1 and 2. It can be observed that the state trajectories are nonnegative and converge to zero.

5. Conclusion

This paper has presented a novel approach to analyzing asymptotic stability of a new class of positive differential-difference equations with unbounded time-varying delays. A numerical example has been considered to illustrate the obtained result. The presented

approach can be further extended to time-varying CDDEs, or time-varying neutral systems whose matrices are bounded by nonnegative matrices.

References

Ait Rami, M. (2009). Stability analysis and synthesis for linear positive systems with time-varying delays. In *Lecture notes in control and information sciences*, *Vol.* 389 (pp. 205–215). Berlin: Spriger-Verlag.

Berman, A., & Plemmons, R. J. (1994). Nonnegative matrices in the mathematical science. SIAM.

Briat, C. (2017). Stability and performance analysis of linear positive systems with delays using input–output methods. *International Journal of Control* Published online, https://doi.org/10.1080/00207179.2017.1326628.

Chen, T., & Liu, X. (2017). µ-stability of nonlinear positive systems with unbounded time-varying delays. *IEEE Transaction on Neural Networks and Learning Systems*, 28(7), 1710–1715.

Feyzmahdavian, H., Charalambous, T., & Johansson, M. (2014). Asymptotic stability and decay rates of homogeneous positive systems with bounded and unbounded delays. SIAM Journal on Control and Optimization, 52(4), 2623–2650.

Fridman, E. (2014). Introduction to Time-Delay Systems-Analysis and Control. Springer.

Gu, K. (2010). Stability problem of systems with multiple delay channels. Automatica, 46(4), 743–751.

Gu, K., Chen, J., & Kharitonov, V. L. (2003). Stability of time delay systems. Birkhauser.
Gu, K., & Liu, J. (2009). Lyapunov-Krasovskii functional for uniform stability of coupled differential-functional equations. Automatica, 45(3), 798–804.

Gu, K., & Niculescu, S.-I. (2006). Stability analysis of time-delay systems: A Lyapunov approach. In: A. Loría, F. Lamnabhi-Lagarrigue, and E. Panteley (Eds.), Lecture notes from FAP 2005.

Gu, K., Zhang, Y., & Xu, S. (2011). Small gain problem in coupled differential-difference equations, time-varying delays, and direct Lyapunov method. International Journal of Robust and Nonlinear Control, 21(4), 429–451.

Kaczorek, T. (2002). Positive 1D and 2D systems. London: Springer-Verlag.

Karafyllis, I., Pepe, P., & Jiang, Z. P. (2009). Stability results for systems described by coupled retarded functional differential equations and functional difference equations. Nonlinear Analysis. Theory, Methods & Applications, 71, 3339–3362.

Li, H., & Gu, K. (2010). Discretized Lyapunov–Krasovskii functional for coupled differential–difference equations with multiple delay channels. *Automatica*, 46(5), 902–909.

Li, X., & Cao, J. (2017). An impulsive delay inequality involving unbounded timevarying delay and applications. *IEEE Transactions on Automatic Control*, 62(7), 3618–3625

Liu, X., & Dang, C. (2011). Stability analysis of positive switched linear systems with delays. *IEEE Transactions on Automatic Control*, 56(7), 1684–1690.

Liu, X., Lu, W., & Chen, T. (2010). Consensus of multi-agent systems with unbounded time-varying delays. IEEE Transactions on Automatic Control, 55(10), 2396–2401.

Liu, X., Yu, W., & Wang, L. (2010). Stability analysis for continuous-time positive systems with time-varying delays. *IEEE Transactions on Automatic Control*, 55(4), 1024–1028.

Mazenc, F., Ito, H., & Pepe, P. (2013). Construction of Lyapunov functionals for coupled differential and continuous time difference equations. In: 52nd IEEE conference on decision and control (pp. 2245–2250).

Nam, P. T., Phat, V. N., Pathirana, P. N., & Trinh, H. (2016). Stability analysis of a general family of nonlinear positive discrete time-delay systems. *International Journal of Control*, 89(7), 1303–1315.

Nam, P. T., Trinh, H., & Pathirana, P. N. (2016). Componentwise ultimate bounds for positive discrete time-delay systems perturbed by interval disturbances. *Automatica*, 72, 153–157.

Ngoc, P. H. A. (2013). Stability of positive differential systems with delay. *IEEE Transactions on Automatic Control*, 58(1), 203–209.

Ngoc, P. H. A., & Trinh, H. (2016). Novel criteria for exponential stability of linear neutral time-varying differential systems. *IEEE Transactions on Automatic Control*, 61(6), 1590–1594.

Niculescu, S.-I. (2001). Lecture notes in control and information science: vol. 269. Delay effects on stability: A robust control approach. London: Springer.

Pepe, P., Jiang, Z. P., & Fridman, E. (2008). A new Lyapunov-Krasovskii methodology for coupled delay differential and difference equations. *International Journal of Control*, 81(1), 107–115.

Phat, V. N., & Sau, N. H. (2014). On exponential stability of linear singular positive delayed systems. *Applied Mathematics Letter*, 38, 67–72.

Răsvan, V. (2006). Functional differential equations of lossless propagation and almost linear behavior. IFAC Proceedings Volumes, 39(10), 138–150.

Shafai, B., Sadaka, H., & Ghadami, R. (2012). Robust stability and constrained stabilization of discrete-time delay systems. In: *Proceedings of 10th IFAC workshop on time delay systems* (pp. 31–36).

Shafai, B., & Sadaka, H. (2012). Robust stability and stabilization of uncertain delay systems. In: Proceedings of 2012 american control conference (pp. 4685–4690).

ARTICLE IN PRESS

P.N. Pathirana et al. / Automatica ■ (■■■■) ■■■-■■■

- Shen, J., & Lam, J. (2014). L_{∞} -gain analysis for positive systems with distributed delays. *Automatica*, 50(1), 175–179.
- Shen, J., & Lam, J. (2015). ℓ_{∞}/L_{∞} -gain analysis for positive linear systems with unbounded time-varying delays. *IEEE Transactions on Automatic Control*, 60(3), 857–862.
- Shen, J., & Zheng, W. X. (2015). Positivity and stability of coupled differential-difference equations with time-varying delays. *Automatica*, *57*, 123–127.
- Sipahi, R., Vyhlidal, T., & Niculescu, S.-I. (2012). Time delay systems: methods, applications and new trends. Springer.
- Zhang, Y., Peet, M., & Gu, K. (2011). Reducing the complexity of the sum-of-squares test for stability of delayed linear systems. *IEEE Transactions on Automatic Control*, 56(1), 229–234.
- Zhou, L. (2013). Dissipativity of a class of cellular neural networks with proportional delays. *Nonlinear Dynamics*, 73(3), 1895–1903.
- Zhou, L. (2014). Global asymptotic stability of cellular neural networks with proportional delays. *Nonlinear Dynamics*, 77(1–2), 41–47.
- Zhu, S., Li, Z., & Zhang, C. (2012). Exponential stability analysis for positive systems with delays. *IET Control Theory & Applications*, 6(6), 761–767.

5