

Dataset	Objects	Features	Clusters	0% CS					KMEANS	GT
				PCCC-N2-S	COPKM	LCC	CSC	DILS		
baa	5,300	2	2	—	—	—	—	—	—	—
letter	20,000	16	26	—	—	—	—	—	—	—
shuttle	57,999	9	7	—	—	—	—	—	—	—
cifar100	100,000	3,072	10	—	—	—	—	—	—	—
cifar100	100,000	3,072	100	—	—	—	—	—	—	—
mnist	70,000	784	10	—	—	—	—	—	—	—
Mean				-1.000*	-1.000*	-1.000*	-1.000*	-1.000*	-1.000	-1.000

*Nan values (—) are replaced with -1 before computing the mean.

Table W104: Average Silhouette coefficients of the PCCC and the PCCC-R algorithms and the four state-of-the-art algorithms (COPKM, CSC, DILS, LCC) obtained with constraint sets of size 0% CS. Higher values indicate better separated clusters. The highest values are stated in bold. The column KMEANS reports the average Silhouette coefficients that were obtained with the unconstrained k-means algorithm. The column GT reports the Silhouette coefficients of the ground truth assignment. The hyphen indicates that the respective algorithm returned no solution within the time limit of 1,800 seconds.