

1. Introduction to the judge environment

2. Prefix sum/precomputation trick

Sample Problem: Even Pairs

Input:

- ▶ first line: a positive integer n
- ▶ second line: a sequence $x_0, \dots, x_{n-1} \in \{0, 1\}$

Sample Problem: Even Pairs

Input:

- ▶ first line: a positive integer n
- ▶ second line: a sequence $x_0, \dots, x_{n-1} \in \{0, 1\}$

Output: a single line containing the number of pairs $0 \leq i \leq j < n$ such that

$$x_i + \dots + x_j$$

is even.

First approach

- (1) for all pairs $i \leq j$, compute the sum $x_i + \cdots + x_j$
- (2) if it is even, increment a counting variable

First approach

- (1) for all pairs $i \leq j$, compute the sum $x_i + \dots + x_j$
- (2) if it is even, increment a counting variable

A few points, but also a **timelimit** error on harder test cases!

First approach

- (1) for all pairs $i \leq j$, compute the sum $x_i + \dots + x_j$
- (2) if it is even, increment a counting variable

A few points, but also a **timelimit** error on harder test cases!

- ▶ this means that our algorithm is too slow

First approach

- (1) for all pairs $i \leq j$, compute the sum $x_i + \dots + x_j$
- (2) if it is even, increment a counting variable

A few points, but also a **timelimit** error on harder test cases!

- ▶ this means that our algorithm is too slow
- ▶ we have **three** nested loops: two for going over all pairs $i \leq j$, and one for summing up the $x_i + \dots + x_j$

First approach

- (1) for all pairs $i \leq j$, compute the sum $x_i + \dots + x_j$
- (2) if it is even, increment a counting variable

A few points, but also a **timelimit** error on harder test cases!

- ▶ this means that our algorithm is too slow
- ▶ we have **three** nested loops: two for going over all pairs $i \leq j$, and one for summing up the $x_i + \dots + x_j$
- ▶ running time is $\Theta(n^3)$

First approach

- (1) for all pairs $i \leq j$, compute the sum $x_i + \dots + x_j$
- (2) if it is even, increment a counting variable

A few points, but also a **timelimit** error on harder test cases!

- ▶ this means that our algorithm is too slow
- ▶ we have **three** nested loops: two for going over all pairs $i \leq j$, and one for summing up the $x_i + \dots + x_j$
- ▶ running time is $\Theta(n^3)$
- ▶ this type of analysis is very important in this course.

Second approach

Observation: if we know the parity of the sum

$$x_i + \cdots + x_j$$

then based on the parity of x_{j+1} we also know the parity of

$$x_i + \cdots + x_j + x_{j+1}$$

Second approach

Observation: if we know the parity of the sum

$$x_i + \cdots + x_j$$

then based on the parity of x_{j+1} we also know the parity of

$$x_i + \cdots + x_j + x_{j+1}$$

Running time: $\Theta(n^2)$

Third approach

Observation:

$$\begin{aligned}x_i + \cdots + x_j &= \sum_{a=0}^j x_a - \sum_{b=0}^{i-1} x_b \\&= S_j - S_{i-1}\end{aligned}$$

Third approach

Observation:

$$\begin{aligned}x_i + \cdots + x_j &= \sum_{a=0}^j x_a - \sum_{b=0}^{i-1} x_b \\ &= S_j - S_{i-1}\end{aligned}$$

- (1) calculate **partial sums** $S_i = \sum_{a=0}^i x_a$ in one iteration
- (2) for every $i \leq j$ check the parity of $S_j - S_{i-1}$

Third approach

Observation:

$$\begin{aligned}x_i + \cdots + x_j &= \sum_{a=0}^j x_a - \sum_{b=0}^{i-1} x_b \\ &= S_j - S_{i-1}\end{aligned}$$

- (1) calculate **partial sums** $S_i = \sum_{a=0}^i x_a$ in one iteration
- (2) for every $i \leq j$ check the parity of $S_j - S_{i-1}$

Running time: $\Theta(n^2)$

Fourth approach

Observation:

$$\begin{aligned}x_i + \cdots + x_j &= \sum_{a=0}^j x_a - \sum_{b=0}^{i-1} x_b \\ &= S_j - S_{i-1}\end{aligned}$$

(1) calculate **partial sums** $S_i = \sum_{a=0}^i x_a$ in one iteration

Fourth approach

Observation:

$$\begin{aligned}x_i + \cdots + x_j &= \sum_{a=0}^j x_a - \sum_{b=0}^{i-1} x_b \\ &= S_j - S_{i-1}\end{aligned}$$

- (1) calculate **partial sums** $S_i = \sum_{a=0}^i x_a$ in one iteration
- (2) $E = \#$ of S_i that are even
- (3) $O = \#$ of S_i that are odd

Fourth approach

Observation:

$$\begin{aligned}x_i + \cdots + x_j &= \sum_{a=0}^j x_a - \sum_{b=0}^{i-1} x_b \\ &= S_j - S_{i-1}\end{aligned}$$

- (1) calculate **partial sums** $S_i = \sum_{a=0}^i x_a$ in one iteration
- (2) $E = \#$ of S_i that are even
- (3) $O = \#$ of S_i that are odd
- (4) result is $\binom{E}{2} + \binom{O}{2} + E$

Fourth approach

Observation:

$$\begin{aligned}x_i + \cdots + x_j &= \sum_{a=0}^j x_a - \sum_{b=0}^{i-1} x_b \\ &= S_j - S_{i-1}\end{aligned}$$

- (1) calculate **partial sums** $S_i = \sum_{a=0}^i x_a$ in one iteration
- (2) $E = \#$ of S_i that are even
- (3) $O = \#$ of S_i that are odd
- (4) result is $\binom{E}{2} + \binom{O}{2} + E$

Running time: $\Theta(n)$

Tricks/techniques: Partial sums/Precomputing

- ▶ Precomputing partial sums allows computing the sum of the elements in an interval in constant time.
- ▶ More generally, precomputing certain values can speed up the running time of an algorithm.

Judge Results

Besides **correct**, **timelimit**, and **wrong-answer**, the judge can give the following results.

- assertion-failure** SIGABRT: memory screwup or assertion failure
- segmentation-fault** SIGSEGV: memory screwup
- run-error** nonzero exit status
- forbidden** bad syscall or other safety

The forum is your main tool for discussing ideas and getting help. Use it.

Of course, you will only learn if you first try to solve the problems **on your own**.

Forum: How To Ask Questions

1. Apply spoiler warnings

Example

SPOILER<<<

Set this text to have a white foreground. It will then be invisible unless marked. The <<<...>>> exploit a bug in the email plugin to also remove the text in plain-text email.

>>>

Forum: How To Ask Questions

1. Apply spoiler warnings
2. Describe the problem, not your guesses or summaries

Example

Bad When I compile, it tells me it cannot find it.

Good When I run `g++ -o foo foo.cpp`, I get
`bash: $'g++\302\240-o': command not found`

Forum: How To Ask Questions

1. Apply spoiler warnings
2. Describe the problem, not your guesses or summaries
3. Code: describe what fails and what you expect instead

Example

Bad The code below doesn't work. Help?

Good I am trying to solve Problem 1. I tried strategy something. My code is below. For some reason, when running it on the provided testcase it emits **no solution** instead of **1**. What am I doing wrong?

Forum: How To Ask Questions

1. Apply spoiler warnings
2. Describe the problem, not your guesses or summaries
3. Code: describe what fails and what you expect instead
4. Code: post minimal examples

Example

Bad When I call `.foo()` on a **vector**, it segfaults. Bug!

Good I am trying to something. The code is below. I get a segfault in the line that calls `.foo()`, but if I remove that line the program continues. What am I doing wrong?

Forum: How To Ask Questions

1. Apply spoiler warnings
2. Describe the problem, not your guesses or summaries
3. Code: describe what fails and what you expect instead
4. Code: post minimal examples
5. Don't rush to claim that you have found a bug

Further reading: [How To Ask Questions The Smart Way](#)

Learning C++ is beyond the scope of this course.

- ▶ True beginners should probably read a book
 - ▶ Andrew Koenig and Barbara E. Moo: Accelerated C++, Addison-Wesley, 2000
 - ▶ Stanley B. Lippman: C++ Primer, 3rd ed., Addison-Wesley, 1998

Learning C++ is beyond the scope of this course.

- ▶ True beginners should probably read a book
 - ▶ Andrew Koenig and Barbara E. Moo: Accelerated C++, Addison-Wesley, 2000
 - ▶ Stanley B. Lippman: C++ Primer, 3rd ed., Addison-Wesley, 1998
- ▶ People familiar with the syntactic family (e.g. C, Java, C#) may get away with a tutorial

Learning C++ is beyond the scope of this course.

- ▶ True beginners should probably read a book
 - ▶ Andrew Koenig and Barbara E. Moo: Accelerated C++, Addison-Wesley, 2000
 - ▶ Stanley B. Lippman: C++ Primer, 3rd ed., Addison-Wesley, 1998
- ▶ People familiar with the syntactic family (e.g. C, Java, C#) may get away with a tutorial
- ▶ Useful in any case: [C++ FAQ Lite](#)

STL is part of the C++ standard library. It is important that you know

- ▶ how and when to use the classes `std::vector`, `std::priority_queue`, `std::set` and `std::map`,
- ▶ how to do I/O using `<iostream>`, and
- ▶ how to use the `sort` function from the `<algorithm>` header file.

That's it.

The most important things to remember:

- ▶ You can find all that you need at our website:
<http://www.cadmo.ethz.ch/education/lectures/HS17/algolab/index.html>

That's it.

The most important things to remember:

- ▶ You can find all that you need at our website:
<http://www.cadmo.ethz.ch/education/lectures/HS17/algolab/index.html>
- ▶ For questions, you should use the forum.

That's it.

The most important things to remember:

- ▶ You can find all that you need at our website:
<http://www.cadmo.ethz.ch/education/lectures/HS17/algolab/index.html>
- ▶ For questions, you should use the forum.
- ▶ Today, we will publish the first week's exercises on the webpage.

That's it.

The most important things to remember:

- ▶ You can find all that you need at our website:
<http://www.cadmo.ethz.ch/education/lectures/HS17/algolab/index.html>
- ▶ For questions, you should use the forum.
- ▶ Today, we will publish the first week's exercises on the webpage.
- ▶ The public input/output files are available in the zip file Week 1 zipfile on Moodle.

That's it.

The most important things to remember:

- ▶ You can find all that you need at our website:
<http://www.cadmo.ethz.ch/education/lectures/HS17/algolab/index.html>
- ▶ For questions, you should use the forum.
- ▶ Today, we will publish the first week's exercises on the webpage.
- ▶ The public input/output files are available in the zip file Week 1 zipfile on Moodle.
- ▶ Next Monday at 17:00, we have the first problem of the week.