

# Algolab 2018

## Winter Games

Michael Hoffmann, Manuel Wettstein

Slides: Sebastian Stich

November 28, 2018

# Objective

**Learn how to solve a problem given by a textual description.**

This includes:

- appropriate problem modeling
- choice of suitable (combinatorial) algorithms, and
- implementation.

## Your Task:

- read the 3 problem descriptions
- sketch your approach (modeling, algorithms)

# Use them all!

## Observations

- $2 \leq n \leq 90'000$
- no overlap
- maximize radius

probably not looking for  $O(n^2)$   
only “close neighbors” matter  
optimization problem?

# Use them all!

## Observations

- $2 \leq n \leq 90'000$
- no overlap
- maximize radius

probably not looking for  $O(n^2)$   
only “close neighbors” matter  
optimization problem?

## Key ideas

- for a fixed cannon, the nearest neighbor determines an upper bound on the operation range

# Use them all!

## Observations

- $2 \leq n \leq 90'000$
- no overlap
- maximize radius

probably not looking for  $O(n^2)$   
only “close neighbors” matter  
optimization problem?

## Key ideas

- for a fixed cannon, the nearest neighbor determines an upper bound on the operation range
- only the closest cannon pair matters

# Use them all! – Solution

Try them all!

- Compute  $\binom{n}{2}$  pairwise distances

$$\rightarrow \Theta(n^2)$$

# Use them all! – Solution

Try them all!

- Compute  $\binom{n}{2}$  pairwise distances  $\rightarrow \Theta(n^2)$

Check only the distance to the nearest neighbor for each cannon

- Compute the Delaunay triangulation  $\rightarrow \Theta(n \log n)$
- Iterate over the edges of the triangulation  $\rightarrow \Theta(n)$

# Use them all! – Solution

Try them all!

- Compute  $\binom{n}{2}$  pairwise distances  $\rightarrow \Theta(n^2)$

Check only the distance to the nearest neighbor for each cannon

- Compute the Delaunay triangulation  $\rightarrow \Theta(n \log n)$
- Iterate over the edges of the triangulation  $\rightarrow \Theta(n)$

## Implementation detail

- Squared distances fit into double:

$$d^2 = d_x^2 + d_y^2 \leq (2^{25})^2 + (2^{25})^2 = 2^{51}$$



# Downhill course

## Observations

- $1 \leq n \leq 5'000$  probably  $O(n^2)$  is fine
- no overlap 2 options for every cannon (on/off)
- each cannon has at most 2 neighbors graph problem?

# Downhill course

## Observations

- $1 \leq n \leq 5'000$  probably  $O(n^2)$  is fine
- no overlap 2 options for every cannon (on/off)
- each cannon has at most 2 neighbors graph problem?

## Key ideas

- graph problem: cannons are vertices, put an edge whenever two ranges overlap

# Downhill course

## Observations

- $1 \leq n \leq 5'000$  probably  $O(n^2)$  is fine
- no overlap 2 options for every cannon (on/off)
- each cannon has at most 2 neighbors graph problem?

## Key ideas

- graph problem: cannons are vertices, put an edge whenever two ranges overlap
- find maximum independent set

# Downhill course

## Observations

- $1 \leq n \leq 5'000$  probably  $O(n^2)$  is fine
- no overlap 2 options for every cannon (on/off)
- each cannon has at most 2 neighbors graph problem?

## Key ideas

- graph problem: cannons are vertices, put an edge whenever two ranges overlap
- find maximum independent set
  - ▶ in general NP-complete
  - ▶ bipartite graphs König's Theorem, Matching
  - ▶ special cases trivial

## Downhill course – Solution

Construct a graph  $G$  to model the dependencies: vertices are cannons and there is an edge between two vertices if the respective operation ranges overlap

- Compute  $\binom{n}{2}$  pairwise distances  $\rightarrow \Theta(n^2)$

## Downhill course – Solution

Construct a graph  $G$  to model the dependencies: vertices are cannons and there is an edge between two vertices if the respective operation ranges overlap

- Compute  $\binom{n}{2}$  pairwise distances  $\rightarrow \Theta(n^2)$

- It suffices to consider for every vertex  $v$   
the nearest neighbor  $v_1 \rightarrow \Theta(n \log n)$   
the second nearest neighbor  $v_2 \rightarrow \Theta(n \log n)$


## Downhill course – Solution

Construct a graph  $G$  to model the dependencies: vertices are cannons and there is an edge between two vertices if the respective operation ranges overlap

- Compute  $\binom{n}{2}$  pairwise distances

$$\rightarrow \Theta(n^2)$$

- It suffices to consider for every vertex  $v$   
the nearest neighbor  $v_1 \rightarrow \Theta(n \log n)$   
the second nearest neighbor  $v_2 \rightarrow \Theta(n \log n)$




## Downhill course – Solution

Construct a graph  $G$  to model the dependencies: vertices are cannons and there is an edge between two vertices if the respective operation ranges overlap

- Compute  $\binom{n}{2}$  pairwise distances

$\rightarrow \Theta(n^2)$

- It suffices to consider for every vertex  $v$   
the nearest neighbor  $v_1 \rightarrow \Theta(n \log n)$   
the second nearest neighbor  $v_2 \rightarrow \Theta(n \log n)$



### Lemma

Let  $v_1$  be a nearest neighbor and  $v_2$  be a second nearest neighbor of  $v$ . Then at least one of  $vv_2$  or  $v_1v_2$  is an edge of the Delaunay triangulation.




## Downhill course – Solution

Construct a graph  $G$  to model the dependencies: vertices are cannons and there is an edge between two vertices if the respective operation ranges overlap

- Compute  $\binom{n}{2}$  pairwise distances  $\rightarrow \Theta(n^2)$

- It suffices to consider for every vertex  $v$   
the nearest neighbor  $v_1 \rightarrow \Theta(n \log n)$   
the second nearest neighbor  $v_2 \rightarrow \Theta(n \log n)$



- maximal degree 2  
 $\Rightarrow$  the graph  $G$  must be a disjoint union of paths and cycles  
 $\Rightarrow$  greedy/ad-hoc solution for every component  $\rightarrow \Theta(n)$

# Software update

## Observations

- $2 \leq n \leq 50$  tiny...
- minimal radius need solution of Exercise 2
- no overlap radii are bounded from above
- maximize sum of the radii optimization problem?

# Software update

## Observations

- $2 \leq n \leq 50$  tiny...
- minimal radius need solution of Exercise 2
- no overlap radii are bounded from above
- maximize sum of the radii optimization problem?

## Key ideas

- optimization problem find a larger radius for each cannon

# Software update

## Observations

- $2 \leq n \leq 50$  tiny...
- minimal radius need solution of Exercise 2
- no overlap radii are bounded from above
- maximize sum of the radii optimization problem?

## Key ideas

- optimization problem find a larger radius for each cannon
  - ▶ the improvement is linear in the radius
  - ▶ lower bounds for the radii
  - ▶ implicit upper bounds: no overlap

## Software update – Solution

Linear program with  $n$  variables and  $n + \binom{n}{2}$  constraints:

- *Variables*: Operation range (radius) of every snow cannon

$$r_i \geq \left\lfloor \frac{\text{closest\_pair\_dist}}{2} \right\rfloor, \quad i = 1, \dots, n$$

## Software update – Solution

Linear program with  $n$  variables and  $n + \binom{n}{2}$  constraints:

- *Variables*: Operation range (radius) of every snow cannon

$$r_i \geq \left\lfloor \frac{\text{closest\_pair\_dist}}{2} \right\rfloor, \quad i = 1, \dots, n$$

- *Constraints*: Operation ranges are not overlapping

$$r_i + r_j \leq \text{dist}(i, j), \quad 1 \leq i, j \leq n$$

## Software update – Solution

Linear program with  $n$  variables and  $n + \binom{n}{2}$  constraints:

- *Variables*: Operation range (radius) of every snow cannon

$$r_i \geq \left\lfloor \frac{\text{closest\_pair\_dist}}{2} \right\rfloor, \quad i = 1, \dots, n$$

- *Constraints*: Operation ranges are not overlapping

$$r_i + r_j \leq \text{dist}(i, j), \quad 1 \leq i, j \leq n$$

- *Objective*: Maximize the sum of the radii

$$\max \sum_i r_i$$

## Software update – Solution

Linear program with  $n$  variables and  $n + \binom{n}{2}$  constraints:

- *Variables*: Operation range (radius) of every snow cannon

$$r_i \geq \left\lfloor \frac{\text{closest\_pair\_dist}}{2} \right\rfloor, \quad i = 1, \dots, n$$

- *Constraints*: Operation ranges are not overlapping

$$r_i + r_j \leq \text{dist}(i, j), \quad 1 \leq i, j \leq n$$

- *Objective*: Maximize the sum of the radii

$$\max \sum_i r_i$$

### Implementation details

- **Input type**: Exact type with sqrt