
Data Structures and Algorithms in Java™

Sixth Edition

Michael T. Goodrich

Department of Computer Science
University of California, Irvine

Roberto Tamassia

Department of Computer Science
Brown University

Michael H. Goldwasser

Department of Mathematics and Computer Science
Saint Louis University

Instructor's Solutions Manual

WILEY

Chapter

5

Recursion

Hints and Solutions

Reinforcement

R-5.1) Hint Don't forget about the space used by the method stack.

R-5.1) Solution If the array has 1 element, that is the maximum. Otherwise, consider the bigger of the first element or the maximum of the other $n - 1$ elements. The running time and space usages is $O(n)$.


R-5.2) Hint When the algorithm finds a match, does it know where?

R-5.2) Solution

```
public static int binarySearch(int[] data, int target, int low, int high) {
    if (low > high)
        return -1; // failed search
    else {
        int mid = (low + high) / 2;
        if (target == data[mid])
            return mid; // index of found match
        else if (target < data[mid])
            return binarySearch(data, target, low, mid - 1);
        else
            return binarySearch(data, target, mid + 1, high);
    }
}
```


R-5.3) Hint This is probably the first power algorithm you were taught.

R-5.3) Solution



R-5.4) Hint Be sure to get the integer division right.

R-5.4) Solution



R-5.5) Hint You can model your figure after Figure 5.11.

R-5.5) Solution

0	1	2	3	4
4	3	6	2	5
5	3	6	2	4
5	2	6	3	4

R-5.6) Hint You should draw small boxes or use a big paper, as there are a lot of recursive calls.

R-5.7) Hint Start with the last term.

R-5.7) Solution The general case is $H_n = H_{n-1} + \frac{1}{n}$.

R-5.8) Hint Process the string from right to left.

R-5.8) Solution Use a single-digit as the base case. For a multiple-digit string, let $s' = sd$ for digit d . We have that $value(s') = d + 10 * value(s)$.

R-5.9) Hint You can rely on bitwise operations to interpret n in binary.

R-5.9) Solution

```
public static double power(double x, int n) {
    int k = 0;
    while ((1 << k) <= n)
        k++;

    double answer = 1;
    for (int j=k-1; j >= 0; j--) {
        answer *= answer;
        if (((1 << j) & n) > 0)
            answer *= x;
    }
    return answer;
}
```

R-5.10) Hint You can use two recursive methods that look like Binary-Sum.

Creativity

C-5.11) Hint The integer part of the base-two logarithm of n is the number of times you can divide by two before you get a number less than 2.

C-5.12) Hint Consider reducing the task of telling if the elements of an array are unique to the problem of determining if the last $n - 1$ elements are all unique and different than the first element.

C-5.13) Hint You need subtraction to count down from m or n and addition to do the arithmetic needed to get the right answer.

C-5.13) Solution The recursive algorithm, *product*(n, m), for computing product using only addition and subtraction, is as follows: If $m = 1$ return n . Otherwise, return n plus the result of a recursive call to the method *product* with parameters n and $m - 1$.

C-5.14) Hint Define a recurrence equation.

C-5.14) Solution let $R(c)$ denote the number of dashes drawn by *drawInterval*(c). We prove by induction that $R(c) = 2^{c+1} - c - 2$. As a base case, we note that *drawInterval*(0) does not produce any output, and that $R(0) =$

$2^{0+1} - 0 - 2 = 0$. For $c > 0$, we note that `drawInterval(c)` invokes two recursive calls of `drawInterval($c - 1$)`, and a call to `drawLine` that produces c dashes. Therefore, $R(c) = c + 2R(c - 1)$, and by the inductive hypothesis, $R(c) = c + 2(2^{(c-1)+1} - (c - 1) - 2) = c + 2(2^c - c - 1) = c + 2^{c+1} - 2c - 2 = 2^{c+1} - c - 2$.

C-5.15) Hint Start by removing the first element x and computing all the subsets that don't contain x .

C-5.16) Hint Consider first the subproblem of moving all but the n^{th} disk from peg a to another peg using the third as “temporary storage.”

C-5.17) Hint Output to `System.out` one character at a time.

C-5.17) Solution

```
void printReverse(String s, int n) {
    if (n >= 0) {
        System.out.print(s.charAt(n))
        printReverse(s, n-1);
    }
}

void printReverse(String s) {
    printReverse(s, s.length() - 1);
}
```

C-5.18) Hint Check the equality of the first and last characters and recur (but be careful to return the correct value for both odd- and even-length strings).

C-5.19) Hint Write your recursive method to first count vowels and consonants.

C-5.20) Hint Consider whether the last element is odd or even and then put it at the appropriate location based on this and recur.

C-5.20) Solution

```

void organize(int[ ] data, int low, int high) {
    if (low < high) {
        if (data[high] & 1 == 0) {           // even
            int temp = data[high];
            data[high] = data[low];
            data[low] = temp;
            organize(data, low+1, high);     // data[low] is known to be even
        } else {
            organize(data, low, high-1);     // data[high] is known to be odd
        }
    }
}

void organize(int[ ] data) {
    organize(data, 0, data.length - 1);
}

```

C-5.21) Hint Begin by comparing the first and last elements in a range of indices in A .

C-5.21) Solution This problem can effectively be solved using the same technique as Exercise C-5.20.

C-5.22) Hint The beginning and the end of a range of indices in A can be used as arguments to your recursive method.

C-5.22) Solution The solution makes use of the method $\text{FindPair}(A, i, j, k)$ below, which given the sorted subarray $A[i..j]$ determines whether there is any pair of elements that sums to k . First it tests whether $A[i] + A[j] < k$. Because A is sorted, for any $j' \leq j$, we have $A[i] + A[j'] < k$. Thus, there is no pair involving $A[i]$ that sums to k , and we can eliminate $A[i]$ and recursively check the remaining subarray $A[i+1..j]$. Similarly, if $A[i] + A[j] > k$, we can eliminate $A[j]$ and recursively check the subarray $A[i..j-1]$. Otherwise, $A[i] + A[j] = k$ and we return true. If no such pair is ever found, eventually all but one element is eliminated ($i = j$), and we return false.

Algorithm $\text{FindPair}(A, i, j, k)$:

Input: An integer subarray $A[i..j]$ and integer k

Output: Returns true if there are two elements of $A[i..j]$ that sum to k

```

if  $i == j$  then
    return false
else
    if  $A[i] + A[j] < k$  then
        return  $\text{FindPair}(A, i+1, j, k)$ 

```

```

else
    if  $A[i] + A[j] > k$  then
        return FindPair( $A, i, j - 1, k$ )
    else
        return true

```

C-5.23) Hint Check the last element and then recur on the rest of A .

C-5.24) Hint Look for a geometric series.

C-5.24) Solution The running time is $O(n)$, as it is $O(n + n/2 + n/4 + n/8 + \dots)$.

C-5.25) Hint Recur on the first $n - 1$ positions.

C-5.25) Solution Let us define a method `reverse(L, n)`, which reverses the first $n \leq L.size()$ nodes in L , and returns a pointer *end* to the node just after the n th node in L (*end* = **null** if $n = L.size()$). If $L.size() \leq 1$, we are done, so let us assume L has at least 2 nodes. If $n = 1$, then we return `L.first().next()`. Otherwise, we recursively call `reverse($L, n - 1$)`, and let *end* denote the returned pointer to the n th node in L . We then set *ret* to `end.next()` if $n < L.size()$, and to **null** otherwise. We then insert the node pointed to by *end* at the front of L and we return *ret*. The total running time is $O(n)$.

C-5.26) Hint View the chain of nodes following the head node as forming themselves another list.

Projects

P-5.27) Hint Review use of the `java.io.File` class.

P-5.28) Hint Use recursion in your main solution engine.

P-5.29) Hint Consider a small example to see why the binary representation of the counter is relevant.

P-5.30) Hint Note the recursive nature of the problem.