

# Scan Report

April 25, 2023

## Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “Ubuntu full scan”. The scan started at Tue Apr 25 14:02:22 2023 UTC and ended at Tue Apr 25 14:40:20 2023 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

## Contents

<b>1</b>	<b>Result Overview</b>	<b>2</b>
1.1	Host Authentications . . . . .	2
<b>2</b>	<b>Results per Host</b>	<b>2</b>
2.1	192.168.56.103 . . . . .	2
2.1.1	High 80/tcp . . . . .	3
2.1.2	High 22/tcp . . . . .	5
2.1.3	High 631/tcp . . . . .	6
2.1.4	High 21/tcp . . . . .	9
2.1.5	Medium 80/tcp . . . . .	11
2.1.6	Medium 22/tcp . . . . .	18
2.1.7	Medium 631/tcp . . . . .	21
2.1.8	Medium 21/tcp . . . . .	25
2.1.9	Low 22/tcp . . . . .	25
2.1.10	Low general/icmp . . . . .	26
2.1.11	Low general/tcp . . . . .	27

## 1 Result Overview

Host	High	Medium	Low	Log	False Positive
<a href="#">192.168.56.103</a>	7	13	3	0	0
Total: 1	7	13	3	0	0

Vendor security updates are not trusted.

Overrides are off. Even when a result has an override, this report uses the actual threat of the result.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 23 results selected by the filtering described above. Before filtering there were 398 results.

### 1.1 Host Authentications

Host	Protocol	Result	Port/User
192.168.56.103	SMB	Success	Protocol SMB, Port 445, User

## 2 Results per Host

### 2.1 192.168.56.103

Host scan start Tue Apr 25 14:03:07 2023 UTC

Host scan end Tue Apr 25 14:40:13 2023 UTC

Service (Port)	Threat Level
<a href="#">80/tcp</a>	High
<a href="#">22/tcp</a>	High
<a href="#">631/tcp</a>	High
<a href="#">21/tcp</a>	High
<a href="#">80/tcp</a>	Medium
<a href="#">22/tcp</a>	Medium
<a href="#">631/tcp</a>	Medium
<a href="#">21/tcp</a>	Medium
<a href="#">22/tcp</a>	Low

... (continues) ...

... (continued) ...

Service (Port)	Threat Level
<a href="#">general/icmp</a>	Low
<a href="#">general/tcp</a>	Low

### 2.1.1 High 80/tcp

High (CVSS: 10.0) NVT: Drupal Coder RCE Vulnerability (SA-CONTRIB-2016-039) - Active Check
<b>Summary</b> Drupal is prone to a remote code execution (RCE) vulnerability.
<b>Vulnerability Detection Result</b> Vulnerable URL: <a href="http://192.168.56.103/drupal/sites/all/modules/coder/coder_upgrade/scripts/coder_upgrade.run.php">http://192.168.56.103/drupal/sites/all/modules/coder/coder_upgrade/scripts/coder_upgrade.run.php</a>
<b>Solution:</b> <b>Solution type:</b> VendorFix Install the latest version.
<b>Vulnerability Insight</b> The Coder module checks your Drupal code against coding standards and other best practices. It can also fix coding standard violations and perform basic upgrades on modules. The module doesn't sufficiently validate user inputs in a script file that has the php extension. A malicious unauthenticated user can make requests directly to this file to execute arbitrary php code.
<b>Vulnerability Detection Method</b> Checks for known error message from affected modules. Details: Drupal Coder RCE Vulnerability (SA-CONTRIB-2016-039) - Active Check OID:1.3.6.1.4.1.25623.1.0.105818 Version used: 2021-12-01T11:10:56Z
<b>References</b> url: <a href="https://www.drupal.org/node/2765575">https://www.drupal.org/node/2765575</a>

High (CVSS: 7.5) NVT: Drupal Core SQLi Vulnerability (SA-CORE-2014-005) - Active Check
<b>Summary</b> Drupal is prone to an SQL injection (SQLi) vulnerability.
<b>Vulnerability Detection Result</b> Vulnerable URL: <a href="http://192.168.56.103/drupal/?q=node&amp;destination=node">http://192.168.56.103/drupal/?q=node&amp;destination=node</a>
... continues on next page ...

...continued from previous page ...
<b>Impact</b> Exploiting this issue could allow an attacker to execute arbitrary code, to gain elevated privileges and to compromise the application, access or modify data, or exploit latent vulnerabilities in the underlying database.
<b>Solution:</b> <b>Solution type:</b> VendorFix Updates are available. Please see the references for more information.
<b>Affected Software/OS</b> Drupal 7.x versions prior to 7.32 are vulnerable.
<b>Vulnerability Insight</b> Drupal fails to sufficiently sanitize user-supplied data before using it in an SQL query.
<b>Vulnerability Detection Method</b> Sends a special crafted HTTP POST request and checks the response. Details: Drupal Core SQLi Vulnerability (SA-CORE-2014-005) - Active Check OID:1.3.6.1.4.1.25623.1.0.105101 Version used: 2022-04-14T11:24:11Z
<b>References</b> cve: CVE-2014-3704 url: <a href="https://www.drupal.org/forum/newsletters/security-advisories-for-drupal-core/2014-10-15/sa-core-2014-005-drupal-core-sql">https://www.drupal.org/forum/newsletters/security-advisories-for-drupal-core/2014-10-15/sa-core-2014-005-drupal-core-sql</a> url: <a href="http://www.securityfocus.com/bid/70595">http://www.securityfocus.com/bid/70595</a> cert-bund: CB-K14/1301 cert-bund: CB-K14/0920 dfn-cert: DFN-CERT-2014-1369 dfn-cert: DFN-CERT-2014-0958

High (CVSS: 7.5)  
NVT: Test HTTP dangerous methods

**Summary**  
Misconfigured web servers allows remote clients to perform dangerous HTTP methods such as PUT and DELETE.

**Vulnerability Detection Result**  
We could upload the following files via the PUT method at this web server:  
<http://192.168.56.103/uploads/puttest1501510269.html>  
<http://192.168.56.103/uploads/BqEV3113.htm/puttest350432513.html>  
We could delete the following files via the DELETE method at this web server:  
<http://192.168.56.103/uploads/puttest1501510269.html>

... continues on next page ...

...continued from previous page ...
<a href="http://192.168.56.103/uploads/BqEV3113.htm/puttest350432513.html">http://192.168.56.103/uploads/BqEV3113.htm/puttest350432513.html</a>
<b>Impact</b> - Enabled PUT method: This might allow an attacker to upload and run arbitrary code on this web server. - Enabled DELETE method: This might allow an attacker to delete additional files on this web server.
<b>Solution:</b> <b>Solution type:</b> Mitigation Use access restrictions to these dangerous HTTP methods or disable them completely.
<b>Affected Software/OS</b> Web servers with enabled PUT and/or DELETE methods.
<b>Vulnerability Detection Method</b> Checks if dangerous HTTP methods such as PUT and DELETE are enabled and can be misused to upload or delete files. Details: Test HTTP dangerous methods OID:1.3.6.1.4.1.25623.1.0.10498 Version used: 2022-05-12T09:32:01Z
<b>References</b> url: <a href="http://www.securityfocus.com/bid/12141">http://www.securityfocus.com/bid/12141</a> owasp: OWASP-CM-001

[ [return to 192.168.56.103](#) ]

### 2.1.2 High 22/tcp

High (CVSS: 7.5) NVT: SSH Brute Force Logins With Default Credentials Reporting
<b>Summary</b> It was possible to login into the remote SSH server using default credentials.
<b>Vulnerability Detection Result</b> It was possible to login with the following credentials <User>:<Password> vagrant:vagrant
<b>Impact</b> This issue may be exploited by a remote attacker to e.g. gain access to sensitive information or modify system configuration.
... continues on next page ...

...continued from previous page ...
<b>Solution:</b> <b>Solution type:</b> Mitigation Change the password as soon as possible.
<b>Vulnerability Insight</b> As the VT 'SSH Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108013) might run into a timeout the actual reporting of this vulnerability takes place in this VT instead.
<b>Vulnerability Detection Method</b> Reports default credentials detected by the VT 'SSH Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108013). Details: SSH Brute Force Logins With Default Credentials Reporting OID:1.3.6.1.4.1.25623.1.0.103239 Version used: 2022-08-04T13:37:02Z
<b>References</b> cve: CVE-1999-0501 cve: CVE-1999-0502 cve: CVE-1999-0507 cve: CVE-1999-0508

[\[ return to 192.168.56.103 \]](#)

### 2.1.3 High 631/tcp

High (CVSS: 7.5) NVT: SSL/TLS: Report Vulnerable Cipher Suites for HTTPS
<b>Summary</b> This routine reports all SSL/TLS cipher suites accepted by a service where attack vectors exists only on HTTPS services.
<b>Vulnerability Detection Result</b> 'Vulnerable' cipher suites accepted by this service via the TLSv1.0 protocol: TLS_RSA_WITH_3DES_EDE_CBC_SHA (SWEET32) 'Vulnerable' cipher suites accepted by this service via the TLSv1.1 protocol: TLS_RSA_WITH_3DES_EDE_CBC_SHA (SWEET32) 'Vulnerable' cipher suites accepted by this service via the TLSv1.2 protocol: TLS_RSA_WITH_3DES_EDE_CBC_SHA (SWEET32)
<b>Solution:</b> <b>Solution type:</b> Mitigation The configuration of this services should be changed so that it does not accept the listed cipher suites anymore.
... continues on next page ...

...continued from previous page ...
Please see the references for more resources supporting you with this task.
<b>Affected Software/OS</b> Services accepting vulnerable SSL/TLS cipher suites via HTTPS.
<b>Vulnerability Insight</b> These rules are applied for the evaluation of the vulnerable cipher suites: - 64-bit block cipher 3DES vulnerable to the SWEET32 attack (CVE-2016-2183).
<b>Vulnerability Detection Method</b> Details: SSL/TLS: Report Vulnerable Cipher Suites for HTTPS OID:1.3.6.1.4.1.25623.1.0.108031 Version used: 2022-08-01T10:11:45Z
<b>References</b> cve: CVE-2016-2183 cve: CVE-2016-6329 cve: CVE-2020-12872 url: <a href="https://bettercrypto.org/">https://bettercrypto.org/</a> url: <a href="https://mozilla.github.io/server-side-tls/ssl-config-generator/">https://mozilla.github.io/server-side-tls/ssl-config-generator/</a> url: <a href="https://sweet32.info/">https://sweet32.info/</a> cert-bund: WID-SEC-2022-2226 cert-bund: WID-SEC-2022-1955 cert-bund: CB-K21/1094 cert-bund: CB-K20/1023 cert-bund: CB-K20/0321 cert-bund: CB-K20/0314 cert-bund: CB-K20/0157 cert-bund: CB-K19/0618 cert-bund: CB-K19/0615 cert-bund: CB-K18/0296 cert-bund: CB-K17/1980 cert-bund: CB-K17/1871 cert-bund: CB-K17/1803 cert-bund: CB-K17/1753 cert-bund: CB-K17/1750 cert-bund: CB-K17/1709 cert-bund: CB-K17/1558 cert-bund: CB-K17/1273 cert-bund: CB-K17/1202 cert-bund: CB-K17/1196 cert-bund: CB-K17/1055 cert-bund: CB-K17/1026 cert-bund: CB-K17/0939 cert-bund: CB-K17/0917 cert-bund: CB-K17/0915
... continues on next page ...

...continued from previous page ...

cert-bund: CB-K17/0877  
cert-bund: CB-K17/0796  
cert-bund: CB-K17/0724  
cert-bund: CB-K17/0661  
cert-bund: CB-K17/0657  
cert-bund: CB-K17/0582  
cert-bund: CB-K17/0581  
cert-bund: CB-K17/0506  
cert-bund: CB-K17/0504  
cert-bund: CB-K17/0467  
cert-bund: CB-K17/0345  
cert-bund: CB-K17/0098  
cert-bund: CB-K17/0089  
cert-bund: CB-K17/0086  
cert-bund: CB-K17/0082  
cert-bund: CB-K16/1837  
cert-bund: CB-K16/1830  
cert-bund: CB-K16/1635  
cert-bund: CB-K16/1630  
cert-bund: CB-K16/1624  
cert-bund: CB-K16/1622  
cert-bund: CB-K16/1500  
cert-bund: CB-K16/1465  
cert-bund: CB-K16/1307  
cert-bund: CB-K16/1296  
dfn-cert: DFN-CERT-2021-1618  
dfn-cert: DFN-CERT-2021-0775  
dfn-cert: DFN-CERT-2021-0770  
dfn-cert: DFN-CERT-2021-0274  
dfn-cert: DFN-CERT-2020-2141  
dfn-cert: DFN-CERT-2020-0368  
dfn-cert: DFN-CERT-2019-1455  
dfn-cert: DFN-CERT-2019-0068  
dfn-cert: DFN-CERT-2018-1296  
dfn-cert: DFN-CERT-2018-0323  
dfn-cert: DFN-CERT-2017-2070  
dfn-cert: DFN-CERT-2017-1954  
dfn-cert: DFN-CERT-2017-1885  
dfn-cert: DFN-CERT-2017-1831  
dfn-cert: DFN-CERT-2017-1821  
dfn-cert: DFN-CERT-2017-1785  
dfn-cert: DFN-CERT-2017-1626  
dfn-cert: DFN-CERT-2017-1326  
dfn-cert: DFN-CERT-2017-1239  
dfn-cert: DFN-CERT-2017-1238  
dfn-cert: DFN-CERT-2017-1090  
dfn-cert: DFN-CERT-2017-1060

...continues on next page ...



...continued from previous page ...

```

dfn-cert: DFN-CERT-2017-0968
dfn-cert: DFN-CERT-2017-0947
dfn-cert: DFN-CERT-2017-0946
dfn-cert: DFN-CERT-2017-0904
dfn-cert: DFN-CERT-2017-0816
dfn-cert: DFN-CERT-2017-0746
dfn-cert: DFN-CERT-2017-0677
dfn-cert: DFN-CERT-2017-0675
dfn-cert: DFN-CERT-2017-0611
dfn-cert: DFN-CERT-2017-0609
dfn-cert: DFN-CERT-2017-0522
dfn-cert: DFN-CERT-2017-0519
dfn-cert: DFN-CERT-2017-0482
dfn-cert: DFN-CERT-2017-0351
dfn-cert: DFN-CERT-2017-0090
dfn-cert: DFN-CERT-2017-0089
dfn-cert: DFN-CERT-2017-0088
dfn-cert: DFN-CERT-2017-0086
dfn-cert: DFN-CERT-2016-1943
dfn-cert: DFN-CERT-2016-1937
dfn-cert: DFN-CERT-2016-1732
dfn-cert: DFN-CERT-2016-1726
dfn-cert: DFN-CERT-2016-1715
dfn-cert: DFN-CERT-2016-1714
dfn-cert: DFN-CERT-2016-1588
dfn-cert: DFN-CERT-2016-1555
dfn-cert: DFN-CERT-2016-1391
dfn-cert: DFN-CERT-2016-1378

```

[ [return to 192.168.56.103](#) ]

#### 2.1.4 High 21/tcp

High (CVSS: 10.0) NVT: ProFTPD 'mod_copy' Unauthenticated Copying Of Files Via SITE CPFR/CPTO
<b>Product detection result</b> cpe:/a:proftpd:proftpd:1.3.5 Detected by ProFTPD Server Version Detection (Remote) (OID: 1.3.6.1.4.1.25623.1.↪0.900815)
<b>Summary</b> ProFTPD is prone to an unauthenticated copying of files vulnerability.
<b>Vulnerability Detection Result</b> ... continues on next page ...

...continued from previous page ...
The target was found to be vulnerable
<b>Impact</b> Under some circumstances this could result in remote code execution
<b>Solution:</b> <b>Solution type:</b> VendorFix Ask the vendor for an update
<b>Vulnerability Detection Method</b> Try to copy /etc/passwd to /tmp/passwd.copy with SITE CPFR/CPTO Details: ProFTPD 'mod_copy' Unauthenticated Copying Of Files Via SITE CPFR/CPTO OID:1.3.6.1.4.1.25623.1.0.105254 Version used: 2022-12-02T10:11:16Z
<b>Product Detection Result</b> Product: cpe:/a:proftpd:proftpd:1.3.5 Method: ProFTPD Server Version Detection (Remote) OID: 1.3.6.1.4.1.25623.1.0.900815)
<b>References</b> cve: CVE-2015-3306 url: <a href="http://bugs.proftpd.org/show_bug.cgi?id=4169">http://bugs.proftpd.org/show_bug.cgi?id=4169</a> cert-bund: CB-K15/0791 cert-bund: CB-K15/0553 dfn-cert: DFN-CERT-2015-0839 dfn-cert: DFN-CERT-2015-0576

High (CVSS: 7.5)

NVT: FTP Brute Force Logins Reporting

**Summary**

It was possible to login into the remote FTP server using weak/known credentials.

**Vulnerability Detection Result**

It was possible to login with the following credentials <User>:<Password>  
vagrant:vagrant

**Impact**

This issue may be exploited by a remote attacker to e.g. gain access to sensitive information or modify system configuration.

**Solution:****Solution type:** Mitigation

... continues on next page ...

...continued from previous page ...
Change the password as soon as possible.
<b>Vulnerability Insight</b> As the VT 'FTP Brute Force Logins' (OID: 1.3.6.1.4.1.25623.1.0.108717) might run into a timeout the actual reporting of this vulnerability takes place in this VT instead.
<b>Vulnerability Detection Method</b> Reports weak/known credentials detected by the VT 'FTP Brute Force Logins' (OID: 1.3.6.1.4.1.25623.1.0.108717). Details: FTP Brute Force Logins Reporting OID:1.3.6.1.4.1.25623.1.0.108718 Version used: 2022-08-04T13:37:02Z
<b>References</b> cve: CVE-1999-0501 cve: CVE-1999-0502 cve: CVE-1999-0507 cve: CVE-1999-0508

[\[ return to 192.168.56.103 \]](#)

### 2.1.5 Medium 80/tcp

Medium (CVSS: 6.1) NVT: jQuery < 1.9.0 XSS Vulnerability
<b>Summary</b> jQuery is vulnerable to Cross-site Scripting (XSS) attacks.
<b>Vulnerability Detection Result</b> Installed version: 1.6.2 Fixed version: 1.9.0 Installation path / port: /phpmyadmin/js/jquery
<b>Solution:</b> <b>Solution type:</b> VendorFix Update to version 1.9.0 or later.
<b>Affected Software/OS</b> jQuery prior to version 1.9.0.
<b>Vulnerability Insight</b> ... continues on next page ...

...continued from previous page ...
<p>The jQuery(strInput) function does not differentiate selectors from HTML in a reliable fashion. In vulnerable versions, jQuery determined whether the input was HTML by looking for the '&lt;' character anywhere in the string, giving attackers more flexibility when attempting to construct a malicious payload. In fixed versions, jQuery only deems the input to be HTML if it explicitly starts with the '&lt;' character, limiting exploitability only to attackers who can control the beginning of a string, which is far less common.</p>
<p><b>Vulnerability Detection Method</b>  Checks if a vulnerable version is present on the target host.  Details: jQuery &lt; 1.9.0 XSS Vulnerability  OID:1.3.6.1.4.1.25623.1.0.141636  Version used: 2021-06-11T08:43:18Z</p>
<p><b>References</b>  cve: CVE-2012-6708  url: <a href="https://bugs.jquery.com/ticket/11290">https://bugs.jquery.com/ticket/11290</a>  cert-bund: WID-SEC-2022-0673  cert-bund: CB-K22/0045  cert-bund: CB-K18/1131  dfn-cert: DFN-CERT-2020-0590</p>
<p>Medium (CVSS: 6.1)  NVT: jQuery &lt; 1.9.0 XSS Vulnerability</p>
<p><b>Summary</b>  jQuery is vulnerable to Cross-site Scripting (XSS) attacks.</p>
<p><b>Vulnerability Detection Result</b>  Installed version: 1.6.2  Fixed version: 1.9.0  Installation  path / port: /phpmyadmin/setup/./js/jquery</p>
<p><b>Solution:</b>  <b>Solution type:</b> VendorFix  Update to version 1.9.0 or later.</p>
<p><b>Affected Software/OS</b>  jQuery prior to version 1.9.0.</p>
<p><b>Vulnerability Insight</b>  ... continues on next page ...</p>

...continued from previous page ...
<p>The jQuery(strInput) function does not differentiate selectors from HTML in a reliable fashion. In vulnerable versions, jQuery determined whether the input was HTML by looking for the '&lt;' character anywhere in the string, giving attackers more flexibility when attempting to construct a malicious payload. In fixed versions, jQuery only deems the input to be HTML if it explicitly starts with the '&lt;' character, limiting exploitability only to attackers who can control the beginning of a string, which is far less common.</p>
<p><b>Vulnerability Detection Method</b>  Checks if a vulnerable version is present on the target host.  Details: jQuery &lt; 1.9.0 XSS Vulnerability  OID:1.3.6.1.4.1.25623.1.0.141636  Version used: 2021-06-11T08:43:18Z</p>
<p><b>References</b>  cve: CVE-2012-6708  url: <a href="https://bugs.jquery.com/ticket/11290">https://bugs.jquery.com/ticket/11290</a>  cert-bund: WID-SEC-2022-0673  cert-bund: CB-K22/0045  cert-bund: CB-K18/1131  dfn-cert: DFN-CERT-2020-0590</p>

<p>Medium (CVSS: 5.0)  NVT: Sensitive File Disclosure (HTTP)</p>
<p><b>Summary</b>  The script attempts to identify files containing sensitive data at the remote web server like e.g.:  - software (Blog, CMS) configuration or log files  - web / application server configuration / password files (.htaccess, .htpasswd, web.config, web.xml, ...)  - database backup files  - SSH or SSL/TLS Private-Keys</p>
<p><b>Vulnerability Detection Result</b>  The following files containing sensitive information were identified:  Description: Microsoft IIS / ASP.NET Core Module web.config file accessible. This could contain sensitive information about the structure of the application / web server and shouldn't be accessible.  Match: &lt;configuration&gt;  &lt;system.webServer&gt;  Used regex: ^\s*&lt;(configuration system\.web(Server)?&gt;  Extra match: &lt;/system.webServer&gt;  &lt;/configuration&gt;  Used regex: ^\s*&lt;/(configuration system\.web(Server)?&gt;  URL: http://192.168.56.103/drupal/web.config</p>
<p><b>Impact</b></p>
<p>... continues on next page ...</p>

...continued from previous page ...
Based on the information provided in these files an attacker might be able to gather additional info and/or sensitive data like usernames and passwords.
<b>Solution:</b> <b>Solution type:</b> Mitigation The sensitive files shouldn't be accessible via a web server. Restrict access to it or remove it completely.
<b>Vulnerability Detection Method</b> Enumerate the remote web server and check if sensitive files are accessible. Details: Sensitive File Disclosure (HTTP) OID:1.3.6.1.4.1.25623.1.0.107305 Version used: 2023-03-06T10:10:02Z

Medium (CVSS: 5.0) NVT: Unprotected Web App / Device Installers (HTTP)
<b>Summary</b> The script attempts to identify installation/setup pages of various web apps/devices that are publicly accessible and not protected by e.g. account restrictions or having their setup finished.
<b>Vulnerability Detection Result</b> The following web app/device installers are unprotected/have not finished their ↪setup and are publicly accessible (URL:Description): http://192.168.56.103/phpmyadmin/setup/index.php - CubeCart / phpMyAdmin install ↪er
<b>Impact</b> It is possible to install or reconfigure the software. In doing so, the attacker could overwrite existing configurations. It could be possible for the attacker to gain access to the base system
<b>Solution:</b> <b>Solution type:</b> Mitigation Setup and/or installation pages for Web Apps should not be publicly accessible via a web server. Restrict access to it, remove it completely or finish the setup of the application / device.
<b>Vulnerability Detection Method</b> Enumerate the remote web server and check if unprotected web apps/devices are accessible for installation. Details: Unprotected Web App / Device Installers (HTTP) OID:1.3.6.1.4.1.25623.1.0.107307 Version used: 2023-03-01T10:09:26Z

Medium (CVSS: 5.0) NVT: Drupal 7.0 Information Disclosure Vulnerability - Active Check
<b>Summary</b> Drupal is prone to an information disclosure vulnerability.
<b>Vulnerability Detection Result</b> Vulnerable URL: <a href="http://192.168.56.103/drupal/modules/simpletest/tests/upgrade/drupal-6.upload.database.php">http://192.168.56.103/drupal/modules/simpletest/tests/upgrade/drupal-6.upload.database.php</a>
<b>Impact</b> Successful exploitation will allow attacker to obtain sensitive information that could aid in further attacks.
<b>Solution:</b> <b>Solution type:</b> WillNotFix No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.
<b>Affected Software/OS</b> Drupal version 7.0 is known to be affected.
<b>Vulnerability Insight</b> The flaw is due to insufficient error checking, allows remote attackers to obtain sensitive information via a direct request to a .php file, which reveals the installation path in an error message.
<b>Vulnerability Detection Method</b> Details: Drupal 7.0 Information Disclosure Vulnerability - Active Check OID:1.3.6.1.4.1.25623.1.0.902574 Version used: 2021-12-01T11:10:56Z
<b>References</b> cve: CVE-2011-3730 url: <a href="http://code.google.com/p/inspathx/source/browse/trunk/paths_vuln/!_README">http://code.google.com/p/inspathx/source/browse/trunk/paths_vuln/!_README</a> url: <a href="http://code.google.com/p/inspathx/source/browse/trunk/paths_vuln/drupal-7.0">http://code.google.com/p/inspathx/source/browse/trunk/paths_vuln/drupal-7.0</a>

Medium (CVSS: 4.8) NVT: Cleartext Transmission of Sensitive Information via HTTP
<b>Summary</b> The host / application transmits sensitive information (username, passwords) in cleartext via HTTP.
<b>Vulnerability Detection Result</b> The following input fields were identified (URL:input name): ... continues on next page ...

...continued from previous page...	
<pre> http://192.168.56.103/drupal/:pass http://192.168.56.103/drupal/?D=A:pass http://192.168.56.103/payroll_app.php:password http://192.168.56.103/phpmyadmin/:pma_password http://192.168.56.103/phpmyadmin/?D=A:pma_password http://192.168.56.103/phpmyadmin/changelog.php:pma_password http://192.168.56.103/phpmyadmin/index.php:pma_password http://192.168.56.103/phpmyadmin/license.php:pma_password http://192.168.56.103/phpmyadmin/url.php:pma_password </pre>	
<p><b>Impact</b></p> <p>An attacker could use this situation to compromise or eavesdrop on the HTTP communication between the client and the server using a man-in-the-middle attack to get access to sensitive data like usernames or passwords.</p>	
<p><b>Solution:</b></p> <p><b>Solution type:</b> Workaround</p> <p>Enforce the transmission of sensitive data via an encrypted SSL/TLS connection. Additionally make sure the host / application is redirecting all users to the secured SSL/TLS connection before allowing to input sensitive data into the mentioned functions.</p>	
<p><b>Affected Software/OS</b></p> <p>Hosts / applications which doesn't enforce the transmission of sensitive data via an encrypted SSL/TLS connection.</p>	
<p><b>Vulnerability Detection Method</b></p> <p>Evaluate previous collected information and check if the host / application is not enforcing the transmission of sensitive data via an encrypted SSL/TLS connection.</p> <p>The script is currently checking the following:</p> <ul style="list-style-type: none"> <li>- HTTP Basic Authentication (Basic Auth)</li> <li>- HTTP Forms (e.g. Login) with input field of type 'password'</li> </ul> <p>Details: Cleartext Transmission of Sensitive Information via HTTP</p> <p>OID:1.3.6.1.4.1.25623.1.0.108440</p> <p>Version used: 2020-08-24T15:18:35Z</p>	
<p><b>References</b></p> <p>url: <a href="https://www.owasp.org/index.php/Top_10_2013-A2-Broken_Authentication_and_Session_Management">https://www.owasp.org/index.php/Top_10_2013-A2-Broken_Authentication_and_Session_Management</a></p> <p>url: <a href="https://www.owasp.org/index.php/Top_10_2013-A6-Sensitive_Data_Exposure">https://www.owasp.org/index.php/Top_10_2013-A6-Sensitive_Data_Exposure</a></p> <p>url: <a href="https://cwe.mitre.org/data/definitions/319.html">https://cwe.mitre.org/data/definitions/319.html</a></p>	
<p>Medium (CVSS: 4.3)</p> <p>NVT: jQuery &lt; 1.6.3 XSS Vulnerability</p>	
<p><b>Summary</b></p> <p>... continues on next page ...</p>	



...continued from previous page ...
jQuery is vulnerable to Cross-site Scripting (XSS) attacks.
<b>Vulnerability Detection Result</b> Installed version: 1.6.2 Fixed version: 1.6.3 Installation path / port: /phpmyadmin/setup/./js/jquery
<b>Solution:</b> <b>Solution type:</b> VendorFix Update to version 1.6.3 or later or apply the patch.
<b>Affected Software/OS</b> jQuery prior to version 1.6.3.
<b>Vulnerability Insight</b> Cross-site scripting (XSS) vulnerability in jQuery before 1.6.3, when using location.hash to select elements, allows remote attackers to inject arbitrary web script or HTML via a crafted tag.
<b>Vulnerability Detection Method</b> Checks if a vulnerable version is present on the target host. Details: jQuery < 1.6.3 XSS Vulnerability OID:1.3.6.1.4.1.25623.1.0.141637 Version used: 2021-06-11T09:02:34Z
<b>References</b> cve: CVE-2011-4969 url: <a href="https://blog.jquery.com/2011/09/01/jquery-1-6-3-released/">https://blog.jquery.com/2011/09/01/jquery-1-6-3-released/</a> cert-bund: CB-K17/0195 dfn-cert: DFN-CERT-2017-0199 dfn-cert: DFN-CERT-2016-0890

Medium (CVSS: 4.3) NVT: jQuery < 1.6.3 XSS Vulnerability
<b>Summary</b> jQuery is vulnerable to Cross-site Scripting (XSS) attacks.
<b>Vulnerability Detection Result</b> Installed version: 1.6.2 Fixed version: 1.6.3 Installation path / port: /phpmyadmin/js/jquery
<b>Solution:</b> ... continues on next page ...

...continued from previous page ...
<b>Solution type:</b> VendorFix Update to version 1.6.3 or later or apply the patch.
<b>Affected Software/OS</b> jQuery prior to version 1.6.3.
<b>Vulnerability Insight</b> Cross-site scripting (XSS) vulnerability in jQuery before 1.6.3, when using location.hash to select elements, allows remote attackers to inject arbitrary web script or HTML via a crafted tag.
<b>Vulnerability Detection Method</b> Checks if a vulnerable version is present on the target host. Details: jQuery < 1.6.3 XSS Vulnerability OID:1.3.6.1.4.1.25623.1.0.141637 Version used: 2021-06-11T09:02:34Z
<b>References</b> cve: CVE-2011-4969 url: <a href="https://blog.jquery.com/2011/09/01/jquery-1-6-3-released/">https://blog.jquery.com/2011/09/01/jquery-1-6-3-released/</a> cert-bund: CB-K17/0195 dfn-cert: DFN-CERT-2017-0199 dfn-cert: DFN-CERT-2016-0890

[ [return to 192.168.56.103](#) ]

### 2.1.6 Medium 22/tcp

Medium (CVSS: 5.3) NVT: Weak Host Key Algorithm(s) (SSH)
<b>Summary</b> The remote SSH server is configured to allow / support weak host key algorithm(s).
<b>Vulnerability Detection Result</b> The remote SSH server supports the following weak host key algorithm(s): host key algorithm   Description ----- ↪----- ssh-dss   Digital Signature Algorithm (DSA) / Digital Signature Stand ↪ard (DSS)
<b>Solution:</b> <b>Solution type:</b> Mitigation Disable the reported weak host key algorithm(s). ... continues on next page ...

...continued from previous page ...

**Vulnerability Detection Method**

Checks the supported host key algorithms of the remote SSH server.

Currently weak host key algorithms are defined as the following:

- ssh-dss: Digital Signature Algorithm (DSA) / Digital Signature Standard (DSS)

Details: **Weak Host Key Algorithm(s)** (SSH)

OID:1.3.6.1.4.1.25623.1.0.117687

Version used: 2021-11-24T06:31:19Z

Medium (CVSS: 5.3)

NVT: Weak Key Exchange (KEX) Algorithm(s) Supported (SSH)

**Summary**

The remote SSH server is configured to allow / support weak key exchange (KEX) algorithm(s).

**Vulnerability Detection Result**

The remote SSH server supports the following weak KEX algorithm(s):

KEX algorithm	Reason
-----	
↔-----	
diffie-hellman-group-exchange-sha1	Using SHA-1
diffie-hellman-group1-sha1	Using Oakley Group 2 (a 1024-bit MODP group
↔) and SHA-1	

**Impact**

An attacker can quickly break individual connections.

**Solution:**

**Solution type:** Mitigation

Disable the reported weak KEX algorithm(s)

- 1024-bit MODP group / prime KEX algorithms:

Alternatively use elliptic-curve Diffie-Hellmann in general, e.g. Curve 25519.

**Vulnerability Insight**

- 1024-bit MODP group / prime KEX algorithms:

Millions of HTTPS, SSH, and VPN servers all use the same prime numbers for Diffie-Hellman key exchange. Practitioners believed this was safe as long as new key exchange messages were generated for every connection. However, the first step in the number field sieve-the most efficient algorithm for breaking a Diffie-Hellman connection-is dependent only on this prime.

A nation-state can break a 1024-bit prime.

**Vulnerability Detection Method**

Checks the supported KEX algorithms of the remote SSH server.

Currently weak KEX algorithms are defined as the following:

... continues on next page ...

...continued from previous page ...
<ul style="list-style-type: none"> <li>- non-elliptic-curve Diffie-Hellmann (DH) KEX algorithms with 1024-bit MODP group / prime</li> <li>- ephemeral generated key exchange groups uses SHA-1</li> <li>- using RSA 1024-bit modulus key</li> </ul> <p>Details: Weak Key Exchange (KEX) Algorithm(s) Supported (SSH)  OID:1.3.6.1.4.1.25623.1.0.150713  Version used: 2022-12-08T10:12:32Z</p>
<p><b>References</b></p> <p>url: <a href="https://weakdh.org/sysadmin.html">https://weakdh.org/sysadmin.html</a>  url: <a href="https://www.rfc-editor.org/rfc/rfc9142.html">https://www.rfc-editor.org/rfc/rfc9142.html</a>  url: <a href="https://www.rfc-editor.org/rfc/rfc9142.html#name-summary-guidance-for-imple">https://www.rfc-editor.org/rfc/rfc9142.html#name-summary-guidance-for-imple</a>  ↪m  url: <a href="https://datatracker.ietf.org/doc/html/rfc6194">https://datatracker.ietf.org/doc/html/rfc6194</a></p>

<p>Medium (CVSS: 4.3)</p> <p>NVT: Weak Encryption Algorithm(s) Supported (SSH)</p>
<p><b>Summary</b></p> <p>The remote SSH server is configured to allow / support weak encryption algorithm(s).</p>
<p><b>Vulnerability Detection Result</b></p> <p>The remote SSH server supports the following weak client-to-server encryption al  ↪gorithm(s):</p> <p>3des-cbc  aes128-cbc  aes192-cbc  aes256-cbc  arcfour  arcfour128  arcfour256  blowfish-cbc  cast128-cbc  rijndael-cbc@lysator.liu.se</p> <p>The remote SSH server supports the following weak server-to-client encryption al  ↪gorithm(s):</p> <p>3des-cbc  aes128-cbc  aes192-cbc  aes256-cbc  arcfour  arcfour128  arcfour256  blowfish-cbc  cast128-cbc  rijndael-cbc@lysator.liu.se</p>
... continues on next page ...

...continued from previous page ...
<b>Solution:</b> <b>Solution type:</b> Mitigation Disable the reported weak encryption algorithm(s).
<b>Vulnerability Insight</b> - The 'arcfour' cipher is the Arcfour stream cipher with 128-bit keys. The Arcfour cipher is believed to be compatible with the RC4 cipher [SCHNEIER]. Arcfour (and RC4) has problems with weak keys, and should not be used anymore. - The 'none' algorithm specifies that no encryption is to be done. Note that this method provides no confidentiality protection, and it is NOT RECOMMENDED to use it. - A vulnerability exists in SSH messages that employ CBC mode that may allow an attacker to recover plaintext from a block of ciphertext.
<b>Vulnerability Detection Method</b> Checks the supported encryption algorithms (client-to-server and server-to-client) of the remote SSH server. Currently weak encryption algorithms are defined as the following: - Arcfour (RC4) cipher based algorithms - none algorithm - CBC mode cipher based algorithms Details: Weak Encryption Algorithm(s) Supported (SSH) OID:1.3.6.1.4.1.25623.1.0.105611 Version used: 2022-12-09T10:11:04Z
<b>References</b> url: <a href="https://www.rfc-editor.org/rfc/rfc4253#section-6.3">https://www.rfc-editor.org/rfc/rfc4253#section-6.3</a> url: <a href="https://www.kb.cert.org/vuls/id/958563">https://www.kb.cert.org/vuls/id/958563</a>

[ [return to 192.168.56.103](#) ]

### 2.1.7 Medium 631/tcp

Medium (CVSS: 4.3) NVT: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection
<b>Summary</b> It was possible to detect the usage of the deprecated TLSv1.0 and/or TLSv1.1 protocol on this system.
<b>Vulnerability Detection Result</b> In addition to TLSv1.2+ the service is also providing the deprecated TLSv1.0 and ↪ TLSv1.1 protocols and supports one or more ciphers. Those supported ciphers c ↪an be found in the 'SSL/TLS: Report Supported Cipher Suites' (OID: 1.3.6.1.4.1 ↪.25623.1.0.802067) VT.
...continues on next page ...

...continued from previous page ...
<p><b>Impact</b></p> <p>An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection.</p> <p>Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.</p>
<p><b>Solution:</b></p> <p><b>Solution type:</b> Mitigation</p> <p>It is recommended to disable the deprecated TLSv1.0 and/or TLSv1.1 protocols in favor of the TLSv1.2+ protocols. Please see the references for more information.</p>
<p><b>Affected Software/OS</b></p> <p>All services providing an encrypted communication using the TLSv1.0 and/or TLSv1.1 protocols.</p>
<p><b>Vulnerability Insight</b></p> <p>The TLSv1.0 and TLSv1.1 protocols contain known cryptographic flaws like:</p> <ul style="list-style-type: none"> <li>- CVE-2011-3389: Browser Exploit Against SSL/TLS (BEAST)</li> <li>- CVE-2015-0204: Factoring Attack on RSA-EXPORT Keys Padding Oracle On Downgraded Legacy Encryption (FREAK)</li> </ul>
<p><b>Vulnerability Detection Method</b></p> <p>Check the used TLS protocols of the services provided by this system.</p> <p>Details: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection</p> <p>OID:1.3.6.1.4.1.25623.1.0.117274</p> <p>Version used: 2021-07-19T08:11:48Z</p>
<p><b>References</b></p> <p>cve: CVE-2011-3389</p> <p>cve: CVE-2015-0204</p> <p>url: <a href="https://ssl-config.mozilla.org/">https://ssl-config.mozilla.org/</a></p> <p>url: <a href="https://bettercrypto.org/">https://bettercrypto.org/</a></p> <p>url: <a href="https://datatracker.ietf.org/doc/rfc8996/">https://datatracker.ietf.org/doc/rfc8996/</a></p> <p>url: <a href="https://vnhacker.blogspot.com/2011/09/beast.html">https://vnhacker.blogspot.com/2011/09/beast.html</a></p> <p>url: <a href="https://web.archive.org/web/20201108095603/https://censys.io/blog/freak">https://web.archive.org/web/20201108095603/https://censys.io/blog/freak</a></p> <p>url: <a href="https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters">https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters</a></p> <p>↔-report-2014</p> <p>cert-bund: CB-K18/0799</p> <p>cert-bund: CB-K16/1289</p> <p>cert-bund: CB-K16/1096</p> <p>cert-bund: CB-K15/1751</p> <p>cert-bund: CB-K15/1266</p> <p>cert-bund: CB-K15/0850</p> <p>cert-bund: CB-K15/0764</p> <p>cert-bund: CB-K15/0720</p>
... continues on next page ...

...continued from previous page ...

cert-bund: CB-K15/0548  
cert-bund: CB-K15/0526  
cert-bund: CB-K15/0509  
cert-bund: CB-K15/0493  
cert-bund: CB-K15/0384  
cert-bund: CB-K15/0365  
cert-bund: CB-K15/0364  
cert-bund: CB-K15/0302  
cert-bund: CB-K15/0192  
cert-bund: CB-K15/0079  
cert-bund: CB-K15/0016  
cert-bund: CB-K14/1342  
cert-bund: CB-K14/0231  
cert-bund: CB-K13/0845  
cert-bund: CB-K13/0796  
cert-bund: CB-K13/0790  
dfn-cert: DFN-CERT-2020-0177  
dfn-cert: DFN-CERT-2020-0111  
dfn-cert: DFN-CERT-2019-0068  
dfn-cert: DFN-CERT-2018-1441  
dfn-cert: DFN-CERT-2018-1408  
dfn-cert: DFN-CERT-2016-1372  
dfn-cert: DFN-CERT-2016-1164  
dfn-cert: DFN-CERT-2016-0388  
dfn-cert: DFN-CERT-2015-1853  
dfn-cert: DFN-CERT-2015-1332  
dfn-cert: DFN-CERT-2015-0884  
dfn-cert: DFN-CERT-2015-0800  
dfn-cert: DFN-CERT-2015-0758  
dfn-cert: DFN-CERT-2015-0567  
dfn-cert: DFN-CERT-2015-0544  
dfn-cert: DFN-CERT-2015-0530  
dfn-cert: DFN-CERT-2015-0396  
dfn-cert: DFN-CERT-2015-0375  
dfn-cert: DFN-CERT-2015-0374  
dfn-cert: DFN-CERT-2015-0305  
dfn-cert: DFN-CERT-2015-0199  
dfn-cert: DFN-CERT-2015-0079  
dfn-cert: DFN-CERT-2015-0021  
dfn-cert: DFN-CERT-2014-1414  
dfn-cert: DFN-CERT-2013-1847  
dfn-cert: DFN-CERT-2013-1792  
dfn-cert: DFN-CERT-2012-1979  
dfn-cert: DFN-CERT-2012-1829  
dfn-cert: DFN-CERT-2012-1530  
dfn-cert: DFN-CERT-2012-1380  
dfn-cert: DFN-CERT-2012-1377

...continues on next page ...

...continued from previous page ...

dfn-cert: DFN-CERT-2012-1292  
dfn-cert: DFN-CERT-2012-1214  
dfn-cert: DFN-CERT-2012-1213  
dfn-cert: DFN-CERT-2012-1180  
dfn-cert: DFN-CERT-2012-1156  
dfn-cert: DFN-CERT-2012-1155  
dfn-cert: DFN-CERT-2012-1039  
dfn-cert: DFN-CERT-2012-0956  
dfn-cert: DFN-CERT-2012-0908  
dfn-cert: DFN-CERT-2012-0868  
dfn-cert: DFN-CERT-2012-0867  
dfn-cert: DFN-CERT-2012-0848  
dfn-cert: DFN-CERT-2012-0838  
dfn-cert: DFN-CERT-2012-0776  
dfn-cert: DFN-CERT-2012-0722  
dfn-cert: DFN-CERT-2012-0638  
dfn-cert: DFN-CERT-2012-0627  
dfn-cert: DFN-CERT-2012-0451  
dfn-cert: DFN-CERT-2012-0418  
dfn-cert: DFN-CERT-2012-0354  
dfn-cert: DFN-CERT-2012-0234  
dfn-cert: DFN-CERT-2012-0221  
dfn-cert: DFN-CERT-2012-0177  
dfn-cert: DFN-CERT-2012-0170  
dfn-cert: DFN-CERT-2012-0146  
dfn-cert: DFN-CERT-2012-0142  
dfn-cert: DFN-CERT-2012-0126  
dfn-cert: DFN-CERT-2012-0123  
dfn-cert: DFN-CERT-2012-0095  
dfn-cert: DFN-CERT-2012-0051  
dfn-cert: DFN-CERT-2012-0047  
dfn-cert: DFN-CERT-2012-0021  
dfn-cert: DFN-CERT-2011-1953  
dfn-cert: DFN-CERT-2011-1946  
dfn-cert: DFN-CERT-2011-1844  
dfn-cert: DFN-CERT-2011-1826  
dfn-cert: DFN-CERT-2011-1774  
dfn-cert: DFN-CERT-2011-1743  
dfn-cert: DFN-CERT-2011-1738  
dfn-cert: DFN-CERT-2011-1706  
dfn-cert: DFN-CERT-2011-1628  
dfn-cert: DFN-CERT-2011-1627  
dfn-cert: DFN-CERT-2011-1619  
dfn-cert: DFN-CERT-2011-1482

[\[ return to 192.168.56.103 \]](#)



**2.1.8 Medium 21/tcp**

Medium (CVSS: 4.8) NVT: FTP Unencrypted Cleartext Login
<b>Summary</b> The remote host is running a FTP service that allows cleartext logins over unencrypted connections.
<b>Vulnerability Detection Result</b> The remote FTP service accepts logins without a previous sent 'AUTH TLS' command ↪. Response(s): Non-anonymous sessions: 331 Password required for openvasvt Anonymous sessions: 331 Anonymous login ok, send your complete email address ↪ as your password
<b>Impact</b> An attacker can uncover login names and passwords by sniffing traffic to the FTP service.
<b>Solution:</b> <b>Solution type:</b> Mitigation Enable FTPS or enforce the connection via the 'AUTH TLS' command. Please see the manual of the FTP service for more information.
<b>Vulnerability Detection Method</b> Tries to login to a non FTPS enabled FTP service without sending a 'AUTH TLS' command first and checks if the service is accepting the login without enforcing the use of the 'AUTH TLS' command. Details: FTP Unencrypted Cleartext Login OID:1.3.6.1.4.1.25623.1.0.108528 Version used: 2020-08-24T08:40:10Z

[\[ return to 192.168.56.103 \]](#)

**2.1.9 Low 22/tcp**

Low (CVSS: 2.6) NVT: Weak MAC Algorithm(s) Supported (SSH)
<b>Summary</b> The remote SSH server is configured to allow / support weak MAC algorithm(s).
<b>Vulnerability Detection Result</b> The remote SSH server supports the following weak client-to-server MAC algorithm ↪(s): ... continues on next page ...

<p>...continued from previous page ...</p> <pre> hmac-md5 hmac-md5-96 hmac-md5-96-etm@openssh.com hmac-md5-etm@openssh.com hmac-sha1-96 hmac-sha1-96-etm@openssh.com The remote SSH server supports the following weak server-to-client MAC algorithm ↔(s): hmac-md5 hmac-md5-96 hmac-md5-96-etm@openssh.com hmac-md5-etm@openssh.com hmac-sha1-96 hmac-sha1-96-etm@openssh.com </pre>
<p><b>Solution:</b>  <b>Solution type:</b> Mitigation  Disable the reported weak MAC algorithm(s).</p>
<p><b>Vulnerability Detection Method</b>  Checks the supported MAC algorithms (client-to-server and server-to-client) of the remote SSH server.  Currently weak MAC algorithms are defined as the following:  - MD5 based algorithms  - 96-bit based algorithms  - none algorithm  Details: Weak MAC Algorithm(s) Supported (SSH)  OID:1.3.6.1.4.1.25623.1.0.105610  Version used: 2021-09-20T11:05:40Z</p>

[\[ return to 192.168.56.103 \]](#)

### 2.1.10 Low general/icmp

<p>Low (CVSS: 2.1)  NVT: ICMP Timestamp Reply Information Disclosure</p>
<p><b>Summary</b>  The remote host responded to an ICMP timestamp request.</p>
<p><b>Vulnerability Detection Result</b>  Vulnerability was detected according to the Vulnerability Detection Method.</p>
<p><b>Solution:</b>  <b>Solution type:</b> Mitigation  ... continues on next page ...</p>

...continued from previous page ...
<p>Various mitigations are possible:</p> <ul style="list-style-type: none"> <li>- Disable the support for ICMP timestamp on the remote host completely</li> <li>- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)</li> </ul>
<p><b>Vulnerability Insight</b></p> <p>The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp. This information could theoretically be used to exploit weak time-based random number generators in other services.</p>
<p><b>Vulnerability Detection Method</b></p> <p>Details: ICMP Timestamp Reply Information Disclosure  OID:1.3.6.1.4.1.25623.1.0.103190  Version used: 2022-11-18T10:11:40Z</p>
<p><b>References</b></p> <p>cve: CVE-1999-0524  url: <a href="http://www.ietf.org/rfc/rfc0792.txt">http://www.ietf.org/rfc/rfc0792.txt</a>  cert-bund: CB-K15/1514  cert-bund: CB-K14/0632  dfn-cert: DFN-CERT-2014-0658</p>

[\[ return to 192.168.56.103 \]](#)

### 2.1.11 Low general/tcp

<p>Low (CVSS: 2.6)  NVT: TCP timestamps</p>
<p><b>Summary</b></p> <p>The remote host implements TCP timestamps and therefore allows to compute the uptime.</p>
<p><b>Vulnerability Detection Result</b></p> <p>It was detected that the host implements RFC1323/RFC7323.  The following timestamps were retrieved with a delay of 1 seconds in-between:  Packet 1: 88362  Packet 2: 88633</p>
<p><b>Impact</b></p> <p>A side effect of this feature is that the uptime of the remote host can sometimes be computed.</p>
<p><b>Solution:</b>  <b>Solution type:</b> Mitigation</p>
... continues on next page ...

...continued from previous page...	
<p>To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.</p> <p>To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.</p> <p>See the references for more information.</p>	
<b>Affected Software/OS</b> TCP implementations that implement RFC1323/RFC7323.	
<b>Vulnerability Insight</b> The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.	
<b>Vulnerability Detection Method</b> Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported. Details: TCP timestamps OID:1.3.6.1.4.1.25623.1.0.80091 Version used: 2020-08-24T08:40:10Z	
<b>References</b> url: <a href="http://www.ietf.org/rfc/rfc1323.txt">http://www.ietf.org/rfc/rfc1323.txt</a> url: <a href="http://www.ietf.org/rfc/rfc7323.txt">http://www.ietf.org/rfc/rfc7323.txt</a> url: <a href="https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152">https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152</a>	

[ [return to 192.168.56.103](#) ]