

Philip Pesic

Week 11

October 30 2022

Week 11 Prog 4

Write and run the code for the second example in the lecture note

```
//
```

```
// main.cpp
```

```
// Week 11 Prog 4
```

```
//
```

```
// Created by Pippo Pesic on 10/24/22.
```

```
//
```

```
// There are DEFAULT paramerters.
```

```
#include <string>
```

```
#include <iostream>
```

```
using namespace std;
```

```
void fun1( void ) { cout << " Void input, no return " << endl ; }
```

```
void fun2( int x = 1 ) { cout << " x = " << x << endl ; }
```

```
void fun3( int x = 12, double d = 34.5, string s = "Default word" ) {
```

```
    cout << " x = " << x << endl ;
```

```
    cout << " d = " << d << endl ;
```

```
    cout << " s = " << s << endl ;
```

```
}
```

Philip Pesic

Week 11

October 30 2022

Week 11 Prog 4

```
int main( )  
{  
    cout << "=====  
    fun1(); // no defaults - no inputs defined  
    cout << "=====  
  
    fun2(); // one default - used  
    cout << "=====  
    fun2(42); // User Parm Input  
    cout << "=====  
  
    // Default parameters loaded from right to left, No gaps or skips...  
    fun3(); // three defaults - all defaults used - no user input  
    cout << "=====  
    fun3(42); // three defaults - first two defaults used, last USER Parm Input  
    cout << "=====  
    fun3(42, 6.9); // three defaults - first default used, last two USER parms input  
    cout << "=====  
    fun3(42, 6.9, "user input value"); // three defaults - all three USER parms inputted  
    cout << "=====
```

Philip Pesic

Week 11


October 30 2022

Week 11 Prog 4

```
cout << "Philip Pesic 10/30/22" << endl;
```

```
return 0;
```

```
}
```



I learned: how to use required and optional function parameters