



# Are Neural Click Models Pointwise IPS Rankers?

---

Philipp Hager<sup>1</sup>, Maarten de Rijke<sup>1</sup>, Onno Zoeter<sup>2</sup>

September 23, 2022

<sup>1</sup>University of Amsterdam <sup>2</sup>Booking.com

`p.k.hager@uva.nl`, `m.derijke@uva.nl`, `onno.zoeter@booking.com`

# Motivation

|





# Unbiased LTR

**Problem:** Clicks are a biased indicator of item relevance [Craswell et al., 2008].

**Unbiased LTR:** Learn rankings from biased user interactions [Joachims et al., 2017].

## Click biases:


- Selection bias
- **Position bias**
- Trust bias
- ...

Observed	Relevant		Clicked
	☆☆☆	document 1	X
	☆☆☆	document 2	✓
	☆☆☆	document 3	X
	☆☆☆	document 4	X

## Probabilistic click models [Chuklin et al., 2015]

- Generative models predicting biased click behavior.
- Bias and relevance are latent parameters jointly inferred using MLE.
- Pointwise rankers

Position-based Model (PBM)



## Inverse-Propensity Scoring

Weight clicks to correct for position bias [Wang et al., 2016, Joachims et al., 2017].

- Decouples bias and relevance estimation.
- Generalizes over document features to require fewer observations of the same query-document pair.
- Introduced as pairwise / listwise rankers.

# Two sides of the same coin?

## Two sides of the same coin?

- Same user models (PBM, Cascade).
- Introduction of neural click models that also use features [Guo et al., 2019].
- Introduction of pointwise IPS methods [Saito et al., 2020].

## How do both approaches compare?

- Theoretically compare their ability for unbiased relevance estimation.
- Empirically on semi-synthetic click datasets used in ULTR.

## Methods

---

## Neural PBM

- Relevance of document  $d$  with features  $x_d$ :  $\hat{y}_d = \sigma(g(\hat{y} \mid x_d))$ .
- Position bias  $\hat{o}_k$  at rank  $k$ .
- Predict clicks:  $\hat{c}_{d,k} = \hat{o}_k \cdot \hat{y}_d$ .

Inference using binary cross-entropy between predicted and observed clicks [Yan et al., 2022]:

$$\mathcal{L}_{\text{pbm}}(\hat{y}, \hat{o}) = - \sum_{(d,k) \in D} c_{d,k} \cdot \log(\hat{y}_d \cdot \hat{o}_k) + (1 - c_{d,k}) \cdot \log(1 - \hat{y}_d \cdot \hat{o}_k).$$



## Pointwise IPS

- Relevance of document  $d$  with features  $x_d$ :  $\hat{y}_d = \sigma(g(\hat{y} \mid x_d))$ .

BCE loss weighting clicks inversely to the position bias [Saito et al., 2020]:

$$\mathcal{L}_{\text{ips}}(\hat{y}, \hat{o}) = - \sum_{(d,k) \in D} \frac{c_{d,k}}{\hat{o}_k} \cdot \log(\hat{y}_d) + (1 - \frac{c_{d,k}}{\hat{o}_k}) \cdot \log(1 - \hat{y}_d).$$

- **IPS:** Saito et al. show that the pointwise IPS estimator is unbiased when correctly estimating position bias [Saito et al., 2020].
- **PBM with joint parameter inference:** Oosterhuis shows that click models jointly inferring bias and relevance are not always consistent estimators of document relevance [Oosterhuis, 2022].
- **PBM only inferring relevance?**

## Click model only inferring relevance?


Find the ideal model that minimizes  $\mathcal{L}_{\text{pbm}}$ :

$$\begin{aligned}\frac{\partial \mathcal{L}_{\text{pbm}}}{\partial \hat{y}} &= 0 \\ -\frac{c - \hat{o}\hat{y}}{\hat{y}(1 - \hat{o}\hat{y})} &= 0 \\ c - \hat{o}\hat{y} &= 0.\end{aligned}$$

The click model also optimizes for unbiased relevance if  $\forall k \in K, \hat{o}_k = o_k$

$$\hat{y} = \frac{\mathbb{E}_o[c]}{\hat{o}} = \frac{o_y}{\hat{o}}.$$

## Comparing loss magnitude



**Figure 1:** Loss for a single document of relevance  $y_d = 0.5$  under increasing position bias.

# Experiments

---

## Experimental setup



Semi-synthetic clicks on MSLR30K, Yahoo!, and Istella-S:

- Sample a query uniformly at random.
- Pre-rank documents with “production” ranker (LambdaMART, 20 train queries).
- Sample clicks using the PBM user model.

We simulate:

- **Position bias:**  $o_k = \left(\frac{1}{1+k}\right)^\eta$
- **Graded relevance:**  $y_d = \epsilon + (1 - \epsilon) \cdot \frac{2^{s_d} - 1}{2^4 - 1}$ , click noise  $\epsilon = 0.1$ .

# Results



○ PBM - Estimated Bias    □ PBM - True Bias    △ Point. IPS - True Bias    ⊕ Point. IPS / PBM - Naive    ◇ Production Ranker

## Hypothesis I - Tuning?



---



**Hypothesis II - Does generalizing  
over features introduce bias?**


---

## Revisiting loss magnitude




- Combined
- $y = 0.1, o = 1.0$
- △  $y = 0.9, o = 0.1$


## Experiment I: One-hot encoded synthetic documents



## Experiment II: Introduce feature collisions between synthetic documents



## Experiment III: Increase the (known) position bias



## Summary

- Both approaches optimize for unbiased document relevance **if the true position bias is known** and relevance is **estimated separately per query-document pair**.
- The neural click model seems to be **affected by (known) position bias** when generalizing over **shared, sometimes conflicting, document features**.

p.k.hager@uva.nl

<https://github.com/philippager/ultr-cm-vs-ips>



[Chuklin et al., 2015] Chuklin, A., Markov, I., and de Rijke, M. (2015).

**Click Models for Web Search.**

Morgan & Claypool.

[Craswell et al., 2008] Craswell, N., Zoeter, O., Taylor, M., and Ramsey, B. (2008).

**An experimental comparison of click position-bias models.**

In *International Conference on Web Search and Data Mining (WSDM)*.

[Guo et al., 2019] Guo, H., Yu, J., Liu, Q., Tang, R., and Zhang, Y. (2019).

**Pal: A position-bias aware learning framework for ctr prediction in live recommender systems.**

In *ACM Conference on Recommender Systems (RecSys)*.

[Joachims et al., 2017] Joachims, T., Swaminathan, A., and Schnabel, T. (2017).

**Unbiased learning-to-rank with biased feedback.**

In *International Conference on Web Search and Data Mining (WSDM)*.

[Oosterhuis, 2022] Oosterhuis, H. (2022).

**Reaching the end of unbiasedness: Uncovering implicit limitations of click-based learning to rank.**

In *International Conference on the Theory of Information Retrieval (ICTIR)*.



[Saito et al., 2020] Saito, Y., Yaginuma, S., Nishino, Y., Sakata, H., and Nakata, K. (2020).

**Unbiased recommender learning from missing-not-at-random implicit feedback.**

*In International Conference on Web Search and Data Mining (WSDM).*

[Wang et al., 2016] Wang, X., Bendersky, M., Metzler, D., and Najork, M. (2016).

**Learning to rank with selection bias in personal search.**

*In International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR).*

[Yan et al., 2022] Yan, L., Qin, Z., Zhuang, H., Wang, X., Bendersky, M., and Najork, M. (2022).

**Revisiting two-tower models for unbiased learning to rank.**

In *International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR)*.