
# Write and Submit your first Linux Kernel Patch

Brandon Philips
SUSE Labs / Novell
brandon@ifup.org



### What are we not going to cover?



## LINUX KERNEL

#### IN A NUTSHELL

A Desktop Quick Reference



Greg Kroab-Hartman

SECOND EDITION

Draft, Sed On ANGI COSON

THE

PROGRAMMING LANGUAGE

> BRIAN W KERNIGHAN DENNIS M. RITCHIE

> > PRENTICE HALL SCIFTWARE SETIES

### What we are going to cover

- git basics
- Linux kernel coding style
- Fixing a file
- Generating a patch
- Emailing the patch



#### git clone

git clone git://git.kernel.org/pub/scm/linux/kernel/git/torvalds/linux-2.6.git

#### git branch


git branch tutorial git checkout tutorial

## Linux Kernel Coding Style

## Why Care?

"It is not merely a matter of aesthetics that programs should be written in a particular style. Rather there is a psychological basis for writing programs in a conventional manner: programmers have strong expectations that other programmers will follow these discourse rules. If the rules are violated, then the utility afforded by the expectations that programmers have built up over time is effectively nullified."

Soloway & Ehrlich



## Use tabs All tabs are 8 characters 80 character line limit

```
if (error != -ENODEV) {
    foo();
    bar();
}
```

```
if (error != -ENODEV) {
        foo();
        bar();
} else {
        report_error();
        goto exit;
```

```
if (error != -ENODEV)
    foo();
else
    goto exit;
```

```
int function(int *baz)
{
    do_something(baz);
    return 0;
}
```

## scripts/checkpatch.pl

```
In the case where a gadget driver is removed while no
transceiver was found at probe time, a bug in
otg put transceiver() will trigger.
Signed-off-by: Robert Jarzmik <robert.jarzmik@free.fr>
Acked-by: David Brownell <dbrownell@users.sourceforge.net>
Signed-off-by: Greg Kroah-Hartman <gregkh@suse.de>
--- a/drivers/usb/otg/otg.c
+++ b/drivers/usb/otg/otg.c
@@ -43,7 +43,8 @@ EXPORT SYMBOL(otg_get_transceiver);
void otg put transceiver(struct otg transceiver *x)
        put device(x->dev);
        if (x)
                put device(x->dev);
```

USB: otg: Fix bug on remove path without transceiver

git diff

git commit

git show

git format-patch

git send-email

### scripts/get\_maintainer.pl

#### Checklist

- Kernel builds with patch applied
- Correct "From:" address
- Concise "Subject:"
- Explain the patch
- Signed-off-by

## kernelnewbies.org



