

One-page cheat sheet

Default rule: use sync. Quit Moom first. Run without sudo.

Everyday sync, including changes from another Mac

```
macos-config-sync.sh sync
```

Check setup and repository status

```
macos-config-sync.sh status
```

For all commands: `macos-config-sync.sh help`. For the release: `version`.

Upgrade an already-synchronised Mac: establish its baseline

```
macos-config-sync.sh adopt
```

Once only, when the clean checkout matches the last deployed state. Then sync. Never use adopt for a new clone or to bypass a warning.

Start a new Mac: prepare the checkout

```
macos-config-sync.sh init
```

Then pull only if you deliberately want the repository to replace managed local settings.

Enrol one new file, then run sync

```
macos-config-sync.sh add scripts/example.sh
```

Keep a local file, remove its repository copy on next sync

```
macos-config-sync.sh forget scripts/example.sh
```

Paths are HOME-relative. Repository deletions can affect other Macs.

Explain what sync does, without changing anything

```
DRY_RUN=1 macos-config-sync.sh sync
```

Not a computed diff or remote-change preview.

Mirror the current repository to the NAS

```
macos-config-sync.sh nas-push
```

Includes deletions. Use a clean, reconciled checkout.

Stopped sync: resolve or cancel

Inspect the checkout. Resolve conflicts there, stage the resolved paths and continue the rebase. Then run sync again.

```
repo="$HOME/.local/share/macos-config"
git -C "$repo" status
git -C "$repo" add home/.zshrc # example resolved file
git -C "$repo" rebase --continue
```

To abandon: preserve manual resolution edits, then rebase --abort if a rebase is active, followed by `macos-config-sync.sh cancel`. `cancel` keeps HOME unchanged, but cannot undo a previous push or deployment.

Recovery only: these can overwrite or delete local files

macos-config-sync.sh pull applies GitHub configuration.

macos-config-sync.sh restore applies the clean local checkout.

Backups: `~/.local/state/macos-config/backups/` (last 10 by default).