

November 24, 2020 at 13:24

**1. Intro.** This little program makes empirical tests by which I can check the accuracy of the SETSET program. (See that program for explanations.)

```
#define m 12      /* size of each hand */
#define n 100000000 /* number of random trials */
#include <stdio.h>
#include "gb_flip.h" /* use the Stanford GraphBase random number routines */
char deck[81];
char occ[81];
char z[3][3] = {{0, 2, 1}, {2, 1, 0}, {1, 0, 2}}; /*  $x + y + z \equiv 0 \pmod{3}$  */
char third[81][128];

main()
{
    register int j, k, t;
    int reps, count;
    <Initialize 2>;
    while (1) {
        count = 0;
        for (reps = 0; reps < n; reps++) {
            <Shuffle the deck 4>;
            <Increase count if there are no SETs 3>;
        }
        printf("%d/%d\n", count, n);
    }
}
```

**2. #define pack(a, b, c, d) (((a) \* 3 + (b)) \* 3 + (c)) \* 3 + (d)**

```
<Initialize 2> ≡
gb_init_rand(0);
for (k = 0; k < 81; k++) deck[k] = k;
for (k = 81 - m; k < 81; k++) occ[k] = 1;
{
    int a, b, c, d, e, f, g, h;
    for (a = 0; a < 3; a++)
        for (b = 0; b < 3; b++)
            for (c = 0; c < 3; c++)
                for (d = 0; d < 3; d++)
                    for (e = 0; e < 3; e++)
                        for (f = 0; f < 3; f++)
                            for (g = 0; g < 3; g++)
                                for (h = 0; h < 3; h++)
                                    third[pack(a, b, c, d)][pack(e, f, g, h)] = pack(z[a][e], z[b][f], z[c][g], z[d][h]);
}
```

This code is used in section 1.

3.  $\langle \text{Increase } count \text{ if there are no SETs } 3 \rangle \equiv$   
**for** ( $j = 81 - m$ ;  $j < 80$ ;  $j++$ )  
     **for** ( $k = j + 1$ ;  $k < 81$ ;  $k++$ )  
         **if** ( $occ[third[deck[j]][deck[k]]]$ ) **goto** *set\_found*;  
     *count*++;  
*set\_found*:

This code is used in section 1.

4.  $\langle \text{Shuffle the deck } 4 \rangle \equiv$   
**for** ( $j = 81$ ;  $j > 81 - m$ ;  $j--$ ) {  
      $t = deck[j - 1]$ ;  
      $occ[t] = 0$ ;  
      $k = gb\_unif\_rand(j)$ ;  
      $deck[j - 1] = deck[k]$ ;  
      $occ[deck[k]] = 1$ ;  
      $deck[k] = t$ ;  
}

This code is used in section 1.

**5. Index.**

*a*: [2](#).  
*b*: [2](#).  
*c*: [2](#).  
*count*: [1](#), [3](#).  
*d*: [2](#).  
*deck*: [1](#), [2](#), [3](#), [4](#).  
*e*: [2](#).  
*f*: [2](#).  
*g*: [2](#).  
*gb\_init\_rand*: [2](#).  
*gb\_unif\_rand*: [4](#).  
*h*: [2](#).  
*j*: [1](#).  
*k*: [1](#).  
*m*: [1](#).  
*main*: [1](#).  
*n*: [1](#).  
*occ*: [1](#), [2](#), [3](#), [4](#).  
*pack*: [2](#).  
*printf*: [1](#).  
*reps*: [1](#).  
*set\_found*: [3](#).  
*t*: [1](#).  
*third*: [1](#), [2](#), [3](#).  
*z*: [1](#).

⟨ Increase *count* if there are no SETs 3 ⟩ Used in section 1.  
⟨ Initialize 2 ⟩ Used in section 1.  
⟨ Shuffle the deck 4 ⟩ Used in section 1.

# SETSET-RANDOM

|             | Section           | Page |
|-------------|-------------------|------|
| Intro ..... | <a href="#">1</a> | 1    |
| Index ..... | <a href="#">5</a> | 3    |