

November 24, 2020 at 13:23

1. Intro. Given n , generate BDDL to compute a representation of all restricted growth sequences $a_1 \dots a_n$ (and thus of all set partitions of $\{1, \dots, n\}$).

```
#define maxn 500
#include <stdio.h>
#include <stdlib.h>
int n;
int subscr[maxn + 1][maxn]; /* allocation of variable subscripts */
main(int argc, char *argv[])
{
    register int i, j, k;
    if (argc != 2 || sscanf(argv[1], "%d", &n) != 1 || n <= 0) {
        fprintf(stderr, "Usage: %s %d\n", argv[0], n);
        exit(-1);
    }
    printf("#beginning the output of BDDL-RGROWTH %d\n", n);
    for (i = 0, k = n; k--;)
        for (j = 0; j < k; j++) subscr[k][j] = i++;
    for (j = 1; j <= n; j++) printf("f%d=c1\n", j);
    for (k = n; k--;)
        for (j = 1; j < k; j++) {
            printf("f0=x%d?f%d:c0\n", subscr[k][0], j);
            printf("f%d=x%d?c0:f%d\n", maxn, subscr[k][0], j + 1);
            printf("f%d=x%d?c0:f%d\n", maxn + 1, subscr[k][0], j);
            for (i = 1; i < j; i++) {
                printf("f0=x%d?f%d:f0\n", subscr[k][i], maxn + 1);
                printf("f%d=x%d?c0:f%d\n", maxn, subscr[k][i], maxn);
                printf("f%d=x%d?c0:f%d\n", maxn + 1, subscr[k][i], maxn + 1);
            }
            printf("f0=x%d?f%d:f0\n", subscr[k][j], maxn);
            for (i++; i < k; i++) printf("f0=x%d?c0:f0\n", subscr[k][i], j);
            printf("f%d=f0\n", j);
        }
    printf("f1=x%d?f1:c0\n", subscr[1][0]);
    printf("!f1 represents restricted growth sequences of length %d\n", n);
}
```

2. Index.

argc: [1](#).
argv: [1](#).
exit: [1](#).
fprintf: [1](#).
i: [1](#).
j: [1](#).
k: [1](#).
main: [1](#).
maxn: [1](#).
n: [1](#).
printf: [1](#).
sscanf: [1](#).
stderr: [1](#).
subscr: [1](#).

BDDL-RGROWTH

	Section	Page
Intro	1	1
Index	2	2