Lecture # 12 CHE331A

- Introduction and design equation for ideal reactors

- Basics of reaction kinetics and Isothermal reactor design - conversions, molar flow rates or concentrations

- Differential, Integral, Initial Rates, Half Life, Non-linear regression method of Analysis

- Differential PBR method of Collection/Analysis

GOUTAM DEO

CHEMICAL ENGINEERING DEPARTMENT

IIT KANPUR

Methanator

$$3H_2 + CO = CH_4 + H_2O$$

Differential reactor is used to determine rate as a function of concentration or partial pressure

▶ Consist of a tube containing a small amount of catalyst

F$_{A0}$
C$_{A0}$

ΔW

F$_{Ae}$
C$_{Ae}$
F$_{P}$

$$F_{A0} - F_{Ae} + r'_A \Delta W = 0$$

$$-r'_A = \frac{F_{A0} - F_{Ae}}{\Delta W}$$

▶ In terms of concentration: $\quad -r'_A = \frac{\dot{v}_0 C_{A0} - \dot{v}.C_{Ae}}{\Delta W} = \frac{\dot{v}_0 (C_{A0} - C_{Ae})}{\Delta W}$

▶ In terms of conversion or product molar flow rate: $\quad -r'_A = \frac{X F_{A0}}{\Delta W} = \frac{\mu_P F_P}{\Delta W}$

○ Thus, rate can be determined as a function of C$_{A0}$

Differential reactor is used to develop rate laws and determine parameter values – Example 5-5

▶ $3H_2 + CO \rightarrow CH_4 + 2H_2O$ methanation reaction; Convert CO

$P_{CO,0}$
$P_{H2,0}$

C_{CH4e}
$\dot{v}_e = 100 \; {dm^3}/{min}$

$\triangle W = 10$ g
$T = 500°F$

(a) relate the rate to $C_{CH4,e}$

(b) assumed: $r'_{CH4} = f(CO).g(H_2)$

(c) determine rate law dependency

and rate law parameters

Run	P_{CO} (atm)	P_{H2} (atm)	C_{CH4} (mol/dm³)
1	1.00	1.0	$1.73*10^{-4}$
2	1.80	1.0	$4.40*10^{-4}$
3	4.08	1.0	$10.0*10^{-4}$
4	1.00	0.1	$1.65*10^{-4}$
5	1.00	0.5	$2.47*10^{-4}$
6	1.00	4.0	$1.75*10^{-4}$

Outlet concentration given not $C_{CO,0}$

Rate of methane formation can be determined and related to rate of CO disappearance

▸ In terms of conversion or product molar flow rate: $-r_A' = \frac{XF_{A0}}{\Delta W} = \frac{\mu_P F_P}{\Delta W}$

▸ $3H_2 + CO \rightarrow CH_4 + 2H_2O$ $\qquad -r_{CO}' = r_{CH4}' = \frac{F_{CH4}}{\Delta W} = \frac{\dot{v}_e C_{CH4}}{\Delta W}$

▸ Thus, $-r_{CO}'$ can be determined

▸ For example, for run 1

$$r_{CH4}' = \left(\frac{300 \, dm^3}{min}\right)\frac{1.73*10^{-4} \, mol/dm^3}{10 \, g \, cat}$$

$$r_{CH4}' = 5.2*10^{-3}\left(\frac{mol \, CH_4}{g.cat*min}\right) = -r_{CO}'$$

Run	P_{CO} (atm)	P_{H2} (atm)	C_{CH4} (mol/dm^3)	r_{CH4}' $\left(\frac{mol \, CH_4}{g.cat*min}\right)$
1	1.00	1.0	$1.73*10^{-4}$	$5.2*10^{-3}$
2	1.80	1.0	$4.40*10^{-4}$	$13.2*10^{-3}$
3	4.08	1.0	$10.0*10^{-4}$	$30.0*10^{-3}$
4	1.00	0.1	$1.65*10^{-4}$	$4.95*10^{-3}$
5	1.00	0.5	$2.47*10^{-4}$	$7.42*10^{-3}$
6	1.00	4.0	$1.75*10^{-4}$	$5.25*10^{-3}$

Proper planning of the experiments assist in determining the form of the rate law

▶ $r'_{CH4} = f(CO).g(H_2)$ for runs 1,2 and 3 P_{H2} is constant and P_{CO} increases → $r'_{CH4} = kP_{CO}^{\alpha}.g(H_2) = k'P_{CO}^{\alpha}$

▶ Taking natural log we have $ln(r'_{CH4}) = lnk' + \alpha.ln(P_{CO})$

▶ By plotting for the first three runs

▶ $\alpha = 1.22 \approx 1.00$

  (more runs would help)

▶ Thus, $r'_{CH4} = k.P_{CO}.g(H_2)$

▶ We need to find the dependency of rate with hydrogen

Run	P_{CO} (atm)	P_{H2} (atm)	C_{CH4} (mol/dm^3)	r'_{CH4} $\left(\dfrac{mol\ CH_4}{g.cat*min}\right)$
1	1.00	1.0	$1.73*10^{-4}$	$5.2*10^{-3}$
2	1.80	1.0	$4.40*10^{-4}$	$13.2*10^{-3}$
3	4.08	1.0	$10.0*10^{-4}$	$30.0*10^{-3}$
4	1.00	0.1	$1.65*10^{-4}$	$4.95*10^{-3}$
5	1.00	0.5	$2.47*10^{-4}$	$7.42*10^{-3}$
6	1.00	4.0	$1.75*10^{-4}$	$5.25*10^{-3}$

Rate dependency on P_{H2} non-monotonic

▶ Dependency of r'_{CH4} with P_{H2} cannot be represented by a power law

▶ With increasing P_{H2}

   ○ Rate increases (run 4 to run 5)

   ○ Low P_{H2}

$$r'_{CH4} \sim P_{H2}^{\beta 1}$$

   ○ High P_{H2}; decreases (run 5 to run 1)

$$r'_{CH4} \sim \frac{1}{P_{H2}^{\beta 2}}$$

   ○ Even higher P_{H2}; rate is relatively constant (run 1 to run 6)

Run	P_{CO} (atm)	P_{H2} (atm)	C_{CH4} (mol/dm³)	r'_{CH4} $\left(\frac{mol\ CH_4}{g.cat * min} \right)$
1	1.00	1.0	$1.73*10^{-4}$	$5.2*10^{-3}$
2	1.80	1.0	$4.40*10^{-4}$	$13.2*10^{-3}$
3	4.08	1.0	$10.0*10^{-4}$	$30.0*10^{-3}$
4	1.00	0.1	$1.65*10^{-4}$	$4.95*10^{-3}$
5	1.00	0.5	$2.47*10^{-4}$	$7.42*10^{-3}$
6	1.00	4.0	$1.75*10^{-4}$	$5.25*10^{-3}$

There should be one Rate law to be consistent with the experimental observations

▶ Rate variations depends on P_{H2} $\quad r'_{CH4} \sim P_{H2}^{\beta 1}$ at low P_{H2}, and

$$r'_{CH4} \sim \frac{1}{P_{H2}^{\beta 2}} \text{ at high } P_{H2}$$

▶ One such rate law is: $\quad r'_{CH4} \sim \dfrac{P_{H2}^{\beta 1}}{1 + b.P_{H2}^{\beta 2}}$ (such forms are common)

▶ Does this rate law satisfies the observed trends?

▶ At low P_{H2} the denominator $\rightarrow 1$ $\quad$ and $r'_{CH4} \sim P_{H2}^{\beta 1}$ $\qquad \beta 2 > \beta 1$

▶ At high P_{H2} the denominator $\rightarrow b.P_{H2}^{\beta 2}$ $\quad$ and $r'_{CH4} \sim \dfrac{P_{H2}^{\beta 1}}{P_{H2}^{\beta 2}} \sim \dfrac{1}{(P_{H2})^{\beta 2 - \beta 1}}$

Non-linear regression is useful to determine the parameters

▶ Taking into account the variation of rate with P_{CO}, the "unified" rate law is

$$r'_{CH4} = \frac{aP_{CO}P_{H2}^{\beta 1}}{1 + b.P_{H2}^{\beta 2}}$$

▶ Need to find the rate law parameters $a, b, \beta 1 \ and \ \beta 2$, which is consistent with the experimental data

▶ Done by non-linear regression, e.g., initial guess for the parameters = 1

▶ Resulting rate law with only six runs (N=6 and K=4)

$$r'_{CH4} = \frac{0.025P_{CO}P_{H2}^{0.61}}{1 + 2.49 * P_{H2}}$$

Rate law for the methanation reaction – additional considerations

▶ The rate law for the methanation reaction: $3H_2 + CO \rightarrow CH_4 + 2H_2O$

$$r'_{CH4} = \frac{0.025 P_{CO} P_{H2}^{0.61}}{1 + 2.49 * P_{H2}}$$

▶ Heterogeneous catalysis, power associated with H_2 is ½ (dissociation adsorption)

▶ Consider a factor of ½, instead of 0.61, and evaluate 2 parameters $a \text{ and } b$

▶ Again by non-linear regression, with initial guess for $a \text{ and } b$ as those obtained previously, and with P_{CO} and P_{H2} in atm

$$r'_{CH4} = \frac{0.018 P_{CO} P_{H2}^{0.5}}{1 + 1.49 * P_{H2}} \frac{mol}{g.cat * s}$$