



NCQE interactions as a background to DSNB events with neutron tagging at SK-Gd

Department of Physics
University of Liverpool

Thesis submitted in accordance with the requirements of the University of Liverpool for
the degree of Doctor in Philosophy by

Pruthvi Hiren Mehta

June 2023

Dedication

નિધિ માટે

In Memoriam



**In Loving Memory of:
Shri Ghanshyam Bhai D. Shukla
and
Shri Mukundroy N. Mehta**

ॐ अस्तो मा सद्गमय ।
तमसो मा ज्योतिर्गमय ।
मृत्योर्मा अमृतं गमय ।

Translation:

**From untruth, lead me to the truth;
From darkness, lead me to the light;
From death, lead me to immortality.**

- Bṛhadāraṇyaka Upaniṣad

Acknowledgements

First and foremost thanks must be given to my academic supervisor Professor Neil McCauley, someone whose intelligence, work ethic and kindness have continuously been a source of inspiration to me.

I am also forever indebted to a number of postdoctoral researchers who I was fortunate enough to have aid me with my research; namely Dr Ka Ming Tsui, Dr Pablo Fernandez Menendez, Dr Lauren Anthony, Dr Adrian Pritchard and Dr Samuel Jamuel Jenkins. Thank you all for your continued encouragement and support, and apologies for emailing all of you for help so much (but in my defence ROOT is the worst).

I am also incredibly grateful to members of the neutron tagging working group, in particular Dr Fabio Iacob whose weekly meetings about my analysis were crucial to my work and who is one of the most patient and kind individuals I have ever met (and I wouldn't have survived calculating the systematics without him). I am also indebted to Seungho Han for his help with the new neutron tagging software, and also Nakajima-sensei, Koshio-sensei, Akutsu-sensei and Tairafune-san for their input in the neutron tagging meetings.

I'd also like to thank current and former members of the Super-Kamiokande and Hyper-Kamiokande calibration groups, Dr Jordan McElwee, Dr Matthew Thiesse, Dr Billy Vining and Yang-san for UKLI MC implementation help.

A huge thank you to Dr Gedminas Elertas, who kept the spirit of scientific curiosity alive inside me, and also to Dr Selina Dhinsey and Hannah Brown, my women physicist comrades in arms who helped me push back against the powers that be: I can't thank you both enough for this.

Many thanks to my wonderful besties from undergrad, Karel Green and Rachel Couchman, I've known both of you for nearly a decade and I treasure your friendship so so much, you've kept me sane and supported throughout this entire journey. Here's to you, babes! Also to my schoolfriends Catherine Thomas, Amy Rose-Mansbridge and Catriona

Bradley, I've known you for over 15 years and it has been incredible to see you all blossom into amazing, capable and talented young women who I'm blessed to know. Also thanks to Patrick Bates for the calmness and profound wisdom that you so often espouse, you wonderful lovely nerd!

Thank you to Joseph (my *imzadi*) for your gentle and kind heart, you've always been so incredibly supportive and I'm so happy to know you.

To my parents, “thank you” isn’t anywhere near a sufficient enough response to how much you’ve supported me. Mum - your strength and wisdom is unparalleled, and dad, well, you’re the best physicist I know. Finally to my sister Nidhi, who this thesis is dedicated to, I love you so much and your kindness and intelligence is something I aspire to everyday. You’re amazing!

Abstract

The error on the DSNB NCQE background is calculated for an estimated future POT of 10×10^{21} starting JFY 2028, and is estimated at $N_{\nu-\text{DSNB}_{NCQE}} = 9.88 \pm 3.62$ events for FHC mode. The neutral current quasi-elastic (NCQE) interactions of neutrinos on ^{16}O generated by the beam neutrinos of the T2K (Tokai-to-Kamioka) experiment produces neutrons in the medium of the far detector Super Kamiokande. This thesis focuses on the detection of these neutrons by a neutron tagging algorithm specifically developed for the addition of 0.026% $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ to Super-Kamiokande (the level present in SK from August 2020 - May 2022), modelled in the MC simulation by the ANNRI-Gd model. The neutron tagging algorithm is complemented by the use of an artificial neural network (ANN), which is used on neutron candidates to improve sensitivity to signal events and to reduce background events. The efficiency of this neutron tagging algorithm is calculated and validated using calibration data from neutrons produced by an Am/Be + 8BGO source.

The calibration work in this thesis centers on developing Monte Carlo for the collimator and diffuser UK Light Injector optics, which were compared against test run data. The time-of-flight (TOF) hit time distributions of these MC were compared against data and the time dispersion of the MC was adjusted to approximate that of data.

Statement of Originality

This thesis and the work presented in it stem from my own original and independent research. However, contributions from other researchers working on the Tokai-to-Kamioka and Super-Kamiokande experiments are also presented and referenced. My NCQE analysis was carried out with input from the neutron tagging working group, and my calibration work was carried out with input from the Super-Kamiokande and Hyper-Kamiokande calibration working groups.

Chapter 1 gives an overview of neutrino physics, including the solar neutrino problem, neutrino oscillation and the diffuse supernova neutrino background, and also an overview of neutrino-nucleus interactions. All relevant books and articles used to gather this information have been cited.

Chapter 2, 3 and 4 give an overview of the T2K and Super-K experiments relevant to this thesis, including design, data acquisition methods, information on the SK-Gd upgrade and information on calibration methods carried out at Super-K. These three chapters summarise prior analyses carried out such as those performed by the EGADS experiment and by the calibration group at Super-K, and relevant publications have been cited.

Chapter 5 presents my contribution to the Super-Kamiokande calibration group and implementation of the UKLI MC. The measurements of the light profiles of the UKLI optics from the test stands were taken by Dr Sammy Valder (University of Warwick), but their implementation into SKDETSIM was done by myself along with the testing of the output and the variation of the time dispersion.

Chapter 6 presents the NCQE analysis of my thesis, with an emphasis on the development of the neutron tagging algorithm. The existing legacy neutron tagging algorithm used for neutron capture on hydrogen analyses was modified by myself to accomodate for the addition of $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ to Super-K. The new NTag algorithm was developed by Seungho Han (ICRR) and was modified by myself to work for the NCQE analysis, and the

NCQE selection code was rewritten from scratch by myself to work with the new NTag algorithm. Due to many factors, there is no SK phase VI data for comparison with the NCQE MC plots in this thesis. This is due to the NIWG model and flux tunings not being updated for this analysis during the completion of this chapter and also due to the collaboration's ongoing investigations into discrepancies regarding neutron capture models between SKDETSIM-SKGd (used in this analysis) and SKG4 (a C++/Geant4 based Super-K detector simulator) for when (or if) the collaboration moves from SKDETSIM-SKGd to SKG4.

Chapter 7 presents the systematic errors for my analysis, and uses the T2K beam working group for the neutrino beam fluxes and the T2K neutrino interaction working group (NIWG) for the neutrino interaction cross sections. Although these inputs were taken from external sources, the method of implementation had to be modified so the errors could be propagated with SKDETSIM-SKGd, as opposed to for SKDETSIM (used in prior NCQE ntag analyses), and this was implemented for each error by myself.

Chapter 8 presents the DSNB NCQE background measurement for a future POT of 10×10^{21} . The total number of NCQE events and the scale factor and DSNB NCQE background measurement error were calculated by myself, however the number of DSNB background events were taken from plots produced by the DSNB working group and presented in the December 2022 Super-Kamiokande Collaboration meeting, and a relevant link and citation have been given.

Contents

1	Introduction	1
1.1	Introduction	1
1.1.1	Neutrino Physics	1
1.1.2	History of Neutrino Physics	1
1.1.3	The Solar Neutrino Problem	2
1.1.4	Neutrino Oscillation Theory	6
1.1.5	Neutrino-nucleus interactions in Super-Kamiokande Gd	9
1.1.6	Diffuse Supernova Neutrino Background	14
1.1.7	Physics motivation behind the Super-Kamiokande Gadolinium Upgrade	26
2	The Tokai-to-Kamioka experiment	28
2.1	The Tokai-to-Kamioka experiment	28
2.1.1	Neutrino beam production	29
2.1.2	Near detectors	31
3	The Super Kamiokande Detector	39
3.1	The Super-Kamiokande detector	39
3.1.1	Background and detector design	39
3.1.2	Data aquisition system	43
3.2	Event Reconstruction	45
3.2.1	Vertex Reconstruction	45
3.2.2	Direction Reconstruction	47
3.2.3	Energy reconstruction	47
3.3	Super-Kamiokande Gadolinium Upgrade	49

3.3.1	Americium/Beryllium Calibration	49
3.3.2	The EGADS project	50
3.3.3	Gadolinium loading into Super-Kamiokande	51
4	Super-Kamiokande Detector Calibration	56
4.1	Inner detector calibration	56
4.1.1	PMT high-voltage setting calibration	56
4.1.2	Relative gain calibration	57
4.1.3	Absolute gain calibration	58
4.1.4	Relative quantum efficiency measurement	59
4.1.5	Timing information calibration	61
4.1.6	Measurement of light reflection on the black sheet and the PMTs	63
5	The UK Light Injection System	71
5.1	The UK Light Injection System Electronics and Optics	71
5.2	Optics test stand measurements	74
5.3	First commissioning data from UKLI	76
5.4	Implementation of UKLI in SK Simulation	80
6	Neutron Tagging and NCQE Interactions with the SK-Gd Upgrade	95
6.1	Event Simulation	96
6.1.1	Neutrino flux	97
6.1.2	Primary interaction	99
6.1.3	Detector response and interactions in the detector medium	101
6.2	Event Reconstruction	104
6.2.1	BONSAI output reconstruction quantities	104
6.2.2	Comparison of BONSAI reconstruction output variables between SKDETSIM versions	108
6.2.3	NCQE event selection	113
6.2.4	Prompt event NCQE reduction cut plots	120
6.3	Neutron tagging information and secondary selection	123
6.3.1	True neutron tagging information	123
6.3.2	Primary selection criteria	127
6.3.3	Secondary selection criteria	132

7 Systematic uncertainty calculations	147
7.1 Introduction	147
7.2 Systematic uncertainty calculation methodology	148
7.2.1 Gamma ray detector response	149
7.2.2 Neutrino beam flux uncertainty	149
7.2.3 Neutrino cross section uncertainty	150
7.2.4 Pion final state interaction (FSI) and secondary interaction (SI) uncertainties	154
7.2.5 Nucleon final state interactions	155
7.2.6 Muon and pion capture on Oxygen-16	158
7.2.7 Nucleon SI	159
7.2.8 MICAP uncertainty calculation	160
7.2.9 HETC uncertainty calculation	161
7.2.10 Uncertainty due to PMT gain simulation	164
7.2.11 Detector response for neutrino events	164
7.2.12 Final systematic error	166
8 The DSNB NCQE background	168
8.1 Introduction	168
8.2 NCQE cross-section uncertainty prediction	169
8.3 Number of DSNB NCQE background events	171
9 Conclusion	174
A Appendix A	190
A.1 Occupancy Plots for the UKLI MC B1 - B5 injector Autocalib data	190
A.2 Probability distribution functions and cumulative distribution functions for the B1 - B5 injectors	190
A.3 Fits to the cumulative distribution functions and their inverse for the B1-B5 injectors	191
A.4 Monte Carlo simulations of the light profiles for the B1-B5 injectors	199
A.5 Validation check to the fits for the inverse cumulative distribution functions	199

List of Figures

1.1	Proton-proton chain cycle in stars with branching percentages shown for each reaction involved	3
1.2	Solar neutrino fluxes predicted by Bachall's Standard Solar Model, and which experiments are able to detect them [1].	4
1.3	Feynman diagrams of charged-current (left) and neutral-current (right) neutrino interactions.	9
1.4	Feynman diagrams of neutral-current (left) and charged-current (right) neutrino-electron scattering.	10
1.5	Feynman diagram for ν_μ and $\bar{\nu}_\mu$ neutral-current elastic scattering (left) and $\bar{\nu}_\mu$ charge-current quasielastic scattering (right).	10
1.6	Feynman diagram for a charged current deep inelastic scattering interaction with an incoming muon neutrino	12
1.7	Feynman diagram for the inverse beta decay reaction.	13
1.8	Feynman diagram for a quasi elastic scattering interaction off a nucleon.	14
1.9	Schematic of neutron production following the interaction of neutrino with a nucleon inside an ^{16}O and the resulting FSI and SI interactions in the detector medium.	15
1.10	Schematic showing core collapse of a star, and the resultant shockwave and neutrino production.	17
1.11	Schematic showing core collapse of a star, and the resultant shockwave and neutrino production.	19
1.12	Luminosity (top panels) and average energy (bottom panels) for three different neutrino flavours as a function of time for the neutronisation phase (left), accretion phase (centre) and cooling phase (right). Taken from [2].	20

1.13	Events detected centered on 16:35:35 JST, where the solid lines are the number of hit PMTs and dashed lines are muon events. The zoomed in plot in the top-right shows an expanded version of the 0.0 - 2.0 second time scale.	22
1.14	DSNB flux against neutrino energy for various theoretical models, “NH” and “IH” are the normal and inverted mass hierchies respectively.	24
1.15	The 90% C.L. for observed and expected upper limits on the electron anti-neutrino flux from SK-I - SK-IV and KamLAND, with the theoretical predictions in Figure 1.14 shown in grey.	25
1.16	Schematic showing the IBD and NCQE interaction mechanisms.	26
1.17	MC study of (a) neutron multiplicity production for ν and $\bar{\nu}$, (b) neutral current, charged current and deep and non-deep inelastic scattering, (c) the correction to the visible energy as a function of neutrino multiplicity. Taken from [3].	27
2.2	Schematic of the neutrino beam line	31
2.3	Schematic of the INGRID cross taken from [4].	32
2.4	Individual INGRID module schematic taken from [4].	33
2.5	INGRID event display showing a typical INGRID event, taken from [5].	33
2.6	Neutrino beam profiles for x (left) and y (right) directions.	34
2.7	Energy of the neutrino plotted against the energy of the parent pion for multiple different off-axis angles, taken from [4].	35
2.8	The probability of survival of muon neutrinos (top plot) and neutrino beam flux at the 295km far detector (bottom) Taken from [4].	36
2.9	Near detector ND280 schematic taken from [5].	37
3.1	Schematic of an ID 50 cm Super-Kamiokande PMT [6].	41
3.2	Water purification system at SK.	42
3.3	Schematic of the charge-to-time converter circuit [7].	44
3.4	Probability density of the timing residual $P(t - t_{\text{tof}} - t_0)$, where t_0 is used for the vertex reconstruction maximum likelihood fit. The peaks at 30ns and 100ns are caused by PMT after-pulsing.	46
3.5	The vertex resolution (the point at which 68% of the events in the distance distribution between the actual and reconstructed vertex are contained) for the different SK phases. SK-I (Blue), SK-III (Red), SK-IV (Black).	46

3.6	(a) Delayed neutron capture time from prompt event with Am/Be source. (b) Reconstructed energy from gamma rays after neutron capture. Taken from [3]	50
3.7	The attenuation length of Cherenkov light measured using cosmic ray muons between March of 2020 and March of 2021, taken from [3]. The green lines on the figure indicate the first gadolinium loading period from July 14th 2020 to August 17th 2020.	52
3.8	Conductivity vs. z position during Gd loading inside the inner detector, taken from [8].	53
3.9	Neutron capture time distribution for the Am/Be source placed at Z=0 m, taken from [8].	54
4.1	Location of 420 reference PMTs used for HV setting calibration. The red lines show the placement of these PMTs with respect to the others (left). The grouping of these PMTs due to their geometry in relation to the light source is also shown (right)	57
4.2	Relative gain of PMTs in Super-Kamiokande	59
4.3	Nickel-californium source used for absolute gain calibration [9]	60
4.4	Single p.e distribution of charge in pC [9]	60
4.5	Schematic of the timing calibration system, with SK ID PMTs in blue and the diffuser ball in purple. The dye laser shifts the wavelength of the laser light to 398 nm to maximise the quantum efficiency of the PMTs and light absorption.	62
4.6	Example TQ distribution for an inner detector PMT, where the horizontal axis gives the charge of each hit (QBin), and the vertical axis gives the time in nanoseconds after subtracting the time of flight.	63
4.7	Residual timing distribution summed over all the readout channels in charge bin 14 (QBin in Figure 4.6.)	64
4.8	Timing resolution as a function of charge for SK-IV	64
4.9	Schematic of the laser light reflectivity. Bird's-eye view (left) and setup inside of Super-Kamiokande (right).	65
4.10	Schematic of the differences between Rayleigh and Mie scattering	66
4.11	Schematic of the laser system	67

4.12	Plot of water coefficient functions used in Monte Carlo production, showing points for symmetric and asymmetric scattering and absorption.	69
4.13	Dependence of temperature on vertical position in the Super-Kamiokande ID.	70
5.1	Collimator schematic including the end-cap, lens mount and mounting sleeve structures.	72
5.2	Photograph of the diffuser by itself (left), empty diffuser enclosure (centre) and diffuser inside enclosure (right).	73
5.3	Photograph of the optical plate which houses the different optics.	73
5.4	Setup of the collimator test stand provided by the University of Warwick.	74
5.5	Light profiles for the collimator optics provided by the University of Warwick. The profile for each barrel collimator (B1-B5) is shown in (a)-(e) respectively. The light intensity in arbitrary units is shown on the y-axis, while the polar angle of the light is shown on the x-axis.	75
5.6	Setup of the diffuser test stand provided by the University of Warwick.	76
5.7	Light profiles for the diffuser optics provided by the University of Warwick. The profile for each barrel diffuser (B1-B5) is shown in (a)-(e) respectively. The light intensity in arbitrary units is shown on the y-axis, while the polar angle scan of the light across the diffuser is shown on the x-axis.	77
5.8	Occupancy plots for the collimator optics from the UKLI November 2019 test run for each barrel collimator in the unrolled volume of the SK detector. The crosses show the injector positions, and the collimator beam spots are also shown (the PMTs with highest occupancy). The corrected time-of-flight plots for the PMT hits is shown in the bottom right corner.	78
5.9	Occupancy plots for the diffuser optics from the UKLI November 2019 test run, where the injector positions are shown by crosses. The corrected time-of-flight plots for the PMT hits is shown in the bottom right corner.	79
5.10	Schematic showing position of the UKLI in autocalib scheduler: the black dashed lines show the UKLI B1-B5 collimator and diffuser optics and the horizontal blue line shows the length of one autocalib cycle.	80
5.11	Occupancy plot for the B1 collimator optic from the UKLI Autocalib July 2020 run.	81
5.12	Occupancy plot for the B1 diffuser optic from the UKLI Autocalib July 2020 run.	81

5.13 Charge weighted z profile plots for the B1 collimator UKLI injector optic, with the September 2019 test run data shown in black and the November 2019 test run data shown in red.	82
5.14 Charge weighted z profile plots for the B4 collimator UKLI injector optic, with the September 2019 test run data shown in black and the November 2019 test run data shown in red.	83
5.15 PDF (left) and CDF (right) for the B1 collimator.	84
5.16 PDF (left) and CDF (right) for the B1 diffuser.	84
5.17 CDF and inverse CDF for the B1 collimator (left) and for the B1 diffuser (right). The y-axis (range 0.0-1.0) on the top subplots for both figures shows the CDF values for the data (blue) and polynomial fit (red) while the x-axis for the top subplots shows the angle scan range for the specific optic in degrees. For the bottom subplots which show the resulting inverse CDF function (green) and fit to this function (purple) these axes are reversed.	85
5.18 Monte Carlo simulations of the B1 collimator (left) and diffuser (right) injectors	86
5.19 B1 diffuser inverse CDF check	86
5.20 Gaussian distributed time dispersion plots, with varying amounts of time dispersion	88
5.21 The included (green) and excluded (red) regions for the TOF timing distributions	88
5.22 TOF comparison between UKLI MC with no time dispersion and Run 82181 test data for B1 collimator	89
5.23 TOF comparison between UKLI MC with 5 ns gaussian time dispersion and Run 82181 test data for B1 collimator	90
5.24 TOF comparison between UKLI MC with 10 ns gaussian time dispersion and Run 82181 test data for B1 collimator, with a gaussian fit to both	91
5.25 TOF comparison between UKLI MC with 15 ns gaussian time dispersion and Run 82181 test data for B1 collimator, with a gaussian fit to both	92
5.26 TOF comparison between UKLI MC with 20 ns gaussian time dispersion and Run 82181 test data for B1 collimator, with a gaussian fit to both	93
6.1 Flowchart showing the stages in this analysis for both the analyses which used the legacy NTag code (blue) and the current NTag code (orange).	96

6.2	Energy spectra of the $(\nu_e, \overline{\nu}_e, \nu_\mu, \overline{\nu}_\mu)$ flavour components for the FHC mode, T2K Run 1-9	98
6.3	Plot showing the NCQE cross section for ^{16}O as a function of incoming neutrino energy and the cross section of gamma ray production, taken from [10]	100
6.4	Representation of NC neutrino scattering off ^{16}O with protons on the left hand side and neutrons on the right arranged according to the shell model	100
6.5	Schematic of the ANNRI Ge spectrometer (dimensions in mm). The beam pipe along with one of the Ge cluster detectors (light blue) is shown. The shaded purple area are the anti-coincidence shields made of bismuth-germanium-oxide (BGO) crystals [11]	103
6.6	Energy spectra for thermal neutron capture on ^{157}Gd energy spectra for different multiplicity values (left) and hit values (right) from one of the germanium crystals in the ANNRI spectrometer. Taken from [11]	103
6.7	Energy spectra for the ANNRI-Gd model broken down into its continuous and discrete components along with data from the ANNRI-Gd experiment [11].	104
6.8	Comparison between neutron capture MC models and ANNRI-Gd data, with the ratio of data and MC on the y-axis, the GLG4sim model in blue, GEANT4 default model in green and the ANNRI-Gd model in red [11].	105
6.9	Schematic of the prompt event vertex and a triplet of independent PMT hits which make up the Cherenkov angle, taken from [12].	107
6.10	Comparisons of prompt event electron reconstructed energy between versions of SKDETSIM	108
6.11	Comparisons of dwall for the prompt event between versions of SKDETSIM	109
6.12	Comparisons of effwall for the prompt event between versions of SKDETSIM	109
6.13	Comparisons of ovaQ for the prompt event between versions of SKDETSIM	110
6.14	Comparisons of Cherenkov angle for the prompt event between versions of SKDETSIM	110
6.15	Comparisons of vertex goodness for the prompt event between versions of SKDETSIM	111
6.16	Comparisons of directional goodness for the prompt event between versions of SKDETSIM	111
6.17	Distance between true and reconstructed neutrino vertex for different SKDET-SIM versions	112
6.18	Reconstructed energy (MeV) comparison	113

6.19	DWall (cm) comparison	114
6.20	Effwall (cm) comparison	114
6.21	Reconstructed Cherenkov angle (degrees)	115
6.22	Comparisons of vertex goodness for the prompt event between versions of SKDETSIM	115
6.23	Spectra of NCQE backgrounds where the ν_μ charged current channel is from decay electron data, whereas the other three are from Monte Carlo. A clear decrease of NC elastic events are shown after 30 MeV. Taken from [13]	116
6.24	Schematic defining the fiducial volume (FV) and the dWall and effWall variables	117
6.25	Optimised cut values for dwall (top left), effwall (top right) and ovaQ (bottom) for Run 8 FHC mode. The red lines are linear fits to the values for these distributions, where events which have values above the lines are used in the analysis [14]. The blue vertical bars are the bin widths involved in the parameter scans for each parameter set.	119
6.26	Comparisons of stacked histograms for the E_{rec} variable between NCQE neutron tag on H analysis (left) and this analysis (right)	120
6.27	Comparisons of stacked histograms for the Dwall variable between NCQE neutron tag on H analysis (left) and this analysis (right)	121
6.28	Comparisons of stacked histograms for the Effwall variable between NCQE neutron tag on H analysis (left) and this analysis (right)	121
6.29	Comparisons of stacked histograms for the ovaQ variable between NCQE neutron tag on H analysis (left) and this analysis (right)	122
6.30	Comparisons of stacked histograms for the θ_C variable between NCQE neutron tag on H analysis (left) and this analysis (right)	122
6.31	Number of events plotted against number of true neutron captures (left) and number of events plotted against the time of all neutron captures (μ s) (right).	123
6.32	Number of gamma rays produced by neutron capture (left) and total energy of gamma rays produced by neutron capture (right) in the Monte Carlo	124
6.33	True neutron capture x-position (cm) (top left), true neutron capture y-position (cm) (top right) and true neutron capture z-position (cm)(bottom)	125
6.34	Number of all true neutrons plotted against true neutron capture time for the legacy NTag (left) and the new NTag (right)	125

6.35 Number of all true neutrons plotted against the distance between the neutrino and neutron capture vertices for the legacy NTag (left) and the new NTag (right)	126
6.36 Plot of fraction of neutron captures on Gd plotted against percentage of Gd by mass in water, taken from [15].	126
6.37 Number of all true neutrons plotted against true neutron capture time for the new NTag, for captures on hydrogen (left) and gadolinium (right).	127
6.38 Number of all true neutrons plotted against the distance between the neutrino and neutron capture vertices for the new NTag, for captures on hydrogen (left) and gadolinium (right)	127
6.39 Distance between true and reconstructed neutron capture vertex in water Monte Carlo [16] (left) and from this analysis (right). The pink arrow on the left plot and the dashed blue line on the right plot shows the 68th percentile of the distributions.	129
6.40 Number of candidate neutrons plotted against the reconstructed Cherenkov opening angle from hits from neutron captures on H	130
6.41 Number of candidate neutrons plotted against the reconstructed Cherenkov opening angle from hits from neutron captures on Gd	130
6.42 Number of candidate neutrons plotted against the reconstructed Cherenkov opening angle from hits from neutron captures on both H and Gd	130
6.43 Number of tagged signal neutrons plotted against neutron capture time (left) and distance between neutrino interaction vertex and neutron capture vertex (right)	130
6.44 Number of tagged signal neutrons plotted against neutron capture time seperated into captures on hydrogen (left) and gadolinium (right).	131
6.45 Number of tagged signal neutrons plotted against distance between neutrino interaction vertex and neutron capture vertex seperated into captures on hydrogen (left) and gadolinium (right).	131

6.46 Neural network output signal likelihood. Total signal neutron capture candidates are shown in the distribution with a blue line, whereas candidates that capture on hydrogen are shown in red, and gadolinium in green, and the distribution of background candidates are shown in pink. The dashed blue line shows the cutoff value of TagOut, where a neutron candidate is determined as being signal if the value of TagOut ≥ 0.7 and background if TagOut < 0.7 .	136
6.47 Number of events plotted against various neural network input variables prior to the neural network	137
6.48 Number of events plotted against various neural network input variables after neural network output	138
6.49 Am/Be + 8BGO source: the Am/Be source is housed at the centre of the 8 BGO crystals, which are 2.5 x 2.5 x 2.5 cm each and themselves placed inside an acrylic case. The edge of each crystal is cut so there is an inner place for the Am/Be source to be kept	141
6.50 Distribution of hits from Am/Be + 8 BGO data within the 14 ns sliding timing window	141
6.51 Efficiency of NTag plotted against DWall cut value	142
6.52 Fitted time relative to the trigger signal with exponential fit (red) for the Am/Be data taken in the centre position (0,0,0)	143
6.53 Fitted time relative to the trigger signal with exponential fit (red) for the Am/Be data taken at (0,0,+12)	143
6.54 Fitted time relative to the trigger signal with exponential fit (red) for the Am/Be data taken at (-12,0,0)	144
6.55 Fitted time relative to the trigger signal with exponential fit (red) for the NCQE MC	145
 7.1 Fractional uncertainties of beam fluxes, taken from [17], for FHC mode.	151
7.2 Tagging efficiency fractional uncertainties caused by neutrino beam flux discrepancies associated with neutrino energy in the 0.1 - 10 GeV range. From left to right the sections in this plot are comprised of the beam flux elements of ($\nu_e \bar{\nu}_e \nu_\mu \bar{\nu}_\mu$) respectively.	152
7.3 Tagging efficiency uncertainty caused by the cross-section parameter variations for the FHC mode	153

7.4	Tagging efficiency fractional uncertainty caused by the variation in the FSI/SI model parameters for the FHC mode	155
7.5	Tagging efficiency fractional uncertainties caused by the nucleon final state interaction model parameter variation for the FHC mode	158
7.6	Fractional uncertainties in the tagging efficiency caused by muon and pion capture on the muon capture CHIPS model, pion capture CHIPS model and the pion capture Bertini model.	159
7.7	Left: Fraction of inelastic cross-section for hydrogen for both the ENDF-V and ENDF-VIII libraries. Right: Difference of the fraction of the inelastic cross-section between the two libraries. Taken from [17].	161
7.8	Left: Fraction of inelastic cross-section for ^{16}O for both the ENDF-V and ENDF-VIII libraries. Right: Difference of the fraction of the inelastic cross-section between the two libraries. Taken from [17].	161
7.9	Tagging efficiency dependence of the true distance between the neutrino and neutron capture vertices between the ENDF V library (used in the nominal MC, shown in cyan) and the ENDF/B VIII library shown in red.	162
7.10	Left: proton-proton (neutron-neutron) cross sections, where the shaded area covers the values which are scaled by $\pm 30\%$. Right: proton-neutron cross sections, where the shaded area covers the values which are scaled by $\pm 30\%$. Taken from [17].	163
7.11	Tagging efficiency dependence of the true distance between the prompt vertex and the neutron capture vertex for the nominal MC (cyan) and the $\pm 30\%$ cross section cases.	163
7.12	Variation in tagging efficiency produced by the error in neutrino detector response parameters (BONSAI output variables). Red: -1σ discrepancy. Blue: $+1\sigma$ discrepancy.	165
8.1	Number of events plotted against E_{rec} for T2K FHC mode	170
8.2	Number of events plotted against E_{rec} for T2K RHC mode	170
8.3	Reconstructed energy spectra after data reduction for the backgrounds and the observed data taken with 552.2 days of SK-VI data. Taken from [18], accessed on 22/03/23.	172

A.1	Occupancy plot for the collimator optics from the UKLI Autocalib July 2020 run for each barrel collimator in the unrolled volume of the SK detector. The crosses show the injector positions, and the collimator beam spots are also shown (the PMTs with highest occupancy). The corrected time-of-flight plots for the PMT hits is shown in the bottom right corner.	192
A.2	Occupancy plot for the diffuser optics from the UKLI Autocalib July 2020 run for each barrel diffuser where the injector positions are shown by crosses. The corrected time-of-flight plots for the PMT hits is shown in the bottom right corner.	193
A.3	PDFs and corresponding CDFs for the B1 - B5 collimators, with intensity in arbitrary units on the y-axis, and angle in degrees on the x-axis.	194
A.4	PDFs and corresponding CDFs for the B1 - B5 diffusers, with intensity in arbitrary units on the y-axis, and angle in degrees on the x-axis.	196
A.5	CDF and inverse CDF fits for the B1 - B5 collimator PDFs. The y-axis (range 0.0-1.0) on the top subplots for both figures shows the CDF values for the data (blue) and polynomial fit (red) while the x-axis for the top subplots shows the angle scan range for the collimator in degrees. For the bottom subplots which show the resulting inverse CDF function (green) and fit to this function (purple) these axes are reversed.	198
A.6	CDF and inverse CDF fits for the B1 - B5 diffuser PDFs. The y-axis (range 0.0-1.0) on the top subplots for both figures shows the CDF values for the data (blue) and polynomial fit (red) while the x-axis for the top subplots shows the angle scan range for the diffuser in degrees. For the bottom subplots which show the resulting inverse CDF function (green) and fit to this function (purple) these axes are reversed.	200
A.7	MC simulations of the B1 - B5 collimators	201
A.8	MC simulations of the B1 - B5 diffusers	202
A.9	Inverse CDF checks of the B1 - B5 diffusers	203

List of Tables

1.1	Supernovae classification along with the element lines present in their spectra [19].	16
3.1	Phases of Super-Kamiokande and main properties of each phase	43
3.2	Table of impurities in the gadolinium sulphate octahydrate powder	51
4.1	Refractive indices of materials inside the Super-K detector, where λ is the wavelength of the light in nm, and n_{real} and n_{img} are the real and imaginary parts of the complex refractive index of the bi-alkali material used in the photocathode of the PMTs.	65
5.1	Beam spot positions (x,y,z) of the UKLI injectors in cm and misalignment of the injectors in degrees.	81
5.2	Sigma of gaussian (ns) for each value of time dispersion along wth the χ^2/ndf value for B1 data and MC comparison between the scattered hits region (blue dashed lines).	90
6.1	Software versions used in analysis from [17]	97
6.2	Oscillation parameters estimated with the reactor constraint	99
6.3	Transition probabilities for different models and states	101
6.4	Abundance and thermal neutron capture cross section of various isotopes of gadolinium	101
6.5	Value of the true neutrino vertex - reconstructed neutrino vertex distribution which encompasses 1-sigma (68%) of the number of events	112
6.6	FHC MC expectation values for each interaction type	120
6.7	NTag primary selection criteria	128

6.8	NTag pre-selection, NN classification and total efficiencies	140
6.9	Am/Be data run numbers, data taking time and Am/Be source positions .	141
6.10	Am/Be time constant value and efficiency values along with the χ^2/ndf value of the exponential fit, the value of the background pedestal (B) events and the number of tagged neutrons from the Am/Be source at different positions	145
7.1	Neutrino cross section parameters. Taken from [20] and [21].	153
7.2	Table showing the pion final state interaction parameters in NEUT and the pion momentum range they are used in, taken from [22]	155
7.3	Pion FSI/SI model parameter nominal value and variations grouped according to inelastic hadron production value, taken from [22].	156
7.4	Nucleon final state interaction parameters of the hA model executed inside GENIE.	157
7.5	Uncertainties on BONSAI output parameters (taken from [23]).	165
7.6	Final systematic uncertainties for the tagging efficiency	166
8.1	FHC MC expectation values for each interaction type with a total SK POT of 10×10^{21}	169
8.2	RHC MC expectation values for each interaction type with a total SK POT of 10×10^{21}	170
8.3	Number of low energy IBD events for each 2 MeV energy bin from 8 - 30 MeV for data and MC	171

Chapter 1

Introduction

“First things first, but not necessarily in that order.”

The Fourth Doctor, Doctor Who:
Megalos (1980)

1.1 Introduction

1.1.1 Neutrino Physics

There are a plethora of physics phenomena in which neutrinos are involved, including beta decay, fusion, and supernovae. As part of the Standard Model, they are described as being Dirac fermions with no electric charge with three flavours: the electron neutrino, the muon neutrino and the tau neutrino, corresponding with their associated leptons: the electron, muon and tauon. Prior to the discovery of neutrino oscillations, it was believed that neutrinos were massless, but they in fact have small but non zero masses ($\leq 1\text{eV}$) [24]. This chapter will discuss a brief history of neutrino physics including the discovery of neutrino oscillations, the manner in which neutrinos interact with nuclei in the Super-Kamiokande detector, and the motivation behind an NCQE neutron tagging analysis.

1.1.2 History of Neutrino Physics

To correct a violation of energy and momentum conservation discovered in beta-decay, Wolfgang Pauli put forward the idea of a neutrino as a solution [25]. He originally named this particle the “neutron”, prior to Chadwick’s discovery of the actual neutron two years

later. Enrico Fermi then proposed to call it the neutrino, Italian for “little neutral one”. In 1934, Enrico Fermi’s theory of beta decay stated that a neutron could decay to a proton, electron and an electron antineutrino [26] and in 1956 [27], Clyde Cowan and Frederick Reines directly confirmed the existence of neutrinos [28], by detecting the electron antineutrino originating from inverse beta decay produced from nuclear reactor or fission products. In inverse beta decay an electron antineutrino interacts with a proton to produce a neutron and positrons [29].

These positrons pair-annihilate with electrons and produce two 0.5 MeV gamma rays. Scintillator material was placed in a tank of water, which was used to detect these gamma photons, and the scintillator light produced flashes of visible light which were detected by photomultiplier tubes. Cadmium chloride was used to detect the coincident neutron, which after exciting and de-exciting, emits a gamma ray within 5 microseconds after the pair-annihilation gammas are detected [30]. In 1962, Lederman, Schwartz and Steinberger detected the muon neutrino [31], [32]. To discover the muon neutrino, the AGS (Alternating Gradient Synchrotron) at Brookhaven [33] was used - the AGS’s beam of protons was used to produce a shower of pions after slamming into a beryllium target. These pions would travel toward a 5,000-ton steel wall (constructed from old battleship plates! [34]) and they would decay into muons and neutrinos, but only neutrinos would be able to pass through the steel wall into a spark chamber filled with neon. As neutrinos coursed through this chamber, one neutrino would occasionally hit a proton in an aluminium nucleus which would produce muon tracks, instead of the showers produced from electrons, proving that there were muon neutrinos in the neutrinos that passed through the chamber [35].

In 2000 the DONUT collaboration (Direct Observation of NU Tau) at Fermilab detected the existence of the tau neutrino [36]. A beam of neutrinos (which they expected to contain tau neutrinos) was fired at iron plates with alternating layers of emulsion, and a very very small number of these tau neutrinos interacted with an iron nucleus to produce the tau lepton, which decayed leaving a track in the emulsion [37]. These tracks contained a kink, which were a sign of the tau neutrino, and only four such tracks were detected out of a possible six million [38].

1.1.3 The Solar Neutrino Problem

The Standard Solar Model predicts that most of the solar neutrino flux (about 90%) comes from the proton-proton chain reaction [39], where the solar neutrinos produced




Figure 1.1: Proton-proton chain cycle in stars with branching percentages shown for each reaction involved

have energies below 0.4 MeV. Figure 1.1 shows the processes which make up the pp chain, along with the branching percentages where it produces a neutrino.

Only experiments that use gallium can detect neutrinos with this energy, whereas experiments whose detector medium is Chlorine can observe neutrinos from ${}^7\text{Be}$ (production equation of which is shown in Figure 1.1). Experiments whose detector medium is water (such as Super-Kamiokande and SNO) can only see the ${}^8\text{B}$ neutrinos, as shown in Figure 1.2.

In the 1960s, the Homestake experiment made the first measurement of solar electron neutrino flux [40]. The experiment used a perchloroethylene-based detector, placed 1,478 metres underground in the Homestake Gold Mine in South Dakota. When an electron neutrino interacts with ${}^{37}\text{Cl}$ in the perchloroethylene, the ${}^{37}\text{Cl}$ becomes a radioactive isotope of ${}^{37}\text{Ar}$ which is extracted by bubbling helium through the tank, and then counted in order




Figure 1.2: Solar neutrino fluxes predicted by Bachall's Standard Solar Model, and which experiments are able to detect them [1].

to determine how many neutrinos had been captured [41]. The theoretical solar neutrino flux calculated by John Bachall was about three times as much as Raymond Davis' results from the experiment: with Bachall's calculations predicting a solar neutrino flux of 8.1 ± 1.2 SNU, whereas the Homestake experimental results showed a flux of 2.56 ± 0.25 SNU [42]. These results were consistent with those from the subsequent Kamiokande, SAGE and GALLEX experiments. Super-Kamiokande's main detection channel for solar neutrinos is the elastic-scattering channel, which has a minimum energy threshold value (recoil electron kinetic energy) of 5 MeV. In this channel, Super-Kamiokande observed a solar neutrino capture rate of 0.45 ± 0.02 SNU, while the solar neutrino model prediction was 1.0 ± 0.2 SNU. Turning our attention to the results of the gallium experiments, namely SAGE and GALLEX, they also showed a discrepancy regarding the solar model predictions. Due to their sensitivity to the bulk of the proton-proton chain neutrino flux, they have a larger solar neutrino capture flux rate, with SAGE observing 70.8 ± 5.0 SNU, and GALLEX observing 77.5 ± 8.0 SNU, while the model prediction was 129 ± 9.0 SNU, a difference of about 40%. This discrepancy of experimental results compared with the Standard Solar Model prediction became known as the Solar Neutrino Problem [43].

The way to combat this discrepancy and prove that the cause of the Solar Neutrino Problem was neutrino oscillations was finding a way to detect solar neutrino flux which was not dependent on neutrino flavour. Due to these experiments only detecting solar neutrinos through charged current interactions, they wouldn't be able to detect muon or tau neutrinos. However, with the Sudbury Neutrino Observatory (SNO) experiment this would change, as SNO used heavy water D_2O as its detector medium. Deuteron consists of a proton and a neutron and due to how little energy it takes to break it apart (2.2 MeV), an electron, muon or tau neutrino can very easily break it apart, so that SNO can detect the final state neutron then muon and tau neutrinos would be visible to the detector. The three main channels SNO uses to detect neutrinos is the elastic scattering channel, the charged current channel, and the neutral current channel. Elastic scattering allows SNO to see muon and tau neutrino flux given by $(\phi(\nu_e) + 0.15(\phi(\nu_\mu) + \phi(\nu_\tau)))$. The most important neutrino interaction channel regarding SNO being able to measure the muon and tau neutrino flux is the neutral current (NC) channel (shown in Equation 1.1), as it allows SNO to measure the total flux [44].

$$\nu + d \rightarrow n + p + \nu \quad (1.1)$$

Using these two reaction channels, along with the charged current channel (CC), which can only measure electron neutrino flux, SNO was able to measure the individual neutrino flavour fluxes, shown in Equation 1.2.

$$\begin{aligned}\phi_{CC} &= \phi(\nu_e) = (1.76 \pm 0.01) \times 10^{-8} \text{ cm}^{-2} \text{ s}^{-1} \\ \phi_{ES} &= \phi(\nu_e) + 0.15(\phi(\nu_\mu) + \phi(\nu_\tau)) = (2.39 \pm 0.26) \times 10^{-8} \text{ cm}^{-2} \text{ s}^{-1} \\ \phi_{NC} &= \phi(\nu_e) + \phi(\nu_\mu) + \phi(\nu_\tau) = (5.09 \pm 0.63) \times 10^{-8} \text{ cm}^{-2} \text{ s}^{-1}\end{aligned}\quad (1.2)$$

From Equation 1.2, you can see that the flux of muon and tau neutrinos from the Sun is $\phi(\nu_\mu) + (\nu_\tau) - \phi(\nu_e) = 3.33 \pm 0.62$, which is 3 times that of the value for $\phi(\nu_e)$, and as we know that the Sun only produces ν_e , it means that the neutrinos must be changing flavour to mu and tau neutrinos on their journey to Earth, definitively solving the solar neutrino problem.

1.1.4 Neutrino Oscillation Theory

In 1957, Bruno Pontecorvo postulated that neutrinos could transition from neutrinos to antineutrinos and vice versa (similarly to how two kinds of neutral kaons \bar{K}_0 , and K_0 were found to oscillate) [45]. Neutrino flavour oscillation theory was then developed by Maki, Nakagawa and Sakata in 1962. The PMNS matrix (Pontecorvo-Maki-Nakagawa-Sakata matrix) is the neutrino analogue of the Cabibbo-Kobayashi-Masakawa quark mixing matrix [46], and is shown in Equation 1.3 as $(U_{\alpha i}^*)$ which shows the relationship between the mass and flavour eigenstates for a neutrino with a definite flavour of α and a definite mass of m_i .

$$\begin{aligned}|\nu_\alpha\rangle &= \sum_i \mathbf{U}_{\alpha i}^* |\nu_i\rangle \\ |\nu_i\rangle &= \sum_\alpha \mathbf{U}_{\alpha i} |\nu_\alpha\rangle\end{aligned}\quad (1.3)$$

In Equation 1.3, the terms $U_{\alpha i}^*$ and $U_{\alpha i}$ are the complex conjugate and normal PMNS matrix. Equation 1.4 shows the 3x3 form of the PMNS matrix, where $c_{ij} = \cos\theta_{ij}$ and $s_{ij} = \sin\theta_{ij}$.

$$\begin{aligned}
U &= \begin{pmatrix} 1 & 0 & 0 \\ 0 & c_{23} & s_{23} \\ 0 & -s_{23} & c_{23} \end{pmatrix} \begin{pmatrix} c_{13} & 0 & s_{13}e^{-i\delta_{CP}} \\ 0 & 1 & 0 \\ -s_{13}e^{i\delta_{CP}} & 0 & c_{13} \end{pmatrix} \begin{pmatrix} c_{12} & s_{12} & 0 \\ -s_{12} & c_{12} & 0 \\ 0 & 0 & 1 \end{pmatrix} \quad (1.4) \\
&= \begin{pmatrix} c_{12}c_{13} & s_{12}c_{13} & s_{13}e^{-i\delta_{CP}} \\ -s_{12}c_{23} - c_{12}s_{13}s_{23}e^{i\delta_{CP}} & c_{12}c_{23} - s_{12}s_{13}s_{23}e^{i\delta_{CP}} & c_{13}s_{23} \\ s_{12}s_{23} - c_{12}s_{13}c_{23}e^{i\delta_{CP}} & -c_{12}s_{23} - s_{12}c_{23}s_{13}e^{i\delta_{CP}} & c_{13}c_{23} \end{pmatrix}
\end{aligned}$$

In Equation 1.4, if the $\sin \delta_{CP}$ terms are not equal to 0, it means that there will be imaginary terms in the matrix, which will contribute to CP (charge-parity) violation [47]. The angles θ_{12} , θ_{23} and θ_{13} are mixing angles [48].

Two-flavour neutrino oscillations in vacuum

If a neutrino is produced in the flavour state $|\nu_\alpha\rangle$ in a vacuum, using the PMNS matrix for the relationship between the mass eigenstate and the flavour eigenstate, propagating the neutrino according to the time-dependent Schrodinger equation with no potential would yield a solution to this equation as a plane wave, shown in Equation 1.5.

$$i\frac{\partial}{\partial t} |\nu_i(x, t)\rangle = E |\nu_i(x, t)\rangle = -\frac{1}{2m_i} \frac{\partial^2}{\partial x^2} |\nu_i(x, t)\rangle \quad (1.5)$$

The solution to Equation 1.5 is a plane wave of the form shown in Equation 1.6.

$$|\nu_k(x, t)\rangle = e^{-i(E_k t - p_k x)} |\nu_k(0, 0)\rangle = e^{-i\phi_k} |\nu_k(0, 0)\rangle \quad (1.6)$$

The probability of oscillation to flavour state $|\nu_\beta\rangle$ at time t is given by Equation 1.7.

$$\begin{aligned}
P(\nu_\alpha \rightarrow \nu_\beta) &= |\langle \nu_\beta | \nu_\alpha(t) \rangle|^2 \quad (1.7) \\
&= \sum_{i,j} (U_{\beta i}^*)(U_{\beta i})(U_{\alpha j})(U_{\beta j}^*) e^{-i(E_i - E_j)t}
\end{aligned}$$

For a two-flavour oscillation probability calculation, the matrix which transforms a vector in flavour basis into mass basis is simply a 2x2 rotation matrix (where θ is the mixing angle) so that:

$$\begin{pmatrix} \nu_\alpha \\ \nu_\beta \end{pmatrix} = \begin{pmatrix} \cos \theta & \sin \theta \\ -\sin \theta & \cos \theta \end{pmatrix} \begin{pmatrix} \nu_1 \\ \nu_2 \end{pmatrix}$$

One could calculate the probability of a neutrino of flavour α oscillating into a neutrino of flavour β by using the formula in Equation 1.8. Here L is the distance travelled by the neutrino in kilometres, Δm^2 is the difference between the mass eigenstates, and E is the difference between the energy of the mass eigenstates (where an assumption has been made that the mass eigenstates are the same for both.) The survival probability of a neutrino of flavour α (i.e. the probability of generating ν_α and detecting ν_α is $P(\nu_\alpha \rightarrow \nu_\alpha) = 1 - P(\nu_\alpha \rightarrow \nu_\beta)$) for two flavour oscillations [49].

$$P(\nu_\alpha \rightarrow \nu_\beta) = \sin^2(2\theta) \sin^2 \left(1.27 \Delta m^2 \frac{L}{E_\nu} \right) \quad (1.8)$$

Neutrino oscillation matter effects

The presence of dense matter affects the vacuum neutrino oscillation probability, since neutrinos interact via the weak interaction with matter. This is called the Mikheyev-Smirnov-Wolfenstein (MSW) effect [50]: due to ordinary matter containing only electrons, muons and tauons, the charged current interactions only affect electron neutrinos and creates an additional potential which affects the vacuum oscillation probability for electron neutrinos, shown in Equation 1.9, where G_F is the Fermi coupling constant [51], and n_e is the number density of electrons in the matter, where the positive sign applies to neutrinos, and the negative sign applies to anti-neutrinos.

$$V_{CC} = \pm \sqrt{2} G_F n_e \quad (1.9)$$

Replacing Δm^2 with Δm_M^2 and $\sin^2 \theta$ with $\sin^2 \theta_M$ gives the two flavour oscillation probability modified to take into account the MSW effect (shown in Equation 1.10, where the factor of $A = 2|V_{CC}|E$).

$$\begin{aligned} \sin 2\theta_M &= \frac{\sin 2\theta}{\sqrt{\sin^2 2\theta + (\cos 2\theta - A/\Delta m^2)^2}} \\ \Delta m_M^2 &= \Delta m^2 \sqrt{\sin^2 2\theta + (\cos 2\theta - A/\Delta m^2)^2} \end{aligned} \quad (1.10)$$




Figure 1.3: Feynman diagrams of charged-current (left) and neutral-current (right) neutrino interactions.

1.1.5 Neutrino-nucleus interactions in Super-Kamiokande Gd

Understanding neutrino interaction modes, and understanding neutrino nucleus interaction modes, in particular the neutral current quasielastic reaction is key to understanding this analysis.

There are two main types of neutrino interaction: charged-current (CC) and neutral current (NC). The former occurs when a W^\pm boson is involved in a nuclear exchange, and the latter occurs when a Z^0 is involved (see Figure 1.3).

One such interaction, and often the simplest interaction, is neutrino-electron elastic scattering ($\nu + e^- \rightarrow \nu + e^-$), which occurs when a neutrino scatters off an electron with a virtual vector boson being exchanged. This type of scattering is used in the detection of low energy neutrinos, primarily those from the sun [52]. Figure 1.4 shows the Feynman diagrams for this kind of interaction.

There are multiple types of neutrino-nucleus interactions that occur which can be either charged current or neutral current interactions. These are given in order of momentum transfer (q^2), with the lowest neutrino energies producing quasi-elastic scattering for charged current interactions, and elastic scattering for neutral current interactions, up to deep inelastic scattering where the target nucleus breaks up.

Starting off with the neutrino-nucleus interaction with the lowest q^2 , the Feynman diagrams for NC elastic and CCQE interactions by a muon neutrino interacting with a neutron are shown in Figure 1.5.

The type of interaction that occurs at higher neutrino energies, i.e. with more q^2




Figure 1.4: Feynman diagrams of neutral-current (left) and charged-current (right) neutrino-electron scattering.




Figure 1.5: Feynman diagram for ν_μ and $\bar{\nu}_\mu$ neutral-current elastic scattering (left) and $\bar{\nu}_\mu$ charge-current quasielastic scattering (right).

available is resonance production [53]. Single mesons can also be produced via neutrino-nucleon reactions: these are mostly pions, but some kaons and eta particles can also be produced. Here a neutrino with a high enough energy interacts with and excites a nucleon, producing a resonant baryon which decays to a nucleon and a single pion (shown in Equation 1.11), where N and N' are nucleons.

$$\begin{aligned} \nu_l + N &\rightarrow l + N^* \\ N^* &\rightarrow \pi + N' \end{aligned} \tag{1.11}$$

The resonant baryon produced during the reaction is usually a $\Delta(1232)$ resonance.

Single pion final states can also be produced by a neutrino which scatters off an entire nucleus (X), shown in Equation 1.12 for the charged current reactions and Equation 1.13 for neutral current reactions.

$$\nu_l + X \rightarrow l^- + X + \pi^+, \quad \bar{\nu}_l + X \rightarrow l^+ + X + \pi^- \tag{1.12}$$

$$\nu_l + X \rightarrow \nu_l + X + \pi^0, \quad \bar{\nu}_l + X \rightarrow \bar{\nu}_l + X + \pi^0 \tag{1.13}$$

At higher energies (above 1 GeV), neutrino interactions can also produce kaons in the final state, due to the higher energies being able to produce strange quarks.

At even higher energies and greater q^2 , deep inelastic scattering is able to occur [54]. Deep inelastic scattering is a type of neutrino interaction where the neutrino scatters off a quark inside the proton or neutron involved in the exchange, via a W (CC) or Z (NC) boson (Equation 1.14), shown in Figure 1.6.

$$\begin{aligned} \nu_l + N &\rightarrow l^- + X, \quad \bar{\nu}_l + N \rightarrow l^+ + X(\text{CC}) \\ \nu_l + N &\rightarrow \nu_l + X, \quad \bar{\nu}_l + N \rightarrow \bar{\nu}_l + X(\text{NC}) \end{aligned} \tag{1.14}$$

The next two neutrino-nucleus interactions explained here are of particular relevance to the analysis in this thesis: inverse beta decay (IBD) and quasi-elastic scattering.

Inverse beta decay is the reaction by which Cowan and Reines first detected electron antineutrinos. It is important at low energies: from the minimum energy for the reaction to




Figure 1.6: Feynman diagram for a charged current deep inelastic scattering interaction with an incoming muon neutrino

take place ($E_\nu = 1.806$ MeV) to tens of MeV [55]. Diffuse Supernova Neutrino Background and low energy antineutrinos produced from nuclear reactors can be detected via this process [56]. Figure 1.7 shows the Feynman diagram for this reaction. The neutron produced by this reaction is integral to the motivation behind the gadolinium-doping upgrade to Super-Kamiokande, which will be explained in the next section.

Finally, we get to the type of interaction investigated in this thesis: quasi-elastic scattering. This makes up the majority of the neutrino-nucleus interaction cross-sections at the energy range from 100 MeV to 2 GeV, and therefore vital for the study of neutrinos from long baseline neutrino experiments and also low energy atmospheric neutrinos [57]. Equation 1.15 shows the equations for both the charged current (CCQE) and neutral current (NCQE) version of this interaction where the incoming neutrino scatters off a nucleon, shown in Figure 1.8.





Figure 1.7: Feynman diagram for the inverse beta decay reaction.

$$\begin{aligned}
 \text{CC} : & \nu(k) + n(p) \rightarrow l^-(k') + p(p') \\
 & \bar{\nu}(k) + p(p) \rightarrow l^+(k') + n(p') \\
 \text{NC} : & \nu(k) + N(p) \rightarrow \nu(k') + N(p') \\
 & \bar{\nu}(k) + N(p) \rightarrow \bar{\nu}(k') + N(p')
 \end{aligned} \tag{1.15}$$

As this analysis relates to the various properties of neutrons produced from NCQE interactions in Super-Kamiokande Gd, it is worth looking at the interactions where neutrons are produced inside the detector medium. In Water Cherenkov detectors, the incoming neutrino or anti-neutrino interacts with an ^{16}O nucleus, and at neutrino energies greater than 200 MeV, a nucleon is knocked out, as shown in Equation 1.16.






Figure 1.8: Feynman diagram for a quasi elastic scattering interaction off a nucleon.

This interaction happens in stages, where there is the initial reaction between the incoming neutrino and the specific nucleon inside the ^{16}O nucleus, hadronic final state interactions (FSI) inside the nucleus itself, and subsequent hadronic secondary interactions (SI) inside the detector medium. These are outlined in the schematic shown in Figure 1.9, with the primary interaction, taken as the CCQE reaction ($\bar{\nu}(k) + p(p) \rightarrow l^+(k') + n(p')$). There are stages to neutrino-nucleus reactions, and for the CCQE reaction shown in Figure 1.9, there are three processes: the initial neutrino-nucleon reaction ($\bar{\nu}(k) + p(p) \rightarrow l^+(k') + n(p')$), the final state interaction (FSI) [58] inside the ^{16}O nucleus ($p + p \rightarrow p + n + \pi^+$), and the secondary (SI) interaction [59] in the detector medium ($n + ^{16}\text{O} \rightarrow n + n + ^{15}\text{O}^*$).

1.1.6 Diffuse Supernova Neutrino Background

A key feature of the analysis presented in this thesis is that it is an investigation into the significant background of the signal for DSNB [60]. It is therefore important to state and understand the process behind the production of supernova relic neutrinos in order to get a firm handle on the motivation behind this analysis.

Supernovae Classification

Supernovae occur when a star with a mass around eight times the mass of our sun explodes, and in a galaxy these occur only a few times in a century [61]. Stars with a mass less than eight times the mass of our sun become white dwarfs, made of mostly electron-degenerate




Figure 1.9: Schematic of neutron production following the interaction of neutrino with a nucleon inside an ^{16}O and the resulting FSI and SI interactions in the detector medium.

Supernova Classification	Element lines present in spectra
Type 1a	No hydrogen, silicon
Type 1b	No hydrogen, no silicon, helium
Type 1c	No hydrogen, no silicon, no helium
Type II	Hydrogen

Table 1.1: Supernovae classification along with the element lines present in their spectra [19].

matter. Supernovae are classified into different types: Type 1a, Type 1b, Type 1c and Type II [62]. The classification of supernovae are determined by looking at the spectral lines in the light emitted from these supernovae. Table 1.1 shows how these supernovae are classed and which spectral line elements are associated with each class.

The kinetic energy of a supernova is 10^{44} J, and 99 % of the energy from core-collapse supernovae (CCSN) are released in the form of neutrinos [63]. Unlike Type 1a supernovae which are usually thermonuclear supernovae, Type 1b, Type 1c and Type II are core-collapse supernovae, from which more neutrinos are emitted which is why these types of supernovae are of more interest.

Core-Collapse Supernovae Mechanism

Using the pressure produced by the process of nuclear fusion, a star is able to support itself against gravitational collapse. During the proton-proton chain reaction, hydrogen will fuse to produce helium and once temperatures and pressures are high enough, helium fusion will occur. After all the helium in the core is used up in the fusion process, the star will contract until the pressure and temperatures get even higher, allowing more massive nuclei to fuse. This reaction will carry on until iron nuclei are produced, this being the element with the highest binding energy, causing the fusion to stop [64].

As more and more iron accumulates in the core of the star, the density and temperature of the core will increase, and these higher energy electrons will increase the rate of electron capture on protons that will occur in the iron nuclei [65]. This will cause a reduction in the electron degeneracy pressure, which is further enhanced by the breakdown of the iron nuclei which occurs at higher temperatures when gamma rays interact with them. The degeneracy pressure is no longer greater than the gravitational forces acting inwards, and gravitational core collapse occurs [66].

The point at which in the core the neutrino mean free paths become approximately the




Figure 1.10: Schematic showing core collapse of a star, and the resultant shockwave and neutrino production.

same size as the proto-neutron star is called the “neutrinosphere” [67]. Figure 1.10 shows the formation of a proto-neutron star (PNS) and the neutrino flux and neutrinosphere produced by the core-collapse mechanism.

The radius of the neutrinosphere becomes as large as that of the inner core of the star, when the inner core of the star reaches a density of $10^{11} \text{ g cm}^{-3}$, and the electron neutrinos produced from electron capture become unable to escape. Gravitational collapse of the star continues until the inner core reaches nuclear density, at which point a shock wave is produced due to the repulsive force between nuclei [68].

When this shock wave reaches the neutrinosphere, neutrino emission begins, which lasts less than 10 milliseconds. After this shockwave passes, nucleons and electrons fall back onto the proto-neutron star which heats it up. This causes neutrinos of all flavours to be produced via pair production and electron capture. This is called the “accretion phase” [69]. Due to this expulsion of neutrinos the shock wave loses energy, but it is re-

vived through matter behind the shock wave being heated by neutrino absorption from the proto-neutron star region [70]. The mechanism for this shown in Figure 1.11, where the shockwave produced depends on antineutrinos being absorbed by the dense post-shock gas.

After the shock wave is revived, if it has enough energy to blow off the outer layer of matter a supernova occurs. Then, depending on the mass of the PNS, it cools to either become a neutron star or a black hole [71]. If the shock wave energy is not high enough to blow off the outer layer of matter, the accretion phase continues until a black hole is formed.

The energy of the emitted neutrinos depend on their flavour - neutrinos emitted from a deeper layer inside the supernova will be higher in temperature and therefore have a higher energy. For electron neutrinos and electron anti-neutrinos, the dominant interactions are charged current interactions with nucleons. Due to the number of neutrons in a proto-neutron star greatly outnumbering the number of protons, the interaction involving ν_e will be far more efficient than those involving $\nu_{\bar{e}}$, meaning the neutrinosphere for $\nu_{\bar{e}}$ is smaller than for ν_e , so they are emitted from the PNS with greater energies.

Due to there being no charged current interactions involving muon neutrinos in the medium, they are involved instead in neutral current reactions, including Bremsstrahlung, neutrino-pair annihilation, and electron-positron pair annihilation [72]. Due to only undergoing these reactions their neutrinosphere is even smaller than that of their electron neutrino and electron anti-neutrino counterparts, therefore being emitted with even higher energies [73]. Figure 1.12 shows the luminosity (top panels) and average energy (bottom panels) for three different neutrino flavours as a function of time for the neutronisation phase (left), accretion phase (centre) and cooling phase (right). Taken from [2].

Kamiokande-II observed neutrinos produced from a supernova, later named 1987A, in the Large Magellenic Cloud. These neutrinos were also observed by the Baskan Neutrino Observatory and the Irvine-Michigan-Brookhaven detector (IMB) [74]. The neutrinos detected from 1987A were detected via the inverse beta decay (IBD) interaction (shown in Figure 1.7), as opposed to the electron elastic scattering, CC interaction with ^{16}O or NC interaction with ^{16}O channels. The positron from this reaction is what is searched for, and these positrons are produced isotropically within the detector. A neutrino burst search from SN1987A was carried out on the data run which ran continuously between 16:09 21 February 1987 to 07:31 24th February 1987 JST [75].

The event selection criteria for a supernova neutrino event were as follows: firstly, the




Figure 1.11: Schematic showing core collapse of a star, and the resultant shockwave and neutrino production.




Figure 1.12: Luminosity (top panels) and average energy (bottom panels) for three different neutrino flavours as a function of time for the neutronisation phase (left), accretion phase (centre) and cooling phase (right). Taken from [2].

total number of photoelectrons per event should be less than 170, as this corresponds to an electron with an energy of 50 MeV, and the neutrinos released from a supernovae have a typical energy of the order of 10 MeV. Secondly, the total number of electrons in the outer detector per event needed to be less than 30, in order for the event to be considered fully contained, and finally, the time between previous events has to be greater than 20 μ sec, in order to avoid Michel electrons. Figure 1.13 shows the time-sequence of all low-energy events. If the neutrinos were to show up in Kamiokande-II, they would arrive in a cluster lasting of order 10s, so intervals of 10 seconds were used to search for clusters of events. In order to classify the event as a supernova neutrino candidate, the event had to be registered by atleast 30 PMTs, and 6 events were found in the first 10s interval which satisfied this, and 2 events in the next 10s interval. A second search was performed on a larger data sample of 42.9 days, from 9th of January to 25th of February 1987, and no other supernova neutrino burst candidates were found. The first two events shown in Figure 1.13 also correlate in angle to the direction of 1987A. As a result, this was considered detection of a genuine supernova neutrino burst, and was the first direct observation of this in neutrino astronomy.

Due to neutrinos carrying away 99% of the energy produced by supernovae, they are the most important signal a supernova can produce, and can be used for finding out when the supernova explosion actually happened - due to neutrinos leaving the supernovae immediately while gamma rays from the the explosion can only leave the supernova when the shock wave reaches the surface of the star [76].

The supernova relic neutrinos emitted from all past CCSN are accumulated and form an everpresent background due to the fact that neutrinos only weakly interact with matter. The total flux of this neutrino background has been theoretically predicted and is called the “diffuse supernova neutrino background” (DSNB). When calculating the total DSNB flux, the redshift caused by the expansion of the universe needs to be taken into account.

Equation 1.17 gives the differential of the DSNB flux with respect to the DSNB energy at Earth [77].

$$dn_\nu(E_\nu) = R_{\text{SN}}(z) \frac{dt}{dz} dz \frac{dN_\nu(E'_\nu)}{dE'_\nu} (1+z)dE_\nu \quad (1.17)$$

Here $E'_\nu = (1+z)E_\nu$ is the energy of neutrinos at a certain redshift z , $R_{\text{SN}}(z)$ is the supernova rate at a comoving volume at z , dN_ν/dE_ν is the number spectrum of neutrinos emitted by one supernova explosion, and $(1+z)^{-3}$ is the expansion of the universe factor.




Figure 1.13: Events detected centered on 16:35:35 JST, where the solid lines are the number of hit PMTs and dashed lines are muon events. The zoomed in plot in the top-right shows an expanded version of the 0.0 - 2.0 second time scale.

The relationship between redshift and time (dt/dz), is given by the Friedmann equation (Equation 1.18), where H_0 is the Hubble constant, Ω_m is the matter density and Ω_Λ is the cosmological constant [78].

$$\frac{dz}{dt} = -H_0(1+z)\sqrt{\Omega_m(1+z)^3 + \Omega_\Lambda} \quad (1.18)$$

It is worth reviewing the lastest searches from Super-Kamiokande for DSNB neutrinos, and the limit on the flux prediction from different Super-Kamiokande phases. While Figure 1.14 shows that the majority of DSNB neutrinos have an energy below 10 MeV, due to massive backgrounds these DSNB are hard to detect, so Super-Kamiokande therefore searches for the DSNB signal in the order of 10 MeV. As mentioned previously the main detection channel is inverse-beta decay, with the prompt signal being the emitted positron and the delayed signal being the photon emission from neutron capture. Up to and including now, there has been no DSNB signal evidence but upper-limits on the flux have been set from both KamLAND and from Super-Kamiokande phases I-IV, shown in Figure 1.15.

Regarding important backgrounds to the DSNB signal, below neutrino energies of 15 MeV NCQE interactions from atmospheric neutrinos form the main background to DSNB searches. The importance of this background motivates the analysis in this thesis: by measuring the NCQE interaction using T2K beam neutrinos [79], the large uncertainty of this interaction in the low energy region can be reduced due to the reason that the atmospheric neutrino energy region is similar to that of the T2K beam energy region. The differential cross section of the neutral-current elastic interaction of a neutrino on a free proton or neutron can be written as shown in Equation 1.19.

$$\frac{d\sigma^{\nu(\bar{\nu})}}{dq^2} = \frac{M^2 G_F^2}{8\pi E_\nu^2} \left\{ A(q^2) \pm B(q^2) \frac{s-u}{M^2} + C(q^2) \frac{(s-u)^2}{M^4} \right\} \quad (1.19)$$

where E_ν is the initial neutrino or antineutrino energy, M is the mass of the nucleon, G_F is the Fermi coupling constant [51], s and u are the Mandelstam variables, and q is the transfer of four momentum between incoming (anti)neutrinos and outgoing (anti)neutrinos. Depending on whether it is an incoming neutrino or antineutrino, there is either a plus or a minus between the A and B terms. A,B and C are terms which are made up of form factors specific to neutral current interactions.




Figure 1.14: DSNB flux against neutrino energy for various theoretical models, “NH” and “IH” are the normal and inverted mass hierarchies respectively.




Figure 1.15: The 90% C.L. for observed and expected upper limits on the electron antineutrino flux from SK-I - SK-IV and KamLAND, with the theoretical predictions in Figure 1.14 shown in grey.




Figure 1.16: Schematic showing the IBD and NCQE interaction mechanisms.

1.1.7 Physics motivation behind the Super-Kamiokande Gadolinium Upgrade

Due to the large cross section of the IBD interaction, IBD events constitute about 88% of the total number of events in the detector [3]. With efficient neutron tagging in Super-Kamiokande, the backgrounds (charged current interactions and muon spallation) in the search for DSNB flux neutrinos would be largely reduced. The neutral current quasielastic (NCQE) background would still remain due to the way the gamma rays arising from neutron capture mimic the signal of the inverse beta decay (IBD) reactions: a schematic of both NCQE and IBD reactions are shown in Figure 1.16. The measurement of the NCQE interactions using T2K beam flux can aid in understanding this background more due to the T2K flux peak being near the atmospheric neutrino flux peak (about 600 MeV).

Efficient neutron tagging aids information about neutrino energy and neutrino interaction type, and when it comes to studying atmospheric neutrino oscillations, accurate neutrino energy reconstruction is particularly important. Figure 1.17 shows the fraction of non-visible energy as a function of the number of tagged neutrons from simulations of atmospheric neutrino interactions at Super-Kamiokande. Here E_ν is the energy of the atmospheric neutrino and E_{vis} is the energy that is reconstructed from charged particles. Due to these neutrinos interacting with nuclei in the detector, more neutrons are produced, and with efficient neutron tagging on gadolinium the neutrino energy can be




Figure 1.17: MC study of (a) neutron multiplicity production for ν and $\bar{\nu}$, (b) neutral current, charged current and deep and non-deep inelastic scattering, (c) the correction to the visible energy as a function of neutrino multiplicity. Taken from [3].

properly reconstructed.

The ideal goal of this analysis is to complement prior analyses which investigate the NCQE cross-section and analyses which produce neutron multiplicity distributions for NCQE interactions. The emphasis on the distributions of neutrons in this thesis and the methods of neutron tagging used are of increasing interest due to the fact that the main purpose behind adding gadolinium to the detector is to make these neutron captures more visible. Furthermore, in Chapter 8, an estimate of the DSNB NCQE background is made, with an uncertainty stemming from the value of the neutron tagging efficiency and systematic uncertainty on this efficiency calculated in Chapter 6 and Chapter 7 of this thesis.

Chapter 2

The Tokai-to-Kamioka experiment

(sarcastically) “Nice experiment,
guys.”

Arnold Rimmer, Red Dwarf: S5E5
Demons and Angels (1992)

2.1 The Tokai-to-Kamioka experiment

The Tokai-to-Kamioka (T2K) experiment [80] is a long baseline neutrino oscillation experiment based in Japan and its purpose is to study neutrino oscillations: specifically a precision measurement of the neutrino oscillation parameters Δm_{23}^2 and $\sin^2 \theta_{23}$ and to improve the measurement of the leptonic CP violating phase δ_{CP} , which is mentioned in Chapter 1. The experiment produces a beam of intense muon neutrinos at J-PARC (Japan Proton Accelerator Research Complex [81]) in Tokai, which is located on the east coast of Japan in Ibaraki Prefecture. The muon neutrino beam travels 295 km west towards the far detector Super-Kamiokande (see Chapter 3.) The neutrino beam is measured by other detectors such as ND280 [82] and INGRID [83] prior to reaching Super-Kamiokande which is important with regards to measuring the neutrino oscillation parameters. Both ND280 and Super-Kamiokande are off-axis detectors, meaning that they are located 2.5° off axis from the centre of the neutrino beam. This results in the peak of the energy of the muon neutrinos to be 0.6 GeV, maximising the neutrino oscillation on the 295 km baseline. This chapter explains production of the muon neutrino beam from the J-PARC proton beam line and the near detector complex.

2.1.1 Neutrino beam production


J-PARC proton beam production

A sequence of three accelerators results in the production of a proton beam from the J-PARC accelerator complex, these are the LINAC (linear accelerator), the RCS (rapid cyclic synchrotron) and the main ring synchrotron (MR) [84], [85]. A negative hydrogen ion is accelerated to a kinetic energy of 400 MeV by a linear accelerator (LINAC), from which a beam of protons is created by converting the negative hydrogen ion beam using charge-stripping foils. This proton beam is then accelerated to a kinetic energy of 3 GeV by the RCS, and about 5% of the bunches produced from this process are passed to the MR where the proton beam will be accelerated up to 30 GeV [86]. The rest of the proton bunches are passed to the neutron and muon beamline in the Material and Life Science Facility [87].

Neutrino beam production

The neutrino beam is produced using the primary and secondary beamline as shown in Figure 2.2. The primary beamline takes the proton beam from the MR and directs it towards Kamioka. The beam is then transferred through a succession of beam monitors which measure facets of the proton beam including the beam profile, intensity and position. The beam monitor which is closest to the graphite target measures the “Protons-On-Target” (POT), a value used to determine the neutrino beam flux. The secondary beamline takes the proton bunches and passes them through a target station, the decay volume and the beam dump [88]. After interacting with the target station, the proton bunches are collimated through a 1.7 m graphite rod where the collimated hole the proton bunches pass through are 30 mm in diameter. Beam profile reconstruction occurs in the OTR (Optical Transition Radiation) monitor, made up of titanium alloy foil placed at a 45 degree angle in order to intercept the beam. As the proton beam enters the foil, the visible light that is produced escapes through a collection of mirrors and is then captured by a charge injection device camera, which creates the beam profile [89].

After beam profiling, the proton beam then impacts upon a graphite rod target which is 91.4 cm long and 2.6 cm in diameter - this collision produces secondary hadrons, including pions which are focused by three magnetic horns (shown in Figures 2.1a, 2.1b and 2.1c). These magnetic horns can be used to produce either a muon neutrino or muon antineutrino beam depending on the polarity of the 250kA current they are pulsed with. If a +250 kA



(a) T2K Horn 1

(b) T2K Horn 2



(c) T2K Horn 3

current is used, the positive pions and kaons produced can go on to make muon neutrino beams whereas if a -250 kA current is used negative pions and kaons can decay to create muon antineutrino beams (both are shown in Equation 2.1). The +250 kA mode is called Forward Horn Current (FHC) mode and the -250 kA mode is called Reversed Horn Current (RHC) mode [90]. The analysis in this thesis will occur in FHC mode only.

$$\begin{aligned} \pi^+ &\rightarrow \mu^+ + \nu_\mu & \text{FHC} \\ \pi^- &\rightarrow \mu^- + \bar{\nu}_\mu & \text{RHC} \end{aligned} \quad (2.1)$$

A 75 ton volume beam dump made of graphite and iron stops the particles, specifically




Figure 2.2: Schematic of the neutrino beam line

the protons, secondary hadrons and mesons which have a momentum below $5 \text{ GeV}/c$, and therefore end up being absorbed by the beam dump. A muon monitor is placed after the beam dump in order to directly measure the the beam intensity and beam direction [91]. Muons can be used to monitor the beam properties because along with the neutrinos these are the main particles produced from pion decay. After the muon monitor, a nucleon emulsion plate detector measures the flux and momentum of the muons.

2.1.2 Near detectors

INGRID detector

The INGRID (Interactive Neutrino GRID) detector is a neutrino detector which unlike ND280 is placed on-axis instead of off-axis. This allows it to directly monitor the direction and the intensity of the neutrino beam by measuring the interactions of the neutrinos with the alternating iron plates that make it up [92]. INGRID is also placed 280 m from the graphite target and consists of 14 modules placed in a cross formation, with the centre of the cross placed at the centre of the neutrino beam. The INGRID modules are comprised of nine iron plates alternating with 11 tracking scintillator planes, which are themselves surrounded by scintillator plates the purpose of which is to reject interactions that occur outside the module. A schematic of the INGRID cross is shown in 2.3 and a schematic of




Figure 2.3: Schematic of the INGRID cross taken from [4].

the modules is shown in 2.4.

An additional module, called the proton module, was added to more precisely measure the neutrino interaction cross-section with the T2K on-axis neutrino beam. This module is used to distinguish the quasi-elastic interaction channel in order to compare it with Monte Carlo simulations of the beamline and neutrino interactions. The Proton Module is made of scintillator planes (no alternating iron plates) and is contained by veto planes. The Proton Module was placed in the centre of the INGRID cross at the intersection of the vertical and horizontal modules [93]. Figure 2.5 shows what a standard neutrino event looks like on the INGRID module. A neutrino enters from the left and after interacting with the scintillator cells (shown in green) produces hits (shown in red), with the relative size of each circle corresponding to the observed signal in that cell. The blue cells show the position of the veto scintillators, while the gray planes show the iron plates.



Figure 2.4: Individual INGRID module schematic taken from [4].




Figure 2.5: INGRID event display showing a typical INGRID event, taken from [5].




Figure 2.6: Neutrino beam profiles for x (left) and y (right) directions.

By reconstructing the profile of the beam in x and y directions using the number of neutrino events in seven horizontal and vertical INGRID modules, and fitting the profiles with a Gaussian, the centre of the beam can be defined as the peak of the Gaussian fit. The beam direction can then be reconstructed as the direction from the proton beam target to the reconstructed beam centre. Figure 2.6 shows these neutrino beam centres from the centre of INGRID, for both the x and y directions, measured in April 2010 [94].

ND280

ND280 is a near detector which sits 280 m from the target. It is an off-axis detector, meaning that just like Super-Kamiokande, it is placed 2.5° off-axis from the center of the beam. This stems from the relationship between the energy of the neutrinos produced from the decay of the pions, a relationship shown in Equation 2.2.

$$E_\nu = \frac{m_\pi^2 - m_\mu^2}{2(E_\pi - \sqrt{E_\pi^2 - m_\pi^2} \cos \theta)} \quad (2.2)$$

where E_π is the energy of the parent pion and θ is the scattering angle between the direction of the outgoing neutrino and the direction of the parent pion's momentum, m_π is the parent pion mass and m_μ is the mass of the outgoing muon. Figure 2.7 shows the neutrino energy from pion decay plotted against the energy of the parent pion for a range of off-axis angles.

As the off-axis angle increases, the intensity of the neutrino beam decreases, and therefore picking an off-axis angle of 2.5° at which to place the ND280 detector complex strikes




Figure 2.7: Energy of the neutrino plotted against the energy of the parent pion for multiple different off-axis angles, taken from [4].

a good balance between keeping a high beam intensity while ensuring a peak energy of 0.6 GeV in order to have the neutrino oscillation be maximised at 295km. The relationship between muon neutrino oscillation probability and muon neutrino energy is shown at the top in Figure 2.8, and at the bottom the muon neutrino flux 295 km away from the graphite target can be seen for three different off-axis angles.

Figure 2.9 shows a schematic of the ND280 detector complex. It has five main goals: firstly, to measure the cross sections of muon neutrino interactions, so neutrino-nucleus interaction models can reduce their systematic uncertainties [95]. Secondly, measuring the component of the neutrino beam which is made of electron neutrinos, hence being able to better constrain the background to electron neutrino appearance at the far detector. Thirdly, to predict the event rate at Super-Kamiokande by measuring the energy spectrum of the muon neutrinos produced. It also aims to study non quasi-elastic processes which produce pions below the Super Kamiokande Cherenkov threshold, and to measure the neutral current (NC) pion-nought production rates.

ND280 is made of a neutral pion detector (P0D), three Time Projection Chambers (TPCs) and two Fine Grained Detectors (FGDs). These are enclosed within Electromagnetic Calorimeters (ECals) and a Side Muon Range Detector (SMRD). These detectors




Figure 2.8: The probability of survival of muon neutrinos (top plot) and neutrino beam flux at the 295km far detector (bottom) Taken from [4].




Figure 2.9: Near detector ND280 schematic taken from [5].

are magnetised using a magnet originally used in the UA1 detector at CERN.

The neutral pion detector is important due to its ability to detect a process that can imitate the signal event of electron neutrino appearance at Super-Kamiokande. Neutral pions are produced during the neutral current interactions on water ($\nu_\mu + N \rightarrow \nu_\mu + N' + \pi^0 + X$) and the purpose of *P0D* is to measure the cross-section of this interaction.

There are also two electromagnetic calorimeters which remove events entering the detector from the outside. The SMRD (Side Muon Range Detector) is used as a way to measure the momenta of muons which escape the detector complex at a large angle relative to the direction of the beam.

There are three time projection chambers placed downstream of the neutral pion detector. These are used for reconstruction of charged particle tracks, particle identification and determination of the momentum of the particle [96]. There are two fine grained detectors (FGDs) in ND280, which have two purposes. Firstly to yield a mass for the neutrino interaction, and secondly, to track the charged particles issuing from the neutrino interaction vertex [97]. Because the far detector, Super-Kamiokande, is a Water Cherenkov detector, the tracker in the ND280 detector needs to measure the neutrino interaction rates with water. This is done by including six water target modules in the second FGD in order to determine neutrino interaction cross-sections with water.

The ECal is an electromagnetic calorimeter which surrounds the P0D, the TPCs and the FGDs [98]. It consists of plastic scintillator layers sandwiched between lead absorber sheets. Its purpose is to aid in the full event reconstruction through detecting photons and measuring their energy and direction, along with detecting charged particles and getting information which helps in their identification (separating out electrons, muons and pions.)

Chapter 3

The Super Kamiokande Detector

“Would you mind telling me how we plan to convert this tank?”

Dr Leonard H. “Bones” McCoy, Star Trek IV: The Voyage Home (1986)

3.1 The Super-Kamiokande detector

3.1.1 Background and detector design

Super-Kamiokande is a neutrino observatory consisting of a cylindrical tank 41.4 m in height and 39.3 m in diameter, and filled with 50 kton of ultrapure water and currently with 0.078% gadolinium sulphate octahydrate (0.03% gadolinium). It is used as a neutrino detector for atmospheric, solar and astrophysical neutrinos, as well as being a far detector of the T2K neutrino beam. It is based in the Mozumi mine, located in Gifu Prefecture, Japan. Due to its location being underneath Mount Ikenoyama, 1000m underground, it is shielded from the cosmic ray muon detector background. Super-Kamiokande is divided into two concentric cylinder volumes, consisting of the inner detector (ID) and outer detector (OD) using a stainless steel structure which supports the photomultiplier tubes. Tyvek and black polyethylene terephthalate sheets are mounted on this structure in order to optically separate the inner and outer detector [99].

The inner detector is a cylinder which has a diameter of 33.8 m and a height of 36.2m, and has a fiducial volume of 22.5 ktons of water. The fiducial volume is defined as the region

inside a surface drawn 2.00 m from the inner detector wall. Using this fiducial volume gives protection against events produced from natural radioactivity in the surrounding rock. The detector contains 11,129 photomultiplier tubes which give 40% photocoverage of its inner surface, with the specific photomultiplier model chosen being the hemispherical, 50.8 cm diameter Hamamatsu R3600 model. The 2 m wide outer detector has only 1885 photomultiplier tubes which are mounted on the outside of stainless steel structure, each with a smaller diameter of 20 cm, and are either the R1408 or R5912 Hamamatsu model. Each outer detector photomultiplier tube is attached to a 50 cm x 50 cm wavelength shifting plate, improving the light collection ability in the OD [6].

A detailed schematic of the photomultiplier tubes used in Super-Kamiokande can be seen in Figure 3.2. The photocathodes used in these PMTs are comprised of bialkali antimony-potassium-caesium material (Sb-K-Cs), which give a greater sensitivity to longer wavelengths, giving the greatest spectral response at 360 nm, near the ultraviolet range [100]. This makes these types of photocathodes suitable to use for matching with light sources in the blue region of the visible spectrum, which is the region in which the wavelength of Cherenkov photons lie. The 11 dynodes which are inside the photomultiplier tube are arranged in a “venetian blind” fashion, meaning that the dynodes consist of an assembly of parallel strips [101]. This results in a good collection efficiency of the multiplied electrons and gives decent protection from external magnetic fields. More protection from external magnetic fields is provided by a set of Helmholtz coils which are aligned outside the inner detector, which reduce the ambient background geomagnetic field from 450 mG to 50 mG. This is needed due to the systematic bias that could occur due to the strength and uniform direction of this magnetic field affecting the photo-electron trajectories and consequently the photomultiplier tube hit timing [102].

Radioactivity from radon, uranium and thorium radioisotopes in the Super-Kamiokande tank water and radon in the surrounding air could provide a low energy background to measurements which should be negated. Microbes present in the mine water also present a problem as they cause a reduction in the light attenuation length [103]. Therefore the water used in Super-Kamiokande has to undergo a purification process - the water used is continuously reprocessed at a rate of 30 tons h^{-1} in a closed loop system, which is the same method used to purify the water when refilling the tank. The first step of this water purification process is to use a 1 μm mesh filter to remove large particulates of impurities from the water [104]. A heat exchanger is then used to cool down the water to a constant 13.0 °C to reduce the dark noise hits of the photomultiplier tubes and the growth of the




Figure 3.1: Schematic of an ID 50 cm Super-Kamiokande PMT [6].

microbes. A treatment with ultraviolet light is then used to kill any remaining microbes in the water. Radon-free air is then dissolved into the water to aid in the later process of radon removal from the water and a high performance membrane ultra filter (UF) is used to remove organic compounds about 10 nm in diameter from the water. After this step a membrane degasifier removes the dissolved radon, where 30 L of radon reduced air is supplied to the membrane degasifier. The dissolved radon will transfer across the membrane but the water will not, allowing for efficient radon reduction. Figure ?? shows a schematic of the water purification system.

The inner detector tank water is circulated by injecting the water at the bottom of the tank and extracting it from the top, where the convection currents are able to maintain the temperature in the region within 11 m to the bottom of tank, however, outside this region the present temperature gradient causes an asymmetry in the attenuation of light, which is discussed more in Chapter 4.

An air purification system is also installed in Super-Kamiokande in order to reduce the amount of radon present which could dissolve into the tank and affect measurements. The level of radon activity achieved after this air purification has taken place is $1 \text{ mBq}/\text{m}^3$.




Figure 3.2: Water purification system at SK.

The Super-Kamiokande experiment began taking data on 1st April 1996, and due to maintenance was shut down in July 2001, which was Phase I of the experiment. A table of the Super-Kamiokande phases is shown in Table 3.1. During the refilling of the tank after maintenance, there was cascade of PMT implosions that occurred on the 12th of November 2001, which were triggered by the implosion of a single photomultiplier tube. This implosion destroyed about 7,000 of the PMTs and in order to avoid such chain reactions in the future, from 2002 onwards all of the inner detector PMTs are fitted with acrylic covers and fiber-glass reinforced plastic (FRP) cases. Detector shutdown and rebuild took nine months and Super-Kamiokande resumed data taking with the full number of photomultiplier tubes in July 2006 which marked the beginning of Super-Kamiokande Phase III. Super-Kamiokande Phase IV began in September 2008 where a new data acquisition system and charge to time (QTC) based electronics with Ethernet (QBEE) was deployed in order to measure arrival times and integrated charge for inner detector and outer detector photomultiplier tube signals. This replaced the ATM (Analogue and Timing Module). The improvements in electronics and calibration methods meant that when Super-Kamiokande Phase IV started running in

September of 2008, electrons with energies as low as 3.5 MeV were able to be detected [105].

Phase	Period	Total PMT no.		FRP case?	Readout	Gd%
		ID (Coverage)	OD			
SK-I	Apr. 1996 - Jul. 2001	11146(40 %)	1884	no	ATM	0
SK-II	Oct. 2002 - Oct. 2005	5182(19 %)	1884	yes	ATM	0
SK-III	Jul. 2006 - Sep. 2008	11129(40 %)	1884	yes	ATM	0
SK-IV	Sep. 2008 - May 2018	11129(40 %)	1884	yes	QBEE	0
SK-V	Jan. 2019 - Jul. 2020	11129(40 %)	1884	yes	QBEE	0
SK-VI	Aug. 2020 - May 2022	11129(40 %)	1884	yes	QBEE	0.01%
SK-VII	Jun. 2022 - Today	11129(40 %)	1884	yes	QBEE	0.03%

Table 3.1: Phases of Super-Kamiokande and main properties of each phase

3.1.2 Data aquisition system

As shown in Table 3.1, Phase IV of the experiment marked the beginning of Super-Kamiokande using QTC-based Electronics with Ethernet (QBEEs). Each QBEE board used in Super-Kamiokande contains a 24 photomultiplier tube input channel, where each channel uses a charge-to-time (QTC) converter and a time-to-digital converter placed in series as shown in Figure 3.3. After a single photoelectron is produced by the photomultiplier tubes after incident photons have been received upon it, the dynodes inside the photomultiplier tube amplify this photoelectron so that each photoelectron that strikes the surface of the dynode produces several more photoelectrons, which are produced from the dynodes as an analogue signal. This signal then enters a charge-to-time converter (QTC), an application specific integrated circuit (ASIC) which was specifically designed for Super-Kamiokande in order to detect photomultiplier tube signals using built-in discriminators and to produce output timing signals whose widths represent the integrated charge of the PMT signal [106]. The QTC used has three input channels per chip, which has three gain ranges (Small, Medium, Large as shown in Figure 3.3). There is a built in discriminator inside the QTC which determines whether the signal from a PMT is a “hit”. If the PMT signal exceeds the threshold value of this discriminator, the QTC integrates the charge of the signal over the next 400 ns, and a square wave pulse is generated whose pulse width is proportional to the integrated charge of the input signal from the PMT. The next 400 ns are used to discharge the integrated charge from the QTC, leading to a total channel dead




Figure 3.3: Schematic of the charge-to-time converter circuit [7].

time of 900 ns due to summing the charge integration and discharge of the QTC.

A time-to-digital converter (TDC) then digitises the output time signal, so the PMT charge information is retained [7]. These digitised outputs are collated by 20 front-end computers which collect all the information from the inner and outer detectors, with each computer taking the PMT hit information from 30 inner detector and 20 outer detector QBEE boards and sorting the PMT hit time information in order of the raw hit time. This information is then sent to “merger” computers, which produce a full time-ordered list of all PMT hits. These merger computers then apply software triggers to select event candidates, using N_{200} , a quantity which determines the number of PMT hits in a 200 ns timing window. When the value of N_{200} surpasses the threshold value of a certain trigger type (whether it is a SLE (Super Low Energy), LE (Low Energy), HE (High Energy), SHE (Super High Energy), OD (Outer Detector) or AFT (After Window) trigger), the trigger is used to select an event candidate. The SLE, LE, HE and SHE triggers roughly define the energy of a certain event, based on the number of hits detected. The OD trigger is used to veto events, and the AFT trigger is of special importance to the analysis in this thesis: it is used to discern when a neutron is produced after a neutrino interaction. The AFT trigger is issued to take 500 μ sec of data after the SHE trigger in order to identify the positron from the prompt event and the delayed 2.2 MeV gamma released from the

neutron capture on the proton during the IBD reaction. Another set of computers acts as an “organiser”: it takes all the information regarding the event candidates from the “merger” computers and writes them onto disks [6].

3.2 Event Reconstruction

3.2.1 Vertex Reconstruction

For low energy events (events up to 100 MeV), Super-Kamiokande currently uses BONSAI (Branch Optimisation Navigating Successive Annealing Interactions) for event reconstruction. Vertex reconstruction for Super-Kamiokande has undergone changes and improvements depending on the phase of the experiment.

For Phase I of Super-Kamiokande, vertex reconstruction depended on a lattice of test vertices with 4 m spacing throughout the detector, with a specific measure of goodness for each test vertex: the test vertex with the highest measure of goodness would have around it a more finely spaced grid, and the process would be repeated. For Phase II of Super-Kamiokande due to the reduced number of PMTs, this approach was no longer as successful as it was in Phase I and as a result the reconstruction performance declined, and BONSAI was created as a replacement. Instead of using a fixed grid which was the case with SK-I and SK-II, BONSAI creates test vertices by selecting groups of four PMT hits and seeing where the timing residuals of the PMT hits would be most reduced [107]. After these test vertices have been identified, a maximum likelihood fit over all the PMT hits in the event is performed, shown in Equation 3.1.

$$\mathcal{L}(\vec{x}, t_0) = \sum_{i=1}^{N_{\text{hit}}} \log(P(t - t_{\text{tof}} - t_0)) \quad (3.1)$$

where (\vec{x}, t_0) is the test vertex, and $(P(t - t_{\text{tof}} - t_0))$ (shown in Figure 3.4) is the probability density function of the timing residual, which for each PMT hit is defined as $(t - t_{\text{tof}} - t_0)$, where t_0 is the time of the interaction, t_{tof} is the time of flight from the interaction vertex position to the position of the hit PMT, t is the PMT hit time. The 1σ difference between the true vertex position and the reconstructed vertex position plotted as a function of true electron energy is shown in Figure 3.5.




Figure 3.4: Probability density of the timing residual $P(t - t_{\text{tof}} - t_0)$, where t_0 is used for the vertex reconstruction maximum likelihood fit. The peaks at 30ns and 100ns are caused by PMT after-pulsing.




Figure 3.5: The vertex resolution (the point at which 68% of the events in the distance distribution between the actual and reconstructed vertex are contained) for the different SK phases. SK-I (Blue), SK-III (Red), SK-IV (Black).

3.2.2 Direction Reconstruction

Cherenkov light is emitted in a conical formation as electrons and positrons travel through water, with a Cherenkov angle of $\approx 42^\circ$. BONSAI can reconstruct the direction of these particles by using this information along with the reconstructed vertex. This reconstruction occurs using a maximum likelihood function defined in Equation 3.2.

$$\mathcal{L}(\vec{d}) = \sum_i^{N_{20}} \log(f(\cos \theta_i, E)) \times \frac{\cos \theta_i}{a(\theta_i)} \quad (3.2)$$

The term $f(\cos \theta_i, E)$ in Equation 3.2 is the expected distribution of the angle between the vector of the direction \vec{d} of the particle, and the observed Cherenkov photon from the position of the reconstructed vertex. The reason there is a spread in this energy distribution is because while the highest value of this distribution occurs at the cosine of the opening Cherenkov angle of 42° , due to the particle travelling through the water being Coulomb scattered multiple times, there is a variation in the angle because of the varying particle energy. The term N_{20} is the number of hits whose residual hit time is within 20 ns of the time of the reconstructed event, which is used in order to reduce the amount dark noise and scattered photons contribute to the direction reconstruction calculation [108]. The variable $a(\theta_i)$ is a correction factor stemming from the acceptance of PMTs and therefore linked to the shape of the PMT and its acrylic case as well as the angle of incidence of the photon on the PMT.

3.2.3 Energy reconstruction

The kinetic energy of a particle is proportional to the amount of Cherenkov photons emitted from it, and if we assume that the Cherenkov photons in a single event come from a single electron, we can reconstruct the total energy of the electron. Instead of using the number of photoelectrons of all hit photomultiplier tubes to reconstruct the energy of low energy events, the number of hit photomultiplier tubes is used instead. The reasons for this are threefold - firstly, low energy events emit a small number of Cherenkov photons, and therefore average about one photon per hit PMT. Secondly, at single photoelectron level, the resolution of the PMTs is poor, and third, the number of photoelectrons produced is related to the gain of the PMT.

To reduce dark noise, energy reconstruction uses N_{50} , which is the number of time of flight corrected photomultiplier tube hits in a 50 ns window. The number of effective

photomultiplier tubes which are hit in this timing window of 50 ns are summed up, while being weighted with correction factors, to give N_{eff} shown in Equation 3.3 [109].

$$N_{eff} = \sum_{i=1}^{N_{50}} \left[(X_i - \epsilon_{dark} + \epsilon_{tail}) \times \frac{N_{all}}{N_{alive}} \times \frac{1}{S(\theta_i, \phi_i)} \times \exp\left(\frac{r_i}{\lambda}\right) \times G(i) \right] \quad (3.3)$$

where X_i is the correction factor hits with many photoelectrons. This correction factor is important because if some photomultiplier tubes are hit by multiple photons (for example, if the edge of the fiducial volume is where the event vertex took place). The number of photoelectrons produced by each hit photomultiplier tube is estimated using the occupancy of the eight photomultiplier tubes which surround it. Using the number of hit photomultiplier tubes (n_i) and the number of functional photomultiplier tubes that surround the i-th photomultiplier tube (N_i), the formula for X_i is shown in Equation 3.4.

$$X_i = \begin{cases} \log(1 - n_i/N_i)^{-N_i/n_i} & (n_i < N_i) \\ 3 & (n_i = N_i) \end{cases} \quad (3.4)$$

The term ϵ_{dark} in Equation 3.4 is a correction factor for dark noise hits, shown in Equation 3.5, where R_{dark} is the average value for the dark rate during the run period that the event is in and $N_{PMTalive}$ is the number of active photomultiplier tubes in the inner detector.

$$\epsilon_{dark} = \frac{N_{PMTalive} \times R_{dark} \times 50 \text{ ns}}{N_{50}} \quad (3.5)$$

The term ϵ_{tail} is the correction factor for photomultiplier tube hits which are in the tail end of the 50ns timing window, and is defined in Equation 3.6.

$$\epsilon_{tail} = \frac{N_{100} - N_{50} - N_{alive} \times R_{dark} \times (100 - 50)\text{ns}}{N_{50}} \quad (3.6)$$

The term $\frac{1}{S(\theta_i, \phi_i)}$ is the inverse of the effective area of the ith hit photomultiplier tube photocathode, from the direction of the incident photon given by its solid angle (θ_i, ϕ_i) .

$G(i)$ is the gain correction for the quantum efficiency of the photomultiplier tubes and $\exp(\frac{r_s}{\lambda})$ is the correction for water transparency which accounts for the amount of attenuation undergone by the photons in water, where λ is the water transparency measured during the run period which includes the event, and r_i is the distance between the reconstructed

event vertex and the i-th hit PMT.

The average of each N_{eff} distribution is taken, after producing multiple N_{eff} distributions with fixed energies using Monte Carlo. These energies are fitted with a polynomial which is a function of the averaged N_{eff} distribution, so the reconstructed energy is converted from N_{eff} .

3.3 Super-Kamiokande Gadolinium Upgrade

In order to be able to observe the diffuse supernova neutrino background (DSNB) flux it was proposed that Gadolinium (Gd) should be added to the water in Super-Kamiokande. There are two natural isotopes of gadolinium, Gd-155 and Gd-157, which have large thermal neutron capture cross sections of 60740 barns and 253700 barns respectively: when neutrons are captured on them there is a cascade of gamma rays that occurs, with an energy totalling 8 MeV. However when a neutron is captured on hydrogen, a single 2.2 MeV gamma ray is produced [110]. The ultimate aim is to load a total amount of gadolinium in the form of gadolinium sulphate octahydrate ($\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$) in Super-Kamiokande which equates to 0.2% of Gd by mass, resulting in 90% neutron capture efficiency. The ability to tag neutrons efficiently in Super-Kamiokande will benefit multiple physics topics, not only for the aforementioned observation of DSNB flux, but also for analyses involving atmospheric neutrinos and proton decay.

3.3.1 Americium/Beryllium Calibration

The use of an Americium/Beryllium (Am/Be) calibration source deployed in Super-Kamiokande and also in the EGADS project (see next section) is very useful for validating the neutron tagging algorithm and for measuring the neutron capture time constant from neutrons captured on gadolinium. An Am/Be source is placed inside a 5 x 5 x 5 BGO (Bismuth Germanate Oxide) crystal cube. A 4.4 MeV gamma ray is produced from the Am/Be source decay (shown in Equation 3.7) and this is detected by the detector from the large number of scintillation photons generated by this gamma ray passing through the BGO crystal. This 4.4 MeV gamma ray serves as the prompt event, and the delayed neutrons produced can be searched for after the 4.4 MeV gamma ray signal [111].



The Am/Be source was used both in both EGADS (see next section) and Super-




Figure 3.6: (a) Delayed neutron capture time from prompt event with Am/Be source. (b) Reconstructed energy from gamma rays after neutron capture. Taken from [3]

Kamiokande in order to measure the gadolinium concentration and the neutron capture time constant, and due to its similarity to the neutral current quasielastic events studied in the analysis in this thesis, it can serve as a helpful control sample and is used in the validation of the neutron tag algorithm tagging efficiency in Chapter 6 and the calculation of the detector response uncertainty in Chapter 7.

3.3.2 The EGADS project

In 2009, prior to the addition of gadolinium in Super-Kamiokande, the EGADS (Evaluating Gadolinium's Action on Detector Systems) project was used to evaluate how the inclusion of $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ would affect water quality and detector components inside Super-Kamiokande and their analyses, and also to test the water system circulation. Measurements regarding neutron tagging were also taken using an Americium/Beryllium (Am/Be) source placed inside EGADS [112]. The delayed neutron capture time from an Am/Be source used in EGADS with the gadolinium sulphate concentration of 0.2% is shown in Figure 3.6. Here, we can see that the neutron capture time from the data is $29 \pm 0.3 \mu\text{s}$ and for the Monte Carlo it is $30 \pm 0.8 \mu\text{s}$.

EGADS represented the most realistic possible soak test, and after two and a half years of running, EGADS was emptied in November 2017 to check the condition of the inner structure and the photomultiplier tubes. There was no deterioration of any of the components, which was an excellent sign for a detector designed to so closely resemble the conditions for the Super-Kamiokande Gadolinium upgrade.

Chain	Isotope	Criterion [mBq/kg]	Physics target
^{238}U	^{238}U	< 5	SRN
	^{226}Ra	< 0.5	Solar
^{232}Th	^{232}Th	< 0.05	Solar
	^{228}Ra	< 0.05	Solar
^{235}U	^{235}U	< 30	Solar
	$^{227}\text{Ac}/^{227}\text{Th}$	< 30	Solar

Table 3.2: Table of impurities in the gadolinium sulphate octahydrate powder

3.3.3 Gadolinium loading into Super-Kamiokande

After the success of EGADS, the Super-Kamiokande Gadolinium project was formed in 2015 with the final goal of adding 0.2% $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ by mass to the detector. The first step of gadolinium loading began with the loading of 13 tons of $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ into Super-Kamiokande from July 14th to August 17th 2020, which is about 10% of the target concentration. The work in this thesis focuses on this first Gd loading period with a Gd concentration of 0.01% (equivalent to a $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ concentration of 0.026%) not the second loading period which began in late May of 2022, with the target concentration of 0.03%.

The SK-Gd water system

The SK-Gd water system was designed to dissolve $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ powder into the detector water, pass it through a “pretreatment” system to remove contaminants from the water, and then to continuously circulate it. The design for this treatment system was successfully tested in EGADS and involves treating this solution with ultraviolet light. Positively charged impurities dissolved in the solution (such as radium ions) and negatively charged impurities (such as uranium) are removed using cation and anion exchange resins respectively, after which a UV steriliser removes bacteria which were introduced in the dissolving process [113].

The acceptable background rate after the final value for Gd loading was set to be less than double that of the background rate for when Super-Kamioknde ran with pure water. As a result, rigorous standards of cleanliness were set for the $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ powder, which meant setting maximum allowed levels of radioactive impurities which are shown in Table 3.2.




Figure 3.7: The attenuation length of Cherenkov light measured using cosmic ray muons between March of 2020 and March of 2021, taken from [3]. The green lines on the figure indicate the first gadolinium loading period from July 14th 2020 to August 17th 2020.

SK-Gd attenuation, transparency and concentration monitoring

After the loading of gadolinium into Super-Kamiokande, water transparency and attenuation length were continuously monitored. This had also been conducted in EGADS (see previous section), but due to the flow rate of the water and method by which gadolinium is loaded into the detector being different in Super-Kamiokande, it is important to monitor these attributes in the SK-Gd upgrade as well. Figure 3.7 shows how the attenuation length of the Cherenkov light in SK-Gd varies with time: this attenuation length is measured using cosmic ray through going muons (as explained in Chapter 4). There is a clear decrease in the attenuation length after the loading of $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$, reaching a minimum of 75 m in August of 2020, and increasing again to its original pre-Gadolinium loading value of 90 m by the beginning of December 2020.

It is important to monitor the concentration of the $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ in the detector - this can be done using either direct sampling via calibration ports or using the Am/Be neutron source. By measuring the conductivity of the ions, the concentration of $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ can be determined. Figure 3.8 shows the variation of the




Figure 3.8: Conductivity vs. z position during Gd loading inside the inner detector, taken from [8].

$\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ concentration in the detector at different depths in the detector during various points in time during the gadolinium loading period.

Deployment of this Am/Be source into the inner detector of Super-Kamiokande using the central calibration port and then monitoring the source at three positions along the Z-axis, the concentration of $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ could be measured [114]. One measurement position is in the middle of the detector ($Z=0$ m) and the other two were at $Z = +12$ and $Z = -12$ m respectively. By searching for neutron capture events on gadolinium from the Am/Be data, a time distribution of neutron capture candidates could be plotted and fit with a function shown in Figure 3.9. The Am/Be source position here was $Z=0$ m and the $0 \mu\text{s}$ time value on the x-axis is the time at which the scintillation photons produced by the 4.4 MeV gamma ray from its passing through the BGO cube are detected.

Using GEANT4 Monte Carlo simulations, the neutron capture time can be converted to a value for Gd concentration. The measured mean capture lifetime of $115 \pm 1 \mu\text{s}$ corresponds to a Gd concentration value of 111 ± 2 ppm, consistent with the target concentration value of 0.011%.

To summarise, Super-Kamiokande has undergone a lot of transformations over its life-time, with modifications made to its data acquisition system and methods of event re-




Figure 3.9: Neutron capture time distribution for the Am/Be source placed at Z=0 m, taken from [8].

construction with each successive new phase. The biggest change made to the detector is the upgrade to Super-Kamiokande Gd, where in the summer of 2020, 0.026% of $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ was added to the detector: a long-awaited next step to enhance sensitivity to the detection of neutrons emitted in inverse beta decay compared to that in water.

Chapter 4

Super-Kamiokande Detector Calibration

“Calibrated to be accurate down to the micrometer. And, I might add, at a very reasonable price.”

Quark, Star Trek DS9: S2E22 The Wire (1994)

In order to achieve optimal event reconstruction for physics analyses, calibration of the Super-Kamiokande detector is crucial. For example, when conducting Monte Carlo simulations of certain processes in the detector, facets of the experiment such as properties of the water, photomultiplier tube response and the inner detector and outer detector electronics are all calibrated so that input parameters for the Monte Carlo simulations can be obtained. This chapter will concern itself with the inner and outer detector calibration, including photomultiplier tube and electronics calibration, PMT gain calibration, quantum efficiency determination and hit timing and charge information calibration.

4.1 Inner detector calibration

4.1.1 PMT high-voltage setting calibration

The high-voltage (HV) setting for all photomultiplier tubes need to be adjusted individually so all the PMTs produce the same amount of charge for a certain light intensity received by them. Placing a light source which distributes light isotropically in the centre of the inner




Figure 4.1: Location of 420 reference PMTs used for HV setting calibration. The red lines show the placement of these PMTs with respect to the others (left). The grouping of these PMTs due to their geometry in relation to the light source is also shown (right)

detector to achieve this calibration means that there is no position in the detector from which the inner detector PMTs are equidistant, so each PMT will not receive the same amount of light from the light source. To avoid this problem, a set of 420 pre-calibrated PMTs inside the detector were used, separated into groups relating to their geometrical distance from the HV calibration light source, which is shown in Figure 4.1 for their location with respect to the other photomultiplier tubes.

4.1.2 Relative gain calibration

Understanding the timing information from the hit photomultiplier tubes depends on how well the charge from the hit PMT is calculated. To carry out charge calibration, a quantity called photomultiplier tube “gain” must be calculated. “Gain” is the conversion factor from the number of photoelectrons produced by the hit PMT and charge, specifically how much charge one can expect from a single photoelectron from the PMT anode. Along with the PMT gain, there are three other quantities which relate to charge calibration: quantum efficiency, collection efficiency and light collection efficiency.

The quantum efficiency (QE) is the ratio of the number of photoelectrons produced by

the photocathode, to the number of incident photons on the photocathode. The collection efficiency is the fraction of the total number of photoelectrons produced which are collected by the first dynode in the PMT. The product of the quantum efficiency and the collection efficiency, gives the light collection efficiency.

Knowing the gain and light collection efficiency of each PMT in the detector is important in order to accurately measure the output charge from each individual PMT, which is done by first calculating the relative gain difference among all PMTs and then working out the average gain difference over all PMTs in the detector. After this, the variation away from this average gain value can be calculated for each separate inner detector photomultiplier tube, and the gain value for each can be extracted.

The relative gain difference is calculated by two measurements using a light source to produce constant-intensity flashes. The first measurement involves using the light source to produce high-intensity flashes so that all photomultiplier tubes in the detector get a certain number of photons, and the second measurement has the light source produce low-intensity flashes so that only a few PMTs are hit. The first measurement provides an average charge value ($Q_{obs}(i)$) for each inner detector PMT, while the second measurement gives single photoelectron hits, providing a number of times ($N_{obs}(i)$) that a single PMT gives a charge which is greater than the PMT threshold value. Equations 4.1 and 4.2 shows how these two values are calculated from the high and low intensity flash values (I), the acceptance of the PMT(i) ($a(i)$), the QE value of the PMT (ε_{qe}) and the PMT gain G .

$$Q_{obs}(i) \propto I_{high} \times a(i) \times \varepsilon_{qe}(i) \times G(i) \quad (4.1)$$

$$N_{obs}(i) \propto I_{low} \times a(i) \times \varepsilon_{qe}(i) \quad (4.2)$$

Therefore, by simply dividing these two values of $Q_{obs}(i)$ and $N_{obs}(i)$ the average gain over all PMTs can be calculated. Figure 4.2 shows the spread of the relative gain over all the PMTs.

4.1.3 Absolute gain calibration

In order to calculate absolute gain, the single photoelectron distribution needs to be measured, this is because absolute gain relates to the observed charge in the photomultiplier tube with the number of photoelectrons produced. A nickel-californium source (shown in Figure 4.3) is used for this measurement due to it releasing gamma rays isotropically, with




Figure 4.2: Relative gain of PMTs in Super-Kamiokande

a total gamma ray cascade energy of 9 MeV [115]. Thermal neutron capture on nickel is used as the gamma ray source, with the neutrons provided by the spontaneous fission of ^{252}Cf . This nickel source is placed in the centre of the inner detector and the gamma rays produced are detected by all the inner detector PMTs. On average the observed number of photoelectrons is 0.004 per event per PMT, meaning that single p.e. hits are observed for more than 99% of the hits. The observed charge distribution of all the hits from this nickel source is used to give the average charge, which is used as a conversion factor from a charge measurement in picoColoumbs and single photo-electrons. The factor is 2.658 pC per photoelectron (calculated at the beginning of SK-IV) which is then used to extract the single-p.e. distribution, shown in Figure 4.4.

4.1.4 Relative quantum efficiency measurement

To measure the relative quantum efficiency, the gamma rays from neutron capture on the nickel source are simulated. Inside this simulation, a common value of QE is used for all the ID PMTs to predict the number of hits for each PMT. Comparing this number of hits to the actual data obtained for each individual PMT by calculating the ratio between them provides us with a value for relative QE for each inner detector PMT which is then used inside the simulation.



Figure 4.3: Nickel-californium source used for absolute gain calibration [9]




Figure 4.4: Single p.e distribution of charge in pC [9]

4.1.5 Timing information calibration

Calibrating the hit timing information of the photomultiplier tubes is essential due to its importance in accurately being able to reconstruct events. Event reconstruction makes use of determining exactly where interaction vertices are and the direction in which particles travel, and to do this the time response needs to be very carefully calibrated. The response time of the PMT also relates to the amount of charge observed: in order for a hit to be registered, the PMT signal must pass the discriminator value of the hit threshold, and the time in which this happens is dependent on the height of the pulse, which is correlated with the observed charge. All these factors need to be considered when calibrating hit timing information.

To aid the timing calibration, a diffuser ball is placed near the centre of the inner detector, into which a nitrogen laser injects pulsed laser light. By varying the intensity of this light, the laser light can be outputted in flashes, and the timing of the laser pulses is monitored using a 2-inch monitor PMT. The schematic of this timing calibration system is shown in Figure 4.5.

The value of these laser pulse timings, and the time-of-flight value from the diffuser ball are subtracted from the PMT hit time. Using the observed charge values and these adjusted hit times, “TQ” (time and charge) distributions can be plotted for each inner detector PMT. An example TQ distribution is shown for an inner detector PMT (cable number 00010) in Figure 4.6, where the vertical axis shows the corrected TOF and laser pulse time corrected PMT hit time, and the horizontal axis shows the observed charge of each hit. Figure taken from [9].

The timing resolution of the PMTs (also known as the transit time spread) is also something that must be calibrated. This is calculated by using the same timing and charge data used to produce the TQ distributions [116]. By correcting all the ID PMT hits by their TQ distributions, these residual timing distributions have an asymmetric Gaussian function fitted to them, from which two values of sigma are extracted: σ_t and $\sigma_{t'}$. These are the values for the timing resolution before and after the peak time of this distribution. Equation 4.4 shows how the asymmetric Gaussian is defined.

$$f(t; t > T_{\text{peak}}) \equiv A_1 \cdot \exp\left(-(t - T_{\text{peak}})^2 / \sigma_t^2\right) + B_1 \quad (4.3)$$

$$f(t; t \leq T_{\text{peak}}) \equiv A_2 \cdot \exp\left(-(t - T_{\text{peak}})^2 / \sigma_{t'}^2\right) + B_2 \quad (4.4)$$




Figure 4.5: Schematic of the timing calibration system, with SK ID PMTs in blue and the diffuser ball in purple. The dye laser shifts the wavelength of the laser light to 398 nm to maximise the quantum efficiency of the PMTs and light absorption.




Figure 4.6: Example TQ distribution for an inner detector PMT, where the horizontal axis gives the charge of each hit (QBin), and the vertical axis gives the time in nanoseconds after subtracting the time of flight.



Figure 4.7 shows an example of the residual timing distribution fitted with an asymmetric gaussian for a certain value of binned charge.

Figure 4.8 shows timing resolution plotted as a function of charge for both before and after the peak time of the residual time distribution (red and blue points respectively) for SK-IV TQ calibration data.

4.1.6 Measurement of light reflection on the black sheet and the PMTs

For SK-IV, four types of material, corresponding to four different refractive indices are taken into account: water, glass, bialkali, and vacuum. Table 4.1 shows the values for each of these materials, λ is the wavelength of the light in nm and n_{real} and n_{img} are the real and imaginary parts of the complex refractive index.

Regarding the black sheet used to line the inside of Super-Kamiokande, it can either reflect or absorb Cherenkov photons. The amount of Cherenkov photons detected is measured by a light injector setup, shown in Figure 4.9. For three different incident angles of laser light (30° , 45° and 60°) and three different laser light wavelengths (337 nm, 400 nm and 420 nm) the charge from the light scattered off the black sheet was measured [117]. The direct charge (i.e. the same setup without the black sheet present) was also measured, with the total black sheet reflectivity being the ratio between the scattered charge and the direct charge.



Material	Refractive index
Water	1.33
Glass	$1.472 + 3670/\lambda^2$
Bi-alkali	$n_{real} + i n_{img}$
Vacuum	1.00

Table 4.1: Refractive indices of materials inside the Super-K detector, where λ is the wavelength of the light in nm, and n_{real} and n_{img} are the real and imaginary parts of the complex refractive index of the bi-alkali material used in the photocathode of the PMTs.




Figure 4.9: Schematic of the laser light reflectivity. Bird's-eye view (left) and setup inside of Super-Kamiokande (right).




Figure 4.10: Schematic of the differences between Rayleigh and Mie scattering

Measurement of absorption and scattering coefficients

In Super-Kamiokande, the detector medium scatters and absorbs the Cherenkov light, attenuating its wavelength. The amount of light attenuation after the light has travelled distance l is given by $\exp(-l/L(\lambda))$. Here $L(\lambda)$ is the attenuation length of the detector medium and is shown by Equation 4.5,

$$L(\lambda) = \frac{1}{\alpha_{\text{sym}}(\lambda) + \alpha_{\text{asym}}(\lambda) + \alpha_{\text{abs}}(\lambda)} \quad (4.5)$$

In Equation 4.5, the α_{sym} parameter consists of two types of scattering: the symmetric component of Mie scattering and Rayleigh scattering, whereas α_{asym} only consists of asymmetric Mie scattering. Figure 4.10 shows the difference between these two types of scattering:

Rayleigh scattering occurs when light is scattered from very small particles, the size of these particles being less than 1/10 of the wavelength of the light. Rayleigh scattering has a strong dependence on wavelength, where the intensity of this scattering is proportional to $1/\lambda^4$, meaning that it is enhanced at shorter wavelengths (as shown in Figure 4.12). For particles larger than the wavelength of the light being scattered, Mie scattering becomes more dominant, with more asymmetric scattering occurring the larger the particle is (i.e. with a greater forward lobe for larger particles.) As a result of this α_{sym} has an angular dependence of $1 + \cos(\theta)^2$ where θ is the angle between the incoming and outgoing scattered photon vectors, but α_{asym} has a $\cos\theta$ dependence, only for forward scattering, and an amplitude of zero for backward scattering. The $\alpha_{\text{abs}}(\lambda)$ is the amplitude of the light absorption. The method by which these measurements were made is by using a laser system (shown in Figure 4.11), where laser light is injected at several points in the tank, denoted in Figure 4.11 by the barrel injectors (B1-B5), the previously used old top injector (OT), the new top injector (NT), and an injector on the tank bottom (BT).




Figure 4.11: Schematic of the laser system

The absorption and scattering coefficients are measured using data from light injected from the new top (NT) injector. A large set of calibration Monte Carlo are generated using laser generation software and the Super-Kamiokande detector simulation (SKDETSIM). These set of Monte Carlo are generated with different values of absorption, symmetric and asymmetric scattering, and their timing distributions are compared to the data from the laser system in order to tune the amount of absorption, symmetric and asymmetric scattering in the calibration Monte Carlo. The way in which the α_{abs} , α_{sym} and α_{asym} are defined is shown in Equation 4.6.

$$\begin{aligned}\alpha_{abs} &= P_0 \times \frac{P_1}{\lambda^4} + C \\ \alpha_{sym} &= \frac{P_1}{\lambda^4} \times \left(1 + \frac{P_5}{\lambda^2}\right) \\ \alpha_{asy} &= P_6 \times \left(1 + \frac{P_7}{\lambda^4} \times (\lambda - P_8)^2\right)\end{aligned}\quad (4.6)$$

The term C in the equation for α_{abs} is based on data from [118] for laser light with wavelengths greater than 464 nm while Equation 4.7 is used for wavelengths less than 464 nm.

$$C = P_0 \times P_2 \times (\lambda/500)^{P_3} \quad (4.7)$$

The values of P_0 to P_8 in Equations 4.6 and 4.7 were taken from fits to laser data taken in April 2009, the water coefficient functions of which are shown in Figure 4.12.

As well as the amount of absorption and scattering in the detector, there is also a dependence with respect to z-position in the detector, defined by Equation 4.8.

$$\alpha_{tba} = (\langle N_{top} \rangle - \langle N_{bottom} \rangle) / \langle N_{barrel} \rangle \quad (4.8)$$

Here $\langle N_{top} \rangle$, $\langle N_{bottom} \rangle$, $\langle N_{barrel} \rangle$ are the averaged hit probabilities of the top, bottom and barrel PMTs, where $\langle N_{top} \rangle$ is about 5% less than $\langle N_{bottom} \rangle$ due to the temperature gradient in the tank. Figure 4.13 shows this dependence, and Equation 4.16 shows how this is taken into account for the absorption coefficient α_{abs} by the factor $A(z, t)$:

$$\begin{aligned}A(z, t) &= 1 + z \cdot \beta(t) \quad \text{for } z \geq -11 \text{ m} \\ &= 1 - 11 \cdot \beta(t) \quad \text{for } z \leq -11 \text{ m}\end{aligned}$$




Figure 4.12: Plot of water coefficient functions used in Monte Carlo production, showing points for symmetric and asymmetric scattering and absorption.




Figure 4.13: Dependence of temperature on vertical position in the Super-Kamiokande ID.

where from Figure 4.13, the value of $A(z, t)$ is constant below $z = -11m$, and above $z = -11m$ this value is determined by the z-position in the tank [119]. The relationship between the value of β is related to the top-bottom asymmetry parameter α_{tba} , and for the April 2009 data α_{tba} and β are -4.91% and 0.01.

Chapter 5 expands upon these measurements by going into detail about the newly developed UK Light Injection system which improves upon the Korean laser system mentioned here used to make water coefficient measurements - it offers much narrower beam profiles which are shone onto the barrel regions, allowing for better analysis of the depth dependence of the water coefficients.

Chapter 5

The UK Light Injection System

“Photon torpedo: isn’t that the universal greeting when communications are down?”
“I think it’s the universal greeting when you don’t like someone.”

William T. Riker and Geordi La Forge
Star Trek: Insurrection (1998)

The UK calibration group’s efforts have been focussed on improving the data analysis method and improving the accuracy of the water coefficient measurements. To aid this effort a new UK developed Light Injection (UKLI) system was installed into Super-Kamiokande during the refurbishment that occurred in the summer of 2018. This system has its own set of optics with multiple beam spot diameters and will be described in detail in this Chapter.

5.1 The UK Light Injection System Electronics and Optics

The electronics setup architecture for the UK Light Injection System is made of sixteen light emitting diode boards, where the light being pulsed by the LEDs has a wavelength of 435 nm and there is 1 LED per injector. Each LED is coupled to three optical fibres: one channel connected to a monitor PMT, one connected to an optical fibre that sends light into the Super-Kamiokande detector, and one is a spare.




Figure 5.1: Collimator schematic including the end-cap, lens mount and mounting sleeve structures.

Unlike the Korean laser system mentioned in Chapter 4 which injects light into the detector using an optical fibre which has an opening angle of 12 degrees, the UK Light Injection system contains three different types of light injection optics, with each having a different opening angle: a bare fibre, a collimator and a diffuser. This range of optics can accommodate a larger variety of calibration measurements, and better suit the multiple applications of the light injection system.

The Collimator Optic

A 2-degree opening half angle is achieved by the collimator optic by using a GRIN (gradient-index) lens [120] to reduce the opening angle of the light coming from the fibre optic. A schematic of the collimator design can be seen in Figure 5.1.

The Diffuser Optic

The diffuser optic is a wide angled beam with an opening half-angle of 40 degrees, allowing for more PMT coverage in the detector, therefore enabling measurements of PMT properties, and measurements of light attenuation length in water. Figure 5.2 shows a photograph of one of the diffusers used, and one of the diffuser ball enclosures. The enclosure is made of high grade stainless steel and using a chemical and water resistant epoxy resin, so all the components were ensured to be watertight.

Bare Fibre and Optical Plate

The bare fibre injector are 1 mm step index fibres, are approximately 20 cm in length and are used for validation purposes with the bare fibres in the Korean optical calibration system. These short fibres are screwed into the back end of the optical plate that the collimator and diffuser optics are mounted on, shown in Figure 5.3.




Figure 5.2: Photograph of the diffuser by itself (left), empty diffuser enclosure (centre) and diffuser inside enclosure (right).




Figure 5.3: Photograph of the optical plate which houses the different optics.




Figure 5.4: Setup of the collimator test stand provided by the University of Warwick.

5.2 Optics test stand measurements

In order to test the collimator and diffuser optics, measurements of the angular distributions were made using diffuser and collimator test-stands and would measure angular distributions of the light intensity. The setup for the collimator test stand at the University of Warwick is shown in Figure 5.4 and captures the beam cross section by moving a CMOS camera along the beam width. For the diffuser test-stand the angular distribution of the light output was measured using the setup shown in Figure 5.6. This test stand setup for the diffuser optics consists of a test diffuser ball placed inside a diffuser enclosure, a rotation stage which allows for the movement of the diffuser between -40 and 40 degrees, and a PMT used for pulse intensity measurement set up 250 mm away from the diffuser. An optical fibre couples the diffuser under test to a laser set to a wavelength of 450 nm.

Figure 5.5 shows fits made by ROOT to the light profiles for the collimator. The angular distributions shown give the distribution of the polar angle in degrees of light intensity which are relative to the virtual position from which the light cone originates, averaged over all the orientations of the azimuthal angle.

Figure 5.7 shows distributions provided by this test stand data which are preliminary fits made by ROOT to the light profiles for the diffuser. These distributions are not phi-averaged, and instead are scans across the front of the diffuser. The asymmetries in the profile intensities between -40° and 0° and 0° and 40° are due to imperfections in the diffuser




Figure 5.5: Light profiles for the collimator optics provided by the University of Warwick. The profile for each barrel collimator (B1-B5) is shown in (a)-(e) respectively. The light intensity in arbitrary units is shown on the y-axis, while the polar angle of the light is shown on the x-axis.




Figure 5.6: Setup of the diffuser test stand provided by the University of Warwick.

balls and their enclosures.

5.3 First commissioning data from UKLI

In September of 2019 and November of 2019 two sets of test data were taken of the collimator, the diffuser and the bare fibre optic (the B2 bare fibre) and using an event display developed by the University of Warwick, occupancy plots of the test data sets were produced. Figure 5.8 shows the occupancy plots for the collimator optic from the November 2019 dataset showing the beam spot inside the unrolled volume of the Super-Kamiokande detector. Similarly, Figure 5.9 shows the occupancy plots for the diffuser optic from the November 2019 dataset. The graph in the bottom right hand corner of the occupancy plots show the corrected time-of-flight plots for the PMT hits from the injector. The intensely dark purple hits in Figure 5.9 are “hot channels” and have not been accounted for - these should not be mistaken for scattered hits.

The UKLI was also added to the “autocalib” system used for long term monitoring of the water parameters in Super-Kamiokande by the Korean laser system. In early 2020 the autocalib scheduler was modified to incorporate data taking by the UKLI system which was very useful for gadolinium loading calibration purposes but also in the longer term, it will be useful in the monitoring of daily/weekly water coefficient property measurements, investigation of depth dependence with respect to the water properties and PMT property calibration. Figure 5.10 shows the schedule for autocalib, and the black dashed lines show the position of the UK barrel collimator and diffusers with respect to the other autocalib data taking streams. The horizontal blue line shows the length of the one autocalib cycle,

Figure 5.7: Light profiles for the diffuser optics provided by the University of Warwick. The profile for each barrel diffuser (B1-B5) is shown in (a)-(e) respectively. The light intensity in arbitrary units is shown on the y-axis, while the polar angle scan of the light across the diffuser is shown on the x-axis.




Figure 5.8: Occupancy plots for the collimator optics from the UKLI November 2019 test run for each barrel collimator in the unrolled volume of the SK detector. The crosses show the injector positions, and the collimator beam spots are also shown (the PMTs with highest occupancy). The corrected time-of-flight plots for the PMT hits is shown in the bottom right corner.





Figure 5.9: Occupancy plots for the diffuser optics from the UKLI November 2019 test run, where the injector positions are shown by crosses. The corrected time-of-flight plots for the PMT hits is shown in the bottom right corner.






Figure 5.10: Schematic showing position of the UKLI in autocalib scheduler: the black dashed lines show the UKLI B1-B5 collimator and diffuser optics and the horizontal blue line shows the length of one autocalib cycle.

which is about 4.6 seconds, with each UKLI optic taking about 3310 events per day.

Figures 5.11 and 5.12 show the occupancy plots for autocalib data taken in July 2020, for the B1 collimator and the B1 diffuser respectively. From this point onwards all plots relating to the B2 - B5 injectors for both the collimators and diffusers will be shown in Appendix A. As can be seen in the text in the upper left hand corner, the number of events in the run is a lot less than the 100,000 events or so taken in the test runs, however they are more than sufficient for monitoring purposes.

5.4 Implementation of UKLI in SK Simulation

In order to simulate the data taken with the UKLI, SKDETSIM [121], the Super Kamiokande Detector Simulator was used. SKDETSIM uses GEANT3 (GEometry ANd Tracking 3 [122]) to simulate what the particles in each event would do inside the detector, and tracks the particle's trajectories and energy loss. Simulating the light injection from the UKLI system in SKDETSIM was done in a similar way to the Korean method of producing Monte Carlo: the same versions of the calibration scripts were used, however, small modifications were made to them and to the version of SKDETSIM used to simulate the input photons from the system in the detector. The calibration software allows for the number of events and the number of injected photons to be set, in order to generate many Monte Carlo files with varying absorption, Rayleigh and Mie scattering parameters.

Along with making sure the position of the injectors was set to that of the UKLI injectors (shown in Table 5.1), the opening angle of the injectors determined by the simulation had to be set to accomodate the fact that the injectors for the UKLI system now consisted of three different opening angles for the collimator, diffuser and bare fibre optics. Previously,




Figure 5.11: Occupancy plot for the B1 collimator optic from the UKLI Autocalib July 2020 run.

Figure 5.12: Occupancy plot for the B1 diffuser optic from the UKLI Autocalib July 2020 run.

to set the angle of the photons in the beam, a parameter relating to the width of the input injector beam was produced using a Gaussian random number generator to output the photon angle. However, an entirely new method of determining the opening angle of the beam was needed to include the information from the light profiles taken from the test stands at Warwick.

In order to validate the positions of the targets for the UKLI system, and the relationship between the width of the beam and the output angle, producing charge weighted histograms from UKLI test runs is very helpful. It allows us to explore the shape of the

UKLI Barrel Injector	x(cm)	y(cm)	z(cm)	Misalignment angle ($^{\circ}$)
B1	1490.73	768.14	1224.0	4.1
B2	1490.73	768.14	742.0	3.5
B3	1490.73	768.14	-200.0	3.4
B4	1490.73	768.14	-747.0	6.3
B5	1490.73	768.14	-1413.0	-

Table 5.1: Beam spot positions (x,y,z) of the UKLI injectors in cm and misalignment of the injectors in degrees.




Figure 5.13: Charge weighted z profile plots for the B1 collimator UKLI injector optic, with the September 2019 test run data shown in black and the November 2019 test run data shown in red.

beam profile and intensity. Figures 5.13 and 5.14 shows the charge weighted z-profiles for the September and November 2019 datasets for the B1 and B4 collimator injectors, where the blue dashed line shows the expected target position. These are produced by selecting hit PMTs which are greater than 2 m away from the injector (to avoid including PMT hits from backscattered light), and filling the histogram with the z-position of the hit PMT and the number of hits the hit PMT receives multiplied by the corrected charge from the PMT. The corrected PMT charge ($q_{corrected}$) is calculated using Equation 5.1, where q is the charge, and the gain correction value ($gain$) is taken from official Super-Kamiokande gain tables. By fitting these charge weighted histograms with a gaussian and calculating its mean value (i.e. the actual target location), it was possible to calculate the deviation from the expected target location given in the simulation (the dashed blue lines in Figures 5.13 and 5.14), and then using simple trigonometry the misalignment angle of the injector was calculated, as shown in Table 5.1.

$$q_{corrected} = q / (1 + gain) \quad (5.1)$$

The profiles from the Warwick optic test stands (shown in Figures 5.5 and 5.7) are then used in the production of the opening angle of the injectors in the detector simulation. This was done by treating the profiles in Figures 5.5 and 5.7 as Probability Distribution Functions




Figure 5.14: Charge weighted z profile plots for the B4 collimator UKLI injector optic, with the September 2019 test run data shown in black and the November 2019 test run data shown in red.

(PDFs) and using inverse transform sampling to make the detector simulation sample at random from it. Inverse transform sampling is a method for generating random numbers from any probability distribution by using the inverse of its cumulative distribution $F^{-1}(x)$. For continuous distributions, such as the results from the collimator and diffuser optics test stands, the algorithm for inverse transform sampling is simple. Firstly, a random variable U is uniformly distributed between $[0,1]$, and secondly the relation $X = F_x^{-1}(U)$ would then produce a distribution X following the original probability distribution function, i.e. that of the original PDFs from the optics test stands.

The first step is to produce the CDFs (cumulative distribution functions) from the PDFs from the optic test stand profile tests. Figure 5.5 shows that the original fits to the collimator data did not reach 4 degrees, and as a result the PDFs produced needed to be linearly extrapolated from 3.5 degrees where the measurements cut off to reach 4 degrees. Figure 5.15 shows the PDFs and CDFs produced from the B1 collimator data and Figure 5.16 shows them for the B1 diffuser data. The CDFs are normalised with a max of one using min-max scaling.

After producing the normalised CDFs, the inverse of these CDFs are calculated - Figure 5.17 shows the comparison of the normalised CDF data for the B1 collimator and diffuser (top sublots, shown in blue) and the polynomial fit to the CDF for the B1 collimator (top




Figure 5.15: PDF (left) and CDF (right) for the B1 collimator.




Figure 5.16: PDF (left) and CDF (right) for the B1 diffuser.




Figure 5.17: CDF and inverse CDF for the B1 collimator (left) and for the B1 diffuser (right). The y-axis (range 0.0-1.0) on the top subplots for both figures shows the CDF values for the data (blue) and polynomial fit (red) while the x-axis for the top subplots shows the angle scan range for the specific optic in degrees. For the bottom subplots which show the resulting inverse CDF function (green) and fit to this function (purple) these axes are reversed.

subplots, shown in red), and the inverse CDF function (bottom subplots shown in green) and the polynomial fit to this function (bottom subplots shown in purple).

After producing the fits to the inverse cumulative distribution functions, these functions were inputted into the detector simulation, SKDETSIM. Using the same event display used to produce the occupancy plots for the autocalib data and the test run data, occupancy plots of the Monte Carlo were produced. These are shown for the B1 collimator and B1 diffuser in Figure 5.18. These MC were produced with the standard optical settings used for SKDETSIM. Because the original profiles from the test stands were taken in air, adjustments were made so that the refractive index of the water in the detector is taken into account when implementing the inverse CDFs into the detector simulation.

In order to validate the diffuser MC inverse cumulative distribution function output, a uniform distribution was run through the equation for the diffuser inverse CDF fits and the original PDF fit for each diffuser was used to fit the output points from the distribution, showing that inverse transform sampling was done correctly for the PDFs. This is shown for the B1 diffuser in Figure 5.19.

After producing the UKLI MC, adjusting the timing distributions in order to match up with the UKLI test run data was the next step. Producing time-of-flight corrected plots for the B1 collimator UKLI MC and overlaying it with the Run 82181 November test




Figure 5.18: Monte Carlo simulations of the B1 collimator (left) and diffuser (right) injectors




Figure 5.19: B1 diffuser inverse CDF check

run data with the standard optical parameters, it was clear that there are disagreements between the Monte Carlo and data in both the scattered hits region and the reflected hits peak. In order to change this, the time dispersion of the injected photons in the MC was varied, in order to match the time dispersion of the injected photons in the data.

The time dispersion for the injected photons in the laser generation in SKDETSIM is governed by a Gaussian distributed random number generated using a Box-Muller transform, where additional time dispersion added would be the sigma of this Gaussian, and after a random number is passed through it, the output number would be added to the time for each track step of the photon giving the time dispersion.

The Box-Muller transform is a random number sampling method for making pairs of independent, normally distributed random sources from a source of uniformly distributed numbers (usually from between 0 and 1) [123]. The form of the Box-Muller method implemented to calculate the added time dispersion is the Marsaglia polar method [124], which works by choosing two independent and uniformly distributed numbers (u, v) between $[-1, +1]$, so that $s = u^2 + v^2$, and if $s = 0$, or $s >= 1$, another pair of numbers are chosen. Then the standard normal deviate which is given by

$$z_0 = u \cdot \sqrt{\frac{-2 \ln s}{s}}$$

is multiplied by the chosen value of time dispersion in seconds and added to the mean (set to zero) to give the normally dispersed extra track step time for a photon in the distribution.

Figure 5.20 shows the effect of implementing this varying time dispersion on the raw hit timing output from the UKLI MC B1 collimator simulation, with the time dispersion shown for 0 ns, 5 ns, 10 ns, 15 ns and 20 ns.

In order to properly compare the timing distributions between data and Monte Carlo, the time-of-flight corrected timing plots are produced. To only select reflected and scattered hits, an exclusion region of hits is set: this is set to be ± 2 m around the injector (in order to avoid using backscattered hits in the analysis), and also ± 3.2 m around the injector target region in order to avoid including direct hits to the beam target. Figure 5.21 shows the regions for the hits which are included and excluded in order to produce the TOF corrected timing distributions.

Figures 5.22, 5.23, 5.24, 5.25, 5.26 show time-of-flight corrected hit timing distributions for the B1 injector. The region between the blue dashed lines are the region for the scattered




Figure 5.20: Gaussian distributed time dispersion plots, with varying amounts of time dispersion




Figure 5.21: The included (green) and excluded (red) regions for the TOF timing distributions




Figure 5.22: TOF comparison between UKLI MC with no time dispersion and Run 82181 test data for B1 collimator

hits and the peak on the right shows the reflected hits. The hits from the injector data are shown in black and the MC hits are shown in red. In order to find the closest match for the time dispersion in the data, a gaussian distribution was fit to the B1 collimator data and Monte Carlo reflected peaks and the width of the gaussian was compared - this was only done for the 10 ns, 15 ns and 20 ns dispersion plots because the value for the time dispersion for the LED pulse is known to be in this range and the peak is too narrow and uneven for the 0 ns and 5 ns dispersion plots to fit a gaussian properly. The reason for the variation in the height of the reflected peaks between the MC and data is due to the detector response, which is why the width is being focussed on here instead.

The sigma of the gaussian fit to the data is 14.07 ± 0.01 ns, while the gaussian fit to the reflected peak for the 10 ns, 15 ns, and 20 ns time dispersed MC distributions is shown in Table 5.2.

From Table 5.2 it can be seen that the 10 ns dispersion had the closest value to the B1 data for the sigma of the gaussian fit to the reflected peak, and also the lowest χ^2/ndf value (where the number of degrees of freedom $ndf = 26$) for the comparison between




Figure 5.23: TOF comparison between UKLI MC with 5 ns gaussian time dispersion and Run 82181 test data for B1 collimator

Time dispersion value (ns)	Sigma of gaussian (ns)	χ^2/ndf values of scattered hits region
0	-	8.15
5	-	4.72
10	19.94 ± 0.39	3.45
15	30.30 ± 0.55	13.17
20	38.46 ± 0.75	22.12

Table 5.2: Sigma of gaussian (ns) for each value of time dispersion along wth the χ^2/ndf value for B1 data and MC comparison between the scattered hits region (blue dashed lines).




Figure 5.24: TOF comparison between UKLI MC with 10 ns gaussian time dispersion and Run 82181 test data for B1 collimator, with a gaussian fit to both




Figure 5.25: TOF comparison between UKLI MC with 15 ns gaussian time dispersion and Run 82181 test data for B1 collimator, with a gaussian fit to both




Figure 5.26: TOF comparison between UKLI MC with 20 ns gaussian time dispersion and Run 82181 test data for B1 collimator, with a gaussian fit to both

the data and MC for the scattered hits region, showing that this 10 ns dispersion was the best to use in the MC. In order to improve this part of the analysis, the scale of the time dispersion values could be more granular, for example, zooming into the 5 - 10 ns range when producing MC in order to more accurately determine the value of the time dispersion for the collimator data.

To summarise the work in this Chapter, data from test stands using the same optics used in the UKLI in Super-Kamiokande were used to produce probability and cumulative distribution functions of the optic light profiles. These were implemented into the Super-Kamiokande detector simulation, and inverse transform sampled in order to produce UKLI MC beam spot outputs which were fitted with the original PDFs to verify the output. Alongside this, in order to better align the hit timing distributions for the MC and data, modifying the track step of the photon in the simulation was used to vary the time dispersion of the hits from the injector. The width of the reflected hits peak in TOF corrected timing distributions was determined with a gaussian fit, and compared with the B1 collimator data, along with a comparison of the difference in hit times in the scattered hits region, which allowed us to determine the optimal value for time dispersion of injected hits was 10 ns.

Chapter 6

Neutron Tagging and NCQE Interactions with the SK-Gd Upgrade

“Yeah, well, I told the Captain I’d have this analysis done in an hour.”

“How long will it really take?”

“An hour.”

“You didn’t tell him how long it would really take, did you?”

Lt. Commander Geordie La Forge and
Montgomery “Scotty” Scott, Star
Trek: TNG S6E4 Relics (1992)

At energies close to the atmospheric peak, the NCQE interaction cross sections can be evaluated using T2K beam neutrinos. This chapter will present the status of the improved neutron tag from SK-Gd and its impact on the measurement of NCQE in T2K, while Chapter 8 will give details on the calculation of DSNB NCQE background events. The prompt and delayed signal of the NCQE interaction mimics that of the DSNB, due to the positron being the prompt signal for DSNB, while the prompt signal for NCQE is given by a gamma ray. Neutron capture constitutes the delayed signal for both DSNB and NCQE interactions. With the recent addition of 0.026% $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ to Super-

Kamiokande, neutron detection has improved due to the gamma cascade signal produced when neutrons are captured on gadolinium. While this percentage is not the final amount of $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ that will be added to Super-Kamiokande, this analysis serves as a useful indicator of how much the addition of gadolinium improves the neutron tagging efficiency, which will only improve as the percentage of $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ increases.

There are multiple stages to this analysis, shown in Figure 6.1, where the “neutron tagging” stage occurs via two methods. Previously the NCQE neutron-tagging analyses used a method for neutron tagging which will be referred to as “legacy NTag code”, but in 2020 the Super-K collaboration decided to proceed to use a new, more compact and streamlined version, which combines most of these stages into one piece of software. This will be referred to as “current NTag code”, and this is shown in Figure 6.1 as well. The red arrows in Figure 6.1 show the steps in the analysis procedure using the legacy NTag code which have been assimilated into the new NTag code.




Figure 6.1: Flowchart showing the stages in this analysis for both the analyses which used the legacy NTag code (blue) and the current NTag code (orange).

A large portion of this analysis was to validate the results regarding the prompt event reconstruction and the neutron truth information between the legacy NTag and the new NTag - while the general neutron tagging algorithm was the same, the complete rearrangement of the structure of the NTag code required there to be checks regarding event reconstruction variable output and true neutron information variables such as the number of neutrons captured and the position in the detector the neutron captures occur at which will be shown later on in this Chapter.

6.1 Event Simulation

This section discusses details about the event simulation, specifically the way neutrino interactions are simulated in order to produce the Monte Carlo. Table 6.1 summarises all

Name	Version
Flux	13a tuning v4.0
NEUT	5.3.3
SKDETSIM-SKGd	ANNRI-Gd model
Geant	4.10.05.p01
T2KReWeight	v1r23
GENIE	R2-12-10

Table 6.1: Software versions used in analysis from [17]

the software packages used in this analysis.

6.1.1 Neutrino flux

As mentioned in Chapter 2, the T2K neutrino beam is generated by having a 30 GeV proton beam impinge on a graphite target, where the pions and kaons that result from this decay, produce anti(neutrinos). Neutrino event rates measured at Super-Kamiokande are compared to Monte-Carlo predictions stemming from flux and cross-section calculations. The NA61/SHINE experiment provides direct hadron production measurements for T2K and other long baseline experiments, and measures the yield of charged hadrons from a proton beam fired at a thin graphite target (2 cm long) and a T2K replica graphite target (90 cm long). From this experimental data, Monte Carlo simulations are tuned and the neutrino flux is predicted. In the beam MC, protons which have 30 GeV of kinetic energy are focused onto a graphite target and after the secondary particles are focused using the horn magnets, the neutrino tracks they decay into are ascertained at the near detectors and at Super-Kamiokande to produce the flux and energy spectra at these locations. The T2K neutrino beam flux version used in this analysis is 13a tuning v4.0 which uses the NA61/SHINE 2009 Replica-Target Data [125]. Figure 6.2 shows the energy spectra of each of the neutrino flavour components for the FHC (forward horn current) mode for the T2K Run 1-9 period.

The oscillation effect on the neutrino flux also needs to be considered after choosing which flux to use: the neutrino-oxygen NCQE cross section does not depend on flavour, and therefore neutrino oscillation affects would have no impact on a fully pure NCQE sample. However, there is a small fraction of charged current events which seep into the NCQE sample, and oscillation weights need to be applied to the charged current events




Figure 6.2: Energy spectra of the $(\nu_e, \bar{\nu}_e, \nu_\mu, \bar{\nu}_\mu)$ flavour components for the FHC mode, T2K Run 1-9

in the sample. The entire Monte Carlo is reweighted as if it was fully comprised of muon neutrinos and muon anti-neutrinos, due to the very small presence of electron neutrinos. Equation 6.1 shows the event weight applied to charge current events for the 2-flavour (electron neutrino and muon neutrino) scenario.

$$\begin{aligned}
 \text{weight } (E_\nu) &= P_{\nu_\mu \rightarrow \nu_\mu} (E_\nu) + P_{\nu_\mu \rightarrow \nu_e} (E_\nu) \times \underbrace{\frac{\sigma_{\nu_e CC} (E_\nu)}{\sigma_{\nu_\mu CC} (E_\nu)}}_{\approx 1} \\
 &\approx P_{\nu_\mu \rightarrow \nu_\mu} (E_\nu) + P_{\nu_\mu \rightarrow \nu_e} (E_\nu) \\
 &= 1 - \cos^4 \theta_{13} \times \sin^2 2\theta_{23} \times \sin^2 \left(1.267 \frac{\Delta m_{32}^2 [\text{eV}^2] \cdot L [\text{km}]}{E_\nu [\text{GeV}]} \right)
 \end{aligned} \tag{6.1}$$

where $P_{\nu_\mu \rightarrow \nu_\mu}$ is the survival probability of muon neutrinos, $P_{\nu_\mu \rightarrow \nu_e}$ is the oscillation probability of electron neutrinos, and $\frac{\sigma_{\nu_e CC} (E_\nu)}{\sigma_{\nu_\mu CC} (E_\nu)}$ is the cross-section of the charged current electron neutrino interaction cross-section to the cross-section of the charged current muon neutrino interaction cross-section. The atmospheric mass mixing parameter is given by Δm_{23} , L is the baseline length of T2K, and E_ν is the energy of the neutrino. The cross-

Osc Parameter	Value
$\sin^2 \theta_{13}$	0.0211 ± 0.0008
$\sin^2 \theta_{23}$	$0.541^{+0.027}_{-0.037}$
$ \Delta m_{32}^2 $	$2.469^{+0.073}_{-0.071} \times 10^{-3} \text{ eV}^2$

Table 6.2: Oscillation parameters estimated with the reactor constraint

section ratio term is simplified to one due to the kinematic difference between e^\pm and μ^\pm not being considered. Table 6.2 shows the oscillation parameters used in Equation 6.2 which are estimated with the reactor constraint taken from [126].

6.1.2 Primary interaction

The interaction between the incoming neutrino event and an oxygen nucleus, and the de-excitation of the nucleus is modelled by NEUT [127], which produces a vector of primary particles used for event simulation in SKDETSIM. Because these are primary particles, they do not take into consideration all the particles produced from the detector response, i.e. the secondary particles produced from the interactions within the medium of the detector, in our case, water doped with $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$. The NEUT cross-section for the interaction between a ^{16}O nucleus and a neutrino is shown in Figure 6.3.

NCQE interactions are modelled in NEUT using the Benhar Spectral Function (SF), while CCQE interactions (including 2p2h interactions, where a neutrino knocks out two nucleons at once) are modelled using the Relativistic Fermi-Gas (RFG) model [128], [129]. 2p2h interactions (2-particle-2-hole) involve a neutrino knocking nucleons out of a nucleus and creating two holes.

The lowest rung of nucleons in Figure 6.4 is the $s_{1/2}$, with $p_{3/2}$ above this level and $p_{1/2}$ above that. The protons in these rungs have removal energies of 42 MeV, 18.4 MeV and 12.1 MeV respectively, and due to neutron levels being more tightly bound, these have an extra removal energy of 3.24 MeV compared to their proton counterparts. The shell model is imperfect due to how it allocates the probability of ^{16}O transitioning to the possible nucleon states. In the shell model, probabilities are allocated by counting the number of nucleons in each energy level and assigning probabilities according to how many there are. In Figure 6.4 it can be seen that the $p_{3/2}$ state has double the number of nucleons compared to the $s_{1/2}$ model and therefore double the probability of transition is assigned for the $p_{3/2}$ state, and the probability of transitioning to any other state is assigned to be




Figure 6.3: Plot showing the NCQE cross section for ^{16}O as a function of incoming neutrino energy and the cross section of gamma ray production, taken from [10]




Figure 6.4: Representation of NC neutrino scattering off ^{16}O with protons on the left hand side and neutrons on the right arranged according to the shell model

Model	$(s_{1/2})^{-1}$	$(p_{3/2})^{-1}$	$(p_{1/2})^{-1}$	others
Shell model	0.25	0.5	0.25	0
Spectral Function	0.1055	0.3515	0.158	0.385
This analysis	0.4905	0.3515	0.158	0

Table 6.3: Transition probabilities for different models and states

Isotope	Abundance [%]	Cross-section [b]
^{152}Gd	0.200	735
^{154}Gd	2.18	85
^{155}Gd	14.80	60900
^{156}Gd	20.47	1.8
^{157}Gd	15.65	254000
^{158}Gd	24.84	2.2
^{160}Gd	21.86	1.4


Table 6.4: Abundance and thermal neutron capture cross section of various isotopes of gadolinium

0, because in the shell model they don't even exist. The Benhar Spectral Function model however is complex and is tuned using electron-nucleus scattering data. The model used in this analysis is a modified version of the Benhar Spectral Function model, where the case of other transition states is dealt with by merging the "others" state into the $s_{1/2}$ state. Table 6.3 gives the probabilities of transition to different states for different models.

6.1.3 Detector response and interactions in the detector medium

Prior analyses to this used SKDETSIM (Super-Kamiokande Detector Simulator) to simulate the trajectories of particles through the water in Super-Kamiokande and output detector response MC. This analysis uses SKDETSIM-SKGd to propagate the particles, due to the requirement of needing gadolinium sulphate present in the simulation. Unlike SKDETSIM, SKDETSIM-SKGd has a GEANT4 function implemented for neutron capture on gadolinium isotopes and its subsequent interactions. The particular isotopes of gadolinium used in the simulation are ^{155}Gd and ^{157}Gd due to their excellent thermal neutron capture cross sections. Table 6.4 shows the relative abundance of various gadolinium isotopes inside natural gadolinium and their associated thermal neutron capture cross sections.

As can be seen in Table 6.4, ^{155}Gd and ^{157}Gd have extremely high neutron capture cross sections compared to the other isotopes. Equation 6.2 shows the neutron capture on both of these isotopes, and the energy of the subsequent gamma rays.



It is therefore important to model the gamma ray emission spectra from both of these isotopes. The model used by SKDETSIM-SKGd is the ANNRI-Gd model, [11], [130]. This uses gamma energy spectrum data from the germanium spectrometer at the ANNRI (Accurate Neutron Nucleus Reaction Measurement Instrument) experiment. This experiment uses the incoming pulsed neutron beam from the Japan Spallation Neutron Source (JSNS) at the Material and Life Science Experimental Facility (MLF) of J-PARC. After a 300 kW beam of protons from the JSNS facility hits a target of mercury and produces neutrons, this neutron beam hits an enriched ^{155}Gd target or a ^{nat}Gd film. The ANNRI spectrometer is placed 21.5 m away from the neutron beam source, with two cluster detectors on either side of the neutron capture target material, which is 13.4 cm away from each cluster detector. Surrounding the target, there are also 8 co-axial germanium detectors. The schematic for the ANNRI-Gd experiment is shown in Figure 6.5.

Figure 6.6 shows the energy spectra for different multiplicity values (left) and hit values (right) from one of the germanium crystals in the ANNRI spectrometer. The multiplicity of an event is the number of sub-clusters of hit germanium crystals, and the hit value is simply the number of total germanium crystals hit in the event.

One of the key differences between the default GEANT4 model for thermal neutron capture on gadolinium and the ANNRI-Gd model is how it conserves energy: the photon evaporation model conserves only the final sum of energy for the captured event, but performs poorly when modelling the gamma-ray energy on an individual event by event basis. One way the ANNRI-Gd model combats this is by separately describing the continuous and discrete peaks in Figure 6.6, where the discrete peaks are shown as spikes below 1500 keV and above 4500 keV. These come from the different ways in which gadolinium de-excites after thermal neutron capture. The continuous spectrum in the plots in Figure 6.6 show the de-excitation of $^{158}\text{Gd}^*$ in multiple steps, producing multiple low energy gamma rays, which accounts for about 93% of the spectrum. The discrete spikes in the




Figure 6.5: Schematic of the ANNRI Ge spectrometer (dimensions in mm). The beam pipe along with one of the Ge cluster detectors (light blue) is shown. The shaded purple area are the anti-coincidence shields made of bismuth-germanium-oxide (BGO) crystals [11]




Figure 6.6: Energy spectra for thermal neutron capture on ^{157}Gd energy spectra for different multiplicity values (left) and hit values (right) from one of the germanium crystals in the ANNRI spectrometer. Taken from [11]

spectra come from a two-step cascade, which produces a high energy gamma ray instead, accounting for the remaining 7% of the spectrum. Figure 6.7 shows the continuous and discrete components of the ANNRI-Gd MC, along with data from the experiment. Figure 6.8 shows a ratio plot of data and MC for the GLG4sim model, the default Geant4 photon evaporation model and the ANNRI-Gd model: here it is clear the ANNRI-Gd model fits the data better than the other two models, especially at energies above 3500 keV. The energy from the neutron capture on gadolinium de-excitation is released in the form of multiple gamma rays, and liquid scintillator detectors would only have to look for the deposition of the energy from these gamma rays, whereas a water Cherenkov detector such as Super-Kamiokande can only detect part of this deposition due to the Cherenkov threshold energy. As a result, understanding the gamma ray multiplicities and their energies in the range 0.8 MeV to 8 MeV is important in order to predict the efficiency of neutron tagging within Monte Carlo simulation.




Figure 6.7: Energy spectra for the ANNRI-Gd model broken down into its continuous and discrete components along with data from the ANNRI-Gd experiment [11].

6.2 Event Reconstruction

6.2.1 BONSAI output reconstruction quantities

Due to this analysis looking specifically at the low energy region, a fitter (LOWFIT) specific to low energies (below 100 MeV) is used to reconstruct events. Both MC and data




Figure 6.8: Comparison between neutron capture MC models and ANNRI-Gd data, with the ratio of data and MC on the y-axis, the GLG4sim model in blue, GEANT4 default model in green and the ANNRI-Gd model in red [11].

neutrino events undergo a reconstruction phase, where the low-energy fitter BONSAI is applied to the event, as discussed in Chapter 2. The reconstruction is carried out using timing and PMT position information, however charge information is omitted - this is because of only single photoelectrons being measured by each PMT, so it makes sense to count the number of hit PMTs instead. The output of BONSAI gives information which will be used in the reduction phase of the data and allow for the selection of the NCQE sample. The following quantities comprise the BONSAI output, the first two being helpful spectator variables and the latter five constituting parameters which are used in the reduction phase of the analysis, from which the neutrino NCQE sample is determined.

1. Neutrino vertex position

The reconstructed location of the neutrino interaction event.

2. Neutrino vertex direction

This vector points towards the direction which is an average over all the Cherenkov cone axes which are produced, due to there being multiple leptons induced in the interaction.

3. Reconstructed energy

In line with the standard SK low energy analysis definition, this energy is simply the

reconstructed kinetic energy of the electrons.

4. Dwall

This variable gives the minimum distance of the neutrino vertex position from the closest wall of the Super-Kamiokande detector.

5. Effwall

This variable gives the distance between the neutrino vertex position and the closest wall, but moving back from the vertex position along the neutrino vertex direction vector.

6. Vertex direction and goodness coefficient

The coefficient $ovaQ$ (defined in Equation 6.3) describes the quality of the vertex reconstruction. It consists of two parameters g_{vtx}^2 and g_{dir}^2 where the former describes the goodness of the vertex which is based on PMT hit timings, and increases the sharper an event is in time. The latter is the directional goodness and measures the azimuthal uniformity in the ring pattern produced by the Cherenkov cone, which decreases the more uniform an event is in space. As a result of this, $ovaQ$ increases the more uniform and sharp in time an event is.

$$ovaQ = g_{vtx}^2 - g_{dir}^2 \quad (6.3)$$

The parameter g_{vtx} is calculated using a fit of the PMT timing distribution and using the hit times of the PMT it is defined as in Equation 6.4.

$$g_{vtx} = \frac{\sum_i w_i e^{-\frac{1}{2}(\frac{\Delta t_i}{\sigma})^2}}{\sum_i w_i} \text{ with } w_i = -\frac{1}{2}(\frac{\Delta t_i}{\omega})^2 \quad (6.4)$$

Here $\sum_i w_i$ is the weight given to the i-th hit PMT for the reduction of dark noise, where ω has a value of 60ns. σ has a value of 5ns which is used to test the goodness, and as a result, a sharp timing distribution produces a large vertex goodness. g_{dir} is calculated by looking at how spatially uniform the PMT hits are in the azimuthal angle around the reconstructed neutrino vertex direction. The hits are ordered from 0 to 2π and compared to a uniform distribution of angles. Equation 6.5 shows how the minimum difference between the uniform distribution and the data is subtracted from the maximum difference and normalized to produce g_{dir} .

$$g_{dir} = \frac{\max_i \{\angle_{uni}(i) - \angle_{data}(i)\} - \min_i \{\angle_{uni}(i) - \angle_{data}(i)\}}{2\pi} \quad (6.5)$$

where $\angle_{\text{data}}(i)$ is the azimuthal angle of the i -th hit real PMT included in the number of hits in 50 ns. $\angle_{\text{uni}}(i) = 2\pi i / N_{50}$ is the azimuthal angle of the i -th virtual PMT hit, but only when uniform distribution of the hits is assumed. As the uniformity of the hit pattern increases, the goodness decreases.

7. Cherenkov angle θ_C

In order to estimate the Cherenkov opening angle, all the possible combinations of PMT hits of three hit PMTs in a 15 nanosecond timing window are binned. A histogram is produced of these binned angles and divided into 100 bins, and by looking at the seven neighbouring bins with the largest number of entries, peaks in the histogram are located. The middle of the seven bins is chosen to be the Cherenkov angle of the event. Figure 6.9 shows the vertex of the prompt event and three PMT hit vectors which produce the Cherenkov opening angle.




Figure 6.9: Schematic of the prompt event vertex and a triplet of independent PMT hits which make up the Cherenkov angle, taken from [12].

For relativistic electrons in water, the value of the Cherenkov opening angle is $\approx 42^\circ$, due to the relation:

$$\cos \theta_{\text{Cherenkov}} = \frac{1}{n\beta} \quad (6.6)$$

where $\beta = v/c \approx 1$ and n is the refractive index of water, 1.33. However due to other particles in the simulation, such as protons or muons, the Cherenkov cone is expected to be narrower, or if multiple leptons are present, the Cherenkov cones will be less distinct and more spread out, leading to deviations from the 42° value.

6.2.2 Comparison of BONSAI reconstruction output variables between SKDETSIM versions

The BONSAI reconstruction output variables were compared between three versions of SKDETSIM, the version used in the previous NCQE neutron capture on hydrogen only analysis, with no neutron capture on Gd implemented (black), the SKDETSIM-SKGd photon-evaporation model mentioned in the previous section (red), and the SKDETSIM SK-Gd ANNRI-Gd model (green). Figure 6.10 to Figure 6.14 shows the comparison of these models for the output BONSAI variables E_{rec} , dwall, effwall, ovaQ, and θ_C , where the y-axis shows the number of events.




Figure 6.10: Comparisons of prompt event electron reconstructed energy between versions of SKDETSIM

To ensure correct implementation of the ANNRI-Gd model, ensuring the BONSAI output variables were similar between these SKDETSIM versions was important as the gadolinium model should only effect the neutron capture in the simulation, not the output from event reconstruction of the neutrino interaction vertex. As can be seen in the SKDETSIM/SKDETSIM-SKGd BONSAI reconstruction variable comparison plots, this




Figure 6.11: Comparisons of dwall for the prompt event between versions of SKDETSIM




Figure 6.12: Comparisons of effwall for the prompt event between versions of SKDETSIM




Figure 6.13: Comparisons of ovaQ for the prompt event between versions of SKDETSIM




Figure 6.14: Comparisons of Cherenkov angle for the prompt event between versions of SKDETSIM

holds true for E_{rec} , dwall, effwall and θ_C , but not for the vertex and goodness coefficient ovaQ, where the ANNRI-Gd model differs for ovaQ between -0.05 and 0.15 compared to the SKDETSIM and SKDETSIM photon-evaporation model. To investigate this difference further, distributions of the vertex goodness and the directional goodness which make up ovaQ (according to Equation 6.3) were also checked, shown in Figure 6.13.




Figure 6.15: Comparisons of vertex goodness for the prompt event between versions of SKDETSIM




Figure 6.16: Comparisons of directional goodness for the prompt event between versions of SKDETSIM

The vertex goodness (gvtx) and directional goodness (gdir) squared comparisons are shown in Figures 6.15 and 6.16 respectively. Figure 6.15 shows a slight discrepancy between

SKDETSIM version	Value (cm)
SKDETSIM-V	113.2
SKDETSIM-SKGd (Photon evaporation model)	109.4
SKDETSIM-SKGd (ANNRI-Gd model)	111.9

Table 6.5: Value of the true neutrino vertex - reconstructed neutrino vertex distribution which encompasses 1-sigma (68%) of the number of events

the SKDETSIM versions, but not enough to warrant further investigation. In addition to checking the previous BONSAI reduction phase quantities, the distance between the true neutrino vertex from the simulation and the neutrino vertex from the BONSAI reconstruction was also checked for the different SKDETSIM versions, shown in Figure 6.17. Table 6.5 shows the value of this distribution which encompasses 1-sigma (68%) of the number of events: this value was very similar for all SKDETSIM versions.




Figure 6.17: Distance between true and reconstructed neutrino vertex for different SKDETSIM versions

Comparisons of event reconstruction output between NTag versions

To ensure that the NCQE event selection and neutron tagging could be carried out using the new NTag code, comparisons of the output BONSAI reconstruction variables between the two versions were made to ensure the validity of the reconstruction output. Figures 6.18, 6.19, 6.20, 6.21 and 6.22 shows the reconstructed energy, dwall, effwall, Cherenkov

angle and ovaQ parameters, with the legacy NTag output in black and the new NTag output in red.




Figure 6.18: Reconstructed energy (MeV) comparison

From the comparisons of the event reconstruction variables we can conclude that there is no significant variation between the way the different gadolinium implementation models in the detector simulation affect the way the prompt event is reconstructed. This makes sense as the only difference the neutron capture model should make should relate to the secondary interactions - checking that the prompt event distributions remain unchanged is a confirmation of this. Similarly, the comparisons between the two NTag versions, legacy and new show that the change in the neutron tagging algorithm didn't affect the prompt event reconstruction either.

6.2.3 NCQE event selection

Prior to applying the neutron tagging algorithm which searches for neutron candidates, events which satisfy the neutral current quasi-elastic criteria need to be selected. This selection only involves the neutrino vertex information, no information about the neutron candidates is used in the NCQE selection process.

The following cuts are applied to the Monte Carlo, in order to select the NCQE events. These include a visible energy cut, a fiducial volume cut, a low energy background cut, and a cut to exclude charged current interaction events (CCQE).




Figure 6.19: DWall (cm) comparison




Figure 6.20: Effwall (cm) comparison




Figure 6.21: Reconstructed Cherenkov angle (degrees)




Figure 6.22: Comparisons of vertex goodness for the prompt event between versions of SKDETSIM




Figure 6.23: Spectra of NCQE backgrounds where the ν_μ charged current channel is from decay electron data, whereas the other three are from Monte Carlo. A clear decrease of NC elastic events are shown after 30 MeV. Taken from [13]

Visible energy cut

The range for E_{rec} in this variable is 3.49 MeV to 29.49 MeV - the estimated kinetic energy under the hypothesis that the event is a singular electron. The upper value for this range is chosen because the background of Michel electrons from muon neutrino and muon anti-neutrino charged current interactions increase but the NCQE signal decreases above 30 MeV. This is shown in Figure 6.23, where the NC elastic (and therefore NCQE) signal decreases significantly above 30 MeV but the decay-e events and electron neutrino charged current events increase.

Radioactivity background cut

Due to radioactive impurities inside the detector material, specifically the wall of the inner detector, there is a cut involving the distance from the detector wall to the prompt interaction vertex - this is the fiducial volume (FV) cut. Events where the distance between the prompt interaction vertex and the detector wall is less than 200 cm are removed.

There are two more cuts used and these involve the distance to the inner detector wall. The variable dWall is defined as the distance from the reconstructed event vertex to the nearest inner detector wall inside the FV, and is set to dWall needing to be less than




Figure 6.24: Schematic defining the fiducial volume (FV) and the dWall and effWall variables

200 cm. A similar cut is also used where events where the distance between the prompt interaction vertex and the distance to the inner detector wall in the neutrino vertex vector direction (effWall) is less than 200 cm are removed. Figure 6.36 shows an illustration of how the variables FV, dWall and effWall are defined.

These are standard cuts applied in all Super-Kamiokande analyses in order to avoid backgrounds and when there are events where the energy region is below 6 MeV even more stringent cuts are required to further reduce background from the inner detector wall, described in the next Subsection.

Low energy background cut

The variables dwall, effwall and ovaQ are used to tune cuts in the energy region below 6 MeV. There are five energy regions with a width of 0.5 MeV used between the lower end of the visible energy cut region (3.49 MeV) and 5.99 MeV where the cuts on the dwall, effwall and ovaQ variables are optimised. Cuts are applied on the dwall, effwall and ovaQ variables and an event is only accepted if the values of dwall, effwall and ovaQ are greater than the threshold cut values. In each 0.5 MeV energy interval, these threshold values are optimised based on the T2K run period due to the beam power and detector conditions being different from run to run, especially since the Gadolinium loading occurred in the

detector. Equation 6.7 shows how the figure-of-merit (FOM) value is to be maximised for the optimisation of each cut.

$$\text{FOM} = \frac{N_{\text{sig}}}{\sqrt{N_{\text{sig}} + N_{\text{bkg}}}} \quad \left(N_{\text{bkg}} = N_{\text{bkg}}^{\text{MC}} + N_{\text{bkg}}^{\text{beam-unrelated}} \right) \quad (6.7)$$

Here N_{sig} is the number of NCQE neutrino events in the FHC Monte Carlo sample and N_{bkg} is the summation of the background events, and the FOM is calculated separately in the five energy intervals, and the optimised cut value is taken as the one which maximises the FOM. Then the optimised cut values in each energy interval are fitted with a linear function dependent on the visible energy variables (E_{rec}). Equation 6.10 gives the relation of E_{rec} to the optimised cut values for dwall, effwall and ovaQ.

$$\text{dwall } ^{\text{CUT}} = p_0^{\text{dwall}} + p_1^{\text{dwall}} \times E_{\text{rec}} \quad (6.8)$$

$$\text{effwall } ^{\text{CUT}} = p_0^{\text{effwall}} + p_1^{\text{effwall}} \times E_{\text{rec}} \quad (6.9)$$

$$\text{ova } Q^{\text{CUT}} = p_0^{\text{ovaQ}} + p_1^{\text{ovaQ}} \times E_{\text{rec}} \quad (6.10)$$

The scan regions and intervals for the dwall, effwall and ovaQ parameters for Equation 6.10 are given in [14].

Charged current event (CC) interaction cut

In order to reduce the number of charged-current events which may be mistakenly included in the NCQE selection, a cut regarding the reconstructed Cherenkov angle of the prompt event is also utilised alongside the low energy background cut, where the accepted Cherenkov angle of a prompt event (θ_C) should be greater than the threshold cut value θ_C^{CUT} where the cut value is determined by the linear equation dependent on E_{rec} as shown in Equation 6.11.

$$\theta_C^{\text{CUT}} = p_0^{\theta_C} + p_1^{\theta_C} \times E_{\text{rec}} \quad (6.11)$$

Just like for the low energy background cut values, the values of the optimised parameters in Equation 6.11 are given in [14] and are shown in Figure 6.25.




Figure 6.25: Optimised cut values for dwall (top left), effwall (top right) and ovaQ (bottom) for Run 8 FHC mode. The red lines are linear fits to the values for these distributions, where events which have values above the lines are used in the analysis [14]. The blue vertical bars are the bin widths involved in the parameter scans for each parameter set.

FHC sample	MC # ν_{det}	MC# ν_{det} fraction (%)
$\nu - NCQE$	204.1	76.6
$\bar{\nu} - NCQE$	5.6	2.1
$NC - \text{other}$	47.8	17.9
CC	8.8	3.3
Total	266.3	100

Table 6.6: FHC MC expectation values for each interaction type

6.2.4 Prompt event NCQE reduction cut plots

Before applying the NTag algorithm, either legacy or new, plots were produced of the number of neutrino events and their dependence on the reduction cut variables mentioned previously. These are shown in Figures 6.26 to 6.30. Each figure shows the corresponding plot for the previous NCQE analysis carried out with neutron tagging on hydrogen on the left (taken from the associated T2K Technical Note [17]), with the plot from this analysis on the right. Due to the FHC sample not purely consisting of neutrino and antineutrino NCQE interactions, Table 6.6 gives the expected number of neutrino events for each type of interaction including neutral current and charged current interactions.

Figure 6.26: Comparisons of stacked histograms for the E_{rec} variable between NCQE neutron tag on H analysis (left) and this analysis (right)




Figure 6.27: Comparisons of stacked histograms for the Dwall variable between NCQE neutron tag on H analysis (left) and this analysis (right)




Figure 6.28: Comparisons of stacked histograms for the Effwall variable between NCQE neutron tag on H analysis (left) and this analysis (right)




Figure 6.29: Comparisons of stacked histograms for the ovaQ variable between NCQE neutron tag on H analysis (left) and this analysis (right)





Figure 6.30: Comparisons of stacked histograms for the θ_C variable between NCQE neutron tag on H analysis (left) and this analysis (right)






Figure 6.31: Number of events plotted against number of true neutron captures (left) and number of events plotted against the time of all neutron captures (μs) (right).

6.3 Neutron tagging information and secondary selection

As mentioned previously, two neutron tagging algorithms were used in this analysis, the legacy NTag code, used in previous NCQE analyses and modified to work with a version of SKDETSIM which has gadolinium included and new NTag code which uses a slightly different neutron tagging algorithm specifically with regards to the primary and secondary selection criteria which will be discussed in later subsections.

6.3.1 True neutron tagging information

Prior to defining the primary and secondary selection criteria for each neutron tagging algorithm, it is important to produce some distributions of basic variables regarding the neutron captures that occur in the simulation, such as neutron capture time, position and number. Figure 6.31 shows the distribution for the number of neutron captures and the true capture time of the neutrons for both the legacy (black) and new (red) NTag code.

In order to classify the neutron captures on hydrogen and gadolinium separately, the energy of the gammas produced from the neutron capture were used, along with the number of gammas produced from the neutron capture. If the energy of the gamma produced is 2.22 MeV and only one gamma ray was produced from the neutron capture, the neutron capture was classified as a capture on a proton. If there are multiple gamma rays produced and if the energy of the gamma cascade is 8.5 MeV in total it is classified as a neutron capture on ^{155}Gd and if the energy of the gamma cascade is 7.9 MeV, it is classified as a neutron capture on ^{157}Gd . Distributions of the number of gammas produced from neutron capture in the simulation, and also the energy of these gammas were plotted, shown for both the legacy (black) and new (red) NTag code, shown in Figure 6.32.

Figure 6.32 shows that both NTag algorithms have the same number of gammas pro-




Figure 6.32: Number of gamma rays produced by neutron capture (left) and total energy of gamma rays produced by neutron capture (right) in the Monte Carlo

duced by neutron capture on hydrogen (shown by the peak at 2.22 MeV), and the same number of gammas for the gamma cascade produced by neutron capture on the ^{155}Gd and ^{157}Gd isotopes of gadolinium, where the modal number of gammas in the cascade for both NTag code is five. In addition to checking the number and energy of the gammas, and the number and time of true neutron captures, the neutron capture positions for the x,y and z directions were also plotted as shown in Figure 6.33.

Truth information reduction cut plots

After ensuring that the truth neutron tagging information was the same between the legacy and new NTag versions, the next step was to produce plots with the NCQE reduction cut criteria in order to see the distribution of neutrons for certain variables which satisfy the NCQE criteria. By rewriting aspects of the new NTag code to incorporate the BONSAI variables needed for the NCQE selection, the same reduction cut criteria could be applied to the new NTag code as it was to the legacy NTag code. Figure 6.34 shows the number of true neutrons plotted against true neutron capture time for the legacy and new NTag, while Figure 6.35 shows the number of true neutrons plotted against the distance between the true neutron and neutrino capture vertices for the legacy and new NTag.

With the level of $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ in the simulation being 0.026%, the number of neutron captures on hydrogen and gadolinium should be approximately equal [131]. This is shown in Figure ??, where 0.026% $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ (which is 0.01% Gd by mass in water) corresponds to 0.5 on the y-axis.

Figure 6.37 shows the the true capture time for the neutrons in the Monte Carlo seperated into captures on hydrogen and captures on gadolinium, and the distributions and the number of events look very similar, confirming this. Similarly, Figure 6.38 shows




Figure 6.33: True neutron capture x-position (cm) (top left), true neutron capture y-position (cm) (top right) and true neutron capture z-position (cm)(bottom)




Figure 6.34: Number of all true neutrons plotted against true neutron capture time for the legacy NTag (left) and the new NTag (right)




Figure 6.35: Number of all true neutrons plotted against the distance between the neutrino and neutron capture vertices for the legacy NTag (left) and the new NTag (right)




Figure 6.36: Plot of fraction of neutron captures on Gd plotted against percentage of Gd by mass in water, taken from [15].




Figure 6.37: Number of all true neutrons plotted against true neutron capture time for the new NTag, for captures on hydrogen (left) and gadolinium (right).




Figure 6.38: Number of all true neutrons plotted against the distance between the neutrino and neutron capture vertices for the new NTag, for captures on hydrogen (left) and gadolinium (right)

the distance between the neutrino interaction vertex and the true neutron capture vertex for captures on hydrogen and gadolinium. Once again the distributions are very similar, showing agreement with the equal number of captures.

6.3.2 Primary selection criteria

The rest of this Chapter focusses on analysis results from the new NTag algorithm, as this is what is currently being used by the collaboration. As input to searching for acceptable neutron candidates in the search window of 3 to 535 ns, the time of flight corrected PMT hit times is used. The reason for calculating the residual time of flight for the gamma hits is because the electrons produced from the Compton scattering of gamma rays produced by the neutron capture on hydrogen and gadolinium appear as a point-like source of Cherenkov

Criterion	Type	New
First	Timing window width	14 nsec
Second	Hit trigger and max	$7 \leq NHits \leq 400$
Third	Minimum hit separation	$\Delta t_0 \geq 200\text{nsec}$

Table 6.7: NTag primary selection criteria

radiation. Due to the differing optical path lengths that these photons have, there is a difference in PMT hit time. The difference in Cherenkov photon travel length before they hit different PMTs after the gamma rays from neutron capture Compton scatter off an electron needs to be taken into account via a time-of-flight (TOF) correction. Equation 6.12 gives the equation for the residual hit times t_i^{res} , where t_i is the hit time of the PMTs in the neutron search window and TOF_i is given by Equation 6.13, where PMT_i is the position vector of the hit PMT and VTX_ν is the position vector of the reconstructed neutrino vertex and c_{wt} is the speed of light in the medium. The reason VTX_ν is used instead of the Compton scattering vertex is because this vertex is unknown.

$$t_i^{res} = t_i - TOF_i \quad i \in \{ \text{Hit PMTs} \} \quad (6.12)$$

$$TOF_i = \frac{\left\| \overrightarrow{PMT_i} - \overrightarrow{VTX_\nu} \right\|}{c_{wt}} \quad (6.13)$$

Before the neutron candidate is passed to the secondary selection, other cuts are used to reject candidates which are not neutrons from NCQE interactions. Table 6.7 shows the three primary selection criteria. The first involves the width of the sliding window used for the neutron tagging search, which is set to 14 ns. The second is the hit trigger for the neutron candidate selection, which is set to 7 hits, which is the same for the previous NCQE hydrogen-ntag analysis, with the maximum value of the hits set to 400. Third, the minimum time separation between the gamma hits is set to 200 ns - the reason for this is to avoid double counting the same hit from the neutron capture candidate.

One of the benefits of the addition of $Gd_2(SO_4)_3 \cdot 8H_2O$ is that the higher visible energy improves the neutron capture vertex resolution. Figure 6.39 shows the distance between the true and reconstructed neutron capture vertices for neutron capture in water Monte Carlo (taken from [16]) on the left, and from the Monte Carlo in this analysis on the right.




Figure 6.39: Distance between true and reconstructed neutron capture vertex in water Monte Carlo [16] (left) and from this analysis (right). The pink arrow on the left plot and the dashed blue line on the right plot shows the 68th percentile of the distributions.

It is clear that the resolution has improved, being reduced from 132.4 cm prior to the addition of gadolinium to 111.5 cm in this analysis.

After finding acceptable neutron candidates it is once again worth looking at the NCQE reduction plots which show distributions of the number of neutron captures, especially distributions that would differ depending on whether the neutron was captured on hydrogen or gadolinium. This is shown in Figure 6.42 which shows the number of neutron candidates plotted against the reconstructed Cherenkov angle of hits from neutron captures for both hydrogen and gadolinium (bottom), and then hydrogen (top left) and gadolinium (top right).

Figure 6.42 clearly shows that the reconstructed Cherenkov angle skews higher for neutron captures on gadolinium compared to neutron captures on hydrogen due to the cascade of multiple gammas causing the Cherenkov angle to be reconstructed with a large opening angle. This is something paralleled when looking at the neural network input variables later on in the Chapter. Examining the distributions of neutron captures that have been classified as a true neutron signal is also important, and similarly to Figure 6.34 and Figure 6.35, NCQE reduction plots have been produced for neutron capture time and distance between neutrino interaction vertex and neutron capture vertex, but this time, for tagged signal neutrons. These are shown in Figure 6.43.

Figure 6.43 shows that for both distributions the number of tagged neutron captures is a little less than 50% of the distributions shown in Figure 6.34 and Figure 6.35. Comparisons




Figure 6.40: Number of candidate neutrons plotted against the reconstructed Cherenkov opening angle from hits from neutron captures on H




Figure 6.41: Number of candidate neutrons plotted against the reconstructed Cherenkov opening angle from hits from neutron captures on Gd




Figure 6.42: Number of candidate neutrons plotted against the reconstructed Cherenkov opening angle from hits from neutron captures on both H and Gd




Figure 6.43: Number of tagged signal neutrons plotted against neutron capture time (left) and distance between neutrino interaction vertex and neutron capture vertex (right)




Figure 6.44: Number of tagged signal neutrons plotted against neutron capture time separated into captures on hydrogen (left) and gadolinium (right).




Figure 6.45: Number of tagged signal neutrons plotted against distance between neutrino interaction vertex and neutron capture vertex separated into captures on hydrogen (left) and gadolinium (right).

between the number of true neutron captures and the number of neutron captures identified as signal can give you the efficiency of the NTag algorithm, calculated later on in this Chapter. Figure 6.44 gives the number of tagged neutrons in the left plot of Figure 6.43 but separated into neutron captures identified as captures on hydrogen (left) and those captured on gadolinium (right). Figure 6.45 does the same but for the distance between the neutrino interaction vertex and the neutron capture vertex.

Figure 6.44 and Figure 6.45 shows that the number of tagged signal neutron captures are a lot less for neutron captures on hydrogen than gadolinium for the truth distributions, showing that the neutron tagging algorithm is much more likely to identify neutron captures on hydrogen as noise, due to the low number of tagged neutron captures on hydrogen showing a lower efficiency, verified in Table 6.8. However, the neutron tagging algorithm is

much more likely to identify true neutron captures on gadolinium as signal, and doing so with a high efficiency, again verified in Table 6.8, improving the overall tagging efficiency of the algorithm.

6.3.3 Secondary selection criteria

Due to the contamination of background events still present amongst the true neutron events after primary selection, a neural network (NN) is used to efficiently remove these background events, while trying to maximise the number of true neutron events. The output of the NN is used to indicate how likely an event is to be a signal/background candidate. Each of the candidates selected during the primary selection process has an associated reconstructed Compton scattering vertex calculated for it. In order to produce residual hit times that are less spread out than TOF-corrected hits towards the neutrino vertex, the TOF-corrected hits towards the Compton scattering vertex are used instead. The aim of searching for the Compton scattering vertex is to use a method by which the standard deviation of the residual times of the hits is minimised. Therefore the Compton scattering vertex n_{VTX} is defined as in Equation 6.14, where r is a trial vertex and t_i^{res} is the TOF-corrected hit time.

$$n_{VTX} = \underset{r}{\operatorname{argmin}} \sqrt{\frac{1}{NHits} \sum_{i=1}^{NHits} [t_i^{\text{res}}(\vec{r}) - \langle t^{\text{res}}(\vec{r}) \rangle]^2} \quad (6.14)$$

By considering a set of trial vertices on a cubic grid and calculating the standard deviation of the residual hit times the minimisation process is performed. After this minimization cycle, a new cycle is performed on a finer and smaller grid and carries on until a certain level of precision is reached.

When the Compton scattering vertex from neutron capture is found by this method, 12 variables which describe different aspects of the neutron candidate are calculated, using NTAG. For each of the neutron candidates the vector of these variables are computed and fed into the neural network and this produces an output value which is between 0 and 1. These variables relate to different features regarding categorising hits from neutron capture on Gd or H, including the number of the hits from neutron capture, the isotropy of these hits, the Cherenkov angles of these hits and the position of the neutron vertex in the detector when capture occurs. The purpose of these variables is to tag the neutrons and better separate tagged neutrons from accidentals and to distinguish when a capture occurs on hydrogen or gadolinium. A description of these variables is given below.

NTag variables

The following twelve variables are fed into the TMVA neural network model for the secondary selection, and the TMVA reader and the input variables to get the classifier output:

NHits

This is defined as the number of hits in a sliding timing window for the neutron candidate, however instead of this being set to a value of 10 nsec as it was for the neutron capture on hydrogen NCQE analyses, this was increased to 14 nsec in order to accomodate for the increased number of hits from gamma cascades from neutron capture on gadolinium.

N200

This is the number of hits within -100 ns and +100 ns from the fitted time relative to the trigger. Signal events produce PMT hits which are close in time, while background events are more spread out, therefore alongside having the NHits variable, N200 is also used to create a wider timing window around the capture time of the candidate event. This spread of background events is clearly visible for the N200 variable both in Figure 6.47 and Figure 6.48: the distributions associated with neutron captures on hydrogen and gadolinium (red and green lines respectively) have distinct peaks, while the background events (magenta) have a more diffuse distribution.

N1300

This is the number of PMT hits in a 1300 ns timing window, specifically between -520 ns and +780 ns from the fitted time relative to the trigger. Similarly to N200 this is a much broader timing window than NHits.

TRMS

This calculates the standard deviation of the time-of-flight corrected PMT hit times from NHits. The spread of hit times varies between signal and background events, due to background events having a larger residual time spread than signal events: this is shown for the TRMS plot in Figure 6.47.

DWall

DWall gives the difference from the fitted neutron vertex to the nearest wall in cm. This variable is used because the reconstructed vertex of background events are more likely to be near the inner detector wall, and therefore DWall can help distinguish background from signal events. As shown in Figure 6.47 and Figure 6.48, the fitted neutron vertex of the background events and signal events follow this pattern, with background events being close to the detector wall and signal events away from it.

DWallMeanDir

This gives the distance from the fitted neutron vertex to the wall in the direction of the mean of the PMT hits for the neutron candidate in cm. The reason this variable is used alongside DWall is that there is also the aspect of the directionality of the hits to consider. Background hits do not have directionality due to them being a product of noise hits but signal events do have directionality due to these hits being produced by Compton scattered electrons originating from gammas produced by neutron capture. This is shown in the DWallMeanDir distribution in Figure 6.47, where the background events have a larger spread than signal events.

OpeningAngleMean

The next set of variables are related to the Cherenkov angle produced from a neutron candidate event: the first of these is OpeningAngleMean. This calculates the mean of all possible opening angles calculated from 3 PMT hits from the neutron captures. Signal events which have PMT hits originating from Compton scattered electrons from 2.2 MeV gamma rays from neutron captures on hydrogen have Cherenkov opening angles which are centered around 42°, while neutron captures on gadolinium produce multiple gamma rays which would skew the value of OpeningAngleMean to be centered around higher values. This is reflected in Figure 6.47, where the background events have a slightly larger spread and therefore not such a strict angular dependence.

OpeningAngleStdev

This is the standard deviation of all possible opening angles calculated from 3 PMT hits from the neutron captures. This variable emphasises what is seen in the OpeningAngleMean distribution, where background events have a larger spread than signal events, shown in Figure 6.47 and Figure 6.48.

OpeningAngleSkew

This is the skewness of all possible opening angles from 3 PMT hits from the neutron captures, calculated using

$$\tilde{\mu}_3 = \frac{\sum_i^N (X_i - \bar{X})^3}{(N - 1) * \sigma^{1.5}} \quad (6.15)$$

where X_i is the hit PMT, \bar{X} is the mean of the 3-hit vector, N is the size of the vector of PMT hits, and σ is the standard deviation of the PMT hits. Signal events are shown to have a more skewed opening angle distribution than background events, especially if they are a neutron capture on gadolinium event.

MeanDirAngleMean

This variable takes the mean of angles between the direction of each hit and the mean of the direction of these hits. Again this will be generally shifted to larger values for neutron captures on gadolinium compared to captures on hydrogen, shown in Figure 6.47 and Figure 6.48.

MeanDirAngleRMS

This variable is simply the RMS of angles between each hit directon and mean hit direction, here we can see from Figure 6.47 that background events will have a larger spread for this variable compared to signal events.

β_l

This variable is used because the signal and background events have a variation in the angular distribution of the hit PMTs. The β_l variable defines the isotropy of the Cherenkov hits according to:

$$\beta_l = \frac{2}{N_{Hits} (N_{Hits} - 1)} \sum_{i \neq j} P_l (\cos \theta_{ij}) \quad (6.16)$$

where P_l are the Legendre polynomials of order l and θ_{ij} is the angle between hit PMTs relative to the neutron capture vertex. $\beta_1, \beta_2, \beta_3, \beta_4, \beta_5$ are all used as input variables to the NN in order to investigate the geometry of the neutron candidate hits related to spherical harmonics. For the sake of brevity only β_1 and β_5 are shown here in Figure 6.47 and Figure 6.48. Because this variable is related to the angular distribution, just like the previous angle related variables, background events have a larger spread compared to signal events.

Figure 6.46 shows the neural network likelihood signal between 0 and 1 (TagOut), for all events, neutron capture on hydrogen candidates and neutron capture on gadolinium candidates. The blue arrow shows the cut on this variable (0.7), so that a neutron candidate that has been analysed is determined to be a signal neutron candidate if its value of TagOut greater than or equal to 0.7, and background if it is less than 0.7. The value of 0.7 was chosen due to the amount of background events being sufficiently low enough past this value, while ensuring a substantial amount of neutron capture candidate signals on hydrogen and gadolinium.

Seeing the signal from neutron captures on hydrogen and gadolinium pre and post neural network is also important along with the background events: these are shown in Figure 6.47 and Figure 6.48.




Figure 6.46: Neural network output signal likelihood. Total signal neutron capture candidates are shown in the distribution with a blue line, whereas candidates that capture on hydrogen are shown in red, and gadolinium in green, and the distribution of background candidates are shown in pink. The dashed blue line shows the cutoff value of TagOut, where a neutron candidate is determined as being signal if the value of TagOut ≥ 0.7 and background if TagOut < 0.7 .




Figure 6.47: Number of events plotted against various neural network input variables prior to the neural network




Figure 6.48: Number of events plotted against various neural network input variables after neural network output

Figure 6.46 shows that the signal likelihood output is closer to 0 for far more neutron capture on hydrogen candidates than neutron capture on gadolinium candidates - this is also shown in Figure 6.47 and Figure 6.48, where the peaks for the neutron capture on hydrogen candidates are significantly more reduced in the post-NN plots than in the pre-NN plots, showing that noise events were more likely to be misidentified as neutron captures on hydrogen. These distributions also show that the value of NHits and also N200 for a neutron capture candidate is more likely to be greater for neutron candidates which are candidates on gadolinium than on hydrogen. Additionally, these plots also show that the opening Cherenkov angle related distributions were skewed towards greater values for gadolinium capture candidates than for hydrogen, due to the presence of the hits from the gamma cascade associated with neutron captures on gadolinium.

After investigating the neutron candidates pre and post neural network to see the candidate signal distributions, it makes sense to evaluate how efficient the neutron tagging algorithm is. There are three stages at which the efficiency is calculated, pre-NN selection (i.e. searching all the truth candidates prior to NN selection), after the NN classification (to show the efficiency of the classifier), and then the combination of these (the total tagging efficiency). Equation 6.17 shows how these three stages, ε_{Pre} , ε_{NN} and $\varepsilon_{\text{NTag}}$ are defined.

$$\begin{aligned}\varepsilon_{\text{Pre}} &= \frac{\# \text{ of truth candidates at pre - selection}}{\# \text{ of truth neutrons}} \\ \varepsilon_{\text{NN}} &= \frac{\# \text{ of tagged truth neutrons}}{\# \text{ of truth candidates at pre-selection}} \\ \varepsilon_{\text{NTag}} &= \varepsilon_{\text{Pre}} \times \varepsilon_{\text{NN}} = \frac{\# \text{ of tagged truth neutrons}}{\# \text{ of truth neutrons}}\end{aligned}\quad (6.17)$$

The values of these efficiencies and their associated statistical uncertainties are shown in Table 6.8, and are calculated separately for captures on hydrogen and gadolinium and for both. The systematic uncertainty on these tagging efficiency values are calculated in Chapter 7.

These efficiencies are as expected, with the efficiency of neutrons captured on gadolinium being much greater than that of captures on hydrogen, due to the gamma cascade making it better able to be differentiated than from the 2.2 MeV from the neutron capture on hydrogen. Making comparisons to tagging efficiencies calculated in prior analyses where neutrons are captured solely on hydrogen ([17], [23]), where the total tagging efficiency is evaluated at around 20%, the efficiency of 50% evaluated in this analysis is a marked improvement in the efficiency of the tagging algorithm.

	Pre-selection efficiency
H + Gd	$50.00 \pm 0.10\%$
H	$13.43 \pm 0.19\%$
Gd	$84.87 \pm 0.10\%$
	NN classification efficiency
H + Gd	$80.30 \pm 0.21\%$
H	$18.96 \pm 1.26\%$
Gd	$89.64 \pm 0.26\%$
	Total efficiency
H + Gd	$40.16 \pm 0.21\%$
H	$2.55 \pm 0.16\%$
Gd	$76.17 \pm 0.20\%$

Table 6.8: NTag pre-selection, NN classification and total efficiencies

However, as the errors on the tagging efficiencies in Table 6.8 are purely statistical (i.e. produced from the number of neutrons in the MC), it is beneficial to do a comparison with an efficiency measurement from actual neutron capture data. In order to assess the validity of the efficiencies from the Monte Carlo, a comparison of the efficiency with data taken from an Am/Be + 8BGO neutron source is used. As mentioned in Chapter 3, the Am/Be + 8BGO source produces a prompt 4.4 MeV gamma ray along with a neutron, with the same prompt and delay signal pattern as NCQE interactions, and similarly to the MC, a timing distribution of hits relative to the 4.4 MeV trigger can be produced for the Am/Be + 8BGO data. Figure 6.49 shows the Am/Be source container and the BGO scintillator that it is enclosed within, and Figure 6.50 shows the distribution of hits (NHits) within the 14 ns sliding timing window.

As shown in Figure 6.51, the efficiency of the neutron capture changes relative to the DWall cut value, and as a result it was advisable to check the efficiency of neutron capture using Am/Be + 8BGO data at different positions in the detector. Table 6.9 shows the runs and positions (x,y,z) of Am/Be + 8BGO data used in this analysis.

First, comparison was done between the MC and the Am/Be data from Run 85622, the 1 hour measurement taken in the central (0,0,0) source position, by looking at the timing distribution from the 4.4 MeV trigger signal. The same neutron tagging algorithm



Figure 6.49: Am/Be + 8BGO source: the Am/Be source is housed at the centre of the 8 BGO crystals, which are $2.5 \times 2.5 \times 2.5$ cm each and themselves placed inside an acrylic case. The edge of each crystal is cut so there is an inner place for the Am/Be source to be kept




Figure 6.50: Distribution of hits from Am/Be + 8 BGO data within the 14 ns sliding timing window

Run	Data taking time	Position (m)
85622	1 hour	(0, 0, 0)
85617	30 min	(0, 0, +12)
85586	30 min	(-12, 0, 0)

Table 6.9: Am/Be data run numbers, data taking time and Am/Be source positions




Figure 6.51: Efficiency of NTag plotted against DWall cut value

was used as for the tagging of neutrons from the MC, with the exact same primary and secondary selection criteria. In addition to this, the following event cuts were used in order to select neutron capture events using this data: the total event charge deposit for the inner detector PMTs to be between 850 and 1150 photoelectrons, the time difference from the previous event should be greater than 1 millisecond, and the number of outer detector PMT hits should be less than 10. In order to find the efficiency of the neutron captures and to find the fitted background with this Am/Be data, an exponential fit was made to the timing distribution (shown in Equation 6.18), and this is shown in Figure 6.52 by the red curve. Similar fits were made for the Am/Be source data taken for the (0,0,+12 m) and (-12 m,0,0) positions.

$$\text{Fit equation: } Ae^{-t/\tau} + B \quad (6.18)$$

In Equation 6.18, t is the time from the event trigger in microseconds, τ is the exponential time constant and B is the background.

Table 6.10 shows the value of τ for each of these positions, along with the χ^2/ndf




Figure 6.52: Fitted time relative to the trigger signal with exponential fit (red) for the Am/Be data taken in the centre position (0,0,0)




Figure 6.53: Fitted time relative to the trigger signal with exponential fit (red) for the Am/Be data taken at (0,0,+12)




Figure 6.54: Fitted time relative to the trigger signal with exponential fit (red) for the Am/Be data taken at (-12,0,0)

value for the exponential fit and the value of the neutron capture efficiency calculated from the Am/Be data at each of these positions. Equation 6.19 shows the method by which the efficiency for the neutron capture on Am/Be data is calculated, by subtracting the number of fitted background events from the number of tagged neutron capture events, and dividing this value by the total number of events. Here N is the number of neutron captures, B is the fitted constant background value, and NTag TMAX and NTag TMIN are the end and start times of the neutron tagging algorithm.

$$\text{Efficiency} = \frac{(N - (B \cdot \text{no. of bins} \cdot (\text{NTag TMAX} - \text{NTag TMIN}) / (\text{fit time range})))}{\text{no. of events}} \quad (6.19)$$

This level of variation for the time constant is within normal limits, especially considering the associated errors, and the χ^2/ndf values for each shows that the exponential fit to the data is good. Figure 6.55 shows the equivalent fitted time from the prompt event for the NCQE MC, which has a corresponding time constant value of $115.6 \pm 0.8 \mu\text{s}$, and a neutron tagging efficiency, as shown in Table 6.8 of 40.2%: these values are in good agreement with the values shown in Table 6.10.

Position (m)	(τ) value (μs)	B	χ^2/ndf	Efficiency (%)	No. tagged neutrons
Centre (0, 0, 0)	114.8 ± 2.5	49.3 ± 3.6	1.01	40.7	15082
(0, 0, +12)	118.3 ± 3.5	19.9 ± 2.6	1.27	39.4	7991
(-12, 0, 0)	109.6 ± 3.7	21.7 ± 2.2	1.17	40.7	6438

Table 6.10: Am/Be time constant value and efficiency values along with the χ^2/ndf value of the exponential fit, the value of the background pedestal (B) events and the number of tagged neutrons from the Am/Be source at different positions




Figure 6.55: Fitted time relative to the trigger signal with exponential fit (red) for the NCQE MC

In conclusion, the work in this chapter involved investigating NCQE interactions via looking at the distributions of neutrons using Monte Carlo simulations post the addition of $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ to the Super-Kamiokande detector. Previous NCQE analyses have used pure water based Monte Carlo simulations, however my analysis extended beyond that due to the inclusion of gadolinium in the detector simulator, with neutron captures on it being modelled by the previously unused ANNRI-Gd model. Comparisons of prompt event reconstruction were carried out between pure-water and gadolinium simulation to ensure minimal changes to the prompt event as only the neutron capture in the simulation should be affected. Additionally, my analysis was the first to use a new NTag algorithm for NCQE interactions and comparisons between the legacy and new NTag algorithm were done to ensure that prompt event reconstruction and neutron truth information were consistent between the two algorithms, both prior to and after NCQE sample selection. The new NTag algorithm primary selection criteria were defined along with the algorithm method of neutron capture vertex reconstruction, and a definite improvement to the neutron capture vertex resolution in MC was seen as a result of the addition of gadolinium to the simulation. To better improve sensitivity to signal events and to reduce background events an artificial neural network was used on neutron candidates that passed the primary selection process. These variables were related to the number of hits, neutron capture vertex position, residual hit time and angular distribution. For many of these variables background events had a distribution that differed greatly from signal events, as well as neutron capture on hydrogen events varying from neutron capture on gadolinium events, and being able to better isolate these different types of captures was interesting. The efficiency of the neutron tagging algorithm was also calculated both before and after the neural network, with the neutron captures on gadolinium having a greater efficiency as expected.

Finally in order to validate the efficiency of the NCQE MC, comparisons were made with Am/Be + 8BGO calibration data. By comparing the timing distributions fitted with an exponential, the neutron capture efficiency was calculated for the Am/Be + 8BGO data at different positions in the tank, with the values for the time constant and the efficiencies being very compatible with the NCQE MC, proving the efficiencies to be valid.

Chapter 7

Systematic uncertainty calculations

“I made an error in my computations.”

“Oh? This could be an historic occasion.”

Mr. Spock and Dr Leonard H.
“Bones” McCoy, Star Trek: TOS
S1E19 Tomorrow Is Yesterday (1967)

7.1 Introduction

Determining the systematic uncertainties on the neutron tagging efficiency is important, because even though the value has been validated against Americium-Beryllium calibration data there are still sources of systematic uncertainty that need to be taken into account. Due to the neutron tagging algorithm using the reconstructed neutrino interaction vertex in order to find neutron candidates, it means that there is an association between the neutrino interaction vertex and the neutron capture vertex which is introduced into the neutron tagging efficiency. This is utilised when calculating the systematic uncertainties stemming from secondary interactions (SI), shown later in this Chapter. Therefore uncertainties involving the neutrino interactions, such as neutrino interaction cross section uncertainties and the uncertainty stemming from neutrino flux are calculated. Uncertainties in how particle interactions occur in the simulation are also calculated such as pion

final state and secondary interaction uncertainties, nucleon final state interaction and secondary interaction uncertainties and uncertainties on how pions and muons are captured upon ^{16}O . There are also uncertainties stemming from the detector itself which need to be taken into account, such as the uncertainty in PMT gain, detector response from neutrino interaction uncertainties and uncertainties from gamma production from neutron capture detector response.

7.2 Systematic uncertainty calculation methodology

Systematic uncertainties are calculated in one of two ways: MC re-weighting or MC regeneration. In the MC-reweighting approach, weights are applied to a quantity and the tagging efficiency of the re-weighted MC is extracted. The general methodology is to have the input of a model, defined by a set of parameters, and to vary them one by one and then calculate the reweighted tagging efficiencies. The set of relative discrepancies δ_i are computed from this set of reweighted tagging efficiencies T_i and the nominal tagging efficiency T_{nom} using Equation 7.1.

$$\delta_i = \frac{T_i - T_{\text{nom}}}{T_{\text{nom}}} \quad i \in \{ \text{parameters} \} \quad (7.1)$$

These relative discrepancies δ_i are used to calculate the one individual discrepancy $\delta_{\text{reweighted}}$ that would describe the final deviation from the nominal tagging efficiency T_{nom} due to the systematic error. The parameter $\delta_{\text{reweighted}}$ describes the model which has been produced through 1σ variations of these parameters, therefore the final probability distribution function which describes the deviation from the nominal MC has an assumed Gaussian distribution with the standard deviation being equal to $\delta_{\text{reweighted}}$.

The other method of estimating a systematic error on the tagging efficiency is Monte Carlo regeneration. This method is used when a single variable is changed, instead of the entire parameter space as with MC re-weighting. Monte Carlo regeneration involves changing a parameter and then re-producing the entire Monte Carlo, and then recalculating the associated tagging efficiency. The deviation of this re-generated Monte Carlo tagging efficiency from the nominal Monte Carlo tagging efficiency is then calculated using Equation 7.1.

The list of systematic errors that affect the tagging efficiency are shown in Table 7.6.

7.2.1 Gamma ray detector response

As mentioned previously, the Americium/Beryllium (Am/Be) source produces a prompt 4.4 MeV gamma ray along with a neutron via Equation 7.2.



In Chapter 6, in order to validate the neutron tagging efficiencies calculated, the tagging efficiency of neutron captures from Am/Be + 8BGO data were also calculated and compared to the Monte Carlo prediction. These efficiencies are shown in Table 6.10 and it is important to understand the errors stemming from the Am/Be + 8BGO neutron capture efficiencies as well. The systematic uncertainties in this Chapter are evaluated by calculating the difference between the nominal tagging efficiency and the tagging efficiency arising from a different process, either a different type of simulation, a different model, or in the case of this uncertainty, a difference in the source of neutrons for neutron capture. Equation 7.1 shows how this systematic is quantified; where δ_i is the fractional discrepancy arising from variation in tagging efficiency, T_i is the neutron tagging efficiency from the Am/Be + 8BGO data, and T_{nom} is the nominal tagging efficiency of the NCQE MC.

However, due to Table 6.10 showing three neutron capture efficiencies for the Am/Be data dependent on position, it makes sense to calculate the deviation of each of these from the nominal, using Equation 7.1 where i denotes the position of the Am/Be source. Equation 7.3 gives the total deviation of the Am/Be tagging efficiency from the nominal, i.e. the total detector response systematic.

$$\delta_{AmBe}^2 = \frac{\delta_{AmBe}^{Centre^2} + \delta_{AmBe}^{+12z^2} + \delta_{AmBe}^{-12x^2}}{3} \tag{7.3}$$

7.2.2 Neutrino beam flux uncertainty

The uncertainty on neutrino beam fluxes can be evaluated by looking at the dependence of the tagging efficiency on the flux variations. The beam fluxes for the four flavour modes ($\nu_e, \bar{\nu}_e, \nu_\mu, \bar{\nu}_\mu$) have the fractional uncertainties given for each mode, FHC and RHC. The binned uncertainties are shown in Figure 7.1, and the fractional error on the flux (y-axis) is given by the difference between the replica-target tuned flux and the nominal flux divided by the nominal flux [132]. The replica tuned flux predictions the uncertainties are derived from were simulated with 1000 JNUBEAM files and the fluxes for Runs 1-9d are combined

as shown in Equation 7.4:

$$\Phi_{\text{combined}}^{\text{SK}} = \frac{1}{N_{\text{P.O.T. total}}^{\text{SK}}} \times \sum_{\text{run } i} N_{\text{P.O.T. run } i}^{\text{SK}} \times \Phi_{\text{run } i}^{\text{SK}} \quad (7.4)$$

Each individual bin for the flux is increased/decreased by its error, the Monte Carlo re-weighting method is then used to extract the tagging efficiency for each flux bin, and Equation 7.1 is used to calculate the fractional uncertainty.

Figure 7.2 shows the fractional errors calculated from the reweighted Monte Carlo, with the red bars showing the -1σ variation and the blue bars showing the $+1\sigma$ variation. Table 7.6 contains the value for the total uncertainty resulting from the neutrino beam flux, which was calculated using Equation 7.5, where the maximum value between the increased and decreased discrepancy is taken and summed over to produce the final neutrino flux beam uncertainty. Although there are known correlations between the flux parameters, these are not taken into account, because the impact on the neutron tagging efficiencies is extremely small [16].

$$\delta_{\nu \text{ flux}} = \sum_{i \in \{ \text{bins} \}} \max [|\delta_i(+\sigma)|, |\delta_i(-\sigma)|] \quad (7.5)$$

7.2.3 Neutrino cross section uncertainty

A group of default neutrino cross section values are used to make up the nominal Monte Carlo from which the tagging efficiency is calculated. The values of the parameters that determine the cross sections are shown in Table 7.1. Each of the parameter values relate to a specific interaction type and are either a normalisation parameter or a parameter which shows a kinematic dependence. These have been taken from the NIWG model and uncertainties for 2017 oscillation analysis [21].

For charged current quasi-elastic interactions, the uncertainty is described by the Fermi momentum of the oxygen nucleus, (p_F^O), the binding energy of the oxygen nucleus, (E_B^O) and the axial mass M_A^{CCQE} . The axial mass for CCQE interactions relates to the axial form factor which along with vector form factors is proportional to the cross section of the interactions. For neutrino interactions with correlated nucleons (2p2h), an overall normalisation parameter takes the uncertainty of these interactions into account. For *CC*




Figure 7.1: Fractional uncertainties of beam fluxes, taken from [17], for FHC mode.

and $NC1\pi$ interactions, the uncertainty is described by the isospin background, the axial form factor C_{A5}^{RES} which just like for CCQE interactions relates to the axial mass M_A^{RES} . For neutral current and charged current interactions (both elastic and inelastic) there are normalisation parameters and energy dependent parameters for the uncertainty to take into account. Finally, for charged current interactions with electron neutrinos, the braking radiation from the lepton in the final state is also considered when calculating the uncertainty and is treated using a normalisation parameter.

The Monte Carlo re-weighting method is used to reweight the nominal Monte Carlo on an event by event basis with each parameter value being increased and decreased by its uncertainty, where the weights applied are produced by T2KReWeight v1r23, and for each reweighted Monte Carlo the equivalent tagging efficiency value is extracted. Equation 7.1 shows how the fractional discrepancies are extracted from the nominal and reweighted




Figure 7.2: Tagging efficiency fractional uncertainties caused by neutrino beam flux discrepancies associated with neutrino energy in the 0.1 - 10 GeV range. From left to right the sections in this plot are comprised of the beam flux elements of $(\nu_e \bar{\nu}_e \nu_\mu \bar{\nu}_\mu)$ respectively.

tagging efficiency values. Just as with the flux parameters, there are known correlations between the cross-section parameters, but due to the impact on the neutron tagging efficiency being very small these have been ignored.

Figure 7.3 shows the reweighted Monte Carlo fractional uncertainty plotted for the FHC sample. Since this sample contains a lot of NCother interactions, the uncertainty for this interaction type is greater than for the others, however compared to the rest of the systematics in this Chapter, the neutrino cross section uncertainty is very small.

Parameter	Interaction	Type	Value
p_F^O	CCQE	^{16}O Fermi momentum	$225 \pm 31\text{MeV}/c$
E_B^O	CCQE	^{16}O binding energy	$27 \pm 9\text{MeV}$
M_A^{CCQE}	CCQE	Axial mass	$1.2 \pm 0.41\text{GeV}/c^2$
$2p2h$	2p2 h	Normalization par.	1.0 ± 1.0
C_{A5}^{RES}	CC and NC1 π	Axial form factor	1.01 ± 0.12
M_A^{RES}	CC and NC1 π	Axial mass	$0.95 \pm 0.15\text{GeV}/c^2$
BG_A^{RES}	CC and NC1 π	I = 1/2 continuum background	1.3 ± 0.2
CC other	CC other	E-dependent par.	0.0 ± 0.4
CC elastic	CC elastic	Normalization par.	1.0 ± 0.3
NC other	NC other	E-dependent par.	1.0 ± 0.3
NC elastic	NC elastic	Normalization par.	1.0 ± 0.3
FSe ⁻ -Bremsstrahlung	CC ν_e	Normalization par.	1.00 ± 0.03

Table 7.1: Neutrino cross section parameters. Taken from [20] and [21].




Figure 7.3: Tagging efficiency uncertainty caused by the cross-section parameter variations for the FHC mode

7.2.4 Pion final state interaction (FSI) and secondary interaction (SI) uncertainties

Even though this is an analysis concerned with neutral current quasi elastic interactions, pion events are a significant contribution to the background, and as a result it is important to examine the pion interaction uncertainties both for final state interactions and secondary interactions as their trajectories span the detector.

The neutrino-nucleus interaction simulator used in this analysis (NEUT) handles pion final state interactions and secondary interactions using a cascade model. This cascade model contains parameters which will have uncertainties on them and these will be transferred to a possible change in the tagging efficiency.

Depending on the momentum of the pions, different interaction types occur in the model. For pions with a momentum less than 500 MeV, the interactions in place are absorption (ABS), quasi-elastic scattering (QE) and charge exchange (CX).

Absorption occurs when the incident pion is absorbed by the nucleus and no pions remain in the final state. Quasi-elastic (QE) scattering occurs when there is only one pion observed in the final state and it has the same charge as the incident beam. Charge exchange occurs when the charged pion interacts with the nucleus and a single π_0 can be seen in the final state.

For pions with a momentum of greater than 500 MeV, a different set of interactions are used. Inelastic interactions (INEL) can now produce hadrons and replace absorption processes, but quasi-elastic scattering (QEH) and charge exchange (CXH) will still occur. The final state interaction parameters and the pion momentum range they are used in can be seen in Table 7.2. Each parameter scales the relevant very small probability of the charged pion interaction at every stage of the intra-nuclear cascade, aside from the parameter for charge exchange which scales only the fraction of low momentum QE scattering.

A set of parameter variations which determine a surface in parameter space have been estimated by pion scattering experiments, the values for which are shown in Table 7.3. The 1σ surface has been explored using the nominal Monte Carlo re-weighting method and the analogous tagging efficiency uncertainty is shown in Equation 7.1, and the uncertainty stemming from the models shown in Table 7.3 is shown in Figure 7.4

The pion FSI/SI uncertainty is then calculated using Equation 7.6, which gives the

Parameter	Description	Momentum Region (MeV/c)
f_{ABS}	Absorption	< 500
f_{QE}	Quasi-elastic scatter	< 500
f_{CX}	Single charge exchange	< 500
$f_{\text{QE}H}$	Quasi-elastic scatter	> 500
$f_{\text{CX}H}$	Single charge exchange	> 500
f_{INEL}	Hadron ($N + n\pi$) production	> 500

Table 7.2: Table showing the pion final state interaction parameters in NEUT and the pion momentum range they are used in, taken from [22]

standard deviation of the fractional uncertainties for each model.

$$\delta_{\pi fsi/si} = \sqrt{\frac{\sum_i (\delta_i - \bar{\delta})^2}{15}} \quad \bar{\delta} = \frac{1}{16} \sum_i \delta_i \quad (7.6)$$




Figure 7.4: Tagging efficiency fractional uncertainty caused by the variation in the FSI/SI model parameters for the FHC mode

7.2.5 Nucleon final state interactions

Uncertainties regarding the nucleon final state interactions can change the number of nucleons knocked out of ^{16}O , therefore how the tagging efficiency is changed due to the variation

Set	ABS	QE	CX	INEL	QE _H	CX _H
Nominal	1.1	1.0	1.0	1.0	1.8	1.8
	0.7	0.6	0.5	1.5	1.1	2.3
	0.7	0.6	1.6	1.5	1.1	2.3
Hadron production Up	1.6	0.7	0.4	1.5	1.1	2.3
	1.6	0.7	1.6	1.5	1.1	2.3
	0.6	1.4	0.6	1.5	1.1	2.3
	0.7	1.3	1.6	1.5	1.1	2.3
	1.5	1.5	0.4	1.5	1.1	2.3
	1.6	1.6	1.6	1.5	1.1	2.3
	0.7	0.6	0.5	0.5	2.3	1.3
	0.7	0.6	1.6	0.5	2.3	1.3
	1.6	0.7	0.4	0.5	2.3	1.3
Hadron production Down	1.6	0.7	1.6	0.5	2.3	1.3
	0.6	1.4	0.6	0.5	2.3	1.3
	0.7	1.3	1.6	0.5	2.3	1.3
	1.5	1.5	0.4	0.5	2.3	1.3
	1.6	1.6	1.6	0.5	2.3	1.3

Table 7.3: Pion FSI/SI model parameter nominal value and variations grouped according to inelastic hadron production value, taken from [22].

Abbreviation	Description of uncertainty	Fractional uncertainty
x_{mfp}^N	Nucleon mean free path (total rescattering probability)	$\pm 20\%$
x_{cex}^N	Nucleon charge exchange probability	$\pm 50\%$
x_{el}^N	Nucleon elastic reaction probability	$\pm 30\%$
x_{inel}^N	Nucleon inelastic reaction probability	$\pm 40\%$
x_{abs}^N	Nucleon absorption probability	$\pm 20\%$
x_π^N	Nucleon pion-production probability	$\pm 20\%$

Table 7.4: Nucleon final state interaction parameters of the hA model executed inside GENIE.

in nucleon final state interactions needs to be investigated. This uncertainty is extracted using GENIE, a Monte Carlo event generator which contains the INTRANUKE (hA) intranuclear transport model [133]. The uncertainties in the total scattering probability for hadrons inside the target nuclei (x_{mfp}^N) and the uncertainties in the likelihood of each hadron rescattering method: elastic (x_{el}^N), inelastic (x_{inel}^N), charge exchange (x_{cex}^N), pion production (x_π^N) and absorption (x_{abs}^N) are taken into account. The fractional uncertainties for these modes for pions is shown in Table 7.4.

A nominal GENIE Monte Carlo sample is generated (a different MC generator from the previously used NEUT Monte Carlo used for the generation of the nominal MC neutrino interaction vectors in Chapter 6) and this is shifted using the re-weighting method to a varied GENIE Monte Carlo by individually increasing and decreasing the parameters in Table 7.4 by its error. For each shifted Monte Carlo produced, the fractional uncertainty can be written as in Equation 7.1.

The tagging efficiency fractional uncertainties are displayed in Figure 7.5, showing which parameter from Table 7.4 each uncertainty has arisen from.

Because the parameters in Table 7.4 are independent, the total uncertainty on the nucleon FSI is calculated by summing the fractional uncertainties on the parameters in quadrature, and then taking the maximum difference between each $\pm\sigma$ pair, as shown in Equation 7.7.

$$\delta_{\text{Nucleon FSI}} = \sqrt{\sum_i \max [\delta_i^2(+\sigma), \delta_i^2(-\sigma)]} \quad (7.7)$$




Figure 7.5: Tagging efficiency fractional uncertainties caused by the nucleon final state interaction model parameter variation for the FHC mode

7.2.6 Muon and pion capture on Oxygen-16

Neutrons are produced from negative muon capture on ^{16}O as shown in Equation 7.8.



Direct neutrons are produced from pion capture on ^{16}O , but also a number of evaporation neutrons that leave the nucleus. For the capture of muons and pions on ^{16}O , the energy spectra of the neutrons produced have been measured: for muons the spectra can range up to 15 MeV, while in the case of pions the spectra can reach up to 100 MeV.

GEANT4 simulates the capture processes for muons and pions, but there are alternate models that can be used: for example, the Chiral Invariant Phase Space (CHIPS) model for muon captures (based on non perturbative QCD) and two different routines for pion capture, one which is based on CHIPS and one based on intra-nuclear cascade.

Because any change in the model can alter the energy spectra of the neutrons, these alternative functions can be used to estimate the fractional uncertainties for the tagging efficiency. This is done by using the MC regeneration method, where the nominal Monte Carlo is regenerated by replacing the default GEANT4 routines with the alternative models. For the alternative muon capture model and the two alternative pion capture models,

the fractional discrepancies are shown in Equation 7.1.

Figure 7.6 shows the fractional uncertainties caused by muon and pion capture on oxygen for each model.




Figure 7.6: Fractional uncertainties in the tagging efficiency caused by muon and pion capture on the muon capture CHIPS model, pion capture CHIPS model and the pion capture Bertini model.

The final total muon and pion capture systematic error is summarised in Equation 7.9. Due to the systematic errors $\delta_{\text{muonCHIPS}}$, $\delta_{\text{pionCHIPS}}$ and δ_{pionBert} , (which are the errors due to the muon capture CHIPS model, pion capture CHIPS model and pion capture Bertini model respectively) being independent of one another they can be added in quadrature.

$$\delta_{\text{muon and pion capture}} = \sqrt{\delta_{\text{muonCHIPS}}^2 + \delta_{\text{pionCHIPS}}^2 + \delta_{\text{pionBert}}^2} \quad (7.9)$$

7.2.7 Nucleon SI

Uncertainties in how Nucleon SI interactions are modelled can affect the tagging efficiency, due to how these uncertainties can affect the final number of nucleons present in the simulation and how far they travel in the detector medium. There are two Monte Carlo code systems used in order to determine how nucleons travel in the simulation, MICAP and

HETC [134]. These come as part of GCALOR, used to determine the energy and direction of incident hadrons, leptons and photons [135]. MICAP (Monte-Carlo-Ionization-Chamber-Analysis-Program), which simulates interactions based on calculated cross section and angular distributions for secondary particles, and is utilised for neutrons with a kinetic energy below 20 MeV [136]. HETC on the other hand, is the High-Energy-Transport-Code, and is responsible for transporting charged hadrons above 20 MeV (up to an energy of 10 GeV) through the detector medium [137].

7.2.8 MICAP uncertainty calculation

A library of cross-section data called ENDF [138] (Evaluated Nuclear Data Files) are used by MICAP to determine what processes the neutrons go through in the detector medium, and their respective cross sections. There are two versions of libraries which are used in evaluating the uncertainty in the tagging efficiency, version B release V (released in 1978) and version B release VIII, released in 2018 [139], [140]. There is very little difference between the total neutron on hydrogen cross sections between the two versions of the code, however, in the energy range of 0.1 MeV to 20 MeV, there are differences of up to 40% in the cross-sections of neutron on oxygen, as shown in Figures 7.7 and 7.8. Both an elastic and inelastic part comprise the total cross-section of a nucleus, and these can affect the way neutrons travel in the simulated detector medium and also the way secondary particles from these interactions are distributed. The way these inelastic processes are simulated depend on the nuclei involved: hydrogen nuclei capture the neutrons in the range (10^{-11} , 10^{-7}) MeV, while neutron captures on oxygen mainly happen on the 4 MeV to 20 MeV energy region. The ENDF/B-VIII library extends the neutron capture energy range for hydrogen to the range (10^{-11} , 10^{-4}) MeV and for captures on oxygen there were differences between ENDF/B-V and ENDF/B-VIII in the 0-10 MeV energy range [16]. To calculate the way uncertainties arise from the way MICAP simulates neutron captures, the ENDF-V library is replaced by ENDF-VIII, and the tagging efficiency using this library (T_{VIII}) is evaluated from regenerated MC. Equation 7.10 shows the fractional uncertainty δ_{MICAP} regarding MICAP.

$$\delta_{mep} = \frac{T_{VIII} - T_{nom}}{T_{nom}} \quad (7.10)$$

A difference in the inelastic component can change the neutron travel distance, so looking at how changing the Nucleon SI changes the distance between the prompt vertex




Figure 7.7: Left:Fraction of inelastic cross-section for hydrogen for both the ENDF-V and ENDF-VIII libraries. Right: Difference of the fraction of the inelastic cross-section between the two libraries. Taken from [17].




Figure 7.8: Left:Fraction of inelastic cross-section for ^{16}O for both the ENDF-V and ENDF-VIII libraries. Right: Difference of the fraction of the inelastic cross-section between the two libraries. Taken from [17].

and the neutron capture vertex is important: this is shown in Figure 7.9.

7.2.9 HETC uncertainty calculation

Due to there being no experimental data for cross-section calculations on nucleon-oxygen scattering in the energy range at which T2K functions, experimental data of proton-carbon scattering is used to assign error on the cross sections. In the proton-carbon scattering analysis, NEUT was used to evaluate the theoretical cross sections of carbon [141], and this uses cross sections calculated using the Bertini model [142], which is also used in HETC [143]. The comparison of these calculated cross sections to other theoretical calculations as well as to data, showed that the total cross sections calculated by Bertini need to be




Figure 7.9: Tagging efficiency dependence of the true distance between the neutrino and neutron capture vertices between the ENDF V library (used in the nominal MC, shown in cyan) and the ENDF/B VIII library shown in red.

varied by $\pm 30\%$ in order to be consistent with them. As a result of this, the Monte Carlo is regenerated twice where the free nucleon-nucleon cross sections are scaled by $\pm 30\%$. Figure 7.10 shows the proton-proton (neutron-neutron) and proton-neutron cross-sections with the shaded area around the line representing the values when the cross sections are scaled by $\pm 30\%$. Equation 7.11 gives the fractional uncertainty stemming from regenerating the MC with this $\pm 30\%$ scaling, where $\delta_{HETC}(\pm)$ is the error and T_{HETC} is the tagging efficiency of the MC with this scaling.

$$\delta_{HETC}(\pm) = \frac{T_{HETC}(\pm) - T_{nom}}{T_{nom}} \quad (7.11)$$

Figure 7.11 shows the dependence of tagging efficiency on the distance between the prompt vertex and neutron capture vertex for the nominal MC and the scaled cross section by $\pm 30\%$.

The fractional discrepancies regarding the HETC codes are not inherently symmetric which is why the positive and negative uncertainties stemming from the Nucleon SI are calculated individually as shown in Equation 7.12, and these values are presented in Table 7.6.




Figure 7.10: Left: proton-proton (neutron-neutron) cross sections, where the shaded area covers the values which are scaled by $\pm 30\%$. Right: proton-neutron cross sections, where the shaded area covers the values which are scaled by $\pm 30\%$. Taken from [17].




Figure 7.11: Tagging efficiency dependence of the true distance between the prompt vertex and the neutron capture vertex for the nominal MC (cyan) and the $\pm 30\%$ cross section cases.

$$\begin{aligned}\delta_{\text{Nucleon FSI}}^+ &= |\delta_{\text{MICAP}}| + |\delta_{\text{HETC}}(+\sigma)| \\ \delta_{\text{Nucleon FSI}}^- &= |\delta_{\text{MICAP}}| + |\delta_{\text{HETC}}(-\sigma)|\end{aligned}\tag{7.12}$$

7.2.10 Uncertainty due to PMT gain simulation

The change in PMT gain over time in the Super-K detector provides a systematic uncertainty for the simulations in this analysis. In SKDETSIM-SKGd the PMT gain drift is modelled by scaling the charge received by the PMT according to Equation 7.13, where G_0 is the amount of average PMT gain value from June 2017.

$$Q \rightarrow Q \times \left(1 + \frac{G(t) - G_0}{G_0} \right) \quad (7.13)$$

In addition to the gain changing over time, so does the number of PMT hits due to the gain, and this has to be adjusted by a correction factor of α which has a value of 1.6, shown in Equation 7.14. This value is estimated by comparing calibration data and simulations [144]. For $\alpha = 1$, Equation 7.14 reduces to Equation 7.13.

$$Q \rightarrow Q \times \left(1 + \alpha \frac{G(t) - G_0}{G_0} \right) \quad (7.14)$$

The discrepancies in tagging efficiency for this systematic uncertainty are produced by looking at the fractional uncertainty in tagging efficiencies between $\alpha = 1.6$ and $\alpha = 1$, according to Equation 7.15.

$$\delta_i = \frac{T_i^{\alpha=1.6} - T_i^{\alpha=1}}{T_i^{\alpha=1}} \quad i \in \{ \text{Regeneration points} \} \quad (7.15)$$

7.2.11 Detector response for neutrino events

The BONSAI fitter output produces parameters that encapsulate the detector response to neutrino events: namely the parameters E_{rec} , dwall, effwall, ovaQ, and θ_C . During the selection of NCQE events, cuts are made on these variables in order to give the most plentiful NCQE sample. However, uncertainties on these parameters can modify the amount of NCQE events and affect the position vector of the reconstructed neutrino vertex, and therefore the NTag algorithm, which could have an impact on the tagging efficiency. The errors on these variables are shown in Table 7.5, and are also provided in TN-374 [23].

The nominal Monte Carlo is re-weighted to produce two new Monte Carlo (\pm) for each of the BONSAI fitter output parameters, i , and the respective tagging efficiencies $T_i(\pm\sigma)$ are calculated. The fractional uncertainties are given using Equation 7.1, where i represents the BONSAI reduction parameter being varied.

Figure 7.12 shows the fractional uncertainties for each parameter. Due to these vari-

Reduction parameter	Uncertainty
E_{rec}	$\pm 5\%$
ovaQ	$\pm 1.5\%$
θ_C	± 2 degree
Effwall	± 50 cm
DWall	± 5 cm

Table 7.5: Uncertainties on BONSAI output parameters (taken from [23]).

ables being considered independent of one another, their uncertainties can be summed in quadrature where as usual the maximum is taken between the $\delta(\pm\sigma)$ pairs, shown in Equation 7.16.

$$\delta_{\nu \text{ response}} = \sqrt{\sum_i \max [\delta_i^2(+\sigma), \delta_i^2(-\sigma)]} \quad (7.16)$$




Figure 7.12: Variation in tagging efficiency produced by the error in neutrino detector response parameters (BONSAI output variables). Red: -1σ discrepancy. Blue: $+1\sigma$ discrepancy.

7.2.12 Final systematic error

Systematic error	Value (%)
PMT gain simulation	± 3.00
ν cross section	± 0.30
ν beam flux	± 0.60
π FSI/SI	± 0.10
Nucleon FSI	± 0.20
Nucleon SI	± 5.40
μ and π capture on ^{16}O	± 0.29
Det. resp. for ν	± 1.36
Det. resp. for gamma rays	± 1.36

Table 7.6: Final systematic uncertainties for the tagging efficiency

In general the systematic errors associated with the tagging efficiency are as expected: the neutrino cross section and beam flux errors provide only a small contribution to the total systematic error on the tagging efficiency because they have very little impact on the neutron tagging efficiency, and the uncertainty on neutron propagation in Super-Kamiokande. Compared to previous analyses which studied neutron tagging in water at Super-K ([\[17\]](#), [\[16\]](#)), the pion FSI/SI error is small. This could be due to the fact that post the addition of $\text{Gd}_2(\text{SO}_4)_3 \cdot 8\text{H}_2\text{O}$ into the simulation, there are more processes occurring within SKDETSIM due to the additional presence of oxygen, gadolinium and sulphate ions. As a result, the impact that this uncertainty has on the total systematic uncertainty is reduced compared to analyses where these additional nuclei are not present. Similarly, the Nucleon SI uncertainty is also small compared to ([\[17\]](#), [\[16\]](#)), because of the additional interactions occurring on the extra nuclei in the simulation, and therefore the nucleon FSI uncertainty that can alter the number of protons and neutrons knocked out of ^{16}O is lessened. The nucleon SI error is the biggest amongst the uncertainties listed in Table 7.6, which is appropriate and in keeping with the results in [\[17\]](#), [\[16\]](#), as variations in the inelastic cross section for ^{16}O and the uncertainties on the cross sections calculated by the Bertini model which are scaled by $\pm 30\%$ will have a direct impact on the distance between the neutrino interaction vertex and the neutron capture vertex, and therefore a direct impact on the neutron tagging efficiency. The muon and pion capture uncertainties on ^{16}O have smaller values than [\[16\]](#), one possible reason for this is the presence of extra

gadolinium and sulphate ions in the simulation so that less muons will capture on ^{16}O , and as a result the impact on the associated energy spectra of neutrons will be less, so the affect on the neutron tagging efficiency will be less. The neutrino detector response uncertainty is in keeping with the uncertainty evaluated in [17], which is understandable as the same errors on the NCQE reduction parameters are used. The detector response from gamma ray uncertainty evaluated by comparisons with Am/Be + 8 BGO data is smaller compared to either of the results from [17] or [16] - this makes sense due to the greater compatibility of the NCQE MC neutron tagging efficiency value with the value obtained by comparisons to the Am/Be + BGO data. The uncertainty of the detector response for the neutrinos being the same as the detector response for gamma ray uncertainty is a coincidence (± 1.36) as these are calculated in two wholly different ways, the former by varying the reduction cut parameters and the latter by comparisons with Am/Be + 8BGO data. The second largest systematic uncertainty in Table 7.6 comes from the uncertainty in the PMT gain. This value is larger than for [17] or [16], however PMT gain increases over time and as the gain increases so does the neutron tagging efficiency discrepancy due to PMT gain.

Chapter 8

The DSNB NCQE background

“Mr. Scott cannot give me exact figures, Admiral, so... I will make a guess.”

Mr. Spock, Star Trek IV: The Voyage Home (1986)

8.1 Introduction

As mentioned in Chapter 1, NCQE interactions form the main background to the DSNB signal, and therefore calculating the number of events that form this background concludes the work of this analysis.

The number of observed neutrino events which are detected at Super-Kamiokande as a function of some observable such as reconstructed neutrino energy $N_\nu(E_\nu)$ is given in Equation 8.1.

$$N_\nu(E_\nu) = \mathcal{C} \int \Phi(E_\nu) \sigma(E_\nu) \epsilon dE_\nu \quad (8.1)$$

Here, \mathcal{C} is the target volume, E_ν is the true incoming neutrino energy, $\Phi(E_\nu)$ is the flux of the incoming neutrino, $\sigma(E_\nu)$ is the cross section for the neutrino interaction and ϵ is the detection efficiency of the neutrino by the far detector. The number of neutrino events from Monte Carlo for each interaction type is given by summing the number of NCQE events for neutrinos and anti-neutrinos, and charged-current and NC-other interactions,

FHC sample	MC # ν_{det}	MC # ν_{det} fraction (%)
$\nu - NCQE$	1199.7	75.0
$\bar{\nu} - NCQE$	34.5	2.2
$NC - \text{other}$	288.1	19.1
CC	17.4	3.7
Total	1599.2	100

Table 8.1: FHC MC expectation values for each interaction type with a total SK POT of 10×10^{21}

where the numbers of the neutrino and antineutrino NCQE events are multiplied by scale factors which scale the simulated NCQE cross section prediction.

8.2 NCQE cross-section uncertainty prediction

The number of events N_{obs} are made up of the sum of the signal (S) and background (B) events, i.e: $N_{obs} = S + B$. The signal events are described by the summation of the number of neutrino and antineutrino NCQE events multiplied by their scale factors: $S = f_{\nu-NCQE} M_{\nu-NCQE}^{\text{FHC}} + f_{\bar{\nu}-NCQE} M_{\bar{\nu}-NCQE}^{\text{FHC}}$ for FHC mode. These scale factors are used to scale the NCQE cross section predictions made by NEUT. By having a similar equation for RHC mode, one can produce the Equations in 8.2, where X and Y are the number of background events for FHC and RHC mode respectively, which give the scale factor values for neutrino and antineutrino NCQE interactions.

$$f_{\nu-NCQE} = \frac{X M_{\bar{\nu}-NCQE}^{\text{RHC}} - Y M_{\bar{\nu}-NCQE}^{\text{FHC}}}{M_{\nu-NCQE}^{\text{FHC}} M_{\bar{\nu}-NCQE}^{\text{RHC}} - M_{\nu-NCQE}^{\text{RHC}} M_{\bar{\nu}-NCQE}^{\text{FHC}}} \quad (8.2)$$

$$f_{\bar{\nu}-NCQE} = \frac{X M_{\nu-NCQE}^{\text{RHC}} - Y M_{\nu-NCQE}^{\text{FHC}}}{M_{\bar{\nu}-NCQE}^{\text{FHC}} M_{\nu-NCQE}^{\text{RHC}} - M_{\bar{\nu}-NCQE}^{\text{RHC}} M_{\nu-NCQE}^{\text{FHC}}}$$

Table 8.1 gives the expected number of neutrino events for each type of interaction including neutral current and charged current interactions for FHC mode for a predicted future POT of 10×10^{21} by Japanese Fiscal Year 2028 [145], and Table 8.2 shows the same information for RHC mode. These have been calculated with the 21bv2 flux uncertainty tuning. Figure 8.2 shows the number of events plotted against the reconstructed energy (E_{rec}) of the event for FHC and RHC mode.

Due to this being a future prediction of the background rate using MC and not data, N_{obs} is the total number of events in the MC, meaning that the value of the scale factor is




Figure 8.1: Number of events plotted against E_{rec} for T2K FHC mode




Figure 8.2: Number of events plotted against E_{rec} for T2K RHC mode

RHC sample	MC # ν_{det}	MC # ν_{det} fraction (%)
$\nu - NCQE$	182.8	31.9
$\bar{\nu} - NCQE$	257.0	44.8
$NC - \text{other}$	118.4	20.6
CC	15.3	2.7
Total	573.5	100

Table 8.2: RHC MC expectation values for each interaction type with a total SK POT of 10×10^{21} .

1.00. However, the uncertainty on the scale factor is not trivial, and Equation 8.3 shows how it is calculated.

$$\delta_f = \left(\frac{\sqrt{N_{\text{obs}}}}{N_{\text{obs}}} \right)^2 + \left(\frac{\delta_\epsilon}{\epsilon} \right)^2 \quad (8.3)$$

The values for the uncertainty on the scale factors for FHC and RHC mode is shown in Equation 8.4.

$$\begin{aligned} \delta f_{\nu-\text{NCQE}} &= \pm 0.129 \\ \delta f_{\bar{\nu}-\text{NCQE}} &= \pm 0.133 \end{aligned} \quad (8.4)$$

8.3 Number of DSNB NCQE background events

The number of DSNB NCQE background events is given by Equation 8.5.

$$N_B = \mathcal{C}\epsilon_N f \int \Phi(ATM)\epsilon_N \sigma(E_\nu) dE_\nu \quad (8.5)$$

Where \mathcal{C} is the target volume, $\Phi(ATM)$ is the atmospheric neutrino flux, σ is the neutrino interaction cross section, ϵ_N is the neutron tagging efficiency and f is the value of the scale factors. In 2021 the Super-Kamiokande DSNB analysis working group released the first results showing the number of low energy inverse beta decay events in MC and data for 552.2 days of SK-Gd data. Table 8.3 shows the number of events for MC and data for each energy bin of 2 MeV in the 8-30 MeV signal region. Figure 8.3 shows the energy spectrum of these events in the signal region after data reduction and neutron tagging, along with the associated backgrounds.

Energy (MeV)	Obs. (/bin)	Exp. (/bin)
8-10	7	9.18 ± 3.58
10-12	4	2.78 ± 0.93
12-16	0	1.05 ± 0.21
16-24	2	0.41 ± 0.09
24-30	1	0.41 ± 0.07

Table 8.3: Number of low energy IBD events for each 2 MeV energy bin from 8 - 30 MeV for data and MC

Scaling the total number of events found from the MC in Figure 8.3, (2.04 events) from




Figure 8.3: Reconstructed energy spectra after data reduction for the backgrounds and the observed data taken with 552.2 days of SK-VI data. Taken from [18], accessed on 22/03/23.

the 552.2 days of taking data to 2028 gives 9.88 events in FHC mode. Using Equation 8.5, the number of predicted DSNB NCQE background events for FHC mode is given in Equation 8.7, with the combined systematic and statistical error on this value calculated as in Equation 8.6.

$$\left(\frac{\delta_{N_{\nu-\text{DSNB}_{NCQE}}}}{N_{\nu-\text{DSNB}_{NCQE}}} \right)^2 = \left(\frac{\sqrt{N_{\text{obs}}}}{N_{\text{obs}}} \right)^2 + \left(\frac{\delta_{\epsilon_N}}{\epsilon_N} \right)^2 + \left(\frac{\delta_f}{f} \right)^2 \quad (8.6)$$

$$N_{\nu-\text{DSNB}_{NCQE}} = 9.88 \pm 3.62 \quad (8.7)$$

To summarise, as shown in Figure 8.3, the dominant atmospheric neutrino background comes from NCQE interactions, and cross section measurements from T2K can be used to estimate this background. Monte Carlo simulations of neutrino and anti-neutrino NCQE interactions can be renormalised using scaling factors from data, while the error on these scale factors are taken as cross-section uncertainties. Values of these scale-factor errors are given in Equation 8.4 and these have been calculated from the expected number of neutrino

events for a future POT of 10×10^{21} starting JFY 2028, shown in Table 8.1 and Table 8.2. The number of DSNB NCQE background events in MC are taken from results from SK-Gd in 2021 and scaled up to the JFY 2028 prediction, with the error on the scale factor used to produce the total uncertainty (Equation 8.6) on this measurement. The estimation of DSNB NCQE background error is important because of NCQE interactions being the dominant atmospheric neutrino background below 15 MeV and its the constraining of this background which is fundamental to DSNB searches.

Chapter 9

Conclusion

“Time may be eternal, Captain, but our patience is not. It’s time to put an end to your trek through the stars, make room for other more worthy species.”

Q, Star Trek: TNG S7E26 All Good Things... (1994)

The work presented in this thesis has two distinct parts: one is the calibration work centered around the Monte Carlo simulations of the UK Light Injection System optics and the other part is my work with neutron tagging for the Super Kamiokande Gadolinium Upgrade and the use of the neutron tagging efficiency to estimate the DSNB NCQE background error.

The work in this thesis on the UK Light Injection system involving modelling the collimator and diffuser optics in Monte Carlo is important for the aim of measuring the scattering and absorption coefficients of the water in Super-Kamiokande using the UKLI. Future work regarding the UKLI system implemented in Super-Kamiokande will involve looking at forward scattering using the collimator optics and water quality analysis with the diffuser beam. Along with the modelling of the beam spots in simulation, the varying of the time dispersion of the optics in MC is something that was also successfully demonstrated in this thesis and will be crucial for future comparisons of UKLI MC with data.

The estimation of the DSNB NCQE background is massively important for DSNB analyses

as NCQE interactions are the dominant atmospheric neutrino background below 15 MeV. Measuring the NCQE interaction with the T2K beam improves the situation due to the T2K energy region being similar to that of atmospheric neutrinos. The neutrons associated with these neutrino interactions need to be studied precisely, and due to the addition of gadolinium in Super-Kamiokande, neutron tagging has been demonstrably improved in Monte Carlo simulations of the NCQE interactions, particularly in regards to the neutron tagging efficiency. The neutron tagging methodology for SK-Gd has been explored in great detail, with efficiency validations made using Am/Be + 8BGO data. We can consider the prospects for the NCQE background estimation by using this efficiency value to calculate the error on a predicted future measurement of DSNB NCQE background events for JFY 2028. With the increased neutron tagging efficiency due to the addition of gadolinium, which is also something that will be replicated in the much larger Hyper-Kamiokande experiment and the greater ability to tag neutrons associated with neutrino interactions, a first observation of DSNB signal seems well within reach in the next decade.

Bibliography

- [1] John N. Bahcall. Solar models: An historical overview. *Nuclear Physics B - Proceedings Supplements*, 118:77–86, apr 2003.
- [2] Sovan Chakraborty, Pijushpani Bhattacharjee, and Kamales Kar. Observing supernova neutrino light curve in future dark matter detectors. *Physical Review D*, 89(1):013011, January 2014.
- [3] Ll. Martí and M. et al. Ikeda. Evaluation of gadolinium’s action on water Cherenkov detector systems with EGADS. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 959:163549, April 2020.
- [4] K. Abe et al. The T2K Neutrino Flux Prediction. *Physical Review D*, 87(1):012001, January 2013. arXiv: 1211.0469.
- [5] K. Abe et al. The T2K Experiment. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 659(1):106–135, December 2011. arXiv: 1106.1238.
- [6] S. Fukuda and Y. et al. Fukuda. The Super-Kamiokande detector. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 501(2-3):418–462, April 2003.
- [7] H. Nishino, K. Awai, Y. Hayato, S. Nakayama, K. Okumura, M. Shiozawa, A. Takeda, K. Ishikawa, A. Minegishi, and Y. Arai. High-speed charge-to-time converter ASIC for the Super-Kamiokande detector. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 610(3):710–717, November 2009. arXiv: 0911.0986.

- [8] K. Abe et al. First gadolinium loading to Super-Kamiokande. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, page 166248, December 2021.
- [9] K. Abe et al. Calibration of the Super-Kamiokande Detector. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 737:253–272, February 2014. arXiv: 1307.0162.
- [10] Artur M. Ankowski, Omar Benhar, Takaaki Mori, Ryuta Yamaguchi, and Makoto Sakuda. Analysis of gamma ray production in neutral-current neutrino-oxygen interactions at energies above 200 mev. *Physical Review Letters*, 108(5), feb 2012.
- [11] Hagiwara et al. Gamma-ray spectrum from thermal neutron capture on gadolinium-157. *Progress of Theoretical and Experimental Physics*, 2019(2), 02 2019. 023D01.
- [12] M. Malek. A Search for Supernova Relic Neutrinos. *PhD Thesis, State University of New York*, 2003.
- [13] K. Bays et al. Supernova relic neutrino search at super-kamiokande. *Physical Review D*, 85(5), mar 2012.
- [14] K. Abe et al. Measurement of neutrino and antineutrino neutral-current quasielastic-like interactions on oxygen by detecting nuclear deexcitation gamma-rays. *Physical Review D*, 100(11), dec 2019.
- [15] Mark Vagins. Large scale testing and development of gadolinium trichloride for use in neutron detection in large water. 9 2007.
- [16] R. Akutsu. A Study of Neutrons Associated with Neutrino and Antineutrino Interactions on the Water Target at the T2K Far Detector. *PhD Thesis, The University of Tokyo*, 2019.
- [17] Fabio Iacob. Measurement of neutrino- and antineutrino-oxygen neutral-current quasielastic-like interaction neutron multiplicity by detecting radiative capture on hydrogen at the far detector. *T2K Technical Note*, (415), 2021.
- [18] M. Harada. Sk-vi dsnb analysis. *Super-Kamiokande Collaboration meeting*, 2022.

- [19] Avishay Gal-Yam. Observational and physical classification of supernovae. In *Handbook of Supernovae*, pages 195–237. Springer International Publishing, 2017.
- [20] K. Mahn. *For Summer 2016 XSEC analyses and onward*, 2018.
- [21] S. Bolognesi. Niwg model and uncertainties for 2017 oscillation analysis. *T2K Technical Note*, (315), 2017.
- [22] P. Perio. NEUT Systematic Studies for 2010a Analysis. *T2K Technical Note*, (32), 2011.
- [23] Y. Ashida. Measurement of neutrino- and antineutrino-oxygen neutral-current quasielastic-like interaction cross sections by detecting nuclear de-excitation gamma-rays at the far detector with Run1-9 FHC and RHC data. *T2K Technical Note*, (374), 2019.
- [24] M. Aker et al. Improved upper limit on the neutrino mass from a direct kinematic method by KATRIN. *Physical Review Letters*, 123(22), nov 2019.
- [25] Laurie M. Brown. The idea of the neutrino. *Physics Today*, 31(9):23–28, September 1978. Publisher: American Institute of Physics.
- [26] Hans Bethe and Rudolph Peierls. The “neutrino”. *Nature*, 133(3362):532–532, 1934.
- [27] Luca Nanni. Fermi theory of beta decay: A first attempt at electroweak unification. *Advanced Studies in Theoretical Physics*, 13:281, 07 2019.
- [28] Jr. Cowan, C. L., F. Reines, F. B. Harrison, H. W. Kruse, and A. D. McGuire. Detection of the Free Neutrino: A Confirmation. *Science*, 124(3212):103–104, July 1956.
- [29] P Vogel and John F Beacom. Angular distribution of neutron inverse beta decay, $\nu_e + p \rightarrow e^+ + n$. *Physical Review D*, 60(5):053003, 1999.
- [30] F Reines and C Cowan. The neutrino. *Nature*, 178(4531):446–449, 1956.
- [31] Gerald Feinberg and Leon M Lederman. The physics of muons and muon neutrinos. *Annual Review of Nuclear Science*, 13(1):431–504, 1963.

- [32] G. Danby, J-M. Gaillard, K. Goulian, L. M. Lederman, N. Mistry, M. Schwartz, and J. Steinberger. Observation of high-energy neutrino reactions and the existence of two kinds of neutrinos. *Phys. Rev. Lett.*, 9:36–44, Jul 1962.
- [33] Ernest D Courant and Hartland S Snyder. Theory of the alternating-gradient synchrotron. *Annals of physics*, 3(1):1–48, 1958.
- [34] Juan Pedro Ochoa Ricoux. *A search for muon neutrino to electron neutrino oscillations in the MINOS experiment*. California Institute of Technology, 2010.
- [35] David Lindley. Landmarks—discovery of a 2nd kind of neutrino. *Physics*, 8:75, 2015.
- [36] K Kodama, N Ushida, C Andreopoulos, N Saoulidou, G Tzanakos, P Yager, B Baller, D Boehnlein, Walter Freeman, B Lundberg, et al. Observation of tau neutrino interactions. *Physics Letters B*, 504(3):218–224, 2001.
- [37] K Kodama, C Andreopoulos, N Giokaris, N Saoulidou, G Tzanakos, B Baller, D Boehnlein, B Lundberg, R Rameika, JS Song, et al. Identification of neutrino interactions using the donut spectrometer. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 516(1):21–33, 2004.
- [38] K Kodama, N Ushida, GS Tzanakos, PM Yager, VS Paolone, CH Hahn, JY Kim, T Bolton, J Conrad, M Shaevitz, et al. Muon neutrino to tau neutrino oscillations. *FNAL Proposal P-803*, 1993.
- [39] Comprehensive measurement of pp-chain solar neutrinos. *Nature*, 562(7728):505–510, 2018.
- [40] Bruce T. Cleveland, Timothy Daily, Jr. Raymond Davis, James R. Distel, Kenneth Lande, C. K. Lee, Paul S. Wildenhain, and Jack Ullman. Measurement of the solar electron neutrino flux with the homestake chlorine detector. *The Astrophysical Journal*, 496(1):505–526, mar 1998.
- [41] Raymond Davis. A review of the homestake solar neutrino experiment. *Progress in Particle and Nuclear Physics*, 32:13–32, 1994.
- [42] J Konijn. The solar neutrino problem. *European Journal of Physics*, 20(6):399, nov 1999.

- [43] W. C. Haxton. The solar neutrino problem. *Annual Review of Astronomy and Astrophysics*, 33(1):459–503, sep 1995.
- [44] PI Krastev and A Yu Smirnov. Global analysis with sno: Toward the solution of the solar neutrino problem. *Physical Review D*, 65(7):073022, 2002.
- [45] B. Pontecorvo. Mesonium and anti-mesonium. *Sov. Phys. JETP*, 6:429, 1957.
- [46] Ziro Maki, Masami Nakagawa, and Shoichi Sakata. Remarks on the Unified Model of Elementary Particles. *Progress of Theoretical Physics*, 28(5):870–880, 11 1962.
- [47] Hiroshi Nunokawa, Stephen Parke, and José W.F. Valle. Cp violation and neutrino oscillations. *Progress in Particle and Nuclear Physics*, 60(2):338–402, 2008.
- [48] Claudio Giganti, Stéphane Lavignac, and Marco Zito. Neutrino oscillations: the rise of the pmns paradigm. *Progress in Particle and Nuclear Physics*, 98:1–54, 2018.
- [49] S. M. Bilenky and S. T. Petcov. Massive neutrinos and neutrino oscillations. *Rev. Mod. Phys.*, 59:671–754, Jul 1987.
- [50] A Yu Smirnov. The msw effect and matter effects in neutrino oscillations. *Physica Scripta*, 2005(T121):57, jan 2005.
- [51] Timo van Ritbergen and Robin G Stuart. On the precise determination of the fermi coupling constant from the muon lifetime. *Nuclear Physics B*, 564(3):343–390, 2000.
- [52] John N. Bahcall. Neutrino-electron scattering and solar neutrino experiments. *Rev. Mod. Phys.*, 59:505–521, Apr 1987.
- [53] Emmanuel A. Paschos, Ji-Young Yu, and Makoto Sakuda. Neutrino production of resonances. *Phys. Rev. D*, 69:014013, Jan 2004.
- [54] Sergey A Kulagin and R Petti. Neutrino inclusive inelastic scattering off nuclei. *Physical Review D*, 76(9):094023, 2007.
- [55] A Oralbaev, M Skorokhvatov, and O Titov. The inverse beta decay: A study of cross section. In *Journal of Physics: Conference Series*, volume 675, page 012003. IOP Publishing, 2016.

- [56] Yu-Feng Li, Mark Vagins, and Michael Wurm. Prospects for the detection of the diffuse supernova neutrino background with the experiments sk-gd and juno. *Universe*, 8(3):181, 2022.
- [57] L Wan, K Abe, C Bronner, Y Hayato, M Ikeda, K Iyogi, J Kameda, Y Kato, Y Kishimoto, Ll Marti, et al. Measurement of the neutrino-oxygen neutral-current quasielastic cross section using atmospheric neutrinos at super-kamiokande. *Physical Review D*, 99(3):032005, 2019.
- [58] Tomasz Golan, Cezary Juszczak, and Jan T. Sobczyk. Effects of final-state interactions in neutrino-nucleus interactions. *Physical Review C*, 86(1), jul 2012.
- [59] Martin David Haigh. Results from t2k. *arXiv preprint arXiv:1501.04283*, 2015.
- [60] M Malek, M Morii, S Fukuda, Y Fukuda, M Ishitsuka, Y Itow, T Kajita, J Kameda, K Kaneyuki, K Kobayashi, et al. Search for supernova relic neutrinos at super-kamiokande. *Physical review letters*, 90(6):061101, 2003.
- [61] Sidney Van Den Bergh. Supernova rates: A progress report. *Physics reports*, 204(6):385–400, 1991.
- [62] Massimo Turatto. Classification of supernovae. In *Supernovae and Gamma-Ray Bursters*, pages 21–36. Springer, 2003.
- [63] Kate Scholberg. Supernova neutrino detection. *Annual Review of Nuclear and Particle Science*, 62:81–103, 2012.
- [64] Sean M Couch. The mechanism (s) of core-collapse supernovae. *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 375(2105):20160271, 2017.
- [65] CL Fryer, AL Hungerford, and S Jones. Gamma-ray probes of supernova engines. *Memorie della Societa Astronomica Italiana*, 90:32, 2019.
- [66] Kevin Ebinger. *Global properties of core-collapse supernovae in numerical simulations*. PhD thesis, University_of_Basel, 2017.
- [67] Milad Delfan Azari, Shoichi Yamada, Taiki Morinaga, Hiroki Nagakura, Shun Furusawa, Akira Harada, Hirotada Okawa, Wakana Iwakami, and Kohsuke Sumiyoshi.

- Fast collective neutrino oscillations inside the neutrino sphere in core-collapse supernovae. *Phys. Rev. D*, 101:023018, Jan 2020.
- [68] W. C. Haxton. Neutrino heating in supernovae. *Phys. Rev. Lett.*, 60:1999–2002, May 1988.
- [69] Michael A Pajkos, Sean M Couch, Kuo-Chuan Pan, and Evan P O’Connor. Features of accretion-phase gravitational-wave emission from two-dimensional rotating core-collapse supernovae. *The Astrophysical Journal*, 878(1):13, 2019.
- [70] A Pascal, J Novak, and M Oertel. Proto-neutron star evolution with improved charged-current neutrino–nucleon interactions. *Monthly Notices of the Royal Astronomical Society*, 511(1):356–370, 2022.
- [71] Evan O’Connor and Christian D Ott. Black hole formation in failing core-collapse supernovae. *The Astrophysical Journal*, 730(2):70, 2011.
- [72] Aurore Betrandhdy and Evan O’Connor. Impact of neutrino pair-production rates in core-collapse supernovae. *Physical Review D*, 102(12):123015, 2020.
- [73] Hiroki Nagakura and Kenta Hotokezaka. Non-thermal neutrinos created by shock acceleration in successful and failed core-collapse supernova. *Monthly Notices of the Royal Astronomical Society*, 502(1):89–107, January 2021. arXiv: 2010.15136.
- [74] K. Hirata and T. et al. Kajita. Observation of a neutrino burst from the supernova SN1987A. *Physical Review Letters*, 58(14):1490–1493, April 1987.
- [75] K. S. Hirata et al. Observation in the Kamiokande-II Detector of the Neutrino Burst from Supernova SN 1987a. *Phys. Rev. D*, 38:448–458, 1988.
- [76] H. A. Bethe. Supernova mechanisms. *Reviews of Modern Physics*, 62(4):801–866, October 1990.
- [77] John F Beacom. The diffuse supernova neutrino background. *Annual Review of Nuclear and Particle Science*, 60:439–462, 2010.
- [78] Shin’ichiro Ando and Katsuhiko Sato. Relic neutrino background from cosmological supernovae. *New Journal of Physics*, 6:170–170, November 2004. arXiv: astro-ph/0410061.

- [79] K Abe, C Bronner, Y Hayato, K Hiraide, M Ikeda, S Imaizumi, J Kameda, Y Kanemura, Y Kataoka, S Miki, et al. Diffuse supernova neutrino background search at super-kamiokande. *Physical Review D*, 104(12):122002, 2021.
- [80] K. Kaneyuki. T2k experiment. *Nuclear Physics B - Proceedings Supplements*, 145:178–181, 2005. NOW 2004.
- [81] Shoji Nagamiya. Introduction to j-parc. *Progress of Theoretical and Experimental Physics*, 2012(1), 2012.
- [82] Yury Kudenko, Representing the T2K Collaboration, et al. The near neutrino detector for the t2k experiment. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 598(1):289–295, 2009.
- [83] K Abe, N Abgrall, Y Ajima, H Aihara, JB Albert, C Andreopoulos, B Andrieu, MD Anerella, S Aoki, O Araoka, et al. Measurements of the t2k neutrino beam properties using the ingrid on-axis near detector. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 694:211–223, 2012.
- [84] Kazuo Hasegawa et al. Status of the j-parc linac. In *Proc. Linear Accelerator Conf. (LINAC2010)*, pages 449–451, 2010.
- [85] Yoichi Sato et al. High power beam operation of the j-parc rcs and mr. *Proceedings of IPAC2018, Vancouver BC, Canada*, 29, 2018.
- [86] Kazuo Hasegawa, Naoki Hayashi, H Oguri, K Yamamoto, M Kinsho, Y Yamazaki, F Naito, T Koseki, Noboru Yamamoto, and Masahito Yoshii. Performance and status of the j-parc accelerators. In *Proceedings of the 8th International Particle Accelerator Conference, Copenhagen, Denmark*, 2017.
- [87] Wataru Higemoto, Ryosuke Kadono, Naritoshi Kawamura, Akihiro Koda, Kenji M Kojima, Shunsuke Makimura, Shiro Matoba, Yasuhiro Miyake, Koichiro Shimomura, and Patrick Strasser. Materials and life science experimental facility at the japan proton accelerator research complex iv: The muon facility. *Quantum Beam Science*, 1(1):11, 2017.

- [88] Tetsuro Sekiguchi. Neutrino beamline for t2k. In *AIP Conference Proceedings*, volume 981, pages 275–277. American Institute of Physics, 2008.
- [89] Sampa Bhadra, Mircea Cadabeschi, Patrick de Perio, Vyacheslav Galymov, Mark Hartz, Brian Kirby, Akira Konaka, Alycia D Marino, John F Martin, David Morris, et al. Optical transition radiation monitor for the t2k experiment. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 703:45–58, 2013.
- [90] Tetsuro Sekiguchi. T2k horn. In *AIP Conference Proceedings*, volume 981, pages 345–347. American Institute of Physics, 2008.
- [91] K Matsuoka, AK Ichikawa, H Kubo, K Maeda, T Maruyama, C Matsumura, A Murakami, T Nakaya, K Nishikawa, T Ozaki, et al. Design and performance of the muon monitor for the t2k neutrino oscillation experiment. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 624(3):591–600, 2010.
- [92] Masashi Otani, A Minamino, K Nitta, A Ichikawa, N Nagai, T Nakaya, D Orme, M Yokoyama, D Autiero, M Besnier, et al. Design and construction of ingrid neutrino beam monitor for the t2k neutrino experiment. In *2008 IEEE Nuclear Science Symposium Conference Record*, pages 2930–2933. IEEE, 2008.
- [93] T Kikawa, T2K collaboration, et al. Development of the new t2k on-axis neutrino detector, ingrid proton module. *Nuclear Physics B-Proceedings Supplements*, 229:451, 2012.
- [94] K. Abe et al. Measurements of the t2k neutrino beam properties using the INGRID on-axis near detector. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 694:211–223, dec 2012.
- [95] Kou Abe, J Adam, H Aihara, T Akiri, C Andreopoulos, S Aoki, A Ariga, S Assylbekov, D Autiero, M Barbi, et al. Measurement of the $\nu \mu$ charged-current quasielastic cross section on carbon with the nd280 detector at t2k. *Physical Review D*, 92(11):112003, 2015.

- [96] Nicolas Abgrall, B Andrieu, P Baron, P Bene, V Berardi, J Beucher, P Birney, F Blaszczyk, Alain Blondel, C Bojochko, et al. Time projection chambers for the t2k near detectors. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 637(1):25–46, 2011.
- [97] P-A Amaudruz, M Barbi, D Bishop, N Braam, DG Brook-Roberge, S Giffin, S Gomi, P Gumplinger, K Hamano, NC Hastings, et al. The t2k fine-grained detectors. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 696:1–31, 2012.
- [98] D Allan, C Andreopoulos, C Angelsen, GJ Barker, G Barr, S Bentham, I Bertram, S Boyd, K Briggs, RG Calland, et al. The electromagnetic calorimeter for the t2k near detector nd280. *Journal of Instrumentation*, 8(10):P10019, 2013.
- [99] Yoichiro Suzuki. The Super-Kamiokande experiment. *The European Physical Journal C*, 79(4):298, April 2019.
- [100] Artem Vukolov, Aleksey Gogolev, Yury Cherepennikov, Andrey Ogrebo, and Alexander Egioya. Portable gamma-ray spectrometer for high intensity beam measuring. In *Advanced Materials Research*, volume 1084, pages 162–167. Trans Tech Publ, 2015.
- [101] AFJ Van Raan, J Van der Weg, and J Van Eck. An experimental study of the response of a venetian blind type photomultiplier. *Journal of Physics E: Scientific Instruments*, 5(10):964, 1972.
- [102] J Brack, B Delgado, J Dhooghe, J Felde, B Gookin, S Grullon, JR Klein, R Knapik, A LaTorre, S Seibert, et al. Characterization of the hamamatsu r11780 12 in. photomultiplier tube. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 712:162–173, 2013.
- [103] Y Nakano, T Hokama, M Matsubara, M Miwa, M Nakahata, T Nakamura, H Sekiya, Y Takeuchi, S Tasaka, and RA Wendell. Measurement of the radon concentration in purified water in the super-kamiokande iv detector. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 977:164297, 2020.

- [104] P. Fernández. Status of GADZOOKS!: Neutron Tagging in Super-Kamiokande. *Nuclear and Particle Physics Proceedings*, 273-275:353–360, April 2016.
- [105] S Yamada, K Awai, Y Hayato, K Kaneyuki, Y Kouzuma, S Nakayama, H Nishino, K Okumura, Y Obayashi, Y Shimizu, et al. Commissioning of the new electronics and online system for the super-kamiokande experiment. *IEEE Transactions on Nuclear Science*, 57(2):428–432, 2010.
- [106] Chenyuan Xu, Super-Kamiokande Collaboration, et al. Current status of sk-gd project and egads. In *Journal of Physics: Conference Series*, volume 718, page 062070. IOP Publishing, 2016.
- [107] Rogelio Caballero, Juan Carlos D’Olivo, Gustavo Medina-Tanco, Lukas Nellen, Federico A Sánchez, and José F Valdés-Galicia. Low energy event reconstruction and selection in super-kamiokande-iii.
- [108] M Shiozawa. Reconstruction algorithms in the super-kamiokande large water cherenkov detector. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 433(1-2):240–246, 1999.
- [109] K Ueno. Analysis of nuclear de-excitation gamma-rays induced by neutrino-nucleon neutral-current interactions at SK using the T2K RUN-I/II data. page 87.
- [110] S Lo Meo, C Massimi, and Rocchi et al. Measurement of the neutron capture cross section for ^{155}Gd and ^{157}Gd for Nuclear Technology. page 8.
- [111] K Abe, Y Haga, Y Hayato, K Hiraide, K Ieki, M Ikeda, S Imaizumi, K Iyogi, J Kameda, Y Kanemura, et al. Neutron tagging following atmospheric neutrino events in a water cherenkov detector. *Journal of Instrumentation*, 17(10):P10029, 2022.
- [112] Lluís Martí Magro. Egads approaching gadzooks! In *EPJ Web of Conferences*, volume 95, page 04041. EDP Sciences, 2015.
- [113] K Hosokawa, M Ikeda, T Okada, H Sekiya, P Fernández, L Labarga, I Bandac, J Perez, S Ito, M Harada, Y Koshio, M D Thiesse, L F Thompson, P R Scovell, E Meehan, K Ichimura, Y Kishimoto, Y Nakajima, M R Vagins, H Ito, Y Takaku,

- Y Tanaka, and Y Yamaguchi. Development of ultra-pure gadolinium sulfate for the Super-Kamiokande gadolinium project. *Progress of Theoretical and Experimental Physics*, 2023(1), 12 2022. 013H01.
- [114] Guillaume Pronost. Looking for gd neutron captures from sn ν with egads detector. In *35th International Cosmic Ray Conference (ICRC2017)*, volume 301, page 964, 2017.
 - [115] Yusuke Koshio. Study of solar neutrinos at super kamiokande. *stat*, 2:0–06, 1998.
 - [116] Michael R Dziomba. *A study of neutrino oscillation models with Super-Kamiokande atmospheric neutrino data*. University of Washington, 2012.
 - [117] J Hosaka, K Ishihara, J Kameda, Yusuke Koshio, A Minamino, C Mitsuda, M Miura, S Moriyama, M Nakahata, T Namba, et al. Solar neutrino measurements in super-kamiokande-i. *Physical Review D*, 73(11):112001, 2006.
 - [118] Robin M. Pope and Edward S. Fry. Absorption spectrum (380–700 nm) of pure water. ii. integrating cavity measurements. *Appl. Opt.*, 36(33):8710–8723, Nov 1997.
 - [119] Andrew Renshaw. Solar neutrino results from super-kamiokande. *Physics Procedia*, 61:345–354, 2015. 13th International Conference on Topics in Astroparticle and Underground Physics, TAUP 2013.
 - [120] Duncan T. Moore. Gradient-index optics: a review. *Appl. Opt.*, 19(7):1035–1038, Apr 1980.
 - [121] M Harada, Y Koshio, and K Hagiwara. Development of geant4 based simulation for super-kamiokande. *Quest for the Origin of Particles and the Universe (KMI2019)*, page 49, 2019.
 - [122] René Brun, F Bruyant, Federico Carminati, Simone Giani, M Maire, A McPherson, G Patrick, and L Urban. *GEANT: Detector Description and Simulation Tool; Oct 1994*. CERN Program Library. CERN, Geneva, 1993. Long Writeup W5013.
 - [123] G. E. P. Box and Mervin E. Muller. A Note on the Generation of Random Normal Deviates. *The Annals of Mathematical Statistics*, 29(2):610 – 611, 1958.

- [124] G. Marsaglia and T. A. Bray. A convenient method for generating normal variables. *SIAM Review*, 6(3):260–264, 1964.
- [125] Tomislav VLADISAVLJEVIC. Constraining the t2k neutrino flux prediction with 2009 na61/shine replica-target data. 2018.
- [126] S. Bienstock. Five sample (nu-nubar, appearance/disappearance, nue CC1pi) joint fit using Ptheta framework. *T2K Technical Note*, (367), 2019.
- [127] K Abe, J Adam, H Aihara, T Akiri, C Andreopoulos, S Aoki, A Ariga, T Ariga, S Assylbekov, D Autiero, et al. Measurement of the neutrino-oxygen neutral-current interaction cross section by observing nuclear deexcitation gamma rays. *Physical Review D*, 90(7):072012, 2014.
- [128] Omar Benhar, Nicola Farina, Hiroki Nakamura, Makoto Sakuda, and Ryoichi Seki. Electron- and neutrino-nucleus scattering in the impulse approximation regime. *Physical Review D*, 72(5):053005, September 2005.
- [129] G. B. King, K. Mahn, L. Pickering, and N. Rocco. Comparing event generator predictions and ab initio calculations of $\nu - {}^{12}\text{C}$ neutral-current quasielastic scattering at 1 gev. *Phys. Rev. C*, 101:065502, Jun 2020.
- [130] Tomoyuki Tanaka, Kaito Hagiwara, and Gazzola et al. Gamma Ray Spectra from Thermal Neutron Capture on Gadolinium-155 and Natural Gadolinium. *arXiv:1907.00788 [hep-ex, physics:nucl-ex, physics:physics]*, February 2020. arXiv: 1907.00788.
- [131] Hiroyuki Sekiya. The super kamiokande gadolinium project. *Journal of Physics: Conference Series*, 1342(1):012044, jan 2020.
- [132] Tomislav Vladisavljevic. Constraining the t2k neutrino flux prediction with 2009 na61/shine replica-target data. June 2018. arXiv:1804.00272 [hep-ex, physics:physics].
- [133] Costas Andreopoulos, A Bell, D Bhattacharya, F Cavanna, J Dobson, S Dytman, H Gallagher, P Guzowski, R Hatcher, P Kehayias, et al. The genie neutrino monte carlo generator. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 614(1):87–104, 2010.

- [134] Georg Weidenspointner, MJ Harris, S Sturner, BJ Teegarden, and C Ferguson. Mgg-pod: a monte carlo suite for modeling instrumental line and continuum backgrounds in gamma-ray astronomy. *The Astrophysical Journal Supplement Series*, 156(1):69, 2005.
- [135] N Sagidova, A Yu Tsaregorodtsev, and A Vorobyov. G calor studies of background in the lhcb muon chambers. Technical report, CERN-LHCb-98-059, 1998.
- [136] C. Zeitnitz and T. A. Gabriel. The GEANT - CALOR interface and benchmark calculations of ZEUS test calorimeters. *Nucl. Instrum. Meth. A*, 349:106–111, 1994.
- [137] TA Gabriel. High energy transport code hetc. Technical report, Oak Ridge National Lab., TN (USA), 1985.
- [138] Yi Ge, Jingang Liang, Qiong Zhang, Wei Tang, and Agustin Munoz-Garcia. A comparison study of geant4 and mcnp6 on neutron-induced gamma simulation. *Applied Radiation and Isotopes*, 190:110514, 2022.
- [139] D.A. Brown et al. Endf/b-viii.0: The 8th major release of the nuclear reaction data library with cielo-project cross sections, new standards and thermal scattering data. *Nuclear Data Sheets*, 148:1–142, 2018. Special Issue on Nuclear Reaction Data.
- [140] Alex Shaw, Farzad Rahnema, Andrew Holcomb, and Doug Bowen. Validation of continuous-energy endf/b-viii.0 16o, 56fe, and 63,65cu cross sections for nuclear criticality safety applications. *Nuclear Science and Engineering*, 195(4):412–436, 2021.
- [141] Yoshinari Hayato. Neut. *Nuclear physics. B, Proceedings, supplements*, 112(1-3):171–176, 2002.
- [142] Aatos Heikkinen, Nikita Stepanov, and J. P. Wellisch. Bertini intra-nuclear cascade implementation in geant4, 2003.
- [143] JP Wellisch. On hadronic shower simulation. *Nuclear Physics B-Proceedings Supplements*, 78(1-3):738–743, 1999.
- [144] L. Wan. Experimental Studies on Low Energy Electron Antineutrinos and Related Physics. *PhD Thesis, Tsinghua University*, 2018.
- [145] K. Abe et al. Proposal for an Extended Run of T2K to 20×10^{21} POT. 9 2016.

A

Appendix A

A.1 Occupancy Plots for the UKLI MC B1 - B5 injector Autocalib data

As mentioned in Chapter 5, this Appendix gives all the relevant calibration plots for the B1-B5 injectors for the purposes of completeness. Figure A.1 shows the occupancy plots for the B1 - B5 collimators from the UKLI Autocalib July 2020 run, while Figure A.2 shows the occupancy plots for the B1 - B5 diffusers from the UKLI Autocalib July 2020 run. These show the beam spot in the unrolled volume of the detector, with the top left corner of each plot stating the date the data was taken, the run number, the run start and end time and the number of events. The timing window in which the time-of-flight cut has been applied is also stated, with the injector and target co-ordinates given in the top right and marked on the plots. The occupancy is the number of hits normalised to have a maximum of one, and the occupancy scale is shown on the right of the plots. As mentioned in Chapter 5, the intensely dark purple hits in Figure 5.9 are “hot channels” and have not been accounted for - these should not be mistaken for scattered hits.

A.2 Probability distribution functions and cumulative distribution functions for the B1 - B5 injectors

Figure A.3 shows the complete PDFs and CDFs for the B1 - B5 collimator data taken from the test stand at Warwick and Figure A.4 shows the complete PDFs and CDFs for the B1 - B5 diffusers. As mentioned in Chapter 5, the original fits to the collimator data did not reach 4 degrees so the probability distribution functions were extrapolated from 3.5 degrees

to 4 degrees. The cumulative distribution functions are normalised with a maximum of one using min-max scaling.

A.3 Fits to the cumulative distribution functions and their inverse for the B1-B5 injectors

This section gives the inverse of the cumulative distribution functions produced from the plots in the previous section for the collimator and diffuser optics. The top subplots show the normalised CDF data in blue and the polynomial fit to this data in red, while the bottom subplots show the inverse CDF of this polynomial in green and the fit applied to it in purple. Due to the more linear nature of the diffuser PDFs the differences to the cumulative distribution function and fit were reduced compared to the similar plots for the collimators.

Figure A.1: Occupancy plot for the collimator optics from the UKLI Autocalib July 2020 run for each barrel collimator in the unrolled volume of the SK detector. The crosses show the injector positions, and the collimator beam spots are also shown (the PMTs with highest occupancy). The corrected time-of-flight plots for the PMT hits is shown in the bottom right corner.



Figure A.2: Occupancy plot for the diffuser optics from the UKLI Autocalib July 2020 run for each barrel diffuser where the injector positions are shown by crosses. The corrected time-of-flight plots for the PMT hits is shown in the bottom right corner.







Figure A.3: PDFs and corresponding CDFs for the B1 - B5 collimators, with intensity in arbitrary units on the y-axis, and angle in degrees on the x-axis.





(g) B4 collimator PDF


(h) B4 collimator CDF




(i) B5 collimator PDF


(j) B5 collimator CDF

Figure A.4: PDFs and corresponding CDFs for the B1 - B5 diffusers, with intensity in arbitrary units on the y-axis, and angle in degrees on the x-axis.







(g) B4 diffuser PDF



(h) B4 diffuser CDF




(i) B5 diffuser PDF



(j) B5 diffuser CDF

Figure A.5: CDF and inverse CDF fits for the B1 - B5 collimator PDFs. The y-axis (range 0.0-1.0) on the top subplots for both figures shows the CDF values for the data (blue) and polynomial fit (red) while the x-axis for the top subplots shows the angle scan range for the collimator in degrees. For the bottom subplots which show the resulting inverse CDF function (green) and fit to this function (purple) these axes are reversed.



A.4 Monte Carlo simulations of the light profiles for the B1-B5 injectors

Figure A.7 shows the Monte Carlo simulations of the B1 - B5 collimators and Figure A.8 shows the Monte Carlo simulations of the B1 - B5 diffusers. Similar to the occupancy plots for data, these show the number of events in the run (all MC simulations were run with 1000 events) and the scale is normalised with a maximum of one. These plots also show the associated corrected time-of-flight plot in the bottom right hand corner, along with vertical lines overlayed to show the time window used to isolate the signal for the beam spots shown.

A.5 Validation check to the fits for the inverse cumulative distribution functions

Figure 5.19 shows the inverse CDF checks for the B1 - B5 diffusers. These were produced by running uniformly distributed random numbers through the function for the inverse cumulative distributions for the B1 - B5 diffusers. The output values produced show good adherence to the original probability distribution function showing that the inverse transform sampling of the original distribution was working correctly in SKDETSIM.

Figure A.6: CDF and inverse CDF fits for the B1 - B5 diffuser PDFs. The y-axis (range 0.0-1.0) on the top subplots for both figures shows the CDF values for the data (blue) and polynomial fit (red) while the x-axis for the top subplots shows the angle scan range for the diffuser in degrees. For the bottom subplots which show the resulting inverse CDF function (green) and fit to this function (purple) these axes are reversed.




Figure A.7: MC simulations of the B1 - B5 collimators




Figure A.8: MC simulations of the B1 - B5 diffusers




Figure A.9: Inverse CDF checks of the B1 - B5 diffusers

