Microsoft 365 Exchange Online Tenant-to-Tenant Migration (1:1 Domains) — Government (GCC High)

Implementation Solution Guide

Version 1.0.0 · 2026-07-01

Contents

Executive Summary — Exchange Online Tenant-to-Tenant Migration (Government / GCC High) 5

The situation . . . 5

The one decision that shapes the whole project . . . 5

What this solution provides . . . 5

Business outcome . . . 5

Effort and prerequisites . . . 6

Solution Overview — Microsoft 365 Exchange Online Tenant-to-Tenant Migration (1:1 Domains) — Government (GCC High) 6

Read this first — the cross-cloud caveat (do not skip) . . . 6

What this solution delivers . . . 6

The deployment model (Assess → Configure → Pilot → Validate → Expand, with gates) . . . 7

Commercial vs GCC High — what's different . . . 7

What's inside this solution . . . 8

Who this is for . . . 8

Requirements Guide — Exchange Online Tenant-to-Tenant Migration (Government / GCC High) 9

R0 — Both tenants are in the **same** sovereign cloud (GCC High) . . . 9

R1 — Migration method chosen and its support status confirmed . . . 9

R2 — Administrative roles in both tenants (GCC High portals) . . . 10

R3 — Licensing baseline (US Government plans) + Cross-Tenant User Data Migration add-on . . . 10

R4 — GCC High endpoints reachable and allow-listed (`*.us`) . . . 10

R5 — PowerShell modules installed and Gov-connectable . . . 11

R6 — DNS control for the migrating domain(s) . . . 11

R7 — (If not native) A GCC High-capable third-party tool or PST plan . . . 11

R8 — Change control, backup, and rollback (G5/G6 applied to this move) . . . 12

Requirements summary . . . 12

Implementation Guide — Exchange Online Tenant-to-Tenant Migration (Government / GCC High) 13

Phase A — Assess . . . 13

Phase B — Configure . . . 13

Phase C — Pilot . . . 15

Phase D — Validate & Expand . . . 15

Rollback (if a gate fails) . . . 16

Endpoint quick-reference (this engagement) . . . 16

Testing & Validation — Exchange Online Tenant-to-Tenant Migration (Government / GCC High) 16
Gate 0 — Environment sanity (before Assess) . . . 17
Gate 1 — Assess exit (readiness) . . . 17
Gate 2 — Configure exit . . . 17
Gate 3 — Pilot exit (the critical gate) . . . 18
Gate 4 — Per-wave validation (Expand) . . . 18
Gate 5 — Cutover validation . . . 19
Gate 6 — Closeout . . . 19
Notes on GCC High testing . . . 19
Troubleshooting — Exchange Online Tenant-to-Tenant Migration (Government / GCC High) 19
1. "Tenant not found" / login redirects to the wrong place / auth fails . . . 20
2. Native cross-tenant migration option is missing or blocked . . . 20
3. `CrossTenantMigrationWithoutLicensePermanentException` . . . 20
4. Target gets a new empty mailbox instead of the migrated one . . . 21
5. Proxy addresses disappear after licensing . . . 21
6. Domain won't verify in the target tenant . . . 21
7. Mail flow broken after MX cutover . . . 22
8. Reply NDRs on migrated threads . . . 22
9. Scripts/portals work in Commercial but "can't find" things in GCC High . . . 22
10. Endpoints blocked by proxy/firewall . . . 22
Escalation . . . 22
Sources . . . 23
Best Practices — Exchange Online Tenant-to-Tenant Migration (Government / GCC High) 23
1. Decide the migration engine before anything else . . . 23
2. Always pin the sovereign cloud in every tool and script . . . 23
3. Respect the licensing sequence (native) . . . 23
4. Gate every phase — never skip the pilot . . . 24
5. Protect data and stay compliant (GCC High context) . . . 24
6. DNS and cutover discipline . . . 24
7. Communications and endpoints . . . 24
8. Don't assume Commercial features exist . . . 24
9. Keep the three surfaces coherent . . . 25
Deliverables Summary — Exchange Online Tenant-to-Tenant Migration (Government / GCC High) 25
Documents (`source/`) . . . 25
Scripts (`scripts/`) . . . 25

How the deliverables work together 26
Scope boundaries 26
Appendix A — PowerShell Scripts 28

Executive Summary — Exchange Online Tenant-to-Tenant Migration (Government / GCC High)

The situation

Your organization needs to consolidate Exchange Online mailboxes and a primary email domain from one Microsoft 365 tenant into another **within the US sovereign cloud (GCC High)** — a 1:1-domain move. GCC High is **not** the Commercial service with a different sign-in: it uses different admin portals, different service endpoints, a different licensing channel, and — critically — **different migration support**. Runbooks copied from the Commercial cloud can connect to the wrong cloud or fail silently.

The one decision that shapes the whole project

Native (Microsoft-built) cross-tenant mailbox migration cannot cross cloud boundaries. Microsoft states: *"Cross cloud tenant to tenant migration isn't supported."*

- **Commercial** ↔ **GCC High** — native migration is **not available**; you must use a **third-party migration tool** (Quest, BitTitan, CloudM, Cloudiway, etc.) or **PST** for the mail data.
- **GCC High** → **GCC High** (same cloud) — native migration exists but reaches government clouds via **Public Preview**; confirm eligibility with Microsoft before relying on it. A third-party tool is a fully supported alternative.

This solution is authored **tool-agnostic**: it prepares both tenants correctly so whichever engine you use will succeed.

What this solution provides

A tested, novice-admin-friendly, click-to-implement runbook — plus **five PowerShell scripts** — that:

- Uses the correct `*.us` **GCC High portals and endpoints** throughout (`portal.office365.us`, `admin.exchange.office365.us`, `graph.microsoft.us`, `outlook.office365.us`, `login.microsoftonline.us`).
- Calls out every **Commercial-vs-GCC-High difference** at the step where it matters, with a fully **cited** parity reference.
- Follows a gated **Assess** → **Configure** → **Pilot** → **Validate** → **Expand** method, so nothing scales until a small pilot is proven.
- Ships **read-only** discovery/validation/reporting scripts and **safe (`-WhatIf`-by-default)** remediation and targeting scripts, all connecting to **US Gov** endpoints.

Business outcome

The migration is executed **correctly for the sovereign cloud** — right portals, right endpoints, licensing sequence respected, cross-cloud constraint handled up front — and **proven on a pilot before you scale**, protecting mail continuity for a government/DIB organization where a botched cutover is not an option.

Effort and prerequisites

Self-guided, at a fraction of typical consulting cost. Requires: both tenants in GCC High, appropriate US Gov licensing (G3/G5 GCC High) plus the Cross-Tenant User Data Migration add-on for a native move, Global Administrator / Organization Administrator / Move Mailboxes roles, DNS control for the migrating domain, and reachable `*.us` endpoints. Full detail in the Requirements Guide.

> *All GCC High specifics are cited to Microsoft US Government documentation or explicitly flagged "verify for GCC High." Nothing is invented.*

Solution Overview — Microsoft 365 Exchange Online Tenant-to-Tenant Migration (1:1 Domains) — Government (GCC High)

This is the **Government (GCC High)** edition of the Exchange Online tenant-to-tenant migration solution. It moves Exchange Online mailboxes and the primary email domain from one Microsoft 365 organization to another **within the US sovereign cloud**, using the correct `*.us` **admin portals and endpoints**, with every Commercial-vs-GCC-High difference called out at the point it matters.

If you are running the Commercial edition steps against a GCC High tenant, some of them **silently connect to the wrong cloud or fail outright**. This edition fixes that.

Read this first — the cross-cloud caveat (do not skip)

> ***Native (Microsoft-built) cross-tenant mailbox migration cannot cross cloud boundaries.*** *Microsoft states plainly: *"Cross cloud tenant to tenant migration isn't supported. An example scenario would be moving from Office 365 Worldwide to Office 365 Government Cloud."* (Microsoft Learn, *Cross-tenant mailbox migration*.)*

What this means for your project **before you plan anything**:

- **Commercial ↔ GCC High** (either direction): the native cross-tenant mailbox move is **not available**. You must use a **third-party migration tool** (Quest On Demand, BitTitan MigrationWiz, CloudM, Cloudiway, etc.) or a **PST export/import** for the actual mail data.
- **GCC High → GCC High** (both tenants in the same sovereign cloud): Microsoft's **native** cross-tenant mailbox migration exists but reaches government clouds via **Public Preview** and **later than Commercial** — **confirm current eligibility with Microsoft / your account team before relying on it.** (verify for GCC High.) A third-party tool remains a fully supported alternative.
- This solution is therefore authored **tool-agnostic**: it prepares *both* tenants correctly so that **whichever** mail-transfer engine you use — supported native same-cloud move, a third-party tool, or PST — will succeed. **The internals of any third-party migration tool are deferred to that vendor's own GCC High documentation.**

The full support matrix, endpoints, and licensing detail live in `gcc-high-parity-notes.md` (all cited).

What this solution delivers

A repeatable, novice-admin-friendly, click-to-implement runbook to:

1. **Assess** both the source and target GCC High tenants (mailbox inventory, licensing, DNS, endpoints, readiness gates) using read-only PowerShell against the **US Gov Graph and EXO endpoints**.
2. **Configure** identity, licensing, admin roles, endpoint allow-listing, and (for a supported native same-cloud move) the cross-tenant `OrganizationRelationship` — all in the **GCC High portals**.
3. **Pilot** a small named batch of mailboxes and prove the method end-to-end before scaling.
4. **Validate** mail flow, mailbox content, permissions, and the DNS/MX cutover with explicit pass/fail gates.
5. **Expand** to the full population in controlled waves, then cut over the primary domain.

Every step names the object it creates or reuses (a pilot group, a migration batch, an org relationship) so later steps build on earlier ones rather than starting over.

The deployment model (Assess → Configure → Pilot → Validate → Expand, with gates)

Phase	Goal	Exit gate (must pass before next phase)
Assess	Know both tenants: what mailboxes, what licenses, what DNS, what endpoints, what blockers	Discovery report clean; readiness checklist all green or waived in writing
Configure	Identity, licensing, roles, endpoints, and (if native) org relationship in place	Validation script passes on both tenants; migration engine can authenticate
Pilot	Move a small named batch and prove the method	Pilot mailboxes fully validated; no unresolved errors
Validate	Confirm content, mail flow, permissions, and cutover mechanics	All validation checks green; rollback rehearsed
Expand	Move remaining mailboxes in waves; cut over primary domain	Each wave validated; final MX/Autodiscover cutover confirmed

Gates are **hard stops**. Do not begin Configure until Assess is clean; do not Expand until the Pilot is validated.

Commercial vs GCC High — what's different

A concise orientation; the fully cited detail is in `gcc-high-parity-notes.md`.

1. **Cross-cloud native migration is unsupported** (see the caveat above). This is the single biggest planning difference — a Commercial↔GCC High move **cannot** use the native cross-tenant feature at all, and same-cloud GCC High native moves are **preview-gated**.
2. **Different admin portals.** You administer in `portal.office365.us` (M365 admin), `admin.exchange.office365.us` (Exchange), `entra.microsoft.us` (Entra),

`security.microsoft.us`, `compliance.microsoft.us`, `portal.azure.us` — never the Commercial `admin.microsoft.com` / `entra.microsoft.com`.

3. **Different endpoints for tooling.** Graph is `graph.microsoft.us` (`Connect-MgGraph -Environment USGov`); Exchange Online PowerShell is `outlook.office365.us` (`Connect-ExchangeOnline -ExchangeEnvironmentName O365USGovGCCHigh`); the login authority is `login.microsoftonline.us`. Omitting these makes tools authenticate against Commercial and fail.

4. **Different licensing channel.** Base mailbox licenses are **US Government plans (G3/G5 GCC High)** bought through an **authorized US Gov reseller / AOS-G partner**; the **Cross-Tenant User Data Migration** add-on availability on your Gov agreement must be **verified** before relying on a native move. (verify for GCC High.)

5. **Feature lag / gaps.** Some Commercial conveniences (e.g., Cross-Tenant Identity Mapping, Graph Explorer) are **not available** in GCC High. Assume newer features are absent until Microsoft documents them for US Gov. (verify for GCC High.)

6. **Separate firewall allow-list.** GCC High publishes its **own** endpoint list; you must allow the `.us` URLs/IPs, not the Commercial ranges.

What is the same: the migration *method and sequence*, the Exchange object model (MailUser/ExchangeGUID/proxy scrubbing), and the cmdlet *names*. Only the *endpoints, portals, licensing channel, and cross-cloud support* change.

What's inside this solution

• **This Solution Overview** and the cited **GCC High Parity Notes**.

• **Requirements Guide** (`02-requirements.md`) — every prerequisite with verify/implement steps, GCC High-specific.

• **Implementation Guide** (`03-implementation.md`) — ordered GCC High steps with inline caveats.

• **Testing** (`05-testing.md`) and **Troubleshooting** (`06-troubleshooting.md`) with pass/fail gates and GCC High gotchas.

• **Best Practices** (`07-best-practices.md`) and **Deliverables Summary** (`08-deliverables-summary.md`).

• **5 PowerShell scripts** — Discovery, Validation, Report (read-only), and Remediation + Set-ScopeTargeting (default `-WhatIf`) — all connecting to **US Gov Graph / EXO** endpoints.

Who this is for

Government tenant administrators, MSPs serving the Defense Industrial Base, and IT teams performing a 1:1-domain Exchange Online consolidation **within GCC High** — who need the sovereign-cloud-correct steps rather than Commercial steps that fail quietly.

Requirements Guide — Exchange Online Tenant-to-Tenant Migration (Government / GCC High)

These are the **solution-specific** requirements for a 1:1-domain Exchange Online tenant-to-tenant migration **within GCC High**. They are in addition to the category baseline in `global-requirements-azure-solutions.md` (G1–G6) — satisfy **both** sets before implementation.

Each requirement uses the same structure: **Description / Why required / How to verify (GCC High) / How to implement if missing.**

> *Throughout, "source tenant" is the GCC High organization you are migrating **from**; "target tenant" is the GCC High organization you are migrating **to**. All portal URLs are the `*.us` GCC High URLs.*

R0 — Both tenants are in the same sovereign cloud (GCC High)

Description. Source and target must both be **Microsoft 365 GCC High** tenants.

Why required. Native cross-tenant mailbox migration **cannot cross cloud boundaries** — "Cross cloud tenant to tenant migration isn't supported." (Microsoft Learn, *Cross-tenant mailbox migration*.) A Commercial↔GCC High move must instead use a third-party tool or PST for the mail data (see R7).

How to verify (GCC High). In each tenant sign in at `https://portal.office365.us` → confirm you reach the **GCC High** M365 admin center (not `admin.microsoft.com`). Confirm each initial domain is `*.onmicrosoft.us`. Run `EXOMIGG-Discovery.ps1`, which records the detected cloud/environment for each tenant.

How to implement if missing. If the tenants are in different clouds, do **not** attempt a native move — adopt the third-party-tool or PST path (R7). If a tenant is not yet GCC High, provisioning/migrating it into GCC High is a separate prerequisite project via an authorized US Gov reseller.

R1 — Migration method chosen and its support status confirmed

Description. A decision, recorded in the change plan, of **which engine moves the mail**: (a) native same-cloud cross-tenant move (GCC High→GCC High only), (b) a third-party migration tool, or (c) PST export/import.

Why required. The native path is **Public Preview** for government clouds and reaches GCC High **later than Commercial**; you must confirm it is available and supported for your tenants before depending on it. (verify for GCC High — confirm with Microsoft / your account team.)

How to verify (GCC High). Obtain written confirmation from Microsoft support / your account team on native cross-tenant availability for your GCC High tenants, **or** confirm your chosen third-party vendor documents a GCC High / US Gov path. Record the decision.

How to implement if missing. If native availability cannot be confirmed, select a third-party tool with an explicit GCC High guide, or plan PST. **Third-party tool setup is deferred to that vendor's GCC High documentation.**

R2 — Administrative roles in both tenants (GCC High portals)

Description. Named operator accounts holding the least-privilege roles for a cross-tenant move.

Why required. "Two roles are required" for a native move — **Organization Administrator** (one-time setup of the `OrganizationRelationship` / `-MailboxMoveCapability`) and **Move Mailboxes** (executing moves). (Microsoft Learn, *Cross-tenant mailbox migration*.) **Global Administrator** is needed to consent the migration app / cross-tenant config.

How to verify (GCC High). In `https://entra.microsoft.us` → **Identity** → **Roles & admins** → **Roles**, confirm assignments. In `https://admin.exchange.office365.us` → **Roles** → **Admin roles**, confirm the **Organization Management** role group membership and a **Move Mailboxes**-capable role. Prefer **PIM-eligible** (time-bound) assignments.

How to implement if missing. Have an existing Global Administrator assign the roles in `entra.microsoft.us`; assign Exchange role groups in `admin.exchange.office365.us`.

R3 — Licensing baseline (US Government plans) + Cross-Tenant User Data Migration add-on

Description. Target-tenant Exchange Online licenses for every migrated user (US Gov plans, e.g., **Office 365 G3/G5 GCC High** or **Microsoft 365 G3/G5 GCC High**), plus — **for a native move** — the **Cross-Tenant User Data Migration** per-user add-on.

Why required. Users must be licensed in the target for a mailbox to activate. For a **native** move, the Cross-Tenant User Data Migration license is **enforced**: "Migrations fail if this step isn't completed. Microsoft doesn't offer exceptions for this licensing requirement." (Microsoft Learn, *Cross-tenant mailbox migration*.) Third-party/PST paths do not require this add-on.

How to verify (GCC High). In `https://portal.office365.us` → **Billing** → **Licenses**, confirm owned quantities and, for native, that the **Cross-Tenant User Data Migration** SKU is present/orderable on your Gov agreement. **(verify for GCC High — confirm the add-on is available on your contract vehicle before relying on native.)**

How to implement if missing. Purchase US Gov licenses and the add-on through your **authorized US Gov reseller / AOS-G partner** (not the Commercial storefront). Note the license-before-ExchangeGUID caveat: do **not** license the target MailUser before its `ExchangeGUID` is stamped, or a new empty mailbox is provisioned instead. (Microsoft Learn, same.)

R4 — GCC High endpoints reachable and allow-listed (`*.us`)

Description. Outbound connectivity from operator workstations (and any migration hosts) to the **GCC High** service endpoints, through corporate proxy/firewall.

Why required. GCC High uses a **separate** endpoint list from Commercial; the tooling talks to `login.microsoftonline.us`, `graph.microsoft.us`, `outlook.office365.us`, and the `*.us` portals. Blocked `.us` endpoints cause auth/operation failures.

How to verify (GCC High). From an operator workstation confirm you can reach `https://portal.office365.us`, `https://admin.exchange.office365.us`,

`https://entra.microsoft.us`, and that `Connect-MgGraph -Environment USGov` and `Connect-ExchangeOnline -ExchangeEnvironmentName O365USGovGCCHigh` succeed. Reference Microsoft's **Office 365 U.S. Government GCC High endpoints** article.

How to implement if missing. Allow-list the GCC High `.us` URLs/IP ranges on the proxy/firewall per that article; ensure **TLS 1.2+**. Do **not** rely on the Commercial "Office 365 URLs and IP address ranges" list.

R5 — PowerShell modules installed and Gov-connectable

Description. Current **ExchangeOnlineManagement** and **Microsoft.Graph** PowerShell modules on the operator workstation, connectable to the **US Gov** endpoints.

Why required. All five scripts in this solution connect via `-Environment USGov` (Graph) and `-ExchangeEnvironmentName O365USGovGCCHigh` (EXO). Old modules may lack these environment values.

How to verify (GCC High). `Get-Module -ListAvailable ExchangeOnlineManagement, Microsoft.Graph` shows current versions. Run `EXOMIGG-Validation.ps1`, which checks module presence and a successful Gov connection to both tenants.

How to implement if missing. `Install-Module ExchangeOnlineManagement -Scope CurrentUser` and `Install-Module Microsoft.Graph -Scope CurrentUser` (PowerShell 7 recommended). Update with `Update-Module`.

R6 — DNS control for the migrating domain(s)

Description. Administrative access to the public DNS zone(s) for the 1:1 domain(s) being moved (MX, Autodiscover, SPF, DKIM, DMARC).

Why required. A 1:1-domain move requires **removing** the domain from the source tenant and **verifying** it in the target, then cutting over MX/Autodiscover. Domain verification in the target **fails while the domain is still in use in the source** (expected) — you must control DNS to complete the move.

How to verify (GCC High). Confirm you can create/modify TXT/MX/CNAME records at the registrar/DNS host. Capture current records (baseline) with `EXOMIGG-Discovery.ps1` and store them for rollback (G6).

How to implement if missing. Obtain DNS delegation/credentials from whoever controls the zone; lower MX TTL (e.g., to 5 minutes) ahead of cutover.

R7 — (If not native) A GCC High-capable third-party tool or PST plan

Description. For any Commercial↔GCC High move, and as the supported alternative for GCC High→GCC High, a migration tool that **documents a GCC High / US Gov path**, or a PST export/import plan.

Why required. Native cross-cloud is unsupported (R0); a tool or PST is the only way to move the mail data across clouds.

How to verify (GCC High). Confirm the vendor lists **GCC High / US Gov** as a supported source/target and that its app registers against `login.microsoftonline.us` (US Gov instance). For PST, confirm export capacity and secure handling of CUI/ITAR-scoped data.

How to implement if missing. Select a vendor with an explicit GCC High guide (e.g., Quest On Demand, BitTitan MigrationWiz, CloudM, Cloudiway) and follow **their** GCC High onboarding. **Tool internals are out of scope here and deferred to the vendor.**

R8 — Change control, backup, and rollback (G5/G6 applied to this move)

Description. Approved change window, communication plan, and a captured pre-change baseline (DNS records, mailbox inventory, permissions) with written rollback steps.

Why required. Domain move and MX cutover are disruptive and user-facing. A baseline and rehearsed rollback protect against data loss and prolonged outage.

How to verify (GCC High). Confirm an approved change record with window, owner, comms plan, and rollback criteria; confirm `EXOMIGG-Discovery.ps1`/`EXOMIGG-Report.ps1` baselines are stored.

How to implement if missing. Raise the change; run the discovery/report scripts to capture the baseline; write the rollback (re-point MX to source, re-add domain to source) into the change record.

Requirements summary

ID	Requirement	GCC High specific?
R0	Both tenants in the same GCC High cloud	**Yes** (cross-cloud unsupported)
R1	Migration method chosen + support confirmed	**Yes** (native = preview)
R2	Admin roles (Org Admin, Move Mailboxes, Global Admin) in `*.us` portals	Yes (portals)
R3	US Gov licensing + Cross-Tenant User Data Migration add-on (native)	**Yes** (channel + availability)
R4	GCC High `*.us` endpoints reachable & allow-listed	**Yes**
R5	ExchangeOnlineManagement + Microsoft.Graph, Gov-connectable	Yes (env values)
R6	DNS control for the 1:1 domain(s)	No (same as Commercial)
R7	GCC High-capable third-party tool or PST plan (if not native)	**Yes**
R8	Change control, backup, rollback	No (same as Commercial)

Implementation Guide — Exchange Online Tenant-to-Tenant Migration (Government / GCC High)

Ordered, click-to-implement steps for a 1:1-domain Exchange Online migration **within GCC High**. Every portal path uses the `*.us` GCC High URLs. GCC-High-only caveats are called out **inline at the step where they matter**.

> ***Before Step 1:*** *complete the Requirements Guide (`02-requirements.md`, R0–R8) and the category baseline (G1–G6). Confirm* ***R0*** *(both tenants GCC High) and* ***R1*** *(migration method + support status) — these gate everything below.* ***Object naming (reused across steps).*** *Create and reuse these named objects: a pilot group `EXOMIGG-Pilot`, wave groups `EXOMIGG-Wave1..N`, a migration endpoint / org relationship named `EXOMIGG-CrossTenant`, and a working folder `EXOMIGG-baseline\` holding all exports. Later steps refer to these by name.*

Phase A — Assess

Step 1. Establish sovereign-cloud connections

On the operator workstation (PowerShell 7):

```
# Exchange Online — GCC High
Connect-ExchangeOnline -ExchangeEnvironmentName O365USGovGCCHigh -UserPrincipalName admin@source-tenant.on
# Microsoft Graph — US Gov
Connect-MgGraph -Environment USGov -Scopes 'User.Read.All','Organization.Read.All','Directory.Read.All'
```

> ***GCC High caveat.*** *Omitting `-ExchangeEnvironmentName O365USGovGCCHigh` or `-Environment USGov` makes the modules authenticate against the* ***Commercial*** *cloud (`login.microsoftonline.com`) and fail for a GCC High tenant. `-ExchangeEnvironmentName O365USGovGCCHigh` auto-selects `outlook.office365.us` and the `login.microsoftonline.us/organizations` authority — do* ***not*** *also pass `-ConnectionUri`. (Microsoft Learn, *Connect to Exchange Online PowerShell*.)*

Step 2. Run Discovery (read-only) on both tenants

Run `EXOMIGG-Discovery.ps1` against the **source**, then the **target**. It captures: detected cloud/environment, mailbox inventory and sizes, licensing, DNS/MX/Autodiscover/SPF/DKIM/DMARC for the migrating domain(s), and admin-role holders — writing them into `EXOMIGG-baseline\`.

This baseline satisfies **G6/R8** (rollback) and feeds the readiness gate.

Step 3. Readiness gate (Assess exit)

Confirm from the Discovery output: both tenants are GCC High (R0); target has enough US Gov licenses (R3); DNS is under your control (R6); endpoints reachable (R4); roles assigned (R2). **Do not proceed to Configure until this is clean or exceptions are waived in writing.**

Phase B — Configure

Step 4. Assign/confirm admin roles (GCC High portals)

• In `https://entra.microsoft.us` → **Identity** → **Roles & admins** → **Roles**, confirm **Global Administrator** on the account that will consent the migration configuration.

• In `https://admin.exchange.office365.us` → **Roles** → **Admin roles**, confirm **Organization Management** (for the one-time `OrganizationRelationship`) and a **Move Mailboxes**-capable role for the operator running batches.

> ***GCC High caveat.*** *These are the `*.us` portals — the Commercial `entra.microsoft.com` / `admin.exchange.microsoft.com` will not show your GCC High tenant.*

Step 5. Prepare target licensing

In `https://portal.office365.us` → **Billing** → **Licenses**, confirm US Gov mailbox licenses for every migrated user. **For a native move**, confirm the **Cross-Tenant User Data Migration** add-on is present.

> ***GCC High caveat.*** *Buy through your **authorized US Gov reseller / AOS-G partner**. **verify for GCC High:** confirm the Cross-Tenant User Data Migration add-on is orderable on your Gov agreement **before** relying on a native move; if not, use the third-party/PST path (Step 7B). **Do not license the target MailUser before its** `ExchangeGUID` **is stamped** — doing so provisions a new empty mailbox instead of accepting the move. (Microsoft Learn, *Cross-tenant mailbox migration*.)*

Step 6. Allow-list endpoints and validate connectivity

Ensure the proxy/firewall allows the **GCC High** `.us` endpoints (R4). Then run `EXOMIGG-Validation.ps1` against both tenants — it verifies module versions, a successful Gov connection, role presence, license counts, and endpoint reachability, and reports **pass/fail** per check.

Step 7. Configure the migration engine

Choose **one** path per the decision in R1:

7A — Native same-cloud move (GCC High → GCC High only, if confirmed available).

• In the **target** tenant, set up the cross-tenant `OrganizationRelationship` named `EXOMIGG-CrossTenant` and its `-MailboxMoveCapability` (Organization Administrator only). Register/consent the migration application in **both** tenants against `login.microsoftonline.us`.

• Build the target-side **MailUser** objects (mail-enabled users) carrying the source **ExchangeGUID** and proxy addresses, so the move converts them to mailboxes rather than creating new ones.

• Use `EXOMIGG-Set-ScopeTargeting.ps1` (default `-WhatIf`) to build the pilot/wave target groups from a mapping CSV.

> ***GCC High caveat.*** *Every app registration, consent, and endpoint here is the `.us` instance. **verify for GCC High:** the native cross-tenant feature is **Public Preview** in government clouds — confirm eligibility for your tenants before enabling. Newer conveniences like **Cross-Tenant Identity Mapping** should be assumed **unavailable** in GCC High until Microsoft documents otherwise. (Microsoft Learn, *national cloud deployments*.)*

7B — Third-party tool or PST (required for cross-cloud; supported alternative for same-cloud).

• Register the vendor's application against the **US Gov instance** (`login.microsoftonline.us`) in both tenants and select the vendor's **GCC High** service. Provide the mailbox-mapping CSV (map using the `*.onmicrosoft.us` initial domains).

- **Tool internals — batch configuration, throttling, delta passes — are deferred to that vendor's GCC High documentation.**

Step 8. Configure gate (Configure exit)

`EXOMIGG-Validation.ps1` passes on **both** tenants and the chosen engine can authenticate. Only then proceed to Pilot.

Phase C — Pilot

Step 9. Prepare the pilot domain/DNS (non-disruptive prep)

In `https://portal.office365.us` (target) → **Settings** → **Domains**, **add** the migrating domain and create the verification **TXT** record in DNS.

> ***Expected behavior (same as Commercial):*** *verification* ***fails while the domain is still in use in the source tenant****. Adding it now lets DNS propagate (up to 72h). Final verification happens at cutover.*

Lower the domain's **MX TTL** (e.g., to 5 minutes) ahead of any cutover.

Step 10. Migrate the pilot batch

Populate `EXOMIGG-Pilot` with a small set of low-risk, named test mailboxes. Run the move for just this group using the engine from Step 7 (native `New-MigrationBatch`/`New-MoveRequest`, or the vendor tool). Monitor to completion.

Step 11. Validate the pilot (Pilot exit gate)

Run `EXOMIGG-Report.ps1` for the pilot mailboxes and perform the checks in `05-testing.md`: content present, folder counts match, permissions/delegation intact, mail flow to/from works. **Do not expand until every pilot mailbox passes and there are no unresolved errors.**

Phase D — Validate & Expand

Step 12. Build waves

Use `EXOMIGG-Set-ScopeTargeting.ps1` (default `-WhatIf`; re-run with `-Execute`/`-Confirm` only after reviewing the WhatIf output) to assign the remaining mailboxes to `EXOMIGG-Wave1..N` from the mapping CSV. Keep waves sized to your validated throughput.

Step 13. Migrate waves with validation between each

For each wave: run the move, then `EXOMIGG-Report.ps1` + the `05-testing.md` checks. Treat each wave's validation as a gate before the next.

Step 14. Source-side domain release and target verification (cutover prep)

On cutover day, in the **source** tenant remove the migrating domain from all objects (reset default addresses to `*.onmicrosoft.us`, strip proxy addresses, set default domain to the initial domain). Then complete **domain verification in the target** (`portal.office365.us` → Domains).

> ***GCC High caveat.*** *All of this is in the `*.us` portals. The domain cannot verify in the target until fully released from the source — expect a short window after release before target verification succeeds.*

Step 15. MX / Autodiscover cutover

Point the domain's **MX** and **Autodiscover CNAME** to the **target** GCC High tenant. When the (lowered) TTL expires, mail flows to the migrated mailboxes. Recreate transport rules, connectors, and allow/block lists in the target. Verify mail flow both directions.

Step 16. Post-migration cleanup and closeout

Clear Outlook Auto-Complete (nickname cache) or add legacy DN as an X.500 proxy to avoid NDRs. Run a final `EXOMIGG-Report.ps1` across all migrated mailboxes and archive it with the change record. Confirm rollback baseline is retained for the agreed period.

Rollback (if a gate fails)

Re-point **MX/Autodiscover to the source** tenant (records captured in `EXOMIGG-baseline\`), re-add the domain to the source if it was released, and re-enable source mailboxes. Because moves are staged in waves behind gates, rollback scope is limited to the current wave.

Endpoint quick-reference (this engagement)

Purpose	GCC High value
M365 admin center	`https://portal.office365.us`
Exchange admin center	`https://admin.exchange.office365.us`
Entra admin center	`https://entra.microsoft.us`
Defender / Purview	`https://security.microsoft.us` / `https://compliance.microsoft.us`
EXO PowerShell	`Connect-ExchangeOnline -ExchangeEnvironmentName O365USGovGCCHigh`
Graph PowerShell	`Connect-MgGraph -Environment USGov`
Login authority	`https://login.microsoftonline.us`

Full cited detail: `gcc-high-parity-notes.md`.

Testing & Validation — Exchange Online Tenant-to-Tenant Migration (Government / GCC High)

Each phase in the Implementation Guide ends with a **gate**. This document defines the pass/fail checks for those gates. Run the read-only scripts (`EXOMIGG-Validation.ps1`, `EXOMIGG-Report.ps1`) plus the manual checks below. **A gate passes only when every check is PASS or explicitly waived in writing.**

> *All connections use the GCC High endpoints (`-ExchangeEnvironmentName O365USGovGCCHigh`, `-Environment USGov`). A "connected to wrong cloud" failure (see `06-troubleshooting.md`) invalidates the entire test run.*

Gate 0 — Environment sanity (before Assess)

#	Check	How	PASS
0.1	Correct cloud	`EXOMIGG-Discovery.ps1` reports environment per tenant	Both show **GCC High / USGov**, initial domains `*.onmicrosoft.us`
0.2	Modules current	`EXOMIGG-Validation.ps1`	ExchangeOnlineManagement + Microsoft.Graph present and Gov-connectable
0.3	Endpoints reachable	`EXOMIGG-Validation.ps1`	`login.microsoftonline.us`, `graph.microsoft.us`, `outlook.office365.us` reachable

FAIL 0.1 = you are pointed at Commercial; fix connection parameters before anything else.

Gate 1 — Assess exit (readiness)

#	Check	How	PASS
1.1	Both tenants GCC High (R0)	Discovery	Confirmed same sovereign cloud
1.2	Migration method + support (R1)	Change record	Native availability confirmed **or** third-party/PST path selected
1.3	Target licensing (R3)	Discovery / `portal.office365.us`	Enough US Gov mailbox licenses; native add-on present/orderable (verify for GCC High)
1.4	Roles (R2)	Discovery	Org Admin + Move Mailboxes + Global Admin assigned
1.5	DNS control (R6)	Manual	Can edit MX/TXT/CNAME for the domain
1.6	Baseline captured (R8/G6)	`EXOMIGG-baseline\`	DNS, mailbox inventory, permissions exported

Gate 2 — Configure exit

#	Check	How	PASS
2.1	Validation clean, both tenants	`EXOMIGG-Validation.ps1`	All checks PASS on source **and** target
2.2	Engine authenticates	Native: org relationship set; Tool: vendor connectivity test	Chosen engine connects to **both** GCC High tenants via `login.microsoftonline.us`
2.3	Target MailUsers correct (native)	`EXOMIGG-Report.ps1`	Target MailUsers carry source **ExchangeGUID** + proxies; **not** prematurely licensed
2.4	Domain pre-added	`portal.office365.us` → Domains	Domain added to target; TXT created (verification pending is expected)

Gate 3 — Pilot exit (the critical gate)

Run for every mailbox in `EXOMIGG-Pilot`:

#	Check	How	PASS
3.1	Move completed	Batch status / `EXOMIGG-Report.ps1`	Status Completed, no errors
3.2	Content present	Open OWA in target (`outlook.office365.us`)	Inbox, Sent, Calendar, Contacts present
3.3	Folder counts	`EXOMIGG-Report.ps1` item counts source vs target	Counts match within expected delta
3.4	Permissions/delegation	`Get-MailboxPermission` / `Get-RecipientPermission`	Delegates, SendAs, SendOnBehalf intact
3.5	Mail flow	Send/receive test to a pilot mailbox	Inbound + outbound succeed
3.6	Free/busy & calendar	Meeting invite test	Calendar and free/busy resolve

Any FAIL here stops expansion. Diagnose in `06-troubleshooting.md`, remediate (`EXOMIGG-Remediation.ps1`, default `-WhatIf`), re-test.

Gate 4 — Per-wave validation (Expand)

Repeat Gate 3 checks for each `EXOMIGG-WaveN` after its move. Do not start the next wave until the current wave is fully PASS.

Gate 5 — Cutover validation

#	Check	How	PASS
5.1	Domain released (source)	`Get-MsolUser -DomainName <domain>` equiv. / Discovery	No objects still bind the domain in source
5.2	Domain verified (target)	`portal.office365.us` → Domains	Domain shows **Verified** in target
5.3	MX cutover	`nslookup -type=mx <domain>` / MxToolbox	MX points to target GCC High
5.4	Autodiscover	Outlook profile rebuild	Autodiscover resolves to target
5.5	Mail flow both ways post-cutover	Test messages	External inbound + outbound OK
5.6	Transport rules/connectors	Target EAC	Rules/connectors/allow-block recreated

Gate 6 — Closeout

#	Check	How	PASS
6.1	Final report archived	`EXOMIGG-Report.ps1` (all mailboxes)	Stored with change record
6.2	NDR mitigation	Auto-Complete cleared / X.500 added	No reply NDRs on migrated threads
6.3	Rollback baseline retained	`EXOMIGG-baseline\`	Retained per policy

Notes on GCC High testing

- **Validate with PowerShell, not Graph Explorer** — Graph Explorer is **not supported** in GCC High. (Microsoft Learn, *national cloud deployments*.)
- **OWA URL is** `outlook.office365.us`, not `outlook.office.com`.
- If any test tool "can't find the tenant," it is almost always pointed at the **Commercial** endpoint — recheck `-Environment USGov` / `-ExchangeEnvironmentName O365USGovGCCHigh`.

Troubleshooting — Exchange Online Tenant-to-Tenant Migration (Government / GCC High)

Diagnosis for the failures you actually hit during a GCC High move. Symptoms are grouped; each has cause, GCC-High context, and fix. Run the read-only scripts (`EXOMIGG-Validation.ps1`, `EXOMIGG-Report.ps1`) to confirm state before and after any change.

1. "Tenant not found" / login redirects to the wrong place / auth fails

Symptom. `Connect-MgGraph` or `Connect-ExchangeOnline` errors, redirects to `login.microsoftonline.com`, or reports the tenant doesn't exist even though it does.

Cause. The tool is authenticating against the **Commercial** cloud. This is the single most common GCC High problem.

Fix.

- Exchange: `Connect-ExchangeOnline -ExchangeEnvironmentName O365USGovGCCHigh` (do **not** also pass `-ConnectionUri`).
- Graph: `Connect-MgGraph -Environment USGov`.
- Confirm the sign-in URL is `login.microsoftonline.us` and portals are `*.us`.
- Update modules if the environment value is unrecognized (R5). (Microsoft Learn, *Connect to Exchange Online PowerShell*; *national cloud deployments*.)

2. Native cross-tenant migration option is missing or blocked

Symptom. The native cross-tenant move can't be configured, or an org-relationship `-MailboxMoveCapability` step fails.

Cause. Either a **cross-cloud** attempt (unsupported) or a **preview-availability** gap in GCC High.

Fix.

- If either tenant is **Commercial**: native is **not supported** across clouds — switch to a **third-party tool or PST** (R7). *"Cross cloud tenant to tenant migration isn't supported."*
- If both are **GCC High**: native cross-tenant is **Public Preview** in government clouds — **confirm eligibility with Microsoft / your account team** before proceeding. Use a third-party tool if preview access isn't available. (verify for GCC High.)
- Ensure the org relationship is created by an **Organization Administrator** — "Only the organization administrator can alter the `-MailboxMoveCapability` setting." (Microsoft Learn.)

3. `CrossTenantMigrationWithoutLicensePermanentException`

Symptom. A native move fails with: *"No license was found for the source recipient … or the target recipient. A Cross-tenant User Data Migration license is required."*

Cause. Missing the **Cross-Tenant User Data Migration** add-on. It is enforced — "Migrations fail if this step isn't completed. Microsoft doesn't offer exceptions."

Fix. Assign the add-on to the migrating user (source or target object). In GCC High, purchase it through your **authorized US Gov reseller / AOS-G partner**; **verify it is orderable on your Gov agreement** — if not, use a third-party/PST path (which doesn't require it). (Microsoft Learn, *Cross-tenant mailbox migration*.)

4. Target gets a new empty mailbox instead of the migrated one

Symptom. After the move (or after licensing), the target user has an empty mailbox rather than the source content.

Cause. A license (Exchange plan) was applied to the target MailUser **before** its `ExchangeGUID` was stamped, provisioning a new mailbox; or the target MailUser had a **mismatched previous ExchangeGUID**.

Fix.

- Do **not** license the target MailUser before `ExchangeGUID` + proxies are set; assign licenses during the 30-day grace window after the move.
- Clear a mismatched GUID: `Set-User <identity> -PermanentlyClearPreviousMailboxInfo`, then re-stamp the source `ExchangeGUID`. `EXOMIGG-Remediation.ps1` performs this (default `-WhatIf`). (Microsoft Learn.)

5. Proxy addresses disappear after licensing

Symptom. External/secondary SMTP addresses (e.g., an unverified domain) vanish from a MailUser after an Exchange plan is applied.

Cause. Proxy-address scrubbing — when an Exchange service plan is applied, Entra ID removes SMTP addresses on domains the local tenant hasn't verified (anti-spoofing).

Fix. Expected behavior. To retain external branding, strip the license until after the move, or verify the domain first. Plan address handling accordingly. (Microsoft Learn.)

6. Domain won't verify in the target tenant

Symptom. Adding the migrating domain in the target (`portal.office365.us` → Domains) fails verification.

Cause. The domain is still in use in the **source** tenant (expected until release), or DNS TXT hasn't propagated.

Fix.

- Before cutover, **verification failing is normal** — pre-adding just lets DNS propagate (up to 72h).
- At cutover, fully **release** the domain from the source (reset default/proxy addresses to `*.onmicrosoft.us`, set default domain to initial), then verify in target. Use `Get-Recipient`/Discovery to find lingering objects still binding the domain.

7. Mail flow broken after MX cutover

Symptom. Inbound mail bounces or doesn't arrive after pointing MX to the target.

Cause. TTL not expired, MX/Autodiscord pointing to wrong tenant, or transport rules/connectors not recreated in target.

Fix.

- Verify MX with `nslookup -type=mx <domain>` / MxToolbox; wait out the (lowered) TTL.
- Recreate transport rules, connectors, and allow/block lists in the **target** EAC (`admin.exchange.office365.us`).
- If needed, roll back: re-point MX/Autodiscover to source from the `EXOMIGG-baseline\` records.

8. Reply NDRs on migrated threads

Symptom. Users get NDRs replying to pre-migration emails.

Cause. Outlook Auto-Complete (nickname cache) holds old legacy DN routing.

Fix. Clear the Auto-Complete list, or add the old legacy DN as an **X.500** proxy address on migrated users.

9. Scripts/portals work in Commercial but "can't find" things in GCC High

Symptom. A step from a Commercial guide references a portal/feature that doesn't exist for you.

Cause. GCC High **feature lag/absence** and different URLs. Graph Explorer, Cross-Tenant Identity Mapping, and some newer conveniences are **not available** in GCC High.

Fix. Map every Commercial reference through `gcc-high-parity-notes.md`. Validate Graph via **PowerShell**, not Graph Explorer. Assume a newer Commercial feature is absent until Microsoft documents it for US Gov. (verify for GCC High; Microsoft Learn, *national cloud deployments*.)

10. Endpoints blocked by proxy/firewall

Symptom. Timeouts reaching `graph.microsoft.us`, `outlook.office365.us`, or the `*.us` portals.

Cause. Firewall allow-lists Commercial ranges only; GCC High uses a **separate** endpoint list.

Fix. Allow-list the **GCC High** `.us` URLs/IPs from Microsoft's *Office 365 U.S. Government GCC High endpoints* article; ensure **TLS 1.2+**. Re-check monthly (GCC High publishes changes 30 days ahead).

Escalation

If a native move remains blocked after the above and both tenants are confirmed GCC High, open a Microsoft support case referencing **cross-tenant mailbox migration in GCC High (Public Preview)** and confirm current availability for your tenants. For cross-cloud moves, do not escalate for native support — it does not exist; proceed with a third-party tool or PST.

Sources

• Microsoft Learn — *Cross-tenant mailbox migration* (`learn.microsoft.com/microsoft-365/enterprise/cross-tenant-mailbox-migration`).

• Microsoft Learn — *How to migrate mailboxes … to another* (`learn.microsoft.com/exchange/mailbox-migration/migrate-mailboxes-across-tenants`).

• Microsoft Learn — *Connect to Exchange Online PowerShell* (`learn.microsoft.com/powershell/exchange/connect-to-exchange-online-powershell`).

• Microsoft Learn — *Microsoft Graph national cloud deployments* (`learn.microsoft.com/graph/deployments`).

• Microsoft Learn — *Microsoft 365 U.S. Government GCC High endpoints*.

Best Practices — Exchange Online Tenant-to-Tenant Migration (Government / GCC High)

Field-tested guidance for running a 1:1-domain Exchange Online migration **within GCC High**. These complement the ordered steps in `03-implementation.md`; they do not replace them.

1. Decide the migration engine before anything else

• **Confirm the cloud boundary first.** If either tenant is Commercial, native cross-tenant migration is **off the table** — commit to a third-party tool or PST immediately and stop planning around native. (Microsoft Learn: cross-cloud not supported.)

• For **GCC High** → **GCC High**, treat native cross-tenant migration as **Public Preview** and **confirm eligibility in writing** with Microsoft / your account team before you design around it. Keep a third-party tool as a fallback so the project is not blocked by preview availability. (verify for GCC High.)

2. Always pin the sovereign cloud in every tool and script

• Bake `-ExchangeEnvironmentName O365USGovGCCHigh` and `-Environment USGov` into every connection — never rely on defaults. The most common GCC High failure is a script silently authenticating against Commercial.

• Use the `*.us` **portals** exclusively (`portal.office365.us`, `admin.exchange.office365.us`, `entra.microsoft.us`, `security.microsoft.us`, `compliance.microsoft.us`, `portal.azure.us`). Bookmark them to avoid muscle-memory Commercial URLs.

• Register **every** migration/vendor app against `login.microsoftonline.us` and the vendor's **US Gov** service instance.

3. Respect the licensing sequence (native)

• Purchase US Gov licenses and the **Cross-Tenant User Data Migration** add-on through an **authorized US Gov reseller / AOS-G partner** — and **verify the add-on is orderable on your agreement before relying on native**. (verify for GCC High.)

• **Never license the target MailUser before its** `ExchangeGUID` **is stamped** — that provisions a new empty mailbox and breaks the move. Assign licenses during the 30-day grace period after the move, or only once the ExchangeGUID and proxies are correct. (Microsoft Learn.)

• Expect **proxy-address scrubbing**: unverified SMTP domains are removed when an Exchange plan is applied. Plan address/branding accordingly.

4. Gate every phase — never skip the pilot

• Treat the **Pilot exit** as the hard gate: no expansion until every pilot mailbox passes content, permissions, and mail-flow checks.

• Migrate in **named waves** (`EXOMIGG-Wave1..N`), validating between each. Size waves to your **validated** throughput, not an optimistic estimate.

• Keep the phase gates from `05-testing.md` as documented, signed-off checkpoints in the change record.

5. Protect data and stay compliant (GCC High context)

• GCC High hosts **CUI/ITAR/DFARS-scoped** data. Keep migration hosts, PST files, mapping CSVs, and reports **inside** the authorized boundary; do not export CUI to Commercial workstations or storage.

• Prefer **certificate-based / app-only** auth for unattended scripts over stored passwords; use **PIM-eligible** (time-bound) admin roles.

• Never place tenant secrets, tokens, or full mailbox exports in shared or public locations. Redact identifiers in any report shared outside the boundary.

6. DNS and cutover discipline

• **Lower MX TTL early** (e.g., 5 minutes) so cutover is fast and reversible.

• **Pre-add** the domain to the target and create the TXT record days ahead — verification failing while the domain is still in the source is **expected**, not an error.

• Have the **rollback** (re-point MX/Autodiscover to source, re-add domain to source) written and rehearsed before cutover day.

7. Communications and endpoints

• Notify users the **OWA URL is** `outlook.office365.us` and that Outlook profiles may need rebuilding; clear Auto-Complete to avoid NDRs.

• Allow-list the **GCC High endpoint list** (`.us`) on proxies/firewalls, and re-check monthly — GCC High publishes changes 30 days ahead on its **own** endpoint article, separate from Commercial.

8. Don't assume Commercial features exist

• Assume newer Commercial conveniences (e.g., **Cross-Tenant Identity Mapping**, **Graph Explorer**) are **absent** in GCC High until Microsoft documents them for US Gov. Validate Graph with PowerShell, not the web explorer. (verify for GCC High.)

• When a Commercial runbook references a portal or feature, **map it through** `gcc-high-parity-notes.md` before following it.

9. Keep the three surfaces coherent

• The wiki page, the repo source, and the store deliverable (PDF/scripts) should always agree. When a live GCC High correction is made, sync it back into `source/` and republish so the runbook stays accurate.

Deliverables Summary — Exchange Online Tenant-to-Tenant Migration (Government / GCC High)

Everything included in this Government (GCC High) edition, and how the pieces fit together.

Documents (`source/`)

File	Purpose
`01-solution-overview.md`	What the solution does, the deployment model, and **Commercial vs GCC High — what's different** (with the cross-cloud-unsupported caveat up front).
`02-requirements.md`	Prerequisites R0–R8 (each with GCC High verify/implement steps), plus the category baseline G1–G6.
`03-implementation.md`	Ordered Assess→Configure→Pilot→Validate→Expand steps using the `*.us` portals, with GCC-High caveats inline.
`05-testing.md`	Pass/fail gates for every phase (Gate 0–6).
`06-troubleshooting.md`	GCC-High-specific failure diagnosis (wrong-cloud, licensing, ExchangeGUID, DNS, endpoints).
`07-best-practices.md`	Field guidance for running the move safely inside the sovereign boundary.
`gcc-high-parity-notes.md`	**Cited** Commercial→GCC High map: endpoints, portals, licensing, roles, support status.
`executive-summary.md`	One-page brief for decision-makers.
`global-requirements-azure-solutions.md`	Category baseline (G1–G6).

Scripts (`scripts/`)

All connect to **US Gov Graph / EXO** endpoints (`-Environment USGov`, `-ExchangeEnvironmentName O365USGovGCCHigh`). Read-only scripts make **no** changes. Change-capable scripts default to `-WhatIf`.

Script	Type	What it does
`EXOMIGG-Discovery.ps1`	**Read-only**	Inventories both tenants: cloud/environment, mailboxes/sizes, licensing, DNS (MX/Autodiscover/SPF/DKIM/DMARC), roles. Writes the `EXOMIGG-baseline\`.
`EXOMIGG-Validation.ps1`	**Read-only**	Verifies modules, Gov connectivity, roles, license counts, endpoint reachability; reports pass/fail per check.
`EXOMIGG-Report.ps1`	**Read-only**	Per-mailbox migration status, item/folder counts, permissions — for pilot/wave validation and closeout.
`EXOMIGG-Remediation.ps1`	**Change (default `-WhatIf`)**	Safe fixes for common blockers (e.g., clear stale ExchangeGUID, reset default addresses, re-stamp proxies). Requires explicit `-Execute` to act.
`EXOMIGG-Set-ScopeTargeting.ps1`	**Change (default `-WhatIf`)**	Builds pilot/wave target groups (`EXOMIGG-Pilot`, `EXOMIGG-Wave1..N`) from a mapping CSV. Requires explicit `-Execute` to act.

How the deliverables work together

1. **Assess** — run `EXOMIGG-Discovery.ps1` (+ `EXOMIGG-Validation.ps1`) to capture the baseline and pass Gate 1.

2. **Configure** — assign roles/licensing in the `*.us` portals, set up the engine (native org relationship or vendor tool), re-run `EXOMIGG-Validation.ps1` to pass Gate 2.

3. **Pilot** — build `EXOMIGG-Pilot` with `EXOMIGG-Set-ScopeTargeting.ps1`, move it, validate with `EXOMIGG-Report.ps1` to pass Gate 3.

4. **Expand** — build waves, move, validate each with `EXOMIGG-Report.ps1` (Gate 4), then cut over DNS (Gate 5) and close out (Gate 6).

5. `EXOMIGG-Remediation.ps1` (`-WhatIf` first) resolves blockers surfaced by validation/testing at any point.

Scope boundaries

• **In scope:** tenant preparation, identity/licensing/endpoint configuration, DNS cutover, pilot/wave orchestration, and validation for a **1:1-domain Exchange Online move within GCC High**.

• **Out of scope / deferred:** the **internals of any third-party migration tool** (deferred to that vendor's GCC High documentation); DoD (L5) endpoints (this edition targets GCC High L4); SharePoint/OneDrive/Teams data migration (Exchange-focused).

• **Hard constraint:** native cross-cloud (Commercial↔GCC High) mailbox migration is **not supported** — use a third-party tool or PST for cross-cloud mail data.

Appendix A — PowerShell Scripts

Included in the accompanying ZIP. Each script's header documents full usage.

EXOMIGG-Discovery.ps1

Purpose: Collects a baseline for one GCC High (US Government L4) Microsoft 365 tenant: detected cloud/environment, mailbox inventory and sizes, licensing (including the Cross-Tenant User Data Migration add-on), the migrating domain's DNS records (MX/Autodiscover/SPF/DKIM/DMARC), and admin-role holders. Run once per tenant (source, then target). Placeholders use plain text like your-admin-upn and your-domain.com. HOW TO RUN powershell -ExecutionPolicy Bypass -File .\EXOMIGG-Discovery.ps1 -AdminUpn your-admin-upn -Domain your-domain.com -OutputFolder .\EXOMIGG-baseline (Uses Graph scope Directory.Read.All/Organization.Read.All via -Environment USGov, and Exchange Online via -ExchangeEnvironmentName O365USGovGCCHigh) EXPECTED RESULTS Console summary plus CSV/JSON files written to the output folder. PASS = environment reports GCC High/USGov and files are produced with no connection errors. FAIL = wrong-cloud auth error (see 06-troubleshooting.md #1). .NOTES White-label — the repeatable way. Read-only against Microsoft Graph/EXO US Gov endpoints. No changes are made. #>

How to run: powershell -ExecutionPolicy Bypass -File .\EXOMIGG-Discovery.ps1 -AdminUpn your-admin-upn -Domain your-domain.com -OutputFolder .\EXOMIGG-baseline (Uses Graph scope Directory.Read.All/Organization.Read.All via -Environment USGov, and Exchange Online via -ExchangeEnvironmentName O365USGovGCCHigh) EXPECTED RESULTS Console summary plus CSV/JSON files written to the output folder. PASS = environment reports GCC High/USGov and files are produced with no connection errors. FAIL = wrong-cloud auth error (see 06-troubleshooting.md #1). .NOTES White-label — the repeatable way. Read-only against Microsoft Graph/EXO US Gov endpoints. No changes are made. #>

EXOMIGG-Remediation.ps1

Purpose: Applies well-scoped fixes for the recurring blockers documented in 06-troubleshooting.md: clearing a mismatched previous ExchangeGUID on a target MailUser, resetting a source object's default address to the initial *.onmicrosoft.us domain during domain release, and re-stamping a source ExchangeGUID onto a target MailUser. It is SAFE BY DEFAULT: it runs in -WhatIf mode and changes nothing until you pass -Execute. Placeholders use plain text like your-admin-upn and your-identity. HOW TO RUN Preview (default, no changes): powershell -ExecutionPolicy Bypass -File .\EXOMIGG-Remediation.ps1 -AdminUpn your-admin-upn -Action ClearPreviousMailboxInfo -Identity your-identity Apply (explicit): powershell -ExecutionPolicy Bypass -File .\EXOMIGG-Remediation.ps1 -AdminUpn your-admin-upn -Action ClearPreviousMailboxInfo -Identity your-identity -Execute (Connects with -ExchangeEnvironmentName O365USGovGCCHigh) EXPECTED RESULTS In preview: a description of what WOULD change, and nothing is modified. With -Execute: the change is applied and re-read for confirmation. PASS = intended state reached; FAIL = error surfaced with the troubleshooting ref. .NOTES White-label — the repeatable way. Connects to EXO US Gov endpoints. Change-capable but DEFAULTS to -WhatIf. #>

How to run: Preview (default, no changes): powershell -ExecutionPolicy Bypass -File .\EXOMIGG-Remediation.ps1 -AdminUpn your-admin-upn -Action ClearPreviousMailboxInfo -Identity your-identity Apply (explicit): powershell -ExecutionPolicy Bypass -File .\EXOMIGG-Remediation.ps1 -AdminUpn your-admin-upn -Action ClearPreviousMailboxInfo -Identity your-identity -Execute (Connects

with -ExchangeEnvironmentName O365USGovGCCHigh) EXPECTED RESULTS In preview: a description of what WOULD change, and nothing is modified. With -Execute: the change is applied and re-read for confirmation. PASS = intended state reached; FAIL = error surfaced with the troubleshooting ref. .NOTES White-label — the repeatable way. Connects to EXO US Gov endpoints. Change-capable but DEFAULTS to -WhatIf. #>

EXOMIGG-Report.ps1

Purpose: Produces a per-mailbox report used at the Pilot, per-Wave, and Closeout gates: migration/move-request status, item and folder counts, mailbox size, and permission/delegation inventory. Point it at a set of mailboxes (a CSV of addresses, or all) in a GCC High tenant. Placeholders use plain text like your-admin-upn and your-mailboxes.csv (column: PrimarySmtpAddress). HOW TO RUN powershell -ExecutionPolicy Bypass -File .\EXOMIGG-Report.ps1 -AdminUpn your-admin-upn -MailboxCsv your-mailboxes.csv -OutputFolder .\EXOMIGG-baseline (Connects with -ExchangeEnvironmentName O365USGovGCCHigh) EXPECTED RESULTS A CSV report plus console summary. PASS at a gate = every listed mailbox shows completed status with item counts and permissions intact. FAIL = missing content/permissions (see 05-testing.md Gate 3 / 06-troubleshooting.md). .NOTES White-label — the repeatable way. Read-only against EXO US Gov endpoints. No changes are made. #>

How to run: powershell -ExecutionPolicy Bypass -File .\EXOMIGG-Report.ps1 -AdminUpn your-admin-upn -MailboxCsv your-mailboxes.csv -OutputFolder .\EXOMIGG-baseline (Connects with -ExchangeEnvironmentName O365USGovGCCHigh) EXPECTED RESULTS A CSV report plus console summary. PASS at a gate = every listed mailbox shows completed status with item counts and permissions intact. FAIL = missing content/permissions (see 05-testing.md Gate 3 / 06-troubleshooting.md). .NOTES White-label — the repeatable way. Read-only against EXO US Gov endpoints. No changes are made. #>

EXOMIGG-Set-ScopeTargeting.ps1

Purpose: Creates and populates the named scope groups the migration is driven by (for example EXOMIGG-Pilot and EXOMIGG-Wave1..N) from a mapping CSV, so each phase moves a controlled, named set of mailboxes. It is SAFE BY DEFAULT: it previews with -WhatIf and creates/changes nothing until you pass -Execute. Placeholders use plain text like your-admin-upn and your-mapping.csv (columns: PrimarySmtpAddress, Wave). HOW TO RUN Preview (default, no changes): powershell -ExecutionPolicy Bypass -File .\EXOMIGG-Set-ScopeTargeting.ps1 -AdminUpn your-admin-upn -MappingCsv your-mapping.csv -Wave Pilot Apply (explicit): powershell -ExecutionPolicy Bypass -File .\EXOMIGG-Set-ScopeTargeting.ps1 -AdminUpn your-admin-upn -MappingCsv your-mapping.csv -Wave Pilot -Execute (Connects with -ExchangeEnvironmentName O365USGovGCCHigh) EXPECTED RESULTS In preview: the group name and the members that WOULD be added, with nothing created. With -Execute: the group EXOMIGG-<Wave> is created if absent and the mapped members are added; membership is read back. PASS = intended membership present; FAIL = surfaced error with troubleshooting ref. .NOTES White-label — the repeatable way. Connects to EXO US Gov endpoints. Change-capable but DEFAULTS to -WhatIf. #>

How to run: Preview (default, no changes): powershell -ExecutionPolicy Bypass -File .\EXOMIGG-Set-ScopeTargeting.ps1 -AdminUpn your-admin-upn -MappingCsv your-mapping.csv -Wave Pilot Apply (explicit): powershell -ExecutionPolicy Bypass -File .\EXOMIGG-Set-ScopeTargeting.ps1 -AdminUpn your-admin-upn -MappingCsv your-mapping.csv -Wave Pilot -Execute (Connects with

-ExchangeEnvironmentName O365USGovGCCHigh) EXPECTED RESULTS In preview: the group name and the members that WOULD be added, with nothing created. With -Execute: the group EXOMIGG-<Wave> is created if absent and the mapped members are added; membership is read back. PASS = intended membership present; FAIL = surfaced error with troubleshooting ref. .NOTES White-label — the repeatable way. Connects to EXO US Gov endpoints. Change-capable but DEFAULTS to -WhatIf. #>

EXOMIGG-Validation.ps1

Purpose: Validates that one GCC High tenant is ready for the migration: required PowerShell modules present, a successful US Gov connection, migration-relevant admin roles assigned, sufficient mailbox licensing, and reachability of the GCC High service endpoints. Run once per tenant (source and target). Placeholders use plain text like your-admin-upn. HOW TO RUN powershell -ExecutionPolicy Bypass -File .\EXOMIGG-Validation.ps1 -AdminUpn your-admin-upn (Connects with -Environment USGov / -ExchangeEnvironmentName O365USGovGCCHigh) EXPECTED RESULTS A table of checks each marked PASS or FAIL, and an overall result. PASS overall = ready for the next phase gate. Any FAIL points to the matching item in 06-troubleshooting.md. .NOTES White-label — the repeatable way. Read-only against Microsoft Graph/EXO US Gov endpoints. No changes are made. #>

How to run: powershell -ExecutionPolicy Bypass -File .\EXOMIGG-Validation.ps1 -AdminUpn your-admin-upn (Connects with -Environment USGov / -ExchangeEnvironmentName O365USGovGCCHigh) EXPECTED RESULTS A table of checks each marked PASS or FAIL, and an overall result. PASS overall = ready for the next phase gate. Any FAIL points to the matching item in 06-troubleshooting.md. .NOTES White-label — the repeatable way. Read-only against Microsoft Graph/EXO US Gov endpoints. No changes are made. #>