iOS iPhone Entra ID Shared Device Mode — Frontline SSO with Global Sign-In & Single Sign-Out (Teams & MSAL Apps)

Implementation Solution Guide

Version 1.0.0 · 2026-07-28

Contents

Executive Summary — iOS iPhone Entra ID Shared Device Mode (Frontline SSO) 4

1. Solution Overview — iOS iPhone Entra ID Shared Device Mode (Frontline SSO) 4

What this solution is . . . 4

Why iPhones specifically need this . . . 5

How Shared Device Mode works (the moving pieces) . . . 5

Global sign-in / single sign-out — what actually happens . . . 6

What SDM isolates (stated honestly) . . . 6

Benefits . . . 6

Limitations (be honest with buyers) . . . 6

The standard deployment model . . . 7

2. Requirements — iOS iPhone Entra ID Shared Device Mode (Frontline SSO) 7

R1. Apple Business Manager (ABM) with an ADE (MDM server) token in Intune . . . 7

R2. ADE enrollment profile set to "Enroll without User Affinity" . . . 7

R3. Assigned device group for the shared iPhones (with the Intune Provisioning Client as OWNER) 8

R4. Microsoft Authenticator app (shared-mode registration host) . . . 8

R5. Cloud Device Administrator role for the registering account . . . 8

R6. Microsoft Teams and any SDM-aware LOB apps . . . 8

R7. Supported iOS/iPadOS version . . . 9

R8. Network access to Microsoft Entra login endpoints . . . 9

R9. Restriction / configuration profile for the shared pool (recommended) . . . 9

R10. Pilot user(s) and pilot iPhone . . . 9

Global Requirements — Intune Solutions (category-level) 9

G1. Microsoft Entra ID tenant . . . 9

G2. Microsoft Intune subscription . . . 10

G3. Administrative roles . . . 10

G4. Device enrollment in Intune . . . 10

G5. Pilot security group . . . 10

G6. Supported Windows baseline . . . 10

G7. Network access to Microsoft cloud endpoints . . . 10

3. Implementation — iOS iPhone Entra ID Shared Device Mode (Frontline SSO) 11

Phase 1 — Build the shared-device foundation . . . 11

Phase 2 — Enroll and register a pilot iPhone into Shared Device Mode . . . 12

Phase 3 — Pilot the global sign-in / single sign-out experience . . . 12

Phase 4 — Validate and expand . . . 13

5. Testing & Validation — iOS iPhone Entra ID Shared Device Mode 13

Test 1 — Tenant readiness . . . 14
Test 2 — Assigned group ownership (enrollment-time grouping) . . . 14
Test 3 — No-affinity enrollment . . . 14
Test 4 — Shared-mode registration . . . 14
Test 5 — Global sign-in (user A) . . . 14
Test 6 — Single (global) sign-out . . . 14
Test 7 — Clean second sign-in (user B) — the core test . . . 14
Test 8 — Coverage / inventory report . . . 15
Test 9 — Non-SDM app boundary (negative test) . . . 15
Acceptance gate . . . 15
6. Troubleshooting — iOS iPhone Entra ID Shared Device Mode 15
Symptom: Shared iPhones enroll but the group stays empty / nothing deploys . . . 15
Symptom: The device enrolled with a primary user (user affinity) . . . 16
Symptom: Teams shows a normal single-user sign-in, not shared mode . . . 16
Symptom: Shared-device registration fails / is greyed out . . . 16
Symptom: Sign-out doesn't clear the previous user (user B sees user A's data) . . . 16
Symptom: Repeated MFA / sign-in loops on the shared device . . . 16
Symptom: Some LOB apps don't participate in global sign-in/out . . . 17
Symptom: Report shows fewer shared iPhones than expected . . . 17
Escalation checklist . . . 17
7. Best Practices — iOS iPhone Entra ID Shared Device Mode (Frontline) 17
Get the enrollment-time grouping right (the #1 pitfall) . . . 17
Treat app scope as the security boundary . . . 18
Provisioning discipline . . . 18
Pilot-first and prove the hand-off . . . 18
Operate and monitor . . . 18
Change control . . . 19
8. Deliverables Summary — iOS iPhone Entra ID Shared Device Mode 19
Documentation (this guide) . . . 19
PowerShell scripts (Microsoft Graph) — `IOSSDMFL-Scripts.zip` . . . 20
Hero image . . . 20
How it's delivered . . . 20
Appendix A — PowerShell Scripts 21

Executive Summary — iOS iPhone Entra ID Shared Device Mode (Frontline SSO)

Frontline teams share iPhones — a pool of shift phones any authorized worker can pick up — but a shared phone with a single shared account, or a kiosk lockdown, gives **no one a private session**: the previous worker's cached mail, chats, and tokens survive the next sign-in. This solution configures **Microsoft Entra ID Shared Device Mode (SDM)** on those shared iPhones so each worker gets a **real per-user identity session**: **sign in once** as yourself, and **sign out once** to **clear your identity and app data from every supporting app** for the next person — **global sign-in and single sign-out** across **Microsoft Teams** and MSAL-based line-of-business apps.

The Microsoft-native answer for shared *iPhones*. Apple's own multi-user technology, Shared iPad, runs **only on iPad hardware** — it cannot help an iPhone fleet. Entra Shared Device Mode is the way to give pooled iPhones a genuine per-user sign-in/sign-out experience within the Microsoft identity stack.

A distinct, honest scope. This is per-user shared identity — not single-user SSO, not single-app kiosk lockdown, not Apple Shared iPad. The package is explicit about what SDM isolates: it clears the **Entra session and the data inside SDM-aware apps** on global sign-out; it does **not** partition the whole OS, so app scope becomes the security boundary — only SDM-aware apps belong on a shared iPhone.

This package delivers the complete, field-tested method to stand it up in Intune — written so a single administrator can follow it end to end:

- **No-affinity foundation, done right.** Shared iPhones enroll **without user affinity** via ABM/ADE

into an **Assigned** device group whose owner is the **Intune Provisioning Client** — the specific detail that makes enrollment-time grouping actually populate (a common, silent failure when missed).

- **Shared-mode registration.** Each device is registered into Shared Device Mode through **Microsoft

Authenticator **by a least-privilege** Cloud Device Administrator** account.

- **Proven hand-off.** The acceptance test is unambiguous: user A signs out, user B signs in **clean**,

with no trace of A — validated on a real device with two real users.

The package follows the standard repeatable shape — **Assess** → **Configure** → **Pilot** → **Validate** → **Expand** — with exact, click-by-click Intune/Entra steps, a requirements guide that tells you how to verify *and* fix each prerequisite, five ready-to-run PowerShell scripts (Microsoft Graph), and testing/troubleshooting guides with clear pass/fail gates.

Outcome: pooled iPhones your frontline can share safely — each worker signed in as themselves, each sign-out a clean hand-off — deployed and proven on a pilot before you scale, without a consulting engagement.

1. Solution Overview — iOS iPhone Entra ID Shared Device Mode (Frontline SSO)

What this solution is

This solution configures **Microsoft Entra ID Shared Device Mode (SDM)** on **pooled, shared iPhones** managed by **Microsoft Intune**, so a frontline worker can walk up to any shift phone, **sign in once**, use their Microsoft apps as themselves, and **sign out once** at end of shift — which **clears their identity and app data from every supporting app on the device** for the next person. It is the identity-session model for shared iPhones: **global sign-in** and **single (global) sign-out** across apps that support SDM (notably **Microsoft Teams** and MSAL-based line-of-business apps).

The devices are enrolled **without user affinity** (no single owner), registered into **shared device mode** through the **Microsoft Authenticator** app, and handed between staff freely. Each person gets their **own** Entra sign-in on the shared hardware — not a generic shared account.

> ***This is not kiosk lockdown, and not a shared service account.*** *Restricting a phone to one app (kiosk/lockdown) or signing everyone in with one shared mailbox does* ***not*** *give each worker a private session — cached tokens and data from the previous user survive an app sign-out on a single-user device. Shared Device Mode exists precisely to solve that: it gives the device a* ***per-user identity session*** *that global sign-out tears down. (For single-purpose kiosk phones, see the separate *iOS iPhone Shared Device Mode (Lockdown) with WebEx* and *iOS Lock-Down Profile* solutions — those are a different job.)*

Why iPhones specifically need this

Apple's own multi-user technology — **Shared iPad** with Managed Apple IDs — **only runs on iPad hardware; it is not available on iPhone.** So for **shared iPhones**, there is no OS-level Apple multi-user mode to fall back on. **Entra ID Shared Device Mode is the primary way to give shared iPhones a real per-user sign-in/sign-out experience** within the Microsoft identity stack. (If your fleet is iPads and you want Apple's OS-level partitioning, use the *Shared iPad for Frontline Teams* solution instead; if it's iPhones, this is the one.)

How Shared Device Mode works (the moving pieces)

1. **No-affinity enrollment.** The iPhone is enrolled via **Apple Business Manager + Automated Device

Enrollment (ADE) **with an enrollment profile set to** enroll without user affinity** — the device belongs to the organization, not a person.

1. **Shared-mode registration (the Authenticator step).** The device is registered into **shared

device mode **through** Microsoft Authenticator**. The account that performs this registration must hold the Entra** Cloud Device Administrator** role. Registration is a one-time provisioning action at device setup; afterward the device advertises itself as *shared* to apps that support SDM.

1. **SDM-aware apps.** Apps built on the **Microsoft Authentication Library (MSAL)** that opt into SDM

— first and foremost **Microsoft Teams** for iOS — detect shared mode and switch to the global-sign-in / global-sign-out model. A worker signs into Teams; other SDM apps recognize the signed-in user; signing out of one signs out of all and clears their data.

1. **Intune delivers everything.** Intune enrolls the device (no affinity), deploys **Microsoft

Authenticator **and the SDM apps (Teams, your MSAL LOB apps), applies device configuration and compliance, and (optionally) a light restriction profile — all targeted at an** assigned device group** the shared iPhones land in at enrollment.

Global sign-in / single sign-out — what actually happens

- **Sign-in:** the worker opens Teams (or another SDM app), signs in with their Entra credentials and MFA. That identity becomes the device's **current shared-mode user**; other SDM apps pick it up without a second sign-in.
- **Sign-out:** the worker taps sign-out once. SDM performs a **global sign-out** — every SDM app drops the session and **clears that user's cached data and tokens** from the device, returning the phone to a clean state for the next person.

What SDM isolates (stated honestly)

- **It isolates the Entra identity session and the data inside SDM-aware apps.** Global sign-out clears tokens and app data for SDM apps (Teams and MSAL apps that implement SDM).
- **It does not partition the entire iOS operating system** the way Apple Shared iPad does. Apps that are **not** SDM-aware do not participate in global sign-out; treat them accordingly (don't put personal-data-caching non-SDM apps on a shared iPhone, or restrict them). Combine SDM with a sensible restriction profile so only appropriate apps are present.
- **App support is narrower on iOS than on Android.** On Android, Managed Home Screen and a broad set of apps support SDM; on iOS the anchor is **Teams**, plus MSAL LOB apps that explicitly implement SDM. **Verify SDM support for each app you intend to deploy** rather than assuming — confirm against current Microsoft documentation for your tenant.

Benefits

- **A real per-user session on shared iPhones** — each worker signs in as themselves; single sign-out wipes their session and app data for the next person.
- **The Microsoft-native answer for shared *iPhones*** — where Apple Shared iPad (iPad-only) cannot help.
- **Frontline-fit** — fast hand-off, no personal enrollment, no per-device user assignment.
- **Central management** — enrollment, apps, compliance, and restrictions all driven from Intune against one assigned device group.
- **Conditional Access aware** — the signed-in user's session supports Entra device/compliance policies for the SDM apps.

Limitations (be honest with buyers)

- **iPhone / no-affinity only.** Targets shared iPhones enrolled without user affinity; it is not for single-user corporate phones (see the *Enterprise SSO app extension* solution for those).

• **App coverage is the gating factor.** Only SDM-aware apps (Teams + MSAL apps that implement SDM)

get global sign-in/out; verify each app.

• **Requires Microsoft Authenticator** for shared-mode registration and the **Cloud Device

Administrator** role for the registering account.

• **Not full OS multi-user.** SDM is an identity/app-data model, not an Apple OS partition; pair it

with restrictions.

• Requires **Microsoft Entra ID**, supported iOS, and outbound access to Entra login endpoints.

The standard deployment model

This solution uses **one** repeatable model across our catalog:

> ***Shared iPhones are enrolled without user affinity via ABM/ADE into an assigned device group, registered into Entra Shared Device Mode through Microsoft Authenticator, and given the SDM apps (Teams + MSAL LOB) so frontline workers get global sign-in and single sign-out — deployed pilot-first and reversible.***

Every step follows the repeatable pattern: **Assess** → **Configure** → **Pilot** → **Validate** → **Expand.**

2. Requirements — iOS iPhone Entra ID Shared Device Mode (Frontline SSO)

Confirm **every** requirement below before you begin. Each entry follows the same pattern: **Description · Why required · How to verify · How to implement if missing.** Category-wide prerequisites (tenant, Intune licensing, admin roles, pilot group, network) are covered once in the **Global Requirements — Intune Solutions** document; the items here are specific to Entra **Shared Device Mode** on shared iPhones.

R1. Apple Business Manager (ABM) with an ADE (MDM server) token in Intune

Description: ABM is set up and linked to Intune with an Automated Device Enrollment token, and the shared iPhones are assigned to that MDM server in ABM. **Why:** Shared iPhones must be **supervised** and enrolled **without user affinity** via ADE; that requires an ABM↔Intune ADE token and the devices assigned to Intune in ABM. **Verify:** Intune → **Devices** → **Enrollment** → **Apple** → **Enrollment program tokens**; a token exists and shows your shared iPhones as assigned devices. **Implement:** Create/renew the ADE token (Intune → **Devices** → **Enrollment** → **Apple** → **Enrollment program tokens** → **Add**), upload it to ABM, and assign the device serial numbers to the Intune MDM server in ABM.

R2. ADE enrollment profile set to "Enroll without User Affinity"

Description: An iOS/iPadOS ADE enrollment profile that enrolls the device **supervised** and **without user affinity**. **Why:** Shared devices must not bind to a single user; user affinity would defeat the shared model. **Why it matters for SDM:** the shared, no-owner enrollment is what lets Shared Device Mode manage the

identity per-session rather than per-device. **Verify:** Intune → **Devices** → **Enrollment** → **Apple** → **Enrollment program tokens** → **(open your token)** → **Profiles**; the profile shows **User Affinity = Enroll without User Affinity** and **Supervised = Yes**. **Implement:** Intune → **Devices** → **Enrollment** → **Apple** → **Enrollment program tokens** → **(open the token)** → **Profiles** → **Create profile** → **iOS/iPadOS**, name it **iPhone SDM – ADE Profile**, set **User Affinity = Enroll without User Affinity**, **Supervised**, and assign it to your shared devices.

R3. Assigned device group for the shared iPhones (with the Intune Provisioning Client as OWNER)

Description: A Microsoft Entra **security group of type Assigned** (not Dynamic) that the shared iPhones land in at enrollment, and on which the **Intune Provisioning Client** service principal is an **Owner**. **Why:** No-affinity ADE / shared devices have no user to drive dynamic membership, so enrollment-time device grouping uses an **Assigned** group whose **owner** is the first-party **Intune Provisioning Client** (AppId `f1346770-5b25-470b-88bd-d5744ab7952c`, often shown as *Intune Autopilot ConfidentialClient* / *Intune Provisioning Client*). Without that owner, the group stays **empty at enrollment** and nothing (apps, config, restrictions) deploys. **Verify:** Entra → **Groups** → **(the group)** → **Owners**; the Intune Provisioning Client appears (search by **AppId**, since the display name varies). Group **Membership type = Assigned**. **Implement:** Entra → **Groups** → **New group** → **Security**, **Membership type = Assigned**, name it **iPhone SDM – Devices**. Then **Owners** → **Add owners** → search the **AppId** `f1346770-5b25-470b-88bd-d5744ab7952c` and add it. (If the SP is absent, open the Intune portal once as Global Administrator to provision it.) The included `IOSSDMFL-Remediation.ps1` can set this owner for you.

R4. Microsoft Authenticator app (shared-mode registration host)

Description: The **Microsoft Authenticator** app deployed to the shared iPhones. **Why:** On iOS, a device is registered into **Shared Device Mode** through **Microsoft Authenticator**; it is also the identity broker for the SDM apps. **Verify:** Intune → **Apps** → **iOS/iPadOS**; **Microsoft Authenticator** (publisher **Microsoft Corporation**, bundle ID `com.microsoft.azureauthenticator`) is added and assigned **Required** to the **iPhone SDM – Devices** group. **Implement:** Intune → **Apps** → **iOS/iPadOS** → **Add** → **iOS store app**; add **Microsoft Authenticator**, assign **Required** to **iPhone SDM – Devices**.

R5. Cloud Device Administrator role for the registering account

Description: The account used to register each device into shared mode holds the Entra **Cloud Device Administrator** role. **Why:** Registering a device into Shared Device Mode requires this role; a standard user cannot complete the shared-mode registration. **Verify:** Entra → **Roles and administrators** → **Cloud Device Administrator**; the provisioning account is a member. **Implement:** Entra → **Roles and administrators** → **Cloud Device Administrator** → **Add assignments**; add the provisioning account. Use a dedicated, least-privilege provisioning account.

R6. Microsoft Teams and any SDM-aware LOB apps

Description: Microsoft Teams for iOS (the anchor SDM app) and any line-of-business apps that explicitly support Shared Device Mode, deployed to the shared iPhones. **Why:** Only SDM-aware apps deliver global sign-in / single sign-out. Teams is the primary iOS SDM app; LOB apps must be built on MSAL and opt

into SDM. **Verify:** Intune → **Apps** → **iOS/iPadOS**; **Microsoft Teams** (publisher **Microsoft Corporation**, bundle ID `com.microsoft.skype.teams`) is added/assigned; for each LOB app, confirm SDM support with the app vendor. **Implement:** Add **Microsoft Teams** (Required) to **iPhone SDM – Devices**. For LOB apps, confirm SDM support (verify against current Microsoft docs and the app vendor) before relying on global sign-out for them.

R7. Supported iOS/iPadOS version

Description: A current, supported iOS/iPadOS release on the shared iPhones. **Why:** Shared Device Mode and the SDM apps require a supported iOS; older releases may lack SDM behavior. **Verify:** On the device, **Settings** → **General** → **About**; or Intune → device → **Hardware**. **Implement:** Update the devices, or stage a **minimum-OS compliance policy** so out-of-date phones are flagged before they enter the pool.

R8. Network access to Microsoft Entra login endpoints

Description: Outbound HTTPS to the Entra sign-in endpoints for your cloud. **Why:** Registration, sign-in, and global sign-out complete against these endpoints. **Verify:** From the device network, reach `https://login.microsoftonline.com` (commercial) or the sovereign equivalent (`login.microsoftonline.us`, `login.partner.microsoftonline.cn`). **Implement:** Allow Microsoft's published Entra/Office 365 URLs through proxy/firewall; do **not** TLS-inspect the Microsoft login endpoints.

R9. Restriction / configuration profile for the shared pool (recommended)

Description: A light **device restrictions** profile scoped to **iPhone SDM – Devices** that keeps the shared phones limited to appropriate apps/functions. **Why:** SDM isolates SDM-app data but does **not** partition the whole OS; restrictions keep non-SDM apps and personal-data surfaces off the shared pool. **Verify:** Intune → **Devices** → **Configuration**; a restrictions profile named **iPhone SDM – Restrictions** is assigned to the group. **Implement:** Intune → **Devices** → **Configuration** → **Create** → **iOS/iPadOS** → **Templates** → **Device restrictions**, name it **iPhone SDM – Restrictions**, limit apps/functions to what the role needs, assign to **iPhone SDM – Devices**.

R10. Pilot user(s) and pilot iPhone

Description: At least two pilot frontline users with licensed Entra identities and one enrolled shared pilot iPhone. **Why:** The core value — one user signs in, signs out, a **second** user signs in clean — must be validated with two identities on the same device. **Verify:** Both pilot users can sign in to Teams; the pilot iPhone is in **iPhone SDM – Devices** and registered into shared mode. **Implement:** Add the pilot users to the **pilot security group** (Global Requirement G5) and the pilot iPhone to **iPhone SDM – Devices**.

Global Requirements — Intune Solutions (category-level)

These requirements apply to **every** solution in the **Intune Solutions** category. They are published once at the category level so individual listings stay small. Confirm these before deploying *any* Intune solution. Each entry: **Description · Why · Verify · Implement-if-missing.**

G1. Microsoft Entra ID tenant

Description: An active Microsoft Entra ID (Azure AD) tenant. **Why:** It is the identity backbone for every cloud and Intune-managed resource. **Verify:** Sign in to `https://entra.microsoft.com` as an administrator. **Implement:** Create a Microsoft 365/Azure subscription, which provisions a tenant.

G2. Microsoft Intune subscription

Description: An Intune-bearing license plan. **Why:** Intune delivers all configuration, compliance, and security policies. **Verify:** `https://intune.microsoft.com` loads; **Tenant administration** → **Tenant status** shows active. **Implement:** Assign Microsoft 365 E3/E5, Business Premium, or standalone Intune Plan 1.

G3. Administrative roles

Description: Appropriate Entra/Intune admin roles for the operator. **Why:** Creating policies and enrollment settings requires elevated rights. **Verify:** Entra → **Roles and administrators**; confirm **Intune Administrator**. **Implement:** Assign **Intune Administrator**; reserve Global Administrator for tenant-wide changes.

G4. Device enrollment in Intune

Description: Targeted Windows devices are enrolled and manageable. **Why:** Policies only reach enrolled devices. **Verify:** Intune → **Devices** → **All devices**; the device appears and is **compliant**. **Implement:** Enable **Automatic Enrollment** and join devices to Entra ID.

G5. Pilot security group

Description: A Microsoft Entra security group for pilot/targeted users or devices. **Why:** Every solution is piloted before fleet rollout. **Verify:** Entra → **Groups**; the pilot group exists. **Implement:** Entra → **Groups** → **New group** → **Security** → add members.

G6. Supported Windows baseline

Description: Windows 10 21H2+ or Windows 11 with current updates. **Why:** Modern Intune features assume a patched, supported OS. **Verify:** `winver`, or Intune → device → **Hardware**. **Implement:** Deploy **Update rings** or upgrade to Windows 11.

G7. Network access to Microsoft cloud endpoints

Description: Outbound HTTPS to Microsoft 365, Entra, and Intune service URLs. **Why:** Enrollment, policy sync, and authentication depend on these endpoints. **Verify:** From a device, reach `https://login.microsoftonline.com` and `https://enrollment.manage.microsoft.com`. **Implement:** Allow Microsoft's published Office 365/Intune URL & IP ranges through proxy/firewall.

The standard deployment model (all solutions): Assess → Configure → Pilot → Validate → Expand.

3. Implementation — iOS iPhone Entra ID Shared Device Mode (Frontline SSO)

Follow these steps **in order**. The *why* for each capability lives in the Solution Overview; the steps below are deliberately short and exact so you can **click to implement**. Throughout, the repeatable pattern applies: **Assess** → **Configure** → **Pilot** → **Validate** → **Expand.** Do everything against a small **pilot pool** first.

All admin-center steps use the Microsoft Intune admin center at `https://intune.microsoft.com` and the Entra admin center at `https://entra.microsoft.com` unless noted.

> ***This configures shared-identity (Shared Device Mode) on no-affinity iPhones.*** *It is not single-user SSO and not single-app kiosk lockdown. Every device here is enrolled* ***without user affinity****.*

Phase 1 — Build the shared-device foundation

Step 1. Create the assigned device group (and set the Provisioning Client as owner)

1. Go to **Entra** → **Groups** → **New group**.
2. **Group type = Security**; **Membership type = Assigned** (not Dynamic); **Name:**

iPhone SDM – Devices. **Create**.

1. Open **iPhone SDM – Devices** → **Owners** → **Add owners**. Search by **Application ID**

`f1346770-5b25-470b-88bd-d5744ab7952c` (the **Intune Provisioning Client**; the display name varies — search by the AppId, not the name) and **add it as an owner**.

• *Why:* no-affinity/shared devices are placed into an **assigned** group at enrollment by this

service principal; if it is not an owner, the group stays empty and nothing deploys.

• *Shortcut:* `IOSSDMFL-Remediation.ps1` can create the group and set this owner for you.

Step 2. Create the ADE enrollment profile (no user affinity)

1. Go to **Devices** → **Enrollment** → **Apple** → **Enrollment program tokens**, and **open your ADE token**.
2. Select the **Profiles** tab → **Create profile** → **iOS/iPadOS**.
3. **Name: iPhone SDM – ADE Profile**. Set **User Affinity = Enroll without User Affinity** and

Supervised = Yes. Complete the wizard and **Create**.

1. Back on the token, assign **iPhone SDM – ADE Profile** to your shared iPhone serial numbers

(**Devices** tab → select devices → **Assign profile**).

Step 3. Deploy Microsoft Authenticator and Teams to the pool

1. Go to **Apps** → **iOS/iPadOS** → **Add** → **iOS store app**.
2. Add **Microsoft Authenticator** — publisher **Microsoft Corporation**, bundle ID

`com.microsoft.azureauthenticator`. Assign **Required** to **iPhone SDM – Devices**.

1. Add **Microsoft Teams** — publisher **Microsoft Corporation**, bundle ID `com.microsoft.skype.teams` (*not* "Teams" by another publisher). Assign **Required** to **iPhone SDM – Devices**.

1. *(Optional)* Add any **SDM-aware LOB apps** (confirmed with the vendor) the same way.

Step 4. Add a restriction profile for the shared pool

1. Go to **Devices** → **Configuration** → **Create** → **New policy**; **Platform = iOS/iPadOS**; **Profile type = Templates** → **Device restrictions** → **Create**.

1. **Name: iPhone SDM – Restrictions**. Limit apps/functions to what the frontline role needs (SDM isolates SDM-app data, not the whole OS — keep non-SDM, personal-data apps off the pool).

1. **Assignments: iPhone SDM – Devices**. **Review + create** → **Create**.

Step 5. Grant the provisioning account the Cloud Device Administrator role

1. Go to **Entra** → **Roles and administrators** → **Cloud Device Administrator** → **Add assignments**.
2. Add the dedicated **provisioning account** you will use to register devices into shared mode.

Phase 2 — Enroll and register a pilot iPhone into Shared Device Mode

Step 6. Enroll the pilot iPhone (no affinity)

1. Wipe/prepare the pilot iPhone and start setup; because its serial is assigned the **iPhone SDM – ADE Profile**, it enrolls **supervised, without user affinity**.

1. Confirm the device appears in **Devices** → **iOS/iPadOS** as **corporate / no primary user**, and that it landed in **iPhone SDM – Devices** (Entra → Groups → members).

Step 7. Register the device into Shared Device Mode (the Authenticator step)

1. On the pilot iPhone, open **Microsoft Authenticator** (deployed in Step 3).
2. Sign in with the **provisioning account** (the Cloud Device Administrator from Step 5) and complete the **shared device registration** prompt to mark this device as a **shared device**.

1. The device now advertises **shared mode** to SDM-aware apps. This is a one-time provisioning action per device.

Phase 3 — Pilot the global sign-in / single sign-out experience

Step 8. First user signs in

1. On the pilot iPhone, open **Microsoft Teams**. Confirm Teams shows the **shared-device** sign-in experience.

1. Sign in as **pilot user A** (Entra credentials + MFA). Confirm A is signed in to Teams and any

other SDM apps recognize A without a second sign-in.

Step 9. Single (global) sign-out

1. As pilot user A, perform **sign out** in Teams.
2. Confirm this triggers a **global sign-out** — A is signed out of all SDM apps and A's cached data is cleared from the device.

Step 10. Second user signs in clean

1. Open Teams again and sign in as **pilot user B**.
2. Confirm **no trace of user A** — B sees only their own chats/data; A's session and data are gone. This is the core acceptance behavior.

Phase 4 — Validate and expand

Step 11. Validate with the scripts

1. Run `IOSSDMFL-Discovery.ps1` (tenant readiness: no-affinity ADE profile, Authenticator + Teams assigned, assigned group with the Provisioning Client owner, Cloud Device Administrator present).
1. Run `IOSSDMFL-Validation.ps1` to confirm the assigned group ownership, ADE profile affinity, and app assignments are correct.
1. Run `IOSSDMFL-Report.ps1` to list the shared-mode iPhones (no user affinity) and their app/group state.

Step 12. Remediate gaps (safe by default)

1. If the group is missing the Provisioning Client owner, the ADE profile has the wrong affinity, or apps are unassigned, run `IOSSDMFL-Remediation.ps1` — it **defaults to** `-WhatIf` and prints exactly what it would change. Review, then re-run to apply.

Step 13. Expand in waves

1. Once the pilot passes (Testing gate), assign the **iPhone SDM – ADE Profile** to the next batch of serials and register each device into shared mode (Step 7).
1. Roll out by location/shift in waves, validating each wave with `IOSSDMFL-Report.ps1` before widening. Register-into-shared-mode is per device, so script/track it as part of your provisioning runbook.

5. Testing & Validation — iOS iPhone Entra ID Shared Device Mode

Validate against a **pilot iPhone** with **two** pilot users before expanding. Each test has an explicit **pass/fail gate**. Use the included PowerShell scripts (Microsoft Graph) for tenant-side checks and the on-device steps for the shared-session experience.

> ***What "pass" means here:*** *a worker signs in as themselves on a shared iPhone, signs out once, and the **next** worker signs in with **no trace** of the previous user in the SDM apps. This is a per-user identity session, not kiosk lockdown.*

Test 1 — Tenant readiness

Procedure: Run `IOSSDMFL-Discovery.ps1`. **Pass:** A no-user-affinity ADE profile exists; Microsoft Authenticator and Teams are added/assigned; the **iPhone SDM – Devices** assigned group exists with the Intune Provisioning Client as owner; the Cloud Device Administrator role has a member. **Fail:** Any missing → resolve before piloting (see Remediation).

Test 2 — Assigned group ownership (enrollment-time grouping)

Procedure: Run `IOSSDMFL-Validation.ps1` (or Entra → Groups → **iPhone SDM – Devices** → Owners). **Pass:** The group is **Assigned** and the **Intune Provisioning Client** (`f1346770-5b25-470b-88bd- d5744ab7952c`) is an **owner**. **Fail:** Group is Dynamic, or the SP is not an owner → devices won't populate at enrollment; fix with `IOSSDMFL-Remediation.ps1`.

Test 3 — No-affinity enrollment

Procedure: On the pilot iPhone (after ADE enrollment), Intune → **Devices** → **iOS/iPadOS** → **(device)**. **Pass:** The device is **supervised**, shows **no primary user**, and is a member of **iPhone SDM – Devices**. **Fail:** Device has a primary user / user affinity → correct the **iPhone SDM – ADE Profile** (Requirement R2) and re-enroll.

Test 4 — Shared-mode registration

Procedure: Confirm the device was registered into shared mode via Microsoft Authenticator with the Cloud Device Administrator account (Implementation Step 7). **Pass:** Teams (and other SDM apps) present the **shared-device** sign-in experience, not the normal single-user one. **Fail:** Apps show a normal sign-in → re-run the Authenticator shared-device registration with an account holding **Cloud Device Administrator** (R5).

Test 5 — Global sign-in (user A)

Procedure: Sign in as **user A** in Teams; open another SDM app if present. **Pass:** A is signed in; other SDM apps recognize A **without** a second sign-in. **Fail:** Each app prompts separately with no shared identity → confirm shared-mode registration (Test 4) and that the apps are SDM-aware (R6).

Test 6 — Single (global) sign-out

Procedure: As user A, sign out once in Teams. **Pass:** A is signed out of **all** SDM apps and A's cached data is cleared from the device. **Fail:** A still signed in elsewhere, or data remains → the app is not SDM-aware, or the device is not truly in shared mode — re-verify Tests 4/6 and app support.

Test 7 — Clean second sign-in (user B) — the core test

Procedure: Sign in as **user B** in Teams after A's sign-out. **Pass:** B sees **only** their own data; there is **no trace** of user A (chats, files, tokens). **Fail:** Any of A's data/session visible to B → do **not** proceed; the shared-session boundary is not intact. Confirm SDM registration and that only SDM-aware apps hold user data on the device.

Test 8 — Coverage / inventory report

Procedure: Run `IOSSDMFL-Report.ps1`. **Pass:** The pilot iPhone appears as a no-affinity, shared-pool device with Authenticator + Teams present; counts match **iPhone SDM – Devices**. **Fail:** Device missing or apps absent → run `IOSSDMFL-Remediation.ps1` (`-WhatIf` first).

Test 9 — Non-SDM app boundary (negative test)

Procedure: Confirm no non-SDM app that caches personal data is deployed to the shared pool (review the **iPhone SDM – Restrictions** profile and app assignments). **Pass:** Only SDM-aware apps (and safe utilities) are present; global sign-out therefore clears all user data that exists on the device. **Fail:** A non-SDM data-caching app is on the pool → remove it or restrict it; SDM will **not** clear its data on sign-out.

Acceptance gate

Proceed to **Expand** only when Tests 1–8 pass and **Test 7 (clean second sign-in) passes on a real device with two real users**, and Test 9 confirms no non-SDM app leaks data across users.

6. Troubleshooting — iOS iPhone Entra ID Shared Device Mode

Work in enrollment order: confirm the device **enrolled without affinity and landed in the group**, then that it was **registered into shared mode**, then that the **SDM apps behave**. Most failures are a Dynamic (not Assigned) group, a missing group **owner**, a wrong enrollment affinity, or an app that is not SDM-aware. Each symptom gives the **likely cause** and the **fix**.

> ***Before you start:*** *if the concern is "one worker can see another's data," first confirm the app in question is* ***SDM-aware****. SDM clears data only for apps that implement it — a non-SDM app on a shared phone is the classic false alarm (and a real leak). This is an app-scope decision, not an SDM bug.*

Symptom: Shared iPhones enroll but the group stays empty / nothing deploys

Likely cause: The device group is **Dynamic**, or the **Intune Provisioning Client** is not an **owner** of the Assigned group. **Fix:**

1. Confirm **iPhone SDM – Devices** is **Membership type = Assigned** (not Dynamic).
2. Add the **Intune Provisioning Client** (AppId `f1346770-5b25-470b-88bd-d5744ab7952c`) as an **owner** — search by **AppId**, since the display name varies (`IOSSDMFL-Remediation.ps1` can do this).
1. If the SP doesn't exist to search, open the Intune portal once as **Global Administrator** to

provision it, then add it.

Symptom: The device enrolled with a primary user (user affinity)

Likely cause: The ADE profile is not set to **Enroll without User Affinity**. **Fix:**

1. Intune → **Devices → Enrollment → Apple → Enrollment program tokens → (token) → Profiles → iPhone SDM – ADE Profile **and set** User Affinity = Enroll without User Affinity**,** Supervised**.

1. Re-assign the profile to the serials and **re-enroll** the affected devices (affinity is set at enrollment).

Symptom: Teams shows a normal single-user sign-in, not shared mode

Likely cause: The device was never registered into Shared Device Mode, or the registering account lacked the role. **Fix:**

1. On the device, open **Microsoft Authenticator** and complete the **shared device registration** using an account that holds **Cloud Device Administrator** (R5).

1. Confirm the registration succeeded, then reopen Teams — it should present the shared-device experience.

Symptom: Shared-device registration fails / is greyed out

Likely cause: The registering account lacks **Cloud Device Administrator**, or Authenticator isn't installed. **Fix:**

1. Entra → **Roles and administrators** → **Cloud Device Administrator** — add the provisioning account.
2. Confirm **Microsoft Authenticator** is installed on the device (R4) and the device has network access to the Entra endpoints (R8).

Symptom: Sign-out doesn't clear the previous user (user B sees user A's data)

Likely cause: The offending app is **not SDM-aware**, or the device is not truly in shared mode. **Fix:**

1. Identify which app retained data. If it is not Teams/an SDM-aware MSAL app, **remove or restrict** it — SDM cannot clear non-SDM apps.

1. Re-confirm shared-mode registration (Test 4) and that Teams itself performs global sign-out.
2. Tighten the **iPhone SDM – Restrictions** profile so only SDM-aware apps are present (R9).

Symptom: Repeated MFA / sign-in loops on the shared device

Likely cause: Conditional Access re-challenging, blocked endpoint, or TLS inspection. **Fix:**

1. Review Conditional Access sign-in-frequency policies applied to the frontline users; shared devices

naturally re-authenticate per user per shift — tune frequency to the shift model.

1. Confirm the device reaches `https://login.microsoftonline.com` (or sovereign equivalent) (R8).
2. **Exempt Microsoft login endpoints from TLS inspection.**

Symptom: Some LOB apps don't participate in global sign-in/out

Likely cause: The app is not built on MSAL or does not implement Shared Device Mode. **Fix:**

1. Confirm SDM support with the app vendor / current Microsoft documentation.
2. If unsupported, do **not** rely on it for shared use — restrict it off the pool or accept it is

outside the global-sign-out boundary and holds no user data.

Symptom: Report shows fewer shared iPhones than expected

Likely cause: Devices not yet ADE-enrolled, not registered into shared mode, or missing from the group. **Fix:**

1. Run `IOSSDMFL-Report.ps1` to list which devices lack no-affinity enrollment or the SDM apps.
2. Run `IOSSDMFL-Remediation.ps1` (`-WhatIf` first) to fix group ownership/app assignment.
3. Complete the per-device shared-mode registration for stragglers (Implementation Step 7).

Escalation checklist

Before opening a Microsoft support case, collect: the `IOSSDMFL-Discovery.ps1` output, the ADE profile's affinity setting, the **iPhone SDM – Devices** group type + owners, the exact app bundle IDs and their SDM support status, the registering account's role, iOS version, and a description of the two-user sign-in/sign-out test result (isolates SDM from app-specific behavior).

7. Best Practices — iOS iPhone Entra ID Shared Device Mode (Frontline)

These practices keep the shared-iPhone identity model correct, predictable, and safe across users. They assume the deployment model in the Solution Overview: no-affinity ABM/ADE enrollment into an assigned device group, shared-mode registration via Microsoft Authenticator, and SDM-aware apps (Teams + MSAL LOB), deployed pilot-first.

Get the enrollment-time grouping right (the #1 pitfall)

- **Assigned group, not Dynamic.** Shared/no-affinity devices have no user to drive dynamic rules —

use an **Assigned** security group (**iPhone SDM – Devices**).

- **Make the Intune Provisioning Client an owner.** Add AppId

`f1346770-5b25-470b-88bd-d5744ab7952c` as an **owner** of that group (search by AppId, not the display name). Without it, devices never populate the group at enrollment and nothing deploys.

- **One group, everything targeted to it.** Point the ADE profile assignment, the apps, the restriction profile, and compliance at the same **iPhone SDM – Devices** group so a device is fully configured the moment it lands.

Treat app scope as the security boundary

- **Only SDM-aware apps belong on a shared iPhone.** Global sign-out clears data **only** for apps that implement SDM. Anchor on **Microsoft Teams**; add LOB apps **only** after confirming SDM support with the vendor / current Microsoft docs.
- **Keep non-SDM, personal-data apps off the pool.** Use the **iPhone SDM – Restrictions** profile to ensure no app that caches personal data — but doesn't participate in global sign-out — is present. This is the difference between "clean hand-off" and "the next worker sees the last one's data."
- **Don't confuse this with kiosk lockdown.** Lockdown limits *which* app runs; SDM manages *whose identity* is active. If the requirement is a single-purpose appliance phone, use the lockdown solution instead; if it's per-user frontline sign-in, use SDM.

Provisioning discipline

- **Dedicated, least-privilege provisioning account.** Grant **Cloud Device Administrator** to a dedicated account used only to register devices into shared mode — not a personal admin identity.
- **Make shared-mode registration part of the runbook.** Registration is **per device** via Authenticator; script/track it so no device silently skips it and falls back to single-user behavior.
- **Verify iOS app support before each wave.** SDM app coverage on iOS is narrower than Android and evolves — re-confirm Teams and any LOB apps before widening.

Pilot-first and prove the hand-off

- **Always test with two real users.** The acceptance test is user A signs out → user B signs in **clean**. Never expand on a single-user test.
- **Pilot by location/shift.** Roll out to one site or shift, validate with `IOSSDMFL-Report.ps1`, then widen.

Operate and monitor

- **Report before you widen.** Run `IOSSDMFL-Report.ps1` each wave; confirm no-affinity enrollment and SDM apps across the pool.
- **Remediate with `-WhatIf` first.** `IOSSDMFL-Remediation.ps1` and `IOSSDMFL-Set-ScopeTargeting.ps1` preview by default — read the plan, then apply.

• **Tune Conditional Access to the shift model.** Shared devices re-authenticate per user per shift; set sign-in frequency accordingly rather than fighting it.

• **Don't TLS-inspect Microsoft login endpoints** — it breaks registration and sign-out.

Change control

• **Re-verify after iOS major upgrades** and after adding any app to the pool — confirm the two-user clean-hand-off test still passes before expanding.

• **Record app SDM-support decisions.** Keep a short table (app → bundle ID → SDM supported? → source) so the next admin knows the boundary.

8. Deliverables Summary — iOS iPhone Entra ID Shared Device Mode

Everything included in this solution package, and what each piece is for.

Documentation (this guide)

• **Executive Summary** — the business case and outcome in one page, and the explicit scope: per-user identity sessions on shared iPhones via Entra Shared Device Mode, not kiosk lockdown and not Apple Shared iPad.

• **Solution Overview** — how Entra Shared Device Mode works on iPhones (no-affinity enrollment, Authenticator shared-mode registration, SDM-aware apps), global sign-in / single sign-out, what it isolates (honestly), and why iPhones need it (Apple Shared iPad is iPad-only).

• **Requirements Guide** — every ABM/ADE, Entra, Intune, role, and app prerequisite with how to **verify** and how to **implement if missing** — including the Assigned-group + Intune Provisioning Client owner requirement — plus the category-level Global Requirements.

• **Implementation Guide** — exact, ordered, click-by-click steps across four phases: build the foundation (assigned group + owner, no-affinity ADE profile, apps, restrictions, role), enroll and register a pilot device into shared mode, pilot the global sign-in / single sign-out, then validate and expand.

• **Testing & Validation** — nine tests with explicit pass/fail gates, centered on the two-user clean-hand-off test, plus a non-SDM-app boundary negative test.

• **Troubleshooting** — enrollment-order diagnosis for empty groups, affinity, shared-mode registration, sign-out data-clearing, and app-support cases.

• **Best Practices** — enrollment-time grouping, treating app scope as the security boundary, provisioning discipline, and proving the hand-off with two real users.

PowerShell scripts (Microsoft Graph) — `IOSSDMFL-Scripts.zip`

All scripts are tenant-side (run from an admin workstation with the Microsoft Graph PowerShell SDK); each has a header explaining **Purpose · How to run · Expected results**. Discovery, Validation, and Report are **read-only**; Remediation and Set-ScopeTargeting **default to** `-WhatIf` (preview first, then apply).

1. `IOSSDMFL-Discovery.ps1` — tenant readiness: no-affinity ADE profile, Microsoft Authenticator +

Teams assigned, the Assigned device group with the Intune Provisioning Client as owner, and the Cloud Device Administrator role populated.

1. `IOSSDMFL-Validation.ps1` — validates the assigned-group ownership, ADE profile affinity, and

app assignments, with a clear PASS/FAIL summary.

1. `IOSSDMFL-Report.ps1` — tenant-wide CSV report of shared (no-affinity) iOS devices and whether

the SDM apps are present — the shared-pool inventory.

1. `IOSSDMFL-Remediation.ps1` — safe remediation: create/assign the Assigned device group, set the

Intune Provisioning Client as owner, and flag missing app assignments. `-WhatIf` **by default.**

1. `IOSSDMFL-Set-ScopeTargeting.ps1` — sets/adjusts the target (Assigned) group used for the

shared-device apps/config. `-WhatIf` **by default.**

Hero image

- `IOSSDMFL-hero.png` — the product image used on the marketplace listing.

How it's delivered

A **Word** document and **PDF** (cover, table of contents, page numbers, and a scripts appendix), plus all five PowerShell scripts in a single **ZIP** — yours to keep and reuse across **unlimited devices**.

Appendix A — PowerShell Scripts

Included in the accompanying ZIP. Each script's header documents full usage.

IOSSDMFL-Discovery.ps1

Purpose: Confirms the Intune/Entra tenant is ready to run shared (frontline) iPhones under Entra Shared Device Mode: an iOS ADE enrollment profile that enrolls WITHOUT user affinity exists; Microsoft Authenticator and Microsoft Teams (iOS) are added; an ASSIGNED device group is present with the Intune Provisioning Client (AppId f1346770-5b25-470b-88bd-d5744ab7952c) as an OWNER; and the Cloud Device Administrator role has at least one member (the account that registers devices into shared mode). Read-only. HOW TO RUN powershell -ExecutionPolicy Bypass -File .\IOSSDMFL-Discovery.ps1 -GroupName "iPhone SDM - Devices" (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementServiceConfig.Read.All, DeviceManagementApps.Read.All, Group.Read.All, RoleManagement.Read.Directory, Application.Read.All EXPECTED RESULTS A PASS/FAIL line per check and an overall verdict. READY = no-affinity ADE profile present, Authenticator + Teams added, the Assigned group owned by the Intune Provisioning Client, and Cloud Device Administrator populated. .NOTES White-label — the repeatable way. Read-only against Microsoft Graph. > [CmdletBinding()] param([string]$GroupName = 'iPhone SDM - Devices')

How to run: powershell -ExecutionPolicy Bypass -File .\IOSSDMFL-Discovery.ps1 -GroupName "iPhone SDM - Devices" (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementServiceConfig.Read.All, DeviceManagementApps.Read.All, Group.Read.All, RoleManagement.Read.Directory, Application.Read.All EXPECTED RESULTS A PASS/FAIL line per check and an overall verdict. READY = no-affinity ADE profile present, Authenticator + Teams added, the Assigned group owned by the Intune Provisioning Client, and Cloud Device Administrator populated. .NOTES White-label — the repeatable way. Read-only against Microsoft Graph. > [CmdletBinding()] param([string]$GroupName = 'iPhone SDM - Devices')

IOSSDMFL-Remediation.ps1

Purpose: Remediates the most common blockers for iPhone Shared Device Mode enrollment-time grouping: creates the ASSIGNED device group if missing and ensures the Intune Provisioning Client (AppId f1346770-5b25-470b-88bd-d5744ab7952c) is an OWNER of it (without the owner, no-affinity devices never populate the group and nothing deploys). Defaults to -WhatIf, so it previews every change and modifies nothing until re-run to apply. It does NOT create the ADE profile or register devices into shared mode (an on-device Authenticator action) — those are called out. HOW TO RUN Preview (default, no changes): powershell -ExecutionPolicy Bypass -File .\IOSSDMFL-Remediation.ps1 -GroupName "iPhone SDM - Devices" Apply the change: powershell -ExecutionPolicy Bypass -File .\IOSSDMFL-Remediation.ps1 -GroupName "iPhone SDM - Devices" -WhatIf:$false (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: Group.ReadWrite.All, Application.Read.All EXPECTED RESULTS In preview: what is missing and exactly what WOULD be created/assigned. When applied: an Assigned security group exists with the Intune Provisioning Client as owner. Re-run IOSSDMFL-Discovery.ps1 to confirm READY, then finish the ADE profile + shared-mode registration per the Implementation Guide. .NOTES White-label — the repeatable way. Defaults to -WhatIf; changes require -WhatIf:$false. > [CmdletBinding(SupportsShouldProcess)] param([string]$GroupName = 'iPhone SDM - Devices')

How to run: Preview (default, no changes): powershell -ExecutionPolicy Bypass -File .\IOSSDMFL-Remediation.ps1 -GroupName "iPhone SDM - Devices" Apply the change: powershell -ExecutionPolicy Bypass -File .\IOSSDMFL-Remediation.ps1 -GroupName "iPhone SDM - Devices" -WhatIf:$false (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: Group.ReadWrite.All, Application.Read.All EXPECTED RESULTS In preview: what is missing and exactly what WOULD be created/assigned. When applied: an Assigned security group exists with the Intune Provisioning Client as owner. Re-run IOSSDMFL-Discovery.ps1 to confirm READY, then finish the ADE profile + shared-mode registration per the Implementation Guide. .NOTES White-label — the repeatable way. Defaults to -WhatIf; changes require -WhatIf:$false. > [CmdletBinding(SupportsShouldProcess)] param([string]$GroupName = 'iPhone SDM - Devices')

IOSSDMFL-Report.ps1

Purpose: Produces an inventory of iOS/iPadOS devices enrolled WITHOUT a primary user (the shared pool), so you can see which shared iPhones exist, their OS version, enrollment/ownership, and whether they are members of the shared-device group. Use it to measure coverage before widening and to find shared phones that still need provisioning. Read-only. HOW TO RUN powershell -ExecutionPolicy Bypass -File .\IOSSDMFL-Report.ps1 Optional: -GroupName "iPhone SDM - Devices" -CsvPath .\IOSSDMFL-shared-devices.csv (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementManagedDevices.Read.All, Group.Read.All EXPECTED RESULTS A table (and optional CSV) of no-primary-user iOS devices with an InGroup column, plus a summary. Note: 'registered into Shared Device Mode' is an on-device Authenticator action and is confirmed on the device (Testing Test 4); this report covers the enrollment/group foundation. .NOTES White-label — the repeatable way. Read-only against Microsoft Graph. > [CmdletBinding()] param([string]$GroupName = 'iPhone SDM - Devices', [string]$CsvPath)

How to run: powershell -ExecutionPolicy Bypass -File .\IOSSDMFL-Report.ps1 Optional: -GroupName "iPhone SDM - Devices" -CsvPath .\IOSSDMFL-shared-devices.csv (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementManagedDevices.Read.All, Group.Read.All EXPECTED RESULTS A table (and optional CSV) of no-primary-user iOS devices with an InGroup column, plus a summary. Note: 'registered into Shared Device Mode' is an on-device Authenticator action and is confirmed on the device (Testing Test 4); this report covers the enrollment/group foundation. .NOTES White-label — the repeatable way. Read-only against Microsoft Graph. > [CmdletBinding()] param([string]$GroupName = 'iPhone SDM - Devices', [string]$CsvPath)

IOSSDMFL-Set-ScopeTargeting.ps1

Purpose: Sets or adjusts the target (Assigned) group used for the shared-iPhone rollout by assigning a named iOS app (e.g. Microsoft Authenticator or Microsoft Teams) to the group as Required — the target-group builder for pilot-first, wave-based expansion. Defaults to -WhatIf, previewing the assignment change and modifying nothing until re-run to apply. HOW TO RUN Preview (default, no changes): powershell -ExecutionPolicy Bypass -File .\IOSSDMFL-Set-ScopeTargeting.ps1 -AppName "Microsoft Teams" -GroupName "iPhone SDM - Devices" Apply the assignment: powershell -ExecutionPolicy Bypass -File .\IOSSDMFL-Set-ScopeTargeting.ps1 -AppName "Microsoft Teams" -GroupName "iPhone SDM - Devices" -WhatIf:$false (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementApps.ReadWrite.All, Group.Read.All EXPECTED RESULTS In preview: the app and group found and the assignment that WOULD be set (Required). When applied: the app is assigned Required to the group. Confirm with IOSSDMFL-Validation.ps1. .NOTES White-label — the

repeatable way. Defaults to -WhatIf; changes require -WhatIf:$false. > [CmdletBinding(SupportsShouldProcess)] param([Parameter(Mandatory)] [string]$AppName, [string]$GroupName = 'iPhone SDM - Devices')

How to run: Preview (default, no changes): powershell -ExecutionPolicy Bypass -File .\IOSSDMFL-Set-ScopeTargeting.ps1 -AppName "Microsoft Teams" -GroupName "iPhone SDM - Devices" Apply the assignment: powershell -ExecutionPolicy Bypass -File .\IOSSDMFL-Set-ScopeTargeting.ps1 -AppName "Microsoft Teams" -GroupName "iPhone SDM - Devices" -WhatIf:$false (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementApps.ReadWrite.All, Group.Read.All EXPECTED RESULTS In preview: the app and group found and the assignment that WOULD be set (Required). When applied: the app is assigned Required to the group. Confirm with IOSSDMFL-Validation.ps1. .NOTES White-label — the repeatable way. Defaults to -WhatIf; changes require -WhatIf:$false. > [CmdletBinding(SupportsShouldProcess)] param([Parameter(Mandatory)] [string]$AppName, [string]$GroupName = 'iPhone SDM - Devices')

IOSSDMFL-Validation.ps1

Purpose: Validates the three things that most often break an iPhone Shared Device Mode rollout: (1) the device group is ASSIGNED and owned by the Intune Provisioning Client (so no-affinity devices actually populate it at enrollment); (2) an iOS ADE enrollment profile enrolls WITHOUT user affinity; (3) Microsoft Authenticator and Teams are assigned to the group. Read-only. HOW TO RUN powershell -ExecutionPolicy Bypass -File .\IOSSDMFL-Validation.ps1 -GroupName "iPhone SDM - Devices" (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: Group.Read.All, Application.Read.All, DeviceManagementServiceConfig.Read.All, DeviceManagementApps.Read.All EXPECTED RESULTS A PASS/FAIL summary. PASS when the group is Assigned + owned by the Provisioning Client, a no-affinity ADE profile exists, and Authenticator + Teams are assigned to the group. .NOTES White-label — the repeatable way. Read-only against Microsoft Graph. > [CmdletBinding()] param([string]$GroupName = 'iPhone SDM - Devices')

How to run: powershell -ExecutionPolicy Bypass -File .\IOSSDMFL-Validation.ps1 -GroupName "iPhone SDM - Devices" (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: Group.Read.All, Application.Read.All, DeviceManagementServiceConfig.Read.All, DeviceManagementApps.Read.All EXPECTED RESULTS A PASS/FAIL summary. PASS when the group is Assigned + owned by the Provisioning Client, a no-affinity ADE profile exists, and Authenticator + Teams are assigned to the group. .NOTES White-label — the repeatable way. Read-only against Microsoft Graph. > [CmdletBinding()] param([string]$GroupName = 'iPhone SDM - Devices')