Windows Interactive Logon & Network-Access Security Options Hardening (Intune)

Implementation Solution Guide

Version 1.0.0 · 2026-07-29

Contents

Executive Summary — Windows Interactive Logon & Network-Access Security Options Hardening (Intune) 4

1. Solution Overview — Windows Interactive Logon & Network-Access Security Options Hardening (Intune) 5

What this solution is . . . 5

Why these four, and why together . . . 6

How it works, step by step . . . 6

What this changes for users (be honest) . . . 7

Limitations (be honest with buyers) . . . 7

The standard deployment model . . . 7

2. Requirements — Windows Interactive Logon & Network-Access Security Options Hardening 8

R1. Windows 10/11 devices enrolled in Intune . . . 8

R2. Settings Catalog available in the tenant . . . 8

R3. Existing hardening coverage identified (avoid overlap) . . . 8

R4. Smart card infrastructure (only if you enable smart-card removal behavior) . . . 8

R5. Network topology understood (Windows Connection Manager non-domain block) . . . 9

R6. User-impact communication plan (automatic restart sign-on) . . . 9

R7. Microsoft Graph PowerShell SDK (for the included scripts) . . . 9

R8. Pilot group and pilot device . . . 9

Global Requirements — Intune Solutions (category-level) 9

G1. Microsoft Entra ID tenant . . . 10

G2. Microsoft Intune subscription . . . 10

G3. Administrative roles . . . 10

G4. Device enrollment in Intune . . . 10

G5. Pilot security group . . . 10

G6. Supported Windows baseline . . . 10

G7. Network access to Microsoft cloud endpoints . . . 10

3. Implementation — Windows Interactive Logon & Network-Access Security Options Hardening 11

Phase 1 — Assess and prepare . . . 11

Phase 2 — Create the Settings Catalog profile . . . 11

Phase 3 — Pilot . . . 13

Phase 4 — Validate and expand . . . 14

5. Testing & Validation — Windows Interactive Logon & Network-Access Security Options Hardening 14

Test 1 — Tenant readiness . . . 15

Test 2 — Profile assignment . . . 15
Test 3 — Profile applied on the device . . . 15
Test 4 — Applied values on the device . . . 15
Test 5 — Network selection UI hidden . . . 15
Test 6 — Smart-card removal locks the session . . . 15
Test 7 — No automatic restart sign-on after an update reboot . . . 15
Test 8 — Non-domain network blocked while on the corporate network . . . 16
Test 9 — Coverage report . . . 16
Test 10 — Nothing else changed (negative test) . . . 16
Acceptance gate . . . 16
6. Troubleshooting — Windows Interactive Logon & Network-Access Security Options Hardening 16
Symptom: The profile never appears on the device . . . 16
Symptom: Profile shows "Error" / "Conflict" in Device status . . . 17
Symptom: A setting isn't taking effect on the device . . . 17
Symptom: Automatic restart sign-on still happens after an update reboot . . . 17
Symptom: Smart-card removal doesn't lock the screen . . . 17
Symptom: Network selection UI still shows at sign-in . . . 18
Symptom: A legitimate workflow lost its non-domain connection . . . 18
Symptom: Works for some devices, not others . . . 18
Symptom: Coverage report shows fewer devices than the group . . . 18
Escalation checklist . . . 18
7. Best Practices — Windows Interactive Logon & Network-Access Security Options Hardening
Own each setting once . . . 19
Communicate the user-visible changes before you enable them . . . 19
Scope narrowly, then widen . . . 19
Get the values right, and verify them . . . 19
Operate and monitor . . . 20
Change control . . . 20
8. Deliverables Summary — Windows Interactive Logon & Network-Access Security Options Hardening 20
Documentation (this guide) . . . 20
PowerShell scripts (Microsoft Graph) — `WINSECOPT-Scripts.zip` . . . 21
Hero image . . . 21
How it's delivered . . . 22
Appendix A — PowerShell Scripts 23

Executive Summary — Windows Interactive Logon & Network-Access Security Options Hardening (Intune)

A security assessment of a Windows fleet always leaves a short list of **Security Options and logon policies** that no other hardening product owns — the settings that sit *between* the well-known workstreams. The NTLM/SMB, RDP, and credential-theft products each carry their own findings; what is left over are the **interactive-logon behaviors** and the **network-access controls at the logon screen** that quietly widen the attack surface: a machine that will happily join an untrusted network while on the corporate LAN, a smart card that can be pulled without locking the session, an automatic sign-in that re-establishes the last user after an update reboot, and a network-selection UI exposed before anyone has authenticated. This solution is the **hardening pack that closes exactly those leftover findings** using **Microsoft Intune Settings Catalog** — no Group Policy, no imaging.

A deliberately scoped, gap-only capability. This package hardens **four** specific Windows policies and nothing else:

- **Prohibit connection to non-domain networks when connected to a domain-authenticated network** —

stops a bridged/dual-homed path off the trusted network (Windows Connection Manager, `fBlockNonDomain = 1`).

- **Interactive logon: Smart card removal behavior = Lock Workstation** — pulling the card locks the

session instead of leaving it open (`scremoveoption = 1`).

- **Disable "Sign-in and lock last interactive user automatically after a restart"** — no automatic

re-establishment of the last user's session after an update reboot (`DisableAutomaticRestartSignOn = 1`).

- **Do not display network selection UI** — hides the network-picker on the sign-in screen so an

unauthenticated user cannot change connectivity (`DontDisplayNetworkSelectionUI = 1`).

It does **not** re-do the work owned by the NTLM/SMB hardening, RDP hardening, or credential-theft / LSA-protection products — it complements them and complements a CIS/STIG baseline. It resolves roughly **four** Windows Client assessment findings that those products leave behind.

Honest about user impact. Disabling automatic restart sign-on means that after a Windows Update reboot, the last interactive user is **not** silently signed back in and locked — the user must log in again. That is the intended, more-secure behavior; this package calls it out so you can set the expectation before rollout rather than field surprised tickets.

This package delivers the complete, field-tested method to stand it up in Intune — written so a single administrator can follow it end to end:

- **One profile, one purpose.** A single named **Settings Catalog** profile —

`Interactive Logon & Network-Access Hardening - Pilot` — carrying the four settings, deployed pilot-first and fully reversible by unassigning it.

- **Verify-don't-invent.** Every exact CSP/Settings-Catalog path and value is given, and the ones that

Microsoft renames between releases are flagged **verify in your tenant** rather than assumed.

• **Pilot-first, reversible.** The standard shape — **Assess → Configure → Pilot → Validate →

Expand** — with explicit pass/fail gates, a negative test that nothing else changed, and five ready-to-run PowerShell scripts (Microsoft Graph; discovery/validation/reporting are read-only, remediation and targeting default to a safe preview).

Outcome: the leftover interactive-logon and network-access Security-Options findings closed across the Windows fleet — hardened, proven on a pilot before you scale, without a consulting engagement and without touching how the devices are enrolled or imaged.

1. Solution Overview — Windows Interactive Logon & Network-Access Security Options Hardening (Intune)

What this solution is

This solution hardens a small, specific set of **Windows interactive-logon and network-access Security Options** on **Windows 10/11** devices managed by **Microsoft Intune**, using the **Settings Catalog**. It is the **"leftover findings" pack** — the Security-Options and logon policies that a fleet assessment flags but that are **not owned** by the NTLM/SMB hardening, RDP hardening, or credential-theft / LSA-protection products. Deploying it removes those remaining findings and complements a CIS or DISA STIG baseline.

Concretely, it configures **four** policies through Intune Settings Catalog — no on-prem Group Policy, no imaging, no re-enrollment:

#	Policy (admin-facing name)	Settings Catalog category	Underlying value
1	Prohibit connection to non-domain networks when connected to domain-authenticated network	Windows Connection Manager	`fBlockNonDomain = 1` (Enabled)
2	Interactive logon: Smart card removal behavior = **Lock Workstation**	Local Policies\Security Options	`scremoveoption = 1`
3	Sign-in and lock last interactive user automatically after a restart = **Disabled**	Administrative Templates\Windows Components\Windows Logon Options	`DisableAutomaticRestartSignOn = 1`
4	Do not display network selection UI = **Enabled**	Administrative Templates\System\Logon	`DontDisplayNetworkSelectionUI = 1`

> ***Scope, stated plainly.*** *This solution delivers **only** these four Security-Options / logon controls. It is **not** NTLM/SMB hardening, **not** RDP hardening, **not** credential-theft protection (Credential Guard / LSA protection / LAPS), and **not** a full CIS/STIG baseline — those are separate products. It is the pack that*

*catches the **remaining** interactive-logon and network-access findings those products leave behind.*

Why these four, and why together

Each of the four is a classic "Security Options" assessment finding that maps to a real, unglamorous risk at the sign-in boundary. They are shipped together because they share the same delivery method (one Settings Catalog profile), the same audience (any enrolled Windows client), and the same lifecycle (pilot, validate, expand):

1. **Prohibit connection to non-domain networks (Windows Connection Manager, `fBlockNonDomain`).**

When a device is connected to a domain-authenticated (corporate) network, Windows will normally let it *also* connect to a non-domain network (a phone hotspot, an untrusted Wi-Fi). That creates a **network bridge** off the trusted segment. Enabling this policy blocks the automatic non-domain connection while the domain connection is active.

1. **Smart card removal behavior = Lock Workstation (`scremoveoption`).** On smart-card sites, pulling

the card should **lock** the workstation immediately. Left at the default ("No Action"), a user can remove their card and walk away with the session unlocked. Setting it to **Lock Workstation** enforces the lock.

1. **Disable automatic restart sign-on (`DisableAutomaticRestartSignOn`).** After a Windows Update

reboot, Windows can automatically sign the **last interactive user** back in and lock the screen so apps resume. Convenient — but it re-establishes a user session without a fresh credential prompt. Setting the GPO **"Sign-in and lock last interactive user automatically after a restart"** to **Disabled** turns this off (`DisableAutomaticRestartSignOn = 1`), so the user must log in again.

1. **Do not display network selection UI (`DontDisplayNetworkSelectionUI`).** By default the Windows

sign-in screen shows a network-selection button, letting an **unauthenticated** person at the lock screen change network connectivity. Enabling this policy hides that UI.

How it works, step by step

1. **One Settings Catalog profile.** You create a single **Windows 10 and later** → **Settings Catalog**

configuration profile named `Interactive Logon & Network-Access Hardening - Pilot` and add the four settings from their Settings Catalog categories (Implementation, Phase 2).

1. **Assign to a pilot group.** The profile is assigned to a named pilot group

(`SEC - Interactive Logon Hardening Pilot`) — never to *All devices* first.

1. **Devices sync and apply.** Enrolled Windows devices in the group pick up the profile on their next

MDM sync; each setting writes its policy CSP value (the registry values in the table above).

1. **Validate the applied state.** The included scripts confirm the profile exists with the four

settings, is assigned to the intended group, and reports **Succeeded** per device.

1. **Expand in waves.** Once the pilot passes the acceptance gate, broaden the assignment or promote the profile to the standard hardening profile for corporate Windows devices.

What this changes for users (be honest)

• **After an update reboot, users re-authenticate.** With automatic restart sign-on disabled, Windows will **not** silently sign the last user back in after an Update reboot. The user sees the normal sign-in screen and logs in again. This is the intended hardening — communicate it so it is not mistaken for a fault.

• **Smart-card users: removing the card locks the screen.** Expected and desired on card sites; make sure users know to keep their card in while working.

• **No network picker at the lock screen.** Users cannot change Wi-Fi from the sign-in screen; they connect after signing in (or you pre-provision Wi-Fi via a separate profile).

• **Non-domain networks blocked while on the corporate network.** A device already on the corporate network will not auto-join a second, non-domain network at the same time. Roaming devices off the corporate network are unaffected.

Limitations (be honest with buyers)

• **Enrolled Windows 10/11 clients only.** Delivered by Intune MDM; it only reaches enrolled devices. It is not a server-hardening or non-Windows product.

• **Gap-only.** It deliberately excludes NTLM/SMB, RDP, credential-theft, and full-baseline controls — those are separate solutions. Deploy it *alongside* them, not instead of them.

• **Reversible, but behavioral.** Unassigning the profile reverts the settings; but while assigned, the user-impact items above are real and intended.

• **Identifiers can change.** The Settings Catalog display names and setting-definition IDs reflect current Microsoft documentation — **verify them in your tenant** before fleet rollout rather than assuming, especially the exact `settingDefinitionId` values used by the scripts.

The standard deployment model

This solution uses **one** repeatable model across our catalog:

> ***Enrolled Windows 10/11 devices receive a single named Settings Catalog profile carrying the four interactive-logon and network-access Security Options, deployed pilot-first and reversible.***

Every step follows the repeatable pattern: **Assess** → **Configure** → **Pilot** → **Validate** → **Expand.**

2. Requirements — Windows Interactive Logon & Network-Access Security Options Hardening

Confirm **every** requirement below before you begin. Each entry follows the same pattern: **Description · Why required · How to verify · How to implement if missing.** Category-wide prerequisites (tenant, Intune licensing, admin roles, pilot group, supported Windows baseline, network) are covered once in the **Global Requirements — Intune Solutions** document; the items here are specific to this interactive-logon & network-access Security Options hardening pack.

> ***Scope reminder.*** *These requirements are for the **four** Security-Options / logon controls in this pack (Windows Connection Manager non-domain block, smart-card removal = Lock Workstation, disable automatic restart sign-on, hide the network selection UI). They deliberately do **not** include NTLM/SMB, RDP, credential-theft, or full-baseline hardening — those are separate solutions.*

R1. Windows 10/11 devices enrolled in Intune

Description: The target devices are Intune-enrolled Windows 10 (21H2+) or Windows 11 clients. **Why:** The Settings Catalog profile is delivered by Intune MDM; it only reaches enrolled devices. **Verify:** Intune admin center (`https://intune.microsoft.com`) → **Devices** → **Windows** → **Windows devices**; the device is listed and **managed** (Entra joined or Entra hybrid joined). **Implement:** Enroll via **Automatic Enrollment** (Entra join + MDM auto-enroll) or Autopilot so the device appears under **Devices** → **Windows**. (Enrollment itself is covered by the enrollment solutions.)

R2. Settings Catalog available in the tenant

Description: The Intune **Settings Catalog** profile type for Windows is available. **Why:** This solution configures all four policies through one Settings Catalog profile rather than device-configuration templates or on-prem Group Policy. **Verify:** Intune → **Devices** → **Configuration** → **Create** → **New policy**; choose **Platform = Windows 10 and later**, **Profile type = Settings catalog**; the catalog search opens. **Implement:** Settings Catalog is standard in current Intune; if it is missing, confirm the tenant is on a supported service release and your account has the **Intune Administrator** role (Global Requirement G3).

R3. Existing hardening coverage identified (avoid overlap)

Description: Awareness of what your NTLM/SMB, RDP, credential-theft, and baseline products already configure. **Why:** This pack is **gap-only** — it closes the *leftover* interactive-logon and network-access findings. Deploying it on top of a baseline that already sets one of these four would create a **duplicate/conflicting** setting. **Verify:** In Intune → **Devices** → **Configuration**, review existing security baselines and hardening profiles for any of: Windows Connection Manager, Interactive logon smart-card removal, automatic restart sign-on, network selection UI. **Implement:** If a baseline already sets one of the four, decide a single owner for that setting (remove it here or there) so exactly one profile controls it — see Best Practices, "Own each setting once."

R4. Smart card infrastructure (only if you enable smart-card removal behavior)

Description: For control #2 (smart-card removal = Lock Workstation), the fleet actually uses smart cards / virtual smart cards for logon. **Why:** The Lock-Workstation-on-removal behavior only has an effect where smart-card logon is in use; on a fleet with no smart cards the setting is harmless but inert. **Verify:** Confirm whether users authenticate with PIV/CAC or virtual smart cards (certificate-based smart-card logon), e.g. via your PKI / certificate-deployment profiles. **Implement:** If you do not use smart cards, you may still

deploy the setting (no effect) or omit control #2 from the profile — document the choice. If you do use them, keep the value **Lock Workstation**.

R5. Network topology understood (Windows Connection Manager non-domain block)

Description: For control #1, an understanding of how devices reach the corporate (domain-authenticated) network and whether any legitimate workflow relies on simultaneous non-domain connectivity. **Why:** Blocking non-domain networks while on the domain network is a security win, but a device that *legitimately* needs a second, non-domain connection at the same time (rare) would be affected. **Verify:** Confirm the corporate network authenticates the machine to the domain (so Windows sees it as "domain-authenticated"), and that no supported workflow depends on a concurrent non-domain link. **Implement:** For the common single-network case, enable the block. If a legitimate dual-connection workflow exists, document the exception before enabling; the setting is per-device via the profile assignment.

R6. User-impact communication plan (automatic restart sign-on)

Description: A short comms plan warning users that after a Windows Update reboot they will need to **sign in again** (no automatic restart sign-on). **Why:** Control #3 changes a visible behavior. Without a heads-up, users may report the re-login as a fault. **Verify:** You have a one-line notice ready for the pilot group ("After updates restart your PC, you will be asked to sign in again — this is expected and more secure"). **Implement:** Include the notice in the pilot invitation and in fleet comms before you expand.

R7. Microsoft Graph PowerShell SDK (for the included scripts)

Description: The **Microsoft.Graph** PowerShell module installed on the admin workstation that runs the scripts. **Why:** All five scripts use Microsoft Graph to read/validate/report and (for remediation/targeting) to create or assign the profile. **Verify:** In PowerShell, `Get-Module Microsoft.Graph -ListAvailable` returns a version. **Implement:** `Install-Module Microsoft.Graph -Scope CurrentUser`. Discovery/Validation/Report need read scopes (`DeviceManagementConfiguration.Read.All`, `DeviceManagementManagedDevices.Read.All`); Remediation/Set-ScopeTargeting need `DeviceManagementConfiguration.ReadWrite.All`.

R8. Pilot group and pilot device

Description: A named Entra security group (`SEC - Interactive Logon Hardening Pilot`) with at least one enrolled Windows pilot device. **Why:** Every solution is validated on a pilot before fleet rollout. **Verify:** Entra → **Groups**; the group exists and contains the pilot device (or the pilot user, for a user-targeted assignment). The pilot device is enrolled (R1). **Implement:** Entra → **Groups** → **New group** → **Security**, name it `SEC - Interactive Logon Hardening Pilot`, add the pilot device/user. This is the group used for the profile assignment (Global Requirement G5).

Global Requirements — Intune Solutions (category-level)

These requirements apply to **every** solution in the **Intune Solutions** category. They are published once at the category level so individual listings stay small. Confirm these before deploying *any* Intune solution.

Each entry: **Description · Why · Verify · Implement-if-missing.**

G1. Microsoft Entra ID tenant

Description: An active Microsoft Entra ID (Azure AD) tenant. **Why:** It is the identity backbone for every cloud and Intune-managed resource. **Verify:** Sign in to `https://entra.microsoft.com` as an administrator. **Implement:** Create a Microsoft 365/Azure subscription, which provisions a tenant.

G2. Microsoft Intune subscription

Description: An Intune-bearing license plan. **Why:** Intune delivers all configuration, compliance, and security policies. **Verify:** `https://intune.microsoft.com` loads; **Tenant administration** → **Tenant status** shows active. **Implement:** Assign Microsoft 365 E3/E5, Business Premium, or standalone Intune Plan 1.

G3. Administrative roles

Description: Appropriate Entra/Intune admin roles for the operator. **Why:** Creating policies and enrollment settings requires elevated rights. **Verify:** Entra → **Roles and administrators**; confirm **Intune Administrator**. **Implement:** Assign **Intune Administrator**; reserve Global Administrator for tenant-wide changes.

G4. Device enrollment in Intune

Description: Targeted Windows devices are enrolled and manageable. **Why:** Policies only reach enrolled devices. **Verify:** Intune → **Devices** → **All devices**; the device appears and is **compliant**. **Implement:** Enable **Automatic Enrollment** and join devices to Entra ID.

G5. Pilot security group

Description: A Microsoft Entra security group for pilot/targeted users or devices. **Why:** Every solution is piloted before fleet rollout. **Verify:** Entra → **Groups**; the pilot group exists. **Implement:** Entra → **Groups** → **New group** → **Security** → add members.

G6. Supported Windows baseline

Description: Windows 10 21H2+ or Windows 11 with current updates. **Why:** Modern Intune features assume a patched, supported OS. **Verify:** `winver`, or Intune → device → **Hardware**. **Implement:** Deploy **Update rings** or upgrade to Windows 11.

G7. Network access to Microsoft cloud endpoints

Description: Outbound HTTPS to Microsoft 365, Entra, and Intune service URLs. **Why:** Enrollment, policy sync, and authentication depend on these endpoints. **Verify:** From a device, reach `https://login.microsoftonline.com` and `https://enrollment.manage.microsoft.com`. **Implement:** Allow Microsoft's published Office 365/Intune URL & IP ranges through proxy/firewall.

The standard deployment model (all solutions): Assess → Configure → Pilot → Validate → Expand.

3. Implementation — Windows Interactive Logon & Network-Access Security Options Hardening

Follow these steps **in order**. The *why* for each capability lives in the Solution Overview; the steps below are deliberately short and exact so you can **click to implement**. Throughout, the repeatable pattern applies: **Assess** → **Configure** → **Pilot** → **Validate** → **Expand.** Do everything against a **pilot group** first.

All admin-center steps use the Microsoft Intune admin center at `https://intune.microsoft.com` unless noted.

> ***This deploys the four Security-Options / logon controls only*** *on* ***enrolled Windows 10/11*** *clients, via a single* ***Settings Catalog*** *profile. It does not enroll or image devices and does not configure NTLM/SMB, RDP, or credential-theft hardening.*

Phase 1 — Assess and prepare

Step 1. Confirm enrollment and the Windows baseline

1. Go to **Devices** → **Windows** → **Windows devices** and confirm the pilot device is **managed** (Entra joined or Entra hybrid joined).
1. Open the device → **Hardware** and confirm **Windows 10 21H2+** or **Windows 11** with current updates.

Step 2. Check for existing owners of these four settings (avoid conflicts)

1. Go to **Devices** → **Configuration** and review your existing **security baselines** and hardening profiles.
1. Confirm that **none** of them already sets: *Windows Connection Manager* non-domain block, *Interactive logon: Smart card removal behavior*, *automatic restart sign-on*, or *Do not display network selection UI*. If one does, decide a single owner for that setting before continuing (Requirements R3).

Step 3. Create (or confirm) the pilot group

1. Go to **Groups** → **New group** (or Entra → **Groups**).
2. **Group type = Security**; **Group name =** `SEC - Interactive Logon Hardening Pilot`.
3. Add the pilot device (for device-targeted assignment) or pilot user, then **Create**.

Phase 2 — Create the Settings Catalog profile

Step 4. Create the profile

1. Go to **Devices** → **Configuration** → **Create** → **New policy**.
2. **Platform = Windows 10 and later**; **Profile type = Settings catalog**; click **Create**.

3. **Basics** → **Name:** `Interactive Logon & Network-Access Hardening - Pilot`. **Description:**

Closes the leftover interactive-logon and network-access Security Options findings (Windows Connection Manager non-domain block, smart-card removal = Lock Workstation, disable automatic restart sign-on, hide network selection UI). Click **Next**.

Step 5. Add setting #1 — Prohibit connection to non-domain networks

1. On **Configuration settings**, click **+ Add settings**.
2. In the settings picker, search `Windows Connection Manager` and select that category.
3. Tick **Prohibit connection to non-domain networks when connected to domain authenticated network**.

Close the picker.

1. Set the setting's toggle to **Enabled**.

• *Underlying value:* `fBlockNonDomain = 1` (policy CSP

`WindowsConnectionManager/ProhibitConnectionToNonDomainNetworksWhenConnectedToDomainAuthenticatedNetwork`). **Verify the exact display name in your tenant** — Microsoft occasionally revises catalog labels.

Step 6. Add setting #2 — Interactive logon: Smart card removal behavior

1. Click **+ Add settings** again. Search `Smart Card Removal Behavior` (category **Local Policies

Security Options**).

1. Tick **Interactive Logon Smart Card Removal Behavior**. Close the picker.
2. Set its value to **Lock Workstation**.

• *Underlying value:* `scremoveoption = 1` (policy CSP

`LocalPoliciesSecurityOptions/InteractiveLogon_SmartCardRemovalBehavior`). Options are *No Action (0)*, **Lock Workstation (1)**, *Force Logoff (2)*, *Disconnect (3)* — choose **Lock Workstation**.

Step 7. Add setting #3 — Disable automatic restart sign-on

1. Click **+ Add settings**. Search **`Sign-in and lock last interactive user automatically after a

restart` **(category** Administrative Templates\Windows Components\Windows Logon Options**).

1. Tick the setting. Close the picker.
2. Set the toggle to **Disabled**. *(Disabling this GPO turns automatic restart sign-on OFF.)*

• *Underlying value:* `DisableAutomaticRestartSignOn = 1` (policy CSP

`WindowsLogon/DisableAutomaticRestartSignOn` — **verify the catalog wording in your tenant**; the ADMX-backed label and the CSP name differ, and setting the ADMX policy to **Disabled** is what yields `DisableAutomaticRestartSignOn = 1`).

Step 8. Add setting #4 — Do not display network selection UI

1. Click **+ Add settings**. Search `Do not display network selection UI` (category

Administrative Templates\System\Logon).

1. Tick the setting. Close the picker.
2. Set the toggle to **Enabled**.

• *Underlying value:* `DontDisplayNetworkSelectionUI = 1` (policy CSP `WindowsLogon/DontDisplayNetworkSelectionUI`).

*After Steps 5–8 the profile carries **four** settings. Click **Next**.*

Step 9. Scope tags, assignment, review

1. **Next** through **Scope tags** (set if you use them).
2. **Assignments:** add the `SEC - Interactive Logon Hardening Pilot` group. Do **not** assign to *All devices* yet. Click **Next**.
1. **Review + create** → **Create**.

*Prefer automation? Run the included `WINSECOPT-Remediation.ps1` (Microsoft Graph) to create the profile with all four settings if it is missing (defaults to **-WhatIf** — preview first, then re-run to apply), `WINSECOPT-Set-ScopeTargeting.ps1` to set/adjust the group assignment (also **-WhatIf** by default), and `WINSECOPT-Discovery.ps1` to confirm the profile is present and correctly configured.*

Phase 3 — Pilot

Step 10. Push and confirm the profile

1. On the pilot device, force an MDM sync: **Settings → Accounts → Access work or school → (your account) → Info → Sync**.
1. In Intune → **Devices → Configuration → `Interactive Logon & Network-Access Hardening - Pilot` → Device status**, **confirm the pilot device shows** Succeeded**.

Step 11. Spot-check the applied values on the device

1. On the pilot device, confirm the four registry values are set (read-only check):

• `HKLM\SOFTWARE\Policies\Microsoft\Windows\WcmSvc\GroupPolicy\fBlockNonDomain = 1`

• `HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Winlogon\scremoveoption = 1`

• `HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System\DisableAutomaticRestartSignOn = 1`

• `HKLM\SOFTWARE\Policies\Microsoft\Windows\System\DontDisplayNetworkSelectionUI = 1`

• **Verify these exact registry paths in your build** — they reflect current Windows behavior but can differ across releases.

Step 12. Validate the user-visible behavior

1. At the **sign-in screen**, confirm the **network-selection button is gone** (setting #4).

2. If smart cards are in use, **remove the card** from a signed-in pilot device and confirm the **session locks** (setting #2).

1. Trigger (or simulate) a **Windows Update reboot** and confirm the device returns to the **sign-in screen** rather than auto-signing the last user back in (setting #3). Tell the pilot user this is expected (Requirements R6).

1. While connected to the corporate network, confirm the device does **not** auto-join a second, non-domain network (setting #1).

Phase 4 — Validate and expand

Step 13. Validate with the scripts

1. Run `WINSECOPT-Discovery.ps1` (tenant readiness: the Settings Catalog profile exists with the four settings present).

1. Run `WINSECOPT-Validation.ps1` to confirm the profile is **assigned** to the intended group and the pilot device shows the profile **applied** (Succeeded).

1. Run `WINSECOPT-Report.ps1` to produce a coverage report (which Windows devices have the hardening profile applied).

Step 14. Remediate gaps (safe by default)

1. If the profile is missing or mis-scoped, run `WINSECOPT-Remediation.ps1` — it **defaults to `-WhatIf`** and prints exactly what it would create/assign. Review, then re-run with `-WhatIf:$false` to apply.

Step 15. Expand in waves

1. Once the pilot passes (Testing gate), broaden the assignment to the next group with `WINSECOPT-Set-ScopeTargeting.ps1` (or make it the standard hardening profile for corporate Windows devices).

1. Re-confirm with `WINSECOPT-Report.ps1` after each wave before widening further, and re-check that no other baseline has started to co-own one of the four settings (Requirements R3).

5. Testing & Validation — Windows Interactive Logon & Network-Access Security Options Hardening

Validate against a **pilot device** before expanding. Each test has an explicit **pass/fail gate**. Use the included PowerShell scripts (Microsoft Graph) for tenant-side checks and the on-device steps for the applied values and user-visible behavior.

> ***What "pass" means here:*** *the single named Settings Catalog profile is assigned and applied, all four settings carry their intended values on the pilot device, and the four user-visible behaviors are correct — with nothing else changed on the device.*

Test 1 — Tenant readiness

Procedure: Run `WINSECOPT-Discovery.ps1`. **Pass:** A Windows **Settings Catalog** profile exists that carries all **four** target settings (Windows Connection Manager non-domain block, smart-card removal behavior, disable automatic restart sign-on, do not display network selection UI). **Fail:** Profile missing or one of the four settings absent → create/complete it (Implementation Steps 4–8, or `WINSECOPT-Remediation.ps1`) before piloting.

Test 2 — Profile assignment

Procedure: Run `WINSECOPT-Validation.ps1` (or check **Devices** → **Configuration** → **(profile)** → **Assignments**). **Pass:** The profile is assigned to `SEC - Interactive Logon Hardening Pilot` and to no unintended broad group. **Fail:** Not assigned, or assigned to "All devices" prematurely → correct the assignment (Implementation Step 9 / `WINSECOPT-Set-ScopeTargeting.ps1`).

Test 3 — Profile applied on the device

Procedure: In Intune → profile → **Device status** (or on the device, force a sync). **Pass:** The `Interactive Logon & Network-Access Hardening - Pilot` profile shows **Succeeded** on the pilot device. **Fail:** Not applied / error → force a sync and re-check; resolve any conflict (Troubleshooting).

Test 4 — Applied values on the device

Procedure: On the pilot device, read the four policy registry values (read-only): `fBlockNonDomain`, `scremoveoption`, `DisableAutomaticRestartSignOn`, `DontDisplayNetworkSelectionUI`. **Pass:** All four equal **1** at the paths listed in Implementation Step 11. **Fail:** Any value missing or `0` → confirm the setting is present in the profile and re-sync; verify the exact registry path for your Windows build.

Test 5 — Network selection UI hidden

Procedure: Sign out and view the **sign-in screen**. **Pass:** No **network-selection** button/UI is shown at the lock/sign-in screen (setting #4). **Fail:** Network picker still visible → confirm setting #4 = **Enabled** and the device re-synced.

Test 6 — Smart-card removal locks the session

Procedure: *(Only if smart cards are used — Requirements R4.)* On a signed-in pilot device, remove the smart card. **Pass:** The workstation **locks** immediately (setting #2 = Lock Workstation). **Fail:** Session stays unlocked → confirm `scremoveoption = 1` and that smart-card logon is actually in use.

Test 7 — No automatic restart sign-on after an update reboot

Procedure: Trigger (or simulate) a **Windows Update** reboot on the pilot device. **Pass:** The device returns to the **sign-in screen**; the last user is **not** auto-signed-in and locked — the user must log in again (setting #3). **Fail:** The last user's session is silently re-established → confirm the GPO "Sign-in and lock last interactive user automatically after a restart" is set to **Disabled** (`DisableAutomaticRestartSignOn = 1`).

Test 8 — Non-domain network blocked while on the corporate network

Procedure: With the pilot device connected to the corporate (domain-authenticated) network, attempt to connect to a non-domain network (e.g. a phone hotspot). **Pass:** Windows does **not** automatically establish the concurrent non-domain connection while the domain connection is active (setting #1). **Fail:** A second non-domain connection is established automatically → confirm setting #1 = **Enabled** and the device is seen as domain-authenticated on the corporate network.

Test 9 — Coverage report

Procedure: Run `WINSECOPT-Report.ps1`. **Pass:** The report lists the pilot device(s) as **profile applied**; counts match the assigned group. **Fail:** Devices missing from the report → run `WINSECOPT-Remediation.ps1` (`-WhatIf` first) to fix assignment/scoping.

Test 10 — Nothing else changed (negative test)

Procedure: Confirm the profile carries **only** the four target settings, and the device's enrollment, ownership, and other baselines are unchanged. **Pass:** Only the four Security-Options / logon values changed; NTLM/SMB, RDP, credential-theft, and other baseline settings are untouched (this pack is gap-only). **Fail:** Other settings changed → confirm you added only the four settings in Steps 5–8 and that no duplicate/conflicting profile is present.

Acceptance gate

Proceed to **Expand** only when Tests 1–9 pass on at least one pilot device, Test 10 confirms the change is limited to the four settings, and a real pilot user confirms the update-reboot re-login behavior is understood and acceptable.

6. Troubleshooting — Windows Interactive Logon & Network-Access Security Options Hardening

Work top-down: confirm the **profile is applied**, then that **each of the four settings carries the intended value**, then the **user-visible behavior**. Most issues are a missing setting in the profile, a **conflict** with a security baseline that already owns the same policy, or the "Disabled-means-on" inversion on the automatic-restart-sign-on control. Each symptom below gives the **likely cause** and the **fix**.

> ***Before you start:*** *confirm no other product owns these settings. If a security baseline or another hardening profile already sets one of the four, that is an ownership/conflict problem (Requirements R3), not a profile error.*

Symptom: The profile never appears on the device

Likely cause: Device not synced, not assigned, or not enrolled. **Fix:**

1. Confirm the device is in `SEC - Interactive Logon Hardening Pilot` and the profile is **assigned** (`WINSECOPT-Validation.ps1`).
1. Force a sync: **Settings** → **Accounts** → **Access work or school** → **(account)** → **Info** → **Sync**.
2. Check **Devices** → **Configuration** → **(profile)** → **Device status** for an error.

Symptom: Profile shows "Error" / "Conflict" in Device status

Likely cause: A security baseline or a second hardening profile already sets one of the four policies to a different value. **Fix:**

1. Run `WINSECOPT-Discovery.ps1` and review your baselines for Windows Connection Manager, Interactive-logon smart-card removal, automatic restart sign-on, or network selection UI.
1. Decide a **single owner** for the conflicting setting — remove it from the baseline or from this profile so exactly one profile controls it (Requirements R3).
1. Re-sync and re-check Device status.

Symptom: A setting isn't taking effect on the device

Likely cause: The setting was not actually added to the profile, or its value is wrong. **Fix:**

1. Confirm all **four** settings are present in the profile (`WINSECOPT-Discovery.ps1` / profile UI).
2. Spot-check the registry value on the device (Testing, Test 4): the value should be **1** at the documented path.
1. If the value is missing, re-add the setting (Implementation Steps 5–8) and re-sync.

Symptom: Automatic restart sign-on still happens after an update reboot

Likely cause: The **inversion** — the ADMX policy was set to *Enabled* instead of **Disabled**, so automatic restart sign-on is still on. **Fix:**

1. Open the profile and confirm **"Sign-in and lock last interactive user automatically after a restart" **is set to** Disabled** (this yields `DisableAutomaticRestartSignOn = 1`).
1. Spot-check `HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System\DisableAutomaticRestartSignOn = 1`.
2. Re-sync and re-test the update reboot (Testing, Test 7).

Symptom: Smart-card removal doesn't lock the screen

Likely cause: Smart-card logon isn't actually in use, or the value isn't Lock Workstation. **Fix:**

1. Confirm the fleet uses smart-card / virtual-smart-card **logon** (Requirements R4) — the behavior only fires for card-based logon.

1. Confirm the setting value is **Lock Workstation** (`scremoveoption = 1`), not "No Action".
2. Re-sync and re-test (Testing, Test 6).

Symptom: Network selection UI still shows at sign-in

Likely cause: Setting #4 not Enabled, or the device hasn't re-synced. **Fix:**

1. Confirm **Do not display network selection UI = Enabled** (`DontDisplayNetworkSelectionUI = 1`).
2. Force a sync and lock the device to re-render the sign-in screen.
3. If users now can't pick Wi-Fi before logon, pre-provision the corporate Wi-Fi with a separate Wi-Fi profile (Best Practices).

Symptom: A legitimate workflow lost its non-domain connection

Likely cause: Setting #1 is blocking a *legitimately* needed concurrent non-domain connection. **Fix:**

1. Confirm the workflow genuinely needs simultaneous domain + non-domain connectivity (rare — Requirements R5).
1. If it does, scope this device out of the assignment (exclusion group via `WINSECOPT-Set-ScopeTargeting.ps1 -ExcludeGroupId ...`) and document the exception, rather than disabling the setting fleet-wide.

Symptom: Works for some devices, not others

Likely cause: Group membership, sync timing, or a per-device conflict. **Fix:**

1. Confirm affected devices are in the assigned group (`WINSECOPT-Report.ps1`).
2. Re-sync stragglers and confirm enrollment (Requirements R1).
3. Check Device status on the affected devices for a conflict with another profile.

Symptom: Coverage report shows fewer devices than the group

Likely cause: Some devices not synced, not enrolled, or in an error state. **Fix:**

1. Run `WINSECOPT-Report.ps1` to list which devices lack the applied profile.
2. Run `WINSECOPT-Remediation.ps1` **(**`-WhatIf` **first)** to correct assignment/scoping.
3. Re-sync stragglers and confirm enrollment (Requirements R1).

Escalation checklist

Before opening a Microsoft support case, collect: the `WINSECOPT-Discovery.ps1` output, the profile's Device status export, the four registry values from an affected device, the Windows build/version, and whether any security baseline co-owns one of the four settings (isolates a genuine platform issue from a policy conflict).

7. Best Practices — Windows Interactive Logon & Network-Access Security Options Hardening

These practices keep the hardening pack precise, predictable, and reversible on enrolled Windows 10/11 devices. They assume the deployment model in the Solution Overview: a single named **Settings Catalog** profile carrying the four interactive-logon and network-access controls, deployed via Intune, pilot-first.

Own each setting once

- **This pack is gap-only — don't co-own settings.** Before deploying, confirm your NTLM/SMB, RDP, credential-theft, and CIS/STIG baselines do **not** already set any of these four. Two profiles that set the same policy differently produce a **conflict** ("Error" in Device status).
- **One profile per concern.** Keep these four in the single named profile `Interactive Logon & Network-Access Hardening - Pilot` so the owner of each Security-Options finding is obvious. If a baseline must own one of the four, remove it here.

Communicate the user-visible changes before you enable them

- **Automatic restart sign-on off = re-login after updates.** Send the one-line notice from Requirements R6 to the pilot group and again before each expansion wave. This single behavior drives most of the "is it broken?" tickets — pre-empt it.
- **Smart-card removal locks the screen.** On card sites, remind users to keep the card in while working; the lock-on-removal is the intended protection.
- **No network picker at sign-in.** If users occasionally need to pick Wi-Fi before logging in, pre-provision the corporate Wi-Fi with a separate Wi-Fi profile so hiding the picker doesn't strand them.

Scope narrowly, then widen

- **Assign to** `SEC - Interactive Logon Hardening Pilot`**, never "All devices" first.** Expand in waves after each gate passes.
- **Rollback is unassignment.** Because this only adds a configuration profile, removing the assignment reverts the four settings — no imaging or account cleanup. Keep the profile so you can re-target quickly.

Get the values right, and verify them

- **Use the intended values exactly:** Windows Connection Manager block **Enabled** (`fBlockNonDomain = 1`); smart-card removal **Lock Workstation** (scremoveoption = 1); automatic restart sign-on GPO **Disabled** (DisableAutomaticRestartSignOn = 1); do not display network

`selection UI` **`Enabled`** (DontDisplayNetworkSelectionUI = 1`).

- **Verify catalog labels and CSP names in your tenant.** Microsoft renames Settings Catalog display strings and occasionally the `settingDefinitionId` values; confirm current names before a wide rollout, and update the scripts' identifiers to match if they have drifted.

- **Mind the "Disabled means on" inversion.** Control #3 is the one that trips people up: you set the ADMX policy to **Disabled** to *disable* automatic restart sign-on. Double-check this one on the pilot with the registry spot-check (Testing, Test 4).

Operate and monitor

- **Report before you widen.** Run `WINSECOPT-Report.ps1` each wave; only broaden when coverage matches the assigned group.

- **Remediate with** `-WhatIf` **first.** `WINSECOPT-Remediation.ps1` and `WINSECOPT-Set-ScopeTargeting.ps1` preview by default — read the plan, then apply with `-WhatIf:$false`.

- **Re-check ownership after baseline changes.** Whenever you update a security baseline, re-run Discovery to confirm the baseline hasn't started to co-own one of these four settings.

Change control

- **Version scope changes.** When you adjust a value or the assignment, note the date and reason; re-run Discovery and Report to confirm no regressions.

- **Review after major Windows upgrades.** Confirm the four settings still apply and the registry paths still match after significant Windows feature updates before expanding further.

8. Deliverables Summary — Windows Interactive Logon & Network-Access Security Options Hardening

Everything included in this solution package, and what each piece is for.

Documentation (this guide)

- **Executive Summary** — the business case and outcome in one page, and the explicit scope: the four leftover interactive-logon and network-access Security Options findings, not NTLM/SMB, RDP, credential-theft, or full-baseline hardening.

- **Solution Overview** — what each of the four controls does (Windows Connection Manager non-domain block, smart-card removal = Lock Workstation, disable automatic restart sign-on, hide the network selection UI), the exact values, the honest user-impact, and how this pack is gap-only and complements a

CIS/STIG baseline.

• **Requirements Guide** — every Intune/Windows prerequisite with how to **verify** and how to **implement if missing**, including checking for existing owners of these settings, plus the category-level Global Requirements.

• **Implementation Guide** — exact, ordered, click-by-click steps across four phases: assess and prepare, build the single named Settings Catalog profile with the four settings, pilot, then validate and expand.

• **Testing & Validation** — ten tests with explicit pass/fail gates (including registry spot-checks and a negative test that nothing else changed) and an acceptance gate.

• **Troubleshooting** — top-down diagnosis for missing/not-applying settings, baseline conflicts, the "Disabled-means-on" inversion, and the user-visible behaviors.

• **Best Practices** — owning each setting once, communicating the user-visible changes, precise values with verify-in-tenant discipline, and reversible pilot-first rollout.

PowerShell scripts (Microsoft Graph) — `WINSECOPT-Scripts.zip`

All scripts are tenant-side (run from an admin workstation with the Microsoft Graph PowerShell SDK); each has a header explaining **Purpose · How to run · Expected results**. Discovery, Validation, and Report are **read-only**; Remediation and Set-ScopeTargeting **default to** `-WhatIf` (preview first, then apply).

1. `WINSECOPT-Discovery.ps1` — tenant readiness: a Windows Settings Catalog profile is present that carries all four target settings.
1. `WINSECOPT-Validation.ps1` — validates the profile's **assignment** and per-device **applied** state, with a clear PASS/FAIL summary.
1. `WINSECOPT-Report.ps1` — tenant-wide CSV report of Windows devices and whether the hardening profile is applied — the coverage report.
1. `WINSECOPT-Remediation.ps1` — safe remediation: creates the Settings Catalog profile with the four settings if missing and assigns it to a target group. `-WhatIf` **by default**; applies only when re-run with `-WhatIf:$false`.
1. `WINSECOPT-Set-ScopeTargeting.ps1` — sets/adjusts the profile's group assignment (target-group builder, with optional exclusion group). `-WhatIf` **by default.**

Hero image

• `WINSECOPT-hero.png` — the product image used on the marketplace listing.

How it's delivered

A **Word** document and **PDF** (cover, table of contents, page numbers, and a scripts appendix), plus all five PowerShell scripts in a single **ZIP** — yours to keep and reuse across **unlimited devices**.

Appendix A — PowerShell Scripts

Included in the accompanying ZIP. Each script's header documents full usage.

WINSECOPT-Discovery.ps1

Purpose: Confirms the Intune tenant carries a Windows Settings Catalog profile that hardens the four leftover interactive-logon and network-access Security Options this solution owns: 1) Windows Connection Manager — prohibit connection to non-domain networks when connected to a domain-authenticated network (fBlockNonDomain = 1); 2) Interactive logon: Smart card removal behavior = Lock Workstation (scremoveoption = 1); 3) Disable "Sign-in and lock last interactive user automatically after a restart" (DisableAutomaticRestartSignOn = 1); 4) Do not display network selection UI (DontDisplayNetworkSelectionUI = 1). Reports a PASS/FAIL per setting and an overall verdict. This checks THIS gap-only pack only — not NTLM/SMB, RDP, credential-theft, or full-baseline hardening. HOW TO RUN powershell -ExecutionPolicy Bypass -File .\WINSECOPT-Discovery.ps1 Optional: -ProfileName "Interactive Logon & Network-Access Hardening - Pilot" (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementConfiguration.Read.All EXPECTED RESULTS A PASS/FAIL line per target setting and an overall verdict. A READY tenant shows a Windows Settings Catalog profile carrying all four settings. .NOTES White-label — the repeatable way. Read-only against Microsoft Graph. Settings Catalog display names and settingDefinitionId values can drift between service releases — verify the identifiers below in your tenant if a match is missed. > [CmdletBinding()] param([string]$ProfileName = 'Interactive Logon & Network-Access Hardening - Pilot')

How to run: powershell -ExecutionPolicy Bypass -File .\WINSECOPT-Discovery.ps1 Optional: -ProfileName "Interactive Logon & Network-Access Hardening - Pilot" (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementConfiguration.Read.All EXPECTED RESULTS A PASS/FAIL line per target setting and an overall verdict. A READY tenant shows a Windows Settings Catalog profile carrying all four settings. .NOTES White-label — the repeatable way. Read-only against Microsoft Graph. Settings Catalog display names and settingDefinitionId values can drift between service releases — verify the identifiers below in your tenant if a match is missed. > [CmdletBinding()] param([string]$ProfileName = 'Interactive Logon & Network-Access Hardening - Pilot')

WINSECOPT-Remediation.ps1

Purpose: Remediates the common gap that leaves these four Security Options unhardened: creates the Windows Settings Catalog profile if none exists — carrying 1) Windows Connection Manager: prohibit non-domain networks when on a domain-authenticated network (fBlockNonDomain = 1); 2) Interactive logon: Smart card removal behavior = Lock Workstation (scremoveoption = 1); 3) Disable "Sign-in and lock last interactive user automatically after a restart" (DisableAutomaticRestartSignOn = 1); 4) Do not display network selection UI (DontDisplayNetworkSelectionUI = 1) — and assigns it to a target group. Defaults to -WhatIf, so it previews every change and modifies nothing until re-run to apply. Remediates THIS gap-only pack only — never NTLM/SMB, RDP, credential-theft, or full-baseline hardening. HOW TO RUN Preview (default, no changes): powershell -ExecutionPolicy Bypass -File .\WINSECOPT-Remediation.ps1 -GroupId your-entra-group-object-id Apply the change: powershell -ExecutionPolicy Bypass -File .\WINSECOPT-Remediation.ps1 -GroupId your-entra-group-object-id -WhatIf:$false (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementConfiguration.ReadWrite.All EXPECTED RESULTS In preview: a report of what is missing and exactly what WOULD be created/assigned. When applied: a Windows Settings Catalog profile

carrying the four settings exists and is assigned to the group. Re-run WINSECOPT-Discovery.ps1 to confirm READY. .NOTES White-label — the repeatable way. Defaults to -WhatIf; changes require -WhatIf:$false. IMPORTANT: the settingDefinitionId / choice option values below reflect current Microsoft documentation for the Windows Settings Catalog. Microsoft occasionally revises these ids — VERIFY them in your tenant (Devices > Configuration > Settings catalog) and update this script if a POST is rejected. When in doubt, build the profile by hand from Implementation Steps 4-8. > [CmdletBinding(SupportsShouldProcess)] param([Parameter(Mandatory)] [string]$GroupId, [string]$Name = 'Interactive Logon & Network-Access Hardening - Pilot')

How to run: Preview (default, no changes): powershell -ExecutionPolicy Bypass -File .\WINSECOPT-Remediation.ps1 -GroupId your-entra-group-object-id Apply the change: powershell -ExecutionPolicy Bypass -File .\WINSECOPT-Remediation.ps1 -GroupId your-entra-group-object-id -WhatIf:$false (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementConfiguration.ReadWrite.All EXPECTED RESULTS In preview: a report of what is missing and exactly what WOULD be created/assigned. When applied: a Windows Settings Catalog profile carrying the four settings exists and is assigned to the group. Re-run WINSECOPT-Discovery.ps1 to confirm READY. .NOTES White-label — the repeatable way. Defaults to -WhatIf; changes require -WhatIf:$false. IMPORTANT: the settingDefinitionId / choice option values below reflect current Microsoft documentation for the Windows Settings Catalog. Microsoft occasionally revises these ids — VERIFY them in your tenant (Devices > Configuration > Settings catalog) and update this script if a POST is rejected. When in doubt, build the profile by hand from Implementation Steps 4-8. > [CmdletBinding(SupportsShouldProcess)] param([Parameter(Mandatory)] [string]$GroupId, [string]$Name = 'Interactive Logon & Network-Access Hardening - Pilot')

WINSECOPT-Report.ps1

Purpose: Produces a coverage report across Windows devices: for each managed Windows 10/11 device, whether the interactive-logon & network-access hardening Settings Catalog profile is applied. Use it to measure coverage before widening a rollout and to find corporate devices still missing the four Security-Options controls. Read-only. Reports THIS gap-only pack only. HOW TO RUN powershell -ExecutionPolicy Bypass -File .\WINSECOPT-Report.ps1 Optional: -ProfileName "Interactive Logon & Network-Access Hardening - Pilot" -CsvPath .\WINSECOPT-coverage.csv (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementConfiguration.Read.All, DeviceManagementManagedDevices.Read.All EXPECTED RESULTS A table (and optional CSV) of Windows devices with an Applied column (Yes/No/Error) plus a coverage summary. Full coverage = every intended device shows Applied = Yes. .NOTES White-label — the repeatable way. Read-only against Microsoft Graph. > [CmdletBinding()] param([string]$ProfileName = 'Interactive Logon & Network-Access Hardening - Pilot', [string]$CsvPath)

How to run: powershell -ExecutionPolicy Bypass -File .\WINSECOPT-Report.ps1 Optional: -ProfileName "Interactive Logon & Network-Access Hardening - Pilot" -CsvPath .\WINSECOPT-coverage.csv (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementConfiguration.Read.All, DeviceManagementManagedDevices.Read.All EXPECTED RESULTS A table (and optional CSV) of Windows devices with an Applied column (Yes/No/Error) plus a coverage summary. Full coverage = every intended device shows Applied = Yes. .NOTES White-label — the repeatable way. Read-only against Microsoft Graph. > [CmdletBinding()] param([string]$ProfileName = 'Interactive Logon & Network-Access Hardening - Pilot', [string]$CsvPath)

WINSECOPT-Set-ScopeTargeting.ps1

Purpose: Sets or adjusts which Entra security group the interactive-logon & network-access hardening Settings Catalog profile is assigned to — the target-group builder for pilot-first, wave-based rollout on corporate Windows devices. Optionally adds an assignment exclusion group. Defaults to -WhatIf, previewing the assignment change and modifying nothing until re-run to apply. Targets THIS gap-only pack's profile only, not NTLM/SMB, RDP, credential-theft, or full-baseline hardening. HOW TO RUN Preview (default, no changes): powershell -ExecutionPolicy Bypass -File .\WINSECOPT-Set-ScopeTargeting.ps1 -GroupId your-entra-group-object-id Apply the assignment: powershell -ExecutionPolicy Bypass -File .\WINSECOPT-Set-ScopeTargeting.ps1 -GroupId your-entra-group-object-id -WhatIf:$false Optional: -ExcludeGroupId your-exclusion-group-object-id ; -ProfileName "Interactive Logon & Network-Access Hardening - Pilot" (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementConfiguration.ReadWrite.All EXPECTED RESULTS In preview: the profile found and the assignment that WOULD be set. When applied: the profile is assigned to the include group (and excludes the exclusion group). Confirm in Intune - Devices - Configuration, or with WINSECOPT-Validation.ps1. .NOTES White-label — the repeatable way. Defaults to -WhatIf; changes require -WhatIf:$false. > [CmdletBinding(SupportsShouldProcess)] param([Parameter(Mandatory)] [string]$GroupId, [string]$ExcludeGroupId, [string]$ProfileName = 'Interactive Logon & Network-Access Hardening - Pilot')

How to run: Preview (default, no changes): powershell -ExecutionPolicy Bypass -File .\WINSECOPT-Set-ScopeTargeting.ps1 -GroupId your-entra-group-object-id Apply the assignment: powershell -ExecutionPolicy Bypass -File .\WINSECOPT-Set-ScopeTargeting.ps1 -GroupId your-entra-group-object-id -WhatIf:$false Optional: -ExcludeGroupId your-exclusion-group-object-id ; -ProfileName "Interactive Logon & Network-Access Hardening - Pilot" (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementConfiguration.ReadWrite.All EXPECTED RESULTS In preview: the profile found and the assignment that WOULD be set. When applied: the profile is assigned to the include group (and excludes the exclusion group). Confirm in Intune - Devices - Configuration, or with WINSECOPT-Validation.ps1. .NOTES White-label — the repeatable way. Defaults to -WhatIf; changes require -WhatIf:$false. > [CmdletBinding(SupportsShouldProcess)] param([Parameter(Mandatory)] [string]$GroupId, [string]$ExcludeGroupId, [string]$ProfileName = 'Interactive Logon & Network-Access Hardening - Pilot')

WINSECOPT-Validation.ps1

Purpose: Validates the Windows interactive-logon & network-access Settings Catalog profile is assigned to the intended group and applied on target devices. Confirms the profile exists, that it is assigned (optionally to a specified -GroupId), and reports each Windows device's applied state (Succeeded / Error / Not applied). Read-only. Validates THIS gap-only pack only — not NTLM/SMB, RDP, credential-theft, or full-baseline hardening. HOW TO RUN powershell -ExecutionPolicy Bypass -File .\WINSECOPT-Validation.ps1 -ProfileName "Interactive Logon & Network-Access Hardening - Pilot" Optional: -GroupId your-entra-group-object-id (assert the profile is assigned to this group) (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementConfiguration.Read.All EXPECTED RESULTS A PASS/FAIL summary: profile found, assigned (to -GroupId if supplied), and a per-device applied-state table. PASS when the profile is assigned and pilot devices report Succeeded. .NOTES White-label — the repeatable way. Read-only against Microsoft Graph. > [CmdletBinding()] param([string]$ProfileName = 'Interactive Logon & Network-Access Hardening - Pilot', [string]$GroupId)

How to run: powershell -ExecutionPolicy Bypass -File .\WINSECOPT-Validation.ps1 -ProfileName "Interactive Logon & Network-Access Hardening - Pilot" Optional: -GroupId your-entra-group-object-id (assert the profile is assigned to this group) (Install once: Install-Module Microsoft.Graph -Scope CurrentUser) Required Graph scopes: DeviceManagementConfiguration.Read.All EXPECTED RESULTS A PASS/FAIL summary: profile found, assigned (to -GroupId if supplied), and a per-device applied-state table. PASS when the profile is assigned and pilot devices report Succeeded. .NOTES White-label — the repeatable way. Read-only against Microsoft Graph. > [CmdletBinding()] param([string]$ProfileName = 'Interactive Logon & Network-Access Hardening - Pilot', [string]$GroupId)