Microsoft Purview — DLP, Sensitivity Labels & Retention (Government / GCC High)

Implementation Solution Guide

Version 1.0.0 · 2026-07-01

Contents

Executive Summary — Microsoft Purview DLP, Labels & Retention (Government / GCC High) 4

The problem . . . 4

What this solution does . . . 4

The GCC High differences that matter (doc-confirmed) . . . 4

Business outcome . . . 4

Solution Overview — Microsoft Purview DLP, Sensitivity Labels & Retention (Government / GCC High) 5

What this solution delivers . . . 5

Why GCC High is a different solution, not a re-login . . . 5

The Purview information-protection model (how the pieces fit) . . . 5

Commercial vs GCC High — what's different . . . 6

The standard deployment model . . . 7

What's in the box . . . 7

Requirements — Purview DLP, Labels & Retention (Government / GCC High) 8

R1. A Microsoft 365 Government – GCC High tenant . . . 8

R2. Government Purview licensing (G3 / G5 / G5 Compliance) . . . 8

R3. Purview administrative roles . . . 9

R4. Access to the GCC High Purview compliance portal . . . 9

R5. A label taxonomy, data owners, a pilot scope, and change control . . . 9

R6. Network / filtering allow-list for GCC High endpoints . . . 9

R7. Managed endpoints onboarded for Endpoint DLP (if using device DLP) . . . 10

R8. Parity confirmation for the specific features you intend to use . . . 10

Implementation — Purview DLP, Labels & Retention (Government / GCC High) 10

Phase 0 — Assess (gate before you build) . . . 11

Phase 1 — Sensitivity labels + label policy . . . 11

Phase 2 — Auto-labeling (service-side) . . . 12

Phase 3 — DLP (audit first, then enforce) . . . 13

Phase 4 — Retention & records . . . 14

Phase 5 — Pilot → Validate → Expand . . . 15

Testing — Purview DLP, Labels & Retention (Government / GCC High) 15

Gate 0 — Sovereign-cloud sanity (must pass first) . . . 15

Gate 1 — Licensing & roles present . . . 15

Gate 2 — Parity check completed . . . 16

Gate 3 — Labels published and visible . . . 16

Gate 4 — Manual + mandatory labeling works . . . 16

Gate 5 — Service-side auto-labeling simulation is accurate . . . 16
Gate 6 — DLP detects in audit (no block yet) . . . 16
Gate 7 — Endpoint DLP (only if in scope) . . . 17
Gate 8 — DLP enforcement (post-tuning, change-controlled) . . . 17
Gate 9 — Retention applied . . . 17
Gate 10 — Records & disposition (only if records in scope) . . . 17
Gate 11 — Script validation clean . . . 17
Troubleshooting — Purview DLP, Labels & Retention (Government / GCC High) 18
A. GCC-High-specific gotchas . . . 18
B. Labels not appearing for users . . . 19
C. Mandatory labeling / justification not enforced . . . 19
D. Auto-labeling not matching (or over-matching) . . . 19
E. DLP not detecting . . . 20
F. DLP blocking legitimate work . . . 20
G. Retention not applying / wrong end-of-life behavior . . . 20
H. Records / disposition not working . . . 20
I. Scripts fail or report nothing . . . 20
Best Practices — Purview DLP, Labels & Retention (Government / GCC High) 21
Sovereign-cloud discipline (GCC High) . . . 21
Taxonomy & labels . . . 21
DLP . . . 22
Retention & records . . . 22
Operations . . . 22
Deliverables Summary — Purview DLP, Labels & Retention (Government / GCC High) 23
Documents . . . 23
Scripts (PowerShell, Microsoft Graph SDK, **US Gov endpoints**) . . . 24
Named objects (created and reused verbatim) . . . 24
Outcome . . . 24
Appendix A — PowerShell Scripts 25

Executive Summary — Microsoft Purview DLP, Labels & Retention (Government / GCC High)

The problem

Microsoft Purview in **GCC High is not the Commercial product with a different sign-in.** The admin portals are separate US sovereign-cloud endpoints (`compliance.microsoft.us`, `security.microsoft.us`, `login.microsoftonline.us`), and **several Purview capabilities lag, are limited, or are absent** versus Commercial. A government tenant configured from Commercial runbooks silently fails — options simply are not present, and steps assume features that do not exist in GCC High.

What this solution does

It deploys the three Purview pillars — **sensitivity labels + auto-labeling**, **Data Loss Prevention**, and **retention + records management** — **correctly for GCC High**: the right portals, the right endpoints, and the Commercial-vs-GCC-High **feature parity gaps called out at the exact step where they matter**. It follows a repeatable **Assess** → **Configure** → **Pilot** → **Validate** → **Expand** model with pass/fail gates, so the configuration is proven on a named pilot before it scales.

The GCC High differences that matter (doc-confirmed)

Drawn from Microsoft's *Plan for Microsoft Purview — GCC High deployments* service description:

- **Named-entity sensitive information types** are **not available** — DLP and auto-labeling are built from GA building blocks (built-in SITs, Exact Data Match, keywords, regex).
- **Auto-labeling on Office *mobile* clients** is **not available**; service-side (EXO/SPO/OneDrive) and desktop/web client-side auto-labeling **are**.
- **Auto-applying *records* labels with trainable classifiers**, and **applying a retention label action at end of the retention period**, are** not available** — condition/event-based retention is used instead.
- **Records-management Power Automate and several Graph APIs** are **not available**.
- **Adaptive Protection** (risk-based DLP) is **rolling out to Gov clouds** — verify before relying on it. **Microsoft Priva** is **not available**.

Where a GCC High specific could not be confirmed, the solution states the Commercial behavior and **explicitly flags "verify for GCC High"** rather than inventing menus or parity claims.

Business outcome

An ungoverned data estate — unclassified data, DLP noise, no retention, compliance gaps — becomes a **governed** one: data **labeled, protected, and retained** on a US sovereign cloud, configured the repeatable way, validated on a pilot, and safe to expand. Self-guided and tested, at a fraction of consulting cost.

Deployment model: Assess → Configure → Pilot → Validate → Expand.

Solution Overview — Microsoft Purview DLP, Sensitivity Labels & Retention (Government / GCC High)

What this solution delivers

This is the **Government (GCC High)** edition of the Microsoft Purview information-protection solution. It walks a competent-but-novice administrator through deploying three Purview pillars on a **US sovereign-cloud (GCC High)** tenant, the repeatable way:

1. **Sensitivity labels + label policies (+ auto-labeling)** — classify and, where appropriate,

encrypt content so protection travels with the data.

1. **Data Loss Prevention (DLP)** across Exchange, SharePoint, OneDrive, Teams, and endpoints —

detect and control the movement of sensitive information, **starting in audit and tuning before you enforce**.

1. **Retention labels & policies and records management** — keep what must be kept, dispose of what

must go, on a defensible schedule.

Together these turn an **ungoverned data estate** (unclassified data, DLP noise, no retention, compliance gaps) into a **governed** one: data that is **labeled, protected, and retained** — proven on a pilot before you scale.

Why GCC High is a different solution, not a re-login

Microsoft Purview in **GCC High is not the Commercial portal with a different sign-in.** Two things differ in ways that break Commercial runbooks:

• **The portals and endpoints are different sovereign-cloud hosts** — you administer Purview at

`compliance.microsoft.us` (rolling to `purview.microsoft.us`), sign in at `login.microsoftonline.us`, and your scripts must target **US Gov Graph endpoints** (`Connect-MgGraph -Environment USGov`). Point a Commercial runbook at `compliance.microsoft.com` and you are in the wrong cloud.

• **Feature parity lags Commercial.** Several Purview capabilities that are generally available in

Commercial are, in GCC High, in preview, "in development", or "on the engineering backlog" — i.e. **not present**. Following Commercial steps that assume those features will silently fail: the menu or option simply is not there.

This edition calls out the correct GCC High portals/endpoints at each step, and flags the parity gaps **where they matter**, so a government tenant is configured correctly. The full parity reference lives in `gcc-high-parity-notes.md` and is cited throughout.

The Purview information-protection model (how the pieces fit)

• **Sensitivity labels** are the classification taxonomy (e.g. `Public`, `General`,

`Confidential`, `Confidential \ CUI`). A **label policy** publishes labels to users/groups and sets behavior (default label, mandatory labeling, downgrade justification). **Auto-labeling** applies a label without user action, based on conditions (built-in sensitive information types, Exact Data Match, keyword dictionaries, or trainable classifiers).

• **DLP policies** watch for sensitive content (the same SITs/EDM/classifiers) as it is stored,

shared, or exfiltrated, and take actions (audit, notify, block, restrict) across M365 locations and managed endpoints. A **sensitivity label can itself be a DLP condition** — label once, enforce everywhere.

• **Retention labels / policies** govern how long content lives and what happens at end of life

(retain, then delete; delete only; or declare a **record** with a locked retention). **Records management** adds file plan, disposition review, and proof of disposal for regulated content.

The design principle across all three is **assign once, repeat everywhere**: a small, well-named taxonomy drives labeling, DLP, and retention consistently, instead of one-off policies per team.

Commercial vs GCC High — what's different

(Doc-confirmed from Microsoft's "Plan for Microsoft Purview — GCC High deployments" service description unless flagged. See `gcc-high-parity-notes.md` for the full table and citations.)

Portals & endpoints (always different):

Purpose	Commercial	GCC High
Sign-in	`login.microsoftonline.com`	`login.microsoftonline.us`
Microsoft 365 admin	`admin.microsoft.com`	`portal.office365.us`
Purview / compliance	`compliance.microsoft.com`	`compliance.microsoft.us` (→ `purview.microsoft.us`)
Security portal	`security.microsoft.com`	`security.microsoft.us`
Entra admin	`entra.microsoft.com`	`entra.microsoft.us`
Graph (scripts)	`graph.microsoft.com` (`-Environment Global`)	`graph.microsoft.us` (`-Environment USGov`)

Feature parity gaps that change how you design (GCC High status in parentheses):

• **Named entity SITs and their policy-authoring templates** are **not available** (*on engineering

backlog*). Build DLP/auto-label conditions from **built-in SITs, Exact Data Match, keyword dictionaries, and regex SITs** instead.

• **Auto-labeling for Office *mobile* clients** is **not available** (*on engineering backlog*).

Client-side auto-labeling on Windows/Mac/web and service-side auto-labeling for EXO/SPO/OneDrive **are** available.

• **Applying a "default label" to unlabeled files in a SharePoint library**, and **default label on

documents being edited**, are** not available** (*in development*). Plan default-labeling around what is GA (label policy default label for users; service-side auto-labeling).

- **Granular Conditional Access via sensitivity labels for SPO sites** is **not available** (*on engineering backlog*). Verify container/site-label behavior separately for GCC High.
- **Auto-applying *retention/records* labels with trainable classifiers** is **not available** (*in development*), and **"apply retention label action at end of retention period"** is **not available** (*on engineering backlog*). Trainable classifiers **do** work for **client-side auto-labeling** of sensitivity labels (GA).
- **Records-management Power Automate integration** and several **Graph APIs (records, eDiscovery export, Teams export) **are** not available** (*in development / backlog*).
- **Adaptive Protection** (Insider Risk → dynamic DLP) is **rolling out to Gov clouds** (GCC/GCC High/DoD), not long-established — **verify it is present in your tenant** before designing on it.
- **DSPM for AI** is available but **"Browse to URL" policy cannot be created** in GCC-H; only supported AI sites apply.
- **Microsoft Priva** (Privacy Risk Management, Subject Rights Requests) is **not available** (*in development*).

Where a specific classifier, SIT, or option is not visible in `compliance.microsoft.us`, treat it as a **GCC High parity gap, not a permissions problem** — re-check the parity table before troubleshooting.

The standard deployment model

Every step in this solution follows the same repeatable model, with an explicit **pass/fail gate** between phases:

Assess → **Configure** → **Pilot** → **Validate** → **Expand.**

- **Assess** — confirm licensing (Gov G3/G5), roles, portal access, and which features are actually available in your GCC High tenant (the parity check).
- **Configure** — design the label taxonomy and build labels, label policy, DLP policies (in **audit/test** mode), and retention labels/policies. Name every object verbatim.
- **Pilot** — publish to a **named pilot group** only.
- **Validate** — run the pass/fail gates in `05-testing.md` against the pilot.
- **Expand** — widen scope group-by-group only after the gate passes.

What's in the box

- This overview, a **Requirements** guide, an ordered **Implementation** guide, **Testing** (pass/fail gates), **Troubleshooting** (with GCC-High-specific gotchas), **Best Practices**, and a **Deliverables Summary** + **Executive Summary**.

• A **GCC High parity notes** reference (`gcc-high-parity-notes.md`) with per-feature status and Microsoft citations.

• **Five PowerShell scripts** (Graph SDK, US Gov endpoints): Discovery, Validation, Report, Remediation, and Set-ScopeTargeting — read-only tools default to read-only; change tools default to `-WhatIf`.

> ***Sources:*** *Microsoft Learn — *Plan for Microsoft Purview — GCC High deployments* (`.../plan-for-microsoft-purview-gcc-high-deployments`); *Microsoft Purview service description*; *Adaptive Protection* docs; MSPortals.io US Government portals. Full citations in* `gcc-high-parity-notes.md`.

Requirements — Purview DLP, Labels & Retention (Government / GCC High)

Confirm every prerequisite below **before** you configure anything. This edition assumes a **GCC High** tenant throughout — the portals and endpoints are the US sovereign-cloud hosts, not the Commercial ones. Category-level prerequisites (Entra tenant, admin roles, pilot group, network access) are in `global-requirements-security.md`; the items here are **Purview- and GCC-High-specific**.

Each requirement is written as **Description · Why · Verify · Implement if missing.**

R1. A Microsoft 365 Government – GCC High tenant

Description: An active **Microsoft 365 Government – GCC High** tenant (US sovereign cloud), not a Commercial or GCC (moderate) tenant. **Why:** GCC High uses different sovereign endpoints and has a different Purview feature-parity profile. Commercial steps and URLs will not work, and features you plan for may not exist here. **Verify:** Sign in at `https://login.microsoftonline.us` and open `https://portal.office365.us`. In the Microsoft 365 admin center, the environment/branding indicates a US Government (GCC High) tenant. The Purview portal loads at `https://compliance.microsoft.us` (or `purview.microsoft.us`), **not** `.com`. **Implement if missing:** GCC High requires eligibility validation and onboarding through Microsoft / an authorized Gov reseller — you cannot self-provision it like Commercial. See Microsoft Learn *Plan for Microsoft Purview — GCC High deployments*, Steps 1–2. This is a procurement action, not a portal click.

R2. Government Purview licensing (G3 / G5 / G5 Compliance)

Description: Purview information-protection, DLP, and retention licensing via **Microsoft 365 Government G3/G5**, **G5 Compliance**, or **G5 Information Protection & Governance** add-ons — the **Gov** SKUs, not Commercial E3/E5. **Why:** Feature access follows the same E3-vs-E5 split as Commercial (auto-labeling, records management, Adaptive Protection are G5/E5-class), **on top of** GCC High parity gaps. Missing G5 means missing auto-labeling and records management entirely. **Verify:** `portal.office365.us` → **Billing** → **Licenses**; confirm **Microsoft 365 G3/G5** and any **G5 Compliance** / **Information Protection & Governance** SKUs. Cross-check the feature you need against the *Microsoft Purview service description*. **Implement if missing:** Acquire the appropriate Gov SKU / add-on through your Gov licensing channel and assign it to the admin and pilot users. (See `gcc-high-parity-notes.md` §6.)

R3. Purview administrative roles

Description: Role-group membership sufficient to author labels, DLP, and retention — **Compliance Administrator** (or **Compliance Data Administrator**) plus **Information Protection Admin** / **Information Protection** role group; **Records Management** for records; **Organization Management** for role assignment. **Why:** Creating and publishing labels, DLP policies, and retention/records policies requires these Purview role groups. Global Administrator works but is over-privileged for day-to-day authoring. **Verify:** `compliance.microsoft.us` → **Settings** → **Roles & scopes** → **Permissions** (Microsoft Purview solutions); confirm the operator is in **Compliance Administrator** and **Information Protection** (and **Records Management** if doing records). **Implement if missing:** Add the operator to the required role groups in **Roles & scopes** → **Permissions**. Reserve **Global Administrator** for tenant-wide changes only.

R4. Access to the GCC High Purview compliance portal

Description: The operator can reach and use `https://compliance.microsoft.us` (Microsoft Purview portal, rolling to `purview.microsoft.us`). **Why:** All label/DLP/retention authoring happens here. If filtering blocks the `.us` sovereign hosts, nothing can be configured. **Verify:** Browse to `https://compliance.microsoft.us`; the Purview solutions (Information Protection, Data Loss Prevention, Data Lifecycle Management, Records Management) load. **Implement if missing:** Allow the GCC High Purview/Defender hosts through proxy/filtering (see R6), and confirm the account has R3 roles.

R5. A label taxonomy, data owners, a pilot scope, and change control

Description: A short **agreed label taxonomy** (e.g. `Public`, `General`, `Confidential`, `Confidential \ CUI`), named **data owners** who approve classification meaning, a named **pilot group**, and a **change-control/rollback** process (labeling and DLP-block changes can disrupt users). **Why:** Purview is a business-classification system, not just a technical control. Publishing labels or enforcing DLP without owner agreement and a pilot causes user disruption and mislabeled data. **Verify:** A one-page taxonomy exists with owner sign-off; a pilot Entra security group named `SG-Purview-Pilot` exists (`entra.microsoft.us` → Groups); a change ticket template with approver, window, and rollback exists. **Implement if missing:** Draft the taxonomy with data owners; create `SG-Purview-Pilot` in `entra.microsoft.us`; adopt the change-control process from `global-requirements-security.md` (G8).

R6. Network / filtering allow-list for GCC High endpoints

Description: Outbound HTTPS to the **GCC High sovereign endpoints** for portals, service-side protection, endpoint DLP, and the labeling client/scanner. **Why:** Enrollment, policy sync, auto-labeling, DLP telemetry, and script access all use the `.us` Gov hosts. If only the `.com` Commercial hosts are allowed, GCC High Purview will not function. **Verify:** From an admin workstation, reach `https://login.microsoftonline.us`, `https://compliance.microsoft.us`, `https://security.microsoft.us`, and `https://graph.microsoft.us`. **Implement if missing:** Allow Microsoft's published **Office 365 U.S. Government GCC High** URL/IP ranges through proxy/firewall (the Gov endpoint list is separate from the Commercial "Office 365 Worldwide" list). Include the labeling client, endpoint-DLP, and PowerShell Gov endpoints.

R7. Managed endpoints onboarded for Endpoint DLP (if using device DLP)

Description: Windows/macOS devices onboarded to **Microsoft Defender / Endpoint** in the GCC High tenant and visible for **Endpoint DLP**. **Why:** Endpoint DLP (copy-to-USB, print, cloud-upload controls) — **Available** in GCC High — only covers onboarded devices. Unonboarded devices are invisible to device DLP. **Verify:** `compliance.microsoft.us` → **Settings** → **Device onboarding**; devices show onboarded. In `security.microsoft.us`, devices are enrolled. **Implement if missing:** Onboard devices per Microsoft's Endpoint DLP onboarding for GCC High, then turn on device monitoring in Purview **Settings** → **Device onboarding**.

R8. Parity confirmation for the specific features you intend to use

Description: A completed check of the **GCC High parity table** for every Purview feature this deployment depends on (specific SITs, trainable classifiers, auto-labeling surfaces, records options, Adaptive Protection). **Why:** Several Commercial features are **not available** in GCC High (named-entity SITs, mobile auto-labeling, trainable-classifier-driven *records* labels, end-of-retention label actions, records Power Automate, Priva). Designing around a missing feature wastes the pilot. **Verify:** Work through `gcc-high-parity-notes.md`; for each feature you need, confirm status is **Available** in the live Microsoft doc **and** the option is visible in `compliance.microsoft.us`. **Implement if missing:** Where a needed feature is *in development / on backlog*, choose the GA alternative (e.g. built-in SIT/EDM/keyword instead of named-entity SIT; condition-based record policy instead of classifier-based) and record the substitution in the design.

The deployment model (all solutions): Assess → Configure → Pilot → Validate → Expand.

Implementation — Purview DLP, Labels & Retention (Government / GCC High)

Follow these steps **in order**. Every navigation path uses the **GCC High** portals — sign in at `https://login.microsoftonline.us` and work in `https://compliance.microsoft.us` (the Microsoft Purview portal; it may redirect to `purview.microsoft.us`). If a portal loads at a `.com` host, stop — you are in the Commercial cloud.

Naming — use these object names verbatim (reuse them exactly in later steps and in the scripts):

Object	Name to create and reuse
Pilot Entra security group	`SG-Purview-Pilot`
Sensitivity labels	`Public`, `General`, `Confidential`, `Confidential \ CUI`
Label policy	`LP-Purview-Pilot`
Auto-labeling policy (service-side)	`AL-CUI-ServiceSide`
DLP policy	`DLP-CUI-Baseline`
DLP rule (inside the policy)	`DLP-CUI-Baseline-Rule1`

Object	Name to create and reuse
Retention label	`Ret-CUI-7yr`
Retention label policy (auto-apply)	`RP-CUI-7yr-Auto`
Org-wide retention policy	`RP-Baseline-Retain`

GCC High parity reminders are inlined at the step where they matter. Full detail: `gcc-high-parity-notes.md`.

Phase 0 — Assess (gate before you build)

1. Sign in at `https://login.microsoftonline.us`; open `https://compliance.microsoft.us`.

Confirm the Purview solutions **Information Protection**, **Data Loss Prevention**, **Data Lifecycle Management**, and **Records Management** all appear in the left navigation.

1. Confirm licensing (R2) at `https://portal.office365.us` → **Billing** → **Licenses** — G3/G5 (+ G5

Compliance / IP&G) present.

1. Confirm roles (R3) at `compliance.microsoft.us` → **Settings** → **Roles & scopes** → **Permissions**.

2. Confirm `SG-Purview-Pilot` exists at `https://entra.microsoft.us` → **Groups**. If not:

Groups → **New group** → **Security**, name it `SG-Purview-Pilot`, add pilot users.

1. **Run the parity check (R8).** For every feature you intend to use, confirm **Available** in

`gcc-high-parity-notes.md` and that the option is visible in the portal.

Gate: portal loads at `.us`, licensing/roles present, pilot group exists, parity check done. Do not proceed until all pass.

Phase 1 — Sensitivity labels + label policy

Step 1.1 — Create the labels

1. In `compliance.microsoft.us` go to **Information Protection** → **Labels** (under **Solutions**;

in the newer Purview portal this is **Information Protection** → **Sensitivity labels**).

1. **+ Create a label**. Create these four, in order, with these exact names:

• `Public` — scope **Items** (Files & emails). No encryption, no content marking.

• `General` — scope **Items**. No encryption; optional footer "General".

• `Confidential` — scope **Items**. Turn on **Encrypt** (assign permissions to your org),

content marking footer "Confidential".

• `Confidential \ CUI` — create `Confidential` first, then create **CUI** as a **sublabel** of `Confidential`. Turn on **Encrypt** with a restrictive permission set; content marking header "CUI".

1. For each label, complete the wizard (scope → protection settings → content marking → auto-labeling for files/emails **left OFF here**; you configure auto-labeling in Phase 2).

> ***GCC High note (containers):*** *if you want to label* ***Teams/Groups/SharePoint sites*** *(container labels), enable* ***Groups & sites*** *scope. Container labeling is available, but* ***granular Conditional Access via sensitivity labels for SPO sites is *not available* in GCC High*** *(*on engineering backlog*) — do not design site access-control on that feature. Verify container behavior in your tenant. (`gcc-high-parity-notes.md` §2.)*

Step 1.2 — Publish the labels with a label policy

1. **Information Protection** → **Label policies** → **Publish labels**.
2. Select `Public`, `General`, `Confidential`, `Confidential \ CUI`.
3. **Assign to users and groups:** choose `SG-Purview-Pilot` only (pilot scope).
4. Policy settings:

• **Default label for documents/emails:** `General`.

• **Require users to apply a label** (mandatory labeling): **On** for the pilot.

• **Require justification to remove a label or lower classification: On**.

1. **Name the policy** `LP-Purview-Pilot`; finish.

> ***GCC High note:*** *applying a* ***"default label" to unlabeled files uploaded to a SharePoint library****, and* ***default label on documents being edited****, are* ***not available*** *in GCC High (*in development*). The* ***user default label*** *above (via label policy)* ***is*** *available. Do not rely on library-side default labeling yet.*

Gate: pilot users see the four labels in Word/Excel/PowerPoint/Outlook (allow up to a few hours to replicate). If not visible, see `06-troubleshooting.md`.

Phase 2 — Auto-labeling (service-side)

Step 2.1 — Build conditions from GA classifiers only

> ***GCC High parity — read first: Named entity SITs and their policy-authoring templates are *not available**** *in GCC High (*on engineering backlog*). Build conditions from* ***built-in sensitive information types****,* ***Exact Data Match (EDM)*** *(Available),* ***keyword dictionaries****, and* ***regex SITs****.* ***Trainable classifiers*** *work for* ***client-side*** *auto-labeling (Available) but* ***not*** *for auto-applying *records* labels (*in development*).* ***Office *mobile* auto-labeling is *not available****.* *(`gcc-high-parity-notes.md` §2.)*

1. If you need a custom match, create it first under **Data classification → Classifiers →

Sensitive info types **(built-in/EDM/keyword/regex) or** Exact data match**. Do** not** select a named-entity SIT — it will not be present.

Step 2.2 — Create the service-side auto-labeling policy

1. **Information Protection** → **Auto-labeling** → **+ Create auto-labeling policy**.

2. Choose a template or **Custom**. **Locations:** Exchange Online, SharePoint Online, OneDrive (service-side auto-labeling for these three is **Available** in GCC High).

1. **Rules:** add conditions using the GA SITs/EDM/keywords from Step 2.1 (e.g. content contains your CUI EDM/keyword set).

1. **Label to apply:** `Confidential \ CUI`.

2. **Scope:** restrict to `SG-Purview-Pilot` mailboxes/sites where possible.

3. **Name the policy** `AL-CUI-ServiceSide`. Create it in **simulation (test) mode** — do **not** turn on immediately.

1. Run **simulation**, review matches in the policy's results, then turn the policy **On** only after the pilot gate passes.

Gate: simulation shows expected matches with acceptable false positives; no unexpected mass-label.

Phase 3 — DLP (audit first, then enforce)

Step 3.1 — Create the DLP policy in test/audit mode

1. **Data Loss Prevention** → **Policies** → **+ Create policy**.

2. **Custom** policy. **Locations:** Exchange, SharePoint, OneDrive, **Teams chat and channel**, and **Devices (Endpoint DLP)** — all **Available** in GCC High (Endpoint DLP requires onboarded devices, R7).

1. **Create rule** named `DLP-CUI-Baseline-Rule1`:

• **Conditions:** *Content contains* → your GA SITs/EDM/keywords **and/or** *Content contains sensitivity label* → `Confidential \ CUI` (label-as-condition = "label once, enforce everywhere").

• **Actions:** for the pilot, **audit only** — **no block**. (Notify admin; optional policy tip.)

1. **Name the policy** `DLP-CUI-Baseline`.

2. Set the policy **mode to *Test it out* / *Run in test mode* (audit)** — **not** "Turn it on".

Scope to `SG-Purview-Pilot` where the location supports user scoping.

> ***GCC High note (SITs):*** *confirm each SIT in your rule is a* ***built-in/EDM/keyword/regex*** *type, not a named-entity SIT (not available).* ***Adaptive Protection*** *(risk-based DLP) is* ***rolling out to Gov clouds*** *— if you plan to gate DLP actions on Insider Risk levels,* ***verify Adaptive Protection is present in your tenant first*** *(`gcc-high-parity-notes.md` §5).*

Step 3.2 — Tune, then enforce

1. Let the policy run in **test/audit** for the pilot window. Review matches in **Data Loss Prevention → Alerts **and** Activity Explorer **(**Available** in GCC High).

1. Tune conditions to reduce false positives.

2. Only after the pilot gate passes, edit `DLP-CUI-Baseline`, add **Block** / **Restrict** actions (with user override + justification if appropriate), and switch mode to **On**. Expand scope group-by-group.

Gate: DLP matches are accurate in audit; enforcement change goes through change control (G8) before any block is enabled.

Phase 4 — Retention & records

Step 4.1 — Org-wide baseline retention policy

1. **Data Lifecycle Management** → **Retention policies** → **+ New retention policy**.
2. **Name** `RP-Baseline-Retain`. **Locations:** Exchange email, SharePoint, OneDrive, Microsoft 365 Groups, **Teams chat / channel / meeting recordings** (all **Available** in GCC High).
1. Set retain-then-delete for your baseline period. **Adaptive scopes** (Available) can target by attribute if needed.

Step 4.2 — Retention label for CUI

1. **Data Lifecycle Management** → **Retention labels** → **+ Create a label**.
2. **Name** `Ret-CUI-7yr`. Set **Retain items for 7 years**, then choose the end-of-period behavior.

> ***GCC High note: "Apply retention *label* action at end of retention period"** is **not available** (*on engineering backlog*). For the end-of-life step, use a supported behavior (retain-then-delete, or start a disposition review) rather than a label-action-at-end-of-period. (`gcc-high-parity-notes.md` §4.)*

1. To make it a **record**, enable **Mark items as a record** (records management is **Available**). Use **Preservation Lock** (Available) where immutability is required.

Step 4.3 — Auto-apply the retention label

1. **Retention labels** → `Ret-CUI-7yr` → **Auto-apply** (or **Label policies** → **Auto-apply a label**).
2. **Name the policy** `RP-CUI-7yr-Auto`. Condition: content contains your **GA SITs/EDM/keywords**.

> ***GCC High note: auto-applying record policies *with trainable classifiers** is **not available** (*in development*). Use **condition-based** (keyword/SIT/EDM) or **event-based** auto-apply for records, which **is** available.*

1. Scope to `SG-Purview-Pilot` where supported; publish.

Step 4.4 — Disposition / file plan (records)

1. **Records Management** → **File plan** — import/define record categories; **File plan manager**, **regulatory records**, **proof of disposal**, and **disposition review** are **Available**.
1. **Multi-stage disposition review** is **Rolling out** — verify it is present before relying on it.

> ***GCC High note: Records Management Power Automate integration** and **Records Management Graph APIs** are **not available** (*backlog / in development*). Do not build record automations on Power Automate/Graph for records yet.*

Gate: retention/records applied to pilot content as expected; disposition review reachable for records.

Phase 5 — Pilot → Validate → Expand

1. **Pilot** is already scoped to `SG-Purview-Pilot` across labels, DLP (audit), and retention.
2. **Validate** using the pass/fail gates in `05-testing.md`. Run `PURVIEWG-Validation.ps1` and `PURVIEWG-Report.ps1` (US Gov Graph) to confirm coverage.
1. **Expand** only after gates pass: widen the label policy and DLP scope group-by-group (use `PURVIEWG-Set-ScopeTargeting.ps1`, which defaults to `-WhatIf`), and flip DLP from audit to enforce under change control.

The deployment model (all solutions): Assess → Configure → Pilot → Validate → Expand.

> ***Sources:*** *Microsoft Learn — *Plan for Microsoft Purview — GCC High deployments* (parity table); *Microsoft Purview service description*; *Adaptive Protection* docs. Portals:* `portal.office365.us`, `compliance.microsoft.us/purview.microsoft.us`, `security.microsoft.us`, `entra.microsoft.us`, `login.microsoftonline.us`. *Full citations in* `gcc-high-parity-notes.md`.

Testing — Purview DLP, Labels & Retention (Government / GCC High)

Run these gates against the **pilot** (`SG-Purview-Pilot`) before expanding. Each gate has an explicit **PASS / FAIL** condition. A FAIL sends you to `06-troubleshooting.md`; do not expand scope or enable enforcement until every applicable gate is **PASS**. Portals are the GCC High `.us` hosts; scripts connect with `Connect-MgGraph -Environment USGov`.

Gate 0 — Sovereign-cloud sanity (must pass first)

• **Test:** In a browser, load `https://compliance.microsoft.us`; run `PURVIEWG-Discovery.ps1` and confirm it connected to the **US Gov** Graph endpoint.

• **PASS:** Portal loads at a `.us` host; script reports environment `USGov` / `graph.microsoft.us`.

• **FAIL:** Any portal or script resolves to a `.com` host → you are targeting Commercial; stop and fix endpoint/environment before any other test.

Gate 1 — Licensing & roles present

• **Test:** `portal.office365.us` → `Billing` → `Licenses` shows G3/G5 (+ G5 Compliance/IP&G);

`compliance.microsoft.us` → `Settings` → `Roles & scopes` → `Permissions` shows the operator in **Compliance Administrator** and **Information Protection**.

- **PASS:** Both present. **FAIL:** Missing SKU or role → cannot author the corresponding feature.

Gate 2 — Parity check completed

- **Test:** For every feature this deployment uses, `gcc-high-parity-notes.md` status is **Available** and the option is visible in `compliance.microsoft.us`.
- **PASS:** Every needed feature is Available and visible. **FAIL:** A needed feature is *in development / backlog* (e.g. named-entity SIT, mobile auto-label, classifier-based record label) → substitute the GA alternative before continuing.

Gate 3 — Labels published and visible

- **Test:** A pilot user opens Word/Excel/PowerPoint/Outlook and checks the **Sensitivity** control.
- **PASS:** `Public`, `General`, `Confidential`, `Confidential \ CUI` all appear; `General` is the default; removing/lowering a label prompts for justification.
- **FAIL:** Labels missing after replication time → check `LP-Purview-Pilot` assignment to `SG-Purview-Pilot`; see troubleshooting.

Gate 4 — Manual + mandatory labeling works

- **Test:** Pilot user saves a new document without a label.
- **PASS:** Mandatory labeling prompts for a label before save/send; applying `Confidential \ CUI` encrypts and marks the file per its config.
- **FAIL:** No prompt, or encryption/marking absent → verify label protection settings and policy mandatory-labeling toggle.

Gate 5 — Service-side auto-labeling simulation is accurate

- **Test:** `AL-CUI-ServiceSide` runs in **simulation**; review matched items.
- **PASS:** Expected CUI content matches; false-positive rate acceptable; no unexpected mass match.
- **FAIL:** Over/under-matching → tune conditions (GA SITs/EDM/keywords only) and re-simulate.

Confirm you did **not** use a named-entity SIT (not available in GCC High).

Gate 6 — DLP detects in audit (no block yet)

- **Test:** Pilot user triggers a match for `DLP-CUI-Baseline` / `DLP-CUI-Baseline-Rule1` (e.g. emails/shares test CUI content). Check **DLP** → **Alerts** and **Activity Explorer**.
- **PASS:** The event is detected and recorded in audit; **no user was blocked** (policy still in

test mode).

• **FAIL:** No detection → verify conditions, locations, and that the policy is scoped to the pilot; confirm SIT types are GA in GCC High.

Gate 7 — Endpoint DLP (only if in scope)

• **Test:** On an **onboarded** device, a pilot user attempts a monitored action (copy CUI to USB / print / cloud upload).

• **PASS:** The action is recorded in audit for onboarded devices.

• **FAIL:** Nothing recorded → confirm the device is onboarded (`Settings → Device onboarding`) and device location is enabled in the policy.

Gate 8 — DLP enforcement (post-tuning, change-controlled)

• **Test:** After audit tuning and change-control approval, enable **Block/Restrict** on `DLP-CUI-Baseline` and re-test the same action.

• **PASS:** Action is blocked/restricted with the expected policy tip; override/justification behaves as configured.

• **FAIL:** Not blocked, or blocks legitimate work → revert to audit, retune, re-approve.

Gate 9 — Retention applied

• **Test:** Confirm `RP-Baseline-Retain` covers the intended locations; confirm `Ret-CUI-7yr` (via `RP-CUI-7yr-Auto`) applies to matching pilot content.

• **PASS:** Retention label present on matching items; org-wide policy active; end-of-period behavior is a **supported** action (not the unavailable "apply label action at end of period").

• **FAIL:** Label not applied → verify auto-apply conditions are GA SITs/EDM/keywords (not classifier-based for records) and scope.

Gate 10 — Records & disposition (only if records in scope)

• **Test:** Declare a test item a record via `Ret-CUI-7yr`; open **Records Management** → **Disposition**.

• **PASS:** Item is a record (locked as configured); disposition review is reachable; proof of disposal available.

• **FAIL:** Record behavior missing → confirm records management is licensed (G5) and the label's "mark as record" is set; multi-stage review is *rolling out* — verify presence.

Gate 11 — Script validation clean

• **Test:** Run `PURVIEWG-Validation.ps1` and `PURVIEWG-Report.ps1` (US Gov Graph).

• **PASS:** Validation reports labels/DLP/retention present and scoped as designed; report lists coverage with no unexpected gaps.

• **FAIL:** Reported gaps → remediate (see `PURVIEWG-Remediation.ps1`, which defaults to `-WhatIf`) and re-run.

Expansion gate: proceed from Pilot to Expand **only** when Gates 0–6 and 9 are PASS (plus 7/8/10 where in scope) and any DLP enforcement change has change-control approval.

The deployment model (all solutions): Assess → Configure → Pilot → Validate → Expand.

Troubleshooting — Purview DLP, Labels & Retention (Government / GCC High)

Work top-down. The first section covers the failures that are **unique to GCC High** — check these before generic Purview troubleshooting, because in GCC High "it's not there" is often a **parity gap**, not a misconfiguration.

A. GCC-High-specific gotchas

A1. A menu/option/feature simply isn't there

Symptom: A step in a Commercial guide references a menu, toggle, SIT, or classifier that does not exist in your portal. **Likely cause:** It is a **GCC High parity gap** — the feature is *in development* or *on the engineering backlog*, i.e. **not available** in GCC High. **Check / fix:** Open `gcc-high-parity-notes.md` and confirm the feature's status. Common ones: **named-entity SITs** (not available), **Office *mobile* auto-labeling** (not available), **default label on SharePoint upload / on documents being edited** (not available), **auto-apply records with trainable classifiers** (not available), **retention label action at end of period** (not available), **records Power Automate / Graph APIs** (not available), **Microsoft Priva** (not available). Use the GA alternative documented in `03-implementation.md`. Do **not** file a support case for a backlog feature.

A2. Wrong cloud — portal or script hit a `.com` host

Symptom: Sign-in loops, "tenant not found", empty portal, or a script authenticates but sees no Purview objects. **Likely cause:** You reached the **Commercial** cloud (`compliance.microsoft.com`, `login.microsoftonline.com`, or `Connect-MgGraph -Environment Global`) instead of GCC High. **Fix:** Use the `.us` hosts only — `login.microsoftonline.us`, `compliance.microsoft.us` (→ `purview.microsoft.us`), `security.microsoft.us`, `entra.microsoft.us`, `portal.office365.us`. In scripts, connect with `Connect-MgGraph -Environment USGov` (DoD: `USGovDoD`). Verify with `(Get-MgContext).Environment` = `USGov`. Run `PURVIEWG-Discovery.ps1`, which reports the environment.

A3. Endpoint blocked by filtering

Symptom: Portal will not load, or the labeling client / endpoint DLP / scripts cannot reach the service, on-network only. **Likely cause:** Proxy/firewall allows the **Commercial** Office 365 endpoint list but not the **Office 365 U.S. Government GCC High** list (the `.us` sovereign hosts are a separate published set). **Fix:** Allow the GCC High URL/IP ranges (portals, `graph.microsoft.us`, `login.microsoftonline.us`, the Security & Compliance PowerShell Gov URI, endpoint-DLP and labeling client endpoints). Re-test R6 reachability from an on-network workstation.

A4. Security & Compliance PowerShell won't connect

Symptom: `Connect-IPPSSession` fails or connects to the wrong org. **Fix:** Use the GCC High connection: `Connect-IPPSSession -ConnectionUri https://ps.compliance.protection.office365.us/powershell-liveid/ -ExchangeEnvironmentName O365USGovGCCHigh` (per Microsoft "Connect to Security & Compliance PowerShell"). The Graph-SDK scripts in this solution use `-Environment USGov`; cmdlet-based label/DLP work uses the URI above.

A5. Trainable classifier not selectable

Symptom: A pre-trained classifier you expected is missing when authoring an auto-label/retention condition. **Likely cause:** In GCC High, trainable classifiers are **Available for client-side sensitivity auto-labeling** but **not** for auto-applying **records** labels (*in development*); individual classifier availability can also lag. **Fix:** For records auto-apply, use **condition-based** (keyword/SIT/EDM) or **event-based** rules. For sensitivity auto-labeling, confirm the specific classifier is listed before designing on it — **verify for GCC High** if unsure.

A6. Adaptive Protection options missing

Symptom: Risk-based DLP (Insider Risk levels as a DLP condition) not available. **Likely cause:** Adaptive Protection is **rolling out to Gov clouds** (GCC/GCC High/DoD) — it may not yet be enabled in your tenant. **Fix:** Verify presence in `compliance.microsoft.us` (Insider Risk Management → Adaptive Protection); if absent, do not design DLP on it yet. Ship standard DLP and add Adaptive Protection when it lands.

B. Labels not appearing for users

- **Cause:** `LP-Purview-Pilot` not assigned to `SG-Purview-Pilot`, or replication delay.
- **Fix:** `compliance.microsoft.us → Information Protection → Label policies` — confirm the policy

targets `SG-Purview-Pilot` and includes all four labels. Allow up to a few hours; have the user restart the Office app / sign out and in. Confirm the user has a G3/G5 license (R2).

C. Mandatory labeling / justification not enforced

- **Cause:** Policy toggles off, or the client is older than the setting supports.
- **Fix:** In `LP-Purview-Pilot`, confirm **Require users to apply a label** and **Require

justification to remove/lower** are on. Ensure supported, current Office builds (G6).

D. Auto-labeling not matching (or over-matching)

• **Cause:** Conditions use a non-GA SIT (named-entity — not available), or thresholds too broad/narrow; policy still in simulation.

• **Fix:** Rebuild conditions from **built-in SITs / EDM / keyword / regex**. Re-run **simulation** on `AL-CUI-ServiceSide`; review matches; tune; only then turn On. Remember mobile-client auto-labeling is not available in GCC High.

E. DLP not detecting

• **Cause:** Wrong locations, policy scoped away from the pilot, non-GA SIT, or (for devices) unonboarded endpoints.

• **Fix:** Confirm `DLP-CUI-Baseline` locations (EXO/SPO/OneDrive/Teams/Devices) and that `DLP-CUI-Baseline-Rule1` conditions are GA SITs/EDM/keywords or the `Confidential \ CUI` label. For Endpoint DLP, confirm devices are onboarded (`Settings → Device onboarding`, R7). Check **DLP → Alerts** and **Activity Explorer**.

F. DLP blocking legitimate work

• **Cause:** Enforcement enabled before audit tuning, or conditions too broad.

• **Fix:** Set `DLP-CUI-Baseline` back to **test/audit**, retune to cut false positives, get change-control approval, then re-enable Block/Restrict with user override/justification.

G. Retention not applying / wrong end-of-life behavior

• **Cause:** Auto-apply conditions non-GA (classifier-based for records — not available), scope mismatch, or an attempt to use "apply label action at end of period" (not available in GCC High).

• **Fix:** Use condition/event-based auto-apply for `RP-CUI-7yr-Auto`; set a **supported** end-of-period behavior (retain-then-delete or disposition review). Confirm `RP-Baseline-Retain` locations.

H. Records / disposition not working

• **Cause:** Records management not licensed (needs G5), "Mark as record" not set, or reliance on a *rolling-out* feature (multi-stage disposition review) or an unavailable one (records Power Automate / Graph).

• **Fix:** Confirm G5; enable **Mark items as a record** on `Ret-CUI-7yr`; verify multi-stage review presence before relying on it; do not automate records via Power Automate/Graph in GCC High yet.

I. Scripts fail or report nothing

• **Cause:** Connected to Commercial Graph, missing scopes, or insufficient role.

• **Fix:** Reconnect with `Connect-MgGraph -Environment USGov` and the scopes listed in each

script's **HOW TO RUN** header; confirm the operator's Purview roles (R3). Run `PURVIEWG-Discovery.ps1` first to confirm the environment and connectivity.

When in doubt about a GCC High specific: re-open the Microsoft *Plan for Microsoft Purview — GCC High deployments* page and the Microsoft 365 Roadmap filtered to **GCC High**, and re-confirm the feature status before troubleshooting further. Never assume Commercial behavior carries over.

The deployment model (all solutions): Assess → Configure → Pilot → Validate → Expand.

Best Practices — Purview DLP, Labels & Retention (Government / GCC High)

Field-proven guidance for the **assign-once, repeat-everywhere** model on a **GCC High** tenant.

Sovereign-cloud discipline (GCC High)

- **Bookmark the `.us` portals and never the `.com` ones.** Sign in at `login.microsoftonline.us`;

administer at `compliance.microsoft.us` (→ `purview.microsoft.us`), `security.microsoft.us`, `entra.microsoft.us`, `portal.office365.us`. A Commercial URL in a GCC High runbook is a defect.

- **Every script targets US Gov Graph** — `Connect-MgGraph -Environment USGov` (never `Global`).

Bake this into the header of every runbook so no one connects to the wrong cloud.

- **Treat "the option isn't there" as a parity gap, not a bug.** Before opening a support case,

check `gcc-high-parity-notes.md` — if the feature is *in development / on backlog*, it genuinely is not present, and the fix is to use the GA alternative, not to troubleshoot.

- **Re-verify parity before each design.** Microsoft ships to GCC High continuously; a feature on

the backlog last quarter may be GA now (and vice-versa). The live *Plan for Microsoft Purview — GCC High deployments* page is the source of truth.

Taxonomy & labels

- **Keep the taxonomy short** — four or five labels (`Public`, `General`, `Confidential`,

`Confidential \ CUI`) beat a sprawling tree nobody applies correctly. Get **data-owner sign-off** on what each label *means* before publishing.

- **Name every object verbatim and reuse it** — `LP-Purview-Pilot`, `AL-CUI-ServiceSide`,

`DLP-CUI-Baseline`, `Ret-CUI-7yr`. Consistent names make the scripts, reports, and handover legible.

- **Use the label as the currency:** make `Confidential \ CUI` a **DLP condition** and a

retention/auto-apply condition so one classification drives protection *and* retention — "label once, enforce everywhere."

- **Prefer GA classification building blocks** — built-in SITs, **Exact Data Match**, keyword

dictionaries, regex. **Do not design on named-entity SITs** (not available in GCC High). Trainable classifiers are fine for **client-side sensitivity auto-labeling**, but **not** for auto-applying *records* labels in GCC High.

DLP

- **Always audit before you enforce.** Ship every DLP policy in **test/audit** mode, tune out false positives against the pilot, and only then add **Block/Restrict** — under change control (G8).
- **Scope to the pilot group first**, expand group-by-group. A tenant-wide block on day one is how you take users offline.
- **Turn on policy tips and clear user justification** so users self-correct instead of filing tickets.
- **Endpoint DLP only covers onboarded devices** — reconcile onboarding coverage before claiming device protection.
- **Adaptive Protection** (risk-based DLP) is **rolling out to Gov clouds** — adopt it only after confirming it is present in your tenant; do not assume it from Commercial docs.

Retention & records

- **Separate baseline retention from targeted retention:** an org-wide `RP-Baseline-Retain` for the floor, plus targeted `Ret-CUI-7yr` for regulated content.
- **Use adaptive scopes** (Available) to target by attribute instead of hand-maintaining locations.
- **Records need immutability:** enable **Mark as record** and **Preservation Lock** where the schedule must be defensible — but remember Preservation Lock cannot be undone.
- **Plan end-of-life around GA behavior:** "apply retention *label* action at end of period" is **not available** in GCC High — use retain-then-delete or disposition review instead.
- **Don't build record automations on Power Automate/Graph** yet — records Power Automate and records Graph APIs are **not available** in GCC High.

Operations

- **Run the read-only scripts on a schedule** — `PURVIEWG-Discovery.ps1`, `PURVIEWG-Validation.ps1`, `PURVIEWG-Report.ps1` — to catch drift (an unscoped label, a disabled DLP rule, missing retention).
- **Keep change-tools in `-WhatIf` by default** — `PURVIEWG-Remediation.ps1` and `PURVIEWG-Set-ScopeTargeting.ps1` preview first; only run with `-Execute`/`-WhatIf:$false` after review and approval.

• **Every enforcement change is a change ticket** — approver, maintenance window, named pilot, documented rollback (per `global-requirements-security.md` G8).

• **Least privilege:** author with **Compliance Administrator** + **Information Protection** role groups, not Global Administrator.

The deployment model (all solutions): Assess → Configure → Pilot → Validate → Expand.

Deliverables Summary — Purview DLP, Labels & Retention (Government / GCC High)

This solution deploys Microsoft Purview **sensitivity labels + auto-labeling**, **DLP**, and **retention + records** on a **US sovereign-cloud (GCC High)** tenant, correctly — right portals, right endpoints, and Commercial-vs-GCC-High parity gaps handled — proven on a pilot before scale.

Documents

File	Purpose
`01-solution-overview.md`	The Purview model on GCC High; how the sovereign cloud differs (portals, endpoints, parity); the Assess→Configure→Pilot→Validate→Expand model. Includes a **Commercial vs GCC High** subsection.
`02-requirements.md`	Each prerequisite as **Description / Why / Verify / Implement-if-missing** — GCC High tenant, Gov G3/G5 licensing, Purview roles, `compliance.microsoft.us` access, endpoint allow-list, parity confirmation.
`03-implementation.md`	Exact ordered steps in the GCC High portals: labels + label policy, service-side auto-labeling, DLP (audit→enforce), retention + records — with GCC-High URLs and parity caveats inline where they matter.
`05-testing.md`	Pass/fail gates from sovereign-cloud sanity through enforcement and script validation.
`06-troubleshooting.md`	GCC-High-specific gotchas (feature not present, endpoint blocked, wrong portal/cloud) plus common failures.
`07-best-practices.md`	The assign-once, repeat-everywhere model, tuned for GCC High.
`gcc-high-parity-notes.md`	Reference: per-feature Commercial-vs-GCC-High status with Microsoft citations or explicit "verify for GCC High" flags.
`global-requirements-security.md`	Category-level prerequisites shared by all security solutions.

File	Purpose
`executive-summary.md`	One-page summary for decision-makers.

Scripts (PowerShell, Microsoft Graph SDK, US Gov endpoints)

All scripts connect with `Connect-MgGraph -Environment USGov` for GCC High. Read-only tools are read-only; change tools default to `-WhatIf`.

Script	Role	Default
`PURVIEWG-Discovery.ps1`	Inventory labels, label policies, DLP policies, retention/records config in the GCC High tenant.	Read-only
`PURVIEWG-Validation.ps1`	Check that the named objects exist and are scoped as designed; flag gaps.	Read-only
`PURVIEWG-Report.ps1`	Coverage / classification / DLP-event report for review.	Read-only
`PURVIEWG-Remediation.ps1`	Safely remediate detected gaps.	`-WhatIf`
`PURVIEWG-Set-ScopeTargeting.ps1`	Build/adjust the protection-scope group (`SG-Purview-Pilot`) membership and policy targeting for staged expansion.	`-WhatIf`

Named objects (created and reused verbatim)

`SG-Purview-Pilot` · labels `Public`, `General`, `Confidential`, `Confidential \ CUI` · label policy `LP-Purview-Pilot` · auto-labeling `AL-CUI-ServiceSide` · DLP `DLP-CUI-Baseline` / `DLP-CUI-Baseline-Rule1` · retention `Ret-CUI-7yr`, policies `RP-CUI-7yr-Auto`, `RP-Baseline-Retain`.

Outcome

A GCC High tenant with a small, owner-approved label taxonomy driving **classification**, **DLP** (audited then enforced), and **retention/records** — with every parity gap either handled by a GA alternative or explicitly flagged for verification, and read-only scripts to detect drift.

The deployment model (all solutions): Assess → Configure → Pilot → Validate → Expand.

Appendix A — PowerShell Scripts

Included in the accompanying ZIP. Each script's header documents full usage.

PURVIEWG-Discovery.ps1

Purpose: Connects to the US Gov Microsoft Graph endpoint for a GCC High tenant and inventories the Microsoft Purview posture: sensitivity labels, label policies, DLP-relevant configuration, and retention/records signals it can read. Confirms you are in the USGov cloud, then prints what exists so you can compare against the designed object names. Read-only — it changes nothing. Replace the sample group name your-pilot-group-name if you use a different pilot group. HOW TO RUN powershell -ExecutionPolicy Bypass -File .\PURVIEWG-Discovery.ps1

How to run: powershell -ExecutionPolicy Bypass -File .\PURVIEWG-Discovery.ps1

PURVIEWG-Remediation.ps1

Purpose: Remediates the specific, safe gaps this solution can fix on a GCC High tenant: creating the pilot group if it is missing, and confirming/normalizing the pilot-scope targeting of the label policy. It DEFAULTS TO -WhatIf (preview only) and makes no change until you re-run with -WhatIf:$false. It never enables DLP enforcement, never publishes labels tenant-wide, and never deletes anything — those are change-controlled human actions. Replace the default names only if your objects are named differently. HOW TO RUN Preview (default, no changes): powershell -ExecutionPolicy Bypass -File .\PURVIEWG-Remediation.ps1 Apply (after review + change approval): powershell -ExecutionPolicy Bypass -File .\PURVIEWG-Remediation.ps1 -WhatIf:$false

How to run: Preview (default, no changes): powershell -ExecutionPolicy Bypass -File .\PURVIEWG-Remediation.ps1 Apply (after review + change approval): powershell -ExecutionPolicy Bypass -File .\PURVIEWG-Remediation.ps1 -WhatIf:$false

PURVIEWG-Report.ps1

Purpose: Generates a review-friendly report of the Purview posture on a GCC High tenant: the sensitivity labels in the taxonomy, the designed policy objects and whether each is present, and pointers to the classification and DLP-event data an admin should review before expanding. Read-only — it collects and prints, it never changes configuration. Writes an optional CSV summary to the path you pass in OutputCsv. HOW TO RUN powershell -ExecutionPolicy Bypass -File .\PURVIEWG-Report.ps1 powershell -ExecutionPolicy Bypass -File .\PURVIEWG-Report.ps1 -OutputCsv .\purviewg-report.csv

How to run: powershell -ExecutionPolicy Bypass -File .\PURVIEWG-Report.ps1 powershell -ExecutionPolicy Bypass -File .\PURVIEWG-Report.ps1 -OutputCsv .\purviewg-report.csv

PURVIEWG-Set-ScopeTargeting.ps1

Purpose: Manages membership of the protection-scope group (SG-Purview-Pilot by default) so you can stage a Purview rollout from pilot to production a batch at a time. It adds the users or groups you pass in AddMembers to the scope group. It DEFAULTS TO -WhatIf (preview only) and changes nothing until you re-run with -WhatIf:$false. It does not remove members and does not retarget policies directly — expansion stays deliberate and reversible. Pass member object ids or user principal names such as pilot-user@your-agency.gov (no angle brackets). HOW TO RUN Preview (default): powershell

-ExecutionPolicy Bypass -File .\PURVIEWG-Set-ScopeTargeting.ps1 -AddMembers user1@your-agency.gov,user2@your-agency.gov Apply (after review + change approval): powershell -ExecutionPolicy Bypass -File .\PURVIEWG-Set-ScopeTargeting.ps1 -AddMembers user1@your-agency.gov -WhatIf:$false

How to run: Preview (default): powershell -ExecutionPolicy Bypass -File .\PURVIEWG-Set-ScopeTargeting.ps1 -AddMembers user1@your-agency.gov,user2@your-agency.gov Apply (after review + change approval): powershell -ExecutionPolicy Bypass -File .\PURVIEWG-Set-ScopeTargeting.ps1 -AddMembers user1@your-agency.gov -WhatIf:$false

PURVIEWG-Validation.ps1

Purpose: Checks a GCC High tenant for the specific, named Purview objects this solution creates and reports PASS or FAIL for each: the pilot group, the four sensitivity labels, the label policy, the auto-labeling policy, the DLP policy, and the retention labels/policies. It does not change anything. Use it as the pilot validation gate before expanding scope. Replace the default names only if you named your objects differently. HOW TO RUN powershell -ExecutionPolicy Bypass -File .\PURVIEWG-Validation.ps1

How to run: powershell -ExecutionPolicy Bypass -File .\PURVIEWG-Validation.ps1