Hybrid Identity with Active Directory & Microsoft Entra Connect

Implementation Solution Guide

Version 1.0.0 · 2026-06-28

Contents

Executive Summary — Hybrid Identity with Active Directory & Microsoft Entra Connect 4
- What you get . . . 4
- What this delivers . . . 4
- The deployment model . . . 4
- Outcome . . . 4

1. Solution Overview — Hybrid Identity with Active Directory & Microsoft Entra Connect 5
- What hybrid identity is . . . 5
- How it works . . . 5
- Connect Sync vs. Cloud Sync (which engine) . . . 5
- Authentication methods (choose one primary) . . . 5
- What you can control . . . 6
- Benefits . . . 6
- Limitations (be honest with buyers) . . . 6
- Why this matters (the why lives here) . . . 6
- The standard deployment model . . . 7

2. Requirements Guide — Hybrid Identity with Active Directory & Microsoft Entra Connect 7
- 2.1 Entra ID licensing . . . 7
- 2.2 Entra Connect host server . . . 7
- 2.3 Healthy Active Directory . . . 7
- 2.4 UPN and domain hygiene . . . 7
- 2.5 Authentication method decision . . . 8
- 2.6 Administrative roles . . . 8
- 2.7 Break-glass accounts . . . 8
- 2.8 Pilot scope group . . . 8
- 2.9 Network access . . . 8
- Checklist . . . 8

3. Implementation Guide — Hybrid Identity with Active Directory & Microsoft Entra Connect 9
- Step 1 — Prepare AD and the pilot scope . . . 9
- Step 2 — Verify the public domain in Entra . . . 9
- Step 3 — Install Microsoft Entra Connect on the host . . . 9
- Step 4 — Choose the authentication method (in the wizard) . . . 10
- Step 5 — Connect to Entra ID and AD . . . 10
- Step 6 — Scope the synchronization . . . 10
- Step 7 — Optional features, then stage the first sync . . . 10
- Step 8 — Take the server out of staging mode (go live for the pilot) . . . 10

Step 9 — Enable Seamless SSO and confirm the auth method . . . 11
Step 10 — Enable hybrid Entra join (devices) . . . 11
Step 11 — Validate the pilot . . . 11
Step 12 — Expand to production . . . 11
5. Testing Guide — Hybrid Identity with Active Directory & Microsoft Entra Connect 12
Test 1 — Sync engine healthy and running . . . 12
Test 2 — Pilot objects synchronized . . . 12
Test 3 — No sync errors / no duplicates . . . 12
Test 4 — Authentication method works . . . 12
Test 5 — Password writeback (if enabled) . . . 12
Test 6 — Hybrid Entra join . . . 12
Test 7 — Staging-mode failover rehearsal (optional) . . . 12
Pass/fail gate . . . 13
6. Troubleshooting Guide — Hybrid Identity with Active Directory & Microsoft Entra Connect 13
A. Synchronization not running / stalled . . . 13
B. Duplicate or merged accounts / sync errors . . . 13
C. Sign-in failures . . . 14
D. Hybrid Entra join not completing . . . 14
E. Accidental-deletion safeguard tripped . . . 14
F. Diagnostics quick reference . . . 14
G. When to escalate . . . 15
7. Best Practices — Hybrid Identity with Active Directory & Microsoft Entra Connect 15
8. Deliverables Summary — Hybrid Identity with Active Directory & Microsoft Entra Connect 16
Documentation . . . 16
PowerShell scripts . . . 16
What the buyer receives . . . 16
Outcome . . . 16
Appendix A — PowerShell Scripts 17

Executive Summary — Hybrid Identity with Active Directory & Microsoft Entra Connect

Workplace Marketplace · Entra ID Solutions

Most organizations still run Active Directory on-premises while their apps, devices, and security live in the cloud. When the bridge between them is misconfigured you get duplicate accounts, broken sign-ins, and devices that will not join. This solution establishes solid hybrid identity with Active Directory and Microsoft Entra Connect: reliable synchronization, the right authentication method, hybrid Entra join, and the health monitoring to keep it that way.

This is a complete, deploy-it-today package for implementing hybrid identity, written for an administrator with no prior identity-integration experience — and it treats the identity plane as the high-risk surface it is.

What you get

- A plain-language Solution Overview of synchronization, Connect Sync vs. Cloud Sync, the three

authentication methods (password hash sync, pass-through authentication, federation), Seamless SSO, and hybrid Entra join.

- A Requirements Guide with verify / implement-if-missing for every prerequisite.
- An Implementation Guide of precise, click-to-implement steps in the required order.
- Five PowerShell scripts for readiness discovery, sync and sign-in validation, sync-health and

object-coverage reporting, safe remediation of sync errors and duplicates, and a sync-scope helper.

- Testing and Troubleshooting guides for a confident, staged rollout.

What this delivers

A clean, reliable hybrid identity: Microsoft Entra Connect synchronizing a scoped set of AD objects, the right authentication method (password hash sync recommended, with PTA or federation where required and PHS as a backup), Seamless SSO for corporate-network users, hybrid Entra join for domain-joined Windows devices, and ongoing synchronization-health monitoring.

The deployment model

Assess -> Configure -> Pilot -> Validate -> Expand — rehearsed in staging mode, with break-glass accounts ready throughout.

Outcome

One reliable identity spanning Active Directory and Entra ID — synchronized cleanly, authenticated by the right method, with hybrid join and healthy sync — deployable by a single administrator and validated on a pilot before fleet rollout.

1. Solution Overview — Hybrid Identity with Active Directory & Microsoft Entra Connect

What hybrid identity is

Most organizations keep user accounts in on-premises Active Directory (AD) while their apps, devices, and security live in Microsoft Entra ID (the cloud directory). Hybrid identity is the bridge between the two: a synchronization engine copies AD users, groups, and contacts into Entra ID, and an authentication method decides where the password is actually checked. Done well, a user has one identity and one password that works on-premises and in the cloud. Done badly, you get duplicate accounts, broken sign-ins, and devices that will not join.

How it works

1. Microsoft Entra Connect runs on a host server and synchronizes objects from AD to Entra ID on a schedule (every 30 minutes by default).

1. A synchronization scope (domain and organizational-unit filters) decides which AD objects are in scope, so test or service objects stay out of the cloud.

1. An authentication method decides how sign-in is validated: password hash sync (PHS), pass-through authentication (PTA), or federation.

1. Seamless single sign-on (Seamless SSO) lets domain-joined users on the corporate network sign in to cloud apps without re-typing a password.

1. Hybrid Entra join registers domain-joined Windows devices into Entra ID so they satisfy Conditional Access and cloud device management.

1. Synchronization health and sign-in are monitored so a stalled sync or an auth-method fault is caught before users feel it.

Connect Sync vs. Cloud Sync (which engine)

• Entra Connect Sync is the full-featured engine: complex filtering, device writeback, password writeback, and large or multi-forest environments. It runs on a dedicated server.

• Entra Cloud Sync uses a lightweight agent and the cloud does the heavy lifting; it suits simpler or disconnected-forest scenarios and multiple small domains, with fewer advanced options.

• This solution implements Connect Sync as the primary path because it covers hybrid join and writeback; Cloud Sync is noted where it is the better fit.

Authentication methods (choose one primary)

• Password hash sync (PHS) synchronizes a (hashed, salted) representation of the password so Entra

ID validates sign-in itself. Simplest and most resilient — the cloud keeps working if the on-premises servers are down. Recommended default.

• Pass-through authentication (PTA) validates the password against AD in real time via lightweight agents, so no password representation leaves the network. Requires the agents (and AD) to be available for cloud sign-in.

• Federation (AD FS) hands authentication to an on-premises federation farm. Most complex and highest-maintenance; choose it only for a specific requirement (for example a third-party MFA at the federation layer or strict on-premises sign-in control).

• PHS is recommended as a backup even when PTA or federation is primary, so cloud sign-in survives an on-premises outage.

What you can control

• Which AD objects synchronize (sync scope, OU and domain filters).

• The authentication method (PHS, PTA, or federation) and whether Seamless SSO is on.

• Password writeback (self-service password reset writing back to AD) and other writeback options.

• Hybrid Entra join for domain-joined Windows devices.

• The synchronization schedule and staging-mode (a parallel, no-export rehearsal server).

Benefits

• One identity — the same account and password on-premises and in the cloud.

• Reliable sign-in — the right authentication method with PHS resilience as a safety net.

• Devices that just work — hybrid Entra join satisfies Conditional Access and cloud management.

• Clean directory — scoped sync and UPN hygiene prevent duplicate and orphaned accounts.

• Visibility — sync health and object coverage are monitored and reportable.

Limitations (be honest with buyers)

• Synchronization is one-way for most attributes (AD to Entra ID); AD stays the source of truth.

• A misconfigured sync scope or duplicate UPN/proxyAddress causes sync errors and merged or split accounts; UPN/domain hygiene is a prerequisite, not an afterthought.

• Federation is a significant ongoing commitment (certificates, the AD FS farm, its own outage surface); prefer PHS or PTA unless a requirement forces federation.

• One active sync server exports at a time; a second server runs in staging mode for failover.

Why this matters (the why lives here)

The identity plane underpins every other security and management control — Conditional Access, MFA, device compliance, and app access all read from it. That is exactly why this solution treats it as high risk: changes are rehearsed in staging mode, rolled out to a pilot group first, validated, and only then expanded, with break-glass accounts ready throughout. The remaining guides are click-to-implement and avoid re-explaining the why.

The standard deployment model

> *Prepare AD and domains -> install and configure Entra Connect -> choose and enable the authentication method -> scope synchronization -> enable hybrid Entra join -> validate sign-in and sync health, on a pilot first. The repeatable way: Assess -> Configure -> Pilot -> Validate -> Expand.*

2. Requirements Guide — Hybrid Identity with Active Directory & Microsoft Entra Connect

Verify every requirement before configuring. Each entry: Description / Why / Verify / Implement-if-missing. Category-wide prerequisites are in `global-requirements-entra-id-solutions.md`.

2.1 Entra ID licensing

Description: Microsoft Entra ID P1 (P2 if you also want risk-based sign-in or PIM). Why: Hybrid features (Seamless SSO, password writeback, Conditional Access for hybrid join) need P1+. Verify: M365 admin center -> `Billing -> Licenses`. Implement: Assign M365 E3/E5, EMS, or standalone Entra ID P1/P2.

2.2 Entra Connect host server

Description: A dedicated, patched, domain-joined Windows Server 2016 or later for Connect Sync. Why: The sync engine runs as a service here and must reach AD and Entra ID over HTTPS. Verify: Server is domain-joined, patched, TLS 1.2 enabled; run `HYBID-Discovery.ps1`. Implement: Provision a server (not a production domain controller), patch it, enable TLS 1.2, and install the ActiveDirectory PowerShell module.

2.3 Healthy Active Directory

Description: AD replication, DNS, and time sync are healthy across domain controllers. Why: Sync reads from AD; replication or DNS faults stall or corrupt synchronization. Verify: `dcdiag` and `repadmin /replsummary` clean on a DC; run `HYBID-Discovery.ps1`. Implement: Resolve replication, DNS, and time-sync errors before synchronizing.

2.4 UPN and domain hygiene

Description: User UPNs use a public, verified, routable domain (no `.local`); no duplicate UPNs or proxyAddresses. Why: Non-routable or duplicate UPNs/proxyAddresses cause sign-in failures and sync errors (merged/split accounts). Verify: Entra -> `Identity -> Settings -> Domain names` shows the public domain Verified; run `HYBID-Discovery.ps1` (flags `.local` UPNs and duplicates). Implement: Add and verify the public domain in Entra; add the matching UPN suffix in AD; update user UPNs; resolve duplicates with `HYBID-Remediation.ps1`.

2.5 Authentication method decision

Description: A decision on the primary authentication method — PHS, PTA, or federation. Why: It is the single most consequential design choice and drives the install options. Verify: A documented decision (default PHS) and whether Seamless SSO and password writeback are wanted. Implement: Default to password hash sync with Seamless SSO; choose PTA or federation only for a stated requirement, and keep PHS enabled as a backup.

2.6 Administrative roles

Description: Hybrid Identity Administrator for ongoing work; Global Administrator for the first-sync consent. Why: Configuring directory sync and authentication needs these roles. Verify: Entra -> `Roles and administrators`. Implement: Assign `Hybrid Identity Administrator`; use a `Global Administrator` only for the one-time first-sync grant.

2.7 Break-glass accounts

Description: Two cloud-only emergency access accounts excluded from broad policies. Why: An identity change can lock out admins; break-glass accounts restore access. Verify: Entra -> `Users`; two cloud-only `@onmicrosoft.com` admins exist. Implement: Create them, exclude from Conditional Access/MFA-broad policies, store credentials securely, and monitor their sign-ins.

2.8 Pilot scope group

Description: An AD organizational unit (or group) of representative pilot users/devices. Why: Every change is validated on a pilot before the fleet. Verify: An OU such as `Hybrid Pilot Sync Scope - Pilot - Pilot` exists with representative members. Implement: Create the pilot OU and place pilot users/devices in it; see Implementation Step 1.

2.9 Network access

Description: Outbound HTTPS (443) from the Connect host to Entra ID and Microsoft 365 endpoints. Why: Sync, authentication agents, and tokens depend on these endpoints. Verify: From the host, reach `https://login.microsoftonline.com`; Microsoft 365 URL/IP ranges allowed. Implement: Allow the Microsoft 365 / Entra published URL and IP ranges through proxy/firewall.

Checklist

- Entra ID P1/P2 licensing assigned
- Entra Connect host server ready (domain-joined, patched, TLS 1.2) — `HYBID-Discovery.ps1`
- Active Directory healthy (`dcdiag`, `repadmin`)
- UPN/domain hygiene fixed (public verified domain, no duplicates) — `HYBID-Discovery.ps1`
- Authentication method decided (default PHS) and Seamless SSO/writeback choices made
- Hybrid Identity Administrator role assigned; Global Admin available for first sync

- Two break-glass accounts created and excluded from broad policies
- Pilot sync scope OU/group created
- Network allows Entra/Microsoft 365 endpoints from the host

3. Implementation Guide — Hybrid Identity with Active Directory & Microsoft Entra Connect

Follow these steps in order. Work happens in two places: the Microsoft Entra Connect wizard on the host server, and the cloud portal at `https://entra.microsoft.com` (Identity -> Hybrid management).

> *Model: rehearse in staging mode, validate on a pilot scope, then expand to the whole directory. The identity plane is high risk — keep your break-glass accounts to hand before every change.*

Objects you will create (name them exactly as written and reuse verbatim):

- AD organizational unit: `Hybrid Pilot Sync Scope - Pilot - Pilot`
- AD organizational unit: `Hybrid Production Sync Scope - All-Domains - Expand`
- Entra security group: `Hybrid Join Devices - Pilot - Pilot`
- Hybrid join service connection point config: `Hybrid Entra Join - Domain - Configure`

Step 1 — Prepare AD and the pilot scope

1. On a domain controller, open `Active Directory Users and Computers`.
2. Create an OU named `Hybrid Pilot Sync Scope - Pilot - Pilot` and move a handful of representative

pilot users (and test devices) into it.

1. Create an OU (or confirm the existing structure) named

`Hybrid Production Sync Scope - All-Domains - Expand` to represent the full production scope for later expansion.

1. Run `HYBID-Discovery.ps1` and resolve every flagged item (`.local` UPNs, duplicate UPNs/proxyAddresses, AD health).

Step 2 — Verify the public domain in Entra

1. In `https://entra.microsoft.com`, go to `Identity -> Settings -> Domain names`.
2. Confirm your public domain shows Verified (add and verify it with the displayed DNS TXT record if not).
3. Ensure AD user UPN suffixes match that public domain (fix in `Active Directory Domains and Trusts` if needed).

Step 3 — Install Microsoft Entra Connect on the host

1. On the Connect host server, download Microsoft Entra Connect and launch the installer.

2. Accept the license, then choose `Customize` (so you can scope the sync and pick the auth method).

3. On `Install required components`, leave the defaults and click `Install`.

Step 4 — Choose the authentication method (in the wizard)

1. On the `User sign-in` page, select the primary method:

• `Password Hash Synchronization` (recommended default), or

• `Pass-through authentication`, or

• `Federation with AD FS` (only for a stated requirement).

1. Tick `Enable single sign-on` (Seamless SSO) for domain-joined corporate-network users.

2. Click `Next`.

Step 5 — Connect to Entra ID and AD

1. On `Connect to Microsoft Entra ID`, sign in with a `Global Administrator` (the one-time first-sync consent).

2. On `Connect your directories`, add your AD forest with an enterprise-admin (or delegated sync) credential. Click `Next`.

3. On `Microsoft Entra sign-in configuration`, confirm the UPN suffix is the verified public domain (resolve any warning here before continuing).

Step 6 — Scope the synchronization

1. On `Domain and OU filtering`, choose `Sync selected domains and OUs`.

2. Select only `Hybrid Pilot Sync Scope - Pilot - Pilot` for the pilot. Click `Next`.

3. On `Uniquely identifying your users`, accept the default (`Users are represented once`) unless you have a multi-forest match attribute.

4. On `Filter users and devices`, keep `Synchronize all users and devices`. Click `Next`.

Step 7 — Optional features, then stage the first sync

1. On `Optional features`, enable what you need — for example `Password writeback` and (if PTA/federation primary) keep `Password hash synchronization` ticked as a backup. Click `Next`.

2. On `Ready to configure`, tick `Enable staging mode` so the first run imports and rehearses without exporting to the cloud. Click `Install`.

3. When it finishes, run `HYBID-Validation.ps1` and `HYBID-Report.ps1` on the host to review what would export, the connector-space object counts, and any sync errors — fix errors before going live.

Step 8 — Take the server out of staging mode (go live for the pilot)

1. Re-run the Microsoft Entra Connect wizard, choose `Configure staging mode`, and clear the

`Enable staging mode` checkbox. Finish the wizard.

1. Force a sync cycle: on the host run `Start-ADSyncSyncCycle -PolicyType Delta`.
2. In `https://entra.microsoft.com -> Identity -> Hybrid management -> Microsoft Entra Connect ->

Connect Sync, `confirm sync status is healthy and the pilot users now appear under` Identity -> Users`.

Step 9 — Enable Seamless SSO and confirm the auth method

1. In `Identity -> Hybrid management -> Microsoft Entra Connect`, confirm the chosen sign-in method

shows Enabled and (for PTA) at least two healthy authentication agents.

1. For Seamless SSO, ensure the AZUREADSSO computer object exists in AD and roll out the two browser

settings via Group Policy to pilot devices (Microsoft documents the exact registry/policy values).

Step 10 — Enable hybrid Entra join (devices)

1. Create an Entra security group named `Hybrid Join Devices - Pilot - Pilot` for pilot devices.
2. Re-run the Microsoft Entra Connect wizard -> `Configure device options` -> `Configure Hybrid Azure AD join`; this writes the service connection point named `Hybrid Entra Join - Domain - Configure`. Select your device OS/platform and finish.
3. On a pilot device, run `dsregcmd /status` and confirm `AzureAdJoined : YES` and `DomainJoined : YES` (allow a policy cycle and a sign-in).

Step 11 — Validate the pilot

1. Run `HYBID-Validation.ps1` -> confirms sync ran, pilot objects exported, and a test sign-in works.
2. Run `HYBID-Report.ps1` -> confirms sync health, object coverage, and zero unresolved sync errors.
3. Complete the Testing Guide. Do not expand until the pilot gate passes.

Step 12 — Expand to production

1. Re-run the wizard -> `Customize synchronization options` -> `Domain and OU filtering` and add

`Hybrid Production Sync Scope - All-Domains - Expand` to the sync scope. Finish.

1. Run `Start-ADSyncSyncCycle -PolicyType Initial` for a full sync of the new scope.
2. Re-run `HYBID-Report.ps1` to confirm coverage and health across the full directory; add

`Hybrid Join Devices - Pilot - Pilot` members (or a production device group) as you expand hybrid join.

Order of operations

`Prepare AD + pilot scope -> verify domain -> install Connect -> choose auth method -> connect directories -> scope sync -> stage first sync -> exit staging (pilot live) -> Seamless SSO -> hybrid join -> validate -> expand`

5. Testing Guide — Hybrid Identity with Active Directory & Microsoft Entra Connect

Run after the pilot goes live (Implementation Step 11) and after each change to scope, auth method, or hybrid join.

Test 1 — Sync engine healthy and running

Do: On the host run `Get-ADSyncScheduler` and `HYBID-Validation.ps1`. Expected: `SyncCycleEnabled : True`, the server is not in staging mode, and a delta cycle completes.

Test 2 — Pilot objects synchronized

Do: In `https://entra.microsoft.com -> Identity -> Users`, search for a pilot user; run `HYBID-Report.ps1`. Expected: Pilot users from `Hybrid Pilot Sync Scope - Pilot - Pilot` appear in Entra ID with the correct UPN.

Test 3 — No sync errors / no duplicates

Do: Run `HYBID-Report.ps1` (and `HYBID-Validation.ps1`). Expected: Zero unresolved sync errors; no duplicate-attribute (UPN/proxyAddress) errors.

Test 4 — Authentication method works

Do: Sign a pilot user in at `https://myapps.microsoft.com` (incognito), then on a domain-joined corporate device. Expected: Sign-in succeeds; for PHS the cloud validates; for PTA an agent shows the auth in `Hybrid management`; Seamless SSO does not re-prompt on the corporate network.

Test 5 — Password writeback (if enabled)

Do: Have a pilot user reset their password via self-service password reset; then sign in on-premises. Expected: The new password works against AD — writeback succeeded.

Test 6 — Hybrid Entra join

Do: On a pilot device run `dsregcmd /status`. Expected: `AzureAdJoined : YES` and `DomainJoined : YES`; the device appears in `Identity -> Devices`.

Test 7 — Staging-mode failover rehearsal (optional)

Do: If a second Connect server exists in staging mode, run `HYBID-Report.ps1` against it. Expected: It imports and previews the same objects without exporting — ready to promote on failover.

Pass/fail gate

Gate	Requirement
Pilot pass	Tests 1-4 pass; zero unresolved sync errors; a pilot user signs in cloud and on a hybrid-joined device
Expand pass	Tests 1-3, 6 pass across the production scope before declaring complete

6. Troubleshooting Guide — Hybrid Identity with Active Directory & Microsoft Entra Connect

Use `HYBID-Validation.ps1` / `HYBID-Discovery.ps1` for host and identity state, `HYBID-Report.ps1` for sync health and coverage, and `HYBID-Remediation.ps1` (`-WhatIf` by default) for safe fixes. Keep your break-glass accounts ready before any change.

A. Synchronization not running / stalled

Symptom	Cause	Remediation
No new objects appear in Entra	Server in staging mode, or scheduler disabled	Run `Get-ADSyncScheduler`; exit staging mode (wizard); `Set-ADSyncScheduler -SyncCycleEnabled $true`; `Start-ADSyncSyncCycle -PolicyType Delta`
Cycle errors immediately	AD replication/DNS fault, or credentials expired	Run `HYBID-Discovery.ps1`; fix `dcdiag`/`repadmin` issues; refresh the connector account
Nothing in scope	OU/domain filter excludes the objects	Review with `HYBID-Set-SyncScopeHelper.ps1`; widen the sync scope in the wizard

B. Duplicate or merged accounts / sync errors

Symptom	Cause	Remediation
Duplicate-attribute error	Two objects share a UPN or proxyAddress	Run `HYBID-Report.ps1` to list them; resolve with `HYBID-Remediation.ps1` (review the `-WhatIf` output first)

Symptom	Cause	Remediation
Cloud account separate from on-prem	Soft-match failed (UPN/proxyAddress mismatch)	Align the on-prem UPN/proxyAddress to the cloud value, or hard-match by `ImmutableId`; re-sync
`.onmicrosoft.com` UPN in cloud	Non-routable `.local` UPN on-premises	Add the verified public domain and matching UPN suffix; update user UPNs; re-sync

C. Sign-in failures

- Password hash sync: confirm PHS is enabled in `Hybrid management`; force a full sync if a single user is stale.
- Pass-through authentication: confirm at least two healthy authentication agents; an offline agent breaks PTA sign-in (PHS backup, if enabled, keeps users working).
- Federation: check the AD FS service and token-signing certificate validity; an expired certificate blocks all federated sign-in.
- Seamless SSO: confirm the AZUREADSSO computer object exists and the browser policies are applied to the device.

D. Hybrid Entra join not completing

Symptom	Cause	Remediation
`dsregcmd /status` shows `AzureAdJoined : NO`	Service connection point missing, or device not synced	Re-run the wizard `Configure device options`; confirm the `Hybrid Entra Join - Domain - Configure` SCP; let a policy cycle + sign-in complete
Join works for users but not devices	Computer objects out of sync scope	Add the device OU to the sync scope (`HYBID-Set-SyncScopeHelper.ps1`); re-sync

E. Accidental-deletion safeguard tripped

- A large scope change can trip the export deletion threshold (a safety feature). Confirm the deletes are intended, then `Enable-ADSyncExportDeletionThreshold` / re-run with the threshold raised only after verifying with `HYBID-Report.ps1`.

F. Diagnostics quick reference

```
Get-ADSyncScheduler                                  # sync schedule + staging mode
Start-ADSyncSyncCycle -PolicyType Delta              # trigger a delta sync
Get-ADSyncConnectorRunStatus                         # is a run in progress
dsregcmd /status                                     # device hybrid-join state
dcdiag /q ; repadmin /replsummary                    # AD health
```

Connector and run-profile detail is in the Synchronization Service Manager (`miisclient.exe`) on the host.

G. When to escalate

If sync runs clean, AD is healthy, the auth method is enabled with healthy agents/certificates, and a user still cannot sign in or hybrid-join after a full sync and a policy cycle, collect the `HYBID-Report.ps1` output and the connector run details and open a Microsoft support case.

7. Best Practices — Hybrid Identity with Active Directory & Microsoft Entra Connect

• Treat the identity plane as high risk. Rehearse every change in staging mode, validate on a pilot scope, and only then expand — this is the single most important practice.

• Keep break-glass accounts ready. Two cloud-only emergency admins, excluded from broad policies, before you touch sync, auth methods, or hybrid join.

• Prefer password hash sync. PHS is the simplest, most resilient method and keeps cloud sign-in working if the on-premises servers are down; keep it enabled as a backup even under PTA/federation.

• Fix UPN and domain hygiene first. A verified public routable domain and no duplicate UPN/proxyAddress values prevent the most common sync errors and broken sign-ins.

• Scope synchronization deliberately. Use OU/domain filters so test, service, and stale objects stay out of the cloud; name your scopes with the `<Purpose> - <Scope> - <Stage>` convention and reuse them.

• Run one active sync server, one in staging. The staging server is your rehearsal surface and your failover; never run two active exporters.

• Don't reach for federation by default. AD FS is a large ongoing commitment (certificates, a farm, its own outage surface); choose PHS or PTA unless a requirement forces federation.

• Monitor sync health continuously. Check `HYBID-Report.ps1` and the `Hybrid management` blade for errors and export latency; chase duplicate-attribute and large-delete safeguards promptly.

• Respect the export deletion threshold. Keep the accidental-deletion safeguard on so a bad filter change cannot mass-delete cloud objects; investigate before overriding it.

• Document the design. Record the auth method, sync scopes, writeback settings, and hybrid-join configuration for audits and repeatability.

8. Deliverables Summary — Hybrid Identity with Active Directory & Microsoft Entra Connect

Documentation

Document	Purpose
Executive Summary	Business case and what is in the box
1. Solution Overview	Hybrid identity, Connect Sync vs. Cloud Sync, auth methods, Seamless SSO, hybrid join, sync health
2. Requirements Guide	Every prerequisite with Verify / Implement-if-missing
Global Requirements (Entra ID Solutions)	Category-wide prerequisites, published once
3. Implementation Guide	Exact, ordered steps (prepare AD, install Connect, auth method, scope, hybrid join, expand)
5. Testing Guide	Validation procedures with pass/fail gates
6. Troubleshooting Guide	Field issues and remediation
7. Best Practices	Field-proven recommendations

PowerShell scripts

Script	What it does
`HYBID-Discovery.ps1`	AD/identity readiness: AD health, `.local`/duplicate UPNs, host and TLS readiness (read-only)
`HYBID-Validation.ps1`	Confirms the sync ran, objects exported, and a test sign-in works (read-only)
`HYBID-Report.ps1`	Sync health + object coverage across AD and Entra ID via ADSync and Microsoft Graph (read-only)
`HYBID-Remediation.ps1`	Safely fixes sync errors and duplicate UPN/proxyAddress values; `-WhatIf` by default
`HYBID-Set-SyncScopeHelper.ps1`	Helper to review and stage OU/domain sync-scope changes for the wizard

What the buyer receives

- This implementation guide as a branded Word document and PDF.
- All five PowerShell scripts in a single ZIP.
- A repeatable process: Assess -> Configure -> Pilot -> Validate -> Expand.

Outcome

One reliable identity spanning Active Directory and Entra ID — synchronized cleanly, authenticated by the right method, with hybrid join and healthy sync, proven on a pilot before you scale.

Appendix A — PowerShell Scripts

Included in the accompanying ZIP. Each script's header documents full usage.

HYBID-Discovery.ps1

Purpose: Read-only readiness check before installing Microsoft Entra Connect. Reports the Entra Connect host OS/TLS readiness, AD forest/domain and UPN suffixes, flags non-routable (.local) UPNs and duplicate UPN/proxyAddress values, and surfaces basic AD health hints. HOW TO RUN On the planned Connect host (domain-joined), elevated: powershell -ExecutionPolicy Bypass -File .\HYBID-Discovery.ps1 Requires the ActiveDirectory PowerShell module (RSAT) to read directory objects. EXPECTED RESULTS Host/TLS summary, forest/domain + UPN suffixes, counts of .local UPNs and duplicate UPN/proxyAddress values, and any AD health warning. No changes are made. .NOTES Workplace Marketplace — Entra ID Solutions. Read-only. #> [CmdletBinding()] param()

How to run: On the planned Connect host (domain-joined), elevated: powershell -ExecutionPolicy Bypass -File .\HYBID-Discovery.ps1 Requires the ActiveDirectory PowerShell module (RSAT) to read directory objects. EXPECTED RESULTS Host/TLS summary, forest/domain + UPN suffixes, counts of .local UPNs and duplicate UPN/proxyAddress values, and any AD health warning. No changes are made. .NOTES Workplace Marketplace — Entra ID Solutions. Read-only. #> [CmdletBinding()] param()

HYBID-Remediation.ps1

Purpose: Addresses the two most common hybrid-identity faults: (1) duplicate proxyAddress values in AD that cause duplicate-attribute sync errors, and (2) a stalled sync engine. By default it runs in -WhatIf mode and only reports what it WOULD change — re-run with -Apply to act. With -Apply it removes the conflicting (lower-priority) duplicate proxyAddress entries you confirm, then triggers a delta sync cycle. HOW TO RUN Dry run (default, no changes): powershell -ExecutionPolicy Bypass -File .\HYBID-Remediation.ps1 Apply fixes after reviewing the dry run: powershell -ExecutionPolicy Bypass -File .\HYBID-Remediation.ps1 -Apply Requires the ActiveDirectory module; the sync trigger requires the ADSync (Connect) role. EXPECTED RESULTS A list of duplicate proxyAddress conflicts (always), and — only with -Apply — the removals performed plus a triggered delta sync. Nothing is changed unless -Apply is supplied. .NOTES Workplace Marketplace — Entra ID Solutions. Defaults to -WhatIf (no changes). #> [CmdletBinding(SupportsShouldProcess = $true)] param([switch]$Apply)

How to run: Dry run (default, no changes): powershell -ExecutionPolicy Bypass -File .\HYBID-Remediation.ps1 Apply fixes after reviewing the dry run: powershell -ExecutionPolicy Bypass -File .\HYBID-Remediation.ps1 -Apply Requires the ActiveDirectory module; the sync trigger requires the ADSync (Connect) role. EXPECTED RESULTS A list of duplicate proxyAddress conflicts (always), and — only with -Apply — the removals performed plus a triggered delta sync. Nothing is changed unless -Apply is supplied. .NOTES Workplace Marketplace — Entra ID Solutions. Defaults to -WhatIf (no changes). #> [CmdletBinding(SupportsShouldProcess = $true)] param([switch]$Apply)

HYBID-Report.ps1

Purpose: Read-only report of hybrid-identity health and coverage. From ADSync it reports the connectors and the last run-profile results (errors/aborts). From Microsoft Graph it reports how many users are on-premises-synced vs. cloud-only, and how many devices are hybrid-joined, so you can confirm coverage before and after expansion. HOW TO RUN On the Connect host, elevated: powershell -ExecutionPolicy

Bypass -File .\HYBID-Report.ps1 ADSync cmdlets require the Microsoft Entra Connect role. The Graph section needs the Microsoft Graph SDK and Directory.Read.All / Device.Read.All. EXPECTED RESULTS Connector list, recent run results with any error counts, and synced vs. cloud-only user and hybrid-joined device counts. No changes are made. .NOTES Workplace Marketplace — Entra ID Solutions. Read-only. #> [CmdletBinding()] param()

How to run: On the Connect host, elevated: powershell -ExecutionPolicy Bypass -File .\HYBID-Report.ps1 ADSync cmdlets require the Microsoft Entra Connect role. The Graph section needs the Microsoft Graph SDK and Directory.Read.All / Device.Read.All. EXPECTED RESULTS Connector list, recent run results with any error counts, and synced vs. cloud-only user and hybrid-joined device counts. No changes are made. .NOTES Workplace Marketplace — Entra ID Solutions. Read-only. #> [CmdletBinding()] param()

HYBID-Set-SyncScopeHelper.ps1

Purpose: Helps you plan the Microsoft Entra Connect domain/OU sync scope. It lists candidate OUs with the count of users and computers each contains, so you can decide what to include, and it previews how many objects a proposed set of OUs would bring into scope BEFORE you set the filter in the wizard. It does NOT change the Connect filter itself (OU/domain filtering is set in the Microsoft Entra Connect wizard); it produces the object list and counts to drive that decision safely. HOW TO RUN Inventory candidate OUs (read-only): powershell -ExecutionPolicy Bypass -File .\HYBID-Set-SyncScopeHelper.ps1 Preview a proposed scope (read-only): powershell -ExecutionPolicy Bypass -File .\HYBID-Set-SyncScopeHelper.ps1 ^ -IncludeOU "OU=Hybrid Pilot Sync Scope - Pilot - Pilot,DC=corp,DC=example,DC=com" Requires the ActiveDirectory module (RSAT AD tools). EXPECTED RESULTS A table of OUs with user/computer counts, or — when -IncludeOU is supplied — the total users and computers the proposed scope would synchronize. No directory or sync changes are made. .NOTES Workplace Marketplace — Entra ID Solutions. Read-only (planning helper). #> [CmdletBinding()] param([string[]]$IncludeOU)

How to run: Inventory candidate OUs (read-only): powershell -ExecutionPolicy Bypass -File .\HYBID-Set-SyncScopeHelper.ps1 Preview a proposed scope (read-only): powershell -ExecutionPolicy Bypass -File .\HYBID-Set-SyncScopeHelper.ps1 ^ -IncludeOU "OU=Hybrid Pilot Sync Scope - Pilot - Pilot,DC=corp,DC=example,DC=com" Requires the ActiveDirectory module (RSAT AD tools). EXPECTED RESULTS A table of OUs with user/computer counts, or — when -IncludeOU is supplied — the total users and computers the proposed scope would synchronize. No directory or sync changes are made. .NOTES Workplace Marketplace — Entra ID Solutions. Read-only (planning helper). #> [CmdletBinding()] param([string[]]$IncludeOU)

HYBID-Validation.ps1

Purpose: Read-only validation after the pilot goes live. Confirms the ADSync scheduler is enabled and the server is out of staging mode, reports the last sync run result, and (with Microsoft Graph) confirms on-premises sync is enabled in the tenant and lists recently synced users so you can verify a pilot account is present. HOW TO RUN On the Connect host, elevated: powershell -ExecutionPolicy Bypass -File .\HYBID-Validation.ps1 ADSync cmdlets require the Microsoft Entra Connect role. The Graph check needs the Microsoft Graph SDK and Directory.Read.All / User.Read.All. EXPECTED RESULTS "SYNC HEALTHY" when the scheduler is on, the server is not in staging mode, the last run succeeded, and the tenant shows on-premises sync enabled. .NOTES Workplace Marketplace — Entra ID Solutions. Read-only. #> [CmdletBinding()] param()

How to run: On the Connect host, elevated: powershell -ExecutionPolicy Bypass -File .\HYBID-Validation.ps1 ADSync cmdlets require the Microsoft Entra Connect role. The Graph check needs the Microsoft Graph SDK and Directory.Read.All / User.Read.All. EXPECTED RESULTS "SYNC HEALTHY" when the scheduler is on, the server is not in staging mode, the last run succeeded, and the tenant shows on-premises sync enabled. .NOTES Workplace Marketplace — Entra ID Solutions. Read-only. #> [CmdletBinding()] param()