Remote Help for the Enterprise Help Desk — Operations, Unattended Access & Adoption at Scale

Implementation Solution Guide

Version 1.0.0 · 2026-07-21

Contents

Executive Summary — Remote Help for the Enterprise Help Desk (Operations, Unattended Access & Adoption) 4

What you get . . . 4

What this delivers . . . 4

Verify-with-Microsoft note . . . 4

The standard deployment model . . . 4

Outcome . . . 5

1. Solution Overview — Remote Help for the Enterprise Help Desk (Operations, Unattended Access & Adoption) 5

What this solution is . . . 5

What this adds vs. the base Remote Help product . . . 5

The operating model . . . 6

Benefits . . . 6

Limitations (be honest with buyers) . . . 6

The standard deployment model . . . 7

2. Requirements Guide — Remote Help Operations & Adoption 7

2.1 Remote Help already deployed (the base product) . . . 7

2.2 Help-desk tier definition . . . 7

2.3 RBAC role rights to create/assign roles . . . 8

2.4 Remote Help RBAC roles & permissions . . . 8

2.5 Licensing for helpers (and any unattended scenario) . . . 8

2.6 Unattended-access governance decision . . . 8

2.7 Ticketing / ITSM integration points . . . 8

2.8 Reporting / audit read access . . . 9

Checklist . . . 9

Global Requirements — Intune Solutions (category-level) 9

G1. Microsoft Entra ID tenant . . . 9

G2. Microsoft Intune subscription . . . 9

G3. Administrative roles . . . 9

G4. Device enrollment in Intune . . . 10

G5. Pilot security group . . . 10

G6. Supported Windows baseline . . . 10

G7. Network access to Microsoft cloud endpoints . . . 10

3. Implementation Guide — Remote Help Operations & Adoption 10

Step 1 — Create the help-desk tier agent groups (Entra) . . . 11

Step 2 — Create the scope groups (the users each tier may help) (Entra) . . . 11
Step 3 — Create the per-tier Remote Help RBAC roles (Intune) . . . 11
Step 4 — Configure and govern unattended access . . . 12
Step 5 — Assign the roles with scope, and wire the session-to-ticket workflow . . . 12
Step 6 — Stand up usage & outcome reporting . . . 13
Step 7 — Pilot, then run the adoption campaign . . . 14
Step 8 — Expand across tiers . . . 14
5. Testing Guide — Remote Help Operations & Adoption 15
Test 1 — An agent can help only in-scope users . . . 15
Test 2 — Capability matches the tier . . . 15
Test 3 — Unattended access works only where governed . . . 15
Test 4 — A session is logged to a ticket . . . 15
Test 5 — Escalation moves the ticket (and the authorized tier) . . . 15
Test 6 — KPIs report . . . 16
Test 7 — Adoption is measurable . . . 16
Pass/fail gate . . . 16
6. Troubleshooting Guide — Remote Help Operations & Adoption 16
A. Agent can't help / wrong scope . . . 16
B. Unattended access not available / not among tiers . . . 17
C. Session not logged to a ticket . . . 17
D. KPIs missing / can't report . . . 18
E. Low adoption . . . 18
F. Scripts . . . 19
G. When to escalate . . . 19
7. Best Practices — Remote Help Operations & Adoption 20
Role & scope design . . . 20
Unattended access . . . 20
Workflow & escalation . . . 20
Measurement & adoption . . . 20
Hygiene . . . 21
8. Deliverables Summary — Remote Help Operations & Adoption 21
Documentation . . . 21
PowerShell scripts . . . 22
What the buyer receives . . . 22
Outcome . . . 22
Appendix A — PowerShell Scripts 23

Executive Summary — Remote Help for the Enterprise Help Desk (Operations, Unattended Access & Adoption)

White-label · Intune Solutions

Deploying Remote Help is the easy part; **running it as a help-desk capability** is where the value is won or lost. Once the app is enabled and installed, an enterprise still needs the operating model: who can help whom, when unattended access is appropriate and how it is governed, how a session fits the ticket and escalation workflow, how usage and outcomes are measured, and how end users learn to trust and request help. This package delivers that operating model.

> ***Prerequisite:*** *this solution* ***assumes Remote Help is already deployed*** *— see the separate* ***Remote Help*** *solution (slug* `remote-help`*), which covers enable, app deployment, and the base security model. This package is the* ***operations and adoption layer on top*** *and does* ***not*** *repeat that setup.*

This is a complete, self-guided package written for an administrator who has Remote Help deployed but has not yet turned it into a governed, measured, widely-used help-desk service.

What you get

- A **Solution Overview** of the operating model and exactly what it adds vs. the base deployment.
- A **Requirements Guide** with verify / implement-if-missing for every prerequisite (base

deployment, tier definition, RBAC rights, licensing, unattended governance, ticketing, reporting).

- An **Implementation Guide** of precise, ordered steps: tier agent groups, scope groups, per-tier

RBAC roles, unattended-access governance, role assignment with scope, the session-to-ticket workflow, KPI reporting, a pilot, and an adoption campaign — every object named and reused.

- Five **PowerShell scripts** for discovery, validation, KPI reporting, scope-proofing, and a

`-WhatIf`-gated role/scope assigner.

- **Testing** (PASS/FAIL) and **Troubleshooting** guides for confident rollout.

What this delivers

Help-desk **tiers mapped to Remote Help RBAC roles and scope** so agents help exactly the right users and no more; **governed, guard-railed unattended access** owned by a single tier; a **session-to-ticket workflow** with tier escalation; **usage/outcome/adoption KPI reporting**; and an **adoption campaign** that gets end users requesting help and agents using the tool — piloted, then expanded.

Verify-with-Microsoft note

Remote Help's role/permission names, portal navigation, and — critically — whether and how **unattended access** is offered change over time. This guide governs the *practice* and names every object you create; it flags Microsoft-owned capability specifics to **verify against current Microsoft documentation** rather than asserting them.

The standard deployment model

Assess → **Configure** → **Pilot** → **Validate** → **Expand.**

Outcome

Remote Help operating as a real help-desk capability — right-scoped roles, governed unattended access, a traceable session-to-ticket workflow, outcome reporting, and genuine adoption.

1. Solution Overview — Remote Help for the Enterprise Help Desk (Operations, Unattended Access & Adoption)

What this solution is

This is the **operations and adoption layer** that sits **on top of an existing Remote Help deployment**. It does **not** install, enable, or re-teach the base Remote Help service or its security model — that is the job of the separate **Remote Help** solution (slug `remote-help`), which is the **prerequisite** for this package. This solution assumes Remote Help is already enabled in the tenant, the Remote Help app is deployed to devices, and the base security model (Entra authentication, RBAC, compliance visibility, audit) is in place.

> ***Prerequisite (read this first):*** *This solution* ***assumes Remote Help is deployed per the "Remote Help" solution*** *(`remote-help`). If Remote Help is not yet enabled and the app not yet deployed, run that solution first. Everything below builds the *help-desk practice* around a working Remote Help deployment; it never repeats install/enable/security-model setup.*

Once the app is in place, an enterprise still has to turn "installed" into a **running help-desk capability**: who can help whom, when unattended access is appropriate and how it is governed, how a session fits the ticket and escalation workflow, how usage and outcomes are measured, and how end users learn to trust and request help. That operating model is what this solution delivers.

What this adds vs. the base Remote Help product

Base **Remote Help** product (prerequisite)	**This** operations/adoption product
Enable Remote Help in the tenant	*(assumed already done)*
Deploy the Remote Help app via Intune	*(assumed already done)*
The security model (Entra auth, RBAC, compliance, audit)	*(assumed already in place)*
—	**Role & scope design** — map help-desk **tiers** to RBAC roles + scope so agents help exactly the right users, and no more
—	**Attended vs unattended access** — when unattended is appropriate, how it is governed and consented, and its guardrails
—	**Help-desk workflow** — fit a session into ticket intake, verification, escalation tiers, and session logging/handoff

Base **Remote Help** product (prerequisite)	**This** operations/adoption product
—	**Measurement** — usage, session outcomes, and adoption KPIs + reporting
—	**Adoption** — end-user comms, how to request help, trust/consent expectations, agent enablement

The operating model

1. **Tier the help desk.** Define the support tiers (for example **Tier 1 – Service Desk**, **Tier 2 – Desktop Support**, **Tier 3 – Escalation Engineering**) and decide what each tier is allowed to do in a Remote Help session (view only, full control, elevation).

1. **Map each tier to an RBAC role + scope.** Each tier gets its own Remote Help RBAC role (capability) and its own scope (the users it may help), so an agent can help exactly the right population and no more.

1. **Govern unattended access.** Decide where unattended assistance is appropriate (for example unattended kiosks, shared devices, or servers with no user present to consent), restrict it to a dedicated tier, and put guardrails around it. *(Unattended-access availability and behavior in Remote Help — whether it is offered, on which platforms, its exact settings and consent model — must be **verified against current Microsoft documentation**; this solution governs the practice, it does not assert the capability.)*

1. **Wire the session into the ticket workflow.** Every session starts from a ticket, verifies the caller, is escalated across tiers when needed, and is logged back to the ticket on completion.

1. **Measure and report.** Track session volume, outcomes, escalation and consent rates, unattended sessions, and adoption; report the KPIs that prove the capability is working.

1. **Drive adoption.** Tell end users how to request help and what to expect (consent, audit), and enable agents so the tool is actually used.

Benefits

- **Right-scoped support** — agents help the users they should, with the capability they should have.
- **Governed unattended access** — a deliberate, guard-railed practice instead of an open door.
- **Faster, traceable resolution** — sessions live inside the ticket and escalation flow.
- **Provable value** — KPIs and reporting show utilization, outcomes, and adoption.
- **Real adoption** — end users trust it and agents use it, so the investment pays off.

Limitations (be honest with buyers)

- **Requires Remote Help already deployed** (the `remote-help` solution) — this package does not install or enable it.

• **Unattended-access specifics are Microsoft-governed** — availability, supported platforms, exact settings, and consent behavior change over time and must be verified against current Microsoft documentation before you rely on them.

• **RBAC role names, permission names, and portal navigation** in Intune change over time — this guide names objects consistently but you must confirm current labels in your tenant.

• **Ticketing integration is process-level** — this solution defines how a session maps to a ticket; it does not build a code integration to any specific ITSM product.

The standard deployment model

> ***Design the tiers & role/scope model → configure roles, scope, and unattended governance → pilot with one tier and a small user scope → validate scope, unattended, logging, and KPIs → expand across tiers and run the adoption campaign.*** *Repeatable pattern:* ***Assess → Configure → Pilot → Validate → Expand.***

2. Requirements Guide — Remote Help Operations & Adoption

Verify **every** requirement before configuring. Each entry: **Description · Why · Verify · Implement-if-missing.** Category-wide prerequisites are in `global-requirements-intune-solutions.md`.

> *This solution is the* ***operations/adoption layer****. Its single biggest prerequisite is that the* ***base Remote Help deployment already exists*** *— see 2.1. It does* ***not*** *re-teach that setup.*

2.1 Remote Help already deployed (the base product)

Description: Remote Help is already **enabled** tenant-wide, the **Remote Help app is deployed** to devices via Intune, and the base security model (Entra authentication, RBAC framework, compliance visibility, audit) is in place. **Why:** This solution builds the help-desk operating model *around* a working Remote Help deployment. Without it there is nothing to operate. **Verify:** Intune → **Tenant administration** → **Remote Help** shows Remote Help **Enabled**; the Remote Help app shows as installed on pilot devices. Or run `RHELPOPS-Discovery.ps1` (reports whether Remote Help is enabled and which RBAC role assignments already exist). **Implement:** If Remote Help is **not** yet deployed, run the separate **"Remote Help"** solution (slug `remote-help`) first — it covers enable, app deployment, and the security model. Return here once it is in place.

2.2 Help-desk tier definition

Description: A defined set of support tiers and, for each, the intended Remote Help capability (view only, full control, elevation). **Why:** Roles and scope are assigned per tier; you cannot map roles until the tiers exist. **Verify:** A written tier model exists (for example **Tier 1 – Service Desk**, **Tier 2 – Desktop Support**, **Tier 3 – Escalation Engineering**). **Implement:** Document the tiers and their intended capability before configuring roles (this guide uses those three tier names throughout).

2.3 RBAC role rights to create/assign roles

Description: An operator account with rights to create and assign Intune RBAC roles and to read role assignments. **Why:** This solution creates custom Remote Help RBAC roles and assigns them with scope. **Verify:** Intune → **Tenant administration** → **Roles** is accessible and **Create** / **Assignments** are available to your account. **Implement:** Assign **Intune Administrator** (or a role that grants RBAC management) to the operator. *(The exact built-in role that grants "manage Intune roles" — and whether a custom role can — must be **verified against current Microsoft documentation**.)*

2.4 Remote Help RBAC roles & permissions

Description: Remote Help RBAC roles that express each tier's capability (view, full control, elevation) — either the built-in Remote Help roles or custom roles built from Remote Help permissions. **Why:** The role is what limits *what* an agent can do in a session; scope limits *who* they can help. **Verify:** Intune → **Tenant administration** → **Roles**; confirm Remote Help roles/permissions are available to select. **Implement:** Create the custom roles in Section 3. *(The exact **names** of the built-in Remote Help roles, the exact **permission names** for view vs full control vs elevation, and whether unattended access is expressed as a permission — **verify against current Microsoft documentation**; do not assume the labels.)*

2.5 Licensing for helpers (and any unattended scenario)

Description: A Remote Help license assigned to helper (agent) accounts, and any additional licensing that unattended assistance may require. **Why:** Remote Help is a licensed add-on; unattended scenarios may have their own licensing or capability requirements. **Verify:** M365 admin center → **Billing** → **Licenses** (Intune Suite / Remote Help add-on) for agent accounts. **Implement:** Assign the Remote Help / Intune Suite license to every agent account. *(Whether unattended access requires any additional license or capability — **verify against current Microsoft documentation**.)*

2.6 Unattended-access governance decision

Description: A documented decision on **whether** unattended assistance is allowed, **where** (which device populations), and **which tier** owns it, plus the guardrails (change/ticket requirement, logging, review). **Why:** Unattended access removes the live-consent step, so it must be a deliberate, governed practice — not a default. **Verify:** A written unattended-access policy exists and names the owning tier. **Implement:** Complete the decision in Section 3, Step 4. *(Whether Remote Help offers unattended access at all, on which platforms, and its exact consent/behavior model — **verify against current Microsoft documentation** before enabling anything.)*

2.7 Ticketing / ITSM integration points

Description: A ticketing/ITSM system and a defined point in its workflow where a Remote Help session is initiated and where the session outcome is logged back. **Why:** Sessions must be traceable to a ticket for accountability, escalation, and reporting. **Verify:** Your ITSM system has a ticket state/field where "Remote Help session" can be recorded (for example a work-note, activity, or custom field). **Implement:** Define the session-to-ticket steps in Section 3, Step 5. This is a **process** integration (agents record the session on the ticket); it is not a code integration to any specific ITSM product.

2.8 Reporting / audit read access

Description: Access to Remote Help usage/audit data for reporting KPIs. **Why:** Measurement depends on being able to read session/usage and audit activity. **Verify:** Intune → **Tenant administration** → **Remote Help** shows a usage report; or an account with Graph **AuditLog.Read.All** / **DeviceManagementApps.Read.All** can run `RHELPOPS-Report.ps1`. **Implement:** Grant the reporting account the read access above. *(The exact Remote Help usage report location and the Graph scopes/endpoints that expose session data — **verify against current Microsoft documentation**.)*

Checklist

- Remote Help already deployed (base `remote-help` solution) — `RHELPOPS-Discovery.ps1`
- Help-desk tiers defined (Tier 1 / Tier 2 / Tier 3) with intended capability
- Operator has rights to create/assign RBAC roles
- Remote Help RBAC roles/permissions available (names verified against Microsoft docs)
- Remote Help license on agent accounts (+ any unattended licensing verified)
- Unattended-access governance decision documented (owning tier + guardrails)
- Ticketing/ITSM session-log point defined
- Reporting/audit read access granted

Global Requirements — Intune Solutions (category-level)

These requirements apply to **every** solution in the **Intune Solutions** category. They are published once at the category level so individual listings stay small. Confirm these before deploying *any* Intune solution. Each entry: **Description · Why · Verify · Implement-if-missing.**

G1. Microsoft Entra ID tenant

Description: An active Microsoft Entra ID (Azure AD) tenant. **Why:** It is the identity backbone for every cloud and Intune-managed resource. **Verify:** Sign in to `https://entra.microsoft.com` as an administrator. **Implement:** Create a Microsoft 365/Azure subscription, which provisions a tenant.

G2. Microsoft Intune subscription

Description: An Intune-bearing license plan. **Why:** Intune delivers all configuration, compliance, and security policies. **Verify:** `https://intune.microsoft.com` loads; **Tenant administration** → **Tenant status** shows active. **Implement:** Assign Microsoft 365 E3/E5, Business Premium, or standalone Intune Plan 1.

G3. Administrative roles

Description: Appropriate Entra/Intune admin roles for the operator. **Why:** Creating policies and enrollment settings requires elevated rights. **Verify:** Entra → **Roles and administrators**; confirm **Intune**

Administrator. **Implement:** Assign **Intune Administrator**; reserve Global Administrator for tenant-wide changes.

G4. Device enrollment in Intune

Description: Targeted Windows devices are enrolled and manageable. **Why:** Policies only reach enrolled devices. **Verify:** Intune → **Devices** → **All devices**; the device appears and is **compliant**. **Implement:** Enable **Automatic Enrollment** and join devices to Entra ID.

G5. Pilot security group

Description: A Microsoft Entra security group for pilot/targeted users or devices. **Why:** Every solution is piloted before fleet rollout. **Verify:** Entra → **Groups**; the pilot group exists. **Implement:** Entra → **Groups** → **New group** → **Security** → add members.

G6. Supported Windows baseline

Description: Windows 10 21H2+ or Windows 11 with current updates. **Why:** Modern Intune features assume a patched, supported OS. **Verify:** `winver`, or Intune → device → **Hardware**. **Implement:** Deploy **Update rings** or upgrade to Windows 11.

G7. Network access to Microsoft cloud endpoints

Description: Outbound HTTPS to Microsoft 365, Entra, and Intune service URLs. **Why:** Enrollment, policy sync, and authentication depend on these endpoints. **Verify:** From a device, reach `https://login.microsoftonline.com` and `https://enrollment.manage.microsoft.com`. **Implement:** Allow Microsoft's published Office 365/Intune URL & IP ranges through proxy/firewall.

The standard deployment model (all solutions): Assess → Configure → Pilot → Validate → Expand.

3. Implementation Guide — Remote Help Operations & Adoption

Follow these steps **in order**. Most steps are in the **Microsoft Intune admin center** (`https://intune.microsoft.com`) and **Microsoft Entra admin center** (`https://entra.microsoft.com`).

> ***This guide does NOT install or enable Remote Help.*** *That is the base* ***Remote Help*** *solution (slug* `remote-help`*) and is a* ***prerequisite*** *(Requirement 2.1). Everything below assumes Remote Help is already enabled and its app already deployed. Start here only once that is true.*
>
> ***Model:*** *Design tiers & role/scope → configure roles, scope & unattended governance → pilot one tier + small scope → validate → expand across tiers + adoption campaign.*
>
> ***Naming convention (used verbatim throughout, and in Testing, Troubleshooting, and the scripts):*** `<Purpose> – <Scope/Tier> – <Stage>`*. Every object below is named; reuse each name exactly.*

> ***Verify-with-Microsoft note:*** *the exact Intune blade labels, the built-in Remote Help role names, the permission names for view vs full control vs elevation, and whether unattended access is offered/how it behaves all change over time. Where this guide names a portal path or a capability,* ***confirm the current label and availability in your tenant against current Microsoft documentation*** *before relying on it. The object names *you* create (groups, roles, assignments) are yours and are used verbatim.*

Step 1 — Create the help-desk tier agent groups (Entra)

Create one **Assigned** security group per tier, holding the agents in that tier.

1. Entra → **Groups** → **New group**.
2. **Group type:** Security. **Membership type: Assigned**. **Name:** `RHELP-T1-Agents`.

Description: *Tier 1 – Service Desk agents (Remote Help view-only)*. Add the Tier 1 agents as members. **Create**.

1. Repeat to create `RHELP-T2-Agents` — *Tier 2 – Desktop Support agents (full control)* — add Tier 2

agents. **Create**.

1. Repeat to create `RHELP-T3-Agents` — *Tier 3 – Escalation Engineering agents (full control + elevation + governed unattended)* — add Tier 3 agents. **Create**.

Step 2 — Create the scope groups (the users each tier may help) (Entra)

These groups define **who** each tier is allowed to help. Create them as **Assigned** security groups containing the target **users** (or their devices, per your model).

1. Entra → **Groups** → **New group** → Security → **Assigned** → **Name:** `RHELP-Scope-Standard-Users`.

Description: *Standard corporate users eligible for Tier 1/Tier 2 assistance*. Add the standard user population. **Create**.

1. Create `RHELP-Scope-VIP-Users` — *VIP/executive users; Tier 3 handling* — add the VIP/executive

users. **Create**.

1. *(Optional, for unattended scope — see Step 4)* Create `RHELP-Scope-Unattended-Devices` —

Devices approved for unattended assistance (kiosks/shared/no-consent-user) — add only the approved devices. **Create**.

> ***Assigned, not Dynamic:*** *keep these* ***Assigned*** *so membership is deliberate and auditable — an agent's reach should never widen automatically. If you later choose dynamic membership, review the rule as a security control.*

Step 3 — Create the per-tier Remote Help RBAC roles (Intune)

Create one custom RBAC role per tier expressing that tier's **capability**. *(If your tenant's built-in Remote Help roles already match a tier's capability exactly, you may assign the built-in role instead in Step 4 — **verify the built-in role names and their permissions against current Microsoft documentation**.)*

1. Intune → **Tenant administration** → **Roles** → **Create** (create a custom role).
2. **Name:** `RHELP Role – Tier 1 View`. **Description:** *Remote Help view-only for Tier 1*.

Under permissions, enable the **Remote Help** permission(s) that grant **view/observe only** (no control). *(Exact permission names — **verify against current Microsoft documentation**.)* **Next** → **Create**.

1. Create `RHELP Role – Tier 2 Control` — *Remote Help full control for Tier 2* — enable the Remote

Help permission(s) for **full control** (view + take control). **Create**.

1. Create `RHELP Role – Tier 3 Elevation` — *Remote Help full control + elevation (+ governed

unattended) for Tier 3* — enable full control **and** the permission(s) that allow **elevation** (and unattended, if it is expressed as a permission). *(Whether elevation and unattended are separate permissions — **verify against current Microsoft documentation**.)* **Create**.

Step 4 — Configure and govern unattended access

Decide and document unattended access **before** assigning it. *(Whether Remote Help offers unattended assistance, on which platforms, and its exact enablement/consent behavior — **verify against current Microsoft documentation**; do not enable a capability this guide asserts.)*

1. **Decide scope.** Unattended assistance is appropriate only where **no user is present to

consent **and the business need is clear — for example approved kiosks, shared devices, or unattended endpoints. Put** only** those devices in `RHELP-Scope-Unattended-Devices` (Step 2.3).

1. **Assign one owning tier.** Grant unattended handling to **Tier 3 only** (`RHELP-T3-Agents` via

`RHELP Role – Tier 3 Elevation`). No other tier gets unattended.

1. **Set guardrails (documented policy):**

• Every unattended session **requires an approved change/ticket** referencing the device.

• Unattended sessions are **logged to the ticket** (Step 5) and **flagged as unattended** in

reporting (Step 6).

• Unattended scope membership is **reviewed** on a fixed cadence (for example monthly).

1. **Enable the capability** (if and where Microsoft offers it) for the unattended scope only, per

current Microsoft documentation. **Do not** enable it tenant-wide or for attended scopes.

> *If Microsoft does **not** offer unattended assistance for your platform/scenario, record that in the policy and route those cases to an alternative governed path — do not work around it.*

Step 5 — Assign the roles with scope, and wire the session-to-ticket workflow

5a — Assign each role to its tier group with its scope (Intune)

1. Intune → **Tenant administration** → **Roles** → open `RHELP Role – Tier 1 View` → **Assignments →

Assign**.** Assignment name: `RHELP Assignment – Tier 1`**.** Members (groups): `RHELP-T1-Agents`**.** Scope (Groups): `RHELP-Scope-Standard-Users`**.** Save**.

1. Open `RHELP Role – Tier 2 Control` → **Assignments** → **Assign**. **Assignment name:**

`RHELP Assignment – Tier 2`. **Members:** `RHELP-T2-Agents`. **Scope (Groups):** `RHELP-Scope-Standard-Users`. **Save**.

1. Open `RHELP Role – Tier 3 Elevation` → **Assignments** → **Assign**. **Assignment name:**

`RHELP Assignment – Tier 3`. **Members:** `RHELP-T3-Agents`. **Scope (Groups):** `RHELP-Scope-Standard-Users`, `RHELP-Scope-VIP-Users`, and (for unattended) `RHELP-Scope-Unattended-Devices`. **Save**.

> ***How scope limits "who can help whom":*** *the role* ***scope*** *is what restricts an agent tier to its intended user population. *(Exactly how Remote Help evaluates scope groups vs. scope tags to gate a session — **verify against current Microsoft documentation**; this guide assigns scope by group as the intended control.)* Validate it in Testing (Section 5) before you trust it.*

5b — Define the session-to-ticket workflow (process)

Document this as the standard agent procedure (no portal change — this is the operating process):

1. **Intake.** A ticket is created in your ITSM system. The agent works from the ticket, never

ad-hoc.

1. **Verify the caller.** The agent confirms the user's identity per your verification policy

before starting any session.

1. **Right tier / right scope.** Tier 1 handles standard requests within `RHELP-Scope-Standard-Users`;

Tier 2 takes control cases; Tier 3 takes VIP (`RHELP-Scope-VIP-Users`) and unattended cases.

1. **Start the session** from the ticket context (attended: user consents in Remote Help;

unattended: only per Step 4 governance).

1. **Escalate when needed.** If out of tier capability or scope, the agent escalates the **ticket**

to the next tier — they do **not** exceed their role. Escalation moves the ticket, which moves the authorized tier.

1. **Log & hand off.** On completion the agent records on the ticket: session start/end time,

attended vs unattended, actions taken, and outcome (resolved / escalated). Unattended sessions additionally reference the approving change/ticket.

Step 6 — Stand up usage & outcome reporting

1. Define the KPIs you will report (see Section 7 for the recommended set): session volume per tier,

average handle time, first-contact resolution, escalation rate, consent/decline rate, unattended session count, and adoption rate.

1. Run `RHELPOPS-Report.ps1` to export usage/outcome/adoption KPIs to CSV on your cadence (for example weekly). *(The exact Remote Help usage data available via the portal vs. Graph — **verify against current Microsoft documentation**; the script exports what is available and marks gaps.)*

1. Cross-reference the export with your ITSM ticket data (from Step 5b logging) to complete outcome and adoption KPIs the platform alone cannot show.

Step 7 — Pilot, then run the adoption campaign

7a — Pilot (one tier, small scope)

1. Start with **Tier 1** (`RHELP-T1-Agents`) and a small subset of `RHELP-Scope-Standard-Users`.

2. Run `RHELPOPS-Validate.ps1` → confirms the role/scope model is in place and reporting is available.

1. Run `RHELPOPS-Test-Scope.ps1` → proves a Tier 1 agent is scoped to the intended users **and no more**.

1. Complete the **Testing Guide** (Section 5) for the pilot before expanding.

7b — Adoption campaign

1. **End-user comms.** Publish a short "How to get remote help" note: how to request help (raise a ticket), what to expect (an Entra-authenticated agent, a **consent prompt**, and that sessions are **audited**), and — where applicable — that some approved devices may receive **governed unattended assistance**. Set trust/consent expectations plainly.

1. **Self-service entry point.** Point users to the single request path (the ticket queue) so demand is captured and measurable.

1. **Agent enablement.** Train each tier on its capability, its scope, the escalation rule, and the session-to-ticket logging. Make clear an agent never exceeds their tier — they escalate the ticket.

1. **Measure adoption.** Track the adoption rate KPI (share of eligible tickets using Remote Help) from Step 6 and iterate the comms where uptake is low.

Step 8 — Expand across tiers

1. Add **Tier 2** and **Tier 3** to live handling; extend `RHELP-Scope-Standard-Users` / `RHELP-Scope-VIP-Users` to the full populations in waves.

1. Bring `RHELP-Scope-Unattended-Devices` online only after the Step 4 governance and a successful unattended validation (Section 5).

1. Re-run `RHELPOPS-Validate.ps1` and `RHELPOPS-Test-Scope.ps1` each wave; keep reporting on the weekly cadence.

Order of operations

`Tier agent groups → Scope groups → Per-tier RBAC roles → Unattended governance → Role assignments (with scope) + session-to-ticket workflow → Reporting → Pilot + adoption campaign → Expand`

5. Testing Guide — Remote Help Operations & Adoption

Run after the pilot setup (Implementation Step 7a) and after each expansion wave. Each test has an explicit **PASS/FAIL**. All object names match Section 3 exactly.

Test 1 — An agent can help only in-scope users

Do: As a **Tier 1** agent (`RHELP-T1-Agents`), start a Remote Help session to a user **in** `RHELP-Scope-Standard-Users`; then attempt a user **not** in any scope assigned to Tier 1 (for example a `RHELP-Scope-VIP-Users`-only user). Also run `RHELPOPS-Test-Scope.ps1`. **PASS:** The in-scope session is permitted; the out-of-scope attempt is **not** available/permitted, and `RHELPOPS-Test-Scope.ps1` reports the Tier 1 scope resolves to the intended users **and no more**. **FAIL:** A Tier 1 agent can help a user outside `RHELP-Scope-Standard-Users`.

Test 2 — Capability matches the tier

Do: Verify a **Tier 1** session is **view-only** (no control), a **Tier 2** session allows **full control**, and a **Tier 3** session allows control **and** elevation. **PASS:** Each tier has exactly its intended capability (`RHELP Role – Tier 1 View` / `RHELP Role – Tier 2 Control` / `RHELP Role – Tier 3 Elevation`). **FAIL:** A tier has more (or less) capability than its role defines — for example Tier 1 can take control.

Test 3 — Unattended access works only where governed

Do: As **Tier 3**, attempt an unattended session to a device **in** `RHELP-Scope-Unattended-Devices` (with the approving change/ticket); then attempt an unattended session to a device **not** in that group, and attempt unattended as **Tier 1/Tier 2**. **PASS:** Unattended succeeds **only** for approved devices **and only** for Tier 3; every non-approved device and every non-Tier-3 attempt is refused. **FAIL:** Unattended works on a non-approved device, or a non-Tier-3 tier can run unattended. *(If Microsoft does not offer unattended for your platform, this test's PASS is: no unattended path exists anywhere, and the policy records that — **verify against current Microsoft documentation**.)*

Test 4 — A session is logged to a ticket

Do: Run an attended session end-to-end from a ticket, then inspect the ticket. **PASS:** The ticket records session start/end time, attended vs unattended, actions taken, and outcome (resolved/escalated), per Step 5b. Unattended sessions also reference the approving change. **FAIL:** A completed session leaves no ticket record, or is missing the required fields.

Test 5 — Escalation moves the ticket (and the authorized tier)

Do: As Tier 1, hit a case beyond your capability/scope and escalate. **PASS:** The **ticket** moves to Tier 2/Tier 3, and the higher tier (not the Tier 1 agent) performs the control/elevation/VIP action. The Tier 1

agent never exceeds `RHELP Role – Tier 1 View`. **FAIL:** An agent exceeds their tier instead of escalating the ticket.

Test 6 — KPIs report

Do: Run `RHELPOPS-Report.ps1` for the reporting window and review the CSV; run `RHELPOPS-Validate.ps1`. **PASS:** The report produces the defined KPIs (session volume per tier, average handle time, first-contact resolution, escalation rate, consent/decline rate, unattended session count, adoption rate) — populated from Remote Help usage plus ITSM ticket data — and `RHELPOPS-Validate.ps1` reports the role/scope model in place, reporting available, and unattended governed. **FAIL:** KPIs cannot be produced, or `RHELPOPS-Validate.ps1` reports the model/reporting/unattended governance is missing.

Test 7 — Adoption is measurable

Do: Confirm the single request path (ticket queue) is the entry point and that the adoption-rate KPI (share of eligible tickets using Remote Help) is populated for the pilot population. **PASS:** Adoption rate is being measured from the defined entry point. **FAIL:** There is no single request path, or adoption cannot be measured.

Pass/fail gate

Gate	Requirement
Pilot pass	Tests 1, 2, 4, 6, 7 pass for the pilot tier/scope (Test 3 if unattended is in scope)
Wave pass	Tests 1, 2, 4, 6 pass before the next expansion wave
Unattended go-live	Test 3 passes before `RHELP-Scope-Unattended-Devices` goes live

6. Troubleshooting Guide — Remote Help Operations & Adoption

Use `RHELPOPS-Discovery.ps1` to see the current role/scope model, `RHELPOPS-Validate.ps1` for a PASS/FAIL check of the whole model, `RHELPOPS-Test-Scope.ps1` to prove a tier's reach, and `RHELPOPS-Report.ps1` for KPI data. Object names match the Implementation Guide exactly.

> *This layer assumes Remote Help is already deployed (base `remote-help` solution). If the app won't enable/install or a session won't connect **at all**, that is a base-deployment issue — see the base Remote Help solution's troubleshooting, not this one.*

A. Agent can't help / wrong scope

Symptom	Cause	Remediation
Agent can't help a user they should	Agent not in the tier group, or the scope group doesn't contain that user	Add the agent to `RHELP-T1/2/3-Agents`; add the user to the correct `RHELP-Scope-*` group; run `RHELPOPS-Test-Scope.ps1`
Agent **can** help a user they should NOT (over-reach)	Role scope too broad, or tier assigned an extra scope group	Run `RHELPOPS-Test-Scope.ps1` (reports over-reach); remove the extra scope group from that tier's assignment (`RHELP Assignment – Tier N`)
Agent has more control than intended (e.g. Tier 1 can take control)	Wrong role on the tier	Confirm the tier uses its role — Tier 1 → `RHELP Role – Tier 1 View`, Tier 2 → …`Control`, Tier 3 → …`Elevation`; re-assign with `RHELPOPS-Set-RoleScope.ps1`
Scope seems ignored	How Remote Help evaluates scope groups vs. scope tags may differ from expectation	**Verify the current scope-gating behavior against Microsoft documentation**; re-run Testing Test 1 to confirm the actual boundary before trusting it

B. Unattended access not available / not among tiers

Symptom	Cause	Remediation
Unattended option missing entirely	Remote Help may not offer unattended for your platform/scenario, or it isn't enabled	**Verify availability against current Microsoft documentation**; if unsupported, record it in the policy and route those cases to an alternative governed path — do not work around it
Unattended works on a device it shouldn't	Device wrongly in `RHELP-Scope-Unattended-Devices`	Remove the device from the group; keep only approved kiosks/shared/no-consent devices
A non-Tier-3 tier can run unattended	Unattended scope attached to a role other than Tier 3	Detach `RHELP-Scope-Unattended-Devices` from Tier 1/Tier 2 assignments; keep it only on `RHELP Assignment – Tier 3`; re-run `RHELPOPS-Validate.ps1`
Unattended session has no approving change	Guardrail skipped	Enforce the change/ticket precondition (Step 4.3); reject sessions without it

C. Session not logged to a ticket

Symptom	Cause	Remediation
Completed session leaves no ticket record	Agent started ad-hoc, not from a ticket	Enforce "every session starts from a ticket" (Step 5b.1); coach the agent
Ticket record missing required fields	Logging step skipped	Require start/end time, attended/unattended, actions, and outcome on close (Step 5b.6); add it to the ticket template
Can't tie platform activity to a ticket	No ticket id captured	Record the `TicketId` in the session log so `RHELPOPS-Report.ps1` output can be joined to ITSM data

D. KPIs missing / can't report

Symptom	Cause	Remediation
`RHELPOPS-Report.ps1` returns nothing	Reporting access missing, or the Graph usage endpoint differs	Grant the reporting account read access; **verify the current Remote Help usage endpoint/scopes against Microsoft documentation**; fall back to Intune → Tenant administration → Remote Help usage report
Volume shows but outcome/adoption KPIs blank	Those KPIs need ITSM data	Enrich the CSV with ticket data (attended/unattended, handle time, FCR, escalation, ticket id) per the provided columns
Per-tier split missing	Tier isn't derivable from platform data alone	Map the agent to its tier group (from `RHELPOPS-Discovery.ps1`) when enriching the report
`RHELPOPS-Validate.ps1` FAILs "reporting reachable"	Audit/usage endpoint didn't respond	Confirm scopes/permissions and endpoint; retry

E. Low adoption

Symptom	Cause	Remediation
Users don't request help / low adoption rate	No single request path or unclear comms	Publish the "How to get remote help" note (Step 7b.1); make the ticket queue the one entry point
Users decline sessions	Trust/consent not set	State plainly that agents are Entra-authenticated, sessions need **consent**, and are **audited**

Symptom	Cause	Remediation
Agents don't use the tool	Enablement gap	Train each tier on capability, scope, escalation, and logging (Step 7b.3)
Adoption can't be measured	No defined entry point/KPI	Define the adoption-rate KPI (eligible tickets using Remote Help) and measure from the ticket queue

F. Scripts

Run from a workstation with the **Microsoft Graph PowerShell SDK** installed (`Install-Module Microsoft.Graph -Scope CurrentUser`). All are read-only **except** `RHELPOPS-Set-RoleScope.ps1`, which **defaults to** `-WhatIf` (dry run) and changes nothing until you pass `-WhatIf:$false`.

Script	Use it when
`RHELPOPS-Discovery.ps1`	You need to see the current role assignments, scope groups, and who-can-help-whom
`RHELPOPS-Validate.ps1`	You want a PASS/FAIL on role/scope model, reporting, and unattended governance
`RHELPOPS-Test-Scope.ps1`	You must prove a tier is scoped to the intended users and no more (over-reach/gap)
`RHELPOPS-Report.ps1`	You need the usage/outcome/adoption KPI export (CSV)
`RHELPOPS-Set-RoleScope.ps1`	You want to apply/adjust one tier's role+scope binding (dry-run first)

```
# See the current model
powershell -ExecutionPolicy Bypass -File .\RHELPOPS-Discovery.ps1

# Validate the whole operating model (exit code = number of failed checks)
powershell -ExecutionPolicy Bypass -File .\RHELPOPS-Validate.ps1

# Prove Tier 1 is scoped to standard users and no more
powershell -ExecutionPolicy Bypass -File .\RHELPOPS-Test-Scope.ps1 -TierAgentGroup RHELP-T1-Agents -Expect

# Export KPIs
powershell -ExecutionPolicy Bypass -File .\RHELPOPS-Report.ps1 -Days 30 -CsvPath C:\Temp\rhelpops-kpis.csv

# Assign a role+scope to a tier (DRY RUN by default; add -WhatIf:$false to commit)
powershell -ExecutionPolicy Bypass -File .\RHELPOPS-Set-RoleScope.ps1 -RoleName 'RHELP Role – Tier 1 View'
```

G. When to escalate

If the role/scope model validates (`RHELPOPS-Validate.ps1` PASS), scope proves correct (`RHELPOPS-Test-Scope.ps1` PASS), unattended is governed to Tier 3 only, and sessions still behave unexpectedly (scope not honored, unattended behaving differently than documented), capture the behavior and **verify the current Remote Help capability against Microsoft documentation**; if it still

conflicts, open a Microsoft Intune support case with the role/assignment details.

7. Best Practices — Remote Help Operations & Adoption

Role & scope design

• **One role per tier, one capability per tier.** Keep `RHELP Role – Tier 1 View` view-only, reserve full control for `RHELP Role – Tier 2 Control`, and elevation for `RHELP Role – Tier 3 Elevation`. Never blur capabilities across tiers.

• **Scope is the "who," role is the "what."** Use scope groups (`RHELP-Scope-Standard-Users`, `RHELP-Scope-VIP-Users`) to limit who each tier can help; use the role to limit what they can do.

• **Keep scope groups Assigned, not Dynamic.** An agent's reach should widen only by a deliberate, auditable change — never automatically.

• **Route VIP/executive support to a dedicated tier.** Handle `RHELP-Scope-VIP-Users` at Tier 3 so sensitive users get consistent, senior handling.

Unattended access

• **Treat unattended as an exception, not a default.** Grant it to **Tier 3 only** and only for devices in `RHELP-Scope-Unattended-Devices`.

• **Require a change/ticket for every unattended session** and flag it as unattended in reporting.

• **Review the unattended device scope on a cadence** (for example monthly) and remove devices that no longer need it.

• **Verify the capability before you rely on it.** Whether Remote Help offers unattended access, on which platforms, and how consent behaves must be confirmed against current Microsoft documentation.

Workflow & escalation

• **Every session starts from a ticket** — no ad-hoc help. It is the record, the scope, and the KPI source.

• **Verify the caller before connecting**, every time.

• **Escalate the ticket, never exceed the role.** When a case is beyond a tier, the ticket moves to the tier that is authorized — the agent does not.

• **Log the session on the ticket on completion** (time, attended/unattended, actions, outcome).

Measurement & adoption

• **Define KPIs up front** and report them on a fixed cadence with `RHELPOPS-Report.ps1`.

• **Combine platform usage with ITSM data** — outcome and adoption KPIs need both.

• **Give end users one request path** and set consent/audit expectations plainly so they trust it.

• **Enable agents on scope, capability, escalation, and logging** — adoption fails when agents are unsure what they may do.

• **Iterate the comms where uptake is low** — a downward escalation rate and a rising adoption rate mean the model is working.

Hygiene

• **Document the role/scope model** (which tier, which role, which scope) for audits.

• **Re-validate each wave** with `RHELPOPS-Validate.ps1` and `RHELPOPS-Test-Scope.ps1`.

• **Confirm current portal labels and role/permission names** against Microsoft documentation before each major change — they drift.

8. Deliverables Summary — Remote Help Operations & Adoption

> ***Prerequisite:*** *the base* ***Remote Help*** *solution (slug* `remote-help`*) — this package is the operations/adoption layer on top of it and does not repeat install/enable/security-model setup.*

Documentation

Document	Purpose
Executive Summary	Business case: turning a Remote Help deployment into a running help-desk capability
1. Solution Overview	The operating model, what this adds vs. the base product, benefits, limitations
2. Requirements Guide	Every prerequisite with Verify / Implement-if-missing (base deployment, tiers, RBAC, licensing, ticketing, reporting)
Global Requirements (Intune Solutions)	Category-wide prerequisites, published once
3. Implementation Guide	Ordered steps: tier groups, scope groups, per-tier RBAC roles, unattended governance, role assignment + session-to-ticket workflow, reporting, pilot + adoption, expand
5. Testing Guide	PASS/FAIL validation (in-scope only, capability per tier, governed unattended, ticket logging, escalation, KPIs, adoption)

Document	Purpose
6. Troubleshooting Guide	Field issues and remediation (wrong scope, unattended not available, session not logged, KPIs missing, low adoption)
7. Best Practices	Field-proven recommendations for role/scope, unattended, workflow, and adoption

PowerShell scripts

Script	What it does
`RHELPOPS-Discovery.ps1`	Read-only: reports existing Remote Help RBAC role assignments, scope groups, and who-can-help-whom
`RHELPOPS-Validate.ps1`	PASS/FAIL: role/scope model in place, reporting available, unattended governed
`RHELPOPS-Report.ps1`	Exports usage/outcome/adoption KPIs to CSV
`RHELPOPS-Test-Scope.ps1`	Read-only: proves an agent tier is scoped to the intended users and no more
`RHELPOPS-Set-RoleScope.ps1`	The only state-changer: assigns a Remote Help RBAC role + scope group to a help-desk tier. **Defaults to `-WhatIf`.**

What the buyer receives

- This operations/adoption guide as a **Word** document and **PDF**.
- All five **PowerShell scripts** in a single ZIP.
- A repeatable process following the standard model: **Assess** → **Configure** → **Pilot** → **Validate** → **Expand.**

Outcome

Remote Help running as a real help-desk capability — right-scoped tier roles, governed unattended access, a session-to-ticket workflow with escalation, outcome/adoption reporting, and end-user adoption — not just an installed app.

Appendix A — PowerShell Scripts

Included in the accompanying ZIP. Each script's header documents full usage.

RHELPOPS-Discovery.ps1

Purpose: Reports the current Remote Help RBAC role assignments, the scope groups attached to them, and — from that — who-can-help-whom. Use it to see the operating model as it exists today before you design or change tiers. This is the OPERATIONS layer; it assumes Remote Help is already deployed (see the base "Remote Help" solution). HOW TO RUN powershell -ExecutionPolicy Bypass -File .\RHELPOPS-Discovery.ps1 Requires the Microsoft Graph PowerShell SDK. Sign in with an account that can read Intune RBAC and Entra groups. GRAPH SCOPES DeviceManagementRBAC.Read.All, Group.Read.All, User.Read.All (Exact scopes/endpoints that expose Remote Help role assignments and their scope members may change — verify against current Microsoft documentation.) EXPECTED RESULTS A console table of each Intune role definition, its assignments, the member (agent) groups, and the scope groups — i.e. which tier can help which user population. Read-only; changes nothing. .NOTES White-label — Intune Solutions. Read-only against Graph. Verify current role/permission names and Graph endpoints against Microsoft documentation. > [CmdletBinding()] param()

How to run: powershell -ExecutionPolicy Bypass -File .\RHELPOPS-Discovery.ps1 Requires the Microsoft Graph PowerShell SDK. Sign in with an account that can read Intune RBAC and Entra groups. GRAPH SCOPES DeviceManagementRBAC.Read.All, Group.Read.All, User.Read.All (Exact scopes/endpoints that expose Remote Help role assignments and their scope members may change — verify against current Microsoft documentation.) EXPECTED RESULTS A console table of each Intune role definition, its assignments, the member (agent) groups, and the scope groups — i.e. which tier can help which user population. Read-only; changes nothing. .NOTES White-label — Intune Solutions. Read-only against Graph. Verify current role/permission names and Graph endpoints against Microsoft documentation. > [CmdletBinding()] param()

RHELPOPS-Report.ps1

Purpose: Pulls the Remote Help usage/audit activity available via Graph and shapes it into the operating-model KPIs: session volume (overall and, where derivable, per tier), attended vs unattended counts, and the raw activity needed to compute average handle time, first-contact resolution, escalation rate, consent/decline rate, and adoption rate. Outcome/adoption KPIs that the platform cannot show are exported as columns for you to complete from ITSM ticket data. Read-only. HOW TO RUN powershell -ExecutionPolicy Bypass -File .\RHELPOPS-Report.ps1 -Days 30 -CsvPath C:\Temp\rhelpops-kpis.csv Requires the Microsoft Graph PowerShell SDK. GRAPH SCOPES DeviceManagementApps.Read.All, AuditLog.Read.All (Verify the current Remote Help usage endpoint/scopes against Microsoft documentation — the data exposed via Graph vs. the Intune portal usage report changes over time.) EXPECTED RESULTS A console summary of the KPIs that can be computed from platform data, plus a CSV at -CsvPath containing per-session rows and KPI columns (platform-derived populated; ITSM-dependent left blank to fill from ticket data). Changes nothing. .NOTES White-label — Intune Solutions. Read-only against Graph. Combine this export with your ITSM ticket data to complete outcome + adoption KPIs. > [CmdletBinding()] param([int]$Days = 30, [string]$CsvPath)

How to run: powershell -ExecutionPolicy Bypass -File .\RHELPOPS-Report.ps1 -Days 30 -CsvPath C:\Temp\rhelpops-kpis.csv Requires the Microsoft Graph PowerShell SDK. GRAPH SCOPES DeviceManagementApps.Read.All, AuditLog.Read.All (Verify the current Remote Help usage

endpoint/scopes against Microsoft documentation — the data exposed via Graph vs. the Intune portal usage report changes over time.) EXPECTED RESULTS A console summary of the KPIs that can be computed from platform data, plus a CSV at -CsvPath containing per-session rows and KPI columns (platform-derived populated; ITSM-dependent left blank to fill from ticket data). Changes nothing. .NOTES White-label — Intune Solutions. Read-only against Graph. Combine this export with your ITSM ticket data to complete outcome + adoption KPIs. > [CmdletBinding()] param([int]$Days = 30, [string]$CsvPath)

RHELPOPS-Set-RoleScope.ps1

Purpose: Creates an Intune role assignment that binds a Remote Help RBAC role to a tier's agent group (members) with a scope group (the users that tier may help) — i.e. it wires one row of the operating model from the Implementation Guide (Step 5a). Use it to apply or adjust a single tier's role/scope without clicking through the portal. HOW TO RUN Dry run (default — shows exactly what WOULD change, changes nothing): powershell -ExecutionPolicy Bypass -File .\RHELPOPS-Set-RoleScope.ps1 `-RoleName 'RHELP Role – Tier 1 View' -AgentGroup 'RHELP-T1-Agents'` -ScopeGroup 'RHELP-Scope-Standard-Users' -AssignmentName 'RHELP Assignment – Tier 1' Commit the change (explicit opt-in): ... same command ... -WhatIf:$false Requires the Microsoft Graph PowerShell SDK and rights to manage Intune RBAC. GRAPH SCOPES DeviceManagementRBAC.ReadWrite.All, Group.Read.All (Verify the current role-assignment endpoint/payload shape against Microsoft documentation before committing — it changes over time.) EXPECTED RESULTS In -WhatIf mode: prints the resolved role, agent group, scope group, and the assignment it WOULD create — and exits without writing. With -WhatIf:$false: creates the role assignment and prints its id. .NOTES White-label — Intune Solutions. State-changing (guarded). Defaults to -WhatIf = no change. Object names match the Implementation Guide (RHELP Role – Tier *, RHELP-T*-Agents, RHELP-Scope-*). > [CmdletBinding(SupportsShouldProcess=$true, ConfirmImpact='High')] param([Parameter(Mandatory)][string]$RoleName, [Parameter(Mandatory)][string]$AgentGroup, [Parameter(Mandatory)][string]$ScopeGroup, [string]$AssignmentName = 'RHELP Assignment', DEFAULT-SAFE: dry run unless the caller explicitly sets -WhatIf:$false [switch]$WhatIf = $true)

How to run: Dry run (default — shows exactly what WOULD change, changes nothing): powershell -ExecutionPolicy Bypass -File .\RHELPOPS-Set-RoleScope.ps1 `-RoleName 'RHELP Role – Tier 1 View' -AgentGroup 'RHELP-T1-Agents'` -ScopeGroup 'RHELP-Scope-Standard-Users' -AssignmentName 'RHELP Assignment – Tier 1' Commit the change (explicit opt-in): ... same command ... -WhatIf:$false Requires the Microsoft Graph PowerShell SDK and rights to manage Intune RBAC. GRAPH SCOPES DeviceManagementRBAC.ReadWrite.All, Group.Read.All (Verify the current role-assignment endpoint/payload shape against Microsoft documentation before committing — it changes over time.) EXPECTED RESULTS In -WhatIf mode: prints the resolved role, agent group, scope group, and the assignment it WOULD create — and exits without writing. With -WhatIf:$false: creates the role assignment and prints its id. .NOTES White-label — Intune Solutions. State-changing (guarded). Defaults to -WhatIf = no change. Object names match the Implementation Guide (RHELP Role – Tier *, RHELP-T*-Agents, RHELP-Scope-*). > [CmdletBinding(SupportsShouldProcess=$true, ConfirmImpact='High')] param([Parameter(Mandatory)][string]$RoleName, [Parameter(Mandatory)][string]$AgentGroup, [Parameter(Mandatory)][string]$ScopeGroup, [string]$AssignmentName = 'RHELP Assignment', DEFAULT-SAFE: dry run unless the caller explicitly sets -WhatIf:$false [switch]$WhatIf = $true)

RHELPOPS-Test-Scope.ps1

Purpose: For a given tier, resolves the users the tier CAN help (the union of the scope groups on that tier's Remote Help role assignments) and compares them to the users you EXPECT it to help. Reports the

overlap plus any users the tier can reach that it should NOT ("over-reach") and any it should reach but cannot ("gap"). This is the read-only proof behind Testing Test 1. Changes nothing. HOW TO RUN powershell -ExecutionPolicy Bypass -File .\RHELPOPS-Test-Scope.ps1 -TierAgentGroup RHELP-T1-Agents -ExpectedScopeGroup RHELP-Scope-Standard-Users Requires the Microsoft Graph PowerShell SDK. GRAPH SCOPES DeviceManagementRBAC.Read.All, Group.Read.All, User.Read.All (Verify current endpoints that expose role assignments + scope members against Microsoft docs.) EXPECTED RESULTS Counts and PASS/FAIL: PASS when the tier's reachable users equal the expected scope (no over-reach); FAIL when the tier can reach any user outside the expected scope. .NOTES White-label — Intune Solutions. Read-only against Graph. Object names match the Implementation Guide (RHELP-T*-Agents, RHELP-Scope-*). > [CmdletBinding()] param([Parameter(Mandatory)][string]$TierAgentGroup, [Parameter(Mandatory)][string]$ExpectedScopeGroup)

How to run: powershell -ExecutionPolicy Bypass -File .\RHELPOPS-Test-Scope.ps1 -TierAgentGroup RHELP-T1-Agents -ExpectedScopeGroup RHELP-Scope-Standard-Users Requires the Microsoft Graph PowerShell SDK. GRAPH SCOPES DeviceManagementRBAC.Read.All, Group.Read.All, User.Read.All (Verify current endpoints that expose role assignments + scope members against Microsoft docs.) EXPECTED RESULTS Counts and PASS/FAIL: PASS when the tier's reachable users equal the expected scope (no over-reach); FAIL when the tier can reach any user outside the expected scope. .NOTES White-label — Intune Solutions. Read-only against Graph. Object names match the Implementation Guide (RHELP-T*-Agents, RHELP-Scope-*). > [CmdletBinding()] param([Parameter(Mandatory)][string]$TierAgentGroup, [Parameter(Mandatory)][string]$ExpectedScopeGroup)

RHELPOPS-Validate.ps1

Purpose: Checks that the help-desk operating model is actually in place: (1) the per-tier role/scope model exists (tier agent groups assigned to Remote Help roles with scope groups), (2) usage/audit reporting is reachable, and (3) unattended access is governed (an approved unattended scope group exists and is only attached to the Tier 3 role). Prints PASS or FAIL per check. Read-only; changes nothing. HOW TO RUN powershell -ExecutionPolicy Bypass -File .\RHELPOPS-Validate.ps1 Requires the Microsoft Graph PowerShell SDK. GRAPH SCOPES DeviceManagementRBAC.Read.All, Group.Read.All, DeviceManagementApps.Read.All, AuditLog.Read.All (Verify the current scopes/endpoints that expose Remote Help role assignments and usage against Microsoft documentation.) EXPECTED RESULTS A PASS/FAIL line per check and an overall result. Any FAIL tells you which part of the model (role/scope, reporting, unattended governance) is missing. .NOTES White-label — Intune Solutions. Read-only against Graph. Object names match the Implementation Guide (RHELP-T1/2/3-Agents, RHELP-Scope-*, RHELP Role - Tier *). > [CmdletBinding()] param([string[]]$TierAgentGroups = @('RHELP-T1-Agents','RHELP-T2-Agents','RHELP-T3-Agents'), [string[]]$ScopeGroups = @('RHELP-Scope-Standard-Users','RHELP-Scope-VIP-Users'), [string]$UnattendedScope = 'RHELP-Scope-Unattended-Devices', [string]$Tier3Role = 'RHELP Role – Tier 3 Elevation')

How to run: powershell -ExecutionPolicy Bypass -File .\RHELPOPS-Validate.ps1 Requires the Microsoft Graph PowerShell SDK. GRAPH SCOPES DeviceManagementRBAC.Read.All, Group.Read.All, DeviceManagementApps.Read.All, AuditLog.Read.All (Verify the current scopes/endpoints that expose Remote Help role assignments and usage against Microsoft documentation.) EXPECTED RESULTS A PASS/FAIL line per check and an overall result. Any FAIL tells you which part of the model (role/scope, reporting, unattended governance) is missing. .NOTES White-label — Intune Solutions. Read-only against Graph. Object names match the Implementation Guide (RHELP-T1/2/3-Agents, RHELP-Scope-*, RHELP Role - Tier *). > [CmdletBinding()] param([string[]]$TierAgentGroups = @('RHELP-T1-Agents','RHELP-T2-Agents','RHELP-T3-Agents'), [string[]]$ScopeGroups =

```
@('RHELP-Scope-Standard-Users','RHELP-Scope-VIP-Users'), [string]$UnattendedScope =
'RHELP-Scope-Unattended-Devices', [string]$Tier3Role = 'RHELP Role – Tier 3 Elevation' )
```