iOS/iPadOS Intune Enrollment "Access Denied / Not Authorized" — Root-Cause & Remediation (License, MDM Scope, Enrollment Restrictions & Conditional Access) Troubleshooting Guide

Implementation Solution Guide

Version 1.0.0 · 2026-09-01

Contents

Executive Summary 4
- The situation . . . 4
- Why it matters . . . 4
- The approach . . . 4
- What you get . . . 4
- The outcome . . . 4

Solution Overview 5
- What this solution is . . . 5
- What the screen actually means . . . 5
- The gates that produce it (in order of likelihood) . . . 5
- How you diagnose it — the deterministic path . . . 5
- The standard deployment model . . . 6
- Benefits . . . 6
- Limitations & scope . . . 6

Requirements 6
- 1. Intune administrator + Entra read access . . . 6
- 2. The diagnostic IDs from the failure screen . . . 7
- 3. Microsoft Graph PowerShell . . . 7
- 4. Confirmation of enrollment type (BYO vs corporate/ADE) . . . 7
- 5. Ability to reproduce and retry on the device . . . 7
- 6. Change approval for MDM scope / restriction / CA changes . . . 8

Global Requirements — Intune Solutions (category-level) 8
- G1. Microsoft Entra ID tenant . . . 8
- G2. Microsoft Intune subscription . . . 8
- G3. Administrative roles . . . 8
- G4. Device enrollment in Intune . . . 9
- G5. Pilot security group . . . 9
- G6. Supported Windows baseline . . . 9
- G7. Network access to Microsoft cloud endpoints . . . 9

Implementation — Root-Cause & Remediation Guide 9
- Phase 1 — Capture and read the failed sign-in (the deterministic step) . . . 9
- Phase 2 — Check and remediate the gate . . . 10
- Phase 3 — Re-enroll and validate . . . 11
- Phase 4 — Prevent recurrence . . . 11

Testing & Validation 11

Test 1 — Reproduce and capture (baseline) . . . 11
Test 2 — Root cause is identified from evidence (not guessed) . . . 11
Test 3 — Gate script confirms the finding . . . 12
Test 4 — Remediation applied (single, scoped change) . . . 12
Test 5 — Clean re-enrollment (the definitive test) . . . 12
Test 6 — No collateral impact . . . 12
Evidence to keep . . . 12
Troubleshooting Guide 13
A. The core failure: "Access Denied — you are not authorized to view this page" . . . 13
B. "Require compliant device" chicken-and-egg . . . 13
C. Enrollment succeeds for some users but not others . . . 14
D. ADE/corporate device: "Access Denied" during Setup Assistant . . . 14
E. Fixed the gate but the device still shows the screen . . . 14
F. Sovereign cloud (GCC High / DoD) . . . 14
Escalation . . . 15
Best Practices 15
Diagnose from evidence, not symptoms . . . 15
Change discipline . . . 15
Design out the common causes . . . 15
Prevent recurrence . . . 15
Evidence & handoff . . . 16
Sovereign clouds . . . 16
Deliverables Summary 16
Documentation (compiled to PDF) . . . 16
PowerShell tools (packaged as a ZIP) . . . 17
Scope . . . 17
Appendix A — PowerShell Scripts 18

Executive Summary

The situation

A user enrolling an iPhone or iPad into Microsoft Intune hits an **"Access Denied — you are not authorized to view this page"** screen, with a block of **Diagnostic information for IT** (Activity Id, Session Id, Timestamp). Enrollment stops. This is **not** a device fault — it is a **tenant-side authorization gate** (licensing, MDM scope, an enrollment restriction, or Conditional Access) refusing the enrollment.

Why it matters

Blocked enrollment means the device can't be managed, secured, or brought into compliance — and the user can't reach corporate resources that require a managed device. Guessing at the cause wastes hours in trial-and-error re-enrollment and can leave a security gap open. The good news: the IDs on the screen make this a **deterministic** diagnosis, not guesswork.

The approach

This solution turns the on-screen diagnostic IDs into an exact root cause and a scoped fix:

1. **Capture** the Activity Id / Session Id / Timestamp / UPN from the failure screen.
2. **Read** the failed enrollment sign-in in the Entra sign-in logs — its failure reason and Conditional Access result name the gate.
1. **Confirm** the gate — license, MDM user scope, enrollment restriction, or Conditional Access — with a dedicated PowerShell check that turns each into a yes/no answer.
1. **Remediate** the single blocking gate, then **re-enroll and validate** that the same sign-in now succeeds and the device appears in Intune.
1. **Prevent** recurrence by fixing the class problem (scope group, restriction assignment, CA pattern).

What you get

- A click-by-click **root-cause-and-remediation runbook** covering every common gate in likelihood order.
- **Five PowerShell tools** — the failed enrollment sign-in reader, plus license, MDM-scope, enrollment-restriction, and Conditional-Access checks.
- **Testing, Troubleshooting/FAQ, and Best-Practice** guidance, with GCC High notes inline.

The outcome

A two-minute root cause from evidence instead of trial-and-error, a surgical fix that doesn't weaken your other controls, the device enrolled and managed, and a prevention step so the next user doesn't hit the same wall. One fixed price; re-run the method for every future "Access Denied" enrollment.

Solution Overview

What this solution is

A focused **root-cause-and-remediation** package for one specific, common iOS/iPadOS enrollment failure: the user starts **Device Management** enrollment into Microsoft Intune and hits an **"Access Denied — You are not authorized to view this page. Your IT department may be able to help"** screen, with a block of **Diagnostic information for IT** (Activity Id, Session Id, Timestamp). It is not a device fault — it is a **tenant-side authorization gate** (licensing, MDM scope, enrollment restrictions, or Conditional Access) refusing the enrollment. This guide turns the diagnostic IDs into the exact reason and fixes it.

What the screen actually means

The "Access Denied / not authorized" page is returned by the Intune **enrollment authorization** service when the signed-in user is **not permitted to enroll**. The **Session Id** and **Activity Id** on the screen are correlation identifiers you look up in the **Entra sign-in logs** and the Intune troubleshooting portal to see precisely which gate blocked the enrollment — so this is a *deterministic* diagnosis, not guesswork.

The gates that produce it (in order of likelihood)

1. **No Intune license on the user.** Enrollment authorizes against the user's license; without an

Intune / EMS service plan the user is "not authorized." This is the most common cause.

1. **User outside the MDM user scope.** In Entra → **Mobility (MDM and WIP)** → **Microsoft Intune**, the

MDM user scope must be **All** or a group that includes the user. If it is **None** or a group they are not in, enrollment is denied.

1. **An enrollment restriction blocks it.** A device-platform restriction disallowing **iOS/iPadOS** or

personally-owned devices, or the **device-limit** restriction (the user is already at their enrolled-device cap).

1. **A Conditional Access policy blocks the sign-in.** A CA policy scoped to the **Microsoft Intune

Enrollment **or** Microsoft Intune** cloud apps that blocks, or imposes a grant the device cannot yet meet — the classic *"require compliant device to enroll"* chicken-and-egg.

1. **An account problem.** A **guest / B2B** account (guests cannot enroll), a blocked/disabled sign-in,

or missing a required group membership.

How you diagnose it — the deterministic path

The IDs on the screen are the fast path:

1. Take the **Session Id** and **Activity Id** with the **timestamp** and open **Entra admin center →

Monitoring → Sign-in logs**; filter to the user/time and the correlation/request ID. The failed sign-in's** failure reason **and its** Conditional Access** tab name the exact gate.

1. Then confirm the specific gate — **license**, **MDM user scope**, **enrollment restriction**, or

CA — with the included scripts, and remediate it.

The standard deployment model

Capture (the diagnostic IDs) → Read the failed enrollment sign-in → Check the four gates (license, MDM scope, restrictions, CA) → Remediate the identified gate → Re-enroll and validate. Every step is evidence-led, and the scripts turn each gate into a yes/no answer.

Benefits

- **Two-minute root cause** from the on-screen IDs instead of trial-and-error re-enrollment.
- **Covers every common gate** — license, MDM scope, enrollment restrictions, Conditional Access, account — in one ordered runbook.
- **Evidence for the ticket** — the failed sign-in, the license/scope/restriction/CA findings, and the successful re-enrollment.
- **Prevention** — fix the class of problem (scope/restriction misconfiguration) so the next user doesn't hit it.

Limitations & scope

- Scope is the **enrollment authorization "Access Denied / not authorized"** failure on iOS/iPadOS. General Intune iOS enrollment setup (ADE/ABM, Company Portal, enrollment profiles) and enrollment-time device grouping are covered by the companion Intune enrollment solutions and referenced, not rebuilt.
- Some checks (the MDM user scope, enrollment-restriction and CA reads) rely on Graph endpoints that evolve; where an API is beta the guide says so and points to the portal as the source of truth.
- **Sovereign clouds:** the gates and method are identical in GCC / GCC High / DoD; portals are `entra.microsoft.us` / `intune.microsoft.us` — called out inline. A single deliverable covers both.

Requirements

Confirm each prerequisite before you begin. Each lists **why** it is required, **how to verify**, and **how to implement** if missing.

1. Intune administrator + Entra read access

- **Description:** A role that can read sign-in logs and edit enrollment configuration — **Intune Administrator **and** Global Reader **/** Security Reader** for the sign-in logs, or least-privilege equivalents.
- **Why required:** You read the failed enrollment sign-in and, where needed, edit MDM scope, enrollment restrictions, or Conditional Access.

• **How to verify:** Sign in to **Entra admin center** (`entra.microsoft.com`; GCC High: `entra.microsoft.us`) → **Sign-in logs**, and **Intune admin center** (`intune.microsoft.com`) → **Devices** → **Enrollment**.

• **How to implement if missing:** Have an admin grant the roles.

2. The diagnostic IDs from the failure screen

• **Description:** The **Activity Id**, **Session Id**, and **Timestamp** shown on the "Access Denied" page (and the affected user's UPN).

• **Why required:** These correlation IDs locate the exact failed sign-in and its failure reason — the deterministic root cause.

• **How to verify:** You have the three values and the user's identity from the screenshot / user.

• **How to implement if missing:** Have the user reproduce the failure and capture the diagnostic block, or provide the UPN and approximate time.

3. Microsoft Graph PowerShell

• **Description:** The **Microsoft.Graph** module to read the sign-in, the user's license, the MDM scope, the enrollment restrictions, and the Conditional Access policies.

• **Why required:** The included scripts turn each gate into a yes/no answer.

• **How to verify:** `Get-Module -ListAvailable Microsoft.Graph`; `Connect-MgGraph` succeeds.

• **How to implement if missing:** `Install-Module Microsoft.Graph -Scope CurrentUser` (scopes include `AuditLog.Read.All`, `Directory.Read.All`, `Policy.Read.All`, `DeviceManagementServiceConfig.Read.All`).

4. Confirmation of enrollment type (BYO vs corporate/ADE)

• **Description:** Whether this device is **personally-owned** (BYO Company Portal enrollment) or **corporate / Automated Device Enrollment (ADE)** via Apple Business Manager.

• **Why required:** The relevant enrollment restriction differs (personal-device block vs ADE profile assignment), and corporate devices add an ABM check.

• **How to verify:** Ask how the device is intended to be managed; check ABM if corporate.

• **How to implement if missing:** Confirm the enrollment type before choosing the remediation path.

5. Ability to reproduce and retry on the device

• **Description:** Access to the affected iOS/iPadOS device (or a test device with the same user) to

remove the management profile and retry enrollment after the fix.

- **Why required:** Validation is a successful re-enrollment plus a successful sign-in in the logs.
- **How to verify:** You can reach the device or a test account.
- **How to implement if missing:** Arrange a test device/account for validation.

6. Change approval for MDM scope / restriction / CA changes

- **Description:** Approved change record before editing the MDM user scope, enrollment restrictions, or a Conditional Access policy.
- **Why required:** These affect enrollment tenant-wide; changes should be staged.
- **How to verify:** Change ticket approved with the identified gate named.
- **How to implement if missing:** Raise the change with the root-cause finding from this guide.

> ***Category-wide prerequisites*** *common to every Intune solution are listed in* `global-requirements-intune-solutions.md`*. General iOS enrollment (ADE/ABM, Company Portal) and enrollment-time device grouping are covered by the companion Intune enrollment solutions.*

Global Requirements — Intune Solutions (category-level)

These requirements apply to **every** solution in the **Intune Solutions** category. They are published once at the category level so individual listings stay small. Confirm these before deploying *any* Intune solution. Each entry: **Description · Why · Verify · Implement-if-missing.**

G1. Microsoft Entra ID tenant

Description: An active Microsoft Entra ID (Azure AD) tenant. **Why:** It is the identity backbone for every cloud and Intune-managed resource. **Verify:** Sign in to `https://entra.microsoft.com` as an administrator. **Implement:** Create a Microsoft 365/Azure subscription, which provisions a tenant.

G2. Microsoft Intune subscription

Description: An Intune-bearing license plan. **Why:** Intune delivers all configuration, compliance, and security policies. **Verify:** `https://intune.microsoft.com` loads; **Tenant administration** → **Tenant status** shows active. **Implement:** Assign Microsoft 365 E3/E5, Business Premium, or standalone Intune Plan 1.

G3. Administrative roles

Description: Appropriate Entra/Intune admin roles for the operator. **Why:** Creating policies and enrollment settings requires elevated rights. **Verify:** Entra → **Roles and administrators**; confirm **Intune Administrator**. **Implement:** Assign **Intune Administrator**; reserve Global Administrator for tenant-wide changes.

G4. Device enrollment in Intune

Description: Targeted Windows devices are enrolled and manageable. **Why:** Policies only reach enrolled devices. **Verify:** Intune → **Devices** → **All devices**; the device appears and is **compliant**. **Implement:** Enable **Automatic Enrollment** and join devices to Entra ID.

G5. Pilot security group

Description: A Microsoft Entra security group for pilot/targeted users or devices. **Why:** Every solution is piloted before fleet rollout. **Verify:** Entra → **Groups**; the pilot group exists. **Implement:** Entra → **Groups** → **New group** → **Security** → add members.

G6. Supported Windows baseline

Description: Windows 10 21H2+ or Windows 11 with current updates. **Why:** Modern Intune features assume a patched, supported OS. **Verify:** `winver`, or Intune → device → **Hardware**. **Implement:** Deploy **Update rings** or upgrade to Windows 11.

G7. Network access to Microsoft cloud endpoints

Description: Outbound HTTPS to Microsoft 365, Entra, and Intune service URLs. **Why:** Enrollment, policy sync, and authentication depend on these endpoints. **Verify:** From a device, reach `https://login.microsoftonline.com` and `https://enrollment.manage.microsoft.com`. **Implement:** Allow Microsoft's published Office 365/Intune URL & IP ranges through proxy/firewall.

The standard deployment model (all solutions): Assess → Configure → Pilot → Validate → Expand.

Implementation — Root-Cause & Remediation Guide

The step-by-step runbook: capture the diagnostic IDs, read the failed enrollment sign-in, check the four gates in order, remediate the one that blocked it, and validate a clean re-enrollment. Portal paths use the commercial hosts; for **GCC High / DoD** use the `*.microsoft.us` equivalents.

Phase 1 — Capture and read the failed sign-in (the deterministic step)

Step 1.1 — Capture the diagnostic block

1. From the "Access Denied" screen, record the **Activity Id**, **Session Id**, **Timestamp**, and the affected user's **UPN**.

Step 1.2 — Find the failed enrollment sign-in

1. Run `ENRLDX-Get-EnrollmentSignin.ps1` with the user (and, if known, the correlation ID / time).

It returns the failed sign-ins for the **Microsoft Intune Enrollment** and **Microsoft Intune** apps with the **failure reason** and the **applied Conditional Access** result.

1. Or, in **Entra admin center** → **Monitoring** → **Sign-in logs**, filter to the user and timestamp, find the failed enrollment sign-in, and read the **Failure reason** and the **Conditional Access** tab.

Step 1.3 — Interpret the failure reason

- **"…not licensed" / no Intune service plan** → Phase 2A (license).
- **"…blocked by policy" / MDM scope** → Phase 2B (MDM user scope).
- **Enrollment restriction / device cap** → Phase 2C.
- **A Conditional Access policy shows Failure** → Phase 2D.
- **Account disabled / guest** → Phase 2E.

If the sign-in log is unambiguous, go straight to that phase. Otherwise, work Phases 2A–2D in order — they are ordered by likelihood.

Phase 2 — Check and remediate the gate

Phase 2A — Intune license

1. Run `ENRLDX-Get-UserIntuneLicense.ps1` for the user. Confirm an **Intune** service plan

(`INTUNE_A`) is **assigned and enabled** (via a Microsoft 365 E3/E5, EMS, or standalone Intune SKU).

1. If missing/disabled: **Microsoft 365 admin center** → **the user** → **Licenses** → assign an Intune-bearing

license (or enable the Intune service plan). Wait for propagation, then retry.

Phase 2B — MDM user scope

1. Run `ENRLDX-Get-MdmUserScope.ps1`. Confirm the **Microsoft Intune** MDM user scope is **All**, or

a group that includes the user.

1. If **None** or a group the user isn't in: **Entra admin center → Devices → Mobility (MDM and WIP) →

Microsoft Intune → **set** MDM user scope **to** All **(or add the user to the scoped group). Confirm the** MDM terms of use / discovery / compliance URLs** are the defaults.

Phase 2C — Enrollment restrictions

1. Run `ENRLDX-Get-EnrollmentRestrictions.ps1`. Check:

- **Device platform restriction** — is **iOS/iPadOS** *Allowed*? Is **personally owned** *Allowed*

(for a BYO device)?

- **Device limit restriction** — is the user already at their enrolled-device cap?

1. Remediate in **Intune** → **Devices** → **Enrollment** → **Enrollment restrictions**: allow the iOS/iPadOS

platform and/or personal ownership for the user's assigned restriction, or raise/clear the device limit. For **corporate/ADE** devices, also confirm the serial is assigned to the **Intune ADE token in ABM** with an enrollment profile assigned.

Phase 2D — Conditional Access

1. Run `ENRLDX-Get-EnrollmentCA.ps1` to list CA policies targeting the **Microsoft Intune

Enrollment **and** Microsoft Intune** cloud apps.

1. If a policy blocks the sign-in (or requires a grant a not-yet-enrolled device can't meet, e.g.

require compliant device), scope it to **exclude enrollment** appropriately, or add the enrollment apps/user to the exclusion — never simply disable the policy. Re-check the sign-in log.

Phase 2E — Account

1. Confirm the account is a **member (not guest/B2B)**, sign-in is **not blocked/disabled**, and the

user holds any group membership required by scope or CA. Fix the account condition.

Phase 3 — Re-enroll and validate

1. On the device, remove the management profile (**Settings** → **General** → **VPN & Device Management** →

remove), then retry enrollment (Company Portal for BYO; re-run Setup Assistant for ADE).

1. Re-run `ENRLDX-Get-EnrollmentSignin.ps1` — the enrollment sign-in for the user should now show

Success, and the device should appear in **Intune** → **Devices**.

1. Keep the before/after sign-in evidence and the gate finding with the ticket.

Phase 4 — Prevent recurrence

1. If the cause was **MDM scope** or an **enrollment restriction**, fix it for the **class** of users

(the scoped group or the restriction assignment), not just this user, so the next enrollment does not hit the same wall.

1. If the cause was **Conditional Access**, document the enrollment exclusion pattern so future CA

changes preserve it.

Testing & Validation

Validation is objective: the same failed enrollment sign-in that produced the "Access Denied" screen must now show **Success**, and the device must appear in Intune.

Test 1 — Reproduce and capture (baseline)

1. On the affected iOS/iPadOS device, attempt enrollment and reproduce the **"Access Denied / not

authorized" **screen. Record the** Activity Id**,** Session Id**,** Timestamp**, and UPN.

1. **Pass criteria:** you have a captured failure with correlation IDs to anchor the diagnosis.

Test 2 — Root cause is identified from evidence (not guessed)

1. Run `ENRLDX-Get-EnrollmentSignin.ps1` (with `-CorrelationId` where possible). Confirm it returns

the failed enrollment sign-in with a **failure reason** and the CA result.

1. **Pass criteria:** exactly one gate is named — license (2A), MDM scope (2B), restriction (2C), CA (2D), or account (2E) — supported by the sign-in log and the matching gate script.

Test 3 — Gate script confirms the finding

1. Run the gate-specific script for the identified cause and confirm it reports the blocking condition:

• **2A** `ENRLDX-Get-UserIntuneLicense.ps1` → Intune plan NOT enabled.

• **2B** `ENRLDX-Get-MdmUserScope.ps1` → scope None, or user not in the scoped group.

• **2C** `ENRLDX-Get-EnrollmentRestrictions.ps1` → iOS/personal blocked, or device limit reached.

• **2D** `ENRLDX-Get-EnrollmentCA.ps1` → a blocking/incompatible CA policy targets the enrollment apps.

1. **Pass criteria:** the script's output matches the sign-in failure reason. Two independent signals agree.

Test 4 — Remediation applied (single, scoped change)

1. Apply only the remediation for the identified gate (Phase 2A–2E). Record the exact change made.
2. **Pass criteria:** one change, matching the named gate, with an approved change record.

Test 5 — Clean re-enrollment (the definitive test)

1. Remove the management profile on the device and retry enrollment (Company Portal for BYO; Setup Assistant for ADE).

1. Re-run `ENRLDX-Get-EnrollmentSignin.ps1`.
2. **Pass criteria:** the enrollment sign-in for the user now shows **Success**; the device appears in **Intune** → **Devices**; the "Access Denied" screen no longer appears.

Test 6 — No collateral impact

1. Confirm the change did not open a hole: an enrollment restriction still blocks unintended platforms; a CA exclusion is scoped to the enrollment apps only, not broadened globally.

1. **Pass criteria:** the fix is surgical — other users/platforms/policies behave exactly as before.

Evidence to keep

• The before (failed) and after (success) enrollment sign-ins.

• The gate-script output naming the cause.

• The change record and the device now visible in Intune.

Troubleshooting Guide

Symptom → most likely cause → verify → fix, for the iOS/iPadOS enrollment **"Access Denied / not authorized"** failure and its neighbours. Work the gates in the order below (by likelihood) unless the sign-in log already names one.

A. The core failure: "Access Denied — you are not authorized to view this page"

Failure reason (sign-in log)	Gate	Verify	Fix
"…not licensed for Intune" / no Intune service plan	Licensing (2A)	`ENRLDX-Get-UserIntuneLicense.ps1`	Assign an Intune-bearing license; wait for propagation; retry
MDM user scope excludes the user	MDM scope (2B)	`ENRLDX-Get-MdmUserScope.ps1`	Set scope **All**, or add the user to the scoped group
Platform/ownership blocked, or device limit hit	Restriction (2C)	`ENRLDX-Get-EnrollmentRestrictions.ps1`	Allow iOS/iPadOS + personal ownership; raise/clear the device limit
A CA policy blocks or gates the enrollment sign-in	Conditional Access (2D)	`ENRLDX-Get-EnrollmentCA.ps1` + the sign-in's CA tab	Exclude the enrollment apps/user; never disable the policy
Guest/B2B or disabled account	Account (2E)	`ENRLDX-Get-UserIntuneLicense.ps1` (UserType/Enabled)	Use a member account; re-enable sign-in; add required group

> ***The fast path:*** *read the failed sign-in first (`ENRLDX-Get-EnrollmentSignin.ps1`). The failure reason plus the Conditional Access result names the gate in one pass — don't guess.*

B. "Require compliant device" chicken-and-egg

- **Symptom:** enrollment blocked by CA requiring a compliant/hybrid-joined device — but the device can't

be compliant until it's enrolled.

- **Verify:** `ENRLDX-Get-EnrollmentCA.ps1` shows a `compliantDevice/domainJoinedDevice` grant on a

policy targeting the enrollment apps; the sign-in's CA tab shows that policy as the blocker.

- **Fix:** exclude the **Microsoft Intune Enrollment** (and where appropriate **Microsoft Intune**) app, or the enrolling user/group, from that policy. Keep the compliance requirement for post-enrollment resource access.

C. Enrollment succeeds for some users but not others

- **Symptom:** same device model/OS; user A enrolls, user B gets "Access Denied."
- **Likely cause:** a **per-user** gate — license difference, MDM scope group membership, or a restriction/CA assignment targeting user B's group.
- **Verify:** run the license, MDM-scope and restriction scripts for **both** users and diff the results.
- **Fix:** align the failing user's license/scope/assignment with the working user's.

D. ADE/corporate device: "Access Denied" during Setup Assistant

- **Symptom:** a Device Enrollment Program (ADE) device hits the failure mid-Setup-Assistant.
- **Likely cause:** license/scope/CA gate as above, **or** the serial isn't assigned to the Intune ADE token in ABM / no enrollment profile assigned.
- **Verify:** the four gate scripts, **plus** confirm in **ABM** the serial is under the Intune MDM server and in **Intune** → **Enrollment** → **Enrollment program tokens** the profile is assigned.
- **Fix:** remediate the gate; assign the device to the token and an enrollment profile; re-run Setup Assistant.

E. Fixed the gate but the device still shows the screen

- **Symptom:** remediation applied, device still denied.
- **Likely cause:** propagation delay (license/scope), a **stale** enrollment attempt, or a **second** gate.
- **Verify:** re-run `ENRLDX-Get-EnrollmentSignin.ps1` for a **fresh** attempt — read the newest event, not the original. Check whether a different failure reason now appears (a second gate).
- **Fix:** wait for licensing/scope propagation (typically minutes), remove the management profile, retry; remediate any newly-revealed gate.

F. Sovereign cloud (GCC High / DoD)

- **Symptom:** the runbook seems not to match the portal URLs.
- **Fix:** use `entra.microsoft.us` and `intune.microsoft.us`; run the scripts with `-Environment USGov`.

The gates and remediation are identical.

Escalation

Open a Microsoft support case only after: the sign-in log names no gate the scripts can confirm; a confirmed remediation doesn't clear a fresh attempt; or a suspected service issue. Attach the failed and post-fix sign-ins (with Activity/Session Ids), the gate-script output, and the change record.

Best Practices

Diagnose from evidence, not symptoms

- Always start from the **failed sign-in** and its correlation IDs. The Activity Id / Session Id on the screen make this a deterministic lookup — treat trial-and-error re-enrollment as a last resort, not a first step.
- Require **two agreeing signals** before you act: the sign-in failure reason **and** the matching gate script. One without the other is a hypothesis, not a root cause.

Change discipline

- Make **one scoped change** per identified gate, with an approved change record naming the gate.
- **Never disable a Conditional Access policy** to fix enrollment — exclude the enrollment apps or the user/group instead, so the policy keeps protecting everything else.
- Keep enrollment restrictions **deny-by-default**: allow exactly the platforms and ownership you intend, nothing broader.

Design out the common causes

- **Licensing at the source:** assign Intune-bearing licenses via **group-based licensing** so new users in the enrollment group are licensed automatically.
- **MDM scope by group, not All-by-accident:** if you scope MDM to a group, make sure the enrollment onboarding process adds users to it. If you intend everyone to enroll, set scope to **All**.
- **Model the CA/enrollment interaction once:** maintain a documented exclusion pattern for the **Microsoft Intune Enrollment** app so every future CA change preserves enrollability.

Prevent recurrence

• When the cause is a **class** problem (scope group, restriction assignment, CA pattern), fix it for the class, then re-test with a pilot user before closing.

• Keep a short **enrollment-readiness checklist** (licensed, in MDM scope, platform allowed, under device limit, not blocked by CA, member account) and run it before onboarding a new iOS fleet or user group.

Evidence & handoff

• Store the before/after sign-ins, the gate-script output, and the change record with the ticket.

• Feed confirmed root causes back into the checklist so the next enrollment wave avoids the same wall.

Sovereign clouds

• Use the `*.microsoft.us` portals and `-Environment USGov`; keep the same gate order and change discipline. Document the environment on the ticket so the correct portal is used every time.

Deliverables Summary

Everything included in this solution.

Documentation (compiled to PDF)

1. **Solution Overview** — what the "Access Denied / not authorized" screen means, the five gates that produce it in likelihood order, and the deterministic diagnosis path from the on-screen IDs.
1. **Requirements** — roles, the diagnostic IDs, Microsoft Graph PowerShell, enrollment-type confirmation, a reproduce/retry path, and change approval — each with why / verify / implement.
1. **Root-Cause & Remediation Guide** — the Phase 1–4 runbook: capture and read the failed sign-in → check and fix the gate (license, MDM scope, restriction, Conditional Access, account) → re-enroll and validate → prevent recurrence.
1. **Testing & Validation** — six objective tests, ending in a clean re-enrollment with a successful enrollment sign-in.
1. **Troubleshooting Guide / FAQ** — symptom→cause→verify→fix for the core failure, the "require compliant device" chicken-and-egg, per-user differences, ADE/Setup Assistant cases, residual failures, and sovereign clouds.
1. **Best Practices** — evidence-first diagnosis, change discipline, and designing out the common causes.
2. **Executive Summary** — the one-page brief for stakeholders.

PowerShell tools (packaged as a ZIP)

1. `ENRLDX-Get-EnrollmentSignin.ps1` — finds the failed **Microsoft Intune Enrollment / Microsoft

Intune** sign-in for the user (by correlation ID or time window) with the failure reason and applied Conditional Access — the deterministic root cause.

1. `ENRLDX-Get-UserIntuneLicense.ps1` — confirms an enabled Intune service plan (Phase 2A).

2. `ENRLDX-Get-MdmUserScope.ps1` — reports the Intune MDM user scope and whether the user is inside

it (Phase 2B).

1. `ENRLDX-Get-EnrollmentRestrictions.ps1` — reports platform/ownership blocks and the device limit

(Phase 2C).

1. `ENRLDX-Get-EnrollmentCA.ps1` — lists Conditional Access policies targeting the enrollment apps,

flagging blocks and incompatible grants (Phase 2D).

All scripts are read-only diagnostics, connect via `Connect-MgGraph`, support `-Environment USGov` for sovereign clouds, and are parse-verified.

Scope

• **In scope:** the iOS/iPadOS enrollment **"Access Denied / not authorized"** authorization failure and

its remediation across all common gates.

• **Referenced, not rebuilt:** general Intune iOS enrollment setup (ADE/ABM, Company Portal, enrollment

profiles) and enrollment-time device grouping — covered by the companion Intune enrollment solutions.

Appendix A — PowerShell Scripts

Included in the accompanying ZIP. Each script's header documents full usage.

ENRLDX-Get-EnrollmentCA.ps1

How to run: .\ENRLDX-Get-EnrollmentCA.ps1 Sovereign cloud: add -Environment USGov.

ENRLDX-Get-EnrollmentRestrictions.ps1

How to run: .\ENRLDX-Get-EnrollmentRestrictions.ps1 Sovereign cloud: add -Environment USGov.

ENRLDX-Get-EnrollmentSignin.ps1

How to run: Connect-MgGraph is invoked with AuditLog.Read.All (+ Directory.Read.All). .\ENRLDX-Get-EnrollmentSignin.ps1 -UserPrincipalName user@contoso.com -Hours 6 .\ENRLDX-Get-EnrollmentSignin.ps1 -UserPrincipalName user@contoso.com -CorrelationId af992f0f-1790-4677-8ef8-b61de01dfc67 Sovereign cloud: add -Environment USGov.

ENRLDX-Get-MdmUserScope.ps1

How to run: .\ENRLDX-Get-MdmUserScope.ps1 .\ENRLDX-Get-MdmUserScope.ps1 -UserPrincipalName user@contoso.com Sovereign cloud: add -Environment USGov.

ENRLDX-Get-UserIntuneLicense.ps1

How to run: .\ENRLDX-Get-UserIntuneLicense.ps1 -UserPrincipalName user@contoso.com Sovereign cloud: add -Environment USGov.