

## Contents

### 1 Advanced algorithms

- 1.1 2-SAT problem . . . . .
- 1.2 Iterative deepening A\* (IDA\*) . . . . .

### 2 Dynamic programming algorithms

- 2.1 0-1 knapsack . . . . .
- 2.2 Longest common subsequence (LCS) . . . . .
- 2.3 Max 2D range sum . . . . .
- 2.4 Traveling salesman problem (TSP) . . . . .

### 3 Graph algorithms

- 3.1 All-pairs shortest paths (APSP) . . . . .
- 3.2 Bipartite matching BFS by David . . . . .
- 3.3 Centroid decomposition . . . . .
- 3.4 Detect negative weight cycle . . . . .
- 3.5 DFS . . . . .
- 3.6 DFS ICPC 2019 Russia problem E . . . . .
- 3.7 Dijkstra by Bill . . . . .
- 3.8 Dijkstra by David . . . . .
- 3.9 Print Euler tour . . . . .
- 3.10 Find articulation points and bridges for undirected graph . . . . .
- 3.11 Floyd Warshall by David . . . . .
- 3.12 Graph edges property check . . . . .
- 3.13 Kruskal by David . . . . .
- 3.14 Max flow . . . . .
- 3.15 Max cardinality bipartite matching (MCBM) . . . . .
- 3.16 Min-cost flow (MCF) . . . . .
- 3.17 Minimum spanning tree (MST) . . . . .
- 3.18 Strongly connected component (SCC) . . . . .

### 4 Greedy algorithms

- 4.1 Interval covering . . . . .
- 4.2 Longest increasing subsequence (LIS) . . . . .
- 4.3 Max 1D range sum . . . . .

### 5 Math algorithms

- 5.1 Chinese remainder theorem . . . . .
- 5.2 Extended greatest common divisor (Ext-GCD) . . . . .
- 5.3 Greatest common divisor (GCD) and least common multiple (LCM) . . . . .
- 5.4 Generate list of prime numbers . . . . .
- 5.5 N choose R combination (nCr) . . . . .
- 5.6 Stirling's approximation . . . . .

### 6 String algorithms

- 6.1 KnuthMorrisPratt algorithm . . . . .
- 6.2 Longest palindromic substring . . . . .
- 6.3 Minimum edit distance . . . . .
- 6.4 Z-algorithm . . . . .

### 7 Data structures

- 7.1 Union-find disjoint sets (UFDS) by David . . . . .
- 7.2 Binary indexed/fenwick tree (BIT) . . . . .
- 7.3 Rope . . . . .
- 7.4 Segment tree . . . . .
- 7.5 Union-find disjoint sets (UFDS) by Bill . . . . .

### 8 Utilities

- 8.1 Bit manipulation . . . . .
- 8.2 C++ input output . . . . .
- 8.3 C++ STL . . . . .
- 8.4 Dates . . . . .
- 8.5 Prime numbers . . . . .

## 1 Advanced algorithms

### 1.1 2-SAT problem

```

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

```

```

void work()
{
    sccNum.assign(V, 0);
    dfs_num.assign(V, UNVISITED);
    dfs_low.assign(V, 0);
    visited.assign(V, 0);
    dfsNumberCounter = numSCC = 0;
    for (int u = 0; u < V; ++u)
        if (dfs_num[u] == UNVISITED)
            tarjanSCC(u);

    if (!possible)
    {
        printf("-1\n");
        return;
    }

    for (int i = 1; i <= K; ++i)
        printf("%c", sccNum[blue(i)] > sccNum[red(i)] ? 'R' : 'B'); // 2-SAT assignment based
    printf("\n");
}

int main()
{
    #ifdef LOCAL
    freopen("in.txt", "r", stdin);
    #endif // LOCAL
    scanf("%d %d", &K, &N);
    V = 2 * K + 2;
    AL.assign(V, vi());
    for (int i = 0; i < N; ++i)
    {
        pair<int, char> a[3];
        for (int j = 0; j < 3; ++j) scanf("%d %c", &a[j].first, &a[j].second);
        for (int j = 0; j < 3; ++j) printf("%d %c ", a[j].first, a[j].second);
        printf("\n");
        createEdge(a[0], a[1]);
        createEdge(a[0], a[2]);
        createEdge(a[1], a[2]);
    }

    work();

    return 0;
}

```

## 1.2 Iterative deepening A\* (IDA\*)

```

// UVa 10181 - 15-Puzzle Problem solved with Iterative Deepening A* (IDA*).
#include <bits/stdc++.h>

using namespace std;

// #define LOCAL
#define N 4 // #rows/columns
#define B 15 // [B]lank tile id
#define PUZZLE (N*N)
#define MAX_STEPS 45 // given by the problem description
#define DIR 4 // 4 [DIR]ections

int dr[DIR] = {0, -1, 0, 1}; // must be right, up, left, down
int dc[DIR] = {1, 0, -1, 0}; // for the XOR operation to work
char dm[] = "RULD"; // [d]irection [m]ove

int p[PUZZLE];
int b_init_pos; // [b]lank [init]ial [pos]ition
int lim; // current [lim]it of the Iterative Deepening Search (IDS)
int pred[MAX_STEPS]; // [pre]viously used [d]irection to go to the current state

bool isViable()
{
    int sum;
    for (int i = 0; i < PUZZLE; ++i)
        for (int j = 0; j < i; ++j)
            if (p[j] > p[i]) ++sum;
    sum += b_init_pos / N + b_init_pos % N;
    sum -= B / N + B % N;
    return sum % 2 == 0;
}

int H()
{
    int h = 0;
    for (int pos = 0; pos < PUZZLE; ++pos) // for all tile 'p[pos]'
    {
        // compute Manhattan distance to goal state
        if (p[pos] == B) continue;
        h += abs(p[pos] / N - pos / N) // position of 'p[pos]' in goal state is 'pos'

```

```

        + abs(p[pos] % N - pos % N); // position of 'p[pos]' in current state is 'pos'
    }
    return h;
}

bool isValid(int r, int c)
{
    return 0 <= r && r < N && 0 <= c && c < N;
}

int Delta_H(int cur_r, int cur_c, int next_r, int next_c)
{
    int val = p[cur_r * N + cur_c]; // [val]ue of the tile being moved into the blank tile position
    int goal_r = val / N; // position of 'val' in goal state is 'val'
    int goal_c = val % N; // get row & column representation of the position
    return - (abs(goal_r - cur_r) + abs(goal_c - cur_c))
        + (abs(goal_r - next_r) + abs(goal_c - next_c));
}

bool dfs(int g, int h, int b_pos)
{
    if (g + h > lim) return false;
    if (h == 0) return true; // found a solution!
    int r = b_pos / N;
    int c = b_pos % N;
    for (int d = 0; d < DIR; ++d)
    {
        if (g != 0 && d == (pred[g] ^ 2)) continue; // this direction gets us back to parent state
        int next_r = r + dr[d];
        int next_c = c + dc[d];
        if (!isValid(next_r, next_c)) continue;
        int next_h = h + Delta_H(next_r, next_c, r, c); // 0(1)
        int b_next_pos = next_r * N + next_c;
        swap(p[b_pos], p[b_next_pos]);
        pred[g+1] = d;

        if (dfs(g + 1, next_h, b_next_pos)) return true;

        swap(p[b_pos], p[b_next_pos]);
    }
    return false;
}

int ida_star()
{
    int init_h = H();
    lim = init_h;
    while (lim <= MAX_STEPS)
    {
        if (dfs(0, init_h, b_init_pos)) return lim;
        ++lim;
    }
    return -1;
}

void output(int steps)
{
    for (int i = 1; i <= steps; ++i)
        printf("%c", dm[ pred[i] ]);
}

int main()
{
    #ifdef LOCAL
    freopen("in.txt", "r", stdin);
    #endif // LOCAL
    int T;
    scanf("%d", &T);
    while (T--)
    {
        for (int i = 0; i < N; ++i)
            for (int j = 0; j < N; ++j)
            {
                int pos = i * N + j;
                scanf("%d", &p[pos]);
                if (p[pos] == 0) p[pos] = B, b_init_pos = pos; // goal state 'p' is 0, 1, 2..14, 15
                // blank tile as 15
            }
        if (!isViable()) // must-consider condition otherwise TLE
        {
            printf("This puzzle is not solvable.\n");
            continue;
        }
        int ret = ida_star();
        if (ret == -1)
        {
            printf("This puzzle is not solvable.\n");
            continue;
        }
        output(ret), printf("\n");
    }
    return 0;
}

```

## 2 Dynamic programming algorithms

### 2.1 0-1 knapsack

```

#define W 1000 // Knapsack weight
#define N 100 // n item
int weight[N]; //item weight
int value[N]; //item value
int bag[W][2];

// 0/1 Knapsack
void ZeroOne() {
    memset(bag, 0, sizeof(bag));
    for(int i = 0; i < N; i++) {
        for(int j = 0; j < W; j++) {
            if( j >= weight[i] )
                bag[j][1] = max( bag[j][0], bag[j-weight[i]][0] + value[i] );

            for(int j = 0; j < W; j++)
                bag[j][0] = bag[j][1];
        }
    }

    // group knapsack
    int group; // how much groups?
    int how_many; // one group has many items?
    int WEIGHT, VALUE;

    void Grouping() {
        memset(bag, 0, sizeof(bag));
        for(int i = 0; i < group; i++) {
            for(int j = 0; j < how_many; j++) {
                scanf("%d %d", &WEIGHT, &VALUE);

                for(int k = 0; k < W; k++) {
                    if( j >= WEIGHT ) {
                        bag[j][1] = max( bag[j][1], bag[j][0] );
                        bag[j][1] = max( bag[j][1], bag[j-WEIGHT][0] + VALUE );
                    }
                }

                for(int j = 0; j < W; j++)
                    bag[j][0] = bag[j][1];
            }
        }

    }

    // multiple knapsack
    int limit[N]; // item limit
    void Multiple() {
        for(int i = 0; i < N; i++) {
            int tmp = 1;
            while( tmp <= weight[i] ) {
                for(int j = 0; j < W; j++) {
                    if( j >= weight[i]*tmp )
                        bag[j][1] = max( bag[j-weight[i]*tmp][0] + value[i]*tmp, bag[j][0] );

                    for(int j = 0; j < W; j++)
                        bag[j][0] = bag[j][1];

                    weight[i] = weight[i]-tmp;
                    tmp = tmp*2;
                }
            }
            if( weight[i] > 0 ) {
                for(int j = 0; j < W; j++)
                    if( j >= weight[i]*tmp )
                        bag[j][1] = max( bag[j-weight[i]*tmp][0] + value[i]*tmp, bag[j][0] );

                for(int j = 0; j < W; j++)
                    bag[j][0] = bag[j][1];
            }
        }

    }

    // inf
    void Unlimited() {
        memset(bag, 0, sizeof(bag));
        for(int i = 0; i < N; i++) {
            for(int j = 0; j < W; j++)
                if( j >= weight[i] )
                    bag[j][1] = max( bag[j][0], bag[j-weight[i]][1] + value[i] );
        }
    }
}

```

### 2.2 Longest common subsequence (LCS)

```

for(int j = 0; j < W; j++)
    bag[j][0] = bag[j][1];
}

#include <iostream>
#include <bits/stdc++.h>
#define LOCAL
using namespace std;

struct LCS {
    int step, max_len;
} Dp[5000][5000];

int main() {
    #ifndef LOCAL
        freopen("in1.txt", "r", stdin);
    #endif // LOCAL
    int intX, intY, Min_step, Max_len;
    string strX, strY;
    while(cin >> intX >> strX >> intY >> strY) {
        //init
        for(int i = 0; i <= intY; i++) {
            Dp[0][i].max_len = 0;
            Dp[0][i].step = i;
        }
        for(int i = 0; i <= intX; i++) {
            Dp[i][0].max_len = 0;
            Dp[i][0].step = i;
        }
        Max_len = 0;
        Min_step = 0;

        //lcs
        for(int i = 1; i <= intX; i++) {
            for(int j = 1; j <= intY; j++) {
                if(strX[i-1] == strY[j-1]) {
                    Dp[i][j].max_len = Dp[i-1][j-1].max_len + 1;
                    Dp[i][j].step = Dp[i-1][j-1].step;

                    //debug
                    //cout << strX[i-1] << ' ' << strY[j-1] << ' ' << Dp[i][j].max_len << '\n';
                    //cout << strX[i-1] << ' ' << strY[j-1] << ' ' << Dp[i][j].step << '\n';
                }
                else {
                    Dp[i][j].max_len = max(Dp[i-1][j].max_len, Dp[i][j-1].max_len);
                    Dp[i][j].step = min( min(Dp[i-1][j-1].step, Dp[i][j-1].step), Dp[i-1][j].step ) + 1;
                }
            }
            cout << Dp[intX][intY].step << '\n';
        }
        return 0;
    }
}

```

### 2.3 Max 2D range sum

```

// Max 2D Range Sum - UVa 108 - solved with DP O(n^4).
// Abridged problem statement: Given an n x n square matrix of integers A where
// each integer ranges from [-127..127], find a sub-matrix of A with the maximum
// sum.
#include <bits/stdc++.h>
using namespace std;
int A[200][200];
int main() {
    int n; scanf("%d", &n); // square matrix size
    for(int i = 0; i < n; ++i)
        for(int j = 0; j < n; ++j) {
            scanf("%d", &A[i][j]);
            if( i > 0 ) A[i][j] += A[i-1][j]; // add from top
            if( j > 0 ) A[i][j] += A[i][j-1]; // add from left
            if( i > 0 && j > 0 ) A[i][j] -= A[i-1][j-1]; // avoid double count
        } // inclusion-exclusion
    int maxSubRect = -127*100*100; // the lowest possible val
    for(int i = 0; i < n; ++i)
        for(int j = 0; j < n; ++j) // start coordinate

```

```

for (int k = i; k < n; ++k)
for (int l = j; l < n; ++l) {
    int subRect = A[k][l]; // end coord
    if (i > 0) subRect -= A[i-1][l]; // from (0, 0) to (k, l)
    if (j > 0) subRect -= A[k][j-1]; // O(1)
    if (i > 0 && j > 0) subRect += A[i-1][j-1]; // O(1)
    maxSubRect = max(maxSubRect, subRect); // the answer is here
}
printf("%d\n", maxSubRect);
return 0;
}

```

## 2.4 Traveling salesman problem (TSP)

// This is a solution for UVa 10496 - Collecting Beepers. The problem is a variant of the Traveling Salesman Problem (TSP): Given  $n$  cities and their pairwise distances in the form of a matrix 'dist' of size  $n \times n$ , compute the minimum cost of making a tour that starts from any city  $s$ , goes through all the other  $n - 1$  cities exactly once, and finally returns to the city  $s$ . In this case, the salesman is Karel in a 2D world who can only move along the  $x$  and  $y$  axis. The cities are beepers whose coordinates are given, from which pairwise distances can be calculated. Algorithm takes time  $O(2^n \cdot n^2)$ . INPUT: The first line is the number of test cases. The first line of each test case is world's size ( $x$ -size and  $y$ -size). Next is the starting position of Karel. Next is the number of beepers. Next are the beepers'  $x$ - and  $y$ -coordinates. OUTPUT: For each test case, output the minimum distance to move from Karel's starting position to each of the beepers and back to the starting position.

```

#include <bits/stdc++.h>
using namespace std;

#define LSOne(S) ((S) & -(S))

const int MAX_n = 11;

int dist[MAX_n][MAX_n], memo[MAX_n][1<<(MAX_n-1)]; // Karel + max 10 beepers

int dp(int u, int mask) {
    if (mask == 0) return dist[u][0]; // mask = free coordinates
    if (ans != -1) return ans; // close the loop
    if (ans != -1) return ans; // computed before
    ans = 2000000000;
    int m = mask;
    while (m) {
        int two_pow_v = LSOne(m); // up to O(n)
        int v = __builtin_ctz(two_pow_v)+1; // but this is fast
        ans = min(ans, dist[u][v] + dp(v, mask^two_pow_v)); // offset v by +1
        m -= two_pow_v; // keep the min
    }
    return ans;
}

int main() {
    int TC; scanf("%d", &TC);
    while (TC--) {
        int xsize, ysize; scanf("%d %d", &xsize, &ysize); // these two values are not used
        int x[MAX_n], y[MAX_n];
        scanf("%d %d", &x[0], &y[0]);
        int n; scanf("%d", &n); ++n; // include Karel
        for (int i = 1; i < n; ++i) // Karel is at index 0
            scanf("%d %d", &x[i], &y[i]);
        for (int i = 0; i < n; ++i) // build distance table
            for (int j = i; j < n; ++j)
                dist[i][j] = dist[j][i] = abs(x[i]-x[j]) + abs(y[i]-y[j]); // Manhattan distance
        memset(memo, -1, sizeof memo);
        printf("The shortest path has length %d\n", dp(0, (1<<(n-1))-1)); // DP-TSP
    }
    return 0;
}

```

## 3 Graph algorithms

### 3.1 All-pairs shortest paths (APSP)

// All-Pairs Shortest Paths (APSP) solved with Floyd Warshall  $O(V^3)$ .  
// inside int main()  
// Precondition: AdjMat[i][j] contains the weight of edge (i, j) or INF (1B)  
// if there is no such edge ('AdjMat' is a 32-bit signed integer array).  
// Let 'p' be 2D parent matrix, where p[i][j] is the last vertex before j on

```

// a shortest path from i to j, i.e. i -> ... -> p[i][j] -> j.
for (int i = 0; i < V; ++i)
for (int j = 0; j < V; ++j)
    p[i][j] = i; // initialize the parent matrix
for (int k = 0; k < V; ++k) // remember that loop order is k->i->j
for (int i = 0; i < V; ++i)
for (int j = 0; j < V; ++j)
    if (AdjMat[i][k] + AdjMat[k][j] < AdjMat[i][j])
        AdjMat[i][j] = AdjMat[i][k] + AdjMat[k][j];
        p[i][j] = p[k][j];

// print shortest paths
void printPath(int i, int j)
{
    if (i != j) printPath(i, p[i][j]);
    printf("%d ", j);
}

```

### 3.2 Bipartite matching BFS by David

```

#include <iostream>
#include <string>
#include <cstdio>
#include <vector>
#define LOCAL
using namespace std;

int fp[100010], fq[100010];
int vfp[100010], vfq[100010];
int turn = 0;
vector<int> cp[100010], cq[100010];

int BFSBfmp(int n) {
    vfp[n] = turn;
    for (int i = 0; i < cp[n].size(); i++) {
        if (vfp[cp[n][i]] != turn) {
            vfp[cp[n][i]] = turn;
            if (fq[cp[n][i]] == -1 || BFSBfmp(fq[cp[n][i]])) {
                fp[n] = cp[n][i];
                cq[cp[n][i]] = n;
                return 1;
            }
        }
    }
    return 0;
}

int main()
{
    ios::sync_with_stdio(false);
    cin.tie(0);
    cout.tie(0);

    int n, p, q, k, x, y;
    cin >> n;
    while (n--) {
        cin >> p >> q >> k;
        int MaxnPQ = max(p, q);
        for (int i = 1; i <= MaxnPQ; i++) {
            cp[i].clear();
            fp[i] = -1;
            cq[i].clear();
            fq[i] = -1;
        }
        int cnt = 0;
        for (int i = 0; i < k; i++) {
            cin >> x >> y;
            cp[x].push_back(y);
            cq[y].push_back(x);
            if (fp[x] == -1 && fq[y] == -1) {
                fp[x] = y;
                fq[y] = x;
                cnt++;
            }
        }
        for (int i = 1; i <= p; i++) {
            if (fp[i] == -1) {
                turn++;
                if (BFSBfmp(i))
                    cnt++;
            }
        }
        cout << cnt << '\n';
    }
    return 0;
}

```

### 3.3 Centroid decomposition

```
#include<iostream>
#include<bits/stdc++.h>
#define LOCAL
#define MAXN 50005
using namespace std;

int n , k , a , b ;
int ans , cnt ;
int Max[MAXN] , sz[MAXN] , rt ;
int head[MAXN] , dis[MAXN];
bool vis[MAXN] ;
struct node{
    int v , nx ;
}Edge[MAXN+2];

void init(int n ){
    Max[0] = n ;
    ans = cnt = 0 ;
    for(int i = 0 ; i <= n ; i++){
        head[i] = -1 ;
        vis[i] = 0 ;
    }
}

void add(int u , int v){
    Edge[cnt].v = v ;
    Edge[cnt].nx = head[u] ;
    head[u] = cnt++ ;
}

void get_rt(int u , int fa ){
    sz[u] = 1 ; Max[u] = 0 ;
    for(int i = head[u] ; ~i ; i=Edge[i].nx){
        int v = Edge[i].v ;
        if(vis[v] || v == fa ) continue ;
        get_rt(v,u);
        sz[u] += sz[v] ;
        Max[u] = max(Max[u] , sz[v]);
    }
    Max[u] = max(Max[u] , n - sz[u]);
    if(Max[rt] > Max[u])
        rt = u ;
}

void get_dis(int u , int fa , int d){
    for(int i = head[u] ; ~i ; i= Edge[i].nx){
        int v = Edge[i].v ;
        if(vis[v] || v == fa ) continue ;
        dis[++cnt] = d + 1 ;
        get_dis(v,u,dis[cnt]);
    }
}

int get_ans(int u , int d ){
    dis[cnt=1] = d ;
    get_dis(u,0,d) ;
    sort(dis+1 , dis+cnt+1) ;
    int l = 1 , ans = 0 ;

    while(l < cnt && dis[l] + dis[cnt] < k ) l++ ;
    while(l < cnt && dis[l] <= k - dis[l]){
        ans += upper_bound(dis + l + 1 , dis + cnt + 1 , k - dis[l]) - lower_bound(dis+l+1 , dis+cnt+1 , k-dis[l]);
        l++ ;
    }
    return ans ;
}

void dfs(int u ){
    vis[u] = 1 ;
    //cout << rt << ' ' << u << '\n' ;
    ans += get_ans(u , 0);
    for(int i = head[u] ; ~i ; i = Edge[i].nx){
        int v = Edge[i].v ;
        if(vis[v]) continue ;
        ans += get_ans(v , 1) ;
        n = sz[v] , rt = 0 , get_rt(v,u);
        dfs(rt);
    }
}

int main(){
    // #ifdef LOCAL
    //     freopen("in1.txt" , "r" , stdin);
    // #endif // LOCAL
```

```
cin >> n >> k ;
init(n);
for(int i =1; i < n ; i++){
    cin >> a >> b ;
    add(a,b);
    add(b,a);
}
rt = 0 ; get_rt(1,0);
dfs(rt);
cout << ans << '\n' ;
}
```

### 3.4 Detect negative weight cycle

```
// Bellman Ford's O(VE)
vi dist(V, INF); dist[s] = 0;
for (int i = 0; i < V - 1; ++i) // relax all E edges V - 1 times
    for (int u = 0; u < V; ++u) // these two loops = O(E)
        for (int j = 0; j < (int)AL[u].size(); ++j) // [A]dacency [L]ist
            {
                ii vw = AL[u][j];
                dist[vw.first] = min( dist[vw.first], dist[u] + vw.second ); // relax
            }
}
```

### 3.5 DFS

```
#include <iostream>
#include <bits/stdc++.h>
#define LOCAL
using namespace std;
int m , n , flag=1;
int Maxn_city = 0 , Maxn_path = 0 ;
vector<int>tree[200020] ;
int city[200020] = {} ;
int visit[200020] = {} ;
vector<int> travel ;

void BFS_to_large_path(int root ){
    visit[root] = 1 ;
    travel.push_back(root);
    for(int i = 0 ; i < tree[root].size() ; i++){
        int node = tree[root][i] ;
        if(!visit[node]){
            BFS_to_large_path(node);
            travel.pop_back();
            visit[root] = 0 ;
        }
    }
    //debug to check large path
    //if (root == 1)
    //    cout << "I=" << travel.size() << ' ' << Maxn_path << ' ' << city[root] << '\n' ;

    if(city[root] && travel.size() > Maxn_path){
        Maxn_city = travel[travel.size()/2];
        Maxn_path = travel.size();
    }
}

void BFS_to_other_path(int root ,int path){
    visit[root] = 1 ;
    for(int i = 0 ; i < tree[root].size() ; i++){
        int node = tree[root][i] ;
        if(!visit[node]){
            BFS_to_other_path(node , path+1);
            visit[root] = 0 ;
        }
    }
    //debug
    if(root == 1 )
        cout << "city=" << root << " path=" << path << '\n' ;

    if(city[root] && path != Maxn_path)
        flag = 0 ;
}

int main(){
    #ifdef LOCAL
        freopen("in1.txt" , "r" , stdin);
    #endif // LOCAL
    cin >> n >> m ;
```

```

int a , b ;
for(int i = 0 ; i < n-1 ; i++){
    cin >> a >> b ;
    tree[a].push_back(b) ;
    tree[b].push_back(a) ;
}

for(int i = 0 ; i < m ; i++){
    cin >> a ;
    city[a] = 1 ;
}
BFS_to_large_path(a);
//visit[a] = 0 ;
BFS_to_other_path(Maxn_city , 1 );
if(flag)
    cout << "YES\n" << Maxn_city ;
else
    cout << "NO" ;

//debug
cout << "Maxn_path= " << Maxn_path << " Maxn_city= " << Maxn_city << '\n' ;
}

```

## 3.6 DFS ICPC 2019 Russia problem E

```

#include <iostream>
#include <bits/stdc++.h>
#define LOCAL
using namespace std;
int m , n , flag=1;
int Maxn_city = 0 , Maxn_path = 0 ;
vector<int> tree[200020] ;
int city[200020] = {} ;
int visit[200020] = {} ;
vector<int> travel ;

void BFS_to_large_path(int root ){
    visit[root] = 1 ;
    travel.push_back(root);
    for(int i = 0 ; i < tree[root].size() ; i++){
        int node = tree[root][i] ;
        if(!visit[node]){
            BFS_to_large_path(node);
            travel.pop_back();
            visit[root] = 0 ;
        }
    }
    //debug to check large path
    //if (root == 1)
    //    cout << "I=" << travel.size() << ' ' << Maxn_path << ' ' << city[root] << '\n' ;

    if(city[root] && travel.size() > Maxn_path){
        Maxn_city = travel[travel.size()/2];
        Maxn_path = travel.size();
    }
}

void BFS_to_other_path(int root ,int path){
    visit[root] = 1 ;
    for(int i = 0 ; i < tree[root].size() ; i++){
        int node = tree[root][i] ;
        if(!visit[node]){
            BFS_to_other_path(node , path+1);
            visit[root] = 0 ;
        }
    }
    //debug
    if(root == 1 )
        cout << "city=" << root << " path= " << path << '\n' ;

    if(city[root] && path != Maxn_path)
        flag = 0 ;
}

int main(){
    #ifdef LOCAL
        freopen("in1.txt" , "r" , stdin);
    #endif // LOCAL
    cin >> n >> m ;
    int a , b ;
    for(int i = 0 ; i < n-1 ; i++){
        cin >> a >> b ;
        tree[a].push_back(b) ;
        tree[b].push_back(a) ;
    }
}

```

```

for(int i = 0 ; i < m ; i++){
    cin >> a ;
    city[a] = 1 ;
}
BFS_to_large_path(a);
//visit[a] = 0 ;
BFS_to_other_path(Maxn_city , 1 );
if(flag)
    cout << "YES\n" << Maxn_city ;
else
    cout << "NO" ;

//debug
cout << "Maxn_path= " << Maxn_path << " Maxn_city= " << Maxn_city << '\n' ;
}

```

## 3.7 Dijkstra by Bill

```

// Dijkstra implementation for negative weight edges O((V + E) log V)
vi dist(V, INF); dist[s] = 0;
priority_queue<ii, vii, greater<ii> > pq;
pq.push(ii(0, s));
while (!pq.empty())
{
    ii front = pq.top(); pq.pop();
    int d = front.first;
    int u = front.second;
    if (d > dist[u]) continue;
    for (int i = 0; i < (int)AL[u].size(); ++i) // [A]djacency [L]ist
    {
        ii vw = AL[u][i];
        int v = vw.first;
        int w = vw.second;
        if (dist[u] + w < dist[v])
        {
            dist[v] = dist[u] + w; // relax operation
            pq.push(ii(dist[v], v));
        }
    }
} // this variant can cause duplicate items in the priority queue

```

## 3.8 Dijkstra by David

```

#include <iostream>
#include <bits/stdc++.h>
#define LOCAL
using namespace std;
#define INF 999999999
int intMap[1010][1010] = {} , intValue[1010][1010] = {};
int m , n ;

struct Node{
    int x , y , v ;
    void read( int _x , int _y , int _v){
        x = _x ; y = _y ; v = _v ;
    }
    bool operator < (const Node &a) const{
        return v > a.v ;
    }
}nodNode;

void print_map(){
    for(int i = 1 ; i <= n ; i++){
        for(int j = 1 ; j <= m ; j++){
            if(intValue[i][j] == 999999999)
                cout << "r" << ' ' ;
            else
                cout << intValue[i][j] << ' ' ;
        }
        cout << '\n' ;
    }
    cout << '\n' ;
}

void bfs(){
    int x , y , intDirection[4][2] = {-1,0 ,0,1 ,1,0 ,0,-1};
    int intDx , intDy ;
    Node nodTemp ;
    priority_queue<Node> deqNode ;
    nodTemp.read(1,1,0);
}

```

```

    deqNode.push(nodTemp);
    while(deqNode.size()){
        x = deqNode.top().x ;
        y = deqNode.top().y ;
        deqNode.pop() ;

        for(int i = 0 ; i < 4 ; i++){
            intDx = intDirection[i][0] + x ;
            intDy = intDirection[i][1] + y ;

            //debug
            //cout << intDx << ' ' << intDy << ' ' << intValue[x][y] + intMap[intDx][intDy] << ' ' <<
                i << '\n' ;

            if(intValue[x][y] + intMap[intDx][intDy] < intValue[intDx][intDy] ){
                intValue[intDx][intDy] = intValue[x][y] + intMap[intDx][intDy] ;
                nodTemp.read(intDx , intDy , intValue[intDx][intDy]);
                deqNode.push(nodTemp) ;
            }
        }
        //print_map() ;
    }
}

int main() {
#ifdef LOCAL
    freopen("in1.txt" , "r" , stdin );
    freopen("out.txt" , "w" , stdout );
#endif
    ios::sync_with_stdio(false);
    int intCase ;
    cin >> intCase ;
    while(intCase --){
        cin >> n >> m ;
        for(int i = 1 ; i <= n ; i++){
            for(int j = 1 ; j <= m ; j++){
                cin >> intMap[i][j] ;
                intValue[i][j] = INF ;
            }
        }

        for(int i = 1 ; i <= n ; i++){
            intValue[i][0] = 0 ;
            intValue[i][m+1] = 0 ;
            intMap[i][0] = INF +1 ;
            intMap[i][m+1] = INF +1 ;
        }

        for(int i = 1 ; i <= m ; i++){
            intValue[0][i] = 0 ;
            intValue[n+1][i] = 0 ;
            intMap[0][i] = INF +1 ;
            intMap[n+1][i] = INF +1 ;
        }
        intValue[1][1] = intMap[1][1] ;

        //debug
        //cout << intValue[1][1] << '\n' ;

        bfs();
        cout << intValue[n][m] << '\n' ;
    }

    return 0;
}

```

### 3.9 Print Euler tour

```

// Given an Eulerian-tour graph - a connected undirected graph whose vertices a-
// ll have even degrees, produce its Euler tour. The graph is unweighted, stored
// in an adjacency list where the second attribute in edge info pair is a boole-
// an '1' (edge can still be used) or '0' (edge can no longer be used).
list<int> cyc;    // we need list for fast insertion in the middle

void EulerTour(list<int>::iterator i, int u)
{
    for (int j = 0; j < (int)AL[u].size(); ++j) // [A]dacency [L]ist
    {
        ii& vw = AL[u][j];
        int v = vw.first;
        if (vw.second)    // if this edge can still be used
        {
            vw.second = 0;    // remove this edge
            // remove bi-directional edge
            for (int k = 0; k < (int)AL[v].size(); ++k)
            {
                ii& uw = AL[v][k];
                if (uw.first == u && uw.second)

```

```

                {
                    uw.second = 0;
                    break;
                }
            }
            // continue the tour
            EulerTour(cyc.insert(i, u), v);
        }
    }
}

// inside int main()
cyc.clear();
EulerTour(cyc.end(), 0);    // 'cyc' contains an Euler tour starting at vertex '0'
for (list<int>::iterator i = cyc.begin(); i != cyc.end(); ++i)
    printf("%d\n", *i);

```

## 3.10 Find articulation points and bridges for undirected graph

```

// Find articulation points & bridges for undirected graph solved with DFS O(V + E).
void articulationPointAndBridge(int u)
{
    dfs_low[u] = dfs_num[u] = dfsNumberCounter++;    // dfs_low[u] <= dfs_num[u]
    for (int i = 0; i < (int)AL[u].size(); ++i)    // [A]dacency [L]ist
    {
        int v = AL[u][i].first;
        if (dfs_num[v] == UNVISITED)    // a tree edge
        {
            dfs_parent[v] = u;
            if (u == dfsRoot) ++rootChildren;    // special case if 'u' is a root

            articulationPointAndBridge(v);

            if (dfs_low[v] >= dfs_num[u]) articulation_vertex[u] = true;
            if (dfs_low[v] > dfs_num[u]) printf("Edge (%d, %d) is a bridge\n", u, v);

            dfs_low[u] = min( dfs_low[u], dfs_low[v] );    // update dfs_low[u]
        }
        else if (v != dfs_parent[u]) dfs_low[u] = min( dfs_low[u], dfs_num[v] );    // update dfs_low[u]
    }
}

// inside int main()
dfsNumberCounter = 0;
dfs_num.assign(V, UNVISITED);
dfs_low.assign(V, 0);
dfs_parent.assign(V, 0);
articulation_vertex.assign(V, 0);
printf("Bridges:\n");
for (int u = 0; u < V; ++u)
    if (dfs_num[u] == UNVISITED)
    {
        dfsRoot = u;
        rootChildren = 0;
        articulationPointAndBridge(u);
        articulation_vertex[dfsRoot] = (rootChildren > 1);    // special case
    }
printf("Articulation Points:\n");
for (int u = 0; u < V; ++u)
    if (articulation_vertex[u]) printf(" Vertex %d\n", u);

```

## 3.11 Floyd Warshall by David

```

#include <iostream>
#include <bits/stdc++.h>
#define LOCAL
using namespace std;
char before[520][520] = {} ;
int after[520][520] = {} ;

int main()
{
#ifdef LOCAL
    freopen("in1.txt" , "r" , stdin );
#endif
    // LOCAL

    int n ;
    cin >> n ;
    for(int i = 0 ; i < n ; i++){
        for(int j = 0 ; j < n ; j++){

```

```

        cin >> before[i][j] ;
    }

    for(int i = 0 ; i < n ; i++){
        for(int j = i+1 ; j < n ; j++){
            int sum = 0 ;
            for(int k = i + 1 ; k < j ; k++){
                if(after[i][k])
                    sum += before[k][j] - '0' ;
            }

            if( (sum + 1) % 10 == before[i][j] - '0'){
                after[i][j] = 1 ;
            }
        }
    }

    for(int i = 0 ; i < n ; i++){
        for(int j = 0; j < n ; j++){
            cout << after[i][j] ;
        }
        cout << '\n' ;
    }

    return 0;
}

```

## 3.12 Graph edges property check

```

// Graph Edges Property Check solved with DFS O(V + E).
void graphCheck(int u)    // DFS for checking graph edge properties
{
    dfs_num[u] = EXPLORED;
    for (int i = 0; i < (int)AL[u].size; ++i) // [A]djacency [L]ist
    {
        int v = AL[u][i].first;
        if (dfs_num[v] == UNVISITED)    // Tree Edge, EXPLORED->UNVISITED
        {
            dfs_parent[v] = u;    // parent of this child is me
            graphCheck(v);
        }
        else if (dfs_num[v] == EXPLORED)    // EXPLORED->EXPLORED
        {
            if (v == dfs_parent[u]) printf(" Two ways (%d, %d)-(%d, %d)\n", u, v, v, u);
            else printf(" Back Edge (%d, %d) (Cycle)\n", u, v); // can check if graph is cyclic
        }
        else if (dfs_num[v] == VISITED)    // EXPLORED->VISITED
            printf(" Forward/Cross Edge (%d, %d)\n", u, v);
    }
    dfs_num[u] = VISITED;
}

// inside int main()
dfs_num.assign(V, UNVISITED);
dfs_parent.assign(V, 0);
for (int u = 0; u < V; ++u)
    if (dfs_num[u] == UNVISITED)
        printf("Component %d:\n", ++numComp), graphCheck(u);

```

## 3.13 Kruskal by David

```

#include <iostream>
#include <bits/stdc++.h>
#define LOCAL
#define ll long long
using namespace std;
int parent[1020] ;

struct edge{
    ll n1, n2, w ;
}node[25020];

int compare(edge A, edge B ){
    return A.w < B.w ;
}

int find_root(int a){
    if(a != parent[a] )
        return parent[a] = find_root(parent[a]) ;
    return a ;
}

```

```

int main()
{
    #ifdef LOCAL
        freopen("in1.txt", "r", stdin );
        freopen("out.txt", "w", stdout );
    #endif // LOCAL
    int n, m, p_n1, p_n2 ; // parent_n1, parent_n2
    vector<int> hce ; //heavy edge circle
    while(cin >> n >> m && n + m != 0 ){
        for(int i = 0 ; i < m ; i++){
            cin >> node[i].n1 >> node[i].n2 >> node[i].w ;
        }

        for(int i = 0 ; i < n ; i++){
            parent[i] = i ;
            sort(node, node + m, compare ) ;
            hce.clear() ;

            //kruskal
            for(int i = 0 ; i < m ; i++){
                p_n1 = find_root(node[i].n1) ;
                p_n2 = find_root(node[i].n2) ;
                if(p_n1 != p_n2 )
                    parent[p_n2] = p_n1 ;
                else
                    hce.push_back(node[i].w) ;

                //debug
                /*
                for(int i = 0 ; i < n ; i++){
                    cout << parent[i] << ' ' ;
                }
                */
            }
            sort(hce.begin(), hce.end()) ;
            if(hce.size()){
                for(int i = 0 ; i < hce.size()-1 ; i++){
                    cout << hce[i] << ' ' ;
                    cout << hce[hce.size()-1] ;
                }
                else
                    cout << "forest" ;
                cout << '\n' ;
            }
            return 0;
        }
    }
}

```

## 3.14 Max flow

```

int res[MAX_V][MAX_V], mf, f, s, t;
vi p; // p stores the BFS spanning tree from s

void augment(int v, int minEdge)
{
    if (v == s) { f = minEdge; return; }
    else if ( p[v] != -1 )
    {
        augment( p[v], min(minEdge, res[ p[v] ][ v ] ) );
        res[ p[v] ][ v ] -= f;
        res[ v ][ p[v] ] += f;
    }
}

// inside int main(): set up 'AL', 'res', 's', and 't' with appropriate values
// remember to add backward edges to 'AL'
mf = 0;
while (true)    // O(V * E^2) Edmonds Karp's algorithm
{
    f = 0;
    vi dist(MAX_V, INF); dist[s] = 0;
    queue<int> q; q.push(s);
    p.assign(MAX_V, -1);
    while (!q.empty())
    {
        int u = q.front(); q.pop();
        if (u == t) break; // immediately stop BFS if we already reach sink t
        for (int i = 0; i < (int)AL[u].size(); ++i)
        {
            int v = AL[u][i];    // vector<vi> [A]djacency [L]ist
            if (res[u][v] > 0 && dist[v] == INF)
                dist[v] = dist[u] + 1, q.push(v), p[v] = u;
        }
    }
    augment(t, INF);    // find the min edge weight 'f' in this path, if any
    if (f == 0) break; // we cannot send any more flow ('f' = 0), terminate
}

```



### 3.15 Max cardinality bipartite matching (MCBM)

```
// Max Cardinality Bipartite Matching (MCBM) solved with augmenting path algorithm O(VE).
vi match, vis;

int Aug(int l)    // return 1 if an augmenting path is found & 0 otherwise
{
    if (vis[l]) return 0;
    vis[l] = 1;
    for (int i = 0; i < (int)AL[l].size(); ++i) // [A]dacency [L]ist
    {
        int r = AL[l][i]; // edge weight not needed -> vector<vi> AL
        if ( match[r] == -1 || Aug(match[r]) )
        {
            match[r] = l; // found 1 matching
            return 1;
        }
    }
    return 0; // no matchings
}

// inside int main()
// build unweighted bipartite graph with directed edge left->right set
// left vertices [0..N-1], right vertices [N..V-1]
int MCBM = 0;
match.assign(V, -1); // V is the number of vertices in bipartite graph
for (int l = 0; l < N; ++l) // N = size of the left set
{
    vis.assign(N, 0); // reset before each recursion
    MCBM += Aug(l);
}
printf("Found %d matchings\n", MCBM);
```

### 3.16 Min-cost flow (MCF)

```
// UVa 10594 - Data Flow solved as Min-Cost Flow (MCF) problem using Edmonds Ka-
// rp and Bellman Ford algorithms with total time O(V^2 * E^3).
#include <bits/stdc++.h>

using namespace std;

#define LOCAL
#define INF 1000000000000000 // 10^15
#define bwd 0 // [b]ack[w]ar[d] direction
#define fwd 1 // [f]or[w]ar[d] direction
#define MAX_V 200

typedef vector<int> vi;
typedef long long int ll;
typedef pair<ll, ll> ll2;
typedef vector<ll> vll;

int V;
vector<vi> AL;
ll res[MAX_V][MAX_V][2], cst[MAX_V][MAX_V][2];
ll mf, f, min_cost;
int s, t;
vector<pair<int, ll> > p;
ll FLOW, CAPACITY;

void augment(int v, ll minEdge)
{
    if (v == s) { f = minEdge; return; }
    else if ( p[v].first != -1 )
    {
        augment( p[v].first, min(minEdge, res[ p[v].first ][ v ][ p[v].second ] ) );
        res[ p[v].first ][ v ][ p[v].second ] -= f;
        res[ v ][ p[v].first ][ p[v].second ] += f;
    }
}

void trace_cost(int v)
{
    if (p[v].first == -1) return;
    min_cost += cst[ p[v].first ][ v ][ p[v].second ] * f;
    trace_cost(p[v].first);
}
```

```
void min_cost_flow()
{
    min_cost = 0;
    mf = 0;
    while (true)
    {
        f = 0;
        p.assign(MAX_V, make_pair(-1, -1));
        vll dist(V, INF); dist[s] = 0;
        for (int i = 0; i < V - 1; ++i)
            for (int u = 0; u < V; ++u)
                for (int j = 0; j < (int)AL[u].size(); ++j)
                {
                    int v = AL[u][j];
                    for (int dir = 0; dir <= 1; ++dir)
                        if (res[u][v][dir] > 0 && dist[u] + cst[u][v][dir] < dist[v])
                        {
                            dist[v] = dist[u] + cst[u][v][dir];
                            p[v] = make_pair(u, dir);
                        }
                }
        augment(t, INF);
        if (f == 0) break;
        f = min(f, FLOW - mf);
        trace_cost(t);
        mf += f;
        if (mf == FLOW) break;
    }
    if (mf < FLOW) printf("Impossible.\n");
    else printf("%lld\n", min_cost);
}

int main()
{
    #ifdef LOCAL
        freopen("in", "r", stdin);
    #endif
    int E;
    while (scanf("%d %d", &V, &E) != EOF)
    {
        AL.assign(V, vi());
        memset(res, 0, sizeof res);
        memset(cst, 0, sizeof cst);
        for (int i = 0; i < E; ++i)
        {
            int u, v;
            ll w;
            scanf("%d %d %d %d", &u, &v, &w);
            u--; v--; // 0-based index
            AL[u].push_back(v);
            AL[v].push_back(u);

            res[u][v][fwd] = res[v][u][bwd] = 1; // real edges
            cst[u][v][fwd] = cst[v][u][bwd] = w;

            res[u][v][bwd] = res[v][u][fwd] = 0; // additional reversed edges
            cst[u][v][bwd] = cst[v][u][fwd] = -w;
        }

        scanf("%lld %lld", &FLOW, &CAPACITY);
        for (int u = 0; u < V; ++u)
            for (int v = 0; v < V; ++v)
            {
                res[u][v][fwd] += CAPACITY;
                res[v][u][bwd] += CAPACITY;
            }

        s = 0;
        t = V-1;
        min_cost_flow();
    }
    return 0;
}
```

### 3.17 Minimum spanning tree (MST)

```
// Minimum Spanning Tree (MST) solved with Kruskal O(E log V)
// inside int main()
vector<pair<int, ii> > EdgeList; // (weight, two vertices) of the edge
for (int i = 0; i < E; ++i)
{
    scanf("%d %d %d", &u, &v, &w);
    EdgeList.push_back( make_pair( w, ii(u, v) ) );
}
sort(EdgeList.begin(), EdgeList.end()); // sort by edge weight O(E log E)
int mst_cost = 0;
UnionFind UF(V); // all V are disjoint sets initially
```

```

for (int i = 0; i < E; ++i)
{
    pair<int, int> front = EdgeList[i];
    if (!UF.isSameSet(front.second.first, front.second.second))
    {
        mst_cost += front.first;
        UF.unionSet(front.second.first, front.second.second);
    }
}
printf("MST cost = %d\n", mst_cost);

```

## 3.18 Strongly connected component (SCC)

```

// Tarjan O(V + E)
vi dfs_num, dfs_low, visited;
int dfsNumberCounter, numSCC;
vi S;

void tarjanSCC(int u)
{
    dfs_low[u] = dfs_num[u] = dfsNumberCounter++; // dfs_low[u] <= dfs_num[u]
    S.push_back(u); // stores 'u' in a vector based on order of visitation
    visited[u] = 1;
    for (int i = 0; i < (int)AL[u].size(); ++i) // [A]djacency [L]ist
    {
        int v = AL[u][i].first;
        if (dfs_num[v] == UNVISITED) tarjanSCC(v);
        if (visited[v]) dfs_low[u] = min(dfs_low[u], dfs_low[v]); // condition for update
    }

    if (dfs_low[u] == dfs_num[u]) // if this is a root (start) of an SCC
    { // this part is done after recursion
        printf("SCC %d:", ++numSCC);
        while (true)
        {
            int v = S.back(); S.pop_back();
            visited[v] = 0;
            printf(" %d", v);
            if (u == v) break;
        }
        printf("\n");
    }
}

// inside int main()
dfs_num.assign(V, UNVISITED);
dfs_low.assign(V, 0);
visited.assign(V, 0);
dfsNumberCounter = numSCC = 0;
for (int u = 0; u < V; ++u)
    if (dfs_num[u] == UNVISITED)
        tarjanSCC(u);

```

## 4 Greedy algorithms

### 4.1 Interval covering

```

// This is a solution for UVa 10382 - Watering Grass. The problem is a variant
// of Interval Covering problem, which is solved by O(n) Greedy algorithm.

#include <bits/stdc++.h>

#define pb push_back
#define not_set -1

using namespace std;

typedef pair<double, double> dd;
typedef vector<dd> vdd;
typedef enum { STOP = 0,
              CONTINUE } status;

int n, l, w;
vdd spinklers;
int answer;
double pivot;

struct sort_compare_t {
    bool operator()(dd a, dd b) const {
        return a.first < b.first || (a.first == b.first && a.second > b.second);
    }
} sort_compare;

```

```

}
} sort_compare;

void InputSpinklers() {
    for (int i = 0; i < n; ++i) {
        double x, r; // must be double otherwise WA.
        scanf("%lf %lf", &x, &r);
        if (w > 2 * r) // ignore spinklers that cannot cover the width of the strip.
        {
            continue;
        }
        if (w == 2 * r) // ignore spinklers that produce no intervals.
        {
            continue;
        }
        double dx = sqrt(r * r - w * w / 4.0);
        spinklers.pb(dd(x - dx, x + dx));
    }
}

status Check(int& j) {
    if (j == not_set) // there is an interval after pivot that cannot be covered.
    {
        return STOP;
    }
    // record j.
    answer++;
    pivot = spinklers[j].second;
    if (pivot >= l) // solution found!
    {
        return STOP;
    }
    j = not_set;
    return CONTINUE;
}

void SolveIntervalCovering() {
    sort(spinklers.begin(), spinklers.end(), sort_compare);
    answer = 0;
    pivot = 0.0;
    int j = not_set;
    int iter = 0;
    while (true) {
        if (iter == spinklers.size()) // iterated through all spinklers/intervals.
        {
            Check(j);
            break;
        }

        if (spinklers[iter].first <= pivot) {
            if (pivot < spinklers[iter].second) // note the next candidate down!
            {
                if (j == not_set || spinklers[iter].second > spinklers[j].second) // note down the
                    most right candidate.
                {
                    j = iter;
                }
                iter++;
            }
            else // skip intervals that are completely covered by the previously selected ones.
            {
                iter++;
            }
        }
        else // out bound.
        {
            if (Check(j) == STOP) {
                break;
            }
        }
    }

    if (pivot >= l) {
        printf("%d\n", answer);
    }
    else {
        printf("-1\n");
    }
}

int main() {
    while (scanf("%d %d %d", &n, &l, &w) != EOF) {
        spinklers.clear();
        InputSpinklers();
        SolveIntervalCovering();
    }
}

```

### 4.2 Longest increasing subsequence (LIS)

```

#include <bits/stdc++.h>
using namespace std;

typedef vector<int> vi;

int n;
vi A;

void print_array(const char *s, vi &L, int n) {
    for (int i = 0; i < n; ++i) {
        if (i) printf(", ");
        else printf("%s: [", s);
        printf("%d", L[i]);
    }
    printf("]\n");
}

vi p; // predecessor array

void print_LIS(int i) {
    if (p[i] == -1) { printf("%d", A[i]); return; } // base case
    print_LIS(p[i]); // backtrack
    printf(" %d", A[i]);
}

int memo[10010]; // old limit: up to 10^4

int LIS(int i) {
    if (i == 0) return 1;
    int &ans = memo[i];
    if (ans != -1) return ans;
    ans = 1; // LIS can start anywhere
    for (int j = 0; j < i; ++j) // O(n) here
        if (A[j] < A[i]) // increasing condition
            ans = max(ans, LIS(j)+1); // pick the max
    return ans;
}

int main() {
    // note: A[n-1] must be set as the largest value ("INF")
    // so that all LIS (that can start anywhere) will end at n-1
    srand(time(NULL));
    int n = 10+rand()%11; // [10..20]
    A.assign(n, 0);
    A[n-1] = 99; // set A[n-1] = INF
    for (int i = 0; i < n-1; ++i)
        A[i] = rand()%101-50; // [-50..50]

    n = 12;
    vi sample({-7, 10, 9, 2, 3, 8, 8, 1, 2, 3, 4, 99});
    A = sample;

    printf("n = %d:", n);
    for (int i = 0; i < n; ++i)
        printf(" %d", A[i]);
    printf("\n");

    // early 2000 problems usually accept O(n^2) solution
    memset(memo, -1, sizeof memo);
    printf("LIS length is %d\n", LIS(n-1)); // with O(n^2) DP

    // 2020s problems will likely only accept O(n log k) solution
    // new limit: n can be up to 200K
    int k = 0, lis_end = 0;
    vi L(n, 0), L_id(n, 0);
    p.assign(n, -1);

    for (int i = 0; i < n; ++i) {
        int pos = lower_bound(L.begin(), L.begin()+k, A[i]) - L.begin();
        L[pos] = A[i]; // greedily overwrite this
        L_id[pos] = i; // remember the index too
        p[i] = pos ? L_id[pos-1] : -1; // predecessor info
        if (pos == k) { // can extend LIS?
            k = pos+1; // k = longer LIS by +1
            lis_end = i; // keep best ending i
        }

        printf("Considering element A[%d] = %d\n", i, A[i]);
        printf("LIS ending at A[%d] is of length %d: ", i, pos+1);
        printf("[");
        print_LIS(i);
        printf("]\n");
        print_array("L is now", L, k);
        printf("\n");
    }

    printf("Final LIS is of length %d: ", k);
    print_LIS(lis_end); printf("\n");

    assert(LIS(n-1) == k); // both must be identical
    return 0;
}

```

## 4.3 Max 1D range sum

```

// Max 1D Range Sum solved with Jay Kadane O(n).
// inside int main()
int n = 9;
int A[] = { 4, -5, 4, -3, 4, 4, -4, 4, -5 }; // a sample array A
int sum = 0;
int ans = 0; // important, 'ans' must be initialized to 0
for (int i = 0; i < n; ++i)
{
    sum += A[i];
    ans = max(ans, sum);
    if (sum < 0) sum = 0;
}
printf("Max 1D Range Sum = %d\n", ans);

```

## 5 Math algorithms

### 5.1 Chinese remainder theorem

```

#include <bits/stdc++.h>
#define gtr ios::sync_with_stdio(0); cin.tie(0);
#define endl '\n'
#define int long long
#define MOD 1000000
using namespace std;

int inv(int a, int m){
    int m0 = m, t, q;
    int x0 = 0, x1 = 1;
    if(m == 1){
        return 0;
    }
    while(a > 1){
        q = a/m;
        t = m;
        m = a%m, a = t;
        t = x0;
        x0 = x1 - q * x0;
        x1 = t;
    }
    if(x1 < 0){
        x1 += m0;
    }
    return x1;
}

int findMinX(vector<int> num, vector<int> rem, int k){
    int prod = 1;
    for(int i = 0; i < k; i++) prod *= num[i];
    int result = 0;
    for(int i = 0; i < k; i++){
        int pp = prod / num[i];
        result += rem[i] * inv(pp, num[i]) * pp;
    }
    return result % prod;
}

int32_t main() { //gtr
    int n = 3;
    vector<int> rem, factor;
    rem.resize(n);
    factor.resize(n);
    for(int i = 0; i < n; i++){
        cin >> factor[i];
    }
    for(int i = 0; i < n; i++){
        cin >> rem[i];
    }
    cout << findMinX(factor, rem, n) << endl;
}

```

### 5.2 Extended greatest common divisor (Ext-GCD)

```

// ax mod b = 1
// ax + by = 1, x=y=0
// a,b Relatively Prime

```

```
LL exgcd(LL a, LL b, LL &x, LL &y){
    if(b){
        LL tmd=exgcd(b, a%b, y, x);
        y=-a/b*x;
        return tmd;
    }
    x=1, y=0;
    return a;
}
```

## 5.3 Greatest common divisor (GCD) and least common multiple (LCM)

```
// or __gcd(a, b) in gcc
int gcd(int a, int b){
    return a%b?gcd(b, a%b):b;
}
int lcm(int a, int b){
    return a*b/gcd(a, b);
}
```

## 5.4 Generate list of prime numbers

```
// Generate list of prime numbers using Sieve of Eratosthenes.
ll _sieve_size;
bitset<10000010> bs; // [b]it [s]et 10^7 should be enough for most cases
vi primes; // compact list of primes

void sieve(ll upperbound) // create list of primes in [0..upperbound]
{
    _sieve_size = upperbound + 1; // add 1 to include upperbound
    bs.set(); // set all bits to 1
    bs[0] = bs[1] = 0; // exception index 0 and 1
    for (ll i = 2; i <= _sieve_size; ++i)
        if (bs[i])
        {
            // cross out multiples of i starting from i * i!
            for (ll j = i * i; j <= _sieve_size; j += i) bs[j] = 0;
            primes.push_back( (int)i );
        }
}

bool isPrime(ll N) // a good enough deterministic prime tester
{
    if (N <= _sieve_size) return bs[N]; // O(1) for small primes
    for (int i = 0; i < (int)primes.size(); ++i)
        if (N % primes[i] == 0) return false;
    return true; // it takes longer if N is a large prime!
} // note: only work for N <= (last prime in vi 'primes')^2

// inside int main()
sieve(10000000); // can go up to 10^7 (need few seconds)
printf("%d\n", isPrime(2147483647)); // 10-digit prime
printf("%d\n", isPrime(136117223861LL)); // not a prime, 104729 * 1299709
```

## 5.5 N choose R combination (nCr)

```
#define MAXN 100
long long nCr[MAXN+5][MAXN+5];
// nCr[i][j] = \binom{C_n}{r}
void build_nCr() {
    for(int i = 1; i < MAXN+5; i++) {
        for(int j = 1; j < MAXN+5; j++) {
            if(i == j)
                nCr[i][j] = 1;
            else if(i > j)
                nCr[i][j] = nCr[i-1][j] * i / (i-j);
        }
    }
}
```

## 5.6 Stirling's approximation

```
double Stirling(int n){
    return (0.5*log(2.0*acos(-1.0)*n)+n*log(n+0.0)-n)/log(10.0);
} // n! Digits
```

## 6 String algorithms

### 6.1 KnuthMorrisPratt algorithm

```
#include <iostream>
#include <bits/stdc++.h>
#define LOCAL
#define MAXN 100020
using namespace std;
string strA, strB;
int b[MAXN], p[MAXN];

void kmp_process(){
    int n = strB.length(), i = 0, j = -1;
    b[0] = -1;
    while(i < n){
        while(j >= 0 && strB[i] != strB[j]) j = b[j];
        i++; j++;
        b[i] = j;
    }

    //debug
    for(int k = 0; k <= n; k++)
        cout << b[k] << ' ';
    cout << '\n';
}

int kmp(){
    int n = strA.length(), m = strB.length(), i = 0, j = 0;
    while(i < n){
        while(j >= 0 && strA[i] != strB[j]) j = b[j];
        i++; j++;
    }
    return j;
}

int main()
{
    #ifdef LOCAL
    freopen("in1.txt", "r", stdin);
    #endif // LOCAL

    while(cin >> strA){
        strB = strA;
        reverse(strB.begin(), strB.end());
        kmp_process();
        int n = kmp();
        cout << strA << strB.substr(n) << '\n';
    }
    return 0;
}
```

### 6.2 Longest palindromic substring

```
#include <iostream>
#include <bits/stdc++.h>
#define LOCAL
#define MAXN 1010
using namespace std;
int dp[MAXN][MAXN] = {};
string strA, strB;
int n, m;

int lcs(){
    n = strA.length();
    m = strB.length();
    for(int i = 0; i <= n; i++) dp[i][0] = 0;
    for(int j = 0; j <= m; j++) dp[0][j] = 0;
    for(int i = 1; i <= n; i++){
        for(int j = 1; j <= m; j++){
            if(strA[i-1] == strB[j-1]) dp[i][j] = dp[i-1][j-1] + 1;
            else dp[i][j] = max(dp[i-1][j], dp[i][j-1]);
        }
    }
    return dp[n][m];
}
```

```

}

int main()
{
#ifdef LOCAL
    freopen("in1.txt", "r", stdin);
#endif // LOCAL
    int t;
    cin >> t;
    cin.ignore();
    while(t--){
        getline(cin, strA);
        strB = strA;
        reverse(strB.begin(), strB.end());
        cout << lcs() << '\n';
    }

    return 0;
}

```

## 6.3 Minimum edit distance

```

#include <iostream>
#include <bits/stdc++.h>
#define LOCAL
#define MAXN 100
using namespace std;
string strA, strB;
int dis[MAXN][MAXN], back_table[MAXN][MAXN];
int cnt, m, n;

void backtracking(int i, int j){
    if(i==0 || j==0){
        while(i > 0){
            cout << cnt++ << " Delete " << i << '\n';
            i--;
        }
        while(j > 0){
            cout << cnt++ << " Insert " << i+1 << ", " << strB[j-1] << '\n';
            j--;
        }
        return;
    }
    if(strA[i-1] == strB[j-1])
        backtracking(i-1, j-1);
    else{
        if(dis[i][j] == dis[i-1][j-1]+1){
            cout << cnt++ << " Replace " << i << ", " << strB[j-1] << '\n';
            backtracking(i-1, j-1);
        }
        else if(dis[i][j] == dis[i-1][j]+1){
            cout << cnt++ << " Delete " << i << '\n';
            backtracking(i-1, j);
        }
        else if(dis[i][j] == dis[i][j-1]+1){
            cout << cnt++ << " Insert " << i+1 << ", " << strB[j-1] << '\n';
            backtracking(i, j-1);
        }
    }
}

void med(){ //Minimum Edit Distance
    for(int i = 0; i <= n; i++) dis[i][0] = i;
    for(int j = 0; j <= m; j++) dis[0][j] = j;
    for(int i = 1; i <= n; i++){
        for(int j = 1; j <= m; j++){
            if(strA[i-1] == strB[j-1]) dis[i][j] = dis[i-1][j-1];
            else dis[i][j] = min(dis[i-1][j-1], min(dis[i-1][j], dis[i][j-1]))+1;
        }
    }
}

int main()
{
#ifdef LOCAL
    freopen("in1.txt", "r", stdin);
    freopen("out.txt", "w", stdout);
#endif // LOCAL
    cin.tie(0);
    cout.tie(0);
    ios::sync_with_stdio(false);
    int flag = 0;
    while(getline(cin, strA) && getline(cin, strB)){
        n=strA.length();

```

```

        m=strB.length();
        cnt = 1;
        med();
        if(flag) cout << '\n';
        flag = 1;
        cout << dis[n][m] << '\n';
        backtracking(n,m);
    }
    return 0;
}

```

## 6.4 Z-algorithm

```

#include <iostream>
#include <bits/stdc++.h>
#define LOCAL
#define MAXN 1000020
using namespace std;
int z[MAXN] = {};
int x=0, y=0, maxn = 0;
string s;

int main()
{
#ifdef LOCAL
    freopen("in1.txt", "r", stdin);
#endif // LOCAL

    cin >> s;
    for(int i = 1; i < s.length(); i++){
        z[i] = max(0, min(z[i-x], y - i + 1));
        while(i + z[i] < s.length() && s[z[i]] == s[i+z[i]]){
            x = i;
            y = i + z[i];
            z[i]++;
        }
    }

    for(int i = 0; i < s.length(); i++){
        if(z[i] == s.length() - i && maxn <= s.length() - i){
            cout << s.substr(0, z[i]);
            return 0;
        }
        maxn = max(maxn, z[i]);
    }
    cout << "Just a legend";
    return 0;
}

```

## 7 Data structures

### 7.1 Union-find disjoint sets (UFDS) by David

```

#include <iostream>
#include <bits/stdc++.h>
#define LOCAL

using namespace std;
int intSum[200080], intParent[200080], intSet[200080];

int find_root(int intA){
    if(intParent[intA] == intA)
        return intA;
    intParent[intA] = find_root(intParent[intA]);
    return intParent[intA];
}

int each_debug(int n){
    for(int i = 1; i <= n; i++){
        cout << i << ' ' << intParent[i] << ' ' <<
            << intSet[find_root(i)] << ' ' << intSum[find_root(i)] << '\n';
    }
    system("Pause");
}

int main()

```

```

{
#ifdef LOCAL
    freopen("in1.txt","r", stdin);
    freopen("out.txt","w", stdout);
#endif // LOCAL

    int n, m, operation, p, q;
    while(cin >> n >> m){
        for(int i = 1; i <= n; i++){
            intParent[i] = i+n;
            intParent[i+n] = i+n;
            intSum[i+n] = i;
            intSet[i+n] = 1;
        }
        while(m--){
            cin >> operation;
            if(operation == 1){
                cin >> p >> q;
                int intRoot_p, intRoot_q;
                intRoot_p = find_root(intParent[p]);
                intRoot_q = find_root(intParent[q]);
                if(intRoot_p != intRoot_q){
                    intParent[intRoot_q] = intRoot_p;
                    intSum[intRoot_p] += intSum[intRoot_q];
                    intSet[intRoot_p] += intSet[intRoot_q];
                }
                //debug
                //each_debug(n);
            }
            else if (operation == 2){
                cin >> p >> q;
                int intRoot_p, intRoot_q;
                intRoot_p = find_root(intParent[p]);
                intRoot_q = find_root(intParent[q]);
                if(intRoot_p != intRoot_q){
                    intParent[p] = intRoot_q;
                    intSum[intRoot_q] += p;
                    intSum[intRoot_p] -= p;
                    intSet[intRoot_q] ++;
                    intSet[intRoot_p] --;
                }
                //debug
                //each_debug(n);
            }
            else if (operation == 3){
                cin >> p;
                cout << intSet[find_root(p)] << ' ' << intSum[find_root(p)] << '\n';
            }
        }
    }
    return 0;
}

```

## 7.2 Binary indexed/fenwick tree (BIT)

```

#include <iostream>
using namespace std;

#define LOGSZ 17

int tree[(1<<LOGSZ)+1];
int N = (1<<LOGSZ);

// add v to value at x
void set(int x, int v) {
    while(x <= N) {
        tree[x] += v;
        x += (x & -x);
    }
}

// get cumulative sum up to and including x
int get(int x) {
    int res = 0;
    while(x) {
        res += tree[x];
        x -= (x & -x);
    }
    return res;
}

// get largest value with cumulative sum less than or equal to x;
// for smallest, pass x-1 and add 1 to result
int getind(int x) {
    int idx = 0, mask = N;

```

```

while(mask && idx < N) {
    int t = idx + mask;
    if(x >= tree[t]) {
        idx = t;
        x -= tree[t];
    }
    mask >>= 1;
}
return idx;
}

```

## 7.3 Rope

```

#include <iostream>
#include <bits/stdc++.h>
#include <ext/rope>
#define LOCAL
#define MAXN 50020
using namespace std;
using namespace __gnu_cxx;

int main()
{
#ifdef LOCAL
    freopen("in1.txt", "r", stdin);
#endif // LOCAL
    int n, t, a, b, c, d=0;
    int v = 0;
    string strA;
    rope<char> r[MAXN], rtmp;
    cin >> n;
    while(n--){
        cin >> t;

        if(t==1){
            cin >> a;
            cin >> strA;
            a -= d;
            r[++v] = r[v];
            r[v].insert(a, strA.c_str());
            //debug
            //cout << r[v] << '\n';
        }
        else if(t==2){
            cin >> a >> b;
            a -= d; b -= d;
            r[++v] = r[v];
            r[v].erase(a-1,b);
            //debug
            //cout << r[v] << ' ' << r[v-1] << '\n';
        }
        else if(t==3){
            cin >> a >> b >> c;
            a -= d; b -= d; c -= d;
            rtmp = r[a].substr(b-1,c);
            cout << rtmp << '\n';
            d += count(rtmp.begin(), rtmp.end(), 'c');
        }
    }
    return 0;
}

```

## 7.4 Segment tree

```

#include <iostream>
#include <bits/stdc++.h>
#include <string>
#define LOCAL
#define Lson(x) ((x <= 1) + 1)
#define Rson(x) ((x <= 1) + 2)
#define INF 99999999
using namespace std;
const int N = 100005;
int shift[35], num[N], len_shift;
string strLine;

struct Node{
    int left, right, Min_Value;
}node[4 * N];

void build(int left, int right, int x = 0){

```

```

node[x].left = left ;
node[x].right = right ;
if(left == right){
    node[x].Min_Value = num[left] ;
    return ;
}
int mid = (left + right ) / 2 ;

//debug
//cout << mid << '\n' ;
//cout << x << ' ' << node[x].left << ' ' << node[x].right << ' ' << '\n' ;

build(left , mid , Lson(x)) ;
build(mid + 1 , right , Rson(x)) ;
node[x].Min_Value = min(node[Lson(x)].Min_Value , node[Rson(x)].Min_Value ) ;
}

void handle(){
    len_shift = 0 ;
    shift[len_shift] = 0;
    for(int i = 6 ; i < strLine.length() ; i++){
        if(strLine[i] >= '0' && strLine[i] <= '9' ){
            shift[len_shift] = shift[len_shift] * 10 + (int) (strLine[i] - '0' ) ;
        }
        else{
            shift[++len_shift] = 0 ;
        }
    }
    //finally char is ')' , so len_shift is right
    sort(shift , shift + len_shift ) ;

    //debug
    //++<
    for(int i = 0 ; i < len_shift ; i++)
        cout << shift[i] << ' ' ;
    cout << '\n' ;
}

int query(int left , int right , int x = 0 ){
    if(node[x].left >= left && node[x].right <= right)
        return node[x].Min_Value ;
    int mid = (node[x].left + node[x].right ) / 2 ;
    int ans = INF ;

    //debug
    //cout << x << ' ' << node[x].left << ' ' << node[x].right << ' ' << node[x].Min_Value << '\n' ;

    if( left <= mid )
        ans = min(ans , query(left , right , Lson(x)) ) ;
    if(mid < right )
        ans = min(ans , query(left , right , Rson(x)) ) ;
    return ans ;
}

void set_num(int position , int value , int x = 0 ){
    if(node[x].left == position && node[x].right == position ){
        node[x].Min_Value = value ;
        return ;
    }
    int mid = (node[x].left + node[x].right ) / 2 ;
    if(position <= mid )
        set_num(position , value , Lson(x)) ;
    if(mid < position )
        set_num(position , value , Rson(x)) ;
    node[x].Min_Value = min(node[Lson(x)].Min_Value , node[Rson(x)].Min_Value ) ;
}

int main()
{
    int n , q , intTemp ;
    ios::sync_with_stdio(0);
#ifdef LOCAL
    freopen("out.txt" , "w" , stdout ) ;
    freopen("in1.txt" , "r" , stdin ) ;
#endif // LOCAL
    cin >> n >> q ;
    for(int i = 1 ; i <= n ; i++){
        cin >> num[i] ;
        build(1,n);

        //debug
        //++<
        for(int i = 0 ; i < 13 ; i++){
            cout << node[i].left << ' ' << node[i].right << ' ' << node[i].Min_Value << '\n' ;
        }
    }
    return 0 ;
}

```

```

*/
while(q--){
    cin >> strLine ;
    if(strLine[0] == 'q'){
        handle();
        cout << query(shift[0] , shift[1] ) << '\n' ;
    }
    else if (strLine[0] == 's'){
        handle();
        intTemp = num[shift[0]] ;

        for(int i = 1 ; i < len_shift ; i++){
            set_num(shift[i-1] , num[shift[i]]) ;
            num[shift[i-1]] = num[shift[i]] ;
        }
        num[shift[len_shift-1]] = intTemp ;
        set_num(shift[len_shift-1] , intTemp ) ;

        //debug
        //cout << intTemp << ' ' << shift[len_shift-1] << '\n' ;
        //for(int i = 1 ; i <= n ; i++)
        //    cout << num[i] << ' ' ;
    }
}
return 0;
}

```

## 7.5 Union-find disjoint sets (UFDS) by Bill

```

class UnionFind
{
public:
    UnionFind(int N)
    {
        rank.assign(N, 0);
        p.assign(N, 0);
        for (int i = 0; i < N; ++i) p[i] = i;
    }
    int findSet(int i) { return (p[i] == i) ? i : ( p[i] = findSet(p[i]) ); }
    bool isSameSet(int i, int j) { return findSet(i) == findSet(j); }
    void unionSet(int i, int j)
    {
        if ( !isSameSet(i, j) )
        {
            int x = findSet(i);
            int y = findSet(j);
            if (rank[x] > rank[y]) p[y] = x;    // rank keeps the tree short
            else
            {
                p[x] = y;
                if (rank[x] == rank[y]) ++rank[y];
            }
        }
    }
private:
    vi p, rank;
};

```

## 8 Utilities

### 8.1 Bit manipulation

```

#define isOn(S, j) (S & (1<<j))
#define setBit(S, j) (S |= (1<<j))
#define clearBit(S, j) (S &= ~(1<<j))
#define toggleBit(S, j) (S ^= (1<<j))
#define lowBit(S) (S & (-S))
#define setAll(S, n) (S = (1<<n)-1)

```

### 8.2 C++ input output

```

#include <iostream>
#include <iomanip>

using namespace std;

```

```
int main()
{
    // Output a specific number of digits past the decimal point,
    // in this case 5
    cout.setf(ios::fixed); cout << setprecision(5);
    cout << 100.0/7.0 << endl;
    cout.unsetf(ios::fixed);

    // Output the decimal point and trailing zeros
    cout.setf(ios::showpoint);
    cout << 100.0 << endl;
    cout.unsetf(ios::showpoint);

    // Output a '+' before positive values
    cout.setf(ios::showpos);
    cout << 100 << " " << -100 << endl;
    cout.unsetf(ios::showpos);

    // Output numerical values in hexadecimal
    cout << hex << 100 << " " << 1000 << " " << 10000 << dec << endl;
}
```

## 8.3 C++ STL

```
// Example for using stringstream and next_permutation

#include <algorithm>
#include <iostream>
#include <sstream>
#include <vector>

using namespace std;

int main(void){
    vector<int> v;

    v.push_back(1);
    v.push_back(2);
    v.push_back(3);
    v.push_back(4);

    // Expected output: 1 2 3 4
    //                  1 2 4 3
    //                  ...
    //                  4 3 2 1
    do {
        ostringstream oss;
        oss << v[0] << " " << v[1] << " " << v[2] << " " << v[3];

        // for input from a string s,
        // istream iss(s);
        // iss >> variable;

        cout << oss.str() << endl;
    } while (next_permutation (v.begin(), v.end()));

    v.clear();

    v.push_back(1);
    v.push_back(2);
    v.push_back(1);
    v.push_back(3);

    // To use unique, first sort numbers. Then call
    // unique to place all the unique elements at the beginning
    // of the vector, and then use erase to remove the duplicate
    // elements.

    sort(v.begin(), v.end());
    v.erase(unique(v.begin(), v.end(), v.end()), v.end());

    // Expected output: 1 2 3
    for (size_t i = 0; i < v.size(); i++)
        cout << v[i] << " ";
    cout << endl;
}
```

## 8.4 Dates

```
// Routines for performing computations on dates. In these routines,
// months are expressed as integers from 1 to 12, days are expressed
// as integers from 1 to 31, and years are expressed as 4-digit
// integers.
```

```
#include <iostream>
#include <string>

using namespace std;

string dayOfWeek[] = {"Mon", "Tue", "Wed", "Thu", "Fri", "Sat", "Sun"};

// converts Gregorian date to integer (Julian day number)
int dateToInt (int m, int d, int y){
    return
        1461 * (y + 4800 + (m - 14) / 12) / 4 +
        367 * (m - 2 - (m - 14) / 12 * 12) / 12 -
        3 * ((y + 4900 + (m - 14) / 12) / 100) / 4 +
        d - 32075;
}

// converts integer (Julian day number) to Gregorian date: month/day/year
void intToDate (int jd, int &m, int &d, int &y){
    int x, n, i, j;

    x = jd + 68569;
    n = 4 * x / 146097;
    x -= (146097 * n + 3) / 4;
    i = (4000 * (x + 1)) / 1461001;
    x -= 1461 * i / 4 - 31;
    j = 80 * x / 2447;
    d = x - 2447 * j / 80;
    x = j / 11;
    m = j + 2 - 12 * x;
    y = 100 * (n - 49) + i + x;
}

// converts integer (Julian day number) to day of week
string intToDay (int jd){
    return dayOfWeek[jd % 7];
}

int main (int argc, char **argv){
    int jd = dateToInt (3, 24, 2004);
    int m, d, y;
    intToDate (jd, m, d, y);
    string day = intToDay (jd);

    // expected output:
    // 2453089
    // 3/24/2004
    // Wed
    cout << jd << endl
        << m << "/" << d << " " << y << endl
        << day << endl;
}
```

## 8.5 Prime numbers

```
// O(sqrt(x)) Exhaustive Primality Test
#include <cmath>
#define EPS 1e-7
typedef long long LL;
bool isPrimeSlow (LL x)
{
    if(x<=1) return false;
    if(x<=3) return true;
    if (!(x%2) || !(x%3)) return false;
    LL s=(LL)(sqrt((double)(x))+EPS);
    for(LL i=5;i<=s;i+=6)
    {
        if (!(x%i) || !(x%(i+2))) return false;
    }
    return true;
}

// Primes less than 1000:
// 2 3 5 7 11 13 17 19 23 29 31 37
// 41 43 47 53 59 61 67 71 73 79 83 89
// 97 101 103 107 109 113 127 131 137 139 149 151
// 157 163 167 173 179 181 191 193 197 199 211 223
// 227 229 233 239 241 251 257 263 269 271 277 281
// 283 293 307 311 313 317 331 337 347 349 353 359
// 367 373 379 383 389 397 401 409 419 421 431 433
// 439 443 449 457 461 463 467 479 487 491 499 503
// 509 521 523 541 547 557 563 569 571 577 587 593
// 599 601 607 613 617 619 631 641 643 647 653 659
// 661 673 677 683 691 701 709 719 727 733 739 743
// 751 757 761 769 773 787 797 809 811 821 823 827
// 829 839 853 857 859 863 877 881 883 887 907 911
// 919 929 937 941 947 953 967 971 977 983 991 997

// Other primes:
```



```
// The largest prime smaller than 10 is 7.
// The largest prime smaller than 100 is 97.
// The largest prime smaller than 1000 is 997.
// The largest prime smaller than 10000 is 9973.
// The largest prime smaller than 100000 is 99991.
// The largest prime smaller than 1000000 is 999983.
// The largest prime smaller than 10000000 is 9999991.
// The largest prime smaller than 100000000 is 99999989.
// The largest prime smaller than 1000000000 is 999999937.
// The largest prime smaller than 10000000000 is 999999967.
// The largest prime smaller than 100000000000 is 999999977.
// The largest prime smaller than 1000000000000 is 9999999989.
// The largest prime smaller than 10000000000000 is 99999999971.
// The largest prime smaller than 100000000000000 is 999999999973.
// The largest prime smaller than 1000000000000000 is 9999999999989.
// The largest prime smaller than 10000000000000000 is 99999999999937.
// The largest prime smaller than 100000000000000000 is 99999999999997.
// The largest prime smaller than 1000000000000000000 is 999999999999989.
```

## 8.6 Theorems

Euler path/tour theorems: An Euler path is a path that visits every edges exactly once. An Euler tour is an Euler path that starts and ends at the same vertex. A graph is an Eulerian-tour graph (i.e. it has an Euler tour) iff all of its vertices has even degrees. A graph is an Eulerian-path graph (i.e. it has an Euler

path) iff all but 2 of its vertices has even degrees.

Euler's handshaking lemma: A graph does not have an Euler tour iff it has an even number of vertices of odd degrees.

Bipartite graph related theorems:

- (1) Min vertex cover (MVC) = Max cardinality bipartite matching (MCBM).
- (2) Max independent set (MIS) =  $V - \text{MCBM}$ .
- (3) The number of spanning tree of a complete bipartite graph  $K(n,m)$  is  $m^{n-1} * n^{m-1}$ .

Cayley's formula: There are  $n^{n-2}$  spanning trees of a complete graph with  $n$  labeled vertices.

Derangement: A permutation of the elements of a set such that none of the elements appear in their original position. The number of derangements ' $der(n)$ ' can be computed as follow:  $der(n) = (n-1) * (der(n-1) + der(n-2))$  where  $der(0) = 1$  and  $der(1) = 0$ .

Erdoes Gallai's theorem: A necessary and sufficient condition for a finite sequence of natural numbers is the degree sequence of a simple graph. A sequence of non-negative integers  $d_1 \geq d_2 \geq \dots \geq d_n$  can be the degree sequence of a simple graph on  $n$  vertices iff

- (1)  $\sum_{i: 1 \rightarrow n} \{d_i\}$  is even, and
- (2)  $\sum_{i: 1 \rightarrow k} \{d_i\} \leq k * (k-1) + \sum_{i: k+1 \rightarrow n} \{\min(d_i, k)\}$  holds for  $1 \leq k \leq n$ .