Command: ED-SECU-PID

Message category: Security Administration

Application: Add/Drop, Rings

Definition:

Edit security on private identifier.

Restrictions:

All parameters in this command are position-defined.

Function:

To edit the user's own password/private identifier.

Command Format:

ED-SECU-PID:[tid]:uid:[ctag]::opid,npid;

Command Parameters	
PARAMETER	EXPLANATION
[tid]	Identification of the target NE (120
	characters). The NE SID code is the
	recommended value. The default value is null.
uid	User identification code (110 characters) of
	the user whose password is to be changed.
	The value can be preceded by UID=, but this is
	not required. Input is case-sensitive.
[ctag]	Correlation tag (16 characters) that links an
	input command with associated output
	responses. The default is 0.
opid	Old password (610 characters). Input is
	case-sensitive. If the non-alphanumeric
	character of the password is interpreted by the
	parser as a symbolic operator, the password
	must be enclosed in double quotes. See Table
	B (Syntactical Operators) in Appendix B (TL1
	Language).
npid	New password (610 characters). The new
	password must be different from the old one
	and must include at least one digit, one letter,
	and one non-alphanumeric character. Input is
	case-sensitive. If the non-alphanumeric

character of the password is interpreted by the
parser as a symbolic operator, the password
must be enclosed in double quotes. See Table
B (Syntactical Operators) in Appendix B (TL1
Language).

Response Format:

Acknowledgment:

If, in less than 2 seconds, a normal or error response cannot be sent, the following acknowledgment response is sent:

```
IP <ctag>
```

After the above response, a new command input may be generated.

Normal Response:

```
sid yy-mm-dd hh:mm:ss
M c COMPLD
   /* ED-SECU-PID:[tid]:uid:[ctag]::opid,npid */;
```

Error Response:

```
sid yy-mm-dd hh:mm:ss

M c DENY
   /* ED-SECU-PID:[tid]:uid:[ctag]::opid,npid */
   errcde
;
```

Response Parameters	
PARAMETER	EXPLANATION
sid	Source NE identification
yy-mm-dd	Year (2 digits), month, and day
hh:mm:ss	Hour (0023), minute, and second
M	Message generated in response to an input
	command
С	If provided, ctag, otherwise 0
COMPLD	Completed
DENY	Input command is denied
/* */	Enclosed are human readable comments -
	unspecified format
errcde	Error code (See Appendix <u>C</u>)

Example:

Change the password of user NORM from DRAAL#1 to ZATHRAS &1.

ED-SECU-PID:RAL:NORM:606::DRAAL#1,ZATHRAS &1;

```
RAL 99-11-31 15:12:30
M 606 COMPLD
/* ED-SECU-PID:RAL:NORM:606::DRAAL#1,ZATHRAS&1 */
.
```

Related Commands:

ED-SECU-USER ENT-SECU-USER RTRV-SECU-UPC RTRV-SECU-USER