

Command: DISC-TACC

Message category: Network Maintenance
Application: Add/Drop, Rings

Definition:

Disconnect test access for DS1.

Restrictions:

All parameters in this command are position-defined. The value of the *tap* parameter must match the active *tap* value of the previous [CONN-TACC-T1](#) command.

Function:

To disconnect test access for DS1 and restore the circuit under test to its through state. Previously provisioned cross-connections are automatically restored.

Command Format:

DISC-TACC:[tid]:tap:[ctag]::

Command Parameters	
PARAMETER	EXPLANATION
[tid]	Identification of the target NE (1...20 characters). The NE SID code is the recommended value. The default value is null.
tap	The TSC-assigned or NE-defined test access path number. The valid value range is 1...999.
[ctag]	Correlation tag (1...6 characters) that links an input command with associated output responses. The default is 0.

Response Format:

Acknowledgment:

If, in less than 2 seconds, a normal or error response cannot be sent, the following acknowledgment response is sent:

IP <ctag>

After the above response, a new command input may be generated.

Normal Response:

```
      sid yy-mm-dd hh:mm:ss
M    c COMPLD
      /* DISC-TACC:[tid]:tap:[ctag]: */
;
```

Error Response:

```
      sid yy-mm-dd hh:mm:ss
M    c DENY
      /* DISC-TACC:[tid]:tap:[ctag]: */
      errcde
;
```

Response Parameters	
PARAMETER	EXPLANATION
sid	Source NE identification
yy-mm-dd	Year (2 digits), month, and day
hh:mm:ss	Hour (00...23), minute, and second
M	Message generated in response to an input command
c	If provided, ctag, otherwise 0
COMPLD	Completed
DENY	Input command is denied
/* */	Enclosed are human readable comments - unspecified format
errcde	Error code (See Appendix C)

Example:

Disconnect test access for test access number 4.

DISC-TACC:RALGH:4:95;

```
      RALGH 99-11-25 15:58:30
M    95 COMPLD
      /* DISC-TACC:RALGH:4:95: */
;
```

Related Commands:

RTRV-ALM-T1	RTRV-COND-T1
RTRV-ATTR-T1	SET-ATTR-T1

