

Command: DLT-PORT

Message category: Memory Administration
Application: Add/Drop, Rings

Definition:

Delete port.

Restrictions:

All parameters in this command are position-defined.

Function:

To delete a port (primary state must be OOS-MA to be deleted).

Command Format:

DLT-PORT:[tid]:aidport:[ctag][:::];

Command Parameters	
PARAMETER	EXPLANATION
[tid]	Identification of the target NE (1...20 characters). The NE's SID code is the recommended value. The default value is null.
aidport	The access identification code which is used to identify a port. The parameter may be preceded by "AID= ", although it is not required. Grouping is allowed. The values are: CRAFT2 2nd craft port SE2A Serial E2A port X25PORT X.25 port ALL All of the above
[ctag]	Correlation tag (1...6 characters) that links an input command with associated output responses. The default is 0.

Response Format:

Acknowledgment:

If, in less than 2 seconds, a normal or error response cannot be sent, the following acknowledgment response will be sent:

IP <ctag>

After the above response, a new command input may be generated.

Normal Response:

```
sid yy-mm-dd hh:mm:ss
M c COMPLD
/* DLT-PORT:[tid]:aidport:[ctag][:::] */
;
```

Error Response:

```
sid yy-mm-dd hh:mm:ss
M c DENY
/* DLT-PORT:[tid]:aidport:[ctag][:::] */
errcde
;
```

Response Parameters	
PARAMETER	EXPLANATION
sid	Source NE identification
yy-mm-dd	Year (2 digits), month, and day
hh:mm:ss	Hour (00...23), minute, and second
M	Message generated in response to an input command
c	If provided, ctag, otherwise 0
COMPLD	Completed
DENY	Input command is denied
/* */	Enclosed are human readable comments - unspecified format
errcde	Error code (See Appendix C)

Example:

Delete the serial E2A port.

DLT-PORT:RALGH:SE2A:365;

```
RALGH 99-11-27 09:12:3
M 365 COMPLD
/* DLT-PORT:RALGH:SE2A:365 */
;
```

Related Commands:

[ED-PORT](#)
[ENT-PORT](#)
[RTRV-PORT](#)

