



ISO 9001:2008

K16Pro - 4 Chanel

HIGH PERFORMANCE POWER AMPLIFIER



HIGH POWER
Stable output, powerful performance



HIGH EFFICIENCY
Class D technology for maximum efficiency



RELIABLE
Professional grade durability & protection



THÔNG SỐ KỸ THUẬT

Power Supply:	AC in 140v-220v / 50Hz-60Hz
8Ω Stereo RMs:	High 1250W x 4 / Low 1050W x 4
4Ω Stereo RMs:	High 2000W x 4 / Low 1850W x 4
8Ω Bridge Mono:	High 4000W / Low 3700W
Peak Voltage:	141V
Peak VPL:	141V/130V
Frequency Response:	20Hz-22KHz
Input Impedance:	20K2 balanced / 10K2 unbalanced
Class:	D
Damping Factor:	>450 @8Ω, 20Hz-200Hz
Input Connectors:	Female XLR & Male XLR
Output Connectors:	6 Speakons
Input Sensitivity:	0.777 / 1.0V
LED Indicators:	Active Bridge, D.T, High Power, Front-to-back / 5 DC fans
Dimensions:	483 x 98 x 350 mm
Net Weight:	9,6 kg
Gross Weight:	10,8 kg
BẢO HÀNH	3 năm
BẢO TRÌ	3 năm
GIÁ NIỀM YẾT	18.000.000 VNĐ