

K16S - 2 Chanel

HIGH PERFORMANCE POWER AMPLIFIER



HIGH POWER
Stable output, powerful performance



HIGH EFFICIENCY
Class D technology for maximum efficiency



RELIABLE
Professional grade durability & protection



THÔNG SỐ KỸ THUẬT

Power Supply:	AC in 140v-220v / 50Hz-60Hz
8Ω Stereo RMs:	High 1600W x 2 / Low 1300W x 2
4Ω Stereo RMs:	High 2800W x 2 / Low 2250W x 2
8Ω Bridge Mono:	High 5600W / Low 4400W
Peak Voltage:	162V
Peak VPL:	162V/145V
Frequency Response:	20Hz-22KHz
Input Impedance:	20KΩ balanced / 10KΩ unbalanced
Class:	D
Input Connectors:	Female XLR & Male XLR
Output Connectors:	6 Speakons
Input Sensitivity:	0.777 / 1.0V
LED Indicators:	Active Bridge, D.T, High Power, Front-to-back / 5 DC fans
Dimensions:	483 x 98 x 350 mm
Net Weight:	8,5 kg
Gross Weight:	9,5 kg

BẢO HÀNH

3 năm

BẢO TRÌ

3 năm

GIÁ NIÊM YẾT

16.000.000 VNĐ