



ISO 9001:2008

K19Pro - 4 Chanel

HIGH PERFORMANCE POWER AMPLIFIER



HIGH POWER
Stable output, powerful performance



HIGH EFFICIENCY
Class D technology for maximum efficiency



RELIABLE
Professional grade durability & protection



THÔNG SỐ KỸ THUẬT

Power Supply:	AC in 140v-220v / 50Hz-60Hz
8Ω Stereo RMs:	High 1650W x 4 / Low 1400W x 4
4Ω Stereo RMs:	High 2450W x 4 / Low 2100W x 4
8Ω Bridge Mono:	High 4900W x 2/ Low 4200W x 2
Peak Voltage:	163V
Peak VPL:	163V/153V
Frequency Response:	20Hz-22KHz
Input Impedance:	20K2 balanced / 10K2 unbalanced
Class:	D
Damping Factor:	>500 @8Ω, 20Hz-200Hz
Input Connectors:	Female XLR & Male XLR
Output Connectors:	6 Speakons
Input Sensitivity:	0.777 / 1.0V
LED Indicators:	Active Bridge, D.T, High Power, Front-to-back / 5 DC fans
Dimensions:	483 x 98 x 350 mm
Net Weight:	10 kg
Gross Weight:	11,2 kg

BẢO HÀNH
BẢO TRÌ
GIÁ NIỀM YẾT

3 năm
3 năm
26.000.000 VNĐ