



ISO 9001:2008

K20S - 2 Chanel

HIGH PERFORMANCE POWER AMPLIFIER



HIGH POWER
Stable output, powerful performance



HIGH EFFICIENCY
Class D technology for maximum efficiency



RELIABLE
Professional grade durability & protection



ON Semiconductor®



THÔNG SỐ KỸ THUẬT

Power Supply:	AC in 140v-220v / 50Hz-60Hz
8Ω Stereo RMs:	High 3000W x 2 / Low 2250W x 2
4Ω Stereo RMs:	High 4800W x 2 / Low 4100W x 2
8Ω Bridge Mono:	High 9600W / Low 8200W
Peak Voltage:	219V
Peak VPL:	219V/190V
Frequency Response:	20Hz-22KHz
Input Impedance:	20K2 balanced 10K2 unbalanced
Class:	D
Damping Factor:	>2000 80, 20Hz-200Hz
Input Connectors:	Female XLR & Male XLR
Output Connectors:	3 Speakons
Input Sensitivity:	0.777 / 1.0V
LED Indicators:	Active Bridge, D.T, High Power, Front-to-back / 5 DC fans
Dimensions:	483 x 98 x 350 mm
Net Weight:	9,5 kg
Gross Weight:	10,8 kg

BẢO HÀNH	3 năm
BẢO TRÌ	3 năm
GIÁ NIỀM YẾT	24.000.000 VNĐ