

Make an Open Source Drone, ESC Calibration Process

In order to calibrate the ESCs on your drone, please follow the process outlined in this document:

1. Place your drone and your radio transmitter ready in front of you. The battery should be attached but not connected to your drone, and the propellers should be removed. The transmitter should be turned off.
2. Turn ON your transmitter and push your throttle stick all the way UP.
3. Power ON the quadcopter, by connecting the battery cables.
4. Wait until you hear some audible signal from ESCs.
5. Turn drone OFF by disconnecting the battery cables.
6. Wait for 10 seconds and then turn your drone ON. It is now on ESC Calibration mode.
7. Wait for some audible signal from ESCs.
8. Push your throttle stick DOWN.
9. You will hear some more audible signal from ESCs, wait for 2-3 seconds.
10. Repeat the same process of pushing throttle stick UP wait for audible signal and again pushing throttle DOWN for several times, usually 7-8 times are enough.
11. Just remember that you have to let it do its job every time you push throttle stick UP or DOWN. It will do its job while you hear the audible signal from ESCs, so do not rush and wait for a few seconds each time.
12. It will be ready when the music stops playing and while trying to push the throttle stick UP, you will see the motors spinning fast.
13. Check that every motor spins to the correct direction, as per steps 14 to 17.
14. TOP LEFT -> CLOCKWISE
15. TOP RIGHT -> COUNTER-CLOCKWISE
16. BOTTOM LEFT -> COUNTER-CLOCKWISE
17. BOTTOM RIGHT -> CLOCKWISE
18. You may touch it lightly to determine spinning direction.
19. If one motor is not spinning in the right direction just change two out of the three cables connecting the motor with the ESC.
20. When you see them spinning correctly just unplug the battery and close the radio transmitter, you are ready to attach the propellers and fly.

