

Infection Controls, Inc. Catalog and Price List - Bid Response 18-7289 HVAC Equipment, Parts, Services and Related

Product ID	Description	UOM	MSRP	Discount Given	Discounted Price
BP2400-110-200	The Bi-Polar® 2400 model uses cold plasma technology that splits water vapor into positive and negative ions that are discharged into the air. These ions attach themselves to allergens such as smoke, dust, pollen, dander, and much more. The particles continue to bond to each other until they are heavy enough to drop out of the air and collect in filters. The positive and negative ions attack odors and other contaminants and convert them into oxygen, water vapor, and carbon dioxide, neutralizing odors and greatly improving your Indoor Air Quality (IAQ). The Bi-Polar® 2400 ionizer air purifier prevents allergens from reproducing by removing hydrogen and disrupting the DNA of the pathogen. For residential and commercial ducted HVAC systems rated up to 3 tons, our Air Oasis nano 9" LO Induct is the ideal in-duct UV air purifier. It can be easily mounted in a standard HVAC (heating, ventilation, and air conditioning) system and can improve the indoor air quality (IAQ) of the whole building. The nano 6" Induct is the best in duct air purifier because it effectively purifies the air wherever the HVAC system reaches. For this reason, many prefer it to countertop air purifier models that can only purify the air in one room.	each	\$ 540.00	5%	\$ 513.00
NINDLO	The nano 9" LO Induct can be installed in less than 15 minutes and requires minimal maintenance. It is capable of connecting to a 110VAC or 240VAC electrical outlet, or it can be hardwired to a 24VAC power supply. Once installed, our HVAC air purifier will immediately set to work reducing carbon-based contaminants in the air like mold, bacteria, viruses, and volatile organic compounds (VOCs) that can cause unpleasant odors. It will continuously clean the air in the building until a replacement AHPCO cell is needed, at which time a blue LED light will advise the owner to make the change. Cells only need to be replaced about once every two years, making the nano 9" Induct the best whole-house air cleaner for those who do not wish to spend a lot of time on upkeep. For residential and commercial ducted HVAC systems rated between 4 and 6 tons, our Air Oasis nano 9" Induct is the ideal in-duct UV air purifier. It can be easily mounted in a standard HVAC (heating, ventilation, and air conditioning) system and can improve the indoor air quality (IAQ) of the whole building. The nano 9" Induct is the best in duct air purifier because it effectively purifies the air wherever the HVAC system reaches. For this reason, many prefer it to countertop air purifier models that can only purify the air in one room.	each	\$ 750.00	5%	\$ 712.50
9 Inch Nano Induct PCO	The nano 9" Induct can be installed in less than 15 minutes and requires minimal maintenance. It is capable of connecting to a 110VAC or 240VAC electrical outlet, or it can be hardwired to a 24VAC power supply. Once installed, our HVAC air purifier will immediately set to work reducing carbon-based contaminants in the air like mold, bacteria, viruses, and volatile organic compounds (VOCs) that can cause unpleasant odors. It will continuously clean the air in the building until a replacement AHPCO cell is needed, at which time a blue LED light will advise the owner to make the change. Cells only need to be replaced about once every two years, making the nano 9" Induct the best whole-house air cleaner for those who do not wish to spend a lot of time on upkeep. For commercial ducted HVAC systems rated at 7+ tons, our Air Oasis nano 9" Hi Induct is the ideal in-duct UV air purifier. It can be easily mounted in a standard HVAC (heating, ventilation, and air conditioning) system and can improve the indoor air quality (IAQ) of the whole building. The nano 14" Induct is the best in duct air purifier because it effectively purifies the air wherever the HVAC system reaches. For this reason, many prefer it to countertop air purifier models that can only purify the air in one room.	each	\$ 750.00	5%	\$ 712.50
14 Inch Nano Induct PCO	The nano 9" HI Induct can be installed in less than 15 minutes and requires minimal maintenance. It is capable of connecting to a 110VAC or 240VAC electrical outlet, or it can be hardwired to a 24VAC power supply. Once installed, our HVAC air purifier will immediately set to work reducing carbon-based contaminants in the air like mold, bacteria, viruses, and volatile organic compounds (VOCs) that can cause unpleasant odors. It will continuously clean the air in the building until a replacement AHPCO cell is needed, at which time a blue LED light will advise the owner to make the change. Cells only need to be replaced about once every two years, making the nano 9" Induct the best whole-house air cleaner for those who do not wish to spend a lot of time on upkeep.	each	\$ 750.00	5%	\$ 712.50
NINDAHPCO-9LO	Replacement cell for 9" LO Nano Induct PCO - replace every 2 years	each	\$ 299.00	5%	\$ 284.05
NINDAHPCO-9	Replacement cell for 9" Nano Induct PCO - replace every 2 years	each	\$ 299.00	5%	\$ 284.05

Infection Controls, Inc. Catalog and Price List - Bid Response 18-7289 HVAC Equipment, Parts, Services and Related

Product ID	Description	UOM	MSRP	Discount Given	Discounted Price
NINDAHPCO-9HI	Replacement cell for 9" HI Nano Induct PCO - replace every 2 years.	each	\$ 299.00	5%	\$ 284.05
GermBlast Service	GermBlast is a high level disinfection program designed to reduce disease causing microorganisms in the environment. This multi-step process addresses all major touch points utilizing safe yet effective disinfectants. The process includes environmental data collected prior to each service so that facilities can discover trends in their environment, making evidence based decisions that help stop potential outbreaks. Note: GermBlast service is quoted on a per facility basis. Because each facility is different GermBlast provides a not-to-exceed pricing model. This means that the price will never exceed the stated price, but can be adjusted lower if a facility has fewer touch points than the average facility.		Not to exceed \$0.10 per square foot of entire facility treated		Not to exceed \$0.095 per square foot of entire facility treated